

prepare_continent_trait_data.R

April 21, 2026

Contents

prepare_continent_trait_data	1
Index	3

prepare_continent_trait_data
<i>Prepare Trait Data for One Continental Unit</i>

Description

Filters and subsets the wide trait table to taxa present in a single continental unit. Removes taxa where all trait values are 'NA'.

Usage

```
prepare_continent_trait_data(  
  continent_id,  
  data_trait_table,  
  data_traits_classified_corrected  
)
```

Arguments

- | | |
|----------------------------------|--|
| continent_id | A single non-empty character string identifying the continental unit (e.g. "eu-rope", "america", "asia"). Must match a value in the 'scale_id' column of 'data_traits_classified_corrected'. |
| data_trait_table | A wide tibble (rows = taxa, columns = 'taxon_name' + trait domain columns) as produced by 'make_trait_table()'. Must contain a 'taxon_name' column. |
| data_traits_classified_corrected | A tibble with at least columns 'scale_id' (character) and 'taxon_resolved' (character), used to identify which taxa belong to 'continent_id'. |

Details

****Steps****:

1. Filter 'data_traits_classified_corrected' to rows where 'scale_id == continent_id' and collect 'distinct(taxon_resolved)'.
2. Use 'dplyr::semi_join()' to subset 'data_trait_table' to those taxa ('taxon_name == taxon_resolved').
3. Remove rows where all trait columns (i.e. all columns except 'taxon_name') are 'NA'.

Value

A tibble with the same column structure as 'data_trait_table' (i.e. 'taxon_name' + trait domain columns) but restricted to taxa present in 'continent_id' and with at least one non-'NA' trait value.

See Also

[save_ft_classification_for_continent()], [cluster_functional_types()]

Index

`prepare_continent_trait_data`, [1](#)