

# Gungnir's Standard Code Library

*Shanghai Jiao Tong University*

Dated: July 25, 2016

## Contents

1	Computational Geometry	1
1.1	2D	1
1.1.1	Basis	1
2	Graph Theory	1
2.1	Basis	1
2.2	Double Connected Graph (vertex)	1

## Chapter 1 Computational Geometry

### 1.1 2D

#### 1.1.1 Basis

```
1 typedef double DB;
2 const DB eps = 1e-8;
3
4 inline int sign(DB x) {
5     return x < -eps ? -1 : ( x > eps ? 1 : 0 );
6 }
7 inline DB msqrt(DB x) {
8     return sign(x) > 0 ? sqrt(x) : 0;
9 }
10
11 struct Point {
12     DB x, y;
13     inline Point(): x(0), y(0) {}
14     inline Point(DB x, DB y): x(x), y(y) {}
15     inline Point operator+(const Point &rhs) const {
16         return Point(x + rhs.x, y + rhs.y);
17     }
18     inline Point operator-(const Point &rhs) const {
19         return Point(x - rhs.x, y - rhs.y);
20     }
21     inline Point operator*(DB k) const {
22         return Point(x * k, y * k);
23     }
24     inline Point operator/(DB k) const {
25         assert(sign(k));
26         return Point(x / k, y / k);
27     }
28 };
29
30 inline DB dot(const P& a, const P& b) {
31     return a.x * b.x + a.y * b.y;
32 }
33
34 inline DB det(const P& a, const P& b) {
35     return a.x * b.y - a.y * b.x;
36 }
```

## Chapter 2 Graph Theory

### 2.1 Basis

```
1 struct Graph { // Remember to call .init()!
2     int e, nxt[M], v[M], adj[N], n;
3     bool base;
4     inline void init(bool _base, int _n = 0) {
5         assert(n < N);
6         n = _n; base = _base;
7         e = 0; memset(adj + base, -1, sizeof(*adj) * n);
8     }
9     inline int new_node() {
10         adj[n + base] = -1;
11         assert(n + base + 1 < N);
12         return n++ + base;
13     }
14     inline void ins(int u0, int v0) { // directional
15         assert(u0 < n + base && v0 < n + base);
16         v[e] = v0; nxt[e] = adj[u0]; adj[u0] = e++;
17         assert(e < M);
18     }
19     inline void bi_ins(int u0, int v0) { // bi-directional
20         ins(u0, v0); ins(v0, u0);
21     }
22 };
```

### 2.2 Double Connected Graph (vertex)

dcc.forest is a set of connected tree whose vertices are chequered with cut-vertex and DCC.

```
1 const bool DCC_VERTEX = 0, DCC_EDGE = 1;
2 struct DCC { // N = N0 + M0. Remember to call init(&raw_graph).
3     Graph *g, forest; // g is raw graph ptr.
4     int dfn[N], DFN, low[N];
5     int stack[N], top;
6     int expand_to[N]; // Where edge i is expanded to in expaned graph.
7     // Vertex i expanded to i.
8     int compress_to[N]; // Where vertex i is compressed to.
9     bool vertex_Type[N], cut[N], compress_cut[N], branch[M];
10    //std::vector<int> DCC_component[N]; // Cut vertex belongs to none.
11    inline void init(Graph *raw_graph) {
12        g = raw_graph;
13    }
14    void DFS(int u, int pe) {
15        dfn[u] = low[u] = ++DFN; cut[u] = false;
16        if (!g->adj[u]) {
17            cut[u] = 1;
18            compress_to[u] = forest.new_node();
19            compress_cut[compress_to[u]] = 1;
20        }
21        for (int e = g->adj[u]; ~e; e = g->nxt[e]) {
22            int v = g->v[e];
23            if ((e ^ pe) > 1 && dfn[v] > 0 && dfn[v] < dfn[u]) {
24                stack[top++] = e;
25                low[u] = std::min(low[u], dfn[v]);
26            }
27            else if (!dfn[v]) {
28                stack[top++] = e; branch[e] = 1;
29                DFS(v, e);
30                low[u] = std::min(low[u], low[v]);
31                if (low[v] >= dfn[u]) {
32                    if (!cut[u]) {
33                        cut[u] = 1;
34                        compress_to[u] = forest.new_node();
35                        compress_cut[compress_to[u]] = 1;
36                    }
37                    int cc = forest.new_node();
38                    forest.bi_ins(compress_to[u], cc);
39                    compress_cut[cc] = 0;
40                    //DCC_component[cc].clear();
41                    do {
42                        int cur_e = stack[--top];
43                        compress_to[expand_to[cur_e]] = cc;
44                        if (branch[cur_e]) {
45                            int v = g->v[cur_e];
46                            if (cut[v])
47                                forest.bi_ins(cc, compress_to[v]);
48                            else {
49                                //DCC_component[cc].push_back(v);
50                                compress_to[v] = cc;
51                            }
52                        }
53                    } while (stack[top] != e);
54                }
55            }
56        }
57    }
58    void solve() {
59        forest.init(g->base);
60        int n = g->n;
61        for (int i = 0; i < g->e; i++) {
62            expand_to[i] = g->new_node();
63            branch[i] = 0;
64        }
65        memset(dfn + g->base, 0, sizeof(*dfn) * n); DFN = 0;
66        for (int i = 0; i < n; i++)
67            if (!dfn[i + g->base]) {
68                top = 0;
69                DFS(i + g->base, -1);
70            }
71    }
72 } dcc;
73
74 dcc.init(&raw_graph);
75 dcc.solve();
76 // Do something with dcc.forest ...
```