

Gungnir's Standard Code Library

Shanghai Jiao Tong University

Dated: October 10, 2016

Contents

1	计算几何	2
1.1	二维	2
1.1.1	基础	2
1.1.2	凸包	3
1.2	三维	3
1.2.1	基础	3
2	数论	3
2.1	$O(m^2 \log n)$ 求线性递推数列第 n 项	3
2.2	求逆元	4
2.3	中国剩余定理	4
3	代数	4
3.1	快速傅里叶变换	4
4	字符串	4
4.1	后缀数组	4
4.2	后缀自动机	5
4.3	回文自动机	5
5	图论	5
5.1	基础	5
5.2	KM	5
5.3	点双连通分量	6
5.4	边双连通分量	6
6	技巧	7
6.1	真正的释放 STL 容器内存空间	7
6.2	无敌的大整数相乘取模	7
6.3	无敌的读入优化	7
6.4	控制 cout 输出实数精度	7
7	提示	7
7.1	线性规划转对偶	7
7.2	32-bit/64-bit 随机素数	7
7.3	NTT 素数及其原根	7

Chapter 1 计算几何

1.1 二维

1.1.1 基础

```
1 typedef double DB;
2 const DB eps = 1e-8;
3
4 int sign(DB x) {
5     return x < -eps ? -1 : ( x > eps ? 1 : 0 );
6 }
7 DB msqrt(DB x) {
8     return sign(x) > 0 ? sqrt(x) : 0;
9 }
10
11 struct Point {
12     DB x, y;
13     Point(): x(0), y(0) {}
14     Point(DB x, DB y): x(x), y(y) {}
15     Point operator+(const Point &rhs) const {
16         return Point(x + rhs.x, y + rhs.y);
17     }
18     Point operator-(const Point &rhs) const {
19         return Point(x - rhs.x, y - rhs.y);
20     }
21     Point operator*(DB k) const {
22         return Point(x * k, y * k);
23     }
24     Point operator/(DB k) const {
25         assert(sign(k));
26         return Point(x / k, y / k);
27     }
28     Point rotate(DB ang) const { // 逆时针旋转 ang 弧度
29         return Point(cos(ang) * x - sin(ang) * y,
30             cos(ang) * y + sin(ang) * x);
31     }
32     Point turn90() const { // 逆时针旋转 90 度
33         return Point(-y, x);
34     }
35     Point unit() const {
36         return *this / len();
37     }
38 };
39 DB dot(const Point& a, const Point& b) {
40     return a.x * b.x + a.y * b.y;
41 }
42 DB det(const Point& a, const Point& b) {
43     return a.x * b.y - a.y * b.x;
44 }
45 #define cross(p1,p2,p3) ((p2.x-p1.x)*(p3.y-p1.y)-(p3.x-p1.x)*(p2.y-p1.y))
46 #define crossOp(p1,p2,p3) sign(cross(p1,p2,p3))
47 bool isLL(const Line& l1, const Line& l2, Point& p) { // 直线与直线交点
48     DB s1 = det(l2.b - l2.a, l1.a - l2.a);
49     s2 = -det(l2.b - l2.a, l1.b - l2.a);
50     if (!sign(s1 + s2)) return false;
51     p = (l1.a * s2 + l1.b * s1) / (s1 + s2);
52     return true;
53 }
54 bool onSeg(const Line& l, const Point& p) { // 点在线段上
55     return sign(det(p - l.a, l.b - l.a)) == 0 && sign(dot(p - l.a, p - l.b)) <= 0;
56 }
57 Point projection(const Line & l, const Point& p) {
58     return l.a + (l.b - l.a) * (dot(p - l.a, l.b - l.a) / (l.b - l.a).len2());
59 }
60 DB disToLine(const Line& l, const Point& p) { // 点到 * 直线 * 距离
61     return fabs(det(p - l.a, l.b - l.a) / (l.b - l.a).len());
62 }
63 DB disToSeg(const Line& l, const Point& p) { // 点到线段距离
64     return sign(dot(p - l.a, l.b - l.a)) * sign(dot(p - l.b, l.a - l.b)) == 1 ?
        disToLine(l, p) : std::min((p - l.a).len(), (p - l.b).len());
```

```
65 }
66 // 圆与直线交点
67 bool isCL(Circle a, Line l, Point& p1, Point& p2) {
68     DB x = dot(l.a - a.o, l.b - l.a);
69     y = (l.b - l.a).len2(),
70     d = x * x - y * ((l.a - a.o).len2() - a.r * a.r);
71     if (sign(d) < 0) return false;
72     Point p = l.a - ((l.b - l.a) * (x / y)), delta = (l.b - l.a) * (msqrt(d) / y);
73     p1 = p + delta; p2 = p - delta;
74     return true;
75 }
76 // 圆与圆的交面积
77 DB areaCC(const Circle& c1, const Circle& c2) {
78     DB d = (c1.o - c2.o).len();
79     if (sign(d - (c1.r + c2.r)) >= 0) return 0;
80     if (sign(d - std::abs(c1.r - c2.r)) <= 0) {
81         DB r = std::min(c1.r, c2.r);
82         return r * r * PI;
83     }
84     DB x = (d * d + c1.r * c1.r - c2.r * c2.r) / (2 * d);
85     t1 = acos(x / c1.r), t2 = acos((d - x) / c2.r);
86     return c1.r * c1.r * t1 + c2.r * c2.r * t2 - d * c1.r * sin(t1);
87 }
88 // 圆与圆交点
89 bool isCC(Circle a, Circle b, P& p1, P& p2) {
90     DB s1 = (a.o - b.o).len();
91     if (sign(s1 - a.r - b.r) > 0 || sign(s1 - std::abs(a.r - b.r)) < 0) return false;
92     DB s2 = (a.r * a.r - b.r * b.r) / s1;
93     DB aa = (s1 + s2) * 0.5, bb = (s1 - s2) * 0.5;
94     P o = (b.o - a.o) * (aa / (aa + bb)) + a.o;
95     P delta = (b.o - a.o).unit().turn90() * msqrt(a.r * a.r - aa * aa);
96     p1 = o + delta, p2 = o - delta;
97     return true;
98 }
99 // 求点到圆的切点, 按关于点的顺时针方向返回两个点
100 bool tanCP(const Circle &c, const Point &p0, Point &p1, Point &p2) {
101     double x = (p0 - c.o).len2(), d = x - c.r * c.r;
102     if (d < eps) return false; // 点在圆上认为没有切点
103     Point p = (p0 - c.o) * (c.r * c.r / x);
104     Point delta = ((p0 - c.o) * (-c.r * sqrt(d) / x)).turn90();
105     p1 = c.o + p + delta;
106     p2 = c.o + p - delta;
107     return true;
108 }
109 // 求圆到圆的内共切线, 按关于 c1.o 的顺时针方向返回两条线
110 std::vector<Line> intanCC(const Circle &c1, const Circle &c2) {
111     std::vector<Line> ret;
112     Point p = (c1.o * c2.r + c2.o * c1.r) / (c1.r + c2.r);
113     Point p1, p2, q1, q2;
114     if (tanCP(c1, p, p1, p2) && tanCP(c2, p, q1, q2)) { // 两圆相切认为没有切线
115         ret.push_back(Line(p1, q1));
116         ret.push_back(Line(p2, q2));
117     }
118     return ret;
119 }
120 // 点在内多边形内
121 bool inPolygon(const Point& p, const std::vector<Point>& poly) {
122     int n = poly.size();
123     int counter = 0;
124     for (int i = 0; i < n; ++i) {
125         P a = poly[i], b = poly[(i + 1) % n];
126         if (onSeg(Line(a, b), p)) return false; // 边界上不算
127         int x = sign(det(p - a, b - a));
128         int y = sign(a.y - p.y);
129         int z = sign(b.y - p.y);
130         if (x > 0 && y <= 0 && z > 0) ++ counter;
131         if (x < 0 && z <= 0 && y > 0) -- counter;
132     }
133     return counter != 0;
134 }
```

```

135 // 用半平面 (q1,q2) 的逆时针方向去切凸多边形
136 std::vector<Point> convexCut(const std::vector<Point>&ps, Point q1, Point q2) {
137     std::vector<Point> qs; int n = ps.size();
138     for (int i = 0; i < n; ++i) {
139         Point p1 = ps[i], p2 = ps[(i + 1) % n];
140         int d1 = crossOp(q1,q2,p1), d2 = crossOp(q1,q2,p2);
141         if (d1 >= 0) qs.push_back(p1);
142         if (d1 * d2 < 0) qs.push_back(isSS(p1, p2, q1, q2));
143     }
144     return qs;
145 }
146 // 求凸包
147 std::vector<Point> convexHull(std::vector<Point> ps) {
148     int n = ps.size(); if (n <= 1) return ps;
149     std::sort(ps.begin(), ps.end());
150     std::vector<Point> qs;
151     for (int i = 0; i < n; qs.push_back(ps[i++]))
152         while (qs.size() > 1 && sign(det(qs[qs.size() - 2], qs.back(), ps[i])) <= 0)
153             qs.pop_back();
154     for (int i = n - 2, t = qs.size(); i >= 0; qs.push_back(ps[i--]))
155         while ((int)qs.size() > t && sign(det(qs[qs.size() - 2], qs.back(), ps[i])) <=
156             0)
157             qs.pop_back();
158     return qs;

```

1.1.2 凸包

```

1 // 凸包中的点按逆时针方向
2 struct Convex {
3     int n;
4     std::vector<Point> a, upper, lower;
5     void make_shell(const std::vector<Point>& p,
6                     std::vector<Point>& shell) { // p needs to be sorted.
7         clear(shell); int n = p.size();
8         for (int i = 0, j = 0; i < n; i++, j++) {
9             for (; j >= 2 && sign(det(shell[j-1] - shell[j-2],
10                                     p[i] - shell[j-2])) <= 0; --j) shell.pop_back();
11             shell.push_back(p[i]);
12         }
13     }
14     void make_convex() {
15         std::sort(a.begin(), a.end());
16         make_shell(a, lower);
17         std::reverse(a.begin(), a.end());
18         make_shell(a, upper);
19         a = lower; a.pop_back();
20         a.insert(a.end(), upper.begin(), upper.end());
21         if ((int)a.size() >= 2) a.pop_back();
22         n = a.size();
23     }
24     void init(const std::vector<Point>& _a) {
25         clear(a); a = _a; n = a.size();
26         make_convex();
27     }
28     void read(int _n) { // Won't make convex.
29         clear(a); n = _n; a.resize(n);
30         for (int i = 0; i < n; i++)
31             a[i].read();
32     }
33     std::pair<DB, int> get_tangent(
34         const std::vector<Point>& convex, const Point& vec) {
35         int l = 0, r = (int)convex.size() - 2;
36         assert(r >= 0);
37         for (; l + 1 < r; ) {
38             int mid = (l + r) / 2;
39             if (sign(det(convex[mid + 1] - convex[mid], vec)) > 0)
40                 r = mid;
41             else l = mid;
42         }
43         return std::max(std::make_pair(det(vec, convex[r]), r),
44             std::make_pair(det(vec, convex[0]), 0));

```

```

45 }
46 int binary_search(Point u, Point v, int l, int r) {
47     int s1 = sign(det(v - u, a[l % n] - u));
48     for (; l + 1 < r; ) {
49         int mid = (l + r) / 2;
50         int smid = sign(det(v - u, a[mid % n] - u));
51         if (smid == s1) l = mid;
52         else r = mid;
53     }
54     return l % n;
55 }
56 // 求凸包上和向量 vec 叉积最大的点, 返回编号, 共线的多个切点返回任意一个
57 int get_tangent(Point vec) {
58     std::pair<DB, int> ret = get_tangent(upper, vec);
59     ret.second = (ret.second + (int)lower.size() - 1) % n;
60     ret = std::max(ret, get_tangent(lower, vec));
61     return ret.second;
62 }
63 // 求凸包和直线 u, v 的交点, 如果不相交返回 false, 如果有则是和 (i, next(i)) 的
64 // 交点, 交在点上不确定返回前后两条边其中之一
65 bool get_intersection(Point u, Point v, int &i0, int &i1) {
66     int p0 = get_tangent(u - v), p1 = get_tangent(v - u);
67     if (sign(det(v - u, a[p0] - u)) * sign(det(v - u, a[p1] - u)) <= 0) {
68         if (p0 > p1) std::swap(p0, p1);
69         i0 = binary_search(u, v, p0, p1);
70         i1 = binary_search(u, v, p1, p0 + n);
71         return true;
72     }
73     else return false;
74 }

```

1.2 三维

1.2.1 基础

```

1 // 三维绕轴旋转, 大拇指指向 axis 向量方向, 四指弯曲方向转 w 弧度
2 Point rotate(const Point& s, const Point& axis, DB w) {
3     DB x = axis.x, y = axis.y, z = axis.z;
4     DB s1 = x * x + y * y + z * z, ss1 = msqrt(s1),
5         cosw = cos(w), sinw = sin(w);
6     DB a[4][4];
7     memset(a, 0, sizeof a);
8     a[3][3] = 1;
9     a[0][0] = ((y * y + z * z) * cosw + x * x) / s1;
10    a[0][1] = x * y * (1 - cosw) / s1 + z * sinw / ss1;
11    a[0][2] = x * z * (1 - cosw) / s1 - y * sinw / ss1;
12    a[1][0] = x * y * (1 - cosw) / s1 - z * sinw / ss1;
13    a[1][1] = ((x * x + z * z) * cosw + y * y) / s1;
14    a[1][2] = y * z * (1 - cosw) / s1 + x * sinw / ss1;
15    a[2][0] = x * z * (1 - cosw) / s1 + y * sinw / ss1;
16    a[2][1] = y * z * (1 - cosw) / s1 - x * sinw / ss1;
17    a[2][2] = ((x * x + y * y) * cosw + z * z) / s1;
18    DB ans[4] = {0, 0, 0, 0}, c[4] = {s.x, s.y, s.z, 1};
19    for (int i = 0; i < 4; ++i)
20        for (int j = 0; j < 4; ++j)
21            ans[i] += a[j][i] * c[j];
22    return Point(ans[0], ans[1], ans[2]);
23 }

```

Chapter 2 数论

2.1 $O(m^2 \log n)$ 求线性递推数列第 n 项

Given a_0, a_1, \dots, a_{m-1}
 $a_n = c_0 \times a_{n-m} + \dots + c_{m-1} \times a_{n-1}$
 Solve for $a_n = v_0 \times a_0 + v_1 \times a_1 + \dots + v_{m-1} \times a_{m-1}$

```

1 void linear_recurrence(long long n, int m, int a[], int c[], int p) {
2     long long v[M] = {1 % p}, u[M << 1], msk = !n;

```

```

3 for(long long i(n); i > 1; i >= 1) {
4     msk <= 1;
5 }
6 for(long long x(0); msk; msk >= 1, x <= 1) {
7     fill_n(u, m <= 1, 0);
8     int b(!!(n & msk));
9     x |= b;
10    if(x < m) {
11        u[x] = 1 % p;
12    } else {
13        for(int i(0); i < m; i++) {
14            for(int j(0), t(i + b); j < m; j++, t++) {
15                u[t] = (u[t] + v[i] * v[j]) % p;
16            }
17        }
18        for(int i((m <= 1) - 1); i >= m; i--) {
19            for(int j(0), t(i - m); j < m; j++, t++) {
20                u[t] = (u[t] + c[j] * u[i]) % p;
21            }
22        }
23    }
24    copy(u, u + m, v);
25 }
26 //a[n] = v[0] * a[0] + v[1] * a[1] + ... + v[m - 1] * a[m - 1].
27 for(int i(m); i < 2 * m; i++) {
28     a[i] = 0;
29     for(int j(0); j < m; j++) {
30         a[i] = (a[i] + (long long)c[j] * a[i + j - m]) % p;
31     }
32 }
33 for(int j(0); j < m; j++) {
34     b[j] = 0;
35     for(int i(0); i < m; i++) {
36         b[j] = (b[j] + v[i] * a[i + j]) % p;
37     }
38 }
39 for(int j(0); j < m; j++) {
40     a[j] = b[j];
41 }
42 }

```

2.2 求逆元

```

1 void ex_gcd(long long a, long long b, long long &x, long long &y) {
2     if(b == 0) {
3         x = 1;
4         y = 0;
5         return;
6     }
7     long long xx, yy;
8     ex_gcd(b, a % b, xx, yy);
9     y = xx - a / b * yy;
10    x = yy;
11 }
12
13 long long inv(long long x, long long MODN) {
14     long long inv_x, y;
15     ex_gcd(x, MODN, inv_x, y);
16     return (inv_x % MODN + MODN) % MODN;
17 }

```

2.3 中国剩余定理

```

1 // 返回 (ans, M), 其中 ans 是模 M 意义下的解
2 std::pair<long long, long long> CRT(const std::vector<long long>& m, const
3     std::vector<long long>& a) {
4     long long M = 1, ans = 0;
5     int n = m.size();
6     for(int i = 0; i < n; i++) M *= m[i];
7     for(int i = 0; i < n; i++) {

```

```

7         ans = (ans + (M / m[i]) * a[i] % M * inv(M / m[i], m[i])) % M; // 可能需要大
8         整数相乘取模
9     }
10    return std::make_pair(ans, M);

```

Chapter 3 代数

3.1 快速傅里叶变换

```

1 // n 必须是 2 的次幂
2 void fft(Complex a[], int n, int f) {
3     for(int i = 0; i < n; ++i)
4         if(R[i] < i) swap(a[i], a[R[i]]);
5     for(int i = 1, h = 0; i < n; i <= 1, h++) {
6         Complex wn = Complex(cos(pi / i), f * sin(pi / i));
7         Complex w = Complex(1, 0);
8         for(int k = 0; k < i; ++k, w = w * wn) tmp[k] = w;
9         for(int p = i <= 1, j = 0; j < n; j += p) {
10            for(int k = 0; k < i; ++k) {
11                Complex x = a[j + k], y = a[j + k + i] * tmp[k];
12                a[j + k] = x + y; a[j + k + i] = x - y;
13            }
14        }
15    }
16 }

```

Chapter 4 字符串

4.1 后缀数组

```

1 const int MAXN = MAXL * 2 + 1;
2 int a[MAXN], x[MAXN], y[MAXN], c[MAXN], sa[MAXN], rank[MAXN], height[MAXN];
3 void calc_sa(int n) {
4     int m = alphabet, k = 1;
5     memset(c, 0, sizeof(*c) * (m + 1));
6     for(int i = 1; i <= n; ++i) c[x[i]] = a[i]++;
7     for(int i = 1; i <= m; ++i) c[i] += c[i - 1];
8     for(int i = n; i; --i) sa[c[x[i]]--] = i;
9     for(; k <= n; k <= 1) {
10        int tot = k;
11        for(int i = n - k + 1; i <= n; ++i) y[i - n + k] = i;
12        for(int i = 1; i <= n; ++i)
13            if(sa[i] > k) y[++tot] = sa[i] - k;
14        memset(c, 0, sizeof(*c) * (m + 1));
15        for(int i = 1; i <= n; ++i) c[x[i]]++;
16        for(int i = 1; i <= m; ++i) c[i] += c[i - 1];
17        for(int i = n; i; --i) sa[c[x[y[i]]]--] = y[i];
18        for(int i = 1; i <= n; ++i) y[i] = x[i];
19        tot = 1; x[sa[1]] = 1;
20        for(int i = 2; i <= n; ++i) {
21            if(max(sa[i], sa[i - 1]) + k > n || y[sa[i]] != y[sa[i - 1]] || y[sa[i] +
22                k] != y[sa[i - 1] + k]) ++tot;
23            x[sa[i]] = tot;
24        }
25        if(tot == n) break; else m = tot;
26    }
27 }
28 void calc_height(int n) {
29     for(int i = 1; i <= n; ++i) rank[sa[i]] = i;
30     for(int i = 1; i <= n; ++i) {
31         height[rank[i]] = max(0, height[rank[i - 1]] - 1);
32         if(rank[i] == 1) continue;
33         int j = sa[rank[i] - 1];
34         while(max(i, j) + height[rank[i]] <= n && a[i + height[rank[i]]] == a[j +
35             height[rank[i]]]) ++height[rank[i]];
36     }
37 }

```

4.2 后缀自动机

```
1 static const int MAXL = MAXN * 2; // MAXN is original length
2 static const int alphabet = 26; // sometimes need changing
3 int l, last, cnt, trans[MAXL][alphabet], par[MAXL], sum[MAXL], seq[MAXL], mxl[MAXL],
   size[MAXL]; // mxl is maxlength, size is the size of right
4 char str[MAXL];
5 inline void init() {
6     l = strlen(str + 1); cnt = last = 1;
7     for (int i = 0; i <= l * 2; ++i) memset(trans[i], 0, sizeof(trans[i]));
8     memset(par, 0, sizeof(*par) * (l * 2 + 1));
9     memset(mxl, 0, sizeof(*mxl) * (l * 2 + 1));
10    memset(size, 0, sizeof(*size) * (l * 2 + 1));
11 }
12 inline void extend(int pos, int c) {
13     int p = last, np = last = ++cnt;
14     mxl[np] = mxl[p] + 1; size[np] = 1;
15     for (; p && !trans[p][c]; p = par[p]) trans[p][c] = np;
16     if (!p) par[np] = 1;
17     else {
18         int q = trans[p][c];
19         if (mxl[p] + 1 == mxl[q]) par[np] = q;
20         else {
21             int nq = ++cnt;
22             mxl[nq] = mxl[p] + 1;
23             memcpy(trans[nq], trans[q], sizeof(trans[nq]));
24             par[nq] = par[q];
25             par[np] = par[q] = nq;
26             for (; trans[p][c] == q; p = par[p]) trans[p][c] = nq;
27         }
28     }
29 }
30 inline void buildsam() {
31     for (int i = 1; i <= l; ++i) extend(i, str[i] - 'a');
32     memset(sum, 0, sizeof(*sum) * (l * 2 + 1));
33     for (int i = 1; i <= cnt; ++i) sum[mxl[i]]++;
34     for (int i = 1; i <= l; ++i) sum[i] += sum[i - 1];
35     for (int i = cnt; i; --i) seq[sum[mxl[i]] - 1] = i;
36     for (int i = cnt; i; --i) size[par[seq[i]]] += size[seq[i]];
37 }
```

4.3 回文自动机

```
1 int nT, nStr, last, c[MAXT][26], fail[MAXT], r[MAXN], l[MAXN], s[MAXN];
2 int allocate(int len) {
3     l[nT] = len;
4     r[nT] = 0;
5     fail[nT] = 0;
6     memset(c[nT], 0, sizeof(c[nT]));
7     return nT++;
8 }
9 void init() {
10    nT = nStr = 0;
11    int newE = allocate(0);
12    int new0 = allocate(-1);
13    last = newE;
14    fail[newE] = new0;
15    fail[new0] = newE;
16    s[0] = -1;
17 }
18 void add(int x) {
19     s[++nStr] = x;
20     int now = last;
21     while (s[nStr - l[now] - 1] != s[nStr]) now = fail[now];
22     if (!c[now][x]) {
23         int newnode = allocate(l[now] + 2), &newfail = fail[newnode];
24         newfail = fail[now];
25         while (s[nStr - l[newfail] - 1] != s[nStr]) newfail = fail[newfail];
26         newfail = c[newfail][x];
27         c[now][x] = newnode;
28     }
29     last = c[now][x];
30 }
```

```
30     r[last]++;
31 }
32 void count() {
33     for (int i = nT - 1; i >= 0; i--) {
34         r[fail[i]] += r[i];
35     }
36 }
```

Chapter 5 图论

5.1 基础

```
1 struct Graph { // Remember to call .init()!
2     int e, nxt[M], v[M], adj[N], n;
3     bool base;
4     __inline void init(bool _base, int _n = 0) {
5         assert(n < N);
6         n = _n; base = _base;
7         e = 0; memset(adj + base, -1, sizeof(*adj) * n);
8     }
9     __inline int new_node() {
10        adj[n + base] = -1;
11        assert(n + base + 1 < N);
12        return n++ + base;
13    }
14    __inline void ins(int u0, int v0) { // directional
15        assert(u0 < n + base && v0 < n + base);
16        v[e] = v0; nxt[e] = adj[u0]; adj[u0] = e++;
17        assert(e < M);
18    }
19    __inline void bi_ins(int u0, int v0) { // bi-directional
20        ins(u0, v0); ins(v0, u0);
21    }
22 };
```

5.2 KM

```
1 struct KM {
2     // Truly O(n^3)
3     // 邻接矩阵, 不能连的边设为 -INF, 求最小权匹配时边权取负, 但不能连的还是 -INF,
   // 使用时先对 1 -> n 调用 hungary(), 再 get_ans() 求值
4     int w[N][N];
5     int lx[N], ly[N], match[N], way[N], slack[N];
6     bool used[N];
7     void init() {
8         for (int i = 1; i <= n; i++) {
9             match[i] = 0;
10            lx[i] = 0;
11            ly[i] = 0;
12            way[i] = 0;
13        }
14    }
15    void hungary(int x) {
16        match[0] = x;
17        int j0 = 0;
18        for (int j = 0; j <= n; j++) {
19            slack[j] = INF;
20            used[j] = false;
21        }
22        do {
23            used[j0] = true;
24            int i0 = match[j0], delta = INF, j1 = 0;
25            for (int j = 1; j <= n; j++) {
26                if (used[j] == false) {
27                    int cur = -w[i0][j] - lx[i0] - ly[j];
28                    if (cur < slack[j]) {
29                        slack[j] = cur;
30                        way[j] = j0;
31                    }
32                }
33            }
34        } while (delta == INF);
35    }
```

```

32         }
33         if (slack[j] < delta) {
34             delta = slack[j];
35             j1 = j;
36         }
37     }
38 }
39 for (int j = 0; j <= n; j++) {
40     if (used[j]) {
41         lx[match[j]] += delta;
42         ly[j] -= delta;
43     }
44     else slack[j] -= delta;
45 }
46 j0 = j1;
47 } while (match[j0] != 0);
48
49 do {
50     int j1 = way[j0];
51     match[j0] = match[j1];
52     j0 = j1;
53 } while (j0);
54 }
55
56 int get_ans() {
57     int sum = 0;
58     for (int i = 1; i <= n; i++) {
59         if (w[match[i]][i] == -INF) ; // 无解
60         if (match[i] > 0) sum += w[match[i]][i];
61     }
62     return sum;
63 }
64 } km;

```

5.3 点双连通分量

bcc.forest is a set of connected tree whose vertices are chequered with cut-vertex and BCC.

```

1 const bool BCC_VERTEX = 0, BCC_EDGE = 1;
2 struct BCC { // N = N0 + M0. Remember to call init(&raw_graph).
3     Graph *g, forest; // g is raw graph ptr.
4     int dfn[N], DFN, low[N];
5     int stack[N], top;
6     int expand_to[N]; // Where edge i is expanded to in expaned graph.
7     // Vertex i expanded to i.
8     int compress_to[N]; // Where vertex i is compressed to.
9     bool vertex_type[N], cut[N], compress_cut[N], branch[M];
10    //std::vector<int> BCC_component[N]; // Cut vertex belongs to none.
11    __inline void init(Graph *raw_graph) {
12        g = raw_graph;
13    }
14    void DFS(int u, int pe) {
15        dfn[u] = low[u] = ++DFN; cut[u] = false;
16        if (!g->adj[u]) {
17            cut[u] = 1;
18            compress_to[u] = forest.new_node();
19            compress_cut[compress_to[u]] = 1;
20        }
21        for (int e = g->adj[u]; ~e; e = g->nxt[e]) {
22            int v = g->v[e];
23            if ((e ^ pe) > 1 && dfn[v] > 0 && dfn[v] < dfn[u]) {
24                stack[top++] = e;
25                low[u] = std::min(low[u], dfn[v]);
26            }
27            else if (!dfn[v]) {
28                stack[top++] = e; branch[e] = 1;
29                DFS(v, e);
30                low[u] = std::min(low[v], low[u]);
31                if (low[v] >= dfn[u]) {
32                    if (!cut[u]) {
33                        cut[u] = 1;

```

```

34        compress_to[u] = forest.new_node();
35        compress_cut[compress_to[u]] = 1;
36    }
37    int cc = forest.new_node();
38    forest.bi_ins(compress_to[u], cc);
39    compress_cut[cc] = 0;
40    //BCC_component[cc].clear();
41    do {
42        int cur_e = stack[--top];
43        compress_to[expand_to[cur_e]] = cc;
44        compress_to[expand_to[cur_e^1]] = cc;
45        if (branch[cur_e]) {
46            int v = g->v[cur_e];
47            if (cut[v])
48                forest.bi_ins(cc, compress_to[v]);
49            else {
50                //BCC_component[cc].push_back(v);
51                compress_to[v] = cc;
52            }
53        }
54    } while (stack[top] != e);
55 }
56 }
57 }
58
59 void solve() {
60     forest.init(g->base);
61     int n = g->n;
62     for (int i = 0; i < g->e; i++) {
63         expand_to[i] = g->new_node();
64     }
65     memset(branch, 0, sizeof(*branch) * g->e);
66     memset(dfn + g->base, 0, sizeof(*dfn) * n); DFN = 0;
67     for (int i = 0; i < n; i++)
68         if (!dfn[i + g->base]) {
69             top = 0;
70             DFS(i + g->base, -1);
71         }
72 }
73 } bcc;
74
75 bcc.init(&raw_graph);
76 bcc.solve();
77 // Do something with bcc.forest ...

```

5.4 边双连通分量

```

1 struct BCC {
2     Graph *g, forest;
3     int dfn[N], low[N], stack[N], tot[N], belong[N], vis[N], top, dfs_clock;
4     // tot[] is the size of each BCC, belong[] is the BCC that each node belongs to
5     pair<int, int> ori[M]; // bridge in raw_graph(raw node)
6     bool is_bridge[M];
7     __inline void init(Graph *raw_graph) {
8         g = raw_graph;
9         memset(is_bridge, false, sizeof(*is_bridge) * g->e);
10        memset(vis + g->base, 0, sizeof(*vis) * g->n);
11    }
12    void tarjan(int u, int from) {
13        dfn[u] = low[u] = ++dfs_clock; vis[u] = 1; stack[++top] = u;
14        for (int p = g->adj[u]; ~p; p = g->nxt[p]) {
15            if ((p ^ 1) == from) continue;
16            int v = g->v[p];
17            if (vis[v]) {
18                if (vis[v] == 1) low[u] = min(low[u], dfn[v]);
19            } else {
20                tarjan(v, p);
21                low[u] = min(low[u], low[v]);
22                if (low[v] > dfn[u]) is_bridge[p / 2] = true;
23            }
24        }

```

```

25     if (dfn[u] != low[u]) return;
26     tot[forest.new_node()] = 0;
27     do {
28         belong[stack[top]] = forest.n;
29         vis[stack[top]] = 2;
30         tot[forest.n]++;
31         --top;
32     } while (stack[top + 1] != u);
33 }
34 void solve() {
35     forest.init(g -> base);
36     int n = g -> n;
37     for (int i = 0; i < n; ++i)
38         if (!vis[i + g -> base]) {
39             top = dfs_clock = 0;
40             tarjan(i + g -> base, -1);
41         }
42     for (int i = 0; i < g -> e / 2; ++i)
43         if (is_bridge[i]) {
44             int e = forest.e;
45             forest.bi_ins(belong[g -> v[i * 2]], belong[g -> v[i * 2 + 1]], g ->
46                 w[i * 2]);
47             ori[e] = make_pair(g -> v[i * 2 + 1], g -> v[i * 2]);
48             ori[e + 1] = make_pair(g -> v[i * 2], g -> v[i * 2 + 1]);
49         }
50 } bcc;

```

Chapter 6 技巧

6.1 真正的释放 STL 容器内存空间

```

1 template <typename T>
2 inline void clear(T& container) {
3     container.clear(); // 或者删除了一堆元素
4     T(container).swap(container);
5 }

```

6.2 无敌的大整数相乘取模

Time complexity $O(1)$.

```

1 // 需要保证 x 和 y 非负
2 long long mult(long long x, long long y, long long MODN) {
3     long long t = (x * y - (long long)((long double)x / MODN * y + 1e-3) * MODN) %
4     MODN;
5     return t < 0 ? t + MODN : t;
6 }

```

6.3 无敌的读入优化

```

1 // getchar() 读入优化 << 关同步 cin << 此优化
2 // 用 isdigit() 会小幅变慢
3 // 返回 false 表示读到文件尾
4 namespace Reader {

```

```

5     const int L = (1 << 15) + 5;
6     char buffer[L], *S, *T;
7     inline bool getchar(char &ch) {
8         if (S == T) {
9             T = (S = buffer) + fread(buffer, 1, L, stdin);
10            if (S == T) {
11                ch = EOF;
12                return false;
13            }
14        }
15        ch = *S++;
16        return true;
17    }
18    inline bool getint(int &x) {
19        char ch; bool neg = 0;
20        for (; getchar(ch) && (ch < '0' || ch > '9'); ) neg ^= ch == '-';
21        if (ch == EOF) return false;
22        x = ch - '0';
23        for (; getchar(ch), ch >= '0' && ch <= '9'; )
24            x = x * 10 + ch - '0';
25        if (neg) x = -x;
26        return true;
27    }
28 }

```

6.4 控制 cout 输出实数精度

```

1 std::cout << std::fixed << std::setprecision(5);

```

Chapter 7 提示

7.1 线性规划转对偶

$$\begin{aligned}
 &\text{maximize } \mathbf{c}^T \mathbf{x} \\
 &\text{subject to } \mathbf{A} \mathbf{x} \leq \mathbf{b}, \mathbf{x} \geq 0
 \end{aligned}
 \iff
 \begin{aligned}
 &\text{minimize } \mathbf{y}^T \mathbf{b} \\
 &\text{subject to } \mathbf{y}^T \mathbf{A} \geq \mathbf{c}^T, \mathbf{y} \geq 0
 \end{aligned}$$

7.2 32-bit/64-bit 随机素数

32-bit	64-bit
73550053	1249292846855685773
148898719	1701750434419805569
189560747	3605499878424114901
459874703	5648316673387803781
1202316001	6125342570814357977
1431183547	6215155308775851301
1438011109	6294606778040623451
1538762023	6347330550446020547
1557944263	7429632924303725207
1981315913	8524720079480389849

7.3 NTT 素数及其原根

Prime	Primitive root
1053818881	7
1051721729	6
1045430273	3
1012924417	5
1007681537	3