

Gungnir's Standard Code Library

Shanghai Jiao Tong University

Dated: September 19, 2016

Contents

| | | |
|----------|--------------------|----------|
| 1 | 计算几何 | 2 |
| 1.1 | 二维 | 2 |
| 1.1.1 | 基础 | 2 |
| 1.1.2 | 凸包 | 2 |
| 1.2 | 三维 | 3 |
| 1.2.1 | 基础 | 3 |
| 2 | 数论 | 3 |
| 2.1 | 求逆元 | 3 |
| 2.2 | 中国剩余定理 | 3 |
| 3 | 代数 | 3 |
| 3.1 | 快速傅里叶变换 | 3 |
| 4 | 字符串 | 3 |
| 4.1 | 后缀自动机 | 3 |
| 5 | 图论 | 4 |
| 5.1 | 基础 | 4 |
| 5.2 | KM | 4 |
| 5.3 | 点双连通分量 | 4 |
| 5.4 | 边双连通分量 | 5 |
| 6 | 技巧 | 5 |
| 6.1 | 真正的释放 STL 容器内存空间 | 5 |
| 6.2 | 无敌的大整数相乘取模 | 5 |
| 6.3 | 无敌的读入优化 | 5 |
| 6.4 | 控制 cout 输出实数精度 | 6 |
| 7 | 提示 | 6 |
| 7.1 | 线性规划转对偶 | 6 |
| 7.2 | 32-bit/64-bit 随机素数 | 6 |

Chapter 1 计算几何

1.1 二维

1.1.1 基础

```
1 typedef double DB;
2 const DB eps = 1e-8;
3
4 int sign(DB x) {
5     return x < -eps ? -1 : (x > eps ? 1 : 0);
6 }
7 DB msqrt(DB x) {
8     return sign(x) > 0 ? sqrt(x) : 0;
9 }
10
11 struct Point {
12     DB x, y;
13     Point(): x(0), y(0) {}
14     Point(DB x, DB y): x(x), y(y) {}
15     Point operator+(const Point &rhs) const {
16         return Point(x + rhs.x, y + rhs.y);
17     }
18     Point operator-(const Point &rhs) const {
19         return Point(x - rhs.x, y - rhs.y);
20     }
21     Point operator*(DB k) const {
22         return Point(x * k, y * k);
23     }
24     Point operator/(DB k) const {
25         assert(sign(k));
26         return Point(x / k, y / k);
27     }
28     Point rotate(DB ang) const { // 逆时针旋转 ang 弧度
29         return Point(cos(ang) * x - sin(ang) * y,
30                     cos(ang) * y + sin(ang) * x);
31     }
32     Point turn90() const { // 逆时针旋转 90 度
33         return Point(-y, x);
34     }
35 };
36 DB dot(const Point& a, const Point& b) {
37     return a.x * b.x + a.y * b.y;
38 }
39 DB det(const Point& a, const Point& b) {
40     return a.x * b.y - a.y * b.x;
41 }
42 bool isLL(const Line& l1, const Line& l2, Point& p) { // 直线与直线交点
43     DB s1 = det(l2.b - l2.a, l1.a - l2.a),
44         s2 = -det(l2.b - l2.a, l1.b - l2.a);
45     if (!sign(s1 + s2)) return false;
46     p = (l1.a * s2 + l1.b * s1) / (s1 + s2);
47     return true;
48 }
49 bool onSeg(const Line& l, const Point& p) { // 点在线段上
50     return sign(det(p - l.a, l.b - l.a)) == 0 && sign(dot(p - l.a, p - l.b)) <= 0;
51 }
52 DB disToLine(const Line& l, const Point& p) { // 点到直线距离
53     return fabs(det(p - l.a, l.b - l.a) / (l.b - l.a).len());
54 }
55 DB disToSeg(const Line& l, const Point& p) { // 点到线段距离
56     return sign(dot(p - l.a, l.b - l.a)) * sign(dot(p - l.b, l.a - l.b)) == 1 ?
57         disToLine(l, p) : std::min((p - l.a).len(), (p - l.b).len());
58 }
59 // 圆与直线交点
60 bool isCL(Circle a, Line l, Point& p1, Point& p2) {
61     DB x = dot(l.a - a.o, l.b - l.a),
62         y = (l.b - l.a).len2(),
63         d = x * x - y * ((l.a - a.o).len2() - a.r * a.r);
64     if (sign(d) < 0) return false;
```

```
64     Point p = l.a - ((l.b - l.a) * (x / y)), delta = (l.b - l.a) * (msqrt(d) / y);
65     p1 = p + delta; p2 = p - delta;
66     return true;
67 }
68 // 求凸包
69 std::vector<Point> convexHull(std::vector<Point> ps) {
70     int n = ps.size(); if (n <= 1) return ps;
71     std::sort(ps.begin(), ps.end());
72     std::vector<Point> qs;
73     for (int i = 0; i < n; qs.push_back(ps[i++]))
74         while (qs.size() > 1 && sign(det(qs[qs.size() - 2], qs.back(), ps[i])) <= 0)
75             qs.pop_back();
76     for (int i = n - 2, t = qs.size(); i >= 0; qs.push_back(ps[i--]))
77         while ((int)qs.size() > t && sign(det(qs[qs.size() - 2], qs.back(), ps[i])) <=
78             0)
79             qs.pop_back();
80     return qs;
```

1.1.2 凸包

```
1 // 凸包中的点按逆时针方向
2 struct Convex {
3     int n;
4     std::vector<Point> a, upper, lower;
5     void make_shell(const std::vector<Point>& p,
6                     std::vector<Point>& shell) { // p needs to be sorted.
7         clear(shell); int n = p.size();
8         for (int i = 0, j = 0; i < n; i++, j++) {
9             for (; j >= 2 && sign(det(shell[j-1] - shell[j-2],
10                                     p[i] - shell[j-2])) <= 0; --j) shell.pop_back();
11             shell.push_back(p[i]);
12         }
13     }
14     void make_convex() {
15         std::sort(a.begin(), a.end());
16         make_shell(a, lower);
17         std::reverse(a.begin(), a.end());
18         make_shell(a, upper);
19         a = lower; a.pop_back();
20         a.insert(a.end(), upper.begin(), upper.end());
21         if ((int)a.size() >= 2) a.pop_back();
22         n = a.size();
23     }
24     void init(const std::vector<Point>& _a) {
25         clear(a); a = _a; n = a.size();
26         make_convex();
27     }
28     void read(int _n) { // Won't make convex.
29         clear(a); n = _n; a.resize(n);
30         for (int i = 0; i < n; i++)
31             a[i].read();
32     }
33     std::pair<DB, int> get_tangent(
34         const std::vector<Point>& convex, const Point& vec) {
35         int l = 0, r = (int)convex.size() - 2;
36         assert(r >= 0);
37         for (; l + 1 < r; ) {
38             int mid = (l + r) / 2;
39             if (sign(det(convex[mid + 1] - convex[mid], vec)) > 0)
40                 r = mid;
41             else l = mid;
42         }
43         return std::max(std::make_pair(det(vec, convex[r]), r),
44                         std::make_pair(det(vec, convex[0]), 0));
45     }
46     int binary_search(Point u, Point v, int l, int r) {
47         int s1 = sign(det(v - u, a[l % n] - u));
48         for (; l + 1 < r; ) {
49             int mid = (l + r) / 2;
50             int smid = sign(det(v - u, a[mid % n] - u));
```

```

51     if (smid == s1) l = mid;
52     else r = mid;
53 }
54 return l % n;
55 }
56 // 求凸包上和向量 vec 叉积最大的点, 返回编号, 共线的多个切点返回任意一个
57 int get_tangent(Point vec) {
58     std::pair<DB, int> ret = get_tangent(upper, vec);
59     ret.second = (ret.second + (int)lower.size() - 1) % n;
60     ret = std::max(ret, get_tangent(lower, vec));
61     return ret.second;
62 }
63 // 求凸包和直线 u, v 的交点, 如果不相交返回 false, 如果有则是和 (i, next(i)) 的
    交点, 交在点上不确定返回前后两条边其中之一
64 bool get_intersection(Point u, Point v, int &i0, int &i1) {
65     int p0 = get_tangent(u - v), p1 = get_tangent(v - u);
66     if (sign(det(v - u, a[p0] - u)) * sign(det(v - u, a[p1] - u)) <= 0) {
67         if (p0 > p1) std::swap(p0, p1);
68         i0 = binary_search(u, v, p0, p1);
69         i1 = binary_search(u, v, p1, p0 + n);
70         return true;
71     }
72     else return false;
73 }
74 };

```

1.2 三维

1.2.1 基础

```

1 // 三维绕轴旋转, 大拇指指向 axis 向量方向, 四指弯曲方向转 w 弧度
2 Point rotate(const Point& s, const Point& axis, DB w) {
3     DB x = axis.x, y = axis.y, z = axis.z;
4     DB s1 = x * x + y * y + z * z, ss1 = msqrt(s1),
5         cosw = cos(w), sinw = sin(w);
6     DB a[4][4];
7     memset(a, 0, sizeof a);
8     a[3][3] = 1;
9     a[0][0] = ((y * y + z * z) * cosw + x * x) / s1;
10    a[0][1] = x * y * (1 - cosw) / s1 + z * sinw / ss1;
11    a[0][2] = x * z * (1 - cosw) / s1 - y * sinw / ss1;
12    a[1][0] = x * y * (1 - cosw) / s1 - z * sinw / ss1;
13    a[1][1] = ((x * x + z * z) * cosw + y * y) / s1;
14    a[1][2] = y * z * (1 - cosw) / s1 + x * sinw / ss1;
15    a[2][0] = x * z * (1 - cosw) / s1 + y * sinw / ss1;
16    a[2][1] = y * z * (1 - cosw) / s1 - x * sinw / ss1;
17    a[2][2] = ((x * x + y * y) * cosw + z * z) / s1;
18    DB ans[4] = {0, 0, 0, 0}, c[4] = {s.x, s.y, s.z, 1};
19    for (int i = 0; i < 4; ++i)
20        for (int j = 0; j < 4; ++j)
21            ans[i] += a[j][i] * c[j];
22    return Point(ans[0], ans[1], ans[2]);
23 }

```

Chapter 2 数论

2.1 求逆元

```

1 void ex_gcd(long long a, long long b, long long &x, long long &y) {
2     if (b == 0) {
3         x = 1;
4         y = 0;
5         return;
6     }
7     long long xx, yy;
8     ex_gcd(b, a % b, xx, yy);
9     y = xx - a / b * yy;
10    x = yy;
11 }
12
13 long long inv(long long x, long long MODN) {

```

```

14     long long inv_x, y;
15     ex_gcd(x, MODN, inv_x, y);
16     return (inv_x % MODN + MODN) % MODN;
17 }

```

2.2 中国剩余定理

```

1 // 返回 (ans, M), 其中 ans 是模 M 意义下的解
2 std::pair<long long, long long> CRT(const std::vector<long long>& m, const
    交点, 交在点上不确定返回前后两条边其中之一
3     std::vector<long long>& a) {
4     long long M = 1, ans = 0;
5     int n = m.size();
6     for (int i = 0; i < n; ++i) M *= m[i];
7     for (int i = 0; i < n; ++i) {
8         ans = (ans + (M / m[i]) * a[i] % M * inv(M / m[i], m[i])) % M; // 可能需要大
9         整数相乘取模
10    }
11    return std::make_pair(ans, M);

```

Chapter 3 代数

3.1 快速傅里叶变换

```

1 // n 必须是 2 的次幂
2 void fft(Complex a[], int n, int f) {
3     for (int i = 0; i < n; ++i)
4         if (R[i] < i) swap(a[i], a[R[i]]);
5     for (int i = 1, h = 0; i < n; i <= 1, h++) {
6         Complex wn = Complex(cos(pi / i), f * sin(pi / i));
7         Complex w = Complex(1, 0);
8         for (int k = 0; k < i; ++k, w = w * wn) tmp[k] = w;
9         for (int p = i <= 1, j = 0; j < n; j += p) {
10            for (int k = 0; k < i; ++k) {
11                Complex x = a[j + k], y = a[j + k + i] * tmp[k];
12                a[j + k] = x + y; a[j + k + i] = x - y;
13            }
14        }
15    }
16 }

```

Chapter 4 字符串

4.1 后缀自动机

```

1 struct Sam {
2     static const int MAXL = MAXN * 2; // MAXN is original length
3     static const int alphabet = 26; // sometimes need changing
4     int l, last, cnt, trans[MAXL][alphabet], par[MAXL], sum[MAXL], seq[MAXL],
5     mxl[MAXL], size[MAXL]; // mxl is maxlength, size is the size of right
6     char str[MAXL];
7     inline void init() {
8         l = strlen(str + 1); cnt = last = 1;
9         for (int i = 0; i <= l * 2; ++i) memset(trans[i], 0, sizeof(trans[i]));
10        memset(par, 0, sizeof(*par) * (l * 2 + 1));
11        memset(mxl, 0, sizeof(*mxl) * (l * 2 + 1));
12        memset(size, 0, sizeof(*size) * (l * 2 + 1));
13    }
14    inline void extend(int pos, int c) {
15        int p = last, np = last = ++cnt;
16        mxl[np] = mxl[p] + 1; size[np] = 1;
17        for (; p && !trans[p][c]; p = par[p]) trans[p][c] = np;
18        if (!p) par[np] = 1;
19        else {
20            int q = trans[p][c];
21            if (mxl[p] + 1 == mxl[q]) par[np] = q;
22            else {

```

```

22     int nq = ++cnt;
23     mxl[nq] = mxl[p] + 1;
24     memcpy(trans[nq], trans[q], sizeof(trans[nq]));
25     par[nq] = par[q];
26     par[np] = par[q] = nq;
27     for (; trans[p][c] == q; p = par[p]) trans[p][c] = nq;
28 }
29 }
30 }
31 inline void buildsam() {
32     for (int i = 1; i <= l; ++i) extend(i, str[i] - 'a');
33     memset(sum, 0, sizeof(*sum) * (l * 2 + 1));
34     for (int i = 1; i <= cnt; ++i) sum[mxl[i]]++;
35     for (int i = 1; i <= l; ++i) sum[i] += sum[i - 1];
36     for (int i = cnt; i; --i) seq[sum[mxl[i]]--] = i;
37     for (int i = cnt; i; --i) size[par[seq[i]]] += size[seq[i]];
38 }
39 } sam;

```

Chapter 5 图论

5.1 基础

```

1 struct Graph { // Remember to call .init()!
2     int e, nxt[M], v[M], adj[N], n;
3     bool base;
4     __inline void init(bool _base, int _n = 0) {
5         assert(n < N);
6         n = _n; base = _base;
7         e = 0; memset(adj + base, -1, sizeof(*adj) * n);
8     }
9     __inline int new_node() {
10         adj[n + base] = -1;
11         assert(n + base + 1 < N);
12         return n++ + base;
13     }
14     __inline void ins(int u0, int v0) { // directional
15         assert(u0 < n + base && v0 < n + base);
16         v[e] = v0; nxt[e] = adj[u0]; adj[u0] = e++;
17         assert(e < M);
18     }
19     __inline void bi_ins(int u0, int v0) { // bi-directional
20         ins(u0, v0); ins(v0, u0);
21     }
22 };

```

5.2 KM

```

1 struct KM {
2     // Truly O(n^3)
3     // 邻接矩阵, 不能连的边设为 -INF, 求最小权匹配时边权取负, 但不能连的还是 -INF,
4     // 使用时先对 1 -> n 调用 hungary(), 再 get_ans() 求值
5     int w[N][N];
6     int lx[N], ly[N], match[N], way[N], slack[N];
7     bool used[N];
8     void init() {
9         for (int i = 1; i <= n; i++) {
10             match[i] = 0;
11             lx[i] = 0;
12             ly[i] = 0;
13             way[i] = 0;
14         }
15     }
16     void hungary(int x) {
17         match[0] = x;
18         int j0 = 0;
19         for (int j = 0; j <= n; j++) {
20             slack[j] = INF;
21             used[j] = false;
22         }
23     }
24 }

```

```

22 do {
23     used[j0] = true;
24     int i0 = match[j0], delta = INF, j1 = 0;
25     for (int j = 1; j <= n; j++) {
26         if (used[j] == false) {
27             int cur = -w[i0][j] - lx[i0] - ly[j];
28             if (cur < slack[j]) {
29                 slack[j] = cur;
30                 way[j] = j0;
31             }
32             if (slack[j] < delta) {
33                 delta = slack[j];
34                 j1 = j;
35             }
36         }
37     }
38     for (int j = 0; j <= n; j++) {
39         if (used[j]) {
40             lx[match[j]] += delta;
41             ly[j] -= delta;
42         }
43         else slack[j] -= delta;
44     }
45     j0 = j1;
46 } while (match[j0] != 0);
47 do {
48     int j1 = way[j0];
49     match[j0] = match[j1];
50     j0 = j1;
51 } while (j0);
52 }
53 int get_ans() {
54     int sum = 0;
55     for (int i = 1; i <= n; i++) {
56         if (w[match[i]][i] == -INF) ; // 无解
57         if (match[i] > 0) sum += w[match[i]][i];
58     }
59     return sum;
60 }
61 } km;

```

5.3 点双连通分量

bcc.forest is a set of connected tree whose vertices are chequered with cut-vertex and BCC.

```

1 const bool BCC_VERTEX = 0, BCC_EDGE = 1;
2 struct BCC { // N = N0 + M0. Remember to call init(&raw_graph).
3     Graph *g, forest; // g is raw graph ptr.
4     int dfn[N], DFN, low[N];
5     int stack[N], top;
6     int expand_to[N]; // Where edge i is expanded to in expanded graph.
7     // Vertex i expanded to i.
8     int compress_to[N]; // Where vertex i is compressed to.
9     bool vertex_type[N], cut[N], compress_cut[N], branch[M];
10     //std::vector<int> BCC_component[N]; // Cut vertex belongs to none.
11     __inline void init(Graph *raw_graph) {
12         g = raw_graph;
13     }
14     void DFS(int u, int pe) {
15         dfn[u] = low[u] = ++DFN; cut[u] = false;
16         if (!~g->adj[u]) {
17             cut[u] = 1;
18             compress_to[u] = forest.new_node();
19             compress_cut[compress_to[u]] = 1;
20         }
21         for (int e = g->adj[u]; ~e; e = g->nxt[e]) {
22             int v = g->v[e];
23         }
24     }
25 }

```

```

23     if ((e ^ pe) > 1 && dfn[v] > 0 && dfn[v] < dfn[u]) {
24         stack[top++] = e;
25         low[u] = std::min(low[u], dfn[v]);
26     }
27     else if (!dfn[v]) {
28         stack[top++] = e; branch[e] = 1;
29         DFS(v, e);
30         low[u] = std::min(low[v], low[u]);
31         if (low[v] >= dfn[u]) {
32             if (!cut[u]) {
33                 cut[u] = 1;
34                 compress_to[u] = forest.new_node();
35                 compress_cut[compress_to[u]] = 1;
36             }
37             int cc = forest.new_node();
38             forest.bi_ins(compress_to[u], cc);
39             compress_cut[cc] = 0;
40             //BCC_component[cc].clear();
41             do {
42                 int cur_e = stack[--top];
43                 compress_to[expand_to[cur_e]] = cc;
44                 compress_to[expand_to[cur_e^1]] = cc;
45                 if (branch[cur_e]) {
46                     int v = g->v[cur_e];
47                     if (cut[v])
48                         forest.bi_ins(cc, compress_to[v]);
49                     else {
50                         //BCC_component[cc].push_back(v);
51                         compress_to[v] = cc;
52                     }
53                 }
54             } while (stack[top] != e);
55         }
56     }
57 }
58 }
59 void solve() {
60     forest.init(g->base);
61     int n = g->n;
62     for (int i = 0; i < g->e; i++) {
63         expand_to[i] = g->new_node();
64     }
65     memset(branch, 0, sizeof(*branch) * g->e);
66     memset(dfn + g->base, 0, sizeof(*dfn) * n); dfn = 0;
67     for (int i = 0; i < n; i++)
68         if (!dfn[i + g->base]) {
69             top = 0;
70             DFS(i + g->base, -1);
71         }
72 }
73 } bcc;
74
75 bcc.init(&raw_graph);
76 bcc.solve();
77 // Do something with bcc.forest ...

```

5.4 边双连通分量

```

1 struct BCC {
2     Graph *g, forest;
3     int dfn[N], low[N], stack[N], tot[N], belong[N], vis[N], top, dfs_clock;
4     // tot[] is the size of each BCC, belong[] is the BCC that each node belongs to
5     pair<int, int> ori[M]; // bridge in raw_graph(raw node)
6     bool is_bridge[M];
7     __inline void init(Graph *raw_graph) {
8         g = raw_graph;
9         memset(is_bridge, false, sizeof(*is_bridge) * g->e);
10        memset(vis + g->base, 0, sizeof(*vis) * g->n);
11    }
12    void tarjan(int u, int from) {
13        dfn[u] = low[u] = ++dfs_clock; vis[u] = 1; stack[++top] = u;
14        for (int p = g->adj[u]; ~p; p = g->nxt[p]) {

```

```

15        if ((p ^ 1) == from) continue;
16        int v = g->v[p];
17        if (vis[v]) {
18            if (vis[v] == 1) low[u] = min(low[u], dfn[v]);
19        } else {
20            tarjan(v, p);
21            low[u] = min(low[u], low[v]);
22            if (low[v] > dfn[u]) is_bridge[p / 2] = true;
23        }
24    }
25    if (dfn[u] != low[u]) return;
26    tot[forest.new_node()] = 0;
27    do {
28        belong[stack[top]] = forest.n;
29        vis[stack[top]] = 2;
30        tot[forest.n]++;
31        --top;
32    } while (stack[top + 1] != u);
33 }
34 void solve() {
35     forest.init(g->base);
36     int n = g->n;
37     for (int i = 0; i < n; ++i)
38         if (!vis[i + g->base]) {
39             top = dfs_clock = 0;
40             tarjan(i + g->base, -1);
41         }
42     for (int i = 0; i < g->e / 2; ++i)
43         if (is_bridge[i]) {
44             int e = forest.e;
45             forest.bi_ins(belong[g->v[i * 2]], belong[g->v[i * 2 + 1]], g->
46                 w[i * 2]);
47             ori[e] = make_pair(g->v[i * 2 + 1], g->v[i * 2]);
48             ori[e + 1] = make_pair(g->v[i * 2], g->v[i * 2 + 1]);
49         }
50 } bcc;

```

Chapter 6 技巧

6.1 真正的释放 STL 容器内存空间

```

1 template <typename T>
2 __inline void clear(T& container) {
3     container.clear(); // 或者删除了一堆元素
4     T(container).swap(container);
5 }

```

6.2 无敌的大整数相乘取模

Time complexity $O(1)$.

```

1 // 需要保证 x 和 y 非负
2 long long mult(long long x, long long y, long long MODN) {
3     long long t = (x * y - (long long)((long double)x / MODN * y + 1e-3) * MODN) %
4     MODN;
5     return t < 0 ? t + MODN : t;
6 }

```

6.3 无敌的读入优化

```

1 // getchar() 读入优化 << 关同步 cin << 此优化
2 // 用 isdigit() 会小幅变慢
3 // 返回 false 表示读到文件尾
4 namespace Reader {
5     const int L = (1 << 15) + 5;
6     char buffer[L], *S, *T;

```

```

7  __inline bool getchar(char &ch) {
8      if (S == T) {
9          T = (S = buffer) + fread(buffer, 1, L, stdin);
10         if (S == T) {
11             ch = EOF;
12             return false;
13         }
14     }
15     ch = *S++;
16     return true;
17 }
18 __inline bool getint(int &x) {
19     char ch; bool neg = 0;
20     for (; getchar(ch) && (ch < '0' || ch > '9'); ) neg ^= ch == '-';
21     if (ch == EOF) return false;
22     x = ch - '0';
23     for (; getchar(ch), ch >= '0' && ch <= '9'; )
24         x = x * 10 + ch - '0';
25     if (neg) x = -x;
26     return true;
27 }
28 }

```

6.4 控制 cout 输出实数精度

```
1 std::cout << std::fixed << std::setprecision(5);
```

Chapter 7 提示

7.1 线性规划转对偶

$$\begin{array}{ll}
 \text{maximize } \mathbf{c}^T \mathbf{x} & \\
 \text{subject to } \mathbf{Ax} \leq \mathbf{b}, \mathbf{x} \geq 0 & \iff \\
 \text{minimize } \mathbf{y}^T \mathbf{b} & \\
 \text{subject to } \mathbf{y}^T \mathbf{A} \geq \mathbf{c}^T, \mathbf{y} \geq 0 &
 \end{array}$$

7.2 32-bit/64-bit 随机素数

| 32-bit | 64-bit |
|------------|---------------------|
| 73550053 | 1249292846855685773 |
| 148898719 | 1701750434419805569 |
| 189560747 | 3605499878424114901 |
| 459874703 | 5648316673387803781 |
| 1202316001 | 6125342570814357977 |
| 1431183547 | 6215155308775851301 |
| 1438011109 | 6294606778040623451 |
| 1538762023 | 6347330550446020547 |
| 1557944263 | 7429632924303725207 |
| 1981315913 | 8524720079480389849 |