

# OnePlace

---

OnePlace - smart client for [Steem](#) and [Golos](#) blockchains. As a basis we took [Vue](#) with [SSR](#) module for frontend and [LoopBack](#) for backend.

## Installation

### Clone the repository and install npm modules

```
git clone git@github.com:OnePlace-media/oneplace.git
cd oneplace && npm i
```

### Install dependencies

This instruction is for debian based linux

#### NodeJS

Install NodeJS, we recommend using last [LTS version](#) and [nvm](#) for installation:

```
nvm install 8.9.4
nvm use 8.9.4
```

Also you need to install [mysql](#) and [redis](#) databases. Use [Docker Compose](#) with our [docker-compose.yml](#) or make manual install:

#### MySQL

```
sudo apt-get update
sudo apt-get install mysql-server
```

This repository includes init sql script, you can use it for fast start.

```
# Insert int sql script to ypu mysql daemon
mysql -u root < ./server/data/mysql/mysql-init.sql
# Login Mysql
mysql -u root
# Create new mysql user
CREATE USER 'oneplace'@'localhost' IDENTIFIED BY
'password';
# config privileges
GRANT ALL PRIVILEGES ON oneplace.* TO
'oneplace'@'localhost'
```

Also you can use [MySql WorkBench](#) with our [model file](#) to extend sql schema.

## Redis

```
sudo apt-get install redis
```

## Configuration

After you clone the repository and install dependencies you need to create configuration files.

```
cd server
# Main config file
```

```
cp config.sample.json config.json
# config for databases
cp datasources.sample.json datasources.json
```

## config.json

```
{
  ...,
  "postingWrapper": {
    "steemDomain": "...", // steem node with HTTP
    JSON-RPC
    "golosDomain": "...", // golos node with HTTP
    JSON-RPC
    "WIF": "APPLICATION POSTING_KEY", // you APP
    POSTING KEY
    "username": "APPLICATION USERNAME" // APP
    USERNAME in b`chains. Same name for all b`chains
  }
}
```

## Build and start

We prepared npm commands for fast build and start services. First you must build client with you config.

```
# Build front-end part of repo
npm run build
```

For start instances we also recommend using [PM2](#). See [process.json](#).

```
pm2 start process.json
```

```
# start monitoring panel
pm2 monit
```

But you can also try manual start.

### Manual start

```
# Start LoopBack-API server
npm start

# Start VueSSR server
npm run client
```

Please see [package.json](#) for more details.

## Post-install

This example is for nginx config file.

```
location /api {
    proxy_pass http://127.0.0.1:3001;
    proxy_set_header Host $host;
    proxy_set_header X-Forwarded-For
$proxy_add_x_forwarded_for;
    proxy_set_header X-Real-IP $remote_addr;
}
location ~* ^/(dist|static) {
    root
/var/www/oneplace/data/www/oneplace.media/client;
    expires 7d;
}
location / {
    proxy_pass http://127.0.0.1:3000;
```

```
proxy_set_header Host $host;
proxy_set_header X-Forwarded-For
$proxy_add_x_forwarded_for;
proxy_set_header X-Real-IP $remote_addr;
}
```

## Coming soon

- Cluster start and graceful reload, with zero downtime
- Full coverage Unit (frontend side) and BTD(API) test with Karma, Mocha and PhantomJS
- Continuous Integration and Auto Deploy
- Git flow and release notes
- Full documentation

## Issues

To report a non-critical issue, please file an issue on this GitHub project.

If you find a security issue please report details to:

[oneplace83@gmail.com](mailto:oneplace83@gmail.com)

We will evaluate the risk and make a patch available before filing the issue.