

User ID: 1 Cal. ID: 37

Date : 2024-01-08 11:54

### **Product Information**

Series ESM

Model ESMU20AS5

Flow Configuration BOT INTAKE - TOP DISC

Refrigerant R410A

Unit Dimension LxDxH 800 x 890 x 1985 mm<sup>3</sup>

Power Supply 400V-3ph-50Hz

#### **Fan Information**

Fan Type AC 450 D

No. of Fan

Fan Speed 1400 RPM

Filter Type G4

Airflow Rate 4890 m<sup>3</sup>/hr

External Static Pressure 184 Pa
Total Static Pressure 352 Pa
Motor Heat 1.1 kW

# **Entering Air Properties**

Dry Bulb Temperature 25.0 °C Relative Humidity 45.0 % Wet Bulb Temperature 17.1 °C

## **Outlet Air Properties**

Dry Bulb Temperature 14.0 °C Relative Humidity 84.9 % Wet Bulb Temperature 12.5 °C

## **Refrigeration System/Circuit**

Ambient Temperature 35.0 °C
No. of Circuit 1
Condenser Model HCC244
Heat Rejection 26.36 kW
Compressor Size 6HP
Evaporating Temperature 8.8 °C
Condensing Temperature 51.1 °C
Compressor Power Input 5.8 kW

# **Unit Capacity**

Gross Total Capacity

Gross Sensible Capacity

Gross SHR

Net Total Capacity

Net Sensible Capacity

Net SHR

20.56 kW

18.87 kW

0.92

19.46 kW

17.77 kW

0.91