A. Sum of Numbers I

Time limit	1 second
Memory limit	256 megabytes

Given integers n and m, compute their sum.

Input format

The single line contains integers n and m ($1 \le n, m \le 1000$).

Output format

Print a single integer — the sum $n + m$.

Samples

#	stdin	stdout
1	3 4	7

Scoring

Subgroup	Limits	Score	Required subgroups
0	Sample tests	0	—
1	$(1 \le n, m \le 1000)$	100	0

B. Sum of Numbers II

Time limit	1 second
Memory limit	256 megabytes

Given integers n and m, compute their sum.

Input format

The single line contains integers n and m ($1 \le n, m \le 1000$).

Output format

Print a single integer — the sum $n + m$.

Samples

#	stdin	stdout
1	3 4	7

Scoring

Subgroup	Limits	Score	Required subgroups
0	Sample tests	0	—
1	$(1 \le n, m \le 500)$	50	0
2	$(1 \le n, m \le 1000)$	50	—

C. Sum of Numbers III

Time limit	1 second
Memory limit	256 megabytes

Given integers n and m, compute their sum.

Input format

The single line contains integers n and m ($1 \le n, m \le 1000$).

Output format

Print a single integer — the sum $n + m$.

Samples

#	stdin	stdout
1	3 4	7

Scoring

Subgroup	Limits	Score	Required subgroups
0	Sample tests	0	—
1	$(1 \le n, m \le 1000)$	50	179

D. Sum of Numbers IV

Time limit	1 second
Memory limit	256 megabytes

This is a problem with subgroup merging.
Given integers n and m, compute their sum.

Input format

The single line contains integers n and m ($1 \le n, m \le 1000$).

Output format

Print a single integer — the sum $n + m$.

Samples

#	stdin	stdout
1	3 4	7

Scoring

Subgroup	Limits	Score	Required subgroups
0	Sample tests	0	—
1	$(1 \le n, m \le 500)$	50	0
2	$(1 \le n, m \le 1000)$	50	—

E. Sum of Numbers V

Time limit	1 second
Memory limit	256 megabytes

This is a problem with per-test scoring.
Given integers n and m, compute their sum.

Input format

The single line contains integers n and m ($1 \le n, m \le 1000$).

Output format

Print a single integer — the sum $n + m$.

Samples

#	stdin	stdout
1	3 4	7

Scoring

This problem has two tests in addition to the sample tests; each of them is scored independently and is worth 50 points.

F. Guess the Number

Time limit	1 second
Memory limit	256 megabytes

This is an interactive problem.

An integer from 1 to t is chosen, where t is a positive integer reported to the program. At most k queries of the form `? x` may be made (k is a hidden number):

- if x equals the chosen number, the interactor replies `=`, and the program must terminate immediately;
- if the chosen number is less than x, the interactor replies `<`;
- otherwise the interactor replies `>`.

Interactive protocol

First, the interactor reports a positive integer t $(1 \le t \le 10000)$ — the upper bound on the chosen number.

Then the program may make at most t queries of the form `? x`, where x is an integer from 1 to t. To each query the interactor replies with one of the symbols `<`, `>` or `=`.

After receiving the reply `=`, the program must terminate immediately.

Samples

#	Interactor	Solution
1	10 > < =	 ? 5 ? 8 ? 7

Scoring

Subgroup	Limits	Score	Required subgroups
0	Sample tests	0	—
1	$(1 \le t \le 10000)$	100	0

G. Add 1

Time limit	1 second
Memory limit	256 megabytes

This is a run-twice problem.
The program is run twice. In the first run it receives an integer n and must print $n + 1$. In the second run it receives the value printed by the first run and must recover the original number n. The second run receives no other information about n.

The first run

The single line contains an integer n ($1 \le n \le 1000$). Print $n + 1$.

The second run

The single line contains an integer v ($2 \le v \le 1001$) — the result of the first run. Print $v - 1$.

Samples

#	Run	stdin	stdout
1	The first run	`0` `10`	`11`
1	The second run	`1` `11`	`10`

Comments

The example shows both runs separately.

Scoring

Subgroup	Limits	Score	Required subgroups
0	Sample tests	0	—
1	($1 \le n \le 1000$)	100	0