## Coverage for ISO/IEC 8652:2012 in ACATS 3.x and 4.x

Clauses 4.5.7 - 4.5.8

A Key to Kinds and subkinds is found on the sheet named Key. Tests new to ACATS 3.0 are shown in **bold**; ACATS 3.1 in **bold italic**; ACATS 4.0 in **blue bold**; ACATS 4.1 in **blue bold italic**. ACATS 4.2 in **green bold italic**.

				_			Objective		Submitted tests	
se	Para.	Lines	Kind	Subkind	Notes	Tests	New Priority	Objective Text	Objective notes	(will need work)
	1/3		General							
	2/3		Syntax							
	3/3		Syntax							
	4/3		Syntax							
	5/3		Syntax							
	6/3		Syntax							
	7/3		Syntax		This is a syntax rule, but we test it because it's in English and it is so weird.	B457006	Part	Check that parentheses can be omitted around an if expression if it is in a context in which it is already surrounded 5 by parentheses.	C-Test. Test singleton parameters, qualified expressions, type conversions singleton indexing, pragma Assert, expression functions, and a singleton generic instance. Also possible for attribute parameters, which is too weird and the wrong type.	
								Check that parentheses can be omitted around a case expression if it is in a context in which it is already surrounded 4 by parentheses.	C-Test. Test singleton parameters, qualified expressions, type conversions singleton indexing, pragma Assert, expression functions, and a singleton generic instance. Also possible for attribute parameters, which is too weird and the wrong type.	
				Negative		B457006	All	Check that an if expression has to be surrounded in parentheses if it is not already surrounded by them.		
				Negative				Check that a case expression has to be surrounded in 6 parentheses if it is not already surrounded by them.	B-Test. Try in parameter lists with multiple parameters, indexing with multiple indexes, and in generic instances with multiple parameters.	Base on B457006?? N very likely to b different.
	8/3		NameRes			C457006 (enum literals)	Part	Check that overloaded functions can be resolved when they 7 appear as dependent expressions in an if expression.	C-Tests. Still need to try functions and operators, see C457006 for the pattern	
						C457006 (enum literals)	Part	Check that overloaded functions can be resolved when they 7 appear as dependent expressions in a case expression.	C-Tests. Still need to try functions and operators, see C457006 for the pattern	
						C457007	All	Check that literals can be resolved when they appear as dependent expressions in an if expression.		
						C457007	All	Check that literals can be resolved when they appear as dependent expressions in a case expression.		
	9/3		NameRes	Portion	Lead-in for following rules					
	10/3		NameRes					Check that an if expression used as the operand of a type conversion effectively distributes the conversion to each 8 dependent expression.	C-Test. Try cases where the dependent expressions have different but convertible types.	t
								Check that a case expression used as the operand of a type conversion effectively distributes the conversion to each 7 dependent expression.	C-Test. Try cases where the dependent expressions have different but convertible types.	t

11/3		NameRes		This does not appear testable separately; the paragraph 8/3 tests check the interesting cases.		
12/3		NameRes		This does not appear testable separately; the paragraph 8/3 tests check the interesting cases.		
13/3		NameRes		This does not appear testable separately; the paragraph 8/3 tests check the interesting cases.		
			Negative	If none of the above cases apply, the conditional expression does not resolve.	B457007	All
			Negative		B457007	All
14/3		NameRes		This rule was moved from 5.3, it is an Ada 83 rule.	C87B42A	
			Negative			
15/3		NameRes			C457004	All
			Negative	Based on the decision of Al12-0040-1; could check in 8.6, but it really relates here.	B860001	All
16/3		Legality	Widely- used	Any C-Test of a conditional expression will test.	200007	All
			Negative			
			-			
			Negative			
17/3	1	Legality	Subpart	Positive cases are listed under line 2.		

Check that if the type of an if expression is not determined by the resolution rules, it is illegal.

Check that if the type of a case expression is not determined by the resolution rules, it is illegal.

Check that a condition resolves if the overloading includes 2 only one solution involving boolean types.

C-Test. The existing test only tries while, if, and exit. Try other cases: entry barrier, guard, if expression (both if and elsif), elsif in an if statement. Low priority: unlikely to find a problem here.

B-Test. Try cases where there are no solutions, and cases where there are multiple solutions. Try in all condition contexts (if statement, if expression, exit statement, while loop, guard, entry barrier).

Check that a condition does not resolve if there is not exactly 3 one solution involving boolean types.

Check that the selecting\_expression of a case statement can be resolved if it is an overloaded function call, of which exactly one has a discrete type.

Check that the choices of a case expression have the type of C-Test. Borrow from the case 4 the selecting expression.

Check that the selecting expression of a case expression cannot be resolved if information from the choices is required to resolve it.

statement tests for this objective?

Check that an if expression is illegal if any of the dependent expressions cannot be converted to the type of the 7 expression.

B-Test. Try various legality rules related to conversion, like access-to-constant vs. access-to-variable, and accessibility. All 4.6 rules are available when the conditional expression is nested in a type conversion.

Check that a case expression is illegal if any of the dependent accessibility. All 4.6 rules are available expressions cannot be converted to the type of the 6 expression.

B-Test. Try various legality rules related to conversion, like access-to-constant vs. access-to-variable, and when the conditional expression is nested in a type conversion.

		Negative		B457005	All	Check that if the expected type of a if expression is a specific tagged type, then if some (but not all) of the dependent expressions are dynamically tagged, the expression is illegal.  Check that if the expected type of a case expression is a	
		Negative		B457005	All	specific tagged type, then if some (but not all) of the dependent expressions are dynamically tagged, the expression is illegal.	
2						Check that the dependent expressions of an if expression can be dynamically tagged, and that the expression can be used in a context that requires a dynamically tagged expression.  Check that the dependent expressions of a case expression can be dynamically tagged, and that the expression can be used in a context that requires a dynamically tagged expression.	C-Test.
					4	Check that the dependent expressions of an if expression can be tag-indeterminate, and that the expression can be used in a context that requires a tag-indeterminate expression.	C-Test.
					2	Check that the dependent expressions of a case expression can be tag-indeterminate, and that the expression can be used in a context that requires a tag-indeterminate expression.	C-Test.
					3	Check that the dependent expressions of an if expression can be statically tagged, and that the expression can be used in a context that requires a statically tagged expression.	C-Test.
					3	Check that the dependent expressions of a case expression can be statically tagged, and that the expression can be used in a context that requires a statically tagged expression.	C-Test.
18/3	Legality			C457002 (one case), <i>B457003</i>	All	Check that the else part can be omitted from a boolean if expression, and it has the value True.	Don't have a C-Test for a non-Boolean boolean type, but that seems hardly usage-oriented.
		Negative		B457003	All	Check that if the type of an if expression is not a boolean type, the else part cannot be omitted.	
19/3	Legality	Widely- used	Legal case expressions will of course meet these rules. We note the particular rules below.				
		Negative	5.4(5/3), sentence 1.	B457001 (dynamic predicates), B457004 (variables, subtypes)	All	Check that a case expression is illegal if any of the choices is non-static.	
		Negative	5.4(5/3), sentence 2.	B457002	All	Check that a case expression is illegal if others is not the last choice or does not stand alone.	
		-	5.4(6-9/3).	<b>B457001</b> (static predicates), <i>B457004</i> (non-predicate cases)	All	Check that a case expression is illegal if any of the possible values of the selecting expression are not covered by a choice.	
		Negative		B457001 (static predicates), B457004 (non-predicate cases)	All	Check that a case expression is illegal if more than one choice covers the same value.	

	20/3		Dynamic			C457001, C457002	All	Check that for the evaluation of an if expression, the condition specified after if, and any conditions specified after elsif, are evaluated in succession, until one evaluates to true.  Check that result of an if expression is the result of evaluating		
						C457001, C457002	All	the dependent expression corresponding to the condition that evaluates to True.		
	21/3	1	Dynamic					Check that the evaluation of a case expression starts by 5 evaluated the selecting expression.	C-Test. Pretty basic stuff.	
		2				<b>C457003</b> , <b>C457005</b> (others, ignored predicates)	, All	Check that result of an case expression is the result of evaluating the dependent expression corresponding to the choice selected by the selecting expression.		
						C457003	All	Check that only the selected dependent expression is evaluated in a case expression, along with the selecting expression.		
		3				C457003	All	Check that if the value of the selecting expression is not covered by any case alternative, Constraint_Error is raised.	This is almost untestable, since it is impossible to create an invalid value without making the program erroneous. But we can play tricks with uninitialized objects, as in this test. A better, but limited, way is in the next objective.	
						C457005	All	If the selecting expression of a case expression is a name with a static nominal subtype and has a static predicate, the case statement does not have an others clause, and the static predicate is disabled, then Constraint_Error is raised if the value of the selecting expression does not satisfy the predicate.		
4.5.8	0.1/4		Conoral		Added by AI12 0159 1					
4.3.0	1/3		General Syntax		Added by AI12-0158-1.					
	2/3		Syntax							
	3/3		Syntax							
	4/3		Syntax		This is a syntax rule, but we test it because it's in English and it is so weird.			Check that parentheses can be omitted around a quantified expression if it is in a context in which it is already surrounded 5 by parentheses.	C-Test. Test singleton parameters, qualified expressions, type conversions, singleton indexing, pragma Assert, and a singleton generic instance. Also possible for attribute parameters, which is too weird and the wrong type.	
				Negative				Check that a quantified expression has to be surrounded in 5 parentheses if it is not already surrounded by them.	B-Test. Try in parameter lists with multiple parameters, indexing with multiple indexes, and in generic instances with multiple parameters.	Base on B457006?? Not very likely to be different.
	5/3		NameRes					Check that the predicate of a quantified expression can be 7 resolved if it is an overloaded function call.	C-Test. Try overloaded functions that return a boolean and non-boolean type.	
				Negative				Check that the predicate of a quantified expression cannot 7 have a different type than the entire quantified expression.	B-Test.	
	6/4		Dynamic		Modified by Al12-0158-1, objectives unchanged.	C458001	All	Check that the predicate of a quantified expression is evaluated in the order specified by the loop_parameter_specification.		

7/3		Dynamic	Portion	This is lead-in text.		
8/4	1,2	Dynamic		Modified by Al12-0158-1, objectives unchanged.	C458001 (normal for loop)	Part
	3				C458001 (normal for loop)	Part
	4					
9/4	1, 2	Dynamic		Modified by Al12-0158-1, objectives unchanged.	<b>C458001</b> (normal for loop)	Part
	3				C458001 (normal for loop)	Part
	4					

Check that the predicate of a quantified expression is evaluated in the order specified by an array component 8 iterator specification.

Check that the predicate of a quantified expression is evaluated in the order specified by a generalized iterator 8 specification.

Check that the predicate of a quantified expression is evaluated in the order specified by a container element iterator C-Test. Use the foundation defined 8 specification.

Check that if the quantifier is all, the result of a quantified expression is True if the predicate is True for all values and 9 False otherwise.

Check that if the quantifier is all, the result of a quantified 8 expression is True if there are no values in the domain.

Check that evaluation of predicates stops for a quantified expression with a quantifier of all when a predicate evaluates 9 to False.

Check that any exceptions propagated by the predicate of a quantified expression with a quantifier of all is propagated by 5 the quantified expression.

Check that if the quantifier is some, the result of a quantified expression is True if the predicate is True for some value and 9 False otherwise.

Check that if the quantifier is some, the result of a quantified 8 expression is False if there are no values in the domain.

Check that evaluation of predicates stops for a quantified expression with a quantifier of some when a predicate 9 evaluates to True.

Check that any exceptions propagated by the predicate of a quantified expression with a quantifier of some is propagated 5 by the quantified expression.

C-Test.

C-Test. Use a foundation to define the iterator here, so it can be shared amongst a bunch of tests for this subclause. (Either that or make one giant test.)

above.

C-Test. Try for each kind of iterator.

C-Test. Try for each kind of iterator.

C-Test. Try for each kind of iterator. Make sure no extra evaluations are

C-Test. Try for each kind of iterator.

C-Test. Try for each kind of iterator.

C-Test. Try for each kind of iterator.

C-Test. Try for each kind of iterator. Make sure no extra evaluations are made.

C-Test. Try for each kind of iterator.

Paragraphs:		Objectives with tests:	Objectives to test: Total objectives:
2 31		30	34
	Must be tested	Objectives with Priority 10	0
		Objectives with Priority 9	4
	Important to test	Objectives with Priority 8	6
		Objectives with Priority 7	6
	Valuable to test	Objectives with Priority 6	2
		Objectives with Priority 5	6
	Ought to be tested	Objectives with Priority 4	6
		Objectives with Priority 3	3
	Worth testing	Objectives with Priority 2	1
	Not worth testing	Objectives with Priority 1	0
		Total:	34
		Objectives covered by new tests since ACATS 2.6	29

Completely:

Objectives with submitted tests: