Paper2MD-Tran...

Settings

Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features

App Home
Agents & AI Apps NEW
Work Object Previews NEW
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Steps from Apps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace

Review & Submit


Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

App Home

Where people find your app on Slack

Your app's home includes three tabs (Home, Messages and About) that help people have richer interactions with your app and better understand its functionality.
Learn more



Your App's Presence in Slack

Your app display name and presence is how your users will see your app in Slack.

App Display Name Edit

Display Name (Bot Name): Paper2MD-Translator

Default Name: paper2mdtranslator

Always Show My Bot as Online

Bot Token Added

A bot token in your app lets users at-mention it, add it to channels and conversations, and allows you to turn on tabs in your app's home. It makes it possible for users to interact with your app in Slack. You can adjust your Bot Token's permissions in OAuth & Permissions.

Show Tabs

Turn on the Home tab and/or Message tab to display in your app home.

Home Tab

Block Kit components you add to this tab let people easily interact with this app.

Helpful links

- App Home documentation
- How to use Block Kit
- Block Kit Builder tool

Messages Tab

Direct messages your app sends will show in this tab.

☐ Allow users to send Slash commands and messages from the messages tab

About Tab

Helpful info about what this app does will show in this tab. You can edit this info in the app's basic information section.

Paper2MD-Tran...

Settings

Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features

App Home
Agents & AI Apps NEW
Work Object Previews NEW
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Steps from Apps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace

Review & Submit

Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

Bolt app minimum versioning for org-level apps

If you use any of the Bolt frameworks to build your Slack app, please make sure you have a version that supports organization-level apps. Learn more

Enable org-readiness

An org-ready app is installed one time in your organization.

After installation, your app can then be made accessible to one, many, or all workspaces within the organization. Access is managed by your organization administrator.

Certain app features require org-readiness in order to function properly. Learn more.

Paper2MD-Tran...

Settings

Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features

App Home
Agents & AI Apps NEW
Work Object Previews NEW
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Steps from Apps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace

Review & Submit

Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

Incoming Webhooks

Activate Incoming Webhooks

Off

Incoming webhooks are a simple way to post messages from external sources into Slack. They make use of normal HTTP requests with a JSON payload, which includes the message and a few other optional details. You can include message attachments to display richly-formatted messages.

Adding incoming webhooks requires a bot user. If your app doesn't have a bot user, we'll add one for you.

Each time your app is installed, a new Webhook URL will be generated.

Paper2MD-Tran...

Settings

Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features

App Home
Agents & AI Apps NEW
Work Object Previews NEW
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Steps from Apps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace

Review & Submit

Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

Interactivity & Shortcuts

Interactivity

On

Any interactions with shortcuts, modals, or interactive components (such as buttons, select menus, and datepickers) will be sent to a URL you specify. Learn more.

Request URL

https://[redacted].ngrok-free.app/slack/events

Slack will send an HTTP POST request with information to this URL when users interact with a shortcut or interactive component.

Shortcuts

Let people take actions — like filing a bug or adding a new sales lead — while using your app in Slack. Learn more.

Name	Location	Callback ID

Create New Shortcut

Select Menus

If you want to load external data in your select menus, you need to provide an options load URL. Learn more.

Options Load URL

https://my.app.com/slack/options-load-endpoint

For interactions with select menus where `type` is set to `external_select`, Slack will send an HTTP POST request with information to load options from this URL upon user invocation.

Discard Changes Save Changes

Paper2MD-Tran...

Settings

Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features

App Home
Agents & AI Apps NEW
Work Object Previews NEW
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Steps from Apps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace

Review & Submit

Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

Slash Commands

Commands enable users to interact with your app from within Slack. Learn more.

Adding commands requires a bot user. If your app doesn't have a bot user, we'll add one for you.

Create New Command | Copy Existing Command

Paper2MD-Tran...

Settings

Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features

App Home
Agents & AI Apps NEW
Work Object Previews NEW
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Steps from Apps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace

Review & Submit

Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

OAuth & Permissions

Advanced token security via token rotation

Recommended for developers building on or for security-minded organizations – opting into token rotation allows app tokens to automatically expire after they're issued within your app code. View documentation.

⚠ At least one redirect URL needs to be set below before this app can be opted into token rotation

Opt In

OAuth Tokens

These tokens were automatically generated when you installed the app to **Tohoku NLP**. You can use these to authenticate your app. Learn more.

Bot User OAuth Token

xo[redacted] Copy

Access Level: Workspace

Reinstall to Tohoku NLP

Redirect URLs

You will need to configure redirect URLs in order to automatically generate the Add to Slack button or to distribute your app. If you pass a URL in an OAuth request, it must (partially) match one of the URLs you enter here. Learn more.

Redirect URLs

You haven't added any Redirect URLs

Add New Redirect URL

Save URLs

Scopes

A Slack app's capabilities and permissions are governed by the scopes it requests.

Bot Token Scopes

Scopes that govern what your app can access.

OAuth Scope	Description
app_mentions:read	View messages that directly mention @Paper2MD-Translator in conversations that the app is in
channels:history	View messages and other content in public channels that Paper2MD-Translator has been added to
channels:read	View basic information about public channels in a workspace
chat:write	Send messages as @Paper2MD-Translator
files:read	View files shared in channels and conversations that Paper2MD-Translator has

	been added to
files:write	Upload, edit, and delete files as Paper2MD-Translator
groups:history	View messages and other content in private channels that Paper2MD-Translator has been added to
groups:read	View basic information about private channels that Paper2MD-Translator has been added to
im:history	View messages and other content in direct messages that Paper2MD-Translator has been added to
mpim:history	View messages and other content in group direct messages that Paper2MD-Translator has been added to
mpim:read	View basic information about group direct messages that Paper2MD-Translator has been added to

Add an OAuth Scope

User Token Scopes

Scopes that access user data and act on behalf of users that authorize them.

OAuth Scope	Description
You haven't added any OAuth Scopes for your User token.	

Add an OAuth Scope

Scopes define the API methods an app is allowed to call, which information and capabilities are available on the workspace it's installed on. Many scopes are restricted to specific resources like channels or files.

Restrict API Token Usage

Slack can limit use of your app's OAuth tokens to a list of IP addresses and ranges you provide. Slack will then reject Web API method calls from unlisted IP addresses. Learn More.

Allowed IP Address Ranges

You haven't added any IP address ranges

Add a new IP address range

Save IP address ranges

Revoke All OAuth Tokens

You can revoke all OAuth tokens if you want to invalidate the access any existing tokens have to Slack workspace data. Users will need to grant your app permissions again to use it.

Revoke Tokens

Paper2MD-Tran...

Settings

Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features

App Home
Agents & AI Apps NEW
Work Object Previews NEW
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Steps from Apps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace

Review & Submit

Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

Event Subscriptions

Enable Events

On

Your app can subscribe to be notified of events in Slack (for example, when a user adds a reaction or creates a file) at a URL you choose. Learn more.

Request URL Verified ✓

https://[redacted].ngrok-free.app/slack/events Change

We'll send HTTP POST requests to this URL when events occur. As soon as you enter a URL, we'll send a request with a `challenge` parameter, and your endpoint must respond with the challenge value. Learn more.

Subscribe to bot events

Apps can subscribe to receive events the bot user has access to (like new messages in a channel). If you add an event here, we'll add the necessary OAuth scope for you.

Event Name	Description	Required Scope	
app_home_opened	User clicked into your App Home	none	🗑
member_joined_channel	A user joined a public channel, private channel or MPDM.	channels:read or groups:read or mpim:read	🗑
message.channels	A message was posted to a channel	channels:history	🗑
message.groups	A message was posted to a private channel	groups:history	🗑
message.im	A message was posted in a direct message channel	im:history	🗑
message.mpim	A message was posted in a multiparty direct message channel	mpim:history	🗑

Add Bot User Event

Subscribe to events on behalf of users

You may also want your app to receive events related to users who have authorized the app (and conversations they're part of). If you add an event here, we'll add the necessary OAuth scope for you.

Event Name	Description	Required Scope

No events added yet.

Add Workspace Event

App unfurl domains

Your app can be notified when users post links from up to 5 domains. This requires the `links:read` scope and a subscription to the `link_shared` event.

You'll receive events for any subdomain, or path of the selected domains or hosts. Ports are ignored, so requests on any port will trigger an event. Using IP addresses is not allowed. Learn more.

Add Domain

Discard Changes Save Changes

Paper2MD-Tran...

Settings

Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features

App Home
Agents & AI Apps NEW
Work Object Previews NEW
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Steps from Apps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace

Review & Submit

Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

User ID Translation

Translate Global IDs

On

Slack will automatically translate global (W) user IDs to local user IDs.

Enterprise Grid workspaces feature global user IDs, identifying team members across workspaces. Your app may encounter both local user IDs and global user IDs representing the same users.

Disable translation to send and receive global user IDs exclusively. Learn more.

Paper2MD-Transla

Settings
Basic Information
Collaborators
Socket Mode
Install App
Manage Distribution

Features
App Home
App Agents & AI Apps...
Work Object Previews...
Workflow Steps NEW
Org Level Apps
Incoming Webhooks
Interactivity & Shortcuts
Slash Commands
Workflow Steps LEGACY
OAuth & Permissions
Event Subscriptions
User ID Translation
App Manifest NEW
Beta Features

Submit to Slack Marketplace
Prepare & Submit
1. Your App Listing
2. Review scopes
3. Security and compliance
4. Testing information
5. Automated checks

Give feedback

Slack ♥
Help
Contact
Policies
Our Blog

App Manifest

Save Changes

The manifest below captures your app as it's currently configured. You can make any changes to your basic info, settings, or feature configurations right here.

Have suggestions or feature requests? Give us feedback

JSON YAML View Example Copy to Clipboard Download


```
{
    "display_information": {
        "name": "Paper2MD-Translator",
        "description": "Simply paste a paper's URL/PDF to generate translated Markdown",
        "background_color": "#6373a6",
        "long_description": "*【使い方 】*\r\n\r\nこのアプリを使用することで、論文 PDF もしくは 論文 PDF の URL から日本語 Markdown ファイルを生成すると同時に要約も生成します。\r\n\r\n現在、対応している論文 pdf は以下のものになります。\r\n・論文 PDF を直接添付\r\n・http://hoge.pdf, https://hoge.pdf のような形式の URL\r\n・arXiv リンク\r\n ・e.g., https://arxiv.org/abs/2304.08485\r\n ・e.g., https://arxiv.org/pdf/2304.08485\r\n\r\n以下のように、 `@Paper2MD-Translator` へのメンション付きで論文 URL/PDF を添付して送信することで、クエリが投入されます。\r\n\r\n```\r\n@Paper2MD-Translator\r\nhttps://arxiv.org/abs/2304.08485\r\n```\r\n\r\n==========\r\n==========\r\n\r\n*【Q&A】*\r\n\r\n----------\r\n\r\nQ: 処理が開始されません。なぜでしょうか？以下のようなクエリを送っています。\r\n```\r\n@Paper2MD-Translator\r\nTowards Understanding How Knowledge Evolves in Large Vision-Language Models (Wang+, CVPR2025)\r\nhttps://openaccess.thecvf.com/content/CVPR2025/papers/Wang_Towards_Understanding_How_Kn[…]volves_in_Large_Vision-Language_Models_CVPR_2025_paper.pdf\r\n```\r\n\r\nA: URL が長くなってしまう場合、省略記号が入る（e.g., Kn[…]volves_ ）ことによって、正しい URL を取得できずに URL から pdf のダウンロードに失敗してしまいます。このように URL が長くなってしまう場合には、インラインコード記法で URL を囲む（e.g., `https://hoge.pdf` ）ことで解決します。\r\n\r\n----------\r\n\r\nQ: Gyazo の API KEY はどこで確認できるのでしょうか？また、何に使われるのでしょうか？\r\n\r\nA: Gyazo の API KEY はここ（https://gyazo.com/oauth/applications）から入手できます。作成時の Callback URL は適当で良いです（e.g., https://pdftoimage.com）。\r\nまた、Gyazo API KEY を追加することで、アプリから出力されるマークダウンファイルに含まれる画像（図や表）が Gyazo 画像アドレス付きで出力される仕様になっています。そのため、マークダウンファイルに Gyazo 画像アドレスを埋め込んで利用されたい方は、Gyazo API KEY を追加してください。また、Gyazo API KEY を追加されない場合、マークダウンファイル中の画像（図や表）はサーバー上の絶対パスで埋め込まれます。\r\n\r\n----------\r\n\r\nQ: Gemini, Claude の API KEY は何に使われるのでしょうか？\r\n\r\nA: 現状、Gemini, Claude の API KEY は何にも使われません。ですので、API KEY の入力は不要です。将来的に、ユーザーがモデルを選択して使用できるように拡張予定であり、そのためにフォームだけ追加されているといった経緯になります。\r\n\r\n----------"
    },
    "features": {
        "app_home": {
            "home_tab_enabled": true,
            "messages_tab_enabled": false,
            "messages_tab_read_only_enabled": true
        },
        "bot_user": {
            "display_name": "Paper2MD-Translator",
            "always_online": false
        }
    },
    "oauth_config": {
        "scopes": {
            "bot": [
                "app_mentions:read",
                "channels:history",
                "chat:write",
                "files:write",
                "groups:history",
                "im:history",
                "mpim:history",
                "files:read",
                "channels:read",
                "groups:read",
                "mpim:read"
            ]
        }
    },
    "settings": {
        "event_subscriptions": {
            "request_url": "https://[redacted].ngrok-free.app/slack/events",
            "bot_events": [
                "app_home_opened",
                "member_joined_channel",
                "message.channels",
                "message.groups",
                "message.im",
                "message.mpim"
            ]
        },
        "interactivity": {
            "is_enabled": true,
            "request_url": "https://[redacted].ngrok-free.app/slack/events"
        },
        "org_deploy_enabled": false,
        "socket_mode_enabled": false,
        "token_rotation_enabled": false
    }
}
```