Cross-Lingual Evidence Verification: Verifier Prediction Sensitivity Under Hindi-to-English Translation Shift

Onkar Kharat[1] **Himanshu Jadhav**[2]
[1]Lead Researcher, Cross-Lingual Evidence Verification Project
[2]Co-Author & Research Contributor
Repository: https://github.com/Onkar-Kharat/research-crosslingual-rag

Abstract

Cross-lingual claim verification systems frequently convert non-English evidence texts into intermediate English representations prior to automated veracity classification. However, translating evidence introduces a critical tension between exploiting high-capacity English language models and introducing semantic distortion. In this study, we present a controlled empirical investigation of verifier prediction sensitivity under Hindi-to-English translation shift on authentic claim-evidence pairs from the X-Fact benchmark ($N = 266$: 103 development, 163 held-out test). Holding the claim, pre-retrieved evidence snippets, and cross-lingual verifier (`mDeBERTa-v3-base`) fixed, we evaluate veracity decisions across four paired conditions: *No-Check* (machine-translated English evidence), *Direct Multilingual* (original Hindi evidence), *Always-Check* (unconditional posterior consensus), and a risk-calibrated *Selective-Check* cascade tuned on development data ($\tau^* = 0.650$).

We observe an overall paired prediction disagreement rate of 63.80% (104/163; 95% CI: [56.19%, 70.78%]) between original and translated evidence representations. When translated evidence predicts SUPPORTED, evaluating the original Hindi evidence flips the prediction to CONTRADICTED in 48.44% of cases (31/64). Direct Multilingual verification achieves 42.94% accuracy (70/163), significantly outperforming the No-Check baseline (28.22%, 46/163; McNemar exact $p = 0.008772$, $b = 27, c = 51$). However, risk-calibrated Selective-Check does not surpass No-Check accuracy (28.22%, 46/163; coverage 7.98%), and paired permutation tests on class-balanced Macro-F1 reveal no statistically significant difference across conditions ($p = 0.1898$ and $p = 0.1180$), reflecting the high variance of harmonic metrics under severe natural class skew (87.12% CONTRADICTED, 0.0% gold SUPPORTED). We transparently document the exploratory nature of this evaluation, the prior inspection of the test split, and the necessity of pending bilingual human validation before causal translation claims can be substantiated.

1 Introduction

Automated claim verification and fact-checking are essential technical defenses against misinformation across multilingual digital ecosystems (Thorne et al., 2018; Gupta and Srikumar, 2021). In retrieval-augmented generation (RAG) and evidence-grounded verification architectures operating in multilingual environments, retrieved evidence passages frequently originate in a language different from the claim or the primary training language of the downstream verifier (Lewis et al., 2020; Liu et al., 2025).

To address multilingual discrepancies, practical verification architectures routinely adopt a "translate-then-verify" paradigm: source-language evidence snippets are machine-translated into English bridge sequences before being processed by a cross-lingual entailment model (Ranaldi et al., 2026; Singhal et al., 2024). While projecting into an English bridge format allows systems to leverage high-capacity English language models, machine translation can subtly distort fine-grained factual relationships, including named entities, negation scope, numerals, and temporal qualifiers (Singhal et al., 2024). Conversely, cross-lingual verifiers evaluating original evidence directly (*Direct Multilingual*) avoid translation artifacts but may exhibit reduced reasoning accuracy in lower-resource languages or incur substantial latency penalties (Wang et al., 2026; Conneau et al., 2020).

While recent literature has actively examined cross-lingual RAG for generative question answering (Liu et al., 2025; Ranaldi et al., 2026) and uncovered language bias in dense document rerankers (Wang et al., 2026), previous studies have largely

treated evidence translation as a monolithic utility. As a result, two fundamental empirical questions remain unresolved for cross-lingual claim verification:

1. **Prediction Sensitivity Under Translation Shift:** When an identical claim and evidence passage are evaluated by the same cross-lingual verifier, to what extent do predictions flip between the original language and machine-translated representations, and what specific directional transitions characterize this disagreement?

2. **Efficacy of Selective Original-Evidence Fallback:** Can a lightweight, test-time risk trigger (combining verifier predictive uncertainty and numeral overlap) selectively consult original evidence, and does such a selective cascade improve overall veracity accuracy compared to translated-only and unconditional dual-language consensus?

To address these questions, we establish a controlled empirical investigation using authentic journalistic fact-checks from the Hindi partition of the X-Fact benchmark (Gupta and Srikumar, 2021). By holding the claim, retrieved evidence snippets, verifier architecture (`mDeBERTa-v3-base`; He et al. 2021; Laurer et al. 2024), and decoding configuration fixed across paired conditions, we isolate the specific sensitivity of the verifier to evidence language representation.

We define four paired conditions:

- **No-Check (Translated English Only):** Evaluates machine-translated evidence passages (e_{trans}).
- **Direct Multilingual (Original Hindi Only):** Evaluates original Hindi evidence passages (e_{orig}).
- **Always-Check (Dual Consensus):** Unconditionally averages class posterior distributions from both representations.
- **Selective-Check:** Employs a risk-gated cascade tuned strictly on development data ($\tau^* = 0.650$), consulting original Hindi evidence only when predictive uncertainty or numeral mismatch is elevated.

Scope and Empirical Guardrails. To ensure strict research integrity, we explicitly define the boundaries of this study:

- *Evidence Representation, Not End-to-End RAG:* This study evaluates pre-retrieved evidence snippets; upstream retrieval mechanisms and downstream generative answer synthesis are not varied.
- *Observational Model Sensitivity, Not Translation Causality:* Without completed bilingual human validation, model prediction disagreement cannot be definitively attributed to translation distortion. All findings are reported as observational prediction sensitivity.
- *Exploratory Diagnostic Evaluation:* Because the test split ($N = 163$) was evaluated during earlier exploratory research, all evaluations are designated as diagnostic rather than confirmatory holdout testing.
- *Dataset Imbalance Disclosure:* The official X-Fact Hindi test partition contains 142 CONTRADICTED and 21 INSUFFICIENT_EVIDENCE instances, and exactly zero gold SUPPORTED instances. Accuracy and nominal Macro-F1 are analyzed as secondary descriptive proxies rather than general fact-checking capabilities.

Key Findings. Our empirical results on the test partition reveal:

1. **Substantial Prediction Disagreement:** Verifier predictions disagree across language representations on 63.80% of instances (104/163; 95% CI: [56.19%, 70.78%]).
2. **Pronounced Directional Flips:** When translated evidence predicts SUPPORTED, evaluating the original Hindi evidence flips the prediction to CONTRADICTED on 48.44% of cases (31/64).
3. **Accuracy Disparity and McNemar Significance:** Direct Multilingual achieves 42.94% accuracy (70/163), significantly outperforming the No-Check baseline (28.22%, 46/163; McNemar exact $p = 0.008772$, $b = 27, c = 51$).
4. **Selective Cascade Limitations:** Selective-Check ($\tau^* = 0.650$) triggers on 7.98% of test

instances (saving 59.2% compute relative to Direct Multilingual) but matches No-Check accuracy exactly (46 vs. 46, 28.22%; McNemar exact $p = 1.0000$). On development data, the zero-check baseline utility ($J = 0.2104$) exceeds the cascade peak ($J = 0.2023$).

5. **Metric Discordance Under Class Skew:** While accuracy gains for Direct Multilingual are statistically significant under McNemar's paired test, paired permutation tests on class-balanced Macro-F1 ($B = 5,000$, seed 42) do not reach significance ($p = 0.1898$ and $p = 0.1180$), demonstrating the vulnerability of harmonic metrics under severe benchmark class imbalance.

2 Related Work

We situate our empirical investigation at the intersection of multilingual retrieval-augmented generation, cross-lingual claim verification, translation distortion in downstream NLP, and selective classification cascades.

2.1 Multilingual and Cross-Lingual RAG

Retrieval-augmented generation (RAG) grounds language model predictions in external non-parametric evidence passages (Lewis et al., 2020). In multilingual settings, systems must bridge linguistic gaps when queries, evidence documents, or downstream generation targets diverge in language. Liu et al. (2025) formalize cross-lingual RAG (XRAG) across diverse language pairs (e.g., Arabic, Chinese, German, Spanish, English), demonstrating that retrieving evidence across languages introduces severe generative drift and syntactic interference during answer synthesis. To mitigate multilingual knowledge disparities, Ranaldi et al. (2026) introduce CrossRAG, which converts non-English search contexts into an intermediate English representation prior to generative decoding by an English reader model. While CrossRAG demonstrates empirical gains on open-domain question answering benchmarks (MKQA, MLQA, XOR-TyDi), it evaluates continuous text generation where downstream decoders can tolerate mild paraphrase variance. In contrast, claim verification requires sharp, discrete entailment decisions where subtle semantic shifts induce categorical veracity flips.

Concurrently, investigations into cross-lingual indexing bias demonstrate that neural retrieval and reranking systems systematically prioritize English-centric documents over non-English counterparts (Wang et al., 2026; Conneau et al., 2020). While Wang et al. (2026) examine upstream retrieval representation bias, our work investigates the complementary downstream stage: holding pre-retrieved evidence fixed, how sensitive is the veracity decision of a multilingual verifier to evidence language representation?

2.2 Cross-Lingual Fact and Claim Verification

Automated fact verification has expanded from monolingual English benchmarks such as FEVER (Thorne et al., 2018) to multi-language and real-world claim contexts. The X-Fact benchmark (Gupta and Srikumar, 2021) introduced naturally occurring fact-checks across 25 languages, reflecting authentic journalistic claims labeled by professional fact-checkers. Recent comprehensive benchmarking on X-Fact by Shcharbakova et al. (2025) reveals a critical architectural insight: fine-grained claim verification on low- and medium-resource languages remains an immense challenge for large generative language models (7B–12B parameters), which frequently succumb to multilingual hallucination, whereas specialized multilingual encoder-based NLI verifiers (`mDeBERTa-v3`, `XLM-RoBERTa`) consistently achieve superior evidence grounding and calibration (He et al., 2021; Laurer et al., 2024). However, Shcharbakova et al. (2025) evaluate evidence passages strictly in their scraped source language, leaving the interaction between machine translation and multilingual verification unexamined.

2.3 Translation Shift and Semantic Distortion

The "translate-then-verify" paradigm rests on the assumption that translation bridges language barriers without perturbing factual content. However, machine translation systems (Tiedemann and Thottingal, 2020) frequently suffer from subtle hallucinations, mistranslation of named entities, altered numerical quantities, and dropped negation markers. In an exploratory evaluation of multilingual fact-checking with LLMs, Singhal et al. (2024) observed that pipeline translation into English frequently deteriorated classification accuracy in low-resource languages. Nevertheless, prior literature has treated translation degradation as a monolithic aggregate drop, failing to provide directional transition analyses, paired statistical hypothesis tests, or diagnostic error stratifications.

2.4 Selective Prediction and Cascade Verification

Selective prediction (or classification with a reject option) enables models to abstain or defer uncertain predictions to a more capable or expensive oracle (Geifman and El-Yaniv, 2017). In cost-sensitive NLP, cascade architectures route easy queries to lightweight, low-latency models and difficult queries to large models. We adapt this principle to cross-lingual verification: rather than unconditionally translating or unconditionally running heavy dual-language models, we evaluate whether a lightweight risk gating mechanism can selectively trigger original-language verification only when the translation path exhibits high predictive uncertainty or surface-level entity corruption.

2.5 Summary of Literature Positioning

Table 1 summarizes how this study relates to and differs from prior work across task, language setting, architecture, evaluation design, and empirical focus. Our study does not claim to present a new foundation model or a universally optimal RAG pipeline. Instead, it provides the first rigorously controlled, paired empirical characterization of verifier prediction sensitivity under Hindi-to-English translation shift, establishing transparent directional transition matrices and identifying the fundamental diagnostic challenges posed by benchmark class imbalance.

3 Task Formulation and Research Questions

We formalize the cross-lingual evidence verification problem, define the four evaluated system conditions, and state our pre-registered empirical research questions.

3.1 Formal Task Definition

Let a verification instance be defined as a tuple $(c, e_{\text{orig}}, y^*)$, where:

- c denotes a natural language claim written in or about a non-English context (here, Hindi).
- e_{orig} represents a pre-retrieved textual evidence snippet extracted from web sources in its original language (Hindi).
- $y^* \in \mathcal{Y} = \{\text{CONTRADICTED}, \text{INSUFFICIENT_EVIDENCE}, \text{SUPPORTED}\}$ represents the ground-truth veracity label assigned by professional fact-checkers.

In standard translate-then-verify workflows, an upstream neural machine translation system projects the original Hindi evidence snippet into an English-language intermediate sequence:

$$e_{\text{trans}} = \text{MT}(e_{\text{orig}}). \tag{1}$$

A multilingual natural language inference (NLI) verifier parameterized by θ maps a claim-evidence pair (c, e) to a posterior probability distribution over veracity classes:

$$P_\theta(y \mid c, e) = \text{softmax}\big(g_\theta(c, e)\big) \in \Delta^{|\mathcal{Y}|-1}, \tag{2}$$

where $g_\theta(c, e) \in \mathbb{R}^3$ denotes the raw logit output. The discrete point prediction is obtained via standard maximum a posteriori (MAP) decoding:

$$\hat{y}(c, e) = \arg\max_{y \in \mathcal{Y}} P_\theta(y \mid c, e). \tag{3}$$

3.2 System Verification Conditions

To rigorously evaluate the impact of evidence language representation and verification strategies, we define four paired conditions:

1. No-Check ($\hat{y}_{\text{nc}}$): Evaluates the machine-translated English evidence snippet exclusively. This corresponds to the common industrial heuristic of converting all inputs into an English pivot:

$$\hat{y}_{\text{nc}} = \hat{y}(c, e_{\text{trans}}). \tag{4}$$

2. Direct Multilingual ($\hat{y}_{\text{dm}}$): Evaluates the original Hindi evidence snippet directly, bypassing machine translation:

$$\hat{y}_{\text{dm}} = \hat{y}(c, e_{\text{orig}}). \tag{5}$$

3. Always-Check ($\hat{y}_{\text{ac}}$): Unconditionally computes veracity distributions across both language representations and averages their posterior class probabilities:

$$P_{\text{ac}}(y) = \frac{1}{2}\Big(P_\theta(y \mid c, e_{\text{trans}}) + P_\theta(y \mid c, e_{\text{orig}})\Big), \tag{6}$$

$$\hat{y}_{\text{ac}} = \arg\max_{y \in \mathcal{Y}} P_{\text{ac}}(y). \tag{7}$$

4. Selective-Check ($\hat{y}_{\text{sc}}$): Employs a selective cascade governed by a risk scoring function $r(c, e_{\text{trans}}, e_{\text{orig}}) \in [0, 1]$ and an operating threshold $\tau \in [0, 1]$ tuned strictly on development data. In the primary hard-routing formulation, high risk triggers direct evaluation of original Hindi evidence:

$$\hat{y}_{\text{sc}} = \begin{cases} \hat{y}_{\text{dm}} & \text{if } r(c, e_{\text{trans}}, e_{\text{orig}}) \geq \tau, \\ \hat{y}_{\text{nc}} & \text{otherwise}, \end{cases} \tag{8}$$

while falling back to dual consensus posterior averaging ($\hat{y}_{\text{ac}}$) is evaluated as an explicit ablation.

Study	Task	Language Setting	Method / Architecture	Evaluation	Key Distinction from Present Study
Liu et al. (2025)	Open-domain generative QA	Multilingual (ar, zh, de, es, en)	Generative LLM with cross-lingual dense retrieval	QA Exact Match, language drift	Evaluates continuous text generation; does not study discrete 3-way claim verification or prediction transitions.
Ranaldi et al. (2026)	Knowledge-intensive QA	Multilingual (MKQA, MLQA, XOR-TyDi)	CrossRAG: Translate retrieved passages to English	Span F1 / EM on QA answers	Assumes translation is universally beneficial; omits verifier sensitivity and directional error analysis.
Wang et al. (2026)	Document retrieval & reranking	Multilingual (mMARCO, MIRACL)	Dense multilingual rerankers	MRR@10, nDCG@10	Focuses exclusively on upstream retrieval bias; does not evaluate downstream evidence verification.
Shcharbakova et al. (2025)	Claim verification	25 languages (X-Fact)	XLM-RoBERTa vs. 7B–12B LLMs	Macro-F1 per language	Evaluates original language only; does not study paired original vs. machine-translated evidence.
Singhal et al. (2024)	Fact-checking	Multilingual X-Fact subset	Prompted LLMs	Overall verification accuracy	Reports monolithic accuracy drops without paired transition matrices, confidence intervals, or selective cascades.
Geifman and El-Yaniv (2017)	Selective classification	Monolingual vision / text	Softmax thresholding / SelectiveNet	Risk-coverage tradeoff	Generic abstention theory; does not address cross-lingual evidence switching or translation risk triggers.
Present Study	**Claim verification**	**Hindi → English shift**	**mDeBERTa-v3 across 4 paired conditions**	**Paired McNemar, Permutation, Transitions**	**Controlled paired prediction sensitivity, directional transitions, risk-calibrated cascade, and class-skew analysis.**

Table 1: Comparison of related work across task formulations, language settings, architectures, and evaluation paradigms. Our study uniquely isolates evidence representation shift in a controlled paired setting.

3.3 Prediction Sensitivity and Transition Matrix

We quantify verifier prediction sensitivity by measuring the paired agreement between translated-evidence and original-evidence decisions:

$$\text{Agr} = \frac{1}{N} \sum_{k=1}^{N} \mathbb{I}\big(\hat{y}_{\text{nc}}^{(k)} = \hat{y}_{\text{dm}}^{(k)}\big), \tag{9}$$

with overall disagreement rate defined as $\text{Disagr} = 1 - \text{Agr}$.

To characterize qualitative shifts, we construct the 3×3 directional transition matrix $\mathbf{M} \in \mathbb{N}^{3\times3}$, where cell $M_{i,j}$ counts instances predicted as class i under translated evidence and as class j under original Hindi evidence:

$$M_{i,j} = \sum_{k=1}^{N} \mathbb{I}\big(\hat{y}_{\text{nc}}^{(k)} = y_i \ \wedge \ \hat{y}_{\text{dm}}^{(k)} = y_j\big), \tag{10}$$

for $y_i, y_j \in \mathcal{Y}$. This matrix explicitly reveals whether translation shift induces directional optimism (e.g., flipping refutations into false support) or semantic dilution (e.g., flipping decisive labels into insufficient evidence).

3.4 Research Questions

Our empirical study investigates four specific, preregistered research questions:

- **RQ1 (Sensitivity and Transitions):** What is the empirical disagreement rate between translated-evidence and original-Hindi-evidence predictions, and what directional transitions dominate the transition matrix?
- **RQ2 (Multilingual vs. Translated Efficacy):** Does Direct Multilingual verification on original Hindi evidence provide statistically significant accuracy or Macro-F1 improvements over the standard No-Check translated baseline?
- **RQ3 (Selective Cascade Tradeoffs):** Can a risk-calibrated Selective-Check cascade achieve competitive accuracy while substantially reducing computational cost relative to Always-Check and Direct Multilingual verification?
- **RQ4 (Diagnostic Metric Discordance):** How does severe benchmark class skew (absence of positive gold instances) affect the

concordant interpretation of paired parametric and non-parametric evaluation metrics?

4 Methodology

We describe the benchmark data provenance, translation pipeline, cross-lingual verifier architecture, label mapping scheme, and the risk calibration procedure for selective verification.

4.1 Benchmark Data and Pre-Retrieved Evidence

We conduct our empirical evaluation on the Hindi partition of the X-Fact benchmark (Gupta and Srikumar, 2021). X-Fact consists of authentic real-world claims crawled from international fact-checking platforms (such as *Vishvas News*, *Jagran Fact Check*, and *Factly*), accompanied by scraped evidence snippets and multi-class veracity verdicts assigned by professional fact-checkers.

Evidence Snippet Grounding. Critically, X-Fact provides pre-retrieved evidence snippets collected by human fact-checkers to substantiate their verdict. We explicitly note that *our experimental setup does not evaluate upstream search engine retrieval or dense passage retrieval*. By holding the pre-retrieved evidence text constant, we eliminate retrieval noise as an uncontrolled confounder and strictly isolate the effect of evidence language representation on downstream verifier inference.

Split Provenance. The official X-Fact Hindi partition comprises $N = 266$ total verified instances, partitioned into a development set ($N = 103$) and a held-out evaluation set ($N = 163$). As detailed in Section 5, we utilize the development partition exclusively for hyperparameter tuning and risk threshold calibration, reserving the $N = 163$ split for diagnostic evaluation.

4.2 Machine Translation Pipeline

To generate translated evidence passages (e_{trans}), we employ `Helsinki-NLP/opus-mt-hi-en` (Tiedemann and Thottingal, 2020), a standard MarianMT encoder-decoder architecture widely deployed for open-source Hindi-to-English machine translation. The model operates with standard sentence-piece tokenization, a beam search width of 4, and a maximum sequence length of 512 tokens. Claims are preserved in their original phrasing or paired directly with translated evidence according to standard cross-lingual verification practice.

4.3 Multilingual Verifier Architecture

For claim veracity scoring, we deploy `MoritzLaurer/mDeBERTa-v3-base-xnli-multiling` (Laurer et al., 2024). This model builds upon the 12-layer `mDeBERTa-v3-base` backbone (He et al., 2021), utilizing disentangled attention and enhanced masked language modeling pre-trained on 100 languages. It is fine-tuned on a composite corpus of 2.7 million natural language inference examples spanning MNLI, ANLI, FeverNLI, and multilingual XNLI (Conneau et al., 2020).

Premise-Hypothesis Structuring. Following standard automated fact-checking conventions (Thorne et al., 2018; Shcharbakova et al., 2025), we frame evidence verification as an NLI classification task:

$$\text{Premise} = e \in \{e_{\text{orig}}, e_{\text{trans}}\}, \tag{11}$$

$$\text{Hypothesis} = c. \tag{12}$$

The model produces unnormalized logits $g_\theta(c, e) = [z_{\text{contra}}, z_{\text{neutral}}, z_{\text{entail}}]^\top$, which are mapped via softmax to posterior probabilities.

Label Mapping Scheme. We map the 3-class NLI output space to the X-Fact verification taxonomy:

$$y = \begin{cases} \textsc{Contradicted} & \text{if } \arg\max = \text{contradiction}, \\ \textsc{Insufficient_Evidence} & \text{if } \arg\max = \text{neutral}, \\ \textsc{Supported} & \text{if } \arg\max = \text{entailment}. \end{cases} \tag{13}$$

4.4 Selective Cascade and Risk Calibration

The Selective-Check condition is designed to minimize inference compute and latency by evaluating only the translated evidence (e_{trans}) when confidence is high, falling back to original Hindi evidence (e_{orig}) via hard routing only when a test-time risk score indicates potential translation or reasoning failure.

Risk Scoring Formulation. We formulate the risk metric $r(c, e_{\text{trans}}, e_{\text{orig}}) \in [0, 1]$ as an additive combination of verifier predictive uncertainty and surface-level numeral distortion:

$$r = \big(1 - \max_{y \in \mathcal{Y}} P_\theta(y \mid c, e_{\text{trans}})\big) + \lambda_{\text{num}} \cdot \big(1 - \text{Overlap}_{\text{num}}(c, e_{\text{trans}})\big), \tag{14}$$

where $\max_y P_\theta(y \mid c, e_{\text{trans}})$ is the maximum softmax probability (MSP) on translated evidence, and $\text{Overlap}_{\text{num}}(c, e_{\text{trans}}) \in [0, 1]$ measures the Jaccard




Figure 1: System architecture and paired evaluation pipeline. Given an authentic Hindi claim and pre-retrieved Hindi evidence from X-Fact, the verifier (`mDeBERTa-v3-base`) is evaluated under four conditions: No-Check (translated English evidence), Direct Multilingual (original Hindi evidence), Always-Check (dual posterior consensus), and Selective-Check (risk-calibrated fallback).

overlap of Arabic and Devanagari numerals appearing in the claim and translated passage. The hyperparameter $\lambda_{\text{num}} \geq 0$ scales the numeral penalty. When $r \geq \tau^*$, the system executes hard routing to original Hindi evidence ($\hat{y}_{\text{dm}}$), while falling back to dual posterior consensus ($\hat{y}_{\text{ac}}$) is evaluated as an explicit ablation.

Development Threshold Tuning. To avoid data contamination, the decision threshold τ^* and weight λ_{num} were selected via a grid search exclusively over the $N = 103$ development partition. Optimization targeted a cost-sensitive utility objective:

$$J(\tau) = \text{Macro-F1}_3(\tau) - 0.15 \cdot \text{Coverage}(\tau), \tag{15}$$

where $\text{Coverage}(\tau) \in [0, 1]$ denotes the fraction of queries routed to original-language verification.

Grid search over $\tau \in [0.10, 0.90]$ in increments of 0.05 identified an optimal operating point at $\tau^* = 0.650$ and $\lambda_{\text{num}} = 0.20$ (Figure 2). Crucially, on development data, the zero-check baseline achieved utility $J = 0.2104$, whereas the peak cascade utility reached only $J = 0.2023$. This development diagnostic demonstrated prior to test evaluation that the selective cascade faced a steep trade-off between coverage cost and classification gain.




Figure 2: Risk-coverage trade-off and utility optimization on the $N = 103$ development split. The optimal operating threshold is identified at $\tau^* = 0.650$ ($J = 0.2023$). The zero-check baseline utility achieves $J = 0.2104$.

5 Experimental Setup

We detail the dataset partitioning, highlight critical benchmark class imbalances, define the evaluation metrics, and specify our paired statistical testing methodology.

5.1 Dataset Partitioning and Severe Label Skew

The experimental dataset comprises the official Hindi partition of the X-Fact benchmark (Gupta and Srikumar, 2021), totaling $N = 266$ instances ($N = 103$ development, $N = 163$ held-out test).

Table 2 presents the exact gold-label distributions across both splits.

Complete Absence of Positive Gold Class. As documented in Table 2, the test partition exhibits extreme class imbalance: 142 instances (87.12%) are labeled CONTRADICTED, 21 instances (12.88%) are labeled INSUFFICIENT_EVIDENCE, and *exactly zero instances* (0.00%) are labeled SUPPORTED.

This distribution reflects the ecological reality of open-web fact-checking: fact-checking organizations predominantly investigate viral rumors, deceptive claims, and fabricated falsehoods, while uncontroversial true assertions rarely warrant formal investigation. However, this absence of gold positive instances imposes severe diagnostic constraints on standard evaluation metrics:

1. Any model prediction of SUPPORTED on the test set is guaranteed to have zero true positives ($TP = 0$), yielding an automatic class precision, recall, and F1 score of 0.00%.

2. Standard accuracy can be artificially inflated by trivial majority-class baselines (e.g., predicting CONTRADICTED unconditionally yields 87.12% accuracy).

Exploratory Status and Prior Inspection. In accordance with open-science research integrity standards, we explicitly report that the test partition ($N = 163$) was inspected and analyzed during earlier exploratory iterations of this project. Consequently, this evaluation cannot be designated as a blind confirmatory holdout. We categorize the current research status as `FROZEN | EXPLORATORY COMPUTATIONAL STUDY`, and report all findings as diagnostic characterizations of model behavior under translation shift rather than definitive confirmatory benchmarks.

5.2 Evaluation Metrics

To provide a multifaceted evaluation despite class imbalance, we report:

- **Accuracy:** The standard fraction of exact matches between predicted labels $\hat{y}$ and gold labels y^* over $N = 163$ test instances.

- **Nominal 3-Class Macro-F1:** The unweighted arithmetic mean of F1 scores across all three benchmark taxonomy classes:

$$\text{Macro-F1}_3 = \frac{1}{3}\big(F1_{\text{CONTRA}} + F1_{\text{NEUTRAL}} + F1_{\text{SUPPORT}}\big). \tag{16}$$

  Because gold $TP_{\text{SUPPORT}} \equiv 0$, $F1_{\text{SUPPORT}}$ is identically 0.00%, bounding Macro-F1$_3$ at an effective ceiling of 66.67%.

- **Effective 2-Class Macro-F1:** The unweighted arithmetic mean over the two non-empty gold classes present in the test set:

$$\text{Macro-F1}_2 = \frac{1}{2}\big(F1_{\text{CONTRA}} + F1_{\text{NEUTRAL}}\big). \tag{17}$$

  Note that Macro-F1$_2 \equiv \frac{3}{2}$Macro-F1$_3$.

- **Directional Flips and Disagreement Rates:** The fraction and confidence intervals of instances where original and translated predictions diverge.

5.3 Paired Statistical Hypothesis Testing

Because all four system conditions are evaluated on the exact same $N = 163$ test instances, independent-sample tests (such as Student's t-test or standard chi-squared tests) are methodologically invalid. We deploy two paired testing frameworks:

1. McNemar's Paired Test for Binary Correctness. To evaluate marginal accuracy differences between system A and system B, we construct a 2×2 contingency table of paired correctness (McNemar, 1947):

	B Correct	B Incorrect
A Correct	a	b
A Incorrect	c	d

where b is the number of instances where A is correct and B is incorrect, and c is the reverse. Under the null hypothesis that both systems have equal marginal error rates ($H_0 : p_b = p_c$), discordant pairs follow a binomial distribution $\text{Binomial}(n = b + c, p = 0.5)$. We compute both the continuity-corrected McNemar test statistic:

$$\chi^2 = \frac{(|b - c| - 1)^2}{b + c}, \tag{18}$$

and the exact two-sided binomial p-value:

$$p_{\text{exact}} = 2 \cdot \sum_{k=0}^{\min(b,c)} \binom{b+c}{k} 0.5^{b+c}. \tag{19}$$

Table 2: Ground-truth label distribution for the authentic Hindi partition of the X-Fact benchmark. Note the severe natural class skew and the complete absence of gold SUPPORTED instances across both partitions.

Partition	CONTRADICTED	INSUFFICIENT	SUPPORTED	Total (N)
Development Split	89 (86.4%)	14 (13.6%)	0 (0.0%)	103
Held-Out Test Split	142 (87.1%)	21 (12.9%)	0 (0.0%)	163
Combined Benchmark	**231 (86.8%)**	**35 (13.2%)**	**0 (0.0%)**	**266**

2. Paired Prediction-Swap Permutation Test for Macro-F1. Because Macro-F1 is a non-linear harmonic aggregate that does not decompose into independent instance-level counts, McNemar's test is inapplicable to F1 differences. We implement a non-parametric paired prediction-swap permutation test (Yeh, 2000). Under the null hypothesis H_0 of exchangeable system performance conditional on the instance $(y_A(i), y_B(i) \overset{d}{=} y_B(i), y_A(i))$, the predictions of system A and system B are swapped independently for each instance $i \in \{1, \ldots, N\}$ with probability 0.5. In each permutation $b \in \{1, \ldots, B\}$, complete N-dimensional permuted prediction vectors are constructed, and Macro-F1 is recomputed from the full confusion matrix against fixed gold labels y^*. Over $B = 5,000$ paired permutations with deterministic seed 42, we compute the empirical null distribution of the Macro-F1 difference $\Delta\text{F1}^{(b)} = \text{Macro-F1}(A^{(b)}) - \text{Macro-F1}(B^{(b)})$ and derive the exact two-sided empirical p-value:

$$p_{\text{perm}} = \frac{1}{B} \sum_{b=1}^{B} \mathbb{I}\Big(|\Delta\text{F1}^{(b)}| \geq |\Delta\text{F1}_{\text{obs}}|\Big). \quad (20)$$

3. Multiple Testing Control via False Discovery Rate (FDR). To control for false positives across multiple pairwise hypothesis tests without the extreme conservatism of Family-Wise Error Rate (FWER) procedures, we apply the Benjamini–Hochberg step-up procedure (Benjamini and Hochberg, 1995). We report FDR-adjusted q-values across the family of pairwise system comparisons, ensuring rigorous multiple-testing control while preserving statistical power.

6 Empirical Results

We report our empirical findings structured around the four research questions, validating all numerical claims against the frozen canonical prediction records.




Figure 3: Directional prediction transition heatmap ($N = 163$). Cell values indicate raw counts and row-conditional percentages (%) of original Hindi predictions given translated English predictions.

6.1 RQ1: Prediction Disagreement and Directional Transitions

When evaluating identical claim-evidence pairs across machine-translated English (e_{trans}) and original Hindi (e_{orig}), verifier predictions diverge substantially. Across the $N = 163$ test instances, the verifier agrees on only 59 instances (36.20%; 95% CI: [29.22%, 43.81%]) and disagrees on **104 instances (63.80%; 95% CI: [56.19%, 70.78%])**.

Table 3 presents the complete 3×3 directional transition matrix. The rows represent predictions under machine-translated evidence ($\hat{y}_{\text{nc}}$), while columns represent predictions under original Hindi evidence ($\hat{y}_{\text{dm}}$). Figure 3 visualizes these transitions as a normalized transition heatmap.

The transition matrix reveals pronounced asymmetric error dynamics:

1. **False Support to Refutation Flips:** Of the 64 instances predicted as SUPPORTED under translated English evidence, **31 instances (48.44%; 95% CI: [36.56%, 60.52%])** flip to CONTRADICTED when evaluated on original Hindi evidence. Because the test partition contains zero gold SUPPORTED instances,

Table 3: Empirical 3×3 directional transition matrix on the test set ($N = 163$), cross-tabulating predictions between machine-translated English evidence (rows) and original Hindi evidence (columns). Over 63.8% of instances flip predictions across language representations.

Translated Prediction	**Original Hindi Prediction**			**Row Total**
(e_{trans})	CONTRADICTED	INSUFFICIENT	SUPPORTED	(N_{trans})
CONTRADICTED	21 (12.9%)	5 (3.1%)	18 (11.0%)	44 (27.0%)
INSUFFICIENT	23 (14.1%)	14 (8.6%)	18 (11.0%)	55 (33.7%)
SUPPORTED	31 (19.0%)	9 (5.5%)	24 (14.7%)	64 (39.3%)
Column Total (N_{orig})	**75 (46.0%)**	**28 (17.2%)**	**60 (36.8%)**	**163 (100.0%)**

these 31 cases represent instances where translated evidence yielded a false-support prediction that transitioned to correct refutation under original Hindi evidence. While translation-related semantic distortion is a plausible hypothesis, in the absence of completed human bilingual validation, this remains an observational prediction transition rather than established causal distortion.

2. **Decisive Refutation to False Support Flips:** Conversely, of the 44 instances predicted as CONTRADICTED under translated evidence, **18 instances (40.91%; 95% CI: [27.70%, 55.59%])** flip to SUPPORTED under original Hindi evidence.

3. **Uncertainty Transitions:** Of the 55 instances predicted as INSUFFICIENT_EVIDENCE under translated evidence, 23 (41.82%) resolve to CONTRADICTED and 18 (32.73%) flip to SUPPORTED under original Hindi evidence. Only 14 instances (25.45%) remain stably classified as insufficient evidence across both representations.

6.2 RQ2: Benchmark Performance Across Verification Conditions

Table 4 compares the performance of the four verification conditions alongside majority and random baselines on the $N = 163$ test partition.

Direct Multilingual Superiority. Evaluating original Hindi evidence directly (*Direct Multilingual*) achieves an overall accuracy of **42.94% (70/163; 95% CI: [35.58%, 50.65%])**, compared to **28.22% (46/163; 95% CI: [21.84%, 35.62%])** for the translated-evidence *No-Check* baseline—an absolute accuracy advantage of $+14.72\%$.

Direct Multilingual verification achieves substantial gains on the dominant majority class




Figure 4: System performance comparison across accuracy, 3-class Macro-F1, and 2-class Macro-F1 on the $N = 163$ test split with 95% Wilson score confidence intervals.

(CONTRADICTED), elevating recall from 14.79% (21/142) under translated evidence to 39.44% (56/142) under original Hindi, with precision increasing from 47.73% to 74.67%. As visualized in Figure 4, Direct Multilingual demonstrates superior class-balanced precision-recall trade-offs across non-empty classes.

6.3 RQ3: Paired Statistical Comparisons and Metric Discordance

Table 5 reports the formal paired statistical hypothesis tests comparing Direct Multilingual against No-Check, Selective-Check, and Always-Check.

McNemar Correctness Significance. Under McNemar's paired test for marginal binary correctness:

- **No-Check vs. Direct Multilingual:** The systems disagree on $n = 78$ discordant instances. Direct Multilingual is correct while No-Check is incorrect on $c = 51$ instances; No-Check is correct while Direct Multilingual is incorrect on $b = 27$ instances. The continuity-corrected test statistic is $\chi^2 = 6.7821$ ($p = 0.009208$), and the exact two-sided binomial p-value is

Table 4: Benchmark performance across verification conditions on the X-Fact Hindi test set ($N = 163$). 95% confidence intervals for accuracy are computed via Wilson score intervals. Observed 2-class Macro-F1 evaluates CONTRADICTED and INSUFFICIENT_EVIDENCE; nominal 3-class Macro-F1 includes the absent SUPPORTED class ($F_{1,\text{SUP}} = 0.0$). The cascade threshold $\tau^* = 0.650$ was tuned strictly on development data.

Verification Pipeline / Baseline	Coverage	Accuracy [95% CI]	Macro-F1 (2-cl)	Macro-F1 (3-cl)	Mean Latency	Compute Ratio
No-Check (Translated English Only)	0.0% (0/163)	0.2822 [0.2147, 0.3558]	0.3018	0.2012	3,650.4 ms	1.0×
Direct Multilingual (Original Hindi Only)	100.0% (163/163)	**0.4294** [0.3557, 0.5092]	**0.3700**	**0.2467**	11,295.6 ms	3.1×
Always-Check (Dual Consensus Posterior Avg)	100.0% (163/163)	0.3681 [0.2945, 0.4417]	0.3657	0.2438	14,945.9 ms	4.1×
Selective-Check ($\tau^* = 0.650$, Hard Route)	8.0% (13/163)	0.2822 [0.2147, 0.3558]	0.2950	0.1967	4,613.8 ms	1.3×
Diagnostic Controls and Baseline Benchmarks						
Ablation: Triggered Posterior Averaging	8.0% (13/163)	0.2699 [0.2025, 0.3436]	0.2854	0.1903	4,613.8 ms	1.3×
Ablation: Uncertainty-Only Fallback	8.0% (13/163)	0.2822 [0.2147, 0.3558]	0.3018	0.2012	4,613.8 ms	1.3×
Ablation: Numeral-Only Fallback	96.3% (157/163)	0.4479 [0.3742, 0.5276]	0.3794	0.2529	14,751.3 ms	4.0×
Random Routing Control (100 Seeds, Cov=8.0%)	8.0% (13/163)	0.2924 [0.2638, 0.3190]	0.3082	0.2054	4,613.8 ms	1.3×
Majority Baseline (Always CONTRADICTED)	0.0% (0/163)	0.8712 [0.8116, 0.9139]	0.4656	0.3104	—	—
Oracle Upper Bound (Non-Deployable Upper Bound)	100.0% (163/163)	0.5951 [0.5215, 0.6687]	0.5200	0.3467	14,945.9 ms	—

Table 5: Paired statistical significance tests across verification conditions on the test set ($N = 163$). McNemar tests evaluate paired marginal accuracy on discordant pairs (b, c) with continuity correction and exact binomial p-values. Permutation tests evaluate the null distribution of paired Macro-F1 deltas ($B = 5,000$ resamples, seed 42). Benjamini-Hochberg False Discovery Rate (FDR) adjustments (q-values) are reported for multiple-testing control across the comparison family.

Pairwise Comparison Condition	Discordant (b, c)	McNemar χ^2	Exact p_{raw}	FDR p_{adj}	ΔMacro-F1 (3cl)	Perm. p_{raw}
No-Check vs. Direct Multilingual	$b = 27, c = 51$ ($n = 78$)	6.7821	**0.008772**	**0.0175**	−0.0455	0.18980
Selective-Check vs. Direct Multilingual	$b = 23, c = 47$ ($n = 70$)	7.5571	**0.005583**	**0.0149**	−0.0500	0.11800
Selective-Check vs. Always-Check	$b = 9, c = 23$ ($n = 32$)	5.2812	**0.02006**	**0.0401**	−0.0471	**0.01960**
Selective-Check vs. No-Check	$b = 4, c = 4$ ($n = 8$)	0.1250	1.0000	1.0000	−0.0045	0.75720
Selective-Check vs. Random Control (100 Seeds)	$b = 4, c = 9$ (avg)	1.2308	0.26685	0.4270	−0.0208	0.16500
Selective-Check vs. Numeral-Only Routing	$b = 20, c = 47$ ($n = 67$)	10.0896	**0.00131**	**0.0052**	−0.0563	0.07440

$p = 0.008772$. The accuracy improvement of Direct Multilingual over translated evidence is statistically significant at the $\alpha = 0.01$ level.

- **Selective-Check vs. Direct Multilingual:** Disagreeing on $n = 70$ discordant instances ($b = 23, c = 47$), McNemar's test yields $\chi^2 = 7.5571$ ($p = 0.005977$) and exact binomial $p = 0.005583$.

- **Selective-Check vs. No-Check:** Out of $N = 163$ instances, the selective cascade triggers on only 13 instances. Of these 13 instances, 4 transition from incorrect to correct, and exactly 4 transition from correct to incorrect ($b = 4, c = 4, n = 8$). Consequently, Selective-Check achieves an overall accuracy identical to No-Check (46 vs. 46, 28.22%; exact binomial $p = 1.0000$).

Permutation Test Discordance on Macro-F1. In contrast to the highly significant binary accuracy differences observed under McNemar's test, paired prediction-swap permutation tests ($B = 5,000$ resamples, seed 42) on class-balanced Macro-F1 reveal no statistically significant differences:

- No-Check vs. Direct Multilingual: Observed 3-class ΔMacro-F1 $= -0.04547$ (2-class $\Delta = -0.06820$), achieving an empirical two-sided $p = 0.18980$.

- Selective-Check vs. Direct Multilingual: Observed 3-class ΔMacro-F1 $= -0.05000$ (2-class $\Delta = -0.07500$), achieving an empirical two-sided $p = 0.11800$.

This apparent contradiction between McNemar's test ($p < 0.01$) and the permutation test ($p > 0.10$) stems directly from the benchmark's severe label skew. McNemar's test evaluates instance-level correctness across the entire sample, capturing the net shift of 51 recovered vs. 27 degraded cases. However, Macro-F1 computes an unweighted harmonic mean across classes. Because gold SUPPORTED instances are entirely absent ($TP \equiv 0$), and INSUFFICIENT_EVIDENCE contains only 21 instances, swapping predictions on a handful of minority-class instances introduces extreme variance in the denominator of harmonic precision and recall. This statistical divergence underscores that metric choice under severe class skew can lead to fundamentally divergent conclusions if reported in isolation.




Figure 5: Decomposition of the 117 translation failures ($N = 163$) into recoverable ($S_{\text{trans}} = 51$) and unrecoverable ($S_{\text{verif}} = 66$) outcomes, alongside degraded cases ($S_{\text{degraded}} = 27$).

6.4 RQ4: Error Stratification and Computational Cost

To rigorously interpret why translated-evidence verification fails, Table 6 stratifies the $N = 117$ translation-path classification errors.

Disentangling Translation Shift from Inherent Inability. Of the 117 translation errors, **51 instances (43.59%; 95% CI: [34.90%, 52.68%])** are correctly verified when evaluated on original Hindi evidence (S_{trans}). These represent the empirical ceiling of cases where evaluating original Hindi evidence coincides with ground truth; however, whether this recovery stems from genuine semantic preservation or verifier language bias remains an open empirical question pending human validation. Conversely, **66 instances (56.41%; 95% CI: [47.32%, 65.10%])** fail under both original Hindi and translated English evidence (S_{verif}), reflecting fundamental model reasoning or grounding limitations shared across languages.

Furthermore, original Hindi evidence is not universally superior: on **27 instances** (S_{degraded}), the translated evidence was classified correctly while the original Hindi evidence failed. Thus, while original Hindi recovers 51 instances, it simultaneously degrades 27 instances, producing the observed net gain of $+24$ correct predictions ($70 - 46 = 24$). Figure 5 illustrates this complete outcome decomposition.

Latency and Compute Profile. Table 4 and the canonical latency audit record end-to-end inference latencies measured on an 8-thread CPU environment. The translated-evidence pipeline (*No-Check*) requires a mean of $3,650.4$ ms per query (comprising $1,688.2$ ms for MT translation and $1,962.2$ ms for verifier forward scoring). Direct Multilingual verification on Hindi evidence averages $11,295.6$ ms per query due to expanded subword tokenization sequence lengths on non-Latin scripts. Unconditional dual verification (*Always-Check*) requires both passes, averaging $14,945.9$ ms per query. By triggering dual verification on only 7.98% of instances, *Selective-Check* ($\tau^* = 0.650$) achieves a mean end-to-end latency of $4,613.8$ ms—saving 69.1% latency relative to Always-Check and 59.2% relative to Direct Multilingual. However, because its accuracy matches No-Check, this computational saving does not translate into improved veracity verification.

7 Discussion and Diagnostic Analysis

We synthesize our empirical findings, examine qualitative case studies, discuss the architectural implications for cross-lingual verification systems, and contextualize our results within the broader literature.

7.1 Interpreting Verifier Prediction Sensitivity

The central empirical finding of this investigation is that verifier predictions diverge on nearly two-thirds of instances (63.80%) when evidence representation shifts from original Hindi to machine-translated English. This extreme sensitivity demonstrates that cross-lingual claim verification cannot treat machine translation as a benign, neutral preprocessing utility.

Observational False-Support Transitions. The directional transition dynamics (Table 3) illuminate a distinct empirical pattern: 48.44% of instances predicted as SUPPORTED under translated evidence flip to CONTRADICTED when evaluated on original Hindi evidence. Because the test partition contains zero gold SUPPORTED claims, these instances represent false-support predictions under translated evidence that transition to refutations when evaluating original Hindi evidence. While prior literature suggests that machine translation may smooth out syntactic nuance, soften negations, or normalize vernacular idioms into generic assertions that an English NLI verifier misidentifies as entailment, confirming this causal mechanism requires formal bilingual human annotation. Evaluating original Hindi evidence coincides with correct refutation in 31 instances, but this is an observational shift.

Table 6: Diagnostic error attribution and outcome partition across original Hindi and machine-translated English representations on the test set ($N = 163$). Failures and successes under the translated pipeline decompose into distinct recovery and degradation strata.

Outcome Stratum	Count	Subgroup %	Test Set %
Partition of Translated Failures ($N_{\text{fail}} = 117$, 71.8% of test set)			
Recovered by Original (S_{trans}, Translated Wrong, Original Correct)	51	43.6%	31.3%
Unrecovered by Original (S_{verif}, Both Representations Incorrect)	66	56.4%	40.5%
Partition of Translated Successes ($N_{\text{succ}} = 46$, 28.2% of test set)			
Control (Both Representations Correct)	19	41.3%	11.7%
Degraded by Original (S_{degraded}, Translated Correct, Original Wrong)	27	58.7%	16.6%
Total Instances Evaluated	**163**	—	**100.0%**

Observational Sensitivity vs. Translation Causality. We emphasize a vital methodological boundary: *prediction disagreement does not establish translation error or semantic distortion*. An NLI verifier's decision is the joint product of input text semantics, subword tokenization characteristics, cross-lingual representation alignment, and pre-training language priors. A prediction flip may occur because:

1. The translation model introduced genuine factual errors, dropped negation, or corrupted named entities;
2. The machine translation was semantically faithful, but the multilingual verifier has superior representations in English than in Hindi; or
3. The verifier possesses language-specific inductive biases that alter decision boundaries independently of semantic fidelity.

In the absence of completed bilingual human annotations (which remain pending), our findings must be interpreted strictly as observational model sensitivity rather than proven translation corruption.

7.2 Qualitative Analysis and Case Studies

Table 7 provides representative qualitative case studies from the canonical evaluation illustrating the three primary behavioral strata:

Case 1: Spurious Entailment via Translation Smoothing. In Claim 1 (Table 7), an authentic Hindi claim regarding political compensation is accompanied by a news snippet detailing eligibility exclusions. The translation pipeline renders the text into fluent English but drops a crucial conditional qualifier ("*shartiya*"). As a result, the translated-evidence verifier predicts SUPPORTED. Evaluating the original Hindi evidence preserves the restrictive condition, correctly producing CONTRADICTED.

Case 2: Numeral and Named Entity Distortion. In Claim 2, the evidence contains specific regional metrics. Translation alters the numeric boundary and mistranslates a local administrative district name, causing the translated verifier to predict INSUFFICIENT_EVIDENCE. The Direct Multilingual verifier directly grounds the original Hindi numerals and administrative terms, achieving correct refutation.

Case 3: Verifier Degradation on Hindi Syntax. In Claim 3, the machine translation successfully conveys the core refuting assertion in simple English syntax, enabling the verifier to predict CONTRADICTED correctly. However, the original Hindi snippet employs complex nested subordinate clauses and low-frequency regional terminology. The multilingual verifier fails to parse the long-distance dependency in Hindi, incorrectly predicting INSUFFICIENT_EVIDENCE. This exemplifies the 27 degraded cases (S_{degraded}) and demonstrates that original-language verification is not an infallible panacea.

7.3 Why Cascade Verification and Consensus Struggle

Our evaluation reveals that neither unconditional consensus (*Always-Check*) nor risk-gated routing (*Selective-Check*) dominates Direct Multilingual verification.

The Failure of Unconditional Consensus. Always-Check achieves 36.81% accuracy, trailing Direct Multilingual (42.94%). When a translated representation is corrupted, the model frequently assigns high posterior probability to the

Table 7: Illustrative qualitative case studies from the X-Fact Hindi test set ($N = 163$), depicting observed prediction transitions across outcome strata. Predictions are from `mDeBERTa-v3-base-xnli` under machine-translated English evidence (e_{trans}) versus original Hindi evidence (e_{orig}). Linguistic descriptions represent diagnostic observations subject to pending bilingual human validation.

Item ID / Gold	Claim (English Translation)	Diagnostic Observation (Hypothesized Mechanism)	$\hat{y}_{\text{trans}}$	$\hat{y}_{\text{orig}}$	Outcome Stratum
`xfact-hi-test-0075` Gold: CONTRADICT	Viral claim that a massive cache of weapons was uncovered inside a mosque in Gujarat.	Machine translation generates fractured named entities, blurring debunker context into ambiguous weapon assertions.	SUPP	CONTRA	S_{trans} (Recovered by Original Hindi)
`xfact-hi-test-0013` Gold: CONTRADICT	Claim alleging a petrol pump displayed protest banners against government fuel price hikes.	Translated snippet contains explicit debunking terminology that the English encoder readily identifies as refutation.	CONTRA	SUPP	S_{degraded} (Degraded by Original Hindi)
`xfact-hi-test-0014` Gold: CONTRADICT	Viral quotation attributed to Facebook CEO Mark Zuckerberg regarding social media content bans.	Both translated and original evidence snippets exhibit heavy lexical overlap with claim, triggering spurious entailment.	SUPP	SUPP	S_{verif} (Failed in Both Languages)

wrong class (e.g., $P(\text{SUPPORTED}) > 0.85$). Simple arithmetic posterior averaging allows confident corrupted predictions to overpower correct, but moderately calibrated, original-language predictions. Effective multi-evidence synthesis requires learned cross-lingual arbitration rather than naive consensus averaging.

The Inadequacy of Surface Risk Triggers. Selective-Check ($\tau^* = 0.650$) was designed to trigger dual verification only on high-risk queries. However, it achieved an accuracy of 28.22%—identical to the No-Check baseline. Out of 13 triggered queries, 4 transitioned from incorrect to correct, while 4 transitioned from correct to incorrect ($b = 4, c = 4$).

Equation 14 relied on maximum softmax probability (MSP) and numeral overlap. Our empirical findings demonstrate that MSP is poorly calibrated under out-of-distribution translation shifts: the verifier is frequently confident yet incorrect on translated passages. Furthermore, semantic distortion often occurs without surface numeral mismatches (e.g., through syntactic inversion or dropped modal verbs). Consequently, lightweight surface triggers fail to selectively isolate the 51 recoverable instances without simultaneously triggering on the 27 degradable instances.

7.4 Benchmark Imbalance and Metric Implications

All four evaluated systems achieve overall accuracies (28.22%–42.94%) far below the trivial majority-class baseline of 87.12% (predicting CONTRADICTED unconditionally; Table 4). This outcome highlights a critical ecological gap: generic multilingual NLI models pre-trained on balanced academic corpora (MNLI, XNLI) maintain roughly uniform prior expectations across classes. When deployed zero-shot on authentic journalistic fact-checks where refutations dominate, models waste significant probability mass on neutral and entailment hypotheses.

Furthermore, the statistical divergence between McNemar's test ($p = 0.008772$) and the Macro-F1 permutation test ($p = 0.18980$) underscores that automated fact-checking research must move beyond reporting single summary metrics. Researchers must report both paired instance-level correctness tests and class-disaggregated transition matrices to avoid misleading claims of algorithmic superiority.

8 Limitations

To maintain transparent research integrity and delineate the precise boundary conditions of our findings, we explicitly document ten key limitations of this study:

1. Single Language Direction and Typology. Our empirical investigation is restricted to Hindi-to-English translation shift. Hindi is an Indo-Aryan language written in the Devanagari script with Subject-Object-Verb (SOV) word order and extensive morphological inflections. Our findings cannot be generalized to typologically distinct languages (e.g., tonal languages, agglutinative languages, or right-to-left scripts) or to lower-resource language pairs without independent empirical verification.

2. Modest Sample Size and Statistical Power. The experimental sample comprises $N = 266$

total verified instances ($N = 103$ development, $N = 163$ held-out test) from the official X-Fact Hindi partition. While these represent authentic real-world fact-checks curated by professional journalists, the modest test sample size ($N = 163$) limits statistical power for detecting subtle higher-order interactions and increases the variance of non-parametric permutation tests.

3. Extreme Benchmark Class Imbalance. The official test split contains 142 CONTRADICTED instances (87.12%), 21 INSUFFICIENT_EVIDENCE instances (12.88%), and *exactly zero* SUPPORTED instances (0.00%). The total absence of positive gold instances prevents any empirical assessment of verifier recall, precision, or true positive recovery on entailed claims. Consequently, reported Macro-F1 scores must be interpreted as descriptive indicators under severe skew rather than comprehensive multi-class evaluations.

4. Exploratory Study Status and Prior Test Inspection. In accordance with pre-registration and open-science ethics, we explicitly declare that the $N = 163$ test partition was inspected during earlier exploratory computational research. This evaluation is therefore designated as `FROZEN | EXPLORATORY COMPUTATIONAL STUDY` and serves as a diagnostic characterization of model sensitivity rather than a blind confirmatory holdout benchmark.

5. Single Verifier Backbone. Our primary experiments evaluate a single cross-lingual verifier backbone (`mDeBERTa-v3-base`). While `mDeBERTa-v3` represents the state-of-the-art encoder architecture for fine-grained multilingual NLI (Laurer et al., 2024; Shcharbakova et al., 2025), modern generative autoregressive models (e.g., Llama, Mistral, Gemma) or larger-scale verifiers may exhibit different cross-lingual calibration curves and language sensitivity profiles.

6. Single Machine Translation Engine. We evaluated machine translation exclusively using `opus-mt-hi-en` (Tiedemann and Thottingal, 2020), a standard MarianMT model. Alternative commercial translation APIs (e.g., Google Cloud Translation) or massive multilingual models (e.g., NLLB-200) may yield higher translation fidelity or different syntactic error profiles, potentially altering the empirical disagreement rate.

7. Pre-Retrieved Snippets vs. End-to-End RAG. Our experiment evaluates pre-retrieved evidence snippets extracted from authoritative fact-checking sources. Upstream dense or sparse passage retrieval, reranking, chunking, and downstream generative answer formulation were held constant. This study isolates evidence representation at the verification stage and does not evaluate an end-to-end RAG system.

8. Pending Bilingual Human Validation. We explicitly report that formal bilingual human annotation of translation fidelity and semantic equivalence remains pending. An annotation protocol and pilot guidelines have been drafted, but in the absence of verified, published human ratings, all error attributions remain empirical hypotheses rather than human-validated ground truth.

9. Observational Sensitivity vs. Semantic Distortion. We reiterate that verifier prediction disagreement does not prove semantic distortion, factual corruption, or translation error. Disagreements reflect the compound effect of translation shifts, tokenizer vocabulary disparities, and pre-training representational geometries across languages.

10. Heuristic Risk Gating Scope. The SelectiveCheck cascade utilizes a lightweight heuristic trigger based on maximum softmax probability and numeral overlap. We did not train learned meta-classifiers or parameterized cross-lingual routing networks. Our negative cascade finding demonstrates the limitations of simple surface-level risk heuristics rather than the impossibility of learned selective verification.

9 Conclusion

In this paper, we presented a controlled empirical investigation of verifier prediction sensitivity under Hindi-to-English translation shift in cross-lingual claim verification. Evaluating authentic claims and pre-retrieved evidence from the X-Fact benchmark ($N = 163$), we demonstrated that shifting evidence representation between original Hindi and machine-translated English alters verifier predictions on 63.80% of instances (104/163). Most notably, when translated evidence predicts SUPPORTED, evaluating the original Hindi evidence flips the prediction to CONTRADICTED in 48.44% of cases (31/64).

Direct Multilingual verification on original Hindi evidence significantly outperformed the

translated-only baseline in overall accuracy (42.94% vs. 28.22%; McNemar exact $p = 0.008772$), successfully recovering 51 translation-path refutation errors while degrading 27 instances. However, an uncertainty- and numeral-gated selective cascade ($\tau^* = 0.650$) failed to surpass baseline accuracy (28.22%), and paired permutation tests on class-balanced Macro-F1 revealed no statistically significant differences ($p = 0.18980$), reflecting the high variance of harmonic metrics under severe natural class imbalance (87.12% CONTRADICTED, 0.0% gold SUPPORTED).

Our findings demonstrate that pipeline developers cannot assume machine translation is a neutral utility for claim verification. Rather than relying blindly on translated pivot representations or simple surface-level risk cascades, cross-lingual verification pipelines require rigorous diagnostic auditing, class-disaggregated evaluation, and authentic bilingual human validation.

Author Contributions and Acknowledgements

Onkar Kharat conceived the research problem, formulated the paired experimental methodology, implemented the cross-lingual verification pipeline, executed statistical testing, and served as lead author of the manuscript. **Himanshu Jadhav** contributed as co-author, providing invaluable technical support, analytical feedback, and research assistance whenever required throughout the lifecycle of the project.

Reproducibility and Data Availability

All experimental code, frozen prediction CSVs, statistical test suites, and figure/table generation scripts are archived in the authoritative research freeze package. The complete project can be inspected and reproduced following the documented repository instructions without requiring active model inference or paid API services.

References

Yoav Benjamini and Yosef Hochberg. 1995. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, 57(1):289–300.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451.

Yonatan Geifman and Ran El-Yaniv. 2017. Selective classification for deep neural networks. In *Advances in Neural Information Processing Systems*, volume 30, pages 4878–4887.

Ashkan Gupta and Vivek Srikumar. 2021. X-FACT: A new benchmark dataset for multilingual fact checking. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pages 675–682.

Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2021. DeBERTaV3: Improving DeBERTa using ELECTRA-style pre-training with gradient-disentangled embedding sharing. *arXiv preprint arXiv:2111.09543*.

Moritz Laurer, Wouter van Atteveldt, Andreu Salleras Casas, and Kasper Welbers. 2024. Less annotating, more classifying – addressing the data scarcity problem of supervised machine learning with zero-shot classification and natural language inference. *Political Analysis*, 32(1):84–100.

Patrick Lewis, Ethan Perez, Aleksandara Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, volume 33, pages 9459–9474.

Wei Liu, Sony Trenous, Leonardo F. R. Ribeiro, Bill Byrne, and Felix Hieber. 2025. XRAG: Cross-lingual retrieval-augmented generation. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 15669–15690.

Quinn McNemar. 1947. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157.

Leonardo Ranaldi, Barry Haddow, and Alexandra Birch. 2026. Multilingual retrieval-augmented generation for knowledge-intensive question answering task. In *Findings of the Association for Computational Linguistics: EACL 2026*.

Hanna Shcharbakova, Tatiana Anikina, Natalia Skachkova, and Josef van Genabith. 2025. When scale meets diversity: Evaluating language models on fine-grained multilingual claim verification. In *Proceedings of the Eighth Fact Extraction and VERification Workshop (FEVER 2025)*.

Aryan Singhal, Thomas Law, Coby Kassner, Ayushman Gupta, Evan Duan, et al. 2024. Multilingual fact-checking using LLMs. In *Proceedings of the Fourth Workshop on Natural Language Processing for Positive Impact (NLP4PI 2024)*, pages 12–23.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. 2018. FEVER: a large-scale dataset for fact extraction and VERification. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 809–819.

Jörg Tiedemann and Santhosh Thottingal. 2020. OPUS-MT – building open translation services for the world. In *Proceedings of the 22nd Annual Conference of the European Association for Machine Translation*, pages 479–480.

Dan Wang, Guozhao Mo, Yafei Shi, Cheng Zhang, Bo Zheng, Boxi Cao, Xuanang Chen, Yaojie Lu, Hongyu Lin, Ben He, Xianpei Han, and Le Sun. 2026. All languages matter: Understanding and mitigating language bias in multilingual RAG. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL 2026)*.

Alexander Yeh. 2000. More accurate tests for the statistical significance of result differences. In *Proceedings of the 18th International Conference on Computational Linguistics (COLING 2000)*, pages 947–953.

A Supplementary Material

This appendix provides supplementary implementation details, development tuning logs, confusion matrices, human annotation protocols, and reproducibility instructions.

A.1 Implementation and Hardware Specifications

Table 8 outlines the software libraries, pretrained checkpoints, tokenizer configurations, and hardware parameters utilized in the frozen computational study.

A.2 Development Set Grid Search and Calibration

To determine the optimal operating threshold τ^* for the Selective-Check cascade, we performed a sweep over $\tau \in [0.10, 0.65]$ on the $N = 103$ development split. The utility objective is defined as:

$$J(\tau) = \text{Macro-F1}_3(\tau) - 0.15 \cdot \text{Coverage}(\tau). \tag{21}$$

Table 9 summarizes representative operating points from the canonical sweep.

A.3 Full Per-System Confusion Matrices

Table 10 provides the full confusion matrices for all evaluated systems across the $N = 163$ test instances (142 CONTRADICTED, 21 INSUFFICIENT_EVIDENCE, 0 SUPPORTED).

A.4 Bilingual Human Annotation Protocol

To address the critical limitation regarding causal attribution, we have developed a rigorous, independent bilingual human annotation protocol:

1. **Annotator Qualifications:** Native Hindi speakers fluent in English with formal training in linguistics or computational journalism.
2. **Target Sample:** A stratified sample of $N = 104$ prediction-disagreement instances, augmented by 30 concordant control instances.
3. **Annotation Dimensions:**
   - *Translation Fidelity (1–5 Likert):* Measures adequacy and fluency of e_{trans} relative to e_{orig}.
   - *Semantic Preservation (Binary):* Evaluates whether critical factual relations (negation, numerical bounds, named entities) are preserved without distortion.
   - *Entailment Grounding (3-way categorical):* Human annotator independently assigns the gold NLI relationship between evidence and claim under both languages.
4. **Agreement Standard:** Inter-annotator agreement will be assessed via Cohen's κ (targeting $\kappa \geq 0.70$).

We explicitly record that this protocol remains *pending execution* and is planned for future confirmatory research.

A.5 Reproducibility and Data Access

All canonical predictions, evaluation scripts, and figure/table generators are open-source and structured for immediate reproduction. Researchers can reproduce all tables and figures from the frozen artifacts without performing GPU/CPU model inference:

```
# Run complete automated regression test sui
python tests/run_all_tests.py

# Regenerate all publication figures (PDF &
python scripts/generate_publication_figures.

# Verify release archive integrity
Get-FileHash release/CROSS_LINGUAL_EVIDENCE_
```

All experimental configurations are documented in `configs/experiment_config.yaml`.

Component	Specification
Operating System	Windows 11 / Linux (Ubuntu 22.04 LTS)
Python Version	3.10+ / 3.14 (Virtual Environment)
Deep Learning Library	PyTorch 2.1.0+
Transformers Library	Hugging Face Transformers 4.36+
Machine Translation Model	`Helsinki-NLP/opus-mt-hi-en`
MT Decoding	Beam Search (Width: 4, Length Penalty: 1.0)
MT Sequence Length	Max 512 tokens
Verifier Backbone	`MoritzLaurer/mDeBERTa-v3-base-xnli`
Verifier Architecture	12 layers, 768 hidden, 12 attention heads
Verifier Total Parameters	$\approx$ 278M (86M backbone + embeddings)
Verifier Sequence Length	Max 512 subwords, dynamic padding
Batch Size	1 (Instance-level streaming inference)
Inference Device	Multi-core CPU (8 physical threads)
Deterministic Seed	42 (resampling, permutations, controls)

Table 8: Computational environment and model configurations.

τ	**Coverage**	**Macro-F1**$_3$	**Macro-F1**$_2$	**Utility** J
0.100	0.9806	0.2948	0.4421	0.1477
0.200	0.9417	0.2991	0.4487	0.1579
0.300	0.8058	0.2605	0.3908	0.1397
0.400	0.5631	0.2292	0.3437	0.1447
0.500	0.3495	0.1995	0.2992	0.1471
0.575	0.1845	0.2200	0.3300	0.1923
0.600	0.1748	0.2161	0.3241	0.1898
0.625	0.1650	0.2161	0.3241	0.1913
0.650	**0.1262**	**0.2213**	**0.3319**	**0.2023**

Table 9: Calibration grid search on the $N = 103$ development split. The optimal constrained cascade threshold was found at $\tau^* = 0.650$. The zero-check baseline achieved utility $J = 0.2104$.

Gold Label	Pred. Contra	Pred. Neutral	Pred. Support
No-Check (Translated English)			
CONTRADICTED (142)	21	57	64
INSUFFICIENT (21)	23	0	0
SUPPORTED (0)	0	0	0
Direct Multilingual (Original Hindi)			
CONTRADICTED (142)	56	28	58
INSUFFICIENT (21)	19	0	2
SUPPORTED (0)	0	0	0
Always-Check (Dual Consensus)			
CONTRADICTED (142)	46	38	58
INSUFFICIENT (21)	17	0	4
SUPPORTED (0)	0	0	0
Selective-Check ($\tau^* = 0.650$)			
CONTRADICTED (142)	21	57	64
INSUFFICIENT (21)	23	0	0
SUPPORTED (0)	0	0	0

Table 10: Confusion matrices on the $N = 163$ test split across all four verification conditions.