



Vidyavardhini's College of Engineering &
Technology

Department of Computer Engineering

Experiment No.3
To install and configure MongoDB to execute NoSQL commands
Date of Performance:31/07/2023
Date of Submission:07/08/2023



AIM: To install and configure MongoDB/ Cassandra/ HBase/ Hypertable and to execute NoSQL commands.

THEORY:

MongoDB can be downloaded from <https://www.mongodb.com/try/download/community2>

Now open command prompt and run the following command

```
C:\>move mongodb-win64-* mongodb  
  
1 dir(s) moved.
```

MongoDB requires a data folder to store its files. The default location for the MongoDB data directory is c:\data\db. So create the folder using the Command Prompt. Execute the following command sequence.

```
C:\>md data  
  
C:\>md data\db
```

In case mongodb is stored in some other location, navigate to that folder.

In command prompt navigate to the bin directory present into the mongodb installation folder. Suppose the installation folder is D:\set up\mongodb

```
C:\Users\XYZ>d:  
  
D:\>cd "set up"  
  
D:\set up>cd mongodb  
  
D:\set up\mongodb>cd bin  
  
D:\set up\mongodb\bin>mongod.exe --dbpath "d:\set up\mongodb\data"
```

Now to run the mongodb, open another command prompt and issue the following command:



```
D:\set up\mongodb\bin>mongo.exe

MongoDB shell version: 2.4.6

connecting to: test

>db.test.save( { a: 1 } )

>db.test.find()

{ "_id" : ObjectId(5879b0f65a56a454), "a" : 1 }

>
```

The use Command

MongoDB use DATABASE_NAME is used to create database. The command will create a new database, if it doesn't exist otherwise it will return the existing database

Syntax:

use DATABASE_NAME

The dropDatabase () Method

MongoDB db.dropDatabase () command is used to drop an existing database.

Syntax:

db.dropDatabase()

The createCollection() Method

MongoDB db.createCollection(name, options) is used to create collection.

Syntax:

db.createCollection(name, options)

Insert Document

To insert data into MongoDB collection, you need to use MongoDB's insert() or save()method

Syntax

>db.COLLECTION_NAME.insert(document)



Example:

```
>db.post.insert([
{
  title: 'MongoDB Overview',
  description: 'MongoDB is no sql
  database', tags: ['mongodb', 'database',
  'NoSQL'], likes: 100
},
{
  title: 'NoSQL Database',
  description: 'NoSQL database doesn't have
  tables', tags: ['mongodb', 'database', 'NoSQL'],
  likes: 20,
  comments: [
    {
      user:'user1',
      message: 'My first comment',
      dateCreated: new Date(2022,11,10,2,35),
      like: 0
    }
  ]
}]
```

Creating sample document:

Example

Suppose a client needs a database design for his blog website. Website has the following requirements.



- Document:

```
{
  _id: POST_ID
  title: TITLE_OF_POST,
  description: POST_DESCRIPTION,
  by: POST_BY,
  url: URL_OF_POST,
  tags: [TAG1, TAG2, TAG3],
  likes: TOTAL_LIKES,
  comments: [
    {
      user:'COMMENT_BY'
      ,
      message: TEXT,
      dateCreated: DATE_TIME,
      like: LIKES
    },
    {
      user:'COMMENT_BY'
      ,
      message: TEXT,
```



Vidyavardhini's College of Engineering &
Technology

Department of Computer Engineering

dateCreated: DATE_TIME,

like: LIKES



```
}  
]  
}
```

OUTPUT:

Show All Databases

```
mongosh mongodb://127.0.0.1:27017/
Microsoft Windows [Version 10.0.22621.2283]
(c) Microsoft Corporation. All rights reserved.

C:\Users\samar>mongosh
Current Mongosh Log ID: 651c354183769c4480038872
Connecting to:  mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.0.1
Using MongoDB: 7.0.2
Using Mongosh: 2.0.1

For mongosh info see: https://docs.mongodb.com/mongosh-shell/

-----
The server generated these startup warnings when booting
2023-10-03T12:02:36.648+05:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
-----

test> show dbs
admin 40.00 KiB
config 12.00 KiB
local 40.00 KiB
```

Create new database

```
mongosh mongodb://127.0.0.1:27017/
Microsoft Windows [Version 10.0.22621.2283]
(c) Microsoft Corporation. All rights reserved.

C:\Users\samar>mongosh
Current Mongosh Log ID: 651c354183769c4480038872
Connecting to:  mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.0.1
Using MongoDB: 7.0.2
Using Mongosh: 2.0.1

For mongosh info see: https://docs.mongodb.com/mongosh-shell/

-----
The server generated these startup warnings when booting
2023-10-03T12:02:36.648+05:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
-----

test> show dbs
admin 40.00 KiB
config 12.00 KiB
local 40.00 KiB
test> use myTestDb
switched to db myTestDb
myTestDb> db
myTestDb
myTestDb> |
```



Know your current selected database

```
mongosh mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.0.1
Microsoft Windows [Version 10.0.22621.2283]
(c) Microsoft Corporation. All rights reserved.

C:\Users\samar>mongosh
Current Mongosh Log ID: 651c354183769c4480038872
Connecting to:  mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.0.1
Using MongoDB: 7.0.2
Using Mongosh: 2.0.1

For mongosh info see: https://docs.mongodb.com/mongosh-shell/

-----
The server generated these startup warnings when booting
2023-10-03T12:02:36.648+05:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
-----

test> show dbs
admin 40.00 KiB
config 12.00 KiB
local 40.00 KiB
test> use myTestDb
switched to db myTestDb
myTestDb> db
myTestDb
myTestDb> |
```

Create collection

```
mongosh mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.0.1
Microsoft Windows [Version 10.0.22621.2283]
(c) Microsoft Corporation. All rights reserved.

C:\Users\samar>mongosh
Current Mongosh Log ID: 651c354183769c4480038872
Connecting to:  mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.0.1
Using MongoDB: 7.0.2
Using Mongosh: 2.0.1

For mongosh info see: https://docs.mongodb.com/mongosh-shell/

-----
The server generated these startup warnings when booting
2023-10-03T12:02:36.648+05:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
-----

test> show dbs
admin 40.00 KiB
config 12.00 KiB
local 40.00 KiB
test> use myTestDb
switched to db myTestDb
myTestDb> db
myTestDb
myTestDb> db.createCollection("Employee");
{ ok: 1 }
myTestDb> |
```

To check collections list

```
myTestDb> db.createCollection("Employee");
{ ok: 1 }
myTestDb> show collections
Employee
myTestDb> |
```




Insert document in collection

```
myTestDb> db.Employee.insert({id:1 , name:'Samarth', address:'Pune'})
DeprecationWarning: Collection.insert() is deprecated. Use insertOne, insertMany, or bulkWrite.
{
  acknowledged: true,
  insertedIds: { '0': ObjectId("651c386283769c4480038873") }
}
myTestDb> db.Employee.insert({id:2 , name:'Shubham', address:'Ratnagiri'})
{
  acknowledged: true,
  insertedIds: { '0': ObjectId("651c387883769c4480038874") }
}
myTestDb> |
```

To insert multiple documents in selected collection

```
myTestDb> db.Employee.insert({id:3 , name:'Dharmesh', address:'Malvan'}, {id:4, name:'Hrushikesh', address:'kochi'})
{
  acknowledged: true,
  insertedIds: { '0': ObjectId("651c394183769c4480038875") }
}
myTestDb> |
```

Get collection document

```
myTestDb> db.Employee.find().pretty()
[
  {
    _id: ObjectId("651c386283769c4480038873"),
    id: 1,
    name: 'Samarth',
    address: 'Pune'
  },
  {
    _id: ObjectId("651c387883769c4480038874"),
    id: 2,
    name: 'Shubham',
    address: 'Ratnagiri'
  },
  {
    _id: ObjectId("651c394183769c4480038875"),
    id: 3,
    name: 'Dharmesh',
    address: 'Malvan'
  }
]
myTestDb> |
```



Update document

```
myTestDb> db.Employee.update({name:'Dharmesh'},{$set:{name:'Hrushikesh'}})
DeprecationWarning: Collection.update() is deprecated. Use updateOne, updateMany, or bulkWrite.
{
  acknowledged: true,
  insertedId: null,
  matchedCount: 1,
  modifiedCount: 1,
  upsertedCount: 0
}
```

Drop database

```
myTestDb> db.dropDatabase()
{ ok: 1, dropped: 'myTestDb' }
```

CONCLUSION:

In this experiment, the installation and configuration of MongoDB, a NoSQL database, to execute NoSQL commands. We customized it to meet our specific needs, including security and performance requirements. We learned how to use NoSQL commands for various database operations, such as inserting, querying, and indexing data. MongoDB demonstrated scalability and performance for unstructured data, making it a good choice for NoSQL applications. The availability of comprehensive documentation and community support helped us succeed, and we gained valuable skills for efficient NoSQL data management using MongoDB.