

Technical Data Sheet


Inbuilt Hinged Enclosure

Product Code: 1.06

1.06

Features & Advantages

- Plain walled enclosure.
- Inbuilt Hinges that keep base and top cover together after opening.
- Polymer Screws.
- Reinforced design of base for extra strength
- Provision for Padlock
- Outside bushes provided to mount box without tampering enclosures and IP Rating
- Pole Mounting with accessories.
- Multiple bushes provided for mounting of din channel, terminals and mounting plate
- Gland holes/Customizations can be machined as per drawings.
- Weather Proof for Outdoor Applications
- Available in Opaque PC/ABS materials
- Option of Polycarbonate Transparent Top Cover with PC/ABS base




Optional Accessories

- External Wall Mounting (SS304 / CRCA Powder Coated)
- Mounting Plate (Polymer / CRCA Powder Coated / Bakelite)
- Antivibration Terminal Block (25 Sq. mm / 35 Sq. mm).
- 4 Way Stud Type Terminal Block (32A / 63A)
- Terminals Type Screw / Screwless / Busbar (2.5 Sq. mm to 70 Sq. mm.)
- Ventilators (Round/Rectangle)
- Polycarbonate Windows
- Pole Mounting Accessory with Clamp as per Pole Diameter
- Latch
- Lock with Key
- Carry Handle (Straight/Flush)
- Cable Glands


Technical Data

Description	ABS	Polycarbonate
Dimension	674x644x277 mm	674x644x277 mm
Material	ABS	PC/Glass Reinforced Polycarbonate (GRP)
Ingress Protection	IP 65, IEC-60529	IP 67, IEC-60529
Ultraviolet Protection	UV Stabilized	UV Stabilized, EN ISO 4892
Impact Resistance	IK07	IK08/09/10, IEC 60068-2-72
Glow Wire Test	650° C	820/960 °C, IS 11000-2-1, IEC 60695-2-10
Ambient Temperature	-20 to +60° C	-25 to +80 Deg. C
Fire Rating	HB / V2 Optional	UL94V-0
ROHS	Compliant	Compliant IEC 62321
Environment Protection	Halogen Free	Halogen Free


Drawings



Front View



Internal View



Side View