

Technical Data Sheet

Plain Wall Industrial Enclosure

Product Code: 2.00A

2.00A

Features & Advantages

- Polymer screws
- Plain walled enclosure.
- Multiple bushes provided for mounting of din channel, terminals and mounting plate with 10x9.5 self tapping screw
- Outside bushes provided to mount box without tampering enclosures and IP Rating
- Gland holes/Customizations can be carried out as per specific drawing.
- Weather Proof for Outdoor Applications
- Available in Opaque PC/ABS materials
- Option of Polycarbonate Transparent Top Cover with PC/ABS base




Optional Accessories

- External Wall Mounting Clamp (SS304 / CRCA Powder Coated)
- Mounting Plate (Polymer / CRCA Powder Coated / Bakelite)
- 4 Way Stud Type Terminal Block (32A)
- Terminals Screw Type / Screwless (2.5 Sq. mm to 25 Sq. mm)
- Ventilators (Round/Rectangle)
- Polycarbonate Windows
- Pole Mounting Accessory with Stainless Steel Screw type Clamp as per Pole Diameter
- Cable Glands

Technical Data

Description	ABS	Polycarbonate
Dimension	180x130x100 mm	180x130x100 mm
Material	ABS	PC/Glass Reinforced Polycarbonate (GRP)
Ingress Protection	IP 65, IEC-60529	IP 67, IEC-60529
Ultraviolet Protection	UV Stabilized	UV Stabilized, EN ISO 4892
Impact Resistance	IK07	IK08/09/10, IEC 60068-2-72
Glow Wire Test	650° C	820/960 °C, IS 11000-2-1, IEC 60695-2-10
Ambient Temperature	-20 to +60° C	-25 to +80 Deg. C
Fire Rating	HB / V2 Optional	UL94V-0
ROHS	Compliant	Compliant IEC 62321
Environment Protection	Halogen Free	Halogen Free

Drawings



Application Picture

