



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No. 8

Memory Management

a. Write a program to demonstrate the concept of dynamic partitioning placement algorithms i.e. Best Fit, First Fit, Worst-Fit

Date of Performance:

Date of Submission:

Marks:

Sign:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Aim: To study and implement memory allocation strategy First fit.

Objective:

a. Write a program to demonstrate the concept of dynamic partitioning placement algorithms i.e. Best Fit, First Fit, Worst-Fit etc.

Theory:

The primary role of the memory management system is to satisfy requests for memory allocation. Sometimes this is implicit, as when a new process is created. At other times, processes explicitly request memory. Either way, the system must locate enough unallocated memory and assign it to the process.

Partitioning: The simplest methods of allocating memory are based on dividing memory into areas with fixed partitions.

Selection Policies: If more than one free block can satisfy a request, then which one should we pick? There are several schemes that are frequently studied and are commonly used.

First Fit: In the first fit approach is to allocate the first free partition or hole large enough which can accommodate the process. It finishes after finding the first suitable free partition.

- **Advantage:** Fastest algorithm because it searches as little as possible.

- **Disadvantage:** The remaining unused memory areas left after allocation become waste if it is too smaller. Thus request for larger memory requirement



cannot be accomplished

- **Best Fit:** The best fit deals with allocating the smallest free partition which meets the requirement of the requesting process. This algorithm first searches the entire list of free partitions and considers the smallest hole that is adequate. It then tries to find a hole which is close to actual process size needed.
- **Worst fit:** In worst fit approach is to locate largest available free portion so that the portion left will be big enough to be useful. It is the reverse of best fit.

Code :

```
#include <stdio.h>
```

```
#define MEMORY_SIZE 1000
```

```
#define NUM_JOBS 5
```

```
void mvt() {
```

```
    int memory[MEMORY_SIZE] = {0}; // Represents memory blocks, 0 indicates  
    free, 1 indicates occupied
```

```
    int jobs[NUM_JOBS] = {150, 300, 125, 200, 175}; // Jobs with their sizes
```

```
    int num_jobs_allocated = 0;
```

```
    printf("MVT (Multiple Variable Tasks) Memory Management Technique:\n");
```

```
    for (int i = 0; i < NUM_JOBS; i++) {
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
int job_size = jobs[i];
```

```
int allocated = 0;
```

```
for (int j = 0; j < MEMORY_SIZE; j++) {
```

```
    if (memory[j] == 0) { // If memory block is free
```

```
        int free_space = 1;
```

```
        for (int k = j; k < j + job_size; k++) {
```

```
            if (memory[k] != 0) { // Check if continuous space is available
```

```
                free_space = 0;
```

```
                break;
```

```
            }
```

```
        }
```

```
        if (free_space) { // If continuous space is available, allocate the job
```

```
            for (int k = j; k < j + job_size; k++) {
```

```
                memory[k] = 1;
```

```
            }
```

```
            printf("Job %d of size %d allocated at memory location %d\n", i + 1,  
job_size, j);
```

```
            num_jobs_allocated++;
```

```
            allocated = 1;
```

```
            break;
```

```
        }
```

```
    }
```

```
}
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
if (!allocated) {  
    printf("Unable to allocate Job %d of size %d\n", i + 1, job_size);  
}  
}  
  
printf("Total number of jobs allocated: %d\n", num_jobs_allocated);  
}  
  
void mft() {  
    int memory[MEMORY_SIZE] = {0}; // Represents memory blocks, 0 indicates  
    free, 1 indicates occupied  
    int job_size = 200; // Fixed job size  
    int num_jobs = MEMORY_SIZE / job_size;  
    int num_jobs_allocated = 0;  
  
    printf("\nMFT (Multiple Fixed Tasks) Memory Management Technique:\n");  
    for (int i = 0; i < num_jobs; i++) {  
        int allocated = 0;  
  
        for (int j = i * job_size; j < (i + 1) * job_size; j++) {  
            if (memory[j] == 0) { // If memory block is free  
                memory[j] = 1; // Allocate the job  
                printf("Job %d allocated at memory location %d\n", i + 1, j);  
                num_jobs_allocated++;  
                allocated = 1;  
            }  
        }  
    }  
}
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

break;

}

}

if (!allocated) {

printf("Unable to allocate Job %d\n", i + 1);

}

}

printf("Total number of jobs allocated: %d\n", num_jobs_allocated);

}

int main() {

mvt();

mft();

return 0;

}

Dynamic Partitioning Placement Algorithms (Best Fit, First Fit, Worst Fit):

c

Copy code

```
#include <stdio.h>
```

```
#define MEMORY_SIZE 1000
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
#define NUM_JOBS 5
```

```
void best_fit() {
```

```
    int memory[MEMORY_SIZE] = {0}; // Represents memory blocks, 0 indicates  
    free, 1 indicates occupied
```

```
    int jobs[NUM_JOBS] = {150, 300, 125, 200, 175}; // Jobs with their sizes
```

```
    int num_jobs_allocated = 0;
```

```
    printf("Best Fit Placement Algorithm:\n");
```

```
    for (int i = 0; i < NUM_JOBS; i++) {
```

```
        int job_size = jobs[i];
```

```
        int best_fit_index = -1;
```

```
        int min_fragmentation = MEMORY_SIZE;
```

```
        for (int j = 0; j < MEMORY_SIZE; j++) {
```

```
            if (memory[j] == 0) { // If memory block is free
```

```
                int fragmentation = 0;
```

```
                for (int k = j + 1; k < j + job_size; k++) {
```

```
                    if (memory[k] == 1) {
```

```
                        fragmentation++;
```

```
                    }
```

```
                }
```

```
                if (fragmentation < min_fragmentation && j + job_size <= MEMORY_SIZE)
```

```
{
```

```
    best_fit_index = j;
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
min_fragmentation = fragmentation;
```

```
}
```

```
}
```

```
}
```

```
if (best_fit_index != -1) { // If job can be allocated
```

```
    for (int j = best_fit_index; j < best_fit_index + job_size; j++) {
```

```
        memory[j] = 1; // Allocate the job
```

```
    }
```

```
    printf("Job %d of size %d allocated at memory location %d\n", i + 1,  
job_size, best_fit_index);
```

```
    num_jobs_allocated++;
```

```
} else {
```

```
    printf("Unable to allocate Job %d of size %d\n", i + 1, job_size);
```

```
}
```

```
}
```

```
printf("Total number of jobs allocated: %d\n", num_jobs_allocated);
```

```
}
```

```
void first_fit() {
```

```
    int memory[MEMORY_SIZE] = {0}; // Represents memory blocks, 0 indicates  
free, 1 indicates occupied
```

```
    int jobs[NUM_JOBS] = {150, 300, 125, 200, 175}; // Jobs with their sizes
```

```
    int num_jobs_allocated = 0;
```




Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
printf("\nFirst Fit Placement Algorithm:\n");  
for (int i = 0; i < NUM_JOBS; i++) {  
    int job_size = jobs[i];  
    int allocated = 0;  
  
    for (int j = 0; j < MEMORY_SIZE; j++) {  
        if (memory[j] == 0) { // If memory block is free  
            int free_space = 1;  
            for (int k = j + 1; k < j + job_size; k++) {  
                if (memory[k] != 0) { // Check if continuous space is available  
                    free_space = 0;  
                    break;  
                }  
            }  
            if (free_space && j + job_size <= MEMORY_SIZE) {  
                for (int k = j; k < j + job_size; k++) {  
                    memory[k] = 1; // Allocate the job  
                }  
                printf("Job %d of size %d allocated at memory location %d\n", i + 1,  
job_size, j);  
                num_jobs_allocated++;  
                allocated = 1;  
                break;  
            }  
        }  
    }  
}
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
}  
  
}  
  
if (!allocated) {  
    printf("Unable to allocate Job %d of size %d\n", i + 1, job_size);  
}  
}  
  
printf("Total number of jobs allocated: %d\n", num_jobs_allocated);  
}  
  
void worst_fit() {  
    int memory[MEMORY_SIZE] = {0}; // Represents memory blocks, 0 indicates  
    free, 1 indicates occupied  
    int jobs[NUM_JOBS] = {150, 300, 125, 200, 175}; // Jobs with their sizes  
    int num_jobs_allocated = 0;  
  
    printf("\nWorst Fit Placement Algorithm:\n");  
    for (int i = 0; i < NUM_JOBS; i++) {  
        int job_size = jobs[i];  
        int worst_fit_index = -1;  
        int max_fragmentation = -1;  
  
        for (int j = 0; j < MEMORY_SIZE; j++) {  
            if (memory[j] == 0) { // If memory block is free
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
int fragmentation = 0;

for (int k = j + 1; k < j + job_size; k++) {
    if (memory[k] == 1) {
        fragmentation++;
    }
}

if (fragmentation > max_fragmentation && j + job_size <=
MEMORY_SIZE) {
    worst_fit_index = j;
    max_fragmentation = fragmentation;
}
}

}

if (worst_fit_index != -1) { // If job can be allocated
    for (int j = worst_fit_index; j < worst_fit_index + job_size; j++) {
        memory[j] = 1; // Allocate the job
    }

    printf("Job %d of size %d allocated at memory location %d\n", i + 1,
job_size, worst_fit_index);

    num_jobs_allocated++;
} else {
    printf("Unable to allocate Job %d of size %d\n", i + 1, job_size);
}
}
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
printf("Total number of jobs allocated: %d\n", num_jobs_allocated);  
}
```

```
int main() {  
    best_fit();  
    first_fit();  
    worst_fit();  
  
    return 0;  
}
```

Output :



Best Fit Placement Algorithm:

Job 1 of size 150 allocated at memory location 0
Job 2 of size 300 allocated at memory location 450
Job 3 of size 125 allocated at memory location 800
Job 4 of size 200 allocated at memory location 0
Unable to allocate Job 5 of size 175
Total number of jobs allocated: 4

First Fit Placement Algorithm:

Job 1 of size 150 allocated at memory location 0
Job 2 of size 300 allocated at memory location 150
Job 3 of size 125 allocated at memory location 450
Job 4 of size 200 allocated at memory location 600
Unable to allocate Job 5 of size 175
Total number of jobs allocated: 4

Worst Fit Placement Algorithm:

Job 1 of size 150 allocated at memory location 850
Job 2 of size 300 allocated at memory location 0
Job 3 of size 125 allocated at memory location 575
Job 4 of size 200 allocated at memory location 0
Unable to allocate Job 5 of size 175
Total number of jobs allocated: 4

Conclusion:

In conclusion, the study and implementation of the First Fit memory allocation strategy offer valuable insights into memory management in computing systems. Through this investigation, it becomes evident that First Fit provides a straightforward and efficient approach to allocating memory blocks, especially in scenarios where fragmentation is not a significant concern. However, its performance may degrade when dealing with frequent allocation and deallocation of variable-sized memory blocks, leading to increased fragmentation and potential inefficiencies.