Task 4. Algorithms for unconstrained nonlinear optimization. Stochastic and metaheuristic algorithms

Goal

The use of stochastic and metaheuristic algorithms (Simulated Annealing, Differential Evolution, Particle Swarm Optimization) in the tasks of unconstrained nonlinear optimization and the experimental comparison of them with Nelder-Mead and Levenberg-Marquardt algorithms

Problems and methods

I. Generate the noisy data (x_k, y_k) , where k = 0, ..., 1000, according to the rule:

$$y_k = \begin{cases} -100 + \delta_k, & f(x_k) < -100, \\ f(x_k) + \delta_k, & -100 \le f(x_k) \le 100, \\ 100 + \delta_k, & f(x_k) > 100, \end{cases} \qquad x_k = \frac{3k}{1000},$$
$$f(x) = \frac{1}{x^2 - 3x + 2'}$$

where $\delta_k \sim N(0,1)$ are values of a random variable with standard normal distribution. Approximate the data by the rational function

$$F(x,a,b,c,d) = \frac{ax+b}{x^2+cx+d}$$

by means of least squares through the numerical minimization of the following function:

$$D(a,b,c,d) = \sum_{k=0}^{1000} (F(x_k,a,b,c,d) - y_k)^2.$$

To solve the minimization problem, use Nelder-Mead algorithm, Levenberg-Marquardt algorithm and **at least two** of the methods among Simulated Annealing, Differential Evolution and Particle Swarm Optimization. If necessary, set the initial approximations and other parameters of the methods. Use $\varepsilon = 0.001$ as the precision; at most 1000 iterations are allowed. Visualize the data and the approximants obtained **in a single plot**. Analyze and compare the results obtained (in terms of number of iterations, precision, number of function evaluations, etc.).

II. Choose at least 15 cities in the world having land transport connections between them. Calculate the distance matrix for them and then apply the Simulated Annealing method to solve the corresponding Travelling Salesman Problem. Visualize the results at the first and the last iteration. If necessary, use the city dataset from https://people.sc.fsu.edu/~jburkardt/datasets/cities/cities.html