1. Arayuz (UI) Hizli Eslestirme Tablosu — IST26 RWD (1 Motor / 1 Invertor)

Panel / Parametre	Girilecek Deger (IST26 RWD)	Repodaki Alan ve Aciklama
[VEHICLE] Mass (incl. driver) [kg]	335.5	C.mass.baseTotal = 335.5 kg (Sprung: 295.64 kg, Unsprung: 39.86 kg)
[VEHICLE] Front weight [%]	47.9	C.mass.fmd = 0.479 (%47.9 On / %52.1 Arka)
[VEHICLE] Wheelbase [mm]	1600	C.geo.wheelbase = 1.600 m
[VEHICLE] Track width [mm]	1270 (1280 F / 1260 R)	C.geo.trackF = 1.280 m, C.geo.trackR = 1.260 m
[VEHICLE] CG height [mm]	247.2	C.geo.hCg = 0.247169 m (247.169 mm)
[VEHICLE] Downforce Cl*A [m^2]	4.14 (Accel: 2.56)	C.aero.clA = 4.14 m^2 (Acceleration etabinda 2.56 m^2)
[VEHICLE] Drag Cd*A [m^2]	1.58 (Accel: 1.06)	C.aero.cdA = 1.58 m^2 (Acceleration etabinda 1.06 m^2)
[VEHICLE] Air density rho [kg/m^3]	1.225	C.aero.rho = 1.225 kg/m^3
[VEHICLE] Aero balance front [%]	48.2	C.aero.balF = 0.482 (%48.2 On / %51.8 Arka)
[VEHICLE] Aero pitch sens. [%/G]	0.0	Modelde sabit aero denge kullaniliyor (Q31/Q32)
[VEHICLE] Rolling resist. Crr [-]	0.010	C.resistance.rrc = 0.010
[VEHICLE] Loaded wheel radius [mm]	205.0 (Nom: 205.7)	rNominal=205.74 mm | MF6.1 Re: 205.20 F / 204.88 R mm | Geom: 201.8 F / 201
[VEHICLE] Front LLTD [%]	38.3 (Elastik: 36.8)	Toplam LLTD: %38.31 | Saf Roll Rijitligi Orani Kf/(Kf+Kr): %36.84
[VEHICLE] Roll center front [mm]	31.4	C.susp.hRcF = 0.03142 m (31.42 mm)
[VEHICLE] Roll center rear [mm]	36.5	C.susp.hRcR = 0.03650 m (36.50 mm)
[VEHICLE] Static camber front [deg]	-1.7	C.tire.camberF = -1.7 deg
[VEHICLE] Static camber rear [deg]	-1.4	C.tire.camberR = -1.4 deg
[VEHICLE] Yaw inertia Izz [kg*m^2]	129.0	C.inertia.baseIzz = 129.0 kg*m^2 (Ixx=33.31, Iyy=115.9)
[VEHICLE] Tire grip scale lambda_mu [-]	1.00	LMUX = 1.00, LMUY = 1.00 (QSS cozucu rezervi 0.97)
[POWERTRAIN] Motor peak torque [Nm]	310.0	C.pt.motorTorque(1) = 310 Nm (0 - 900 RPM arasi sabit)
[POWERTRAIN] Motor peak power [kW]	80.0	C.pt.powerMaxW = 80000 W (2500 - 6000 RPM arasi ~80 kW plato)
[POWERTRAIN] Motor max speed [rpm]	6000 (Ham: 10000)	C.pt.rpmMax = 6000 RPM kesici (ham tablo 10000 RPM e kadar)
[POWERTRAIN] Planetary / Gear ratio [:1]	3.2	C.pt.gearRatio = 3.2 (1 motor, arka aks redüksiyon orani)
[POWERTRAIN] Accumulator limit [kW]	80.0	C.pt.powerMaxW = 80000 W
[POWERTRAIN] Regen limit [kW] / Regen	0 / Kapali (False)	C.pt.regen = false
[POWERTRAIN] Peak wheel/axle torque	942.4 Nm (Ham: 992 Nm)	310 Nm * 3.2 * 0.95 verim = 942.4 Nm (1 motor arka aks)

2. Kutle, Geometri, Atalet ve Suspansiyon Parametreleri (IST26 RWD)

Kategori	Parametre	Deger	Birim / Kod Degiskeni
Kutle & Statik Yuk	Toplam / Yayli (Sprung) Kutle	335.50 / 295.64	kg (C.mass.baseTotal / sprung)
Kutle & Statik Yuk	On / Arka Yaysiz Kutle (Tekerlek Basi)	9.20 / 10.73	kg (Toplam aks: 18.40 / 21.46 kg)
Kutle & Statik Yuk	On / Arka Tekerlek Basi Statik Yuk (Wf / Wr)	788.32 / 857.43	N (C.static.wF / wR)
Geometri	Dingil Mesafesi (L) | lF (CG-On) | lR (CG-Arka)	1.600 | 0.8336 | 0.7664	m (C.geo.wheelbase, lF, lR)
Geometri	On / Arka Iz Genisligi (trackF / trackR)	1.280 / 1.260	m (C.geo.trackF / trackR)
Geometri	CG Yuksekligi (hCg) | Roll Ekseni-CG (hRollAxisToCg)	247.17 | 213.10	mm (C.geo.hCg / C.susp.hRollAxisToCg)
Geometri	Govde Uzunlugu x Genisligi | On Sarkma	3.083 x 1.546 | 0.686	m (bodyLength, bodyWidth, frontOverhang)
Atalet	Govde Ataletleri: Ixx (Roll) | Iyy (Pitch) | Izz (Yaw)	33.31 | 115.90 | 129.00	kg*m^2 (C.inertia.baseIxx/Iyy/Izz)
Atalet	Tekerlek Ataleti (Iw) | Motor Rotor Ataleti (Irotor)	0.2567 | 0.0670	kg*m^2 (baseWheel / baseMotorRotor)
Atalet	QSS Donel Esdeger Kutle (mRot) | Efektif Kutle (mEff)	40.466 | 375.966	kg (QssEffectiveMass.m)
Suspansiyon (Yay)	Fiziksel Heave Yay Rijitligi (On / Arka)	110,000 / 110,000	N/m (ksHeaveF / ksHeaveR = 110 N/mm)
Suspansiyon (Yay)	Fiziksel Roll Yay Rijitligi (On / Arka)	90,000 / 130,000	N/m (ksRollF = 90, ksRollR = 130 N/mm)
Suspansiyon (MR)	Heave Motion Ratio (On / Arka, modal)	2.2486 / 2.2864	teker/yay (mrHeaveF / mrHeaveR)
Suspansiyon (MR)	Roll Motion Ratio (On / Arka, modal)	1.8452 / 1.5800	teker/yay (mrRollF / mrRollR)
Suspansiyon (Rate)	Tekerlek Esdeger Heave Rijitligi (kHeaveF / kHeaveR)	21,755.4 / 21,042.1	N/m (ksHeave / mrHeave^2)
Suspansiyon (Rate)	Modal Roll Rijitligi (kPhiF / kPhiR)	333.795 / 572.382	Nm/deg (19,125 / 32,795 Nm/rad)
Suspansiyon (Rate)	Tekerlek Esdeger Roll Rijitligi (kRollWheelF / R)	23,346.0 / 41,314.0	N/m (2*kPhi / track^2)
Suspansiyon (Damper)	Heave Sonumleme Katsayisi (cHeaveF / cHeaveR)	2,357.01 / 2,421.43	N*s/m (tekerlek esdeger modal)
Suspansiyon (Damper)	Modal Roll Sonumleme Katsayisi (cPhiF / cPhiR)	1,174.57 / 684.97	Nm*s/rad (zeta ~ 0.707)
Suspansiyon (Trim)	Roll Center (On / Arka) | Roll Gradient	31.42 / 36.50 | 1.192	mm | deg/g
Suspansiyon (Trim)	Statik Suspansiyon Cokmesi (On / Arka)	33.33 / 38.49	mm (TR.heaveDeflF / heaveDeflR)

3. Powertrain (1 Motor RWD), Diferansiyel, Fren, Lastik ve Direksiyon Verileri

Kategori	Parametre	Deger	Birim / Aciklama
Powertrain (RWD)	Motor Sayisi | Disli Orani (G) | Aktarma Verimi (eta)	1 (Arka) | 3.2:1 | 0.95	OCP de mekanik 0.92, invertor 0.97
Powertrain (RWD)	Tepe Tork | Maks. Guc | Devir Kesici (rpmCut)	310 Nm | 80 kW | 6000 RPM	Ham egride maks devir 10,000 RPM
Powertrain (RWD)	Tork-Devir (0, 500, 900, 2500, 2944, 3250 RPM)	310, 310, 310, 305.6, 259.5, 235.1	Nm (Motor mil torku)
Powertrain (RWD)	Tork-Devir (3519, 3895, 4050, 4514, 5462, 6000 RPM)	217.1, 196.1, 188.6, 169.2, 139.9, 127.	Nm (6000 RPM interpolasyonlu kesici)
Powertrain (RWD)	Tork-Devir Ham Devami (6827, 8279, 9379, 10000 RPM)	107.2, 82.6, 69.7, 66.0	Nm (6000 RPM ustu modelde kesilir)
Diferansiyel (LSD)	Model | Rampa Acilari (Drive / Coast)	Drexler Salisbury | 50 / 40	deg (Ters cevrilmis rampa ayari)
Diferansiyel (LSD)	Kilit Orani (Drive / Coast) | Preload Torku	0.42 (%42) / 0.60 (%60) | 27.5	Nm (omegaSmooth = 1.0 rad/s)
Fren Sistemi	Tekerlek Basi Maks. Fren Torku (On / Arka)	400 / 320 (Toplam: 1440)	Nm (Aks toplami: 800 On / 640 Arka)
Fren Sistemi	Fren Bias (On Oran) | Maks. Bias Siniri	%55.0 (0.55) | %65.0	Tam pedalda 396 Nm On / 320 Nm Arka
Lastik (Hoosier)	Model | Basinc (On / Arka)	Hoosier 43075 MF6.1 | 12 / 10	psi (82.74 kPa On / 68.95 kPa Arka)
Lastik (Hoosier)	Statik Kamber (On / Arka) | Statik Toe (On / Arka)	-1.7 / -1.4 | +0.3 (Out) / -0.3 (In)	deg (Tekerlek basi)
Lastik (Hoosier)	Dikey Rijitlik (kVertical) | Dikey Sonum (cVertical)	200,000 N/m (200 N/mm) | 300 N*s/m	Statik cokme: 3.94 mm On / 4.29 mm Arka
Lastik (Hoosier)	Gevseme Uzunlugu (Lx / Ly) | VXLOW | Yari Genislik	0.30 m / 0.45 m | 1.0 m/s | 95.25 mm	Kombinasyon modu: friction ellipse
Lastik (Hoosier)	Statik Yukte Tepe Boylamsal / Yanal Kuvvet (On)	Dx = 1654 N (mu=2.10) | Dy = 1895 N	Fz_stat_F = 788.3 N, Ca = 481.2 N/deg
Lastik (Hoosier)	Statik Yukte Tepe Boylamsal / Yanal Kuvvet (Arka)	Dx = 1904 N (mu=2.22) | Dy = 2095 N	Fz_stat_R = 857.4 N, Ca = 496.7 N/deg
Direksiyon	Scrub Radius | Steering Arm | Pinion Radius	10.3 mm | 78.0 mm | 16.1781 mm	Oran: 0.20741 (~4.54:1 direksiyon orani)
Direksiyon	Maks. Simit Acisi | Maks. Surucu Torku | Hiz Limiti	+/-126 deg | 19.0 Nm | 800 deg/s	1. derece zaman sabiti tau = 0.06 s
Direksiyon	Ackermann Polinomu (FL / FR, derece cinsinden)	2.895e-9*d^4 +- 9.619e-7*d^3 + 1.08	Sabit -0.3 terimi statik toe-out tur