COMMERCIAL ACCHARGER.

JéGO Power- towerplug® AC commercial charging station

Reference number: REF 1010

GENERAL SPECIFICATIONS:

- ·2x 22 kW
- Customizable design (logo, color scheme, cable lenght, plug type)
- Customizable communication systems
- · E-Flux by ROAD
- App, Wi-fi & Bluetooth Connectivity, RFID
- Dynamic Load Balancing
- OCCP Connection
- CE Certified
- 24 month warranty

With the towerplug®, JéGO Power provides the best public charging station when it comes to affordability. This floor-installed charging tower comes in a double 22kW output, available in both socket and cable variants. The charger's robust design can be fully customized by selecting colour schemes and logos that suit the occasion. Additionally, the charger can also be controlled with the use of RFID cards and can be monitored via OCPP connection from for example E-Flux by ROAD.



home**plug**®

JéGO Power- homeplug® PRO AC home Wallbox (App Version)

Reference number: REF 1035

GENERAL SPECIFICATIONS:

- -1.4-7.4 kW
- · World's first consumer-friendly wallbox
- Over 75% time reduction on installation
- Delivered with detailed instruction videos and manuals
- Delivered with tools: screwdriver, step-drill, hardware
- Optional Dynamic Load Balancing
- Over 50% reduction in size
- CE Certified
- 24 month warranty

This compact but powerful charging station is the PRO version of the most consumer-friendly charging solution on the market. The homeplug® PRO includes an app that oversees all your charging activities, giving you complete control. Easily schedule charging sessions and manage power settings right from the convenience of your phone. That is how simple it can be and how simple JéGO Power makes it for you. The homeplug® PRO empowers you to reduce installation expenses by enabling you to personally install the charger. Rest assured, we provide comprehensive instruction videos, manuals, and support, to guide you every step of the way.

COMMERCIAL ACCHARGER.

JéGO Power - towerplug® PROMO AC commercial charging station (Advertising Version)

Reference number: REF 1013

GENERAL SPECIFICATIONS:

- 2x 22 kW
- 55 inch Advertising screen
- First multi-purpose AC charging station
- ROI in 2-3 years
- Advertising partner colaboration
- Customizable design (logo, color scheme, cable lenght, plug type)
- E-Flux by ROAD
- OCPP Connection
- Dynamic Load Balancing
- CE Certified
- 24 month warranty

With the towerplug® PROMO, JéGO Power has invented a whole new dimension to charging. This floor-installed charger is equipped with a 55-inch advertising display, for CPOs to generate a secondary revenue stream with advertising while still offering a double 22kW output. The charger's color schemes and design can be customized to any occasion.

Moreover, the charger can also be controlled with the use of RFID cards and can be monitored via OCPP connection from for example E-Flux by ROAD.





homeplug® PRO

Voltage

Current

Power

AC Power Frequency

Mass

Product Dimensions

Connection

Communication Interface

Smart assistance

Protection &

Standards

Environment

Safety Compliance

Multiple Protections

Operating Temperature

Relative Humidity

Altitude IP Level IK Rating AC 230V

6-32A

1.4 - 7.4kW

50/60Hz

1.15 KG

H:130 mm x W:200mm x D:115mm

Type 2 Socket

APP, Bluetooth: Wi-Fi

Dynamic Load Balancing (optional)

IEC 61851-1, IEC61851-21-2 EVSE Mode 3

UVP, OVP, RCD (TypeA+DC6mA) RCP, GFP, OCP,

OTP

-30°C-+55°C

Up to 95% non-condensing

<2000M IP54 IK10



towerplug®

Towerplug® 2x22kW

Input parameter	Input Type	1P +N +PE - 3P+N+PE
	Input Voltage	AC 230/400V+/- 15%
	Power Easter	>0.00

50-60Hz Input Frequency Maximum Current 2x32A Rated Power 2x22kW

User Interface Type 2 Charge Connector **LED Indicator Light** RGB

Output Parameter

Environment

Cable Length 5m or Optional Enclosure Sheet Metal

Authorization Plug & Charge, RFID Card, QR Code, APP, PO5980

Communication Communication Protocol OCPP 1.6J (upgradable)

Wi-Fi Yes Bluetooth Optional Ethernet Yes

Optional (KPN)

Cert. MID Meter Yes RS485 Yes CAN Yes RCD Yes Yes **Emergency Stop**

IP55 / IK10 Protection Rating Safety & Certifications **Electrical Protection**

Over/Under Voltage Protection, Over Current Protection, Over Temperature Protection, Surge Protection, Residual Current Protection, Cable Lock

Residual Current 30mA Type A + 6mA DC Protection

Certifications System Standards MTBF Mounting

Operation Temperature Relative Humidity Operating Altitude **Product Dimension**

(W/H/D)

Mass 35kg

CE, UKCA, CB, RoHS IEC 61851-1/2017 100000 hours

Floor Mounted -30°C~+50°C

5%-95% <2000m

360/1200/250mm,



Jécotowerplug[®] **PROMO**

Towerplug* PROMO 2x22kW

	Towerplug* PROMO 2	AZZRVV
Input Parameter Output Parameter User Interface	Input Type Input Voltage Power Factor Input Frequency Output Voltage Maximum Current Rated Power Peak Efficiency Charge Connector	3P+N+PE AC 380V+/- 15% >0.99 50-60Hz 200-1000V 32A 2x22kW 0.96 Type 2
User interface	LED Indicator Light LCD Display Cable Length Enclosure Authorization	RGB 5-inch HD Touch Screen 5m or Optional Sheet Metal Plug&Charge/RFID Card/APP/ POS 980
Communication	Communication Protocol Wi-Fi Bluetooth Ethernet 4G	OCPP 1.6J (upgradable) Yes Optional Yes Optional (KPN)
Safety & Certifications	Cert. MID Meter Emergency Stop RCD Protection Rating Cooling Method Noise Electrical Protection Certification System Standards MTBF	Yes Yes Yes Yes IP55 / IK10 Forced Air Cooling < 60dB Over/Under Voltage Protection, Over Current Protection, Over Temperature Protection, Surge Protection, Residual Current Protection CE / TUV IEC 61851-1/2017 100000 hours
Environment	Mounting Operation Temperature Relative Humidity Operating Altitude	Floor Mounted -30 C~+55 C 5%-95% <2000m
Dimensions & Mass	Product Dimension (W/H/D) Mass	820/1720/600mm, 145kg
Advertising Screen	Panel Size	55-inch

Panel Size Brightness (nits)

Active Area

Number of pixels Pixel Pitch

Power Consumption

Operating System

Display Colors

2500nit

1210(H)*680(V) 1920(H)*1080(V) pixels

16.7M(8bits-true)

245W(Typ.)

Windows

210(H)*RGB*630(V)um

COMMERCIAL ACHARGER.

JéGO Power - towerplug® PROMO AC commercial charging station (Advertising Version)

Reference number: REF 1013

GENERAL SPECIFICATIONS:

- 2x 22 kW
- 55 inch Advertising screen
- First multi-purpose AC charging station
- ROI in 2-3 years
- Advertising partner colaboration
- Customizable design (logo, color scheme, cable lenght, plug type)
- E-Flux by ROAD
- OCPP Connection
- Dynamic Load Balancing
- CE Certified
- 24 month warranty

With the towerplug® PROMO, Jego Power has invented a whole new dimension to charging. This floor-installed charger is equipped with a 55-inch advertising display, for CPOs to generate a secondary revenue stream with advertising while still offering a double 22kW output. The charger's color schemes and design can be customized to any occasion.

Moreover, the charger can also be controlled with the use of RFID cards and can be monitored via OCPP connection from for example E-Flux by ROAD.

