

The Oomnitza Connector

Oomnitza has created a unified connector, lovingly crafted using Python, which is a single application that can be used to pull data from multiple sources and push it to your Oomnitza application. The connector can presently pull data from the following sources, with more planned in the future.

- Airwatch <http://www.air-watch.com>
- BambhooHR <http://www.bamboohr.com>
- Casper <http://www.jamfsoftware.com/products/casper-suite/>
- Jasper <http://www.jasper.com>
- LDAP e.g., <http://www.openldap.org>, [Active Directory](#)
- MobileIron <http://www.mobileiron.com>
- Okta <https://www.okta.com>
- OneLogin <https://www.onelogin.com>
- SCCM <http://www.microsoft.com>
- ZenDesk <https://www.zendesk.com>

The Oomnitza Connector can be hosted on Oomnitza's server cloud, free of charge, if the third party server is or can be made accessible from the Oomnitza Cloud. Contact us for more details! Organizations with dedicated internal services may prefer to run this connector in-house, behind the same firewall that prevents outside access.

Getting Started

The most current version of this documentation can always be found on [GitHub](#).

Since Oomnitza is highly customizable, there are many possibilities with the connector. Because of this, it is important to think ahead about what data you want to bring in and how you want to store it. Before we begin, take time to think about what information you want, and what Oomnitza fields you want filled out with Casper data. If the fields you want to map in haven't been created yet, now is a good time to do so. (Refer to our [Guide to creating custom fields in Oomnitza](#) to get started.)

Getting the Connector

The Oomnitza Connector code is hosted at <https://github.com/Oomnitza/oomnitza-connector>.

The Oomnitza Connector can also be downloaded from within your Oomnitza instance. Log into your instance and navigate to the System Settings page. Scroll to the bottom of the Integrations page and download either the correct binary or the “Source Code” Package.

- If you will be hosting the connector on a Windows or Mac server, we recommend using the binary version.
- The Source Code package can be use on a Linux server, as well as Windows and Mac. This package requires that a python environment be setup properly, which the binary version avoids.

Runtime Environment Setup

If you choose to run the binary version of the connector, you can skip this section. If you choose to install and run the python code, you will need to install Python 2.7.X as well as the packages which the connector relies upon. Some of the python packages may require build tools to be installed.

Linux Environment

On Ubuntu, the build tools are installed using:

```
> sudo apt-get install build-essential
```

We suggest you setup a [virtual environment](#) and use pip to install the requirements. This can be done as follows (See our [documentation](#) on installing additional Python modules for use in Oomnitza.):

```
> cd /path/to/connector
> virtualenv .
> source bin/activate
> pip install --upgrade pip
> pip install -r requirements.txt
```

Windows Environment

ActiveState has an excellent Python package for Windows. It can be downloaded from <http://www.activestate.com/activepython/downloads>. You will need to install Python 2.7.X. Once this has been downloaded and installed, the remaining setup steps can be performed using PowerShell as an administrator. So, open PowerShell and do the following (feel free to replace c:\oomnitza-connector with the directory of choice):

```
> cd c:\
> mkdir oomnitza-connector
> cd oomnitza-connector
> virtualenv venv --no-setuptools
> venv\Scripts\activate
> Invoke-WebRequest https://raw.githubusercontent.com/pypa/pip/master/contrib/get-pip.py -
OutFile .\get-pip.py
> python get-pip.py
> pip install --upgrade pip
> pip install requests pyodbc pyparsing
> Invoke-WebRequest https://github.com/0omnitza/oomnitza-connector/archive/mast
er.zip -OutFile connector-master.zip
> Add-Type -A System.IO.Compression.FileSystem
> [IO.Compression.ZipFile]::ExtractToDirectory('c:\oomnitza-connector\connector
-master.zip', 'c:\oomnitza-connector\')
> cd oomnitza-connector-master
```

Running the connector

The connector is meant to be run from the command line and as such as multiple command

line options:

```
$ python connector.py
usage: connector.py [-h] [--show-mappings] [--testmode] [--save-data]
                  [--ini INI] [--logging-config LOGGING_CONFIG]
                  [--record-count RECORD_COUNT]
                  {upload,generate-ini,gui} [connectors [connectors ...]]
connector.py: error: too few arguments
(connector)daniels-mbp:Connector daniel$ python connector.py --help
usage: connector.py [-h] [--show-mappings] [--testmode] [--save-data]
                  [--ini INI] [--logging-config LOGGING_CONFIG]
                  [--record-count RECORD_COUNT]
                  {upload,generate-ini,gui} [connectors [connectors ...]]
```

positional arguments:

{upload,generate-ini,gui}	Action to perform.
connectors	Connectors to run.

optional arguments:

-h, --help	show this help message and exit
--show-mappings	Show the mappings which would be used by the connector.
--testmode	Run connectors in test mode.
--save-data	Saves the data loaded from other system.
--ini INI	Config file to use.
--logging-config LOGGING_CONFIG	Use to override logging config file to use.
--record-count RECORD_COUNT	Number of records to pull and process from connection.

The available actions are:

- **gui** (default): launch the config gui.
- **generate-ini** : generate an example config.ini file.

- **upload** : uploads the data from the indicated connectors to Oomnitza. The connector values are taken from the section names in the ini file.

--ini is used to specify which config file to load, if not provided, **config.ini** from the root directory will be used. This option can be used with the **generate-ini** action to specify the file to generate.

--logging-config is used to specify an alternate logging config file.

--show-mappings is used to print out the loaded mappings. These mappings can be a combination of the built-in mappings, config.ini mappings, and mappings setup via the website.

--testmode will print out the records which would have been sent rather than pushing the data to the server. This can be used to see what, exactly, is getting sent to the server.

--record-count is used to limit the number of records to process. Once this number have been processed, the connector will exit. This can be used with **--testmode** to print out a limited number of records then exit cleanly.

--save-data is used to save the data loaded from the remote system to disk. These files can then be used to confirm the data is being loaded and mapped as expected.

Setting the connector to run as an automated task

There are many ways to automate the sync, here are a few:

- OS X: http://www.maclife.com/article/columns/terminal_101_creating_cron_jobs
- OS X: <http://superuser.com/questions/126907/how-can-i-get-a-script-to-run-every-day-on-mac-os-x>
- OS X: <http://launched.zerowidth.com/>
- Linux: <http://www.cyberciti.biz/faq/how-do-i-add-jobs-to-cron-under-linux-or-unix-oses/>
- Windows: <http://bytes.com/topic/python/answers/32605-windows-xp-cron-scheduler->

Connector Configs

Now you should be able to generate a default config file. Running `python connector.py generate-ini` will regenerate the config.ini file, and create a backup if the file already exists. When you edit this file, it will have one section per connection. You can safely remove the section for the connections you will not be using to keep the file small and manageable.

If you require multiple different configurations of a single connector, such as the need to pull from two different LDAP OUs, additional sections can be added by appending a '.' and a unique identifier to the section name. For example, having both a `[ldap]` and `[ldap.Contractors]` section will allow you to pull users from a default and Contractor OU.

An example generated config.ini follows.

```
[oomnitza]
url = https://example.oomnitza.com
api_token =
username = oomnitza-sa
password = ThePassword

[airwatch]
enable = False
url = https://apidev.awmdm.com
username = username@example.com
password = change-me
api_token = YOUR AirWatch API TOKEN
sync_field = 24DCF85294E411E38A52066B556BA4EE

[bamboohr]
enable = False
url = https://api.bamboohr.com/api/gateway.php
system_name = YOUR BambooHR SYSTEM NAME
api_token = YOUR BambooHR API TOKEN
default_role = 25
```

[casper]

enable = False

url = https://jss.jamfcloud.com/example

username = username@example.com

password = change-me

sync_field = 24DCF85294E411E38A52066B556BA4EE

sync_type = computers

update_only = False

[jasper]

enable = False

wsdl_path = http://api.jasperwireless.com/ws/schema/Terminal.wsdl

username = username@example.com

password = change-me

storage = storage.db

api_token = YOUR Jasper API TOKEN

sync_field = 24DCF85294E411E38A52066B556BA4EE

update_only = False

[ldap]

enable = False

url = ldap://ldap.forumsys.com:389

username = cn=read-only-admin,dc=example,dc=com

password =

base_dn = dc=example,dc=com

protocol_version = 3

filter = (objectClass=*)

default_role = 25

default_position = Employee

[mobileiron]

enable = False

url = https://na1.mobileiron.com

username = username@example.com

```
password = change-me
partitions = ["Drivers"]
sync_field = 24DCF85294E411E38A52066B556BA4EE
```

[okta]

```
enable = False
url = https://example-admin.okta.com
api_token = YOUR Okta API TOKEN
default_role = 25
default_position = Employee
```

[onelogin]

```
enable = False
url = https://app.onelogin.com/api/v2/users.xml
api_token = YOUR OneLogin API TOKEN
default_role = 25
default_position = Employee
```

[sccm]

```
enable = False
server = server.example.com
database = CM_DCT
username = change-me
password = change-me
authentication = SQL Server
sync_field = 24DCF85294E411E38A52066B556BA4EE
```

[zendesk]

```
enable = False
system_name = oomnitza
api_token = YOUR Zendesk API TOKEN
username = username@example.com
default_role = 25
default_position = Employee
```


The **[oomnitza]** section is where you configure the connector with the URL and login credentials for connecting to Oomnitza. You can use an existing user's credentials for username and password, but best practice is to create a service account using your standard naming convention. (See the (documentation)[<http://docs>] for managing user accounts in Oomnitza.)

The remaining sections each deal with a single connection to an external service. The "enable" field is common to all connections and if set to "True" will enable this service for processing. Some fields are common to a type of connection. For example, "default_role" and "default_user" are fields for connections dealing with loading People into the Oomnitza app.

Each section can end with a list of field mappings. Simple mappings which just copy a field from the external system to a field inside Oomnitza can be defined here or in the System Settings within Oomnitza. Simple mappings are as follows:

```
mapping.[Oomnitza Field] = {"source": "[external field]"}
```

For fields which require processing before being brought into Oomnitza must be defined in the INI. These mappings are more involved. Please contact support@oomnitza.com for more information. The format is:

```
mapping.[Oomnitza Field] = {"source": "[external field]", "converter": "[converter name]"}
```

Oomnitza Configuration

url : the url of the Oomnitza application. For example: **<https://example.oomnitza.com>**

username : the Oomnitza username to use

password : the Oomnitza password to use

env_password : (optional) the name of the environment variable containing the password value to use. The **password** field will be ignored.

api_token : The API Token belonging to the Oomnitza user. If provided, **password** must be left blank.

Airwatch Configuration

url : the url of the Airwatch server

username : the Airwatch username to use

password : the Airwatch password to use

env_password : (optional) the name of the environment variable containing the password value to use. The **password** field will be ignored.

api_token : HPDL

sync_field : The Oomnitza field which contains the asset's unique identifier (we typically recommend serial number).

Default Field Mappings

To Be Determined

BambooHR Configuration

url : the url of the BambooHR server

system_name : hpdl

api_token : hpdl

default_role = 25

Default Field Mappings

```
mapping.USER = {'source': "workEmail"}
mapping.FIRST_NAME' = {'source': "firstName"}
mapping.LAST_NAME' = {'source': "lastName"}
mapping.EMAIL' = {'source': "workEmail"}
mapping.PHONE' = {'source': "mobilePhone"}
mapping.POSITION' = {'source': "jobTitle"}
mapping.PERMISSIONS_ID' = {'setting': "default_role"}
```

Casper Configuration

The `[casper]` section contains a similar set of preferences; your JSS URL, and the login credentials for an auditor account in Casper (See the [Casper Suite Administrator's Guide](#), pg. 42).

The identifier section of the config.ini file should contain a mapping to a unique field in Oomnitza, which you want to use as the identifier for an asset. Serial Number is the most commonly used identifier since no two assets should share one. This will determine if the script creates a new record for a given serial number on its next sync, or if it updates an existing record that has new information.

`url` : the url of the Casper server

`username` : the Casper username to use

`password` : the Casper password to use. Note: the Casper API will **NOT** work with a password which contains `%` or `*`. `!` is an acceptable character to use.

`env_password` : (optional) the name of the environment variable containing the password value to use. The `password` field will be ignored.

`sync_field` : The Oomnitza field which contains the asset's unique identifier (we typically recommend serial number).

`sync_type` : Sets the type of data to pull from Casper. Options are `computers` or

mobiledevices . When syncing mobile devices a second section should be added to your config.ini file named **[casper.MDM]** and this value should be set to **mobiledevices** .

group_name : Specifies the Group from which to load assets. If **group_name** is missing or empty, all assets will be loaded. If present, only assets from this Group will be processed.

verify_ssl : set to false if the Casper server is running with a self signed SSL certificate.

update_only : set this to True to only update records in Oomnitza. Records for new assets will not be created.

Default Field Mappings

To Be Determined

Jasper Configuration

wSDL_path : The full URL to the Terminal.wsdl. Defaults to:
<http://api.jasperwireless.com/ws/schema/Terminal.wsdl>.

username : the Jasper username to use

password : the Jasper password to use

env_password : (optional) the name of the environment variable containing the password value to use. The **password** field will be ignored.

storage : The path to the storage file used to maintain state about the connector. Defaults to: **storage.db**

api_token : The Jasper API Token.

sync_field : The Oomnitza field which contains the asset's unique identifier.

update_only : set this to True to only update records in Oomnitza. Records for new assets will not be created.

Default Field Mappings

To Be Determined

LDAP Configuration

url : The full URI for the LDAP server. For example: `ldap://ldap.forumsys.com:389`

username : the LDAP username to use. Can be a DN, such as `cn=read-only-admin,dc=example,dc=com`.

password : the LDAP password to use

env_password : (optional) the name of the environment variable containing the password value to use. The **password** field will be ignored.

base_dn : The Base DN to use for the connection.

protocol_version : The LDAP Protocol version to use. Defaults to: 3.

filter : The LDAP filter to use when querying for people. For example: `(objectClass=*)` will load all objects under the `base_db`. This is a very reasonable default.

default_role : The numeric ID of the role which will be assigned to imported users. For example: `25`.

default_position : The position which will be assigned to the user. For example: `Employee`.

MobileIron Configuration

url : The full URI for the MobileIron server. For example: `https://na1.mobileiron.com`

username : the MobileIron username to use.

password : the MobileIron password to use.

env_password : (optional) the name of the environment variable containing the password value to use. The **password** field will be ignored.

partitions : The MobileIron partitions to load. For example: **["Drivers"]** or **["PartOne", "PartTwo"]**

sync_field : The Oomnitza field which contains the asset's unique identifier.

Default Field Mappings

To Be Determined

Okta Configuration

url : The full URI for the Okta server. For example: **https://oomnitza-admin.okta.com**

api_token : The Jasper API Token.

default_role : The numeric ID of the role which will be assigned to imported users. For example: **25** .

default_position : The position which will be assigned to the user. For example: **Employee** .

Default Field Mappings

mapping.USER =	{'source': "login"},
mapping.FIRST_NAME =	{'source': "firstName"},
mapping.LAST_NAME =	{'source': "lastName"},
mapping.EMAIL =	{'source': "email"},
mapping.PHONE =	{'source': "mobilePhone"},
mapping.PERMISSIONS_ID =	{'setting': "default_role"},
mapping.POSITION =	{'setting': "default_position"},

OneLogin Configuration

url : The full URI for the OneLogin server. For example:

`https://app.onelogin.com/api/v2/users.xml`

api_token : The OneLogin API Token.

default_role : The numeric ID of the role which will be assigned to imported users. For example: `25` .

default_position : The position which will be assigned to the user. For example: `Employee` .

Default Field Mappings

mapping.USER =	{'source': "username"}
mapping.FIRST_NAME =	{'source': "firstname"}
mapping.LAST_NAME =	{'source': "lastname"}
mapping.EMAIL =	{'source': "email"}
mapping.PHONE =	{'source': "phone"}
mapping.PERMISSIONS_ID =	{'setting': "default_role"}
mapping.POSITION =	{'setting': "default_position"}

SCCM Configuration

The account used to connect to the SCCM database requires at least read-only access. **Note:** The SCCM connector currently requires a Windows host. While it should be possible to run the connector on a non-Windows host, such as Linux, we do not provide support for this configuration at this time.

server : The server hosting the SCCM database.

database : The SCCM database from which to pull data.

username : The username to use when connecting to the server using `SQL Server` authentication. This user requires read-only access to the DB. Ignored when using `Windows`

authentication.

password : The password to use when connecting to the server using **SQL Server** authentication. Ignored when using **Windows** authentication.

env_password : (optional) the name of the environment variable containing the password value to use. The **password** field will be ignored.

authentication : Sets the type of authentication to use when connecting to the server. Options are **SQL Server** or **Windows** . The default is to use SQL Server Authentication. When using **Windows** authentication, the **username** and **password** fields are ignored and the credentials for the currently logged in user will be used when making the connection to the SCCM database.

sync_field : The Oomnitza field which contains the asset's unique identifier (we typically recommend serial number).

Default Field Mappings

To Be Determined

Zendesk Configuration

system_name : The Zendesk system name to use. For example: **oomnitza**

api_token : The Zendesk API Token.

username : the Zendesk username to use.

default_role : The numeric ID of the role which will be assigned to imported users. For example: **25** .

default_position : The position which will be assigned to the user. For example: **Employee** .

Default Field Mappings


```
mapping.USER = {'source': "email"}
mapping.FIRST_NAME = {'source': "name", 'converter': "first_from_full"}
mapping.LAST_NAME = {'source': "name", 'converter': "last_from_full"}
mapping.EMAIL = {'source': "email"}
mapping.PHONE = {'source': "phone"}
mapping.PERMISSIONS_ID = {'setting': "default_role"}
mapping.POSITION = {'setting': "default_position"}
```

Advanced usage

Logging

The Oomnitza Connector uses the standard python `logging` module. This module is configured via the `logging.json` file. This file can be edited, or copied to a new file, to change the logging behavior of the connector. Please see the [python docs](#) for information of configuring python logging.

SSL Protocol Version

If the service to be connected to requires a particular SSL protocol version to properly connect, the connection's section in the ini file can include a `ssl_protocol` option. The value can be one of: `ssl`, `sslv23`, `sslv3`, `tls`, `tls1`.

Record Filtering

Support has been added for filtering the records passed from the connector to Oomnitza. By default, all records from the remote system will be sent to Oomnitza for processing. To limit the records based on values in those records, a special `recordfilter` value can be added to a connector section in the ini file. This filter is written using the Python programming language.

For example, the following filter will only process records with the `asset_type` field set to `"computer"`:

```
recordfilter:
```

```
    return record.asset_type == "computer"
```

This is a very new feature, with many options, and we are still working on the documentation.

If you are interested in using this feature, please contact support@oomnitza.com for assistance.

The GUI

This section is under construction