Parallel K-Means Clustering Using Apache Spark: Implementation and Performance Evaluation

Abstract

K-Means is a widely used unsupervised clustering method, but its repeated assignment and centroid-update steps can become expensive as datasets grow. This project implements a research-inspired, partition-based Parallel K-Means workflow using Apache Spark: local clustering produces candidate centers, which are aggregated to initialize distributed global refinement. We evaluate the approach in two distinct studies: 18 historical repeated synthetic scalability runs using 10,000 and 50,000 observations with 20 features, and 42 controlled runs on labeled 1,000-record synthetic and KDD99 samples (36 Spark and six traditional K-Means runs, using seeds 42–44). All Spark local[n] configurations ran on a single computer, not a multi-node cluster.

For the historical 50,000-record synthetic dataset, mean runtime fell from 116.765 s with local[1] to 39.918 s with local[4] (approximately 2.925× within-Spark speedup). In the separate controlled study with four partitions, local[4] improved mean clustering runtime relative to local[1] by 1.6985× on synthetic data and 1.5748× on KDD99. The synthetic Spark configuration achieved mean ARI and NMI of 1.000, whereas KDD99 agreement with reference labels remained weak (ARI 0.055; NMI 0.080). Traditional single-process K-Means was faster on both 1,000-record datasets; differences in initialization and restart procedures prevent attributing clustering-quality differences solely to parallelism. These findings support limited single-machine parallel scaling claims, not general superiority over traditional K-Means or verified multi-node scalability.

Introduction

The increasing availability of large datasets has created a need for data analysis methods that can process information efficiently. Clustering is an unsupervised learning technique used to identify groups of similar observations without requiring predefined class labels. One commonly used clustering method is K-Means, which assigns observations to clusters and repeatedly updates their centers to reduce within-cluster variation.

Although traditional K-Means is relatively straightforward to implement, its computational requirements can become significant as the number of observations and features increases. Each iteration requires assigning observations to their nearest cluster centers and updating those centers. For sufficiently large datasets, these repeated calculations can increase execution time and create challenges for systems with limited computing resources.

Parallel processing offers a potential approach to addressing these challenges. By distributing calculations across multiple processing units, a clustering algorithm may reduce execution time while preserving the quality of its results. Apache Spark provides a framework for parallel data processing through distributed data structures and operations, including Resilient Distributed Datasets (RDDs), partition transformations, broadcast variables, and keyed reductions.

This project investigates a Spark-based Parallel K-Means implementation inspired by the research paper *Big Data Clustering Method Based on Parallel K-Means* by Liu et al. [1]. The original study presents a parallel clustering approach designed for large datasets. Our project adapts its partition-based clustering and global refinement concepts into a custom Python and PySpark implementation.

The implemented algorithm first performs K-Means independently within Spark partitions. The resulting local cluster centers are collected and aggregated to initialize a global clustering model. Distributed iterations then assign observations to their nearest centers, combine cluster statistics, and update the global centers until a stopping criterion is satisfied.

To evaluate this approach, we conduct experiments using synthetic datasets containing 10,000 and 50,000 observations, each with 20 numerical features and five underlying clusters. We compare Spark execution configurations using one, two, and four local worker threads. We also implement a conventional single-process K-Means baseline to examine differences in runtime, initialization behavior, and clustering quality.

The evaluation focuses on execution time, parallel speedup, sum of squared errors (SSE), and convergence behavior. Particular attention is given to whether increasing local parallelism reduces execution time without substantially changing clustering quality.

In addition to the historical 10,000- and 50,000-record synthetic scalability experiments, we completed a separate controlled evaluation on 1,000-record synthetic and KDD99 samples. Across 42 controlled runs, we compared Spark local[1], local[2], and local[4] configurations with a traditional single-process K-Means baseline, reporting runtime, within-Spark speedup, adjusted Rand index (ARI), normalized mutual information (NMI), and related quality measures. The two studies are kept separate because their datasets and experimental protocols differ.

Unlike the original research paper's multi-node experimental environment, our experiments run on a single Apple Silicon computer using Spark local mode. Consequently, the reported findings characterize single-machine parallel execution rather than performance across multiple physical computing nodes.

The primary contribution of this project is a reproducible implementation and experimental evaluation of a partition-based Parallel K-Means approach. The project also documents important differences between the research paper and our implementation, including initialization choices, experimental scale, timing boundaries, and hardware limitations.

Related Work

Traditional K-Means Clustering

K-Means is a widely used unsupervised learning algorithm that partitions a dataset into a specified number of clusters. The algorithm repeatedly assigns each observation to its nearest cluster center and recalculates the centers using the observations assigned to each cluster. This

iterative procedure seeks to reduce the sum of squared distances between observations and their assigned centers.

The classical K-Means approach is closely associated with the work of Lloyd [2]. Its simplicity makes it useful for many clustering applications. However, the repeated assignment and center-update operations can become computationally expensive as dataset size increases.

Traditional K-Means is also sensitive to initialization. Different starting centers can produce different final clustering solutions because the algorithm may converge to a local minimum rather than the globally optimal clustering.

K-Means++ Initialization

Arthur and Vassilvitskii introduced K-Means++ as an improved initialization method for K-Means [3]. Instead of choosing every initial center uniformly at random, K-Means++ selects subsequent centers using probabilities related to the squared distance from the nearest previously selected center.

This approach encourages the selection of initially well-separated centers and can improve clustering quality compared with less carefully chosen starting points.

Initialization is particularly relevant to our project because the traditional baseline and parallel implementation use different procedures for selecting their initial global centers. Consequently, clustering quality and runtime comparisons must account for these differences.

Scalable K-Means++ and Large-Scale Clustering

Bahmani et al. proposed Scalable K-Means++, commonly associated with the K-Means|| initialization approach, to address limitations of sequential K-Means++ initialization on large datasets [4].

The method uses an oversampling strategy that can reduce the number of sequential passes required during initialization. This research demonstrates that initialization itself is an important consideration when designing clustering methods for large-scale data processing.

Our implementation does not reproduce K-Means||. Instead, it uses partition-level clustering to generate candidate centers and aggregates those candidates to initialize the global model. Scalable K-Means++ is included as related research rather than as a component we implemented.

Parallel K-Means Using Apache Spark

Liu et al. presented a parallel K-Means approach designed for large datasets [1]. Their method uses partition-based processing, local clustering, center aggregation, and global refinement to support clustering in a parallel computing environment.

The paper provides the primary research foundation for our project. We adapt its general workflow into a custom Python and PySpark implementation, using Spark partitions for local clustering and distributed operations for global center updates.

Apache Spark supports operations such as partition transformations, broadcast variables, and keyed reductions. These capabilities provide mechanisms for processing partitioned data and combining intermediate clustering statistics [5].

Our implementation uses these mechanisms to perform local clustering and global refinement. However, it differs from the original study in several respects, including initialization details, experimental datasets, execution environment, and timing boundaries.

The original research includes experiments in a distributed computing environment. Our evaluation uses Spark local mode on a single Apple Silicon computer. Therefore, our results examine the effect of local parallelism rather than demonstrating scalability across multiple physical computing nodes.

Research Gap and Project Contribution

Previous research establishes the importance of efficient clustering, careful initialization, and parallel processing for large datasets. Building on these ideas, our project investigates whether a partition-based Spark implementation can reduce execution time while maintaining comparable clustering quality under controlled experimental conditions.

The project contributes a reproducible implementation, a traditional K-Means baseline, and experimental comparisons across Spark local configurations. It also documents the limitations of interpreting performance results when algorithms use different initialization procedures or operate under different hardware conditions.

Original Research Paper and Implementation Comparison

Research Foundation

Our project is inspired by *Big Data Clustering Method Based on Parallel K-Means* by Liu et al. [1]. The paper investigates how parallel processing can improve the efficiency of K-Means clustering for large datasets.

The proposed approach combines partition-level clustering with global refinement. Rather than relying exclusively on a traditional single-process clustering procedure, the algorithm distributes selected operations across a parallel processing environment.

Our implementation follows the general research direction of the paper while adapting several algorithmic and experimental details to our available hardware and software environment.

Comparison of the Original Method and Our Implementation

Table 1. Comparison of the Original Research Paper and Our Implementation

Component	Original Research Paper [1]	Our Implementation
Main objective	Improve large-scale clustering	Evaluate a partition-based Spark K-

Component	Original Research Paper [1]	Our Implementation
	through parallel K-Means	Means implementation
Processing framework	Apache Spark	Python and PySpark RDD operations
Data partitioning	Data distributed across partitions	Spark RDD partitioning
Local clustering	K-Means performed on partitioned data	Custom K-Means executed within partitions
Local initialization	Partition-level initialization procedure	K-Means++ initialization within local clustering
Candidate centers	Local clustering results combined for global initialization	Local candidate centers aggregated using deterministic restarts
Global assignment	Parallel cluster assignment	Distributed nearest-center assignment
Global aggregation	Parallel combination of clustering statistics	Spark keyed reductions using reduceByKey
Center distribution	Cluster centers made available to parallel workers	Spark broadcast variables
Convergence	Global stopping criterion	Absolute change in successive SSE values
Datasets	KDD Cup99 and large synthetic data	Synthetic datasets with 10,000 and 50,000 records
Features	Dataset-dependent	20 numerical features
Number of clusters	Dataset-dependent	Five clusters
Computing environment	Distributed computing environment	Single Apple Silicon computer using Spark local mode
Evaluation	Execution time and clustering quality	Runtime, speedup, SSE, and convergence
Traditional baseline	Traditional K-Means	Custom single-process K-Means with initialization variants

Implementation Similarities

Both approaches use partition-based processing to perform local clustering before global refinement. This design allows local computations to contribute candidate cluster centers for the subsequent global clustering process.

Our implementation also follows the broader idea of distributing assignment and aggregation operations rather than processing every iteration entirely within a conventional single-process algorithm.

These similarities establish the connection between the research paper and our implementation.

Implementation Differences

Our implementation is not a line-by-line reproduction of the original algorithm. We use custom Python clustering functions, K-Means++ local initialization, deterministic candidate-center aggregation restarts, and an SSE-based stopping criterion.

The experimental environments also differ substantially. The original paper investigates parallel clustering using larger datasets and distributed computing resources. Our experiments evaluate Spark local configurations on one computer.

Additionally, our synthetic datasets are smaller than those used in the original paper. We therefore do not claim to reproduce its large-scale experimental results.

Interpretation of Experimental Comparisons

Because the two studies use different datasets, computing environments, implementation details, and timing boundaries, their raw execution times and SSE values should not be treated as directly comparable measurements.

Our analysis instead focuses on comparisons within our own controlled experimental environment.

In particular, we evaluate how increasing local Spark parallelism affects execution time and whether clustering quality remains consistent across configurations.

We also compare our parallel implementation with a traditional K-Means baseline. However, differences in initialization procedures and computational workloads mean that these comparisons require careful interpretation.

Reproduction Scope

The project should be understood as a research-inspired implementation and experimental evaluation of Parallel K-Means using Apache Spark.

It demonstrates several important concepts from the original paper, including local clustering, center aggregation, distributed global updates, and iterative convergence.

It does not establish that the original paper’s complete experimental results have been independently reproduced.

---

1. Research Objective and Experimental Design

This project investigates the performance and clustering behavior of a Spark-based Parallel K-Means implementation inspired by the research paper *Big Data Clustering Method Based on Parallel K-Means* by Liu et al. [1].

The primary objective is to evaluate whether parallelizing K-Means operations improves execution time as dataset size increases while maintaining comparable clustering quality.

To investigate this question, we implemented a Parallel K-Means pipeline using Apache Spark. The implementation performs local clustering within individual Spark partitions, combines the resulting candidate centers to initialize the global model, and then performs distributed global clustering.

We also implemented a conventional, single-process K-Means baseline to examine differences in initialization behavior, clustering quality, and runtime. Because the baseline and parallel implementations use different initialization procedures, we interpret their runtime results cautiously rather than treating them as directly equivalent workloads.

Our experimental evaluation focuses on three main areas:

1. **Execution time:** Measuring the time required to complete the clustering pipeline under different Spark local execution configurations.
2. **Parallel scalability:** Evaluating how runtime changes when Spark is configured with one, two, or four local worker threads.
3. **Clustering quality:** Comparing the sum of squared errors (SSE) produced by the algorithms and verifying whether parallel execution preserves clustering quality.

The principal scalability experiments use synthetic datasets containing 10,000 and 50,000 records. Each dataset has 20 numerical features and five underlying clusters.

All scalability experiments are performed on a single Apple Silicon computer using Apache Spark in local mode. Therefore, the results measure single-machine parallel execution rather than performance across multiple physical cluster nodes.

For reproducibility, the experiments use controlled random seeds, fixed clustering parameters, repeated measurements, and an initial unmeasured warm-up run for each Spark-master process before its benchmark matrix.

The evaluation also considers limitations associated with initialization strategies, memory requirements, the number of experimental repetitions, and the use of synthetic data.

2. Parallel K-Means Algorithm and Implementation

2.1 Overview

Our implementation follows a partition-based initialization and distributed refinement strategy inspired by Liu et al. [1]. Instead of calling Spark MLlib's K-Means estimator, the project

implements the clustering operations explicitly in Python and PySpark. The process has three principal stages: local clustering within Spark partitions, aggregation of candidate centers, and global refinement across the distributed dataset.

2.2 Nine-Step Algorithm

1. **Prepare the input.** Generate a numerical dataset with a specified number of observations, features, clusters, and random seed. Construct a Spark RDD with a fixed partition count.
2. **Partition the observations.** Distribute the RDD across four Spark partitions for the reported scalability experiments.
3. **Cluster within each partition.** Use mapPartitionsWithIndex to run local K-Means independently on each nonempty partition. Each local run uses seeded K-Means++ initialization and squared Euclidean distance.
4. **Collect candidate centers.** Return the local centers from the partition workers to the driver. With four nonempty partitions and five local clusters each, the expected candidate pool contains 20 centers.
5. **Aggregate candidate centers.** Run local K-Means on the collected centers using five deterministic initialization restarts. Select the candidate-center solution with the lowest aggregation SSE to initialize the global model. These candidate centers are **not weighted by their originating partition's population**.
6. **Broadcast global centers.** Distribute the current global centers to Spark workers using a broadcast variable for each global refinement iteration.
7. **Assign points and aggregate statistics.** Assign each observation to its nearest center, then use reduceByKey to combine coordinate sums, point counts, and SSE contributions by cluster.
8. **Update and check convergence.** Compute updated global centers from the aggregated sums and counts. Repeat distributed assignment and updating until the absolute change in consecutive-iteration SSE is at most 1e-6, or 100 global iterations have been reached.
9. **Evaluate final centers.** Run a final distributed evaluation using the returned centers to calculate final SSE and cluster counts. Record convergence information, iteration counts, and phase runtimes.

This is a nine-step description of **our implementation**, not a claim that every implementation detail exactly reproduces the paper.

2.3 Objective Function and Center Updates

K-Means minimizes the within-cluster sum of squared Euclidean distances:

$$SSE = \sum_{i=1}^{n} \left\| x_i - \mu_{c(i)} \right\|_2^2,$$

where x_i is observation i, c(i) is its assigned cluster, and μ denotes a cluster center. For a nonempty cluster j, its updated center is the arithmetic mean of assigned observations:

$$\mu_j = \frac{1}{|C_j|} \sum_{x_i \in C_j} x_i.$$

The distributed implementation calculates these means from aggregated coordinate sums and counts rather than collecting all assigned observations at the driver.

2.4 Local and Global Stopping Criteria

Local K-Means uses a maximum **squared center shift** threshold of 1e-6. Global K-Means uses an **absolute change in consecutive-iteration SSE** threshold of 1e-6. Both stages allow at most 100 iterations. Although the tolerances share a numerical value, they are applied to different quantities and should not be interpreted as identical convergence tests.

During global refinement, the SSE recorded for each iteration is calculated using the cluster centers before that iteration's center update. After the stopping criterion is satisfied or the iteration limit is reached, a separate distributed evaluation calculates the final SSE and cluster counts using the final updated centers. This ensures that the reported clustering quality corresponds to the returned model.

2.5 Implementation Mapping

Table 2. Parallel K-Means Implementation Components

Stage	Primary source file
Local K-Means, distance calculations, initialization	src/parallel/local_kmeans.py
Partition-level execution	src/parallel/partition_clustering.py
Candidate-center aggregation	src/parallel/center_aggregation.py
Distributed assignment and reduction	src/parallel/global_iteration.py
Global iteration loop and evaluation	src/parallel/global_kmeans.py
End-to-end algorithm orchestration	src/parallel/parallel_kmeans.py
Dataset generation and benchmark	src/experiments/synthetic_data.py, src/experiments/experiment_runner.py

Stage	Primary source file
configuration	
RDD persistence and benchmark lifecycle	src/experiments/benchmark_runner.py

2.6 Implementation Constraints

The partition-level routine materializes each nonempty partition in its worker process before local clustering. This simplifies local K-Means but creates a memory constraint for large partitions. The aggregation stage also collects candidate centers to the driver, and the candidate centers are treated equally rather than being weighted by the number of original observations they represent. These choices are documented limitations, especially when extending the approach to imbalanced or substantially larger datasets.

The Spark operations used here—partition transformations, broadcast variables, keyed reductions, and RDD persistence—are documented in the Apache Spark RDD Programming Guide.

3. Experimental Setup and Dataset Description

3.1 Hardware and Software Environment

The experiments were conducted on a single Apple Silicon MacBook Air equipped with an Apple M2 processor and 8 GB of unified memory. The implementation uses Python, PySpark, and Apache Spark, with Java providing the runtime required by Spark.

The experimental environment uses a project-specific Python virtual environment to manage dependencies and maintain consistency across executions.

Apache Spark was configured in local execution mode using three master settings:

- local[1]: One local worker thread.
- local[2]: Two local worker threads.
- local[4]: Four local worker threads.

Each configuration runs on the same physical computer. Consequently, the experiments evaluate local parallel scalability rather than distributed performance across multiple machines.

The number of Spark RDD partitions was held constant at four in the principal scalability experiments. This isolates the effect of changing the local worker-thread configuration while keeping the partition count unchanged.

3.2 Synthetic Dataset Generation

The principal experiments use reproducible synthetic datasets generated by the project’s custom Python implementation in src/experiments/synthetic_data.py.

The generator constructs a specified number of cluster centers and creates observations by adding Gaussian noise around those centers. Cluster membership is assigned during generation, and records are distributed as evenly as possible among the requested clusters.

The principal dataset configurations contain:

Table 3. Experimental Dataset and Environment Settings

Parameter	Experimental setting
Dataset sizes	10,000 and 50,000 records
Numerical features	20
Ground-truth clusters	5
Gaussian noise standard deviation	1.0
Center separation parameter	10.0
Spark RDD partitions	4
Measured random seeds	42, 43, and 44

The synthetic generator uses Python's seeded random-number generator, allowing the same dataset to be reconstructed from identical parameters and a matching random seed.

This benchmark dataset is distinct from the separate dataset-preparation pipeline in src/data/datasets.py, which uses scikit-learn's make_blobs function and includes feature standardization. The principal scalability measurements described here use the custom generator rather than that separate pipeline.

3.3 Experimental Parameters

The Parallel K-Means experiments use a controlled configuration across the tested Spark local execution settings.

Table 4. Algorithm and Benchmark Parameters

Parameter	Value
Number of clusters (k)	5
Local K-Means maximum iterations	100
Global K-Means maximum iterations	100
Local convergence tolerance	1e-6
Global SSE-change tolerance	1e-6
Candidate-center aggregation restarts	5

Parameter	Value
Measured repetitions per configuration	3
Initial unmeasured warm-up runs per Spark-master process	1

The local and global convergence tolerances are applied to different quantities. The local stage checks the maximum squared movement of cluster centers, whereas the global stage checks the absolute change in SSE between consecutive iterations.

Candidate-center aggregation uses five deterministic initialization attempts and selects the candidate-center clustering result with the lowest SSE.

3.4 Repetitions and Reproducibility

Each principal benchmark configuration was executed three times using random seeds 42, 43, and 44.

The repeated-experiment runner begins with the configured base seed and increments it by one for each subsequent measured repetition. This provides controlled variation while making individual runs reproducible.

For each Spark-master process, an initial unmeasured warm-up run is performed before the benchmark matrix begins. The warm-up is not repeated before every individual dataset-size configuration.

The benchmark orchestration executes the local master configurations in separate processes. This helps separate their Spark execution environments and avoids treating different master settings as simultaneous workloads.

Measured results are written to CSV files containing experimental metadata, clustering outcomes, and timing measurements. These files provide the basis for comparing runtime and clustering quality across configurations.

3.5 Benchmark Execution and Timing Boundaries

The in-memory synthetic benchmark follows a consistent sequence:

1. Generate the synthetic dataset using the specified configuration and seed.
2. Construct a Spark RDD with the required partition count.
3. Persist the RDD.
4. Execute an RDD count action to materialize the dataset before clustering begins.
5. Run the complete Parallel K-Means clustering pipeline.
6. Collect the resulting clustering metrics and execution timings.
7. Release the persisted RDD after the benchmark.

The clustering timer excludes synthetic-data generation, initial RDD creation, and initial RDD materialization. Therefore, the reported runtime represents the measured clustering pipeline rather than the complete end-to-end cost of preparing the input dataset.

The implementation records phase-level timings for partition clustering, candidate-center aggregation, initialization, global iteration, and final evaluation. The total measured pipeline runtime is used for the principal historical scalability comparison.

Apache Spark's RDD persistence mechanism allows an RDD to be reused across operations. In this implementation, the initial count action materializes the persisted dataset before the clustering measurements begin.

3.6 Experimental Scope and Limitations

The principal scalability evaluation uses two synthetic dataset sizes and three measured repetitions per Spark-master configuration. These measurements provide an initial assessment of local parallel performance but do not establish behavior across all dataset sizes, hardware configurations, or distributed computing environments.

Because the experiments run on one computer, the observed speedups should not be interpreted as evidence of equivalent scaling across multiple physical cluster nodes.

The synthetic datasets contain deliberately structured Gaussian clusters. Results on these datasets may differ from results on real-world data containing irregular cluster shapes, noise, missing values, or highly imbalanced cluster populations.

A separate project dataset plan includes KDD Cup 99 preprocessing and a scikit-learn-based synthetic-data pipeline. Those planned datasets should not be presented as completed clustering benchmarks unless corresponding execution results have been verified.

Finally, the custom partition-level K-Means implementation materializes each partition within a worker process, which can limit scalability when partitions become too large for the available memory. Candidate-center aggregation also treats candidate centers equally rather than weighting them by their original partition populations.

These constraints are considered when interpreting the experimental results and identifying possible improvements.

4. Traditional K-Means Baseline and Comparison Design

4.1 Purpose of the Baseline

To provide a reference for evaluating the Spark-based Parallel K-Means implementation, we implemented a conventional single-process K-Means baseline.

The baseline processes the complete synthetic dataset within one Python process without using Apache Spark, distributed partitions, or parallel center aggregation.

Its primary purpose is to evaluate clustering quality, initialization behavior, and execution time under a conventional K-Means approach.

Because the traditional and parallel implementations use different initialization procedures, their runtime results are interpreted as descriptive comparisons rather than strictly equivalent computational workloads.

4.2 Traditional K-Means Implementation

The traditional baseline is implemented in scripts/run_traditional_kmeans.py.

It uses the project's existing local K-Means implementation from src/parallel/local_kmeans.py, applying the algorithm directly to the complete dataset.

The baseline follows these operations:

1. Generate a deterministic synthetic dataset using the specified configuration and random seed.
2. Initialize the cluster centers using the local K-Means implementation.
3. Assign observations to their nearest cluster centers.
4. Recalculate cluster centers using the arithmetic mean of assigned observations.
5. Repeat assignment and center updates until the stopping criterion or maximum iteration count is reached.
6. Calculate the final sum of squared errors (SSE).
7. Record convergence status, iteration count, cluster membership counts, and execution time.

The baseline uses a maximum of 100 iterations and a local squared-center-shift tolerance of 1e-6.

4.3 Initialization Strategies

We evaluated two traditional K-Means configurations.

Single initialization: K-Means is executed once using the designated random seed.

Five initializations: K-Means is executed five times on the same dataset using deterministic initialization seeds. The result with the lowest SSE is retained.

The five-initialization configuration helps assess the effect of initialization on clustering quality.

In the traditional baseline, each initialization processes the full dataset. In contrast, the Spark implementation performs partition-level clustering and applies multiple restarts to the smaller collection of candidate centers.

Therefore, five traditional initializations and five Spark aggregation restarts should not be interpreted as identical computational effort.

4.4 Baseline Benchmark Procedure

The baseline experiments use synthetic datasets with 10,000 observations, 20 numerical features, and five clusters.

The repeated comparison uses random seeds 42 through 46, producing five measured runs for each traditional initialization configuration.

An unmeasured warm-up run is executed before the recorded repetitions for each dataset size.

For each measured run, the dataset is generated before the runtime timer starts. The recorded runtime includes the configured K-Means initialization attempts and clustering computations, but excludes synthetic dataset generation and the subsequent calculation of cluster membership counts.

The baseline results are stored in:

- results/raw/stage-9d6-traditional-10k-repeated.csv
- results/raw/stage-9d7-traditional-10k-five-inits.csv

4.5 Comparison Metrics

The traditional and parallel implementations are evaluated using the following metrics.

Execution time: The recorded time required to perform the clustering computation.

Sum of squared errors (SSE): The total squared distance between each observation and its assigned cluster center. Lower SSE indicates a more compact clustering solution for the same dataset.

Convergence: Whether the algorithm satisfied its stopping criterion before reaching the maximum number of iterations.

Iteration count: The number of iterations reported by the implementation.

Cluster membership counts: The number of observations assigned to each final cluster.

For repeated experiments, mean runtime and mean SSE are used to summarize overall performance. Runtime variability and individual seed-level results are also considered.

4.6 Comparison Limitations

The traditional and Spark-based algorithms differ in their initialization and execution procedures.

Traditional K-Means operates on the full dataset within a single process, whereas the Spark implementation first performs partition-level clustering, aggregates candidate centers, and then refines the solution through distributed operations.

Consequently, observed runtime differences reflect both the execution framework and differences in the algorithmic workflow.

The strongest parallel-performance comparison is therefore between Spark configurations using the same algorithm, dataset size, partition count, and random seed while varying the local execution setting.

Traditional K-Means comparisons remain useful for evaluating initialization sensitivity and clustering quality, but they do not establish a workload-equivalent parallel speedup.

5. Evaluation Metrics and Statistical Analysis

5.1 Evaluation Overview

The experiments evaluate execution time, local parallel speedup, clustering quality, convergence, and variability across repeated runs.

The principal scalability analysis compares Spark configurations local[1], local[2], and local[4] while holding dataset size, partition count, clustering parameters, and random seed constant.

A separate comparison examines conventional single-process K-Means with one or five initializations and the Spark Parallel K-Means implementation using five matched random seeds.

5.2 Execution Time

Execution time is measured in seconds using Python's high-resolution perf_counter() timer.

For the Spark experiments, the reported total runtime covers the clustering pipeline after the input RDD has been materialized. Synthetic dataset generation and initial RDD materialization are excluded from this measurement.

For the traditional K-Means baseline, timing begins after dataset generation and covers all requested K-Means initializations. The final cluster-count calculation is excluded.

These timing boundaries are similar in purpose but do not make the different algorithms computationally equivalent.

5.3 Mean Runtime and Standard Deviation

For each experimental configuration, the arithmetic mean runtime is:

$$\acute{t} = \frac{1}{r} \sum_{i=1}^{r} t_i$$

where t_i is the measured runtime of repetition i, and r is the number of measured repetitions.

Runtime variability is summarized using the sample standard deviation:

$$s_t = \sqrt{\frac{\sum_{i=1}^{r} (t_i - \acute{t})^2}{r-1}}$$

The principal Spark scalability experiments contain three measured repetitions per configuration, using random seeds 42, 43, and 44.

The separate traditional-versus-Spark comparison contains five measured repetitions per algorithm, using seeds 42 through 46.

Warm-up runs are excluded from all reported statistics.

5.4 Parallel Speedup

Local parallel speedup is calculated by dividing the mean runtime of Spark local[1] by the mean runtime of another Spark configuration at the same dataset size:

$$S_p = \frac{\acute{t}_1}{\acute{t}_p}$$

where $\acute{t}_1$ is the mean runtime using one local worker thread and $\acute{t}_p$ is the mean runtime using p local worker threads.

The corresponding runtime reduction percentage is:

$$R_p = \left(1 - \frac{\acute{t}_p}{\acute{t}_1}\right) \times 100\,\%$$

These metrics describe scaling within one physical computer. They are not measurements of multi-node cluster speedup.

5.5 Clustering Quality

Clustering quality is evaluated using the sum of squared errors (SSE), defined in Section 2.3.

SSE measures the total squared distance between observations and their assigned cluster centers. For the same dataset and feature representation, a lower SSE indicates a more compact clustering solution.

Mean SSE is calculated across measured repetitions for descriptive comparison. Because each random seed generates a different synthetic dataset, SSE values are compared most directly between algorithms or Spark configurations using the same seed.

For the scalability experiments, matching-seed SSE values are checked across local[1], local[2], and local[4] to determine whether changing the local execution configuration affects the reported clustering objective.

5.6 Convergence

Each experimental result records whether the algorithm satisfied its implemented stopping criterion within the permitted iteration limit.

The convergence rate is calculated as:

$$C = \frac{\text{number of converged measured runs}}{\text{total number of measured runs}} \times 100\,\%$$

Convergence does not guarantee that the globally optimal K-Means solution has been found.

5.7 Interpretation and Statistical Limitations

The reported statistics are descriptive. No formal hypothesis test is used to establish statistically significant runtime differences.

The scalability experiments contain only three measured repetitions per configuration, and the algorithm comparison contains five. These sample sizes limit the precision of variability estimates.

The experiments were performed on one computer, so runtime measurements may be influenced by background activity, scheduling, memory pressure, and other system-level effects.

The traditional and Spark implementations use different initialization strategies. Consequently, their runtime comparison is interpreted as an observed algorithm-level comparison rather than a controlled measurement of parallel speedup.

The strongest parallel-performance evidence comes from comparisons between Spark configurations with matching datasets, random seeds, partition counts, and clustering parameters.

6. Experimental Results and Discussion

Results are presented in two complementary groups: (A) 18 historical synthetic scalability runs at 10K/50K records, and (B) 42 controlled labeled-data runs on 1K synthetic and KDD99 samples. These experiment sets differ in scale and purpose and must not be pooled or treated as equivalent.

6.1 Overview of Experimental Results

This section presents the experimental findings obtained from the custom Spark Parallel K-Means implementation and the conventional single-process K-Means baseline.

The primary scalability experiments evaluate two synthetic dataset sizes: 10,000 and 50,000 records. Each dataset contains 20 numerical features and five underlying clusters.

The Spark experiments use four RDD partitions and compare three local execution configurations: local[1], local[2], and local[4].

Each configuration was evaluated using three measured repetitions with random seeds 42, 43, and 44. Runtime results are reported as means and sample standard deviations.

A separate five-repetition experiment compares traditional K-Means with one initialization, traditional K-Means with five initializations, and Spark Parallel K-Means using local[2].

6.2 Execution Time and Scalability

Table 5 summarizes the measured execution times and local speedups.

Table 5. Spark Parallel K-Means Scalability Results

Records	Spark configuration	Mean runtime (s)	Sample SD (s)	Speedup	Runtime reduction
10,000	local[1]	8.033	0.931	1.000x	0.00%

Records	Spark configuration	Mean runtime (s)	Sample SD (s)	Speedup	Runtime reduction
10,000	local[2]	5.642	0.674	1.424x	29.76%
10,000	local[4]	4.090	0.882	1.964x	49.09%
50,000	local[1]	116.765	13.770	1.000x	0.00%
50,000	local[2]	79.243	12.596	1.474x	32.13%
50,000	local[4]	39.918	1.389	2.925x	65.81%

For the 10,000-record dataset, the average runtime decreased from 8.033 seconds with local[1] to 4.090 seconds with local[4]. This corresponds to a speedup of approximately 1.96x.

For the 50,000-record dataset, the average runtime decreased from 116.765 seconds with local[1] to 39.918 seconds with local[4]. This corresponds to a speedup of approximately 2.93x.

The larger dataset exhibited a greater relative benefit from increased local parallelism.

These findings suggest that parallel execution can reduce the measured pipeline runtime as the computational workload increases. However, the observed speedups are not linear, and the experiments do not establish performance across multiple physical machines.

Figure 1. Mean execution time across Spark configurations.





Figure 2. Parallel speedup relative to local[1].



6.3 Clustering Quality Across Spark Configurations

Clustering quality was evaluated using the sum of squared errors (SSE). Table 6 reports the mean SSE across three measured repetitions for each Spark configuration.

Table 6. Mean SSE Across Spark Configurations


Records	local[1]	local[2]	local[4]
10,000	200,921.733	200,921.733	200,921.733
50,000	1,000,547.881	1,000,547.881	1,000,547.881

The SSE values were consistent across all three Spark execution configurations for each matched random seed.

This indicates that changing the number of local Spark worker threads did not change the measured clustering objective in these experiments.

The absolute SSE is larger for the 50,000-record dataset because it contains more observations. Therefore, the absolute SSE values should not be interpreted as a direct quality comparison between the two dataset sizes.

Figure 3. Clustering quality across Spark configurations.



6.4 Traditional K-Means and Parallel K-Means Comparison

A separate matched-dataset comparison used 10,000 records, 20 numerical features, five clusters, and five measured random seeds.

The comparison included:

1. Traditional single-process K-Means with one initialization.
2. Traditional single-process K-Means with five initializations.
3. Spark Parallel K-Means using local[2].

Table 7. Traditional and Spark K-Means Comparison

Algorithm	Mean runtime (s)	Sample SD (s)	Mean SSE	Convergence rate
Traditional K-Means, 1 initialization	0.928	1.106	600,670.256	100%
Traditional K-Means, 5 initializations	3.945	1.177	200,618.907	100%
Spark Parallel K-Means, local[2]	3.161	0.489	200,618.907	100%

The single-initialization traditional baseline had the lowest mean runtime, but it also had a substantially higher mean SSE.

The five-initialization traditional baseline and Spark Parallel K-Means produced matching SSE values for all five tested seeds.

Spark Parallel K-Means also had a lower observed mean runtime than the five-initialization traditional baseline.

However, the initialization procedures differ between these implementations. Consequently, this runtime difference must not be presented as a workload-equivalent parallel speedup.

6.5 Effect of Initialization on Clustering Quality

The most significant difference between the traditional initialization strategies occurred for random seed 45.

With one initialization, traditional K-Means produced an SSE of approximately 2,199,569.877.

With five initializations, traditional K-Means produced an SSE of approximately 199,313.136 for the same dataset seed.


Spark Parallel K-Means also produced an SSE of approximately 199,313.136 for that seed.

For the remaining four seeds, the traditional single-initialization baseline produced SSE values matching the other two approaches within numerical precision.

This result illustrates how a single K-Means initialization can occasionally produce a substantially poorer clustering solution.

Using multiple initializations can improve robustness by allowing the algorithm to retain the solution with the lowest SSE.

Figure 4. Clustering quality comparison between traditional and Spark Parallel K-Means.



10,000 synthetic records; 20 features; 5 clusters. Traditional-5 and Spark have different initialization workloads.

6.6 Convergence Results

All measured runs in the principal scalability experiments reported successful convergence.

All five measured runs in each of the three algorithm-comparison groups also reported convergence.

However, convergence means that the implemented stopping criterion was satisfied. It does not prove that the globally optimal K-Means solution was obtained.

The seed-45 traditional baseline demonstrates this distinction: the single-initialization run converged but produced a much higher SSE than the alternative initialization strategies.

6.7 Interpretation of Findings

The experimental results support three main observations.

First, increasing the number of local Spark worker threads reduced mean execution time for both tested dataset sizes.

Second, the measured clustering quality remained consistent across the Spark configurations when dataset size and random seed were held constant.

Third, the comparison with traditional K-Means demonstrates that initialization strategy can substantially influence the quality of the resulting clusters.

Together, these findings support the practical value of parallel execution and careful initialization when implementing K-Means for larger numerical datasets.

6.8 Limitations of the Results

The experiments were performed on a single Apple Silicon computer using Spark local mode.

Therefore, the reported speedups measure single-machine parallel execution rather than distributed performance across multiple physical cluster nodes.

The historical scalability study used three measured repetitions per configuration. The separate controlled labeled-data study used three random seeds per configuration; other earlier traditional-baseline comparisons used different repetition counts and must not be pooled with these results.

The historical scalability datasets were synthetically generated. The separate controlled study additionally used a 1,000-record KDD99 sample, but that limited sample does not establish performance on larger or more diverse real-world datasets.

The traditional and Spark implementations also use different initialization procedures and computational structures.

Finally, system-level effects such as background processes, memory pressure, and task scheduling may influence the observed execution times.

These limitations should be considered when interpreting the results or generalizing them to larger production environments.

6.9 Controlled Labeled-Data Evaluation (42 Runs)

Controlled Experimental Design

The controlled evaluation contains 42 completed experiments: 36 Spark Parallel K-Means runs and six traditional K-Means runs. The datasets are a synthetic sample containing 1,000 records, 20 features, and five clusters, and a KDD99 sample containing 1,000 records, 41 features, and four clusters. Three random seeds were used: 42, 43, and 44.

Spark was evaluated using local[1], local[2], and local[4], with two and four partitions. These configurations represent local execution on one computer rather than a physical multi-node cluster.

Controlled Runtime and Quality Results

Dataset	Configuration	Partitions	Runtime (s)	ARI	NMI	Purity
kdd99_sample	local[1]	2	0.5348	-0.0742	0.0784	0.7997
kdd99_sample	local[1]	4	0.5679	0.0551	0.0801	0.8030
kdd99_sample	local[2]	2	0.3828	-0.0742	0.0784	0.7997
kdd99_sample	local[2]	4	0.4013	0.0551	0.0801	0.8030
kdd99_sample	local[4]	2	0.3331	-0.0742	0.0784	0.7997
kdd99_sample	local[4]	4	0.3606	0.0551	0.0801	0.8030
kdd99_sample	Traditional	1	0.0736	0.0386	0.1115	0.7963
synthetic_1K_sample	local[1]	2	0.5737	1.0000	1.0000	1.0000
synthetic_1K_sample	local[1]	4	0.5519	1.0000	1.0000	1.0000
synthetic_1K_sample	local[2]	2	0.3537	1.0000	1.0000	1.0000
synthetic_1K_sample	local[2]	4	0.3607	1.0000	1.0000	1.0000
synthetic_1K_sample	local[4]	2	0.3290	1.0000	1.0000	1.0000
synthetic_1K_sample	local[4]	4	0.3250	1.0000	1.0000	1.0000
synthetic_1K_sample	Traditional	1	0.0702	0.9096	0.9561	0.9363

Table: Mean clustering-runtime and quality results across three random seeds per configuration. Runtime refers to recorded clustering time, not necessarily total end-to-end execution time.

Within-Spark Speedup and Efficiency

Dataset	Partitions	Configuration	Speedup	Efficiency
synthetic_1K_sample	2	local[2]	1.622	0.811
synthetic_1K_sample	2	local[4]	1.744	0.436
synthetic_1K_sample	4	local[2]	1.530	0.765
synthetic_1K_sample	4	local[4]	1.698	0.425
kdd99_sample	2	local[2]	1.397	0.698
kdd99_sample	2	local[4]	1.605	0.401
kdd99_sample	4	local[2]	1.415	0.708
kdd99_sample	4	local[4]	1.575	0.394

Speedup is defined as the mean Spark local[1] clustering runtime divided by the mean Spark local[n] clustering runtime for the same dataset and partition count. Efficiency is speedup divided by the local worker count.

With four partitions, Spark local[4] achieved 1.698x within-Spark speedup on the synthetic sample and 1.575x on KDD99.

Synthetic Dataset Interpretation

On the synthetic sample, Spark local[4] with four partitions achieved mean ARI 1.000, NMI 1.000, and purity 1.000. The traditional baseline achieved mean ARI 0.910 and NMI 0.956.

The Spark clusters aligned strongly with the synthetic reference labels. However, traditional and Spark initialization and restart procedures differed, so the quality differences cannot be attributed solely to parallel execution.

KDD99 Dataset Interpretation

On KDD99, Spark local[4] with four partitions achieved mean ARI 0.055, NMI 0.080, and purity 0.803. The traditional baseline achieved mean ARI 0.039 and NMI 0.111.

The low ARI and NMI values indicate weak agreement between generated clusters and reference labels. Purity should be interpreted cautiously because class imbalance can produce relatively high purity even when external agreement remains weak.

Traditional Baseline and Small-Data Overhead

The traditional implementation required approximately 0.0702 seconds on the synthetic sample and 0.0736 seconds on KDD99. These measured times were shorter than the corresponding Spark configurations at 1,000 records.

The small-data experiments therefore do not demonstrate an overall runtime advantage for Spark over traditional K-Means. Within-Spark speedup must be distinguished from traditional-versus-Spark performance.

Historical Scalability Evaluation

The separate historical scalability study contains 18 repeated runs using synthetic datasets of 10,000 and 50,000 records. It evaluated local[1], local[2], and local[4] using three random seeds per configuration.

Previously recorded results for 50,000 records showed mean total measured runtime decreasing from approximately 116.765 seconds under local[1] to 39.918 seconds under local[4], equivalent to approximately 2.925x within-Spark speedup.

Scientific Limitations

- Spark local[n] configurations ran on one computer, not a physical multi-node cluster.
- The controlled datasets contained 1,000 records each.
- Only three random seeds were used.
- Traditional and Spark initialization and restart procedures differed.
- The controlled and historical scalability studies should remain separate.
- ARI, NMI, purity, and SSE measure different properties of clustering.
- SSE values obtained from different preprocessing pipelines are not directly comparable.
- The implementation is research-inspired; exact IEEE algorithm reproduction has not been established.
- Recorded convergence means the implementation's stopping criterion was satisfied, not that a globally optimal clustering was found.

Integrated Research Conclusions

Increasing local Spark parallelism reduced clustering runtime in the tested configurations. The historical synthetic experiments showed stronger scaling at larger dataset sizes. The controlled synthetic sample showed strong external-label agreement, whereas the KDD99 sample showed weak external-label agreement. Traditional K-Means remained faster for the 1,000-record evaluations. These results support a bounded evaluation of the implemented research-inspired approach, rather than a claim of universal superiority.

Future Work

The controlled KDD99 evaluation has already been completed (21 runs). Future work would expand beyond its 1,000-record sample, test preprocessing choices and additional seeds, align initialization procedures, and evaluate actual multi-node Spark deployments.

The current experiments provide an initial evaluation of our Spark-based Parallel K-Means implementation. Several extensions would help determine how well the approach performs under more demanding conditions.

First, future experiments could evaluate larger datasets with more observations and higher feature dimensionality. The current scalability evaluation uses 10,000 and 50,000 records with 20 numerical features. Increasing these values would help determine whether the observed runtime improvements continue as computational requirements grow.

Second, future work should expand the completed 1,000-record KDD99 evaluation to larger, independently validated samples, investigate class imbalance and preprocessing, and assess whether clustering agreement improves under alternative feature choices. Such an experiment would require appropriate preprocessing and careful consideration of the dataset's characteristics. The present study reports results from the 1,000-record KDD99 sample, but not from larger KDD99 datasets.

Third, future work could deploy the implementation across multiple physical computing nodes. Our current experiments use Spark local mode on one computer. A multi-node environment would allow us to examine network communication overhead, data distribution, resource utilization, and distributed scalability. These results would be necessary before making claims about performance in a physical computing cluster.

Fourth, a more controlled comparison of initialization strategies could be performed. The traditional and Spark implementations currently use different initialization procedures. Future experiments could investigate more closely matched initialization workloads to better separate the effects of parallel execution from the effects of initialization.

Finally, additional repetitions and more detailed system monitoring could improve the reliability of the performance evaluation. Measuring memory usage, CPU utilization, and communication overhead would provide further insight into the factors influencing execution time.

These extensions would help determine whether the improvements observed in the current single-machine experiments remain effective for larger, more varied, and genuinely distributed workloads.

Conclusion

This project investigated a custom implementation of Parallel K-Means using Apache Spark, inspired by the approach presented by Liu et al. [1]. The implementation combines partition-level K-Means clustering, candidate-center aggregation, and distributed global updates. A traditional single-process K-Means baseline was also implemented to examine clustering quality, initialization behavior, and execution time.

The scalability experiments evaluated synthetic datasets containing 10,000 and 50,000 observations using Spark configurations local[1], local[2], and local[4]. For the 50,000-record dataset, mean runtime decreased from 116.765 seconds with local[1] to 39.918 seconds with

local[4]. This represents approximately 2.925 times speedup and a 65.81% reduction in mean execution time.

Clustering quality remained consistent across the tested Spark configurations for matched dataset seeds, as measured by the sum of squared errors. All measured scalability runs also satisfied the implementation's convergence criterion.

The traditional K-Means comparison highlighted the importance of initialization. In particular, one tested seed produced a substantially higher SSE with a single initialization than with multiple initializations. This finding demonstrates that convergence alone does not guarantee the best clustering solution.

Overall, the experiments show that increasing local Spark parallelism can reduce execution time while maintaining the measured clustering objective for the evaluated synthetic datasets. However, these findings apply to a single-machine experimental environment and should not be interpreted as evidence of equivalent speedup across multiple physical computing nodes.

The separate controlled evaluation reinforced this interpretation. With four partitions, Spark local[4] achieved mean within-Spark speedups of 1.6985× on the synthetic sample and 1.5748× on KDD99 relative to local[1]. On these 1,000-record samples, traditional single-process K-Means was faster than the Spark implementations. Spark achieved ARI and NMI of 1.000 on the synthetic sample but only approximately 0.055 and 0.080, respectively, on KDD99, indicating weak agreement with its reference labels. Different initialization and restart procedures limit direct quality comparisons between traditional and Spark implementations. These findings do not establish multi-node scalability or exact reproduction of the referenced IEEE algorithm.

The project therefore provides a working implementation and an experimental foundation for further investigation of scalable K-Means clustering using Apache Spark.

Supplementary Verification: Independent Cluster-Quality Check

An additional four-run verification was performed after the 42-run controlled study. Each verification run used 1,000 records, two Spark partitions, seed 42, five clusters, and Spark local[1] or local[2]. The KDD99 verification therefore used five clusters, unlike the four-cluster KDD99 configuration in the controlled study; results from these studies should not be pooled or interpreted as identical configurations.

Dataset	Method	SSE	Purity	ARI	NMI
Synthetic	Traditional	1,032.370	1.0000	1.0000	1.0000
Synthetic	Spark local[1]	1,032.370	1.0000	1.0000	1.0000
Synthetic	Spark local[2]	1,032.370	1.0000	1.0000	1.0000
KDD99	Traditional	9,342.830	0.9750	0.4318	0.5352
KDD99	Spark local[1]	21,072.555	0.7970	-0.0054	0.0111
KDD99	Spark local[2]	21,072.555	0.7970	-0.0054	0.0111

Verification procedure. Final Spark centers were used to independently reassign all 1,000 records to their nearest center and recompute the sum of squared Euclidean distances. The recalculated SSE, assignments, and per-cluster counts matched the Spark evaluation output in all four runs. Ground-truth labels were used only to calculate external evaluation measures (Purity, adjusted Rand index, and normalized mutual information).

Interpretation. The synthetic verification reproduced the traditional baseline exactly on the reported measures. On KDD99, Spark produced a higher SSE and substantially weaker external-label agreement than the traditional baseline for this particular five-cluster configuration. KDD99 is highly imbalanced: the largest true class contains 795 of 1,000 observations, so assigning all records to one cluster would yield a purity of 0.795. The Spark purity of 0.797 is only marginally above that reference, consistent with ARI near zero and NMI near zero. Convergence does not establish clustering quality. These observations do not identify a single causal mechanism; initialization, preprocessing, partitioning, and class imbalance warrant follow-up investigation.

Scope and timing. Spark local[1] and local[2] are single-computer configurations, not separate physical nodes. The four verification runs are a supplemental correctness/quality check, not part of the 42 controlled experiments or the 18 historical scalability runs. The supplementary wall-clock measurements include verification-run overhead and should not be directly compared with the earlier benchmark timing definitions. The six-row result table is saved as results/verified_quality/clustering_quality_comparison.csv (Git commit 78fd4e2).

References

[1] H. Liu, Y. Bai, Z. Chen, and Z. Zhang, “Big data clustering method based on parallel K-means,” in *2024 IEEE 4th International Conference on Power, Electronics and Computer Applications (ICPECA)*, 2024. doi: 10.1109/ICPECA60615.2024.10470970.

[2] S. P. Lloyd, “Least squares quantization in PCM,” *IEEE Transactions on Information Theory*, vol. 28, no. 2, pp. 129–137, 1982. doi: 10.1109/TIT.1982.1056489.

[3] D. Arthur and S. Vassilvitskii, “k-means++: The advantages of careful seeding,” in *Proceedings of the Eighteenth Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pp. 1027–1035, 2007.

[4] B. Bahmani, B. Moseley, A. Vattani, R. Kumar, and S. Vassilvitskii, “Scalable K-Means++,” *Proceedings of the VLDB Endowment*, vol. 5, no. 7, pp. 622–633, 2012. doi: 10.14778/2180912.2180915.

[5] Apache Software Foundation, “RDD Programming Guide,” *Apache Spark Documentation*. https://spark.apache.org/docs/latest/rdd-programming-guide.html