



Cboe Options Exchanges Binary Order Entry Specification

Version 2.10.5

September 18, 2019

Contents

1	Introduction	5
1.1	Overview	5
1.2	Document Format	5
1.3	Hours of Operation	5
1.4	Data Types.....	6
1.5	Optional Fields and Bit fields.....	7
1.6	Protocol Features	7
1.6.1	Complex Instruments and Signed Prices (C1, C2, and EDGX only)	7
1.6.2	Done For Day Restatements	7
1.6.3	Carried Order Restatements	8
1.6.4	Display Indicator Features.....	8
1.6.5	Risk Root.....	9
1.6.6	Market Maker Trade Notifications (C1 Only)	9
1.6.7	Cabinet and Sub-Cabinet Orders (C1 Only)	9
1.6.8	Auction Orders	10
1.6.9	Port Types	10
1.6.10	Floor Routing (C1 Only)	11
2	Session	14
2.1	Message Headers	14
2.2	Login, Replay and Sequencing.....	14
2.3	Sequence Reset	15
2.4	Heartbeats.....	15
2.5	Logging Out	15
3	Session Messages	16
3.1	Member to Cboe	16
3.1.1	Login Request.....	16
3.1.2	Logout Request	19
3.1.3	Client Heartbeat	19
3.2	Cboe to Member	20
3.2.1	Login Response.....	20
3.2.2	Logout	22
3.2.3	Server Heartbeat.....	23
3.2.4	Replay Complete	24
4	Application Messages.....	25
4.1	Member to Cboe	25
4.1.1	New Order.....	25
4.1.2	New Order Cross (C1 and EDGX Only).....	26
4.1.3	New Complex Order (C1, EDGX and C2 Only)	30

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

4.1.4	New Order Cross Multileg (C1 and EDGX Only)	32
4.1.5	Cancel Order	35
4.1.6	Modify Order	37
4.1.7	Quote Update	39
4.1.8	Quote Update (Short)	41
4.1.9	Purge Orders	43
4.1.10	Reset Risk	46
4.1.11	New Complex Instrument (C1, C2, and EDGX Only)	47
4.1.12	Add Floor Trade (C1 Only)	49
4.1.13	Floor Trade Confirmation (C1 Only)	52
4.1.14	Delete Floor Trade (C1 Only)	54
4.2	Cboe to Member	57
4.2.1	Order Acknowledgment	57
4.2.2	Cross Order Acknowledgment (C1 and EDGX Only)	58
4.2.3	Quote Update Acknowledgment	60
4.2.4	Order Rejected	62
4.2.5	Cross Order Rejected (C1 and EDGX Only)	64
4.2.6	Quote Update Rejected	65
4.2.7	Order Modified	66
4.2.8	Order Restated	67
4.2.9	Quote Restated	68
4.2.10	User Modify Rejected	69
4.2.11	Order Cancelled	71
4.2.12	Quote Cancelled	72
4.2.13	Cross Order Cancelled (C1 and EDGX Only)	73
4.2.14	Cancel Rejected	74
4.2.15	Order Execution	75
4.2.16	Quote Execution	78
4.2.17	Trade Cancel or Correct	80
4.2.18	Purge Rejected	82
4.2.19	Reset Risk Acknowledgment	83
4.2.20	Mass Cancel Acknowledgment	84
4.2.21	Complex Instrument Accepted (C1, C2, and EDGX Only)	85
4.2.22	Complex Instrument Rejected (C1, C2, and EDGX Only)	87
4.2.23	Floor Trade Notification (C1 Only)	89
4.2.24	Add Floor Trade Rejected (C1 Only)	91
4.2.25	Floor Trade Confirmation Rejected (C1 Only)	93
4.2.26	Delete Floor Trade Rejected (C1 Only)	94
4.2.27	Delete Floor Trade Acknowledgement (C1 Only)	96
5	Input Bitfields Per Message	97

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

5.1	New Order	98
5.2	New Order Cross (C1 and EDGX Only).....	99
5.3	New Complex Order (C1, C2 and EDGX Only)	99
5.4	New Order Cross Multileg (C1 and EDGX Only)	100
5.5	Cancel Order	100
5.6	Modify Order.....	101
5.7	Purge Orders	101
5.8	New Complex Instrument (C1, C2, and EDGX Only)	102
6	Return Bitfields Per Message.....	103
6.1	Order Acknowledgment	104
6.2	Cross Order Acknowledgment (C1 and EDGX only)	105
6.3	Order Rejected	106
6.4	Cross Order Rejected (C1 and EDGX Only)	107
6.5	Order Modified	108
6.6	Order Restated.....	109
6.7	User Modify Rejected.....	110
6.8	Order Cancelled	111
6.9	Cross Order Cancelled (C1 and EDGX Only)	112
6.10	Cancel Rejected.....	113
6.11	Order Execution	114
6.12	Trade Cancel or Correct	115
6.13	Purge Rejected	116
6.14	Complex Instrument Accepted (C1, C2 and EDGX Only)	117
6.15	Complex Instrument Rejected (C1, C2 and EDGX Only)	118
7	List of Optional Fields	119
8	Reason Codes	137
8.1	Order Reason Codes.....	137
8.2	Quote Reason Codes	138
9	List of Message Types	139
9.1	Member to Cboe	139
9.2	Cboe to Member	139
10	Port Attributes	140
11	Support	145
	Revision History	146

1 Introduction

1.1 Overview

This document describes Binary Order Entry (BOE), the Cboe proprietary order entry protocol.

Where applicable, the terminology (e.g., time in force) used in this document is similar to that used by the FIX protocol to allow those familiar with FIX to more easily understand BOE. This document assumes the reader has basic knowledge of the FIX protocol.

BOE fulfills the following requirements:

- *CPU and memory efficiency.* Message encoding, decoding, and parsing are simpler to code and can be optimized to use less CPU and memory at runtime.
- *Application level simplicity.* State transitions are simple and unambiguous. They are easy to apply to a Member's representation of an order.
- *Session level simplicity.* The session level protocol (login, sequencing, replay of missed messages, logout) is simple to understand.

While Cboe has strived to preserve feature parity between FIX and BOE where possible, some features may only be available in one protocol or the other.

All binary values are in little Endian (used by Intel x86 processors), and not network byte order.

Each message is identified by a unique message type. Not all message types are used in all Cboe's trading environments globally. A listing of the supported message types is provided in 'Section 10 - List of Message Types'.

All communication is via standard TCP/IP.

Please refer to the [Cboe Options Exchange Integration Website](#) for additional details regarding upcoming changes in support of the migration of Cboe Options Exchange to the Bats technology platform.

1.2 Document Format

Blue highlighted sections highlight key differences between the Cboe US Options Exchanges (BZX Options Exchange "BZX", Cboe Options Exchange "C1", C2 Options Exchange "C2", and EDGX Options Exchange "EDGX").

1.3 Hours of Operation

All times noted are Eastern time zone (ET) based.

See the respective exchange websites for holiday schedules.

Cboe Options Exchanges support a Pre-Market Queuing Session that allows orders to be entered and queued prior to the start of the Global Trading Hours ("GTH") session and the Regular Trading Hours ("RTH") session.

For more information on the Cboe Opening Process, please refer to the Cboe Opening Process Specification.

Cboe Options Exchanges do not support a closing auction, but do support extended trading for options on select ETF and index products. All orders remaining after the Regular Trading Session that are not eligible for Extended Trading will be cancelled automatically. All orders remaining after the Extended session will be cancelled automatically. Members will receive Order Cancelled messages for all automatically cancelled orders.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

	C1	C2	BZX	EDGX
Order Acceptance	2:00 am - 3:00 am ET (SPX, VIX and FLEX)	7:30 am - 9:30 am ET (All Products)	7:30 am - 9:30 am ET (All Products)	7:30 am - 9:30 am ET (All Products)
	7:30 am - 9:30 am ET (All Products)			
GTH	3:00 am - 9:15 am ET (SPX, VIX and FLEX)	8:30 am - 9:15 am ET (DJX)	N/A	8:30 am - 9:15 am ET (XSP)
RTH	9:30 am - 4:00 am ET (All Products)	9:30 am - 4:00 pm ET (All Products)	9:30 am - 4:00 pm ET (All Products)	9:30 am - 4:00 pm ET (All Products)
	9:30 am - 4:15 pm ET (Select ETF's/ETN's and Index Products)	9:30 am - 4:15 pm ET	9:30 am - 4:15 pm ET	9:30 am - 4:15 pm ET

1.4 Data Types

The following data types are used by BOE. The size of some data types varies by message. All data types have default values of binary zero, in both Member to Cboe and Cboe to Member contexts.

- **Binary:** Little Endian byte order, unsigned binary value. The number of bytes used depends on the context.
 - One byte: `FE` = 254
 - Four bytes: `64 00 00 00` = 100
- **Signed Binary:** Little Endian byte order, signed two's complement, binary value. The number of bytes used depends on the context.
 - One byte: `DF` = -33
 - Four bytes: `64 00 00 00` = +100
- **Binary Price:** Little Endian byte order value, signed two's complement, eight bytes in size, with four implied decimal places. So, if the value is -123,400, the actual value taking into account implied decimal places is -12.34.
 - `08 E2 01 00 00 00 00 00` = 123,400/10,000 = 12.34
 - `F8 1D FE FF FF FF FF FF` = -123,400/10,000 = -12.34
- **Short Binary Price:** Little Endian byte order value, signed two's complement, four bytes in size, with four implied decimal places. So, if the value is 12,300, the actual value taking into account implied decimal places is 1.23.
 - `0C 30 00 00` = 12,300/10,000 = 1.23
- **Signed Binary Fee:** Little Endian byte order value, signed two's complement, eight bytes in size, with five implied decimal places. So, the value is -123,000 is -1.23 after taking account for the five implied decimal places.
 - `88 1F FE FF FF FF FF FF` = 123,000/100,000 = -1.23
- **Alpha:** Uppercase letters (A-Z) and lowercase letters (a-z) only. ASCII NUL (0x00) filled on the right, if necessary. The number of bytes used depends on the context.
- **Alphanumeric:** Uppercase letters (A-Z), lowercase letters (a-z) and numbers (0-9) only. ASCII NUL (0x00) filled on the right, if necessary.
- **Text:** Printable ASCII characters only. ASCII NUL (0x00) filled on the right, if necessary.
- **DateTime:** Little Endian byte order, eight bytes. The date and time, in UTC, represented as nanoseconds past the UNIX epoch (00:00:00 UTC on 1 January 1970). The nanoseconds portion is currently ignored and

treated as 0 (i.e. the times are only accurate to microseconds) on input, and will always be set to 0 by Cboe in outgoing messages. However, Cboe **may begin populating the nanoseconds portion at any time without warning.**

For example: 1,294,909,373,757,324,000 = 2011-01-13 09:02:53.757324 UTC.

- *Date*: Little Endian byte order, unsigned binary value, 4 bytes in size. The YYYYMMDD expressed as an integer.

1.5 Optional Fields and Bit fields

Some messages such as `New Order` and `Modify Order` have a number of optional fields. A count and number of bitfields in the message specify which optional fields will be present at the end of the message. If a bit is set, the field will be present. Fields are appended to the end of the message. There is no implicit framing between the optional fields. In order to decode the optional fields, they must be appended in a particular order to the end of the message. The fields of the first bitfield are appended first, lowest order bit first. Next, the fields of the next bitfield are appended, lowest order bit first. This continues for all bitfields. While certain reserved bits within a defined bitfield are used within another Cboe market and will be ignored, bits that are reserved for future expansion must be set to 0 when noted in the bitfield description.

The size, data type, and values for each field are described in ‘Section 7 – List of Optional Fields’.

Note that the set of optional fields returned for each Cboe to Member message type is determined at session login (using the `Login Request` message); hence, the exact size and layout of each message received by the client application can be known in advance. **Any requested optional field, which is irrelevant in a particular context, will still be present in the returned message, but with all bytes set to binary zero (0x00).**

Each return message from Cboe to Member indicates the optional fields which are present, even though the Member indicated during login which optional fields are to be sent. The reason for the inclusion (and duplication) is so that each message can be interpreted on its own, without having to find the corresponding login request or response to know which optional fields are present. So, for example, in a log file, decoding a message requires only that single message.

Example messages are shown with each message type, which should help to make this concept clear.

1.6 Protocol Features

1.6.1 Complex Instruments and Signed Prices **(C1, C2, and EDGX only)**

All price fields in the BOE protocol are signed values capable of accommodating complex instruments that can be negative (See Data Types) for a description and an example of using the Binary Price type with a negative price). For an example of the use of the Binary Price type with negative price values in an application message, see the example BOE message in `New Complex Order`.

1.6.2 Done For Day Restatements

Good ‘Til Cancel (“GTC”) and Good ‘Til Day (“GTD”) orders can result in order persisting between sessions. The Cboe BOE protocol provides a mechanism for clients to request end-of-day restatement of GTC/GTD orders that will be persisted to the next trading session. See Section ‘Section 10 – Port Attributes’ for information on available port attributes, including Done For Day Restatements.

When enabled, Done For Day Restatement messages are sent to connected clients after the trading session ends, at 4:00 ET (4:15 for select ETF’s) and prior to the trading session disconnecting at 4:45 ET, for each order that will persist to the next trading session. Any time prior to the 4:45 ET cutoff, customers may send Order Cancel Request messages for any open GTC and GTD orders. All other order message types received after the market closes at 4:00 ET (4:15 ET for select ETF’s) will be rejected.

Done For Day Restatements are represented using `Order Acknowledgement` messages with the following optional attributes set:

- *BaseLiquidityIndicator* = A (Added Liquidity), bitfield 5, bit position 7
- *SubLiquidityIndicator* = D (Done For Day), bitfield 7, bit position 1

To receive Done For Day Restatements, the Done For Day Restatement port attribute must be set (contact Cboe Trade Desk), and customers **must** register to receive *BaseLiquidityIndicator* and *SubLiquidityIndicator* optional fields on `Order Acknowledgement` messages via the `Logon Request` message (See 'Section 3.1.1 – Login Request' for details on registering to receive optional fields on a per-message basis). If the Done For Day Restatement port attribute is set and the bitfield `Logon Message` registration for the `Order Acknowledgement` message does not include but *BaseLiquidityIndicator* and *SubLiquidityIndicator*, the logon attempt will fail.

1.6.3 Carried Order Restatements

Good 'Til Cancel ("GTC") and Good 'Til Day ("GTD") orders can result in orders persisting between sessions. The Cboe BOE protocol provides a mechanism for clients to request restatement of orders that have been carried forward from the previous business day trading session. See 'Section 11 – Port Attributes' for information on available port attributes, including 'Carried Order Restatements'.

When enabled, Carried Order Restatements are sent to connected clients for each product on the Options Exchange for which orders have been carried forward from the previous business day trading session. Carried Order Restatements are sent after connection establishment and before regular trading activity messages on a per-product basis.

Carried Order Restatements are represented using `Order Acknowledgement` messages with the following optional attributes set:

- *BaseLiquidityIndicator* = A (Added Liquidity), bitfield 5, bit position 7
- *SubLiquidityIndicator* = C (Carried), bitfield 7, bit position 1

To receive Carried Order Restatements, the Carried Order Restatement port attribute must be set (contact CFE Trade Desk), and customers **must** register to receive *BaseLiquidityIndicator* and *SubLiquidityIndicator* optional fields on `Order Acknowledgement` messages via the `Logon Request` message (See 'Section 3.1.1 – Login Request' for details on registering to receive optional fields on a per-message basis). If the Carried Order Restatement port attribute is set and the bitfield `Logon Message` registration for the `Order Acknowledgement` message does not include but *BaseLiquidityIndicator* and *SubLiquidityIndicator*, the logon attempt will fail.

1.6.4 Display Indicator Features

Display-Price Sliding **(BZX Only)**

If the original limit price of the unexecuted remainder of a day order does not lock or cross the NBBO then Cboe works the order at the original limit price while displayed at the nearest permissible quoting increment. If the original limit price does lock or cross the NBBO then Cboe makes available Display-Price Sliding.

Display-Price Sliding adjusts the original limit price on entry to the locking price of the NBBO. It will be ranked and worked at a price locking the NBBO but will temporarily adjust the displayed price to the nearest permissible quoting increment. When the NBBO widens, the display price will be readjusted to the adjusted limit price. The display price may be temporarily less aggressive than the adjusted limit price or working price.

Multiple Display-Price Sliding does not permanently adjust the original limit price on entry, but allows for Display-Price slid orders to continue to have their display **and** working prices adjusted towards their original limit price based on changes to the prevailing NBBO.

Contra-side Post Only orders that are received when a Display-Price Slid order is working at a locking price with the NBBO will not result in a reject of a contra-side Post Only order but will instead result in the working price of the Display-Price Slid order to be repriced to one penny away from the locking price.

Price Adjust (BZX, C1, C2, and EDGX)

If the limit price of an order does not lock or cross the NBBO, then the order will be ranked and displayed at the nearest permissible quoting increment.

If the limit price of a Price Adjust eligible order locks or crosses the NBBO, the limit price will be adjusted on entry to the locking price of the NBBO, while the displayed price and ranked price will be temporarily adjusted to the nearest permissible quoting increment. Price Adjust orders will never be ranked at the locking price or at a non-displayable price increment. If the NBBO widens, the displayed price and ranked price will be readjusted to the adjusted limit price.

The limit price of a Multiple Price Adjust order will not be permanently adjusted on entry if the limit price crosses the NBBO. The displayed price and ranked price will be the nearest permissible quoting increment and will be adjusted towards the original limit price based on changes in the prevailing NBBO.

NoRescrapeAtLimit (BZX Only)

Applicable only to fully routable IOC orders (9303=R and 59=3). After walking the price down to the limit, there will be no final scrape at Cboe and the cancel code will state "X: Expired" rather than "N: No Liquidity".

1.6.5 Risk Root

This document refers to the term "Risk Root" to describe Cboe Options Risk Management functionality that is applied at the symbol-level. The Risk Root is defined as the underlying symbol.

This impacts what value must be sent in the defined *RiskRoot* fields when performing a mass cancel or a reset of a risk trip.

See the [Risk Management Specification](#) for more details.

1.6.6 Market Maker Trade Notifications (C1 Only)

Floor Trade Notifications (MMTNs) will be sent to Market Makers if they are identified as the contra party of a floor trade. MMTN messages will be sent over a designated FIXDrop or BOE order entry port. See Port Attributes section for information on available port attributes related to MMTNs.

Market Makers that receive a Floor Trade Notification should use the Floor Trade Confirmation message to respond to the NNTN if they agree with the terms of the trade. Alternatively, a Market Maker can use the Add Floor Trade message to enter their own version of the trade.

1.6.7 Cabinet and Sub-Cabinet Orders (C1 Only)

Cabinet orders are identified via *PriceType* = "0" and must have a valid *TimeInForce* of "Day" or "GTC". Cabinet orders can support a position status of Open or Close identified via the *OpenClose* field. Cabinet orders will only trade with other cabinet orders on the book or floor depending on *FloorRoutingInst* and *FloorDestination* values.

1.6.7.1 Valid Pricing

Orders in non-penny classes must have a limit price **less than or equal to** \$0.01 and orders in penny classes must have a limit price **less than** \$0.01. Limit prices may be up to 4 decimal places.

1.6.7.2 Invalid Pricing

Orders in penny or non-penny classes priced **greater than** \$0.01 and orders in penny classes priced **equal to** \$0.01 will be rejected. Orders with a limit price that locks or crosses a resting non-cabinet order will be rejected.

1.6.7.3 Market Data

Cabinet orders or executions will not be disseminated on OPRA but will be available on http://cdn.cboe.com/resources/membership/US_EQUITIES_OPTIONS_MULTICAST_PITCH_SPECIFICATION.pdf and http://cdn.cboe.com/resources/membership/US_OPTIONS_MULTICAST_TOP_SPECIFICATION.pdf feeds.

1.6.8 Auction Orders

For more information on the following Auction Only Orders, please refer to the [Opening Process Specification](#).

Order Type	Order Entry Details	
Market-On-Open (MOO)	OrdType = 1 (Market)	TimeInForce = 2 (At the open)
Limit-On-Open (LOO)	OrdType = 2 (Limit) Price = [price]	TimeInForce = 2 (At the open)
Settlement Liquidity On Open (SLOO)	OrdType = 2 (Limit) Price = [price]	TimeInForce = 2 (At the open) ExecInst = r (Settlement Liquidity)

1.6.9 Port Types

All BOE port types may be ordered through the Customer Web Portal using the **Logical Port Request** tool. Changes to port attributes may be requested through the same tool by submitting a 'Modify' request for one or more existing BOE ports.

1.6.9.1 BOE Order Ports

Standard BOE ports support simple and complex order entry but do not support the usage of the following message types: *Quote Update*, *Purge Orders*. The attempted usage of any of these message types on standard BOE order ports will result in a rejection of the disallowed message.

Standard BOE ports are limited to 5,000 inbound messages per second. Once the inbound limit is reached new orders are rejected, modifies are handled as cancels, and cancels are processed normally.

1.6.9.2 BOE Bulk Quoting Ports

BOE Bulk Quoting ports are intended for use by firms quoting large numbers of simple options series. As a result, they are unthrottled. However, firms may still experience poor performance on Bulk Quoting ports if excessive message traffic is sent.

The *PreventMatch* field may not be specified on the *Quote Update* message and Match Trade Prevention is only available if defaulted at the port level. For Bulk Quoting ports, only Cancel Newest, Cancel Oldest, or Cancel Both are permitted. If a Bulk Quoting port is not configured with both a default MTP Modifier and Unique ID Level, Match Trade Prevention will be disabled.

Bulk Quoting Port Order Acceptance Table

Message	Simple/Complex	Accepted over Bulk Quoting Port?	Other Conditions
Quote Update	Simple	Yes	
Quote Update (short)	Simple	Yes	
New Order	Simple	Yes	Must have a <i>TimeInForce</i> value of Day or GTD with a same day expiration on C1, C2, and EDGX.
New Order (Auction Response)	Simple	Yes	
New Order Cross (AIM or QCC)	Simple	No	
New Order Cross Multileg	Simple	No	
Purge Orders	Simple/Complex	No	
Reset Risk	Simple/Complex	Yes	
New Complex Instrument	Complex	Yes	

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Quote Update	Complex	No	
New Complex Order	Complex	Yes	Must be Post Only (<i>RoutingInst</i> = P). Must have a <i>TimeInForce</i> value of Day or GTD with a same day expiration on C1, C2, and EDGX.
New Complex Order (COA Response)	Complex	Yes	

Bulk Quoting Port Quote/Order Behavior Matrix

The following matrix describes the liquidity removal behavior of quotes and orders sent on Bulk Quoting ports. Bulk Quoting ports will be available for use by all customers. Only registered Market Makers will be allowed to use quotes for liquidity removal. Orders sent on Bulk Quoting Ports will be allowed to remove liquidity only on BZX Options. On C1, C2, and EDGX Options, only registered Market Makers will be allowed to remove liquidity using New Order messages.

Once any quote or order is posted to the exchange book liquidity removal against any contra capacity will always be allowed in the case that a subsequent event causes the resting quote or order to be re-evaluated, such as the Opening/Re-Opening Process.

Originating Side (<i>Capacity</i>)	Contra Side (<i>Capacity</i>)			
	BZX	C2	EDGX	C1
Quote Update Seeking to Remove (M)	Allowed (ALL)	Allowed (All Except "M")	Allowed (All Except "M")	Allowed (All Except "M")
Quote Update Seeking to Remove (All Except "M")	Reject	Reject	Reject	Reject
New Order Seeking to Remove (M)	Allowed (ALL)	Allowed (All Except "M")	Allowed (All Except "M")	Allowed (All Except "M")
New Order Seeking to Remove (All Except "M")	Allowed (ALL)	Reject	Reject	Reject
Passive Quote Update or New Order (ALL)	Allowed (ALL)	Allowed (ALL)	Allowed (ALL)	Allowed (ALL)

1.6.9.3 BOE Purge Ports

BOE Purge Ports support a single message type: *Purge Orders*. Members may use this port type to request a cancellation of groups of orders, including orders across multiple BOE Order or Bulk Quoting ports.

1.6.10 Floor Routing (C1 Only)

All orders routed to the floor must include explicit routing instructions that includes two features: 1) floor routing instruction indicating Direct or Default routing behavior and 2) floor destination information. Floor routing behavior is specified in *FloorRoutingInst* (22303). Direct routing sends the order to the indicated PAR workstation, while default routing indicates that electronic execution is preferred, but the order may be routed to the indicated PAR if it cannot be processed electronically.

Examples of conditions which cause default routing to the Floor include:

- a complex order having an AON contingency
- a complex order having more than 12 legs
- a complex order with multiple underlying components
- any FLEX order not participating in an auction
- not held orders

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Floor destination instructions are specified in *FloorDestination* (22100), indicating a PAR workstation (ex. W001) to route to on the floor (or "PARO" to route to the Floor PAR Official of the underlying symbol) if not specified on the inbound message. See Section '[FIX Port Attributes](#)' for information on available port attributes, including *Default FloorRoutingInst* and *Default FloorDestination*.

Order Tags/Port Settings				Handling of the Order	
Order Floor Destination	Order FloorRoutingInst	Port Default Floor Destination	Port Default FloorRoutingInst	Orders Only Executed on Floor (i.e. complex AON)	All Other Order Types
			E (default)	Reject: ineligible for electronic book	Process electronically
			D	Reject: requires a floor destination	Reject: requires a floor destination
			X	Reject: requires a floor destination	Reject: requires a floor destination
		W001	E (default)	Reject: ineligible for electronic book	Process electronically
		W001	D	Route to floor: W001	Route to floor: W001
		W001	X	Route to floor: W001	Process electronically
W009			E (default)	Reject: ineligible for electronic book	Process electronically
W009		W001	D	Route to floor: W009	Route to floor: W009
W009			X	Route to floor: W009	Process electronically
W009	E			Reject: ineligible for electronic book	Process electronically
W009	D			Route to floor: W009	Route to floor: W009
W009	X			Route to floor: W009	Process electronically
	E			Reject: ineligible for electronic book	Process electronically
	D			Reject: requires a floor destination	Reject: requires a floor destination
	X			Reject: requires a floor destination	Process electronically

E = Electronic only **D** = Direct **X** = Route to floor if unable to process electronically

1.6.10.1 *Floor Representation Restatements* (C1 Only)

Orders routed to the trading floor will be represented to the open outcry crowd before being traded in the crowd. The Cboe BOE protocol provides a mechanism for clients to receive restatement of orders at the time of representation.

BOE Floor Representation Restatements are sent to connected clients for each order when the floor broker reports representation of the order to the crowd. Floor Representation Restatements sent to BOE ports will also be sent to connected Order by Order Drop clients having the *Floor Representation Restatements* port attribute enabled.

Order Restated messages for floor representation will have *RestatementReason* = "F" (Represented on Floor). The *TransactTime* (60) will be the recorded time of the representation.

2 Session

2.1 Message Headers

Each message has a ten byte header. The two initial *StartOfMessage* bytes are present to aid in message reassembly for network capture purposes. The *MatchingUnit* field is only populated on sequenced, non-session level messages sent from Cboe to the Member. Messages from Member to Cboe and all session level messages must always set this value to 0.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA .
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	Message type.
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH. For session level traffic, the unit is set to 0. For messages from Member to Cboe, the unit must be 0.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Messages from Cboe to Member are sequenced distinctly per matching unit. Messages from Member to Cboe are sequenced across all matching units with a single sequence stream. Member can optionally send a 0 sequence number on all messages from Member to Cboe. Cboe highly recommends that Members send sequence numbers on all inbound messages.

2.2 Login, Replay and Sequencing

Session level messages, both inbound (Member to Cboe) and outbound (Cboe to Member) are unsequenced.

Inbound (Member to Cboe) application messages are sequenced. Upon reconnection, Cboe informs the Member of the last processed sequence number; the Member may choose to resend any messages with sequence numbers greater than this value. A gap forward in the Member's incoming sequence number is permitted at any time and is ignored by Cboe. Gaps backward in sequence number (including the same sequence number used twice) are never permitted and will always result in a *Logout* message being sent and the connection being dropped.

Most (but not all) outbound (Cboe to Member) application messages are monotonically sequenced per matching unit. Each message's documentation will indicate whether it is sequenced or unsequenced. While matching units on BOE correspond directly to matching units on Multicast PITCH, sequence numbers do not.

Upon reconnection, a Member sends the last received sequence number per matching unit in a *Login Request* message. Cboe will respond with any missed messages. However, when the *Login Request NoUnspecifiedUnitReplay* flag is enabled, Cboe will exclude messages from unspecified matching units during replay. Cboe will send a *Replay Complete* message when replay is finished. If there are no messages to replay, a *Replay Complete* message will be sent immediately after a *Login Response* message. Cboe will reject all orders during replay.

Assuming a Member has requested replay messages using a properly formatted `Login Request` after a disconnect, any unacknowledged orders remaining with the Member after the `Replay Complete` message is received should be assumed to be unknown to Cboe.

Unsequenced messages will not be included during replay.

A session is identified by the username and session sub-identifier (both supplied by Cboe). Only one concurrent connection per username and session sub-identifier is permitted.

If a login is rejected, an appropriate `Login Response` message will be sent and the connection will be terminated.

2.3 Sequence Reset

A reset sequence operation is not available for Binary Order Entry. However, a Member can send a `Login Request` message with `NoUnspecifiedUnitReplay` field enabled, and `NumberOfUnits` field set to zero. Then, upon receiving a `Login Response` message from Cboe, the Member can use the field `LastReceivedSequenceNumber` as the sequence starting point for sending future messages.

2.4 Heartbeats

`Client Heartbeat` messages are sent from Member to Cboe and `Server Heartbeat` messages are sent from Cboe to Member if no other data has been sent in that direction for one second. Like other session level messages, heartbeats from Cboe to the Member do not increment the sequence number. If Cboe receives no inbound data or heartbeats for five seconds, a `Logout` message will be sent and the connection will be terminated. **Members are encouraged to have a one second heartbeat interval and to perform similar connection staleness logic.**

2.5 Logging Out

To gracefully log out of a session, a `Logout Request` message should be sent by the Member. Cboe will finish sending any queued data for that port and will then respond with its own `Logout` message and close the connection. After receipt of a `Logout Request` message, Cboe will ignore all other inbound (Member to Cboe) messages except for `Client Heartbeat`.

3 Session Messages

3.1 Member to Cboe

3.1.1 Login Request

A `Login Request` message must be sent as the first message upon connection.

A number of repeating parameter groups, some of which may be required, are sent at the end of the message. Ordering of parameter groups is not important. New parameter groups may be added in the future with no notice.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x37
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	Always 0 for session level messages.
<i>SessionSubID</i>	10	4	Alphanumeric	Session Sub ID supplied by Cboe.
<i>Username</i>	14	4	Alphanumeric	Username supplied by Cboe.
<i>Password</i>	18	10	Alphanumeric	Password supplied by Cboe.
<i>NumberOfParam Groups</i>	28	1	Binary	A number, n (possibly 0), of parameter groups to follow.
<i>ParamGroup₁</i>				First parameter group.
...				
<i>ParamGroup_n</i>				Last parameter group.

Unit Sequences Parameter Group

This parameter group includes the last consumed sequence number per matching unit received by the Member. Cboe uses these sequence numbers to determine what outbound (Cboe to Member) traffic, if any, was missed by the Member. If this parameter group is not sent, it's assumed the Member has not received any messages (e.g., start of day).

The Member does not need to include a sequence number for a unit if they have never received messages from it. For example, if the Member has received responses from units 1, 3, and 4, the `Login Request` message need not include unit 2. If the Member wishes to send a value for unit 2 anyway, 0 would be the only allowed value.

Only one instance of this parameter group may be included.

Field	Offset	Length	Data Type	Description
<i>ParamGroupLength</i>	0	2	Binary	Number of bytes for the parameter group, including this field.
<i>ParamGroupType</i>	2	1	Binary	0x80
<i>NoUnspecified UnitReplay</i>	3	1	Binary	Flag indicating whether to replay missed outgoing (Cboe to Member) messages for unspecified units. 0x00 = False (Replay Unspecified Units) 0x01 = True (Suppress Unspecified Units Replay)

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>NumberOfUnits</i>	4	1	Binary	A number, n (possibly 0), of unit/sequence pairs to follow, one per unit from which the Member has received messages.
<i>UnitNumber₁</i>		1	Binary	A unit number.
<i>UnitSequence₁</i>		4	Binary	Last received sequence number for the unit.
...				
<i>UnitNumber_n</i>		1	Binary	A unit number.
<i>UnitSequence_n</i>		4	Binary	Last received sequence number for the unit.

Return Bitfields Parameter Group

This parameter group, which may be repeated, indicates which attributes of a message will be returned by Cboe for the remainder of the session. This allows Members to tailor the echoed results to the needs of their system without paying for bandwidth or processing they do not need.

Listing of the return bitfields which are permitted per message is contained in ‘Section 7 – Return Bitfields per Message’.

Field	Offset	Length	Data Type	Description
<i>ParamGroupLength</i>	0	2	Binary	Number of bytes for the parameter group, including this field.
<i>ParamGroupType</i>	2	1	Binary	0x81
<i>MessageType</i>	3	1	Binary	Return message type for which the bitfields are being specified (e.g., 0x25 for an <i>Order Acknowledgment</i> message).
<i>NumberOfReturn Bitfields</i>	4	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield₁</i>	5	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfield_n</i>		1	Binary	Last bit field.

Example Login Request Message:

Note this example is for illustrative purposes only. Actual login messages will contain specification of return bitfields for a larger set messages and each return bitfield specification will be complete whereas the example below is only an illustration for purposes of demonstrating the construction of the Login Request message.

Field Name	Hexadecimal	Notes
StartOfMessage	BA BA	Start of message bytes.
MessageLength	3D 00	61 bytes
MessageType	37	Login Request
MatchingUnit	00	Always 0 for inbound messages
SequenceNumber	00 00 00 00	Always 0 for session level messages
SessionSubID	30 30 30 31	0001
Username	54 45 53 54	TEST
Password	54 45 53 54 49 4E 47 00 00 00	TESTING
NumberOfParam Groups	03	3 parameter groups
ParamGroupLength	0E 00	15 bytes for this parameter group
ParamGroupType	80	0x80 = Unit Sequences
NoUnspecified	01	True (replay only specified units)
UnitReplay		
NumberOfUnits	02	Two unit/sequence pairs to follow;
UnitNumber ₁	01	Unit 1
UnitSequence ₁	4A BB 01 00	Last received sequence of 113,482
UnitNumber ₂	02	Unit 2
UnitSequence ₂	00 00 00 00	Last received sequence of 0
ParamGroupLength	08 00	8 bytes for this parameter group
ParamGroupType	81	0x81 = Return Bitfields
MessageType	25	0x25 = Order Acknowledgment
NumberOfReturn Bitfields	03	3 bitfields to follow
ReturnBitfield ₁	00	No bitfields from byte 1
ReturnBitfield ₂	41	Symbol, Capacity
ReturnBitfield ₃	05	Account, ClearingAccount
ParamGroupLength	0B 00	11 bytes for this parameter group
ParamGroupType	81	0x81 = Return Bitfields
MessageType	2C	0x2C = Order Execution
NumberOfReturn Bitfields	06	6 bitfields to follow
ReturnBitfield ₁	00	No bitfields from byte 1
ReturnBitfield ₂	41	Symbol, Capacity
ReturnBitfield ₃	07	Account, ClearingFirm, ClearingAccount
ReturnBitfield ₄	00	No bitfields from byte 4
ReturnBitfield ₅	40	BaseLiquidityIndicator
ReturnBitfield ₆	00	No bitfields from byte 6

3.1.2 Logout Request

To end the session, the Member should send a `Logout Request` message. Cboe will finish sending any queued data and finally respond with a `Logout` message and close the connection.

A Member may simply close the connection without logging out, but may lose any queued messages by doing so.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x02
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	Always 0 for session level messages.

Example Logout Request Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	08 00	8 bytes
<i>MessageType</i>	02	<code>Logout Request</code>
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	00 00 00 00	Always 0 for session level messages

3.1.3 Client Heartbeat

See 'Section 2.4 – Heartbeats' for more information about heartbeats and the session level protocol.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x03
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	Always 0 for session level messages.

Example Client Heartbeat Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	08 00	8 bytes
<i>MessageType</i>	03	<code>Client Heartbeat</code>
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	00 00 00 00	Always 0 for session level messages

3.2 Cboe to Member

3.2.1 Login Response

A *Login Response* message is sent in response to a *Login Request* message. On a successful login, the *LoginResponseStatus* will be set to 'A'. On a failed login, *LoginResponseStatus* will be set to a value other than 'A', and *LoginResponseText* will be set to an appropriate failure description.

Cboe will verify Return Bitfields at login time. If the Return Bitfields in a Return Bitfields Parameter Group are invalid, *LoginResponseStatus* will be set to F, and *LoginResponseText* will include a description of which byte and bit are invalid. This is done to ensure that reserved fields are not used, and only options that apply to the local market are set. See 'Section 6 – Return Bitfields Per Message' for additional information.

Note that two sets of sequence numbers are available on the *Login Response*. The set of sequence numbers in the body are the actual Cboe to Member sequence numbers indicating the highest sequence numbers available per matching unit. If specified during login, the Unit Sequences Parameter Group will be returned as an echo of the sequence numbers the Member presented during login as the highest received. If the sequence numbers are different, the gap will be filled by Cboe during the replay. A subset of units can be provided in the *Login Request*; however, all units will be provided in the *Login Response*.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x24
<i>MatchingUnit</i>	5	1	Binary	Always 0 for session level messages.
<i>SequenceNumber</i>	6	4	Binary	Always 0 for session level messages.
<i>LoginResponseStatus</i>	10	1	Alphanumeric	Accepted, or the reason for the rejection. A = Login Accepted N = Not authorized (invalid username/password) D = Session is disabled B = Session in use S = Invalid session Q = Sequence ahead in Login message I = Invalid unit given in Login message F = Invalid return bit field in login message M = Invalid Login Request message structure
<i>LoginResponseText</i>	11	60	Text	Human-readable text with additional information about the reason for rejection. ASCII NUL (0x00) filled on the right, if necessary.
<i>NoUnspecifiedUnitReplay</i>	71	1	Binary	Echoed back from the original <i>Login Request</i> message.
<i>LastReceivedSequenceNumber</i>	72	4	Binary	Last inbound (Member to Cboe) message sequence number processed by Cboe.
<i>NumberOfUnits</i>	76	1	Binary	A number, n, of unit/sequence pairs to follow, one per unit. A pair for every unit will be sent, even if no messages have been sent to this port today. For unsuccessful logins, this will be 0.
<i>UnitNumber₁</i>		1	Binary	A unit number.
<i>UnitSequence₁</i>		4	Binary	Highest available Cboe to Member sequence number for the unit.
...				
<i>UnitNumber_n</i>		1	Binary	A unit number.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>UnitSequence_n</i>		4	Binary	Highest available Cboe to Member sequence number for the unit.
<i>NumberOfParam Groups</i>		1	Binary	Echoed back from the original Login Request message.
<i>ParamGroup₁</i>				Echoed back from the original Login Request message.
...				
<i>ParamGroup_n</i>				Echoed back from the original Login Request message.

Example Login Response Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	88 00	136 bytes
<i>MessageType</i>	24	Login Response
<i>MatchingUnit</i>	00	Always 0 for session messages
<i>SequenceNumber</i>	00 00 00 00	Always 0 for session level messages
<i>LoginResponseStatus</i>	41	A = Login Accepted
<i>LoginResponseText</i>	41 63 63 65 70 74 65 64 00	Accepted (padding) (padding) (padding) (padding) (padding)
<i>NoUnspecified UnitReplay</i>	01	True (replay only specified units)
<i>Last Received Sequence Number</i>	54 4A 02 00	Last sequence Cboe received of 150,100
<i>NumberOfUnits</i>	04	Four unit/sequence pairs to follow;
<i>UnitNumber 1</i>	01	Unit 1
<i>UnitSequence1</i>	4A BB 01 00	Actual last sequence of 113,482
<i>UnitNumber 2</i>	02	Unit 2
<i>UnitSequence2</i>	00 00 00 00	Actual last sequence of 0
<i>UnitNumber 3</i>	02	Unit 3
<i>UnitSequence3</i>	00 00 00 00	Actual last sequence of 0
<i>UnitNumber 4</i>	02	Unit 4
<i>UnitSequence4</i>	79 A1 00 00	Actual last sequence of 41,337
<i>NumberOfParam Groups</i>	03	3 parameter groups
<i>ParamGroupLength</i>	14 00	20 bytes for this parameter group
<i>ParamGroupType</i>	80	0x80 = Unit Sequences
<i>NoUnspecified UnitReplay</i>	01	True (replay unspecified units)
<i>NumberOfUnits</i>	03	Three unit/sequence pairs to follow;
<i>UnitNumber 1</i>	01	Unit 1
<i>UnitSequence1</i>	4A BB 01 00	Last received sequence of 113,482
<i>UnitNumber 2</i>	02	Unit 2
<i>UnitSequence2</i>	00 00 00 00	Last received sequence of 0
<i>UnitNumber 3</i>	04	Unit 4
<i>UnitSequence3</i>	79 A1 00 00	Last received sequence of 41,337
<i>ParamGroupLength</i>	08 00	8 bytes for this parameter group
<i>ParamGroupType</i>	81	0x81 = Return Bitfields

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>MessageType</i>	25	0x25 = Order Acknowledgment
<i>NumberOfReturn</i>	03	3 bitfields to follow
<i>Bitfields</i>		
<i>ReturnBitfield1</i>	00	No bitfields from byte 1
<i>ReturnBitfield2</i>	41	<i>Symbol, Capacity</i>
<i>ReturnBitfield3</i>	05	<i>Account, ClearingAccount</i>
<i>ParamGroupLength</i>	0C 00	12 bytes for this parameter group
<i>ParamGroupType</i>	81	0x81 = Return Bitfields
<i>MessageType</i>	2C	0x2C = Order Execution
<i>NumberOfReturn</i>	07	7 bitfields to follow
<i>Bitfields</i>		
<i>ReturnBitfield1</i>	00	No bitfields from byte 1
<i>ReturnBitfield2</i>	41	<i>Symbol, Capacity</i>
<i>ReturnBitfield3</i>	07	<i>Account, ClearingFirm, ClearingAccount</i>
<i>ReturnBitfield4</i>	00	No bitfields from byte 4
<i>ReturnBitfield5</i>	40	<i>BaseLiquidityIndicator</i>
<i>ReturnBitfield6</i>	00	No bitfields from byte 6
<i>ReturnBitfield7</i>	01	<i>SubLiquidityIndicator</i>

3.2.2 Logout

A Logout is usually sent in response to a Logout Request. Any queued data is transmitted, a Logout is sent, and Cboe will close the connection. However, a Logout may also be sent if the Member violates the protocol specification (e.g., by moving backwards in sequence number).

The Logout contains the last transmitted sequence number for each unit, allowing the Member to check that their last received sequence number matches.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x08
<i>MatchingUnit</i>	5	1	Binary	Always 0 for session level messages.
<i>SequenceNumber</i>	6	4	Binary	Always 0 for session level messages.
<i>LogoutReason</i>	10	1	Alphanumeric	The reason why the Logout message was sent. U = User Requested E = End of Day A = Administrative ! = Protocol Violation
<i>LogoutReasonText</i>	11	60	Text	Human-readable text with additional information about the reason for logout. Particularly useful if <i>LogoutReason</i> = ! (Protocol Violation).
<i>LastReceived SequenceNumber</i>	71	4	Binary	Last inbound (Member to Cboe) message sequence number processed by Cboe.
<i>NumberOfUnits</i>	75	1	Binary	A number, <i>n</i> (possibly 0), of unit/sequence pairs to follow, one per unit from which the client has received messages.
<i>UnitNumber₁</i>		1	Binary	A unit number.
<i>UnitSequence₁</i>		4	Binary	Highest available sequence number for the unit.
...				
<i>UnitNumber_n</i>		1	Binary	A unit number.
<i>UnitSequence_n</i>		4	Binary	Highest available sequence number for the unit.

Example Logout Response Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	55 00	85 bytes
<i>MessageType</i>	08	Logout
<i>MatchingUnit</i>	00	Always 0 for session level messages
<i>SequenceNumber</i>	00 00 00 00	Always 0 for session level messages
<i>LogoutReason</i>	55	U = User Requested
<i>LogoutReasonText</i>	55 73 65 72 00	User
<i>LastReceived SequenceNumber</i>	54 5A 02 00	Last Cboe received sequence of 150,100
<i>NumberOfUnits</i>	02	Two unit/sequence pairs to follow;
<i>UnitNumber₁</i>	01	Unit 1
<i>UnitSequence₁</i>	4A BB 01 00	Last sent sequence of 113,482
<i>UnitNumber₂</i>	02	Unit 2
<i>UnitSequence₂</i>	00 00 00 00	Last sent sequence of 0

3.2.3 Server Heartbeat

See 'Section 2.4 – Heartbeats' for more information about heartbeats and the session level protocol.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x09
<i>MatchingUnit</i>	5	1	Binary	Always 0 for session level messages.
<i>SequenceNumber</i>	6	4	Binary	Always 0 for session level messages.

Example Server Heartbeat Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	08 00	8 bytes
<i>MessageType</i>	09	Server Heartbeat
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	00 00 00 00	Always 0 for session level messages

3.2.4 Replay Complete

See 'Section 2.2 – Login, Replay and Sequencing' for more information on Login, sequencing and replay.

Field	Offset	Length	Data Type	Description
StartOfMessage	0	2	Binary	Must be 0xBA 0xBA.
MessageLength	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
MessageType	4	1	Binary	0x13
MatchingUnit	5	1	Binary	Always 0 for session level messages.
SequenceNumber	6	4	Binary	Always 0 for session level messages.

Example Replay Complete Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	08 00	8 bytes
<i>MessageType</i>	13	Replay Complete
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	00 00 00 00	Always 0 for session level messages

4 Application Messages

4.1 Member to Cboe

4.1.1 New Order

A `New Order` message consists of a number of required fields followed by a number of optional fields. The optional fields used are specified by setting bits in the `NewOrderBitfields`. Fields must be appended at the end of the message, starting with the lowest order enabled bit in the first bit field first.

Permitted input optional fields are described in ‘Section 5.1 – New Order’.

Field	Offset	Length	Data Type	Description
<code>StartOfMessage</code>	0	2	Binary	Must be 0xBA 0xBA.
<code>MessageLength</code>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <code>StartOfMessage</code> field.
<code>MessageType</code>	4	1	Binary	0x38
<code>MatchingUnit</code>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<code>SequenceNumber</code>	6	4	Binary	The sequence number for this message.
<code>ClOrdID</code>	10	20	Text	Corresponds to <code>ClOrdID</code> (11) in Cboe FIX. ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe. If the <code>ClOrdID</code> matches a live order, the order will be rejected as duplicate. Note: Cboe only enforces uniqueness of <code>ClOrdID</code> values among currently live orders, which includes long-lived, persisting GTC/GTD orders. However, we strongly recommend that you keep your <code>ClOrdID</code> values unique.
<code>Side</code>	30	1	Alphanumeric	Corresponds to <code>Side</code> (54) in Cboe FIX. 1 = Buy 2 = Sell
<code>OrderQty</code>	31	4	Binary	Corresponds to <code>OrderQty</code> (38) in Cboe FIX. Order quantity. System limit is 999,999 contracts.
<code>NumberOfNewOrderBitfields</code>	35	1	Binary	Bitfield identifying which bitfields are set. Field values must be appended to the end of the message.
<code>NewOrderBitfield¹</code>	36	1	Binary	Bitfield identifying fields to follow.
....				
<code>NewOrderBitfieldⁿ</code>		1	Binary	Last bitfield.
<code>Optional fields. . .</code>				

Required Order Attributes:

The following are required to be sent on new orders:

- Some form of symbology (see **Symbology** below);
- *Price* (limit orders) or *Price* and/or *OrdType* (limit order market orders); and,
- *Capacity*;

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

All price fields (*Price*, *StopPx*) must be entered as non-negative values.

All other values have defaults. See the table in **List of Options Fields** for additional information about each optional field, including its default value.

Symbology:

For additional information, refer to the Cboe US Equity and Options Symbology Reference.

Example New Order Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	59 00	89 bytes
<i>MessageType</i>	38	New Order
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>Side</i>	31	Buy
<i>OrderQty</i>	64 00 00 00	100 contracts
<i>NumberOfNewOrder Bitfields</i>	04	Four bitfields to follow
<i>NewOrderBitfield1</i>	04	<i>Price</i>
<i>NewOrderBitfield2</i>	C1	<i>Symbol</i> , <i>Capacity</i> , <i>RoutingInst</i>
<i>NewOrderBitfield3</i>	01	<i>Account</i>
<i>NewOrderBitfield4</i>	17	<i>MaturityDate</i> , <i>StrikePrice</i> , <i>PutOrCall</i> , <i>OpenClose</i>
<i>Price</i>	70 17 00 00 00 00 00 00	0.60
<i>Symbol</i>	4D 53 46 54 00 00 00 00	MSFT
<i>Capacity</i>	43	C = Customer
<i>RoutingInst</i>	52 00 00 00	R = Routable
<i>Account</i>	44 45 46 47 00 00 00 00 00 00 00 00 00 00 00 00	DEFG
<i>MaturityDate</i>	EF DB 32 01	2011-03-19
<i>StrikePrice</i>	98 AB 02 00 00 00 00 00	17.50
<i>PutOrCall</i>	31	1 = Call
<i>OpenClose</i>	4F	O = Open

4.1.2 New Order Cross (C1 and EDGX Only)

A New Order Cross message contains the details for both the agency (initiating) and contra side(s) of a cross order (such as an AIM order). The message consists of a number of required fields including *Symbol*, *Price*, *OrderQty*, and relevant clearing information for all parties, as well as a number of optional fields.

The first order in the list is the agency order, while the rest are contra side responses. There is a maximum of ten (10) contra-parties that can be supplied with the order, for a total of eleven (11) repeating groups, as described below.

In each repeating group, the *Side*, *AllocQty*, *ClOrdID*, *Capacity*, *OpenClose*, and *ClearingFirm* are always required. Beyond that, the bits in the *NewOrderCrossBitfields* control which fields are expected. Any fields that are specified in *NewOrderCrossBitfields* that appear in the repeating groups should not be supplied in the optional fields that come after the repeating groups.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Permitted input optional fields are described in ‘Section 5.2 – New Order Cross’.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x41
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>CrossID</i>	10	20	Text	Corresponds to <i>CrossID</i> (548) in Cboe FIX. Day-unique identifier for the cross order chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe.
<i>CrossType</i>	30	1	Alphanumeric	Corresponds to <i>CrossType</i> (549) in Cboe FIX. Type of auction order being submitted. This indicates the type of auction that will be initiated upon order entry. 1 = Automated Improvement Mechanism (“AIM”) 2 = Qualified Contingent Cross (“QCC”) 3 = Solicitation Cross (“SAM”) (C1 only) Effective on EDGX TBD
<i>CrossPrioritization</i>	31	1	Alphanumeric	Corresponds to <i>CrossPrioritization</i> (550) in Cboe FIX. Indicates which side of the cross order will be prioritized for execution. This identifies the Agency side. 1 = Buy 2 = Sell
<i>Price</i>	32	8	Binary Price	Corresponds to <i>Price</i> (44) in Cboe FIX. Auction Price. Must be non-negative.
<i>OrderQty</i>	40	4	Binary	Corresponds to <i>OrderQty</i> (38) in Cboe FIX. Order quantity. System limit is 999,999 contracts.
<i>NumberOfNewOrderCrossBitfields</i>	44	1	Binary	Bitfield identifying which bitfields are set
<i>NewOrderCrossBitfield¹</i>	45	1	Binary	Bitfield identifying fields to follow.
....				
<i>NewOrderCrossBitfieldⁿ</i>		1	Binary	<i>Last bitfield.</i>
<i>GroupCnt</i>		2	Binary	Number of order allocations represented by repeating groups included in this cross order. Must be at least 2 (One agency and one contra), and no more than 11.
<i>Repeating Groups of...</i>				
<i>Side</i>		1	Alphanumeric	Corresponds to <i>Side</i> (54) in Cboe FIX. 1 = Buy

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				2 = Sell
<i>AllocQty</i>		4	Binary	Corresponds to <i>AllocQty</i> (80) in Cboe FIX. Number of contracts for this party.
<i>ClOrdID</i>		20	Text	Corresponds to <i>ClOrdID</i> (11) in Cboe FIX. Day-unique ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe. If the <i>ClOrdID</i> matches a live order, the order will be rejected as duplicate. Note: Cboe only enforces uniqueness of <i>ClOrdID</i> values among currently live orders. However, we strongly recommend that you keep your <i>ClOrdID</i> values day-unique.
<i>Capacity</i>		1	Alpha	Corresponds to <i>OrderCapacity</i> (47) in Cboe FIX. C = Customer M = Market Maker F = Firm U = Professional Customer N = Non-Cboe Market Maker B = Broker-Dealer J = Joint Back Office
<i>OpenClose</i>		1	Alphanumeric	Corresponds to <i>OpenClose</i> (77) in Cboe FIX. Indicates status of client position in the option leg. O = Open C = Close N = None* *Option legs with a <i>Capacity</i> of "M" or "N" will not be required to specify <i>OpenClose</i> on their legs or may optionally specify a value of "N", unless the series is limited to closing only. If the leg is limited to closing only transactions only a <i>Capacity</i> of M or N will be permitted to submit <i>OpenClose</i> = O.
<i>GiveUpFirmID</i>		4	Alpha	Corresponds to <i>GiveUpFirmID</i> (9946) in Cboe FIX. EFID that will clear the trade.
<i>Account (Optional)</i>		16	Text	See List of Optional Fields .
<i>CMTANumber (Optional)</i>		4	Binary	See List of Optional Fields .
<i>ClearingAccount (Optional)</i>		4	Text	See List of Optional Fields .
<i>FrequentTraderID (Optional)</i>		6	Text	See List of Optional Fields .
<i>Optional fields. . .</i>				Optional fields as set in the bitmap. Note, optional fields that occur in the repeating groups appear above, repeating per group, not within this block.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Required Order Attributes:

- Some form of symbology (see **Symbology** below)
- Agency order's *Side* must match the cross order's *CrossPrioritization*
- Each contra-party allocation must have the opposite *Side*
- Each side's cumulative *AllocQty* must equal the cross order's *OrderQty*

Symbology:

For additional information, refer to the Cboe US Equity and Options Symbology Reference.

Example New Order Cross Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	B0 00	176 bytes
<i>MessageType</i>	41	New Order Cross
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>CrossID</i>	4E 5A 31 56 37 42 4A 5F 41 63 63 65 70 74 42 75 79 00 00 00	NZ1V7BJ_AcceptBuy
<i>CrossType</i>	31	1 = AIM Order
<i>CrossPrioritization</i>	31	1 = Agency Buy
<i>Price</i>	20 4E 00 00 00 00 00 00	\$2.00
<i>OrderQty</i>	64 00 00 00	100 contracts
<i>NumberOfNewOrderCross</i>	02	Two bitfields to follow
<i>Bitfields</i>		
<i>NewOrderCrossBitfield1</i>	41	<i>Symbol, TargetPartyID</i>
<i>NewOrderCrossBitfield2</i>	30	<i>CMTANumber, ClearingAccount</i>
<i>GroupCnt</i>	03 00	Three repeating groups to follow
<i>Side</i>	31	1 = Buy
<i>AllocQty</i>	64 00 00 00	100 contracts
<i>ClOrdID</i>	51 4C 37 53 5A 37 43 5F 61 67 65 6E 63 79 00 00 00 00 00 00	QL7SZ7C_agency
<i>Capacity</i>	43	C = Customer
<i>OpenClose</i>	43	C = Close
<i>GiveUpFirmID</i>	44 45 46 47	DEFG
<i>CMTANumber</i>	00 00 00 00	No <i>CMTANumber</i> for this order
<i>ClearingAccount</i>	00 00 00 00	No <i>ClearingAccount</i> for this order
<i>Side</i>	32	2 = Sell
<i>AllocQty</i>	28 00 00 00	40 contracts
<i>ClOrdID</i>	51 4C 39 4B 38 55 56 5F 63 6F 6E 74 72 61 31 00 00 00 00 00	QL9K8UV_contra1
<i>Capacity</i>	46	F = Firm
<i>OpenClose</i>	4F	O = Open
<i>GiveUpFirmID</i>	41 42 43 44	ABCD
<i>CMTANumber</i>	27 02 00 00	551
<i>ClearingAccount</i>	57 58 59 5A	WXYZ
<i>Side</i>	32	2 = Sell
<i>AllocQty</i>	3C 00 00 00	60 contracts
<i>ClOrdID</i>	51 4C 39 54 35 59 44 5F 63 6F 6E 74 72 61 32 00 00 00 00 00	QL9T5YD_contra2
<i>Capacity</i>	46	F = Firm
<i>OpenClose</i>	4F	O = Open

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>GiveUpFirmID</i>	41 42 43 44	ABCD
<i>CMTANumber</i>	7B 00 00 00	123
<i>ClearingAccount</i>	57 58 59 5A	WXYZ
<i>Symbol</i>	30 30 51 30 6B 41 00 00	00Q0kA
<i>Target Party ID</i>	43 44 45 46	CDEF

4.1.3 New Complex Order (C1, EDGX and C2 Only)

A New Complex Order message contains the details required to enter an order on a complex instrument created with previously entered New Complex Instrument request. The message is similar to a New Order with an additional repeating group of the positions for each leg. The positions must be in the order returned by the system in the Complex Instrument Accepted response message, not the order supplied in the New Complex Instrument request. Complex orders in cross product spreads (ie SPX/SPXW, IWM/RUT, DIA/DJX, VIX/VXX, MNX/NDX) where the products do not operate on the same matching unit cannot leg into the simple book.

Permitted input optional fields are described in 'Section 5.3 – New Complex Order'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x4B
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>ClOrdID</i>	10	20	Text	Corresponds to <i>ClOrdID</i> (11) in Cboe FIX. ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe. If the <i>ClOrdID</i> matches a live order, the order will be rejected as duplicate. Note: Cboe only enforces uniqueness of <i>ClOrdID</i> values among currently live orders, which includes long-lived, persisting GTC/GTD orders. However, we strongly recommend that you keep your <i>ClOrdID</i> values unique.
<i>Side</i>	30	1	Alphanumeric	Corresponds to <i>Side</i> (54) in Cboe FIX. 1 = Buy 2 = Sell
<i>OrderQty</i>	31	4	Binary	Corresponds to <i>OrderQty</i> (38) in Cboe FIX. Order quantity. System limit is 999,999 contracts.
<i>NumberOfNewComplexOrderBitfields</i>	35	1	Binary	Bitfield identifying which bitfields are set. Field values must be appended to the end of the message.
<i>NewComplexOrderBitfield¹</i>	36	1	Binary	Bitfield identifying fields to follow.
....				
<i>NewComplexOrderBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>NoLegs</i>		1	Binary	Corresponds to <i>NoLegs</i> (555) in Cboe FIX.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				Indicates the number of repeating groups to follow. Must be a minimum of 2 and a maximum of 12.
Repeating Group <i>ComplexLegOrderInfo</i> must occur the number of times specified in <i>NoLegs</i> . Each field occurs in each group, in order as shown below. Optional fields occur only if corresponding bits in bitfields are set.				
<i>LegPositionEffect</i>	1	Alphanumeric	Corresponds to <i>LegPositionEffect</i> (564) in Cboe FIX. Indicates status of client position in option for this leg. O = Open C = Close N = None* *Only Orders with an <i>OrderCapacity</i> of "M" or "N" will be allowed to specify "N" for <i>LegPositionEffect</i> . Contracts which are limited to closing only transactions with a <i>LegPositionEffect</i> value of O will be rejected unless the <i>Capacity</i> field is "M" or "N" and <i>TimeInForce</i> is 3 (Immediate or Cancel).	
<i>Optional fields...</i>				Optional fields as set in the bitmap. Note, optional fields that occur in the repeating groups appear above, repeating per group, not within this block.

Required Order Attributes:

The following are required to be sent:

- *Symbol*
- *Price* only (limit orders) or *Price* and/or *OrdType* (limit or market orders); and,
- *Capacity*
- *LegPositionEffect*

All other values have defaults. See the table in **List of Options Fields** for additional information about each optional field, including its default value.

See the Cboe US Equity and Options Symbology Reference for information on symbology.

Example New Complex Order Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	4D 00	77 bytes
<i>MessageType</i>	4B	New Complex Order
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>Side</i>	31	Buy
<i>OrderQty</i>	64 00 00 00	100 contracts
<i>NumberOfNewOrder Bitfields</i>	02	Two bitfields to follow
<i>NewOrderBitfield1</i>	E4	<i>Price</i> , <i>Symbol</i> , <i>Capacity</i> , <i>RoutingInst</i>
<i>NewOrderBitfield2</i>	01	<i>Account</i>
<i>NoLegs</i>	03	Three legs
<i>LegPositionEffect</i>	4F	O = Open
<i>LegPositionEffect</i>	4F	O = Open

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>LegPositionEffect</i>	4F	O = Open
<i>Price</i>	38 FF FF FF FF FF FF FF	-0.02
<i>Symbol</i>	30 30 30 30 43 31 00 00	0000C1
<i>Capacity</i>	43	C = Customer
<i>RoutingInst</i>	42 00 00 00	B = Book only, COA eligible
<i>Account</i>	44 45 46 47 00 00 00 00 00 00 00 00 00 00 00 00	DEFG

4.1.4 New Order Cross Multileg (C1 and EDGX Only)

A New Order Cross Multileg message contains the details for both the agency (initiating) and contra side(s) of a cross order (such as an AIM order). The two-sided order consists of a number of required fields including *Symbol*, *Price*, *OrderQty*, and relevant clearing information for both the agency and contra sides, as well as a number of optional fields. A maximum of ten (10) contra-parties will be accepted per order.

Cross Order Acknowledgement, Cross Order Rejected, and Cross Order Cancelled message types will be used by the Exchange to respond to New Order Cross Multileg messages.

Permitted input optional fields are described in 'Section 5.4 – New Order Cross Multileg'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x5A
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>CrossID</i>	10	20	Text	Corresponds to <i>CrossID</i> (548) in Cboe FIX. Day-unique identifier for the cross order chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe.
<i>CrossType</i>	30	1	Alphanumeric	Corresponds to <i>CrossType</i> (549) in Cboe FIX. Type of auction order being submitted. This indicates the type of auction that will be initiated upon order entry. 1 = Automated Improvement Mechanism ("AIM") (C1 and EDGX only) 2 = Qualified Contingent Cross ("QCC") 3 = Solicitation Cross ("SAM") (C1 only)
<i>CrossPrioritization</i>	31	1	Alphanumeric	Corresponds to <i>CrossPrioritization</i> (550) in Cboe FIX. Indicates which side of the cross multileg order will be prioritized for execution. This identifies the Agency side. 1 = Buy 2 = Sell
<i>Price</i>	32	8	Binary Price	Corresponds to <i>Price</i> (44) in Cboe FIX. Auction Price.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>OrderQty</i>	40	4	Binary	Corresponds to <i>OrderQty</i> (38) in Cboe FIX. Order quantity. System limit is 999,999 contracts.
<i>NumberOfNewOrderCrossMultilegBitfields</i>	44	1	Bit Field	Bitfield identifying which bitfields are set.
<i>NewOrderCrossMultilegBitfield¹</i>	45	1	Bit Field	Bitfield identifying fields to follow.
....				
<i>NewOrderCrossMultilegBitfieldⁿ</i>		1	Bit Field	Last <i>bitfield</i> .
<i>GroupCnt</i>		2	Binary	Number of order allocations represented by repeating groups included in this cross order. Must be at least 2 (One agency and one contra), and no more than 11.
<i>Repeating Groups of...</i>				
<i>Side</i>		1	Alphanumeric	Corresponds to <i>Side</i> (54) in Cboe FIX. 1 = Buy 2 = Sell
<i>AllocQty</i>		4	Binary	Corresponds to <i>AllocQty</i> (80) in Cboe FIX. Number of contracts for this party.
<i>ClOrdID</i>		20	Text	Corresponds to <i>ClOrdID</i> (11) in Cboe FIX. Day-unique ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe. If the <i>ClOrdID</i> matches a live order, the order will be rejected as duplicate. Note: Cboe only enforces uniqueness of <i>ClOrdID</i> values among currently live orders. However, we strongly recommend that you keep your <i>ClOrdID</i> values day-unique.
<i>Capacity</i>		1	Alpha	Corresponds to <i>OrderCapacity</i> (47) in Cboe FIX. C = Customer M = Market Maker F = Firm U = Professional Customer N = Non-Cboe Market Maker B = Broker-Dealer J = Joint Back Office L = Non-Trading Permit Holder Affiliate
<i>GiveUpFirmID</i>		4	Alpha	Corresponds to <i>GiveUpFirmID</i> (9946) in Cboe FIX. EFID that will clear the trade.
<i>LegPositionEffects</i>		12	Alpha	Indicates status of the client position in the option for each complex option leg. This value String of characters "O", "C", and "N", equal in length to the number of option legs of the instrument. If an equity leg is present it will

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				<p>always be the last leg, and the position effect must be set to "N".</p> <p>O = Open C = Close N = None*</p> <p>*Orders with an <i>Capacity</i> of "M" or "N" will not be required to specify a position effect on their orders or may specify a value of "N". A <blank> will be sent to OCC.</p> <p>Contracts which are limited to closing only transactions with a value of "O" will be rejected unless the <i>Capacity</i> field is "M" (Market Maker) and <i>TimeInForce</i> is 3 (Immediate or Cancel).</p>
<i>Account (Optional)</i>		16	Text	See List of Optional Fields .
<i>CMTANumber (Optional)</i>		4	Binary	See List of Optional Fields .
<i>ClearingAccount (Optional)</i>		4	Text	See List of Optional Fields .
<i>ClearingOptionalData (Optional)</i>		16	Text	See List of Optional Fields .
<i>EquityPartyId (Optional)</i>		4	Alpha	See List of Optional Fields .
<i>EquityLegShortSell (Optional)</i>		1	Alpha	See List of Optional Fields .
<i>FrequentTraderID (Optional)</i>		6	Text	See List of Optional Fields .
<i>Optional fields. . .</i>				Optional fields as set in the bitmap. Note, optional fields that occur in the repeating groups appear above, repeating per group, not within this block.

Required Order Attributes:

- Some form of symbology (see **Symbology** below)
- Agency order's *Side* must match the cross order's *CrossPrioritization*
- Each contra-party allocation must have the opposite *Side*
- Each side's cumulative *AllocQty* must equal the cross order's *OrderQty*

Example New Order Cross Multileg Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	E3 00	227 bytes
<i>MessageType</i>	5A	New Order Cross Multileg
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>CrossID</i>	4E 5A 31 56 37 42 4A 5F 41 63 63 65 70 74 42 75 79 00 00 00	NZ1V7BJ_AcceptBuy
<i>CrossType</i>	31	1 = AIM Order
<i>CrossPrioritization</i>	31	1 = Agency Buy
<i>Price</i>	A8 61 00 00 00 00 00 00	\$2.50

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>OrderQty</i>	64 00 00 00	100 contracts
<i>NumberOfNewOrderCross</i>	03	Three bitfields to follow
<i>Multileg Bitfields</i>		
<i>NewOrderCrossMultilegBitfield1</i>	61	<i>Symbol</i> ,
		<i>TargetPartyID</i> , <i>AttributedQuote</i>
<i>NewOrderCrossMultilegBitfield2</i>	30	<i>CMTANumber</i> , <i>ClearingAccount</i>
<i>NewOrderCrossMultilegBitfield3</i>	01	<i>ClientID</i>
<i>GroupCnt</i>	03 00	Three repeating groups to follow
<i>Side</i>	31	1 = Buy
<i>AllocQty</i>	64 00 00 00	100 contracts
<i>ClOrdID</i>	51 4C 37 53 5A 37 43 5F 61 67 65 6E 63 79 00 00 00 00 00 00	QL7SZ7C_agency
<i>Capacity</i>	43	C = Customer
<i>GiveUpFirmID</i>	44 45 46 47	DEFG
<i>LegPositionEffects</i>	43 43 4F 4F 20 20 20 20 20 20 20 20	CCOO – Instrument has four legs, Close first two legs, Open last two legs
<i>CMTANumber</i>	00 00 00 00	No <i>CMTANumber</i> for this order
<i>ClearingAccount</i>	00 00 00 00	No <i>ClearingAccount</i> for this order
<i>Side</i>	32	2 = Sell
<i>AllocQty</i>	28 00 00 00	40 contracts
<i>ClOrdID</i>	51 4C 39 4B 38 55 56 5F 63 6F 6E 74 72 61 31 00 00 00 00 00	QL9K8UV_contra1
<i>Capacity</i>	46	F = Firm
<i>GiveUpFirmID</i>	41 42 43 44	ABCD
<i>LegPositionEffects</i>	43 43 43 43 20 20 20 20 20 20 20 20	CCCC – Instrument has four legs, Close on all four legs
<i>CMTANumber</i>	27 02 00 00	551
<i>ClearingAccount</i>	57 58 59 5A	WXYZ
<i>Side</i>	32	2 = Sell
<i>AllocQty</i>	3C 00 00 00	60 contracts
<i>ClOrdID</i>	51 4C 39 54 35 59 44 5F 63 6F 6E 74 72 61 32 00 00 00 00 00	QL9T5YD_contra2
<i>Capacity</i>	46	F = Firm
<i>GiveUpFirmID</i>	41 42 43 44	ABCD
<i>LegPositionEffects</i>	4F 43 4F 43 20 20 20 20 20 20 20 20	OCOC – Instrument has four legs, mixture of Open and Close
<i>CMTANumber</i>	7B 00 00 00	123
<i>ClearingAccount</i>	57 58 59 5A	WXYZ
<i>Symbol</i>	30 30 51 30 6B 41 00 00	00Q0kA
<i>Target Party ID</i>	43 44 45 46	CDEF
<i>AttributedQuote</i>	5A	Z = Attribute EFID and Client ID
<i>ClientID</i>	52 32 44 32	R2D2

4.1.5 Cancel Order

Request to cancel either a single order or mass cancellation of a group of orders. Note that this does not apply to open orders across multiple sessions.

A single order cancellation references the *ClOrdID* from a previous order (*OrigClOrdID* field). An Order Cancel Request message cannot be used to cancel a single quote, referencing a previous *OrderID* from a quote will be rejected.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Order Cancel Request messages for GTC and GTD orders may continue to be issued anytime after the trading session ends at 4:00 PM ET (4:15 PM ET for select ETF's) and prior to the trading session disconnecting at 4:45 PM ET. All other order message types received after the market closes at 4:00 PM ET (4:15 PM ET for select ETF's) will be rejected.

Mass cancellation of a group of orders can be done with one of two methods, using either the *MassCancel* (legacy) or *MassCancelInst* optional fields. If both optional fields *MassCancel* and *MassCancelInst* are specified, the *Cancel Order* request will be rejected. **Members are encouraged to use the *MassCancelInst* method as the legacy *MassCancel* method will be deprecated in the future with notice.**

Legacy Mass Cancel method:

- Populate the *MassCancel* required field (and do not specify the *MassCancelInst* optional field)
- Specify the *ClearingFirm* field, optionally the *RiskRoot* field, and optionally *MassCancelId* if a single *Mass Cancel Acknowledgement* is requested.
- Specify the *MassCancelLockout* optional field to request subsequent rejection of new orders based on the level of *MassCancel* (i.e. Firm level, Risk Root level, or Custom Group Id level)

MassCancelInst method

- Specify the *MassCancelInst* optional field
- Specify the *ClearingFirm* field, optionally the *RiskRoot* field, and optionally *MassCancelId* if the Acknowledgement Style is set to S or B
- Risk lockout is optionally specified using the *MassCancelInst* field. As a result, the *MassCancelLockout* field will be ignored when *MassCancelInst* is present.

When specifying the *RiskRoot* field, using the underlying symbol is strongly recommended. Mass cancellations are always performed at the risk root (underlying) level.

The system limits the rate at which identical Mass Cancel requests can be submitted to the system. Requests are restricted to twenty (20) messages per second per port.

An identical Mass Cancel message is defined as a message having all of the same *CustomGroupID*, *Symbol*, *Clearing Firm*, *Lockout Instruction*, *Instrument Type Filter* and *GTC Order Filter* field values, as a previously received message.

Permitted input optional fields are described in 'Section 5.4 – Cancel Order'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x39
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>OrigClOrdID</i>	10	20	Text	Corresponds to <i>OrigClOrdID</i> (41) in Cboe FIX. <i>ClOrdID</i> of the order to cancel. For mass cancel requests, must be empty (all zeroes).
<i>NumberOfCancelOrderBitfields</i>	30	1	Binary	Bitfield identifying bitfields which are set. May be 0. Field values must be appended to the end of the message.
<i>CancelOrderBitfield¹</i>	31	1	Binary	Bitfield identifying fields to follow. Only present if <i>NumberOfCancelOrderBitfields</i> is non-zero.
...				
<i>CancelOrderBitfieldⁿ</i>		1	Binary	Last bitfield.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Optional fields. . .				
----------------------	--	--	--	--

Example Cancel Order Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	22 00	34 bytes
<i>MessageType</i>	39	Cancel Order
<i>MatchingUnit</i>	0	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence Number 100
<i>OrigClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>NumberOfCancel</i>	01	One bitfield to follow
<i>OrderBitfields</i>		
<i>CancelOrderBitfield1</i>	01	<i>ClearingFirm</i>
<i>ClearingFirm</i>	54 45 53 54	TEST

Example Mass Cancel Order Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	4F 00	79 bytes
<i>MessageType</i>	39	Cancel Order
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence Number 100
<i>OrigClOrdID</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	(empty)
<i>NumberOfCancel</i>	02	Two bitfields to follow
<i>OrderBitfields</i>		
<i>CancelOrderBitfield1</i>	19	<i>ClearingFirm</i> , <i>RiskRoot</i> , <i>MassCancelId</i>
<i>CancelOrderBitfield2</i>	01	<i>MassCancelInst</i>
<i>ClearingFirm</i>	54 45 53 54	TEST
<i>RiskRoot</i>	4D 53 46 54 00 00	MSFT
<i>MassCancelId</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>MassCancelInst</i>	46 53 4C 42 00 00 00 00 00 00 00 00 00 00 00 00	F = Cancel orders matching clearing firm TEST S = Single ack L = Lockout symbol MSFT B = Cancel simple and complex

4.1.6 Modify Order

Request to modify an order. The order attributes to be modified are selected using *NumberOfModifyBitfields* and some number of bitfields to follow. *Price*, *OrderQty*, *OrdType*, *MaxFloor* (**BZX, C1, and C2 only**), *FrequentTraderID* (**C1 only**), and *StopPx* may be adjusted. Modifies will result in a loss of time priority unless the modification involves a decrease in *OrderQty*, or a change to *MaxFloor*, *FrequentTraderID*, or *StopPx*. *OrdType* may be adjusted from Limit to Market.

Changes in *OrderQty* result in an adjustment of the current order's *OrderQty*. The new *OrderQty* does not directly replace the current order's *LeavesQty*. Rather, a delta is computed from the current *OrderQty* and the replacement *OrderQty*. This delta is then applied to the current *LeavesQty*. If the resulting *LeavesQty* is less than or equal to zero,

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

the order is cancelled. This results in safer behavior when the modification request overlaps partial fills for the current order, leaving the Member in total control of the share exposure of the order.

A *Modify Order* should not be issued until the *Order Acknowledgement* for the previous *New Order* or *Order Modified* message for the previous *Modify Order* has been received. The BOE handler will reject a new *Modify Order* if it has not been accepted or it has not seen the result of the prior modification from the Matching Engine. However, *Modify Order* requests that merely reduce *OrderQty* may be overlapped if the existing *ClOrdID* is reused, as long as the trading identifier has not been opted-in to daily limit trading risk controls. This is the only case where reuse of the *ClOrdID* is allowed.

The *OrderQty* and *Price* fields in the optional field block must be present on all *Modify Order* requests. Messages sent without *OrderQty* or *Price* fields will be rejected.

Permitted input optional fields are described in ‘Section 5.5 – Modify Order’.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x3A
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>ClOrdID</i>	10	20	Text	New <i>ClOrdID</i> for this order.
<i>OrigClOrdID</i>	30	20	Text	Corresponds to <i>OrigClOrdID</i> (41) in Cboe FIX. <i>ClOrdID</i> of the order to replace. In the case of multiple changes to a single order, this will be the <i>ClOrdID</i> of the most recently accepted change.
<i>NumberOfModifyOrderBitfields</i>	50	1	Binary	Bitfield identifying bitfields which are set. May be 0. Field values must be appended to the end of the message.
<i>ModifyOrder Bitfield¹</i>	51	1	Binary	Bitfield identifying fields to follow.
...				
<i>ModifyOrder Bitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Modify Order Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	3E 00	82 bytes
<i>MessageType</i>	3A	Modify Order
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence Number 100
<i>ClOrdID</i>	41 42 43 31 32 34 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC124
<i>OrigClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>NumberOfModifyOrderBitfields</i>	01	One bitfield to follow
<i>ModifyOrderBitfield1</i>	0C	<i>OrderQty</i> , <i>Price</i>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>OrderQty</i>	64 00 00 00	100 contracts
<i>Price</i>	08 E2 01 00 00 00 00 00	12.34

4.1.7 Quote Update

Request to enter or update one or more quotes. *Quote Update* requests will be forwarded in their entirety to the matching engine instance as a single message and will be applied in a single transaction. Optional bitfields are not supported for any response messages for quotes.

All options in a single *Quote Update* must trade under a single risk root. Requests which include options trading under multiple risk roots will be rejected in their entirety.

A quote is unique per port, EFID, and side. You may quote multiple price levels of depth using either multiple EFIDs on a single port or with the same EFID on multiple ports.

Quote requests are one-sided. To delete a quote, send an update with a zero price and size.

Quotes may utilize simple options only; complex options quotes may not be submitted.

All quotes will be automatically cancelled at the end of the trading day.

Quotes may be marked post only. If a quote crosses the NBBO or displayed Cboe book, it will be rejected. If a quote would be displayed at a price that locks the NBBO, it will be accepted/slid or rejected based on the *PostingInstruction* on the quote.

On **BZX Options only**, quote prices at non-displayable increments are permitted. Prices will be adjusted to the most aggressive non-locking price. Quotes may work (but not display) to lock an away market. Once posted, quotes act as a Display Price Sliding order. C2 and EDGX quotes act as Price Adjust orders.

If a quote modification is rejected, the resting quote being modified is also cancelled.

Executions, unsolicited cancels, and unsolicited modification response messages from the exchange are different from those for orders. They are optimized for efficiency and contain some different data elements (e.g., *QuoteUpdateID*) than the respective messages for orders.

The *PreventMatch* field may not be specified on the *Quote Update* message and Match Trade Prevention is only available if defaulted at the port level. For Bulk Quoting ports, only Cancel Newest, Cancel Oldest, or Cancel Both are permitted. If a Bulk Quoting port is not configured with both a default MTP Modifier and Unique ID Level, Match Trade Prevention will be disabled.

Capacity may not be changed when modifying a quote. To change *Capacity* of a resting quote, you must first send a quote with zero price and size and then re-enter the quote with the desired *Capacity*.

The Quote Execution message will be the only Quote related message available over ODROP and FIXDROP.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x55
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>QuoteUpdateID</i>	10	16	Text	<p>ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe.</p> <p>Responses, both to the Quote Update and any Quote Executions, Quote Cancellations, and Quote Modification messages will include this identifier.</p> <p>Note: Cboe only enforces uniqueness of <i>QuoteUpdateID</i> values among those not yet acknowledged by the ME. However, we strongly</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				recommend that you keep your <i>QuoteUpdateID</i> values unique for a trading day.
<i>ClearingFirm</i>	26	4	Alpha	EFID that will clear the trade. If left blank, the port attribute value of 'Default EFID' is used.
<i>ClearingAccount</i>	30	4	Alpha	Corresponds to <i>OnBehalfOfSubID</i> (116) and <i>ClearingAccount</i> (440) in Cboe FIX. See List of Optional Fields for additional information.
<i>CMTANumber</i>	34	4	Binary	Corresponds to <i>CMTANumber</i> (439) in Cboe FIX. See List of Optional Fields for additional information.
<i>Account</i>	38	16	Text	Corresponds to <i>Account</i> (1) in Cboe FIX. See List of Optional Fields for additional information.
<i>CustomGroupID</i>	54	2	Binary	Optional. Used to group orders for use in <i>Purge Orders</i> . Set to 0 if functionality not needed.
<i>Capacity</i>	56	1	Alpha	Corresponds to <i>OrderCapacity</i> (47) in Cboe FIX. See List of Optional Fields for additional information.
<i>Reserved</i>	57	15	Binary	Reserved for future expansion. To maintain forward compatibility, fill with 0.
<i>SendTime</i>	72	8	DateTime	Optional, may be filled with binary zero (0x00). Market Makers desiring the Exchange to report quote events to the CAT under the Options Market Maker Quote Exemption must populate this field with the quote send time with at least millisecond granularity. Market Makers that do not populate this field will be required to report their quotes to CAT.
<i>PostingInstruction</i>	80	1	Text	P = Post Only (do not remove liquidity) B = Book Only (allow removal of liquidity, available for Market Makers only) N = Book Only, No Slide R = Post Only, No Slide (do not remove liquidity)
<i>SessionEligibility</i>	81	1	Text	A = Participates in both Global and Regular Trading Hours (C1, C2, and EDGX only) R = Regular Trading Hours (RTH) only
<i>QuoteCnt</i>	82	1	Binary	Number of repeating groups included in this quote update. Allowed values are 1-20.
<i>Repeating Groups of...</i>				
<i>Symbol</i>		6	Alphanumeric	Cboe native identifier
<i>Side</i>		1	Text	1 = Buy 2 = Sell
<i>OpenClose</i>		1	Text	Corresponds to <i>OpenClose</i> (77) in Cboe FIX. See List of Optional Fields for additional information.
<i>Price</i>		8	Binary Price	Limit price. To cancel an existing quote, specify a size of 0.
<i>OrderQty</i>		4	Binary	Order quantity. System limit is 999,999 contracts. To cancel an existing quote, specify a size of 0.
<i>Reserved</i>		12	Binary	Reserved for future expansion. To maintain forward compatibility, fill with 0.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Example Quote Update Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	91 00	145 bytes
<i>MessageType</i>	55	Quote Update
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>QuoteUpdateID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00	ABC123
<i>ClearingFirm</i>	41 42 43 44	ABCD
<i>ClearingAccount</i>	57 58 59 5A	WXYZ
<i>CMTANumber</i>	31 32 33 34	1234
<i>Account</i>	44 45 46 47 41 42 43 44 00 00 00 00 00 00 00 00	DEFGABCD
<i>CustomGroupID</i>	C8 00	200
<i>Capacity</i>	4D	M = Market Maker
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	Reserved
<i>SendTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>PostingInstruction</i>	50	P (Post Only)
<i>SessionEligibility</i>	52	R (RTH Only)
<i>QuoteCnt</i>	02	Two Quotes
<i>Symbol</i>	30 30 36 69 70 41	006ipA
<i>Side</i>	31	1 = Buy
<i>OpenClose</i>	4F	O = Open
<i>Price</i>	C8 32 00 00 00 00 00 00	1.30
<i>OrderQty</i>	64 00 00 00	100 contracts
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00	Reserved
<i>Symbol</i>	30 30 34 63 53 73	004cSs
<i>Side</i>	32	2 = Sell
<i>OpenClose</i>	4F	O = Open
<i>Price</i>	AC 07 01 00 00 00 00 00	6.75
<i>OrderQty</i>	F4 01 00 00	500 contracts
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00	Reserved

4.1.8 Quote Update (Short)

A shorter version of Quote Update which restricts the information which can be presented. Uses less bandwidth than the Quote Update message but messages presented to the Matching Engine are identical between both Quote Update and Quote Update (Short) messages.

Quote Update (Short) does not allow sending *Account* but a default for this field may be set at the port level. *CMTANumber* may never be included on a Quote Update (Short) message.

This message uses a smaller format *Price* and *OrderQty* on each quote update.

All other comments concerning Quote Update in the previous section apply to Quote Update (Short) equally.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x59

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>QuoteUpdateID</i>	10	16	Text	<p>ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe.</p> <p>Responses, both to the Quote Update and any Quote Executions, Quote Cancellations, and Quote Modification messages will include this identifier.</p> <p>Note: Cboe only enforces uniqueness of <i>QuoteUpdateID</i> values among those not yet acknowledged by the ME. However, we strongly recommend that you keep your <i>QuoteUpdateID</i> values unique for a trading day.</p>
<i>ClearingFirm</i>	26	4	Alpha	EFID that will clear the trade. If left blank, the port attribute value of 'Default EFID' is used.
<i>ClearingAccount</i>	30	4	Alpha	<p>Corresponds to <i>OnBehalfOfSubID</i> (116) and <i>ClearingAccount</i> (440) in Cboe FIX.</p> <p>See List of Optional Fields for additional information.</p>
<i>CustomGroupID</i>	34	2	Binary	Optional. Used to group orders for use in <i>Purge Orders</i> . Set to 0 if functionality not needed.
<i>Capacity</i>	36	1	Alpha	<p>Corresponds to <i>OrderCapacity</i> (47) in Cboe FIX.</p> <p>See List of Optional Fields for additional information.</p>
<i>Reserved</i>	37	3	Binary	Reserved for future expansion. To maintain forward compatibility, fill with 0.
<i>SendTime</i>	40	8	DateTime	<p>Optional, may be filled with binary zero (0x00).</p> <p>Market Makers desiring the Exchange to report quote events to the CAT under the Options Market Maker Quote Exemption must populate this field with the quote send time with at least millisecond granularity. Market Makers that do not populate this field will be required to report their quotes to CAT.</p>
<i>PostingInstruction</i>	48	1	Text	<p>P = Post Only (do not remove liquidity)</p> <p>B = Book Only (allow removal of liquidity, available for Market Makers only)</p> <p>N = Book Only, No Slide</p> <p>R = Post Only, No Slide (do not remove liquidity)</p>
<i>SessionEligibility</i>	49	1	Text	<p>A = Participates in both Global and Regular Trading Hours (C1, C2, and EDGX only)</p> <p>R = Regular Trading Hours (RTH) only</p>
<i>QuoteCnt</i>	50	1	Binary	Number of repeating groups included in this quote update. Allowed values are 1-20.
<i>Repeating Groups of ...</i>				
<i>Symbol</i>		6	Alphanumeric	Cboe native identifier
<i>Side</i>		1	Text	<p>1 = Buy</p> <p>2 = Sell</p>
<i>OpenClose</i>		1	Text	<p>Corresponds to <i>OpenClose</i> (77) in Cboe FIX.</p> <p>See List of Optional Fields for additional information.</p>
<i>Price</i>		4	Short Binary Price	<p>Limit price.</p> <p>To cancel an existing quote, specify a size of 0.</p>
<i>OrderQty</i>		2	Binary	Order quantity. System limit is 999,999 contracts.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				To cancel an existing quote, specify a size of 0.
<i>Reserved</i>		2	Binary	Reserved for future expansion. To maintain forward compatibility, fill with 0.

Example Quote Update Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	91 00	145 bytes
<i>MessageType</i>	59	Quote Update (Short)
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>QuoteUpdateID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00	ABC123
<i>ClearingFirm</i>	41 42 43 44	ABCD
<i>ClearingAccount</i>	57 58 59 00	WXY
<i>CustomGroupID</i>	C8 00	200
<i>Capacity</i>	4D	M = Market Maker
<i>Reserved</i>	00 00 00	Reserved
<i>SendTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>PostingInstruction</i>	50	P (Post Only)
<i>SessionEligibility</i>	52	R (RTH Only)
<i>QuoteCnt</i>	02	Two Quotes
<i>Symbol</i>	30 30 36 69 70 41	006ipA
<i>Side</i>	31	1 = Buy
<i>OpenClose</i>	4F	O = Open
<i>Price</i>	C8 32 00 00	1.30
<i>OrderQty</i>	64 00	100 contracts
<i>Reserved</i>	00 00	Reserved
<i>Symbol</i>	30 30 34 63 53 73	004cSs
<i>Side</i>	32	2 = Sell
<i>OpenClose</i>	4F	O = Open
<i>Price</i>	AC 07 01 00	6.75
<i>OrderQty</i>	F4 01	500 contracts
<i>Reserved</i>	00 00	Reserved

4.1.9 Purge Orders

Request to cancel a group of orders across all the firm's sessions. This differs from a mass cancel request sent via a `Cancel Order` message as the purge request is applied across all of the firm's sessions, not just the session on which the `Cancel Order` was received.

A purge request requires populating the *MassCancel* required field (legacy) or specifying the *MassCancelInst* optional field. If the *MassCancelInst* optional field is specified, the *MassCancel* required field will be ignored.

Members are encouraged to use the *MassCancelInst* method as the legacy *MassCancel* method will be deprecated in the future with notice.

In addition, the `Purge Orders` message accepts a list of up to 10 *CustomGroupID* values as part of the order matching filter. If both *RiskRoot* and a list of *CustomGroupID* values are specified, the `Purge Orders` request will be rejected.

Legacy Mass Cancel method:

- Populate the *MassCancel* required field (and do not specify the *MassCancelInst* optional field)

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

- Specify the *ClearingFirm* field, optionally the *RiskRoot* field, and optionally *MassCancelId* if a single *Mass Cancel Acknowledgement* is requested.
- Specify the *MassCancelLockout* optional field to request subsequent rejection of new orders based on the level of *MassCancel* (i.e. Firm level, Risk Root level, or Custom Group Id level)

MassCancelInst method

- Specify the *MassCancelInst* optional field
- Specify the *ClearingFirm* field, optionally the *RiskRoot* field, and optionally *MassCancelId* if the Acknowledgement Style is set to S or B.
- Risk lockout is optionally specified using the *MassCancelInst* field. As a result, the *MassCancelLockout* field will be ignored when *MassCancelInst* is present.

When specifying the *RiskRoot* field, using the underlying symbol is strongly recommended. Mass cancellations are always performed at the risk root (underlying) level.

The system limits the rate at which identical Purge Orders requests can be submitted to the system. Requests are restricted to twenty (20) messages per second per port.

An identical Mass Cancel message is defined as a message having all of the same *CustomGroupID*, *Symbol*, *Clearing Firm*, *Lockout Instruction*, *Instrument Type Filter* and *GTC Order Filter* field values, as a previously received message. Permitted input optional fields are described in 'Section 5.7 – Purge Orders'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x47
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>MassCancel</i>	10	1	Alphanumeric	Corresponds to <i>MassCancel</i> (7693) in Cboe FIX. Indicates that a mass cancellation is being performed.
<i>NumberOfPurgeOrdersBitfields</i>	11	1	Binary	Bitfield identifying bitfields which are set. May be 0. Field values must be appended to the end of the message.
<i>PurgeOrderBitfield</i> ¹	12	1	Binary	Bitfield identifying fields to follow. Only present if <i>NumberOfPurgeOrdersBitfields</i> is non-zero.
<i>CustomGroupIDCnt</i>	13	1	Binary	Number of repeating <i>CustomGroupID</i> included in this message.
<i>CustomGroupID</i> ¹		2	Binary	First <i>CustomGroupID</i> . Only present if <i>CustomGroupIDCnt</i> is non-zero.
...				
<i>CustomGroupID</i> ⁿ		2	Binary	Last <i>CustomGroupID</i> .
<i>Optional fields. . .</i>				

Example Purge Orders Message (legacy) with CustomGroupID and Lockout:

Field Name	Hexadecimal	Notes
StartOfMessage	BA BA	Start of message bytes
MessageLength	29 00	41 bytes
MessageType	47	Purge Orders
MatchingUnit	0	Always 0 for inbound messages
SequenceNumber	64 00 00 00	Sequence number 100
MassCancel	34	4 = clearing firm match, single ack
NumberOfPurge	01	One bitfield to follow
OrderBitfields		
PurgeOrdersBitfield1	13	ClearingFirm, MassCancelLockout, MassCancelID
CustomGroupIDCnt	02	Two CustomGroupIDs to follow
CustomGroupID1	BF BE	First CustomGroupID of 48831
CustomGroupID2	CO BE	Second CustomGroupID of 48832
ClearingFirm	54 45 53 54	TEST
MassCancelLockout	31	1 = lockout
MassCancelID	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123

Example Purge Orders Message (legacy) with Product Level Filter and no Lockout:

Field Name	Hexadecimal	Notes
StartOfMessage	BA BA	Start of message bytes
MessageLength	2B 00	43 bytes
MessageType	47	Purge Orders
MatchingUnit	00	Always 0 for inbound messages
SequenceNumber	64 00 00 00	Sequence number 100
MassCancel	34	4 = clearing firm match, single ack
NumberOfPurge	01	1 bitfield to follow
OrderBitfields		
PurgeOrdersBitfield1	1B	ClearingFirm, MassCancelLockout, RiskRoot, MassCancelID
CustomGroupIDCnt	00	No CustomGroupID to follow
ClearingFirm	54 45 53 54	TEST
MassCancelLockout	30	0 = no lockout
RiskRoot	41 42 43 00 00 00	ABC
MassCancelID	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123

Example Purge Orders Message with CustomGroupID and Lockout:

Field Name	Hexadecimal	Notes
StartOfMessage	BA BA	Start of message bytes
MessageLength	29 00	58 bytes
MessageType	47	Purge Orders
MatchingUnit	0	Always 0 for inbound messages
SequenceNumber	64 00 00 00	Sequence number 100
MassCancel	00	Not specified
NumberOfPurge	01	One bitfield to follow
OrderBitfields		

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>PurgeOrdersBitfield1</i>	15	<i>ClearingFirm, MassCancelInst, MassCancelID</i>
<i>CustomGroupIDCnt</i>	02	Two CustomGroupIDs to follow
<i>CustomGroupID1</i>	BF BE	First <i>CustomGroupID</i> of 48831
<i>CustomGroupID2</i>	CO BE	Second <i>CustomGroupID</i> of 48832
<i>ClearingFirm</i>	54 45 53 54	TEST
<i>MassCancelInst</i>	46 53 4C 42 00 00 00 00 00 00 00 00 00 00 00 00	F = Cancel orders matching clearing firm TEST S = Single ack L = Lockout both <i>CustomGroupIDs</i> B = Cancel simple and complex
<i>MassCancelID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123

Example Purge Orders Message with Product Level Filter and no Lockout:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	3C 00	60 bytes
<i>MessageType</i>	47	Purge Orders
<i>MatchingUnit</i>	0	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>MassCancel</i>	00	Not specified
<i>NumberOfPurge</i>	01	One bitfield to follow
<i>OrderBitfields</i>		
<i>PurgeOrdersBitfield1</i>	1D	<i>ClearingFirm, MassCancelInst, RiskRoot, MassCancelID</i>
<i>CustomGroupIDCnt</i>	00	No CustomGroupIDs to follow
<i>ClearingFirm</i>	54 45 53 54	TEST
<i>MassCancelInst</i>	46 53 4E 42 00 00 00 00 00 00 00 00 00 00 00 00	F = Cancel orders matching clearing firm TEST S = Single ack N = No lockout B = Cancel simple and complex
<i>RiskRoot</i>	41 42 43 00 00 00	ABC
<i>MassCancelID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123

4.1.10 Reset Risk

Reset or release Firm, Risk Root, or Custom Group ID level lockout conditions resulting from risk profile trips or self-imposed lockouts issued via *Cancel Order* or *Purge Orders* messages. Risk resets can be performed using this message or by using the *RiskReset* field on a *New Order* message.

When specifying the *RiskRoot* field, using the underlying symbol is strongly recommended. Risk Resets are always performed at the risk root (underlying) level.

Only one unique risk reset of a given type (EFID Group, EFID, Risk Root, CustomGroupID) is allowed per second. Additional resets will be ignored (*RiskResetResult* = <space>). For example, a customer may reset risk for *CustomGroupID* = 1 and may not reset risk again for *CustomGroupID* = 1 until one second has elapsed. This restriction is designed to safeguard the trading platform from excessive risk messaging.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x56
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>RiskStatusID</i>	10	16	Text	Unique identifier for this Reset Risk request. Response message will have this corresponding identifier. Note: Cboe only enforces uniqueness of <i>RiskStatusID</i> values among currently unacknowledged requests. However, we strongly recommend that you keep your <i>RiskStatusID</i> values day-unique.
<i>RiskReset</i>	26	8	Text	Corresponds to <i>RiskReset</i> (7692) in Cboe FIX. Indicates Risk Root, Firm, or CustomGroupID lockout reset. See List of Optional Fields for allowed values.
<i>Reserved</i>	34	4	Binary	Reserved for future expansion. To maintain forward compatibility, fill with 0.
<i>ClearingFirm</i>	38	4	Alpha	Risk will be reset for this EFID.
<i>RiskRoot</i>	42	6	Alphanumeric	Populate with Risk Root for resets at the Risk Root level. Leave empty for resets at the firm level.
<i>CustomGroupID</i>	48	2	Binary	Populate with an identifier for resets including a CustomGroupID. Set to 0 to ignore.

Example Reset Risk Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	30 00	48 bytes
<i>MessageType</i>	56	Reset Risk
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>RiskStatusID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00	ABC123
<i>RiskReset</i>	53 46 00 00 00 00 00 00	SF = Symbol and Firm level reset
<i>Reserved</i>	00 00 00 00	
<i>ClearingFirm</i>	54 45 53 54	TEST
<i>RiskRoot</i>	41 42 43 00 00 00	ABC
<i>CustomGroupID</i>	00 00	No <i>CustomGroupID</i>

4.1.11 New Complex Instrument (C1, C2, and EDGX Only)

A *New Complex Instrument* message is used to request that the system create a complex strategy. The resulting symbol (if accepted by the system) will be returned in a *Complex Instrument Accepted* message; a *Complex Instrument Rejected* message will be sent if it is not accepted. All legs must have the same underlying product which can be different OSI Roots (i.e. XYZ and XYZ1).

A *ClearingFirm* must be sent on each *New Complex Instrument* message unless a Default Executing Firm ID is set at the port-level.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Permitted input optional fields are described in 'Section 5.8 – New Complex Instrument'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x4C
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>ClOrdID</i>	10	20	Text	Corresponds to <i>ClOrdID</i> (11) in Cboe FIX. Day-unique ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe. If the <i>ClOrdID</i> matches a live order, the order will be rejected as duplicate. Note: Cboe only enforces uniqueness of <i>ClOrdID</i> values among currently live orders. However, we strongly recommend that you keep your <i>ClOrdID</i> values day-unique.
<i>NumberOfNewComplexInstrumentBitfields</i>	30	1	Binary	Bitfield identifying which bitfields are set. Field values must be appended to the end of the message.
<i>NewComplexInstrumentBitfield¹</i>	31	1	Binary	Bitfield identifying fields to follow.
....				
<i>NewComplexInstrumentBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>NoLegs</i>		1	Binary	Corresponds to <i>NoLegs</i> (555) in Cboe FIX. Indicates the number of repeating groups to follow. Must be a minimum of 2 and a maximum of 12.
Repeating Group <i>ComplexLeg</i> must occur the number of times specified in <i>NoLegs</i> . Each field occurs in each group, in order as shown below. Optional fields occur only if corresponding bits in bitfields are set.				
<i>LegSymbol</i>	8	Alphanumeric	Corresponds to <i>LegSymbol</i> (600) in Cboe FIX. Entire Cboe format symbol or OSI Root. Must send <i>LegCFIcode</i>, <i>LegMaturityDate</i>, and <i>LegStrikePrice</i> if using OSI format.	
<i>LegCFIcode (Optional)</i>	6	Alphanumeric	Corresponds to <i>LegCFIcode</i> (608) in Cboe FIX. CFI Code for leg. Required if <i>LegSymbol</i> is in OSI format. OP = Options Put OC = Options Call E = Equity	
<i>LegMaturityDate (Optional)</i>	4	Date	Corresponds to <i>LegMaturityDate</i> (611) in Cboe FIX. Required if <i>LegSymbol</i> is in OSI format.	
<i>LegStrikePrice (Optional)</i>	8	Binary Price	Corresponds to <i>LegStrikePrice</i> (612) in Cboe FIX. Option strike price. System maximum is 99,999,999. Must be non-negative.	

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

			Required if <i>LegSymbol</i> is in OSI format.
<i>LegRatioQty</i>	4	Binary	Corresponds to <i>LegRatioQty</i> (623) in Cboe FIX. Ratio of number of contracts in this leg per order quantity. Must be between 1 and 99,999.
<i>LegSide</i>	1	Alphanumeric	Corresponds to <i>LegSide</i> (624) in Cboe FIX. 1 = Buy 2 = Sell
<i>Optional fields...</i>			Optional fields as set in the bitmap. Note, optional fields that occur in the repeating groups appear above, repeating per group, not within this block.

Example New Complex Instrument Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	61 00	97 bytes
<i>MessageType</i>	4C	New Complex Instrument
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>NumberOfNewComplexInstrumentBitfields</i>	01	One bitfield to follow
<i>NewComplexInstrumentBitfield1</i>	0F	<i>LegCFICode</i> , <i>LegMaturityDate</i> , <i>LegStrikePrice</i> , <i>ClearingFirm</i>
<i>NoLegs</i>	02	Two legs
<i>LegSymbol</i>	4D 53 46 54 00 00 00 00	MSFT
<i>LegCFICode</i>	4F 43 00 00 00 00	OC = Option Call
<i>LegMaturityDate</i>	EF DB 32 01	2011-03-19
<i>LegStrikePrice</i>	98 AB 02 00 00 00 00 00	17.50
<i>LegRatioQty</i>	02 00 00 00	Ratio of 2
<i>LegSide</i>	31	Buy
<i>LegSymbol</i>	4D 53 46 54 00 00 00 00	MSFT
<i>LegCFICode</i>	4F 50 00 00 00 00	OP = Option Put
<i>LegMaturityDate</i>	F6 DB 32 01	2011-03-26
<i>LegStrikePrice</i>	30 E6 02 00 00 00 00 00	19.00
<i>LegRatioQty</i>	01 00 00 00	Ratio of 1
<i>LegSide</i>	32	Sell
<i>ClearingFirm</i>	54 45 53 54	TEST

4.1.12 Add Floor Trade (C1 Only)

TPHs having in-person Market Makers on the Cboe trading floor can enter their version of a floor trade via the Add Floor Trade message type.

This message may be used to report any floor trades, but is primarily meant to be used to report floor trades between Market Makers. TPHs are encouraged to use Floor Trade Confirmation messages to respond to floor broker allocations (Floor Trade Notification messages) if they agree with the terms of the trade.

The Exchange will respond to an Add Floor Trade message with an Add Floor Trade Rejected message or an Order Acknowledgement message followed by one or more Order Executed messages.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x5C
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>ClOrdID</i>	10	20	Text	<p>Corresponds to <i>ClOrdID</i> (11) in Cboe FIX.</p> <p>Day-unique ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe.</p> <p>If the <i>ClOrdID</i> matches a live order, the order will be rejected as duplicate.</p> <p>Note: Cboe only enforces uniqueness of <i>ClOrdID</i> values among currently live orders. However, we strongly recommend that you keep your <i>ClOrdID</i> values day-unique.</p>
<i>Symbol</i>	30	8	Alphanumeric	<p>Corresponds to <i>Symbol</i> (55) in Cboe FIX.</p> <p>Entire Cboe format symbol or OSI symbol if using long format.</p>
<i>PutOrCall</i>	38	1	Alphanumeric	<p>Corresponds to <i>PutOrCall</i> (201) in Cboe FIX.</p> <p>0 = Put 1 = Call</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>
<i>StrikePrice</i>	39	8	Binary Price	<p>Corresponds to <i>StrikePrice</i> (202) in Cboe FIX.</p> <p>Strike Price for option, 0 – 999,999.99</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>
<i>MaturityDate</i>	47	4	Date	<p>Corresponds to <i>MaturityMonth</i> (200) and <i>MaturityDay</i> (205) in Cboe FIX.</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>
<i>MultilegReportingType</i>	51	1	Alphanumeric	<p>Corresponds to <i>MultilegReportingType</i> (442) in Cboe FIX.</p> <p>Indicates the type of Order Execution message.</p> <p>1 = Single-leg instrument 2 = Individual leg of multi-leg instrument</p>
<i>ComboOrder</i>	52	1	Alpha	<p>Corresponds to <i>ComboOrder</i> (22005) in Cboe FIX.</p> <p>Declare the order as a Combo (for regulatory relief if trading SPX on the floor).</p> <p>N = (Default) No Y = Yes</p>
<i>Account</i>	53	16	Text	<p>Corresponds to <i>Account</i> (1) in Cboe FIX.</p> <p>Reflected back on execution reports associated with this order and also passed through to the OCC in</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				<p>the Optional Data field (16 characters) and Customer ID field (max 10 characters). May be made available in the Member's clearing file. A maximum of 10 characters will be passed through to the OCC Customer ID Field but up to 16 characters will be maintain internally. Allowed characters are alphanumeric and colon.</p> <p><i>Account</i> (1) will only be mapped to the OCC via the Customer ID field (max 10 characters) and the new <i>ClearingOptionalData</i> (9324) field will be mapped to the OCC via the Optional Data field (16 characters).</p>
<i>ClearingOptionalData</i>	69	16	Text	<p>Corresponds to <i>ClearingOptionalData</i> (9324) in Cboe FIX.</p> <p>This field will be reflected back on execution reports , FIX DROP ports and it will be passed through to the OCC in the Optional Data field.</p>
<i>ClearingAccount</i>	85	4	Text	<p>Corresponds to <i>ClearingAccount</i> (440) in Cboe FIX.</p> <p>When <i>Capacity</i> is set to a value of M or N for Market Maker, this field should be filled with the desired market maker ID. When using CMTA, this value is the Market Maker ID for the CMTA member instead of the Cboe member executing the trade. This field will be sent to the OCC.</p> <p>If <i>Capacity</i> is set to something besides Market Maker, this field can be blank or filled out with an optional string that is passed through to the OCC.</p>
<i>CMTANumber</i>	89	4	Binary	<p>Corresponds to <i>CMTANumber</i> (439) in Cboe FIX.</p> <p>CMTA Number of the firm that will clear the trade. Must be specified for CMTA orders and left unspecified for non-CMTA orders.</p>
<i>FloorTraderAcronym</i>	93	3	Alpha	Floor acronym of participant submitting trade.
<i>Side</i>	96	1	Alphanumeric	<p>Corresponds to <i>Side</i> (54) in Cboe FIX.</p> <p>1 = Buy 2 = Sell</p>
<i>OrderQty</i>	97	4	Binary	<p>Corresponds to <i>OrderQty</i> (38) in Cboe FIX.</p> <p>Order quantity. System limit is 999,999 contracts.</p>
<i>Price</i>	101	8	Binary Price	<p>Corresponds to <i>Price</i> (44) in Cboe FIX.</p> <p>Limit price. Order rejected if priced finer than the minimum trading increment for the option.</p>
<i>TransactionTime</i>	109	8	DateTime	Report send time (for audit).
<i>OpenClose</i>	117	1	Alphanumeric	<p>Corresponds to <i>OpenClose</i> (77) in Cboe FIX.</p> <p>Indicates status of client position in the option.</p> <p>O = Open C = Close N = None*</p> <p>*Orders with a <i>Capacity</i> of "M" or "N" will not be required to specify OpenClose on their orders or may optionally specify a value of "N", unless the series is limited to closing only.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				If the series is limited to closing only transactions an order with <i>Capacity</i> of M or N will only be permitted to submit <i>OpenClose</i> = O if the order has a <i>TimeInForce</i> of IOC or <i>RoutingInst</i> of Post Only (P).
<i>TradeTime</i>	118	8	Date Time	Trade time
<i>ContraTrader</i>	126	4	Alphanumeric	Displays the EFID (<i>ClearingFirm</i>) of the contra side firm on all internally matched executions.
<i>Reserved</i>	130	16	Reserved	Reserved

Example Add Floor Trade Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	90 00	144 bytes
<i>MessageType</i>	5C	Add Floor Trade
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>Symbol</i>	30 30 36 69 70 41 00 00	006ipA
<i>PutorCall</i>	00	
<i>StrikePrice</i>	00 00 00 00 00 00 00 00	
<i>MaturityDate</i>	00 00 00 00	
<i>MultilegReportingType</i>	31	1 = Single leg instrument
<i>ComboOrder</i>	4E	N = No
<i>Account</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	
<i>ClearingOptionalData</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	
<i>ClearingAccount</i>	41 42 43 00	ABC
<i>CMTANumber</i>	00 00 00 00	
<i>FloorTraderAcronym</i>	44 45 46	DEF
<i>Side</i>	31	1 = Buy
<i>OrderQty</i>	64 00 00 00	100 contracts
<i>Price</i>	C8 32 00 00 00 00 00 00	1.30
<i>TransactionTime</i>	00 5C DB E2 27 12 B4 15	1,563,894,933,123,456,000
<i>OpenClose</i>	4F	O = Open
<i>TradeTime</i>	68 23 4A 8B 27 12 B4 15	1,563,894,931,654,321,000
<i>ContraTrader</i>	57 58 59	WXY
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	Reserved

4.1.13 Floor Trade Confirmation (C1 Only)

TPHs are encouraged to use Floor Trade Confirmation messages to respond to Floor Trade Notification messages if they agree with the terms of the trade. Alternatively, an Add Floor Trade message may be used to enter their version of the floor trade. If the floor trade notification is not known to the user (for example, if the TPH is misidentified as a contra party to a floor trade), the message can be disregarded; a response is not required.

The exchange will respond to a Floor Trade Confirmation message with an Order Executed message or Floor Trade Confirmation Rejected message.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Field	Offset	Length	Data Type	Description								
StartOfMessage	0	2	Binary	Must be 0xBA 0xBA.								
MessageLength	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the StartOfMessage field.								
MessageType	4	1	Binary	0x5B								
MatchingUnit	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.								
SequenceNumber	6	4	Binary	The sequence number for this message.								
ClOrdID	10	20	Text	<p>Corresponds to ClOrdID (11) in Cboe FIX.</p> <p>Day-unique ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe.</p> <p>If the ClOrdID matches a live order, the order will be rejected as duplicate.</p> <p>Note: Cboe only enforces uniqueness of ClOrdID values among currently live orders. However, we strongly recommend that you keep your ClOrdID values day-unique.</p>								
ExecID	30	8	Binary	<p>Corresponds to ExecID (17) in Cboe FIX.</p> <p>Execution ID. Unique across all matching units on a given day. Note: ExecIDs will be represented on ODROP and FIXDROP ports as nine character, base 36 ASCII. Leading zeros should be added if the converted base 36 value is shorter than nine characters.</p> <p>Example conversion:</p> <table><tr><th>Decimal</th><th>Base 36</th></tr><tr><td>28294005440239</td><td>A1234B567</td></tr><tr><td>76335905726621</td><td>R248BC23H</td></tr><tr><td>728557228187</td><td>09AP05V2Z</td></tr></table>	Decimal	Base 36	28294005440239	A1234B567	76335905726621	R248BC23H	728557228187	09AP05V2Z
Decimal	Base 36											
28294005440239	A1234B567											
76335905726621	R248BC23H											
728557228187	09AP05V2Z											
Symbol	38	8	Alphanumeric	<p>Corresponds to Symbol (55) in Cboe FIX.</p> <p>Entire Cboe format symbol or OSI symbol if using long format.</p>								
PutOrCall	46	1	Alphanumeric	<p>Corresponds to PutOrCall (201) in Cboe FIX.</p> <p>0 = Put 1 = Call</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>								
StrikePrice	47	8	Binary Price	<p>Corresponds to StrikePrice (202) in Cboe FIX.</p> <p>Strike Price for option, 0 – 999,999.99</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>								
MaturityDate	55	4	Date	<p>Corresponds to MaturityMonth (200) and MaturityDay (205) in Cboe FIX.</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>								
TransactionTime	59	8	DateTime	Report send time (for audit).								
PriceType	67	1	Alphanumeric	Corresponds to PriceType (423) in Cboe FIX.								

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				1 = Percentage, when trading FLEX percentage instruments* 2 = (Default) Price per unit (contract) * Percentage pricing for FLEX orders is only available for index products.
<i>Reserved</i>	68	15	Reserved	Reserved

Example Floor Trade Confirmation Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	51 00	81 bytes
<i>MessageType</i>	5B	Floor Trade Confirmation
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>ExecID</i>	01 F0 B7 D9 71 21 00 00	D19800001 (base 36)
<i>Symbol</i>	30 30 36 69 70 41 00 00	006ipA
<i>PutorCall</i>	00	
<i>StrikePrice</i>	00 00 00 00 00 00 00 00	
<i>MaturityDate</i>	00 00 00 00	
<i>TransctionTime</i>	00 5C DB E2 27 12 B4 15	1,563,894,933,123,456,000
<i>PriceType</i>	02	2 = Price per unit
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	Reserved

4.1.14 Delete Floor Trade (C1 Only)

TPHs having in-person Market Makers on the Cboe trading floor can request the deletion of their version of a floor trade via the Delete Floor Trade message type. The trade report to delete will be identified by the *ExecID*. The TPH entering the floor trade deletion message must be on the specified side of the identified trade. The Exchange will respond to a Delete Floor Trade message with a Delete Floor Trade Reject or with a Delete Floor Trade Acknowledgement if the floor trade report is successfully deleted.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x5D
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>ClOrdID</i>	10	20	Text	Corresponds to <i>ClOrdID</i> (11) in Cboe FIX. Day-unique ID chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon, and pipe. If the <i>ClOrdID</i> matches a live order, the order will be rejected as duplicate.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				Note: Cboe only enforces uniqueness of <i>CIOrdID</i> values among currently live orders. However, we strongly recommend that you keep your <i>CIOrdID</i> values day-unique.								
<i>ExecID</i>	30	8	Binary	<p>Corresponds to <i>ExecID</i> (17) in Cboe FIX.</p> <p>Execution ID. Unique across all matching units on a given day. Note: <i>ExecIDs</i> will be represented on ODROP and FIXDROP ports as nine character, base 36 ASCII. Leading zeros should be added if the converted base 36 value is shorter than nine characters.</p> <p>Example conversion:</p> <table><tr><th>Decimal</th><th>Base 36</th></tr><tr><td>28294005440239</td><td>A1234B567</td></tr><tr><td>76335905726621</td><td>R248BC23H</td></tr><tr><td>728557228187</td><td>09AP05V2Z</td></tr></table>	Decimal	Base 36	28294005440239	A1234B567	76335905726621	R248BC23H	728557228187	09AP05V2Z
Decimal	Base 36											
28294005440239	A1234B567											
76335905726621	R248BC23H											
728557228187	09AP05V2Z											
<i>Symbol</i>	38	8	Alphanumeric	<p>Corresponds to <i>Symbol</i> (55) in Cboe FIX.</p> <p>Entire Cboe format symbol or OSI symbol if using long format.</p>								
<i>PutOrCall</i>	46	1	Alphanumeric	<p>Corresponds to <i>PutOrCall</i> (201) in Cboe FIX.</p> <p>0 = Put 1 = Call</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>								
<i>StrikePrice</i>	47	8	Binary Price	<p>Corresponds to <i>StrikePrice</i> (202) in Cboe FIX.</p> <p>Strike Price for option, 0 – 999,999.99</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>								
<i>MaturityDate</i>	55	4	Date	<p>Corresponds to <i>MaturityMonth</i> (200) and <i>MaturityDay</i> (205) in Cboe FIX.</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>								
<i>Side</i>	59	1	Alphanumeric	<p>Corresponds to <i>Side</i> (54) in Cboe FIX.</p> <p>1 = Buy 2 = Sell</p>								
<i>Reserved</i>	60	16	Reserved	Reserved								

Example Delete Floor Trade Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	4A 00	74 bytes
<i>MessageType</i>	5D	Delete Floor Trade
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>CIOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>ExecID</i>	01 F0 B7 D9 71 21 00 00	D19800001 (base 36)
<i>Symbol</i>	30 30 36 69 70 41 00 00	006ipA
<i>PutorCall</i>	00	

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>StrikePrice</i>	00 00 00 00 00 00 00 00	
<i>MaturityDate</i>	00 00 00 00	
<i>Side</i>	31	Buy
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00	Reserved
	00 00 00 00 00 00	

4.2 Cboe to Member

4.2.1 Order Acknowledgment

Order Acknowledgment messages are sent in response to New Order and New Complex Order messages. The message corresponds to a FIX Execution Report with *ExecType* (150) = 0 (New).

Per the instructions given in a Return Bitfields Parameter Group on the Login Request (Section 3.1.1 – Login Request), optional fields may be appended to echo back information provided in the original New Order message. Fields which have been requested to be echoed back but which were not filled in will still be sent, but filled with binary zero (0x00).

Permitted return optional fields are described in ‘Section 6.1 – Order Acknowledgement’.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x25
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>ClOrdID</i>	18	20	Text	Echoed back from the original order.
<i>OrderID</i>	38	8	Binary	Corresponds to <i>OrderID</i> (37) in Cboe FIX. Order identifier supplied by Cboe. This identifier corresponds to the identifiers used in Cboe market data products.
<i>ReservedInternal</i>	46	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	47	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	48	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Order Acknowledgment Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	4E 00	78 bytes
<i>MessageType</i>	25	Order Acknowledgment
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>ReservedInternal</i>	00	Ignore

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>NumberOfReturn Bitfields</i>	03	Three bitfields to follow
<i>ReturnBitfield1</i>	00	No bitfields from byte 1
<i>ReturnBitfield2</i>	41	<i>Symbol, Capacity</i>
<i>ReturnBitfield3</i>	05	<i>Account, ClearingAccount</i>
<i>Symbol</i>	31 32 33 61 42 63 00 00	123aBc
<i>Capacity</i>	50	P = Principal
<i>Account</i>	41 42 43 00 00 00 00 00 00 00	ABC
	00 00 00 00 00 00	
<i>ClearingAccount</i>	00 00 00 00	

Example Minimal Order Acknowledgment Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	2E 00	46 bytes
<i>MessageType</i>	25	Order Acknowledgment
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn Bitfields</i>	00	No bitfields to follow

4.2.2 Cross Order Acknowledgment (C1 and EDGX Only)

Cross Order Acknowledgment messages are sent in response to New Order Cross and New Order Cross Multileg messages. The message corresponds to a FIX Execution Report with *ExecType* (150) = 0 (New). In FIX, multiple execution reports could be generated from one new cross order message.

Per the instructions given in a Return Bitfields Parameter Group on the Login Request (Section 3.1.1 – Login Request), optional fields may be appended to echo back information provided in the original New Order Cross message. Fields which have been requested to be echoed back but which were not filled in will still be sent, but filled with binary zero (0x00).

In each repeating group, the *ClOrdID* and *OrderID* are always returned. Beyond that, the bits specified in the optional return bitfields parameter group control which fields are returned. Any fields that appear in the repeating groups will not appear in the optional fields that come after the repeating groups.

Permitted return optional fields are described in ‘Section 6.2 – Cross Order Acknowledgement’.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x43
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>CrossID</i>	18	20	Text	Corresponds to <i>CrossID</i> (548) in Cboe FIX. Echoed back from the original order.
<i>AuctionId</i>	38	8	Binary	Corresponds to <i>AuctionId</i> (9370) in Cboe FIX. Auction order identifier supplied by Cboe. This identifier corresponds to the identifiers used in Cboe market data products.
<i>ReservedInternal</i>	46	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	47	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	48	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>GroupCnt</i>		2	Binary	Number of order allocations represented by repeating groups included in this message.
<i>Repeating Groups Of...</i>				
<i>ClOrdId</i>		20	Text	Echoed back from the original order.
<i>OrderId</i>		8	Binary	OrderId assigned by the matching engine.
<i>Side (Optional)</i>		1	Alphanumeric	See List of Optional Fields .
<i>AllocQty (Optional)</i>		4	Binary	See List of Optional Fields .
<i>Capacity (Optional)</i>		1	Alpha	See List of Optional Fields .
<i>OpenClose (Optional)</i>		1	Alphanumeric	See List of Optional Fields .
<i>GiveUpFirmID (Optional)</i>		4	Alpha	See List of Optional Fields .
<i>Account (Optional)</i>		16	Text	See List of Optional Fields .
<i>CMTANumber (Optional)</i>		4	Binary	See List of Optional Fields .
<i>ClearingAccount (Optional)</i>		4	Text	See List of Optional Fields .
<i>Optional fields. . .</i>				Optional fields as set in the bitmap. Note, optional fields that occur in the repeating groups appear above, repeating per group, not within this block.

Example Cross Order Acknowledgment Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	91 00	145 bytes
<i>MessageType</i>	43	Cross Order Acknowledgment
<i>MatchingUnit</i>	02	Matching Unit 2
<i>SequenceNumber</i>	01 00 00 00	Sequence number 1
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>CrossID</i>	4E 5A 31 56 37 42 4A 5F 41 63 63 65 70 74 42 75 79 00 00 00	NZ1V7BJ_AcceptBuy

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>AuctionId</i>	01 C0 91 A2 94 AB 78 04	2G4GYK000001 (base 36)
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn</i>	02	Two bitfields to follow
<i>Bitfields</i>		
<i>ReturnBitfield1</i>	00	No bitfields from byte 1
<i>ReturnBitfield2</i>	41	<i>Symbol, Capacity</i>
<i>GroupCnt</i>	03 00	Three repeating groups to follow
<i>ClOrdID</i>	4E 5A 31 56 37 47 4E 5F 61 67 65 6E 63 79 00 00 00 00 00 00	NZ1V7GN_agency
<i>OrderID</i>	02 C0 91 A2 94 AB 78 04	2G4GYK000002 (base 36)
<i>Capacity</i>	43	C = Customer
<i>ClOrdID</i>	4E 5A 31 56 37 4B 46 5F 63 6F 6E 74 72 61 31 00 00 00 00 00	NZ1V7KF_contra1
<i>OrderID</i>	03 C0 91 A2 94 AB 78 04	2G4GYK000003 (base 36)
<i>Capacity</i>	46	F = Firm
<i>ClOrdID</i>	4E 5A 31 56 37 4E 48 5F 63 6F 6E 74 72 61 32 00 00 00 00 00	NZ1V7NH_contra2
<i>OrderID</i>	04 C0 91 A2 94 AB 78 04	2G4GYK000004 (base 36)
<i>Capacity</i>	46	F = Firm
<i>Symbol</i>	30 30 51 30 6B 41 00 00	00Q0kA

4.2.3 Quote Update Acknowledgment

Quote Update Acknowledgment messages are sent in response to a Quote Update message. The effect of each requested update will be found in this response. The ordering between request and response is preserved.

For quotes not marked post only which are priced at an executable price and which may remove liquidity against non-Market Maker liquidity, *QuoteResult* reason of “D” or “d” will be provided. In these cases, executions or cancellations (as needed) will immediately follow as additional messages. In some cases, an execution may not be permitted (e.g., risk management causes cancellation of the targeted order before execution), no additional messages will follow and the quote will post.

In some cases, a new *OrderID* will be assigned for an existing quote. There are currently two situations where this occurs, but others may be added in the future:

1. An order which has received a large number of quote updates over its life will be assigned a new *OrderID* if receiving an update which would cause a loss in priority.
2. A quote update sent to modify the *PostingInstruction* will be assigned a new *OrderID* if there is an existing quote in that symbol on that port and for that EFID.

If using the *OrderID* in your system or to correlate with an *OrderID* on PITCH, always be prepared to receive an update on an Quote Update Acknowledgment.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x51
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH. Unsequenced application message. <i>MatchingUnit</i> will be set to 0.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit. This will be an unsequenced application message. The sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>QuoteUpdateID</i>	18	16	Text	Echoed back from the Quote Update request.
<i>QuoteRejectReason</i>	34	1	Text	Reason for rejection of an entire Quote Update message by the matching engine. If an error is indicated, then no quotes were entered or updated. <i>QuoteCnt</i> will be 0. <space> = Success See Quote Reason Codes for a list of possible quote reject codes. Additional reasons may be added in the future without warning.
<i>Reserved</i>	35	17	Binary	Reserved for future expansion. Filled with 0.
<i>QuoteCnt</i>	52	1	Binary	Number of repeating groups included in this acknowledgment. Allowed values are 1-20.
<i>Repeating Groups of ...</i>				
<i>OrderID</i>		8	Binary	Order ID assigned by the matching engine. Corresponds to order ID on PITCH.
<i>QuoteResult</i>		1	Text	Result of the quote request. <i>Acceptance:</i> A = New Quote L = Modified; loss of priority R = Modified; retains priority (size reduction) N = No change, matches existing quote D = New Quote, but may remove liquidity d = Modified, but may remove liquidity V = No change, existing constituent series quote modify attempt after cutoff time (C1 only) <i>Cancellation:</i> U = User cancelled (zero size/price requested) <i>Rejection:</i> a = Admin P = Rejected, can't post f = Risk management firm or Custom Group ID level S = Rejected, symbol not found p = Rejected, invalid price r = Invalid Remove s = Risk management risk root level u = Rejected, other reason + = Risk management EFID Group level c = Rejected, closing only series v = Rejected, attempt to add constituent series quote after cutoff time (C1 only)

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				Additional reasons indicating a reject may be added in the future with no notice.
<i>SubLiquidity Indicator</i>		1	Text	N = Normal S = NBBO Setter J = NBBO Joiner U = Market Turner (C1 only) <space> = No quote on book New values may be added in the future without warning.
<i>Reserved</i>		6	Binary	Reserved for future expansion. Filled with 0.

Example Quote Update Acknowledgment Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	53 00	83 bytes
<i>MessageType</i>	51	Quote Update Acknowledgment
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>QuoteUpdateID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00	ABC123
<i>QuoteRejectReason</i>	20	<space> = Success
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	
<i>QuoteCnt</i>	02	Two Quotes
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>QuoteResult</i>	64	d = Modified, but may remove liquidity
<i>SubLiquidityIndicator</i>	4E	N = Normal
<i>Reserved</i>	00 00 00 00 00 00 00 00	
<i>OrderID</i>	06 10 1E B7 5E 39 2F 02	171WC1000006 (base 36)
<i>QuoteResult</i>	4C	L = Modified, loss of priority
<i>SubLiquidityIndicator</i>	53	S = NBBO Setter
<i>Reserved</i>	00 00 00 00 00 00 00 00	

4.2.4 Order Rejected

Order Rejected messages are sent in response to a New Order which must be rejected. This message corresponds to a FIX Execution Report with *ExecType* (150) = 8 (Rejected). Order Rejected messages are unsequenced.

Permitted return optional fields are described in 'Section 6.4 – Order Rejected'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x26
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>SequenceNumber</i>	6	4	Binary	Unsequenced application message. Sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>CIOrdID</i>	18	20	Text	Echoed back from the original order.
<i>OrderRejectReason</i>	38	1	Text	Reason for an order rejection. See Order Reason Codes for a list of possible reasons.
<i>Text</i>	39	60	Text	Human readable text with more information about the reject reason.
<i>ReservedInternal</i>	99	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturnBitfields</i>	100	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	101	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Order Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	85 00	133 bytes
<i>MessageType</i>	26	Order Rejected
<i>MatchingUnit</i>	0	Unsequenced message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced message, sequence = 0
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>CIOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderRejectReason</i>	44	D
<i>Text</i>	44 75 70 6C 69 63 61 74 65 20 43 6C 4F 72 64 49 44 00	Duplicate CIOrdID
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturnBitfields</i>	04	Four bitfields to follow
<i>ReturnBitfield1</i>	00	No bitfields from byte 1
<i>ReturnBitfield2</i>	01	<i>Symbol</i>
<i>ReturnBitfield3</i>	06	<i>ClearingFirm, ClearingAccount</i>
<i>ReturnBitfield4</i>	0F	<i>MaturityDate, StrikePrice, PutOrCall, OpenClose</i>
<i>Symbol</i>	54 4E 44 4D 00 00 00 00	TNDM
<i>ClearingFirm</i>	54 45 53 54	TEST
<i>ClearingAccount</i>	00 00 00 00	(empty)
<i>MaturityDate</i>	EF DB 32 01	2011-03-19
<i>StrikePrice</i>	98 AB 02 00 00 00 00 00	17.50

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>PutOrCall</i>	31	1 = Call
<i>OpenClose</i>	4F	0 = Open

4.2.5 Cross Order Rejected (C1 and EDGX Only)

Cross Order Rejected messages are sent in response to a New Order Cross and New Order Cross Multileg which must be rejected. This message corresponds to a FIX Execution Report with *ExecType* (150) = 8 (Rejected). Order Rejected messages are unsequenced.

Permitted return optional fields are described in 'Section 6.5 – Cross Order Rejected'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x44
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	Unsequenced application message. Sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>CrossID</i>	18	20	Text	Echoed back from the original order.
<i>OrderRejectReason</i>	38	1	Text	Reason for an order rejection. See Order Reason Codes for a list of possible reasons.
<i>Text</i>	39	60	Text	Human readable text with more information about the reject reason.
<i>ReservedInternal</i>	99	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	100	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	101	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Cross Order Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	59 00	89 bytes
<i>MessageType</i>	44	Cross Order Rejected
<i>MatchingUnit</i>	0	Unsequenced message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced message, sequence = 0
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderRejectReason</i>	41	A

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>Text</i>	53 65 72 69 65 73 20 6E 6F 74 20 63 75 72 72 65 6E 74 6C 79 20 74 72 61 64 69 6E 67 00	Series not currently trading
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn</i>	02	Two bitfields to follow
<i>Bitfields</i>		
<i>ReturnBitfield1</i>	00	No bitfields from byte 1
<i>ReturnBitfield2</i>	01	<i>Symbol</i>
<i>Symbol</i>	30 30 51 30 6B 41 00 00	00Q0kA

4.2.6 Quote Update Rejected

Quote Update Rejected messages are sent in response to a Quote Update message when the entire quote block is rejected by the order handler. No existing quotes are updated or cancelled as a result.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x58
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	Unsequenced application message. Sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>QuoteUpdateID</i>	18	16	Text	Echoed back from the Quote Update request.
<i>QuoteRejectReason</i>	34	1	Text	Reason for rejection of an entire Quote Update message. See Quote Reason Codes for a list of possible quote reject codes. Additional reasons may be added in the future without warning.
<i>Reserved</i>	35	17	Binary	Reserved for future expansion. Filled with 0.

Example Quote Update Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	32 00	50 bytes
<i>MessageType</i>	58	Quote Update Rejected
<i>MatchingUnit</i>	0	Unsequenced message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced message, sequence = 0
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>QuoteUpdateID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>QuoteRejectReason</i>	4D	M = symbols not on same matching engine

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Reserved 00 00 00 00 00 00 00 00 00 00 *Reserved*
00 00 00 00 00 00 00 00

4.2.7 Order Modified

Order Modified messages are sent in response to a Modify Request to indicate that the order has been successfully modified.

Note: You must opt-in to receiving *LeavesQty* in Order Modified messages. In some cases, the last message to be received on an order's lifecycle will be an Order Modified message. The way to know the order is no longer live is to inspect *LeavesQty*. An example of this would be modification of an order whilst an execution is being generated, resulting in the order being reduced to zero outstanding quantity.

Permitted return optional fields are described in 'Section 6.6 – Order Modified'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x27
<i>MatchingUnit</i>	5	1	Binary	The Matching Unit which created this message. Matching units in BOE correspond to Matching Units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per Matching Unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>ClOrdID</i>	18	20	Text	Client order ID. This is the <i>ClOrdID</i> from the Modify Order message.
<i>OrderID</i>	38	8	Binary	Corresponds to <i>OrderID</i> (37) in Cboe FIX. The unique <i>OrderID</i> . Modifications do <i>not</i> change the <i>OrderID</i> .
<i>ReservedInternal</i>	46	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	47	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	48	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Order Modified Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	35 00	63 bytes
<i>MessageType</i>	27	Order Modified
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>ReservedInternal</i>	00	Ignore

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>NumberOfReturn Bitfields</i>	05	Five bitfields to follow
<i>ReturnBitfield1</i>	04	<i>Price</i>
<i>ReturnBitfield2</i>	00	No fields from byte 2
<i>ReturnBitfield3</i>	00	No fields from byte 3
<i>ReturnBitfield4</i>	00	No fields from byte 4
<i>ReturnBitfield5</i>	02	<i>LeavesQty</i>
<i>Price</i>	08 E2 01 00 00 00 00 00	12.34
<i>LeavesQty</i>	00 00 00 00	0 (order done)

4.2.8 Order Restated

Order Restated messages are sent to inform the Member that an order has been asynchronously modified for some reason without an explicit Modify Order request having been sent. Some example (non-exhaustive) reasons for Order Restated messages being sent:

- A reserve (iceberg) order has been reloaded (BZX , C1, and C2 Only).
- An order's remaining quantity was decremented because of a prevented wash trade.
- An order is represented on the Cboe Options Trading Floor (C1 Only).
- A routed order has returned to rest on the book after matching liquidity on another market.

Members should be prepared to accept and apply Order Restated messages for any reason. The return bitfields indicate the characteristics of the order which have changed. Optional fields will be present at the end of the message with the new values.

Note: You must opt-in to receiving *LeavesQty* in Order Restated messages. In some cases, the last message to be received on an order's lifecycle will be an Order Restated message. The way to know the order is no longer live is to inspect *LeavesQty*. An example of this would be restatement of an order in some cases due to *PreventMatch* being set to d.

Permitted return optional fields are described in 'Section 6.7 – Order Restated'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x28
<i>MatchingUnit</i>	5	1	Binary	The Matching Unit which created this message. Matching units in BOE correspond to Matching Units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per Matching Unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>CIOrdID</i>	18	20	Text	The <i>CIOrdID</i> is the identifier from the open order.
<i>OrderID</i>	38	8	Binary	Corresponds to <i>OrderID</i> (37) in Cboe FIX. The unique <i>OrderID</i> . For informational purposes only. Restatements do <i>not</i> change the <i>OrderID</i> .
<i>RestatementReason</i>	46	1	Alphanumeric	The reason for this Order Restated message. E = Reduction of OrdQty due to Equity Leg Reject (C1 only) F = Represented on Floor (C1 only) L = Reload P = Price Sliding Reprice Q = Liquidity Updated

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				R = Reroute S = Ship and Post (SWP) W = Wash f = Unsolicited Floor Action (C1 only) Cboe reserves the right to add new values as necessary without prior notice.
<i>ReservedInternal</i>	47	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturnBitfields</i>	48	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	49	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Order Restated Message for a reserve (iceberg) reload:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	41 00	65 bytes
<i>MessageType</i>	28	Order Restated
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>RestatementReason</i>	4C	L = Reload
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturnBitfields</i>	06	Six bitfields to follow
<i>ReturnBitfield1</i>	00	No fields from byte 1
<i>ReturnBitfield2</i>	00	No fields from byte 2
<i>ReturnBitfield3</i>	00	No fields from byte 3
<i>ReturnBitfield4</i>	00	No fields from byte 4
<i>ReturnBitfield5</i>	02	<i>LeavesQty</i>
<i>ReturnBitfield6</i>	01	<i>SecondaryOrderID</i>
<i>LeavesQty</i>	64 00 00 00	100 contracts
<i>SecondaryOrderID</i>	0A 10 1E B7 5E 39 2F 02	171WC100000A (base 36)

4.2.9 Quote Restated

Quote Restated messages are sent to inform the Member that an order has been asynchronously modified for some reason by the Exchange. For quotes, this could happen if the MTP decrement method has been used by an inbound order against a resting quote. On BZX Options, if a hidden working price is covered by an inbound post only order or quote, a restatement will also occur. Additional reasons may be added in the future.

This message may be expanded in length in the future with new fields added to the end. To maintain forward compatibility, be prepared to receive a message longer than the documented length and to gracefully ignore those extra fields.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x52
<i>MatchingUnit</i>	5	1	Binary	The Matching Unit which created this message. Matching units in BOE correspond to Matching Units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per Matching Unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>QuoteUpdateID</i>	18	16	Text	Echoed back from the most recent <i>Quote Update</i> request for this quote.
<i>OrderID</i>	34	8	Binary	Corresponds to <i>OrderID</i> (37) in Cboe FIX. The unique <i>OrderID</i> . For informational purposes only. Restatements do <i>not</i> change the <i>OrderID</i> .
<i>LeavesQty</i>	42	4	Binary	New quantity available for execution
<i>WorkingPrice</i>	46	8	Binary	New working price
<i>Symbol</i>	54	6	Alphanumeric	Cboe native identifier
<i>Side</i>	60	1	Alphanumeric	1 = Buy 2 = Sell
<i>RestatementReason</i>	61	1	Alphanumeric	The reason for this Quote Restated message. K = Price sliding reprice (BZX only) Q = Liquidity W = Wash Cboe reserves the right to add new values as necessary without prior notice.

Example Quote Restated Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	3C 00	60 bytes
<i>MessageType</i>	52	Quote Restated
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>QuoteUpdateID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>LeavesQty</i>	14 00 00 00	20 contracts
<i>WorkingPrice</i>	AC 07 01 00 00 00 00 00	6.75
<i>Symbol</i>	30 30 34 63 53 73	004cSs
<i>Side</i>	31	1 = Buy
<i>MassCancel</i>	57	W = Wash

4.2.10 User Modify Rejected

User Modify Rejected messages are sent in response to a Modify Order for an order which cannot be modified. User Modify Rejected messages are unsequenced.

This message corresponds to a FIX Execution Report with *MsgType* (35) = 9 (Order Cancel Reject) and *CxlRejResponseTo* (434) = 2 (Order Cancel/Replace Request).

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Permitted return optional fields are described in 'Section 6.8 – User Modify Rejected'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x29
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	Unsequenced application message. Sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>ClOrdID</i>	18	20	Text	The <i>ClOrdID</i> of the modify request which was rejected.
<i>ModifyRejectReason</i>	38	1	Text	Reason for a modify rejection. See Order Reason Codes for a list of possible reasons.
<i>Text</i>	39	60	Text	Human readable text with more information about the reject reason.
<i>ReservedInternal</i>	99	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturnBitfields</i>	100	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	101	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example User Modify Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	63 00	99 bytes
<i>MessageType</i>	29	User Modify Rejected
<i>MatchingUnit</i>	00	Unsequenced Message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced Message, sequence = 0
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00	ABC123
	00 00 00 00 00 00 00 00 00 00	
<i>ModifyRejectReason</i>	50	Pending Fill
<i>Text</i>	50 65 6E 64 69 6E 67 00 00 00	Pending
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturnBitfields</i>	00	No optional fields

4.2.11 Order Cancelled

An order has been cancelled. Permitted return optional fields are described in 'Section 6.9 – Order Cancelled'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x2A
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>CIOrdID</i>	18	20	Text	The order which was cancelled.
<i>CancelReason</i>	38	1	Text	Reason for the order cancellation. See Order Reason Codes for a list of possible reasons.
<i>ReservedInternal</i>	39	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	40	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	41	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Order Cancelled Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	48 00	72 bytes
<i>MessageType</i>	2A	Order Cancelled
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>CIOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>CancelReason</i>	55	U = User Requested
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn Bitfields</i>	05	Five bitfields to follow
<i>ReturnBitfield1</i>	00	No fields from byte 1
<i>ReturnBitfield2</i>	00	No fields from byte 2
<i>ReturnBitfield3</i>	06	<i>ClearingFirm, ClearingAccount</i>
<i>ReturnBitfield4</i>	00	No fields from byte 4
<i>ReturnBitfield5</i>	01	<i>OrigCIOrdID</i>
<i>ClearingFirm</i>	54 45 53 54	TEST
<i>ClearingAccount</i>	31 32 33 34	1234
<i>OrigCIOrdID</i>	41 42 43 31 32 31 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC121

4.2.12 Quote Cancelled

A `Quote Cancelled` message will be sent to indicate an unsolicited cancellation of a quote entered with a `Quote Update` message. An unsolicited cancellation is used, for example, when a resting quote is cancelled due to MTP with an inbound order or quotes are being cancelled due to a risk trip.

This message may be expanded in length in the future with new fields added to the end. To maintain forward compatibility, be prepared to receive a message longer than the documented length and to gracefully ignore those extra fields.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x53
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH. Unsequenced application message. <i>MatchingUnit</i> will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit. This will be an unsequenced application message. The sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>QuoteUpdateID</i>	18	16	Text	Echoed back from the most recent <code>Quote Update</code> request for this quote.
<i>OrderID</i>	34	8	Binary	Order ID assigned by the matching engine
<i>Symbol</i>	42	6	Alphanumeric	Cboe native identifier
<i>Side</i>	48	1	Alphanumeric	1 = Buy 2 = Sell
<i>CancelReason</i>	49	1	Text	Reason for the quote cancellation. See Order Reason Codes for a list of possible reasons.

Example Quote Cancelled Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	30 00	48 bytes
<i>MessageType</i>	53	Quote Cancelled
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>QuoteUpdateID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>Symbol</i>	30 30 36 69 70 41	006ipA
<i>Side</i>	32	2 = Sell

CancelReason

41

A = Admin

4.2.13 Cross Order Cancelled (C1 and EDGX Only)

A *New Order Cross* has been cancelled. Individual order allocations from the original *New Order Cross* and *New Order Cross Multileg* message will be echoed back in the repeating groups.

In each repeating group, the *ClOrdID* and *OrderID* are always returned. Beyond that, the bits specified in the optional return bitfields parameter group control which fields are returned. Any fields that appear in the repeating groups will not appear in the optional fields that come after the repeating groups.

Permitted return optional fields are described in 'Section 6.10 – Cross Order Cancelled'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x46
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>CrossID</i>	18	20	Text	The cross order which was cancelled.
<i>CancelReason</i>	38	1	Text	Reason for the order cancellation. See Order Reason Codes for a list of possible reasons.
<i>ReservedInternal</i>	39	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	40	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	41	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>GroupCnt</i>		2	Binary	Number of order allocations represented by repeating groups included in this message.
<i>Repeating Groups Of...</i>				
<i>ClOrdID</i>		20	Text	Copied from original cross order.
<i>OrderID</i>		8	Binary	The order id of the cross order that was cancelled.
<i>Side (Optional)</i>		1	Alphanumeric	See List of Optional Fields .
<i>AllocQty (Optional)</i>		4	Binary	See List of Optional Fields .
<i>Capacity (Optional)</i>		1	Alpha	See List of Optional Fields .
<i>OpenClose (Optional)</i>		1	Alphanumeric	See List of Optional Fields .

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>GiveUpFirmID</i> (Optional)		4	Alpha	See List of Optional Fields.
<i>Account</i> (Optional)		16	Text	See List of Optional Fields.
<i>CMTANumber</i> (Optional)		4	Binary	See List of Optional Fields.
<i>ClearingAccount</i> (Optional)		4	Text	See List of Optional Fields.
<i>Optional fields. . .</i>				Optional fields as set in the bitmap. Note, optional fields that occur in the repeating groups appear above, repeating per group, not within this block.

Example Cross Order Cancelled Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	8A 00	138 bytes
<i>MessageType</i>	46	Cross Order Cancelled
<i>MatchingUnit</i>	02	Matching Unit 2
<i>SequenceNumber</i>	01 00 00 00	Sequence number 1
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	4E 5A 31 56 37 42 4A 5F 41 63 63 65 70 74 42 75 79 00 00 00	NZ1V7BJ_AcceptBuy
<i>CancelReason</i>	55	U = User Requested
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn</i>		
<i>Bitfields</i>	02	Two bitfields to follow
<i>ReturnBitfield1</i>	00	No fields from byte 1
<i>ReturnBitfield2</i>	41	<i>Symbol, Capacity</i>
<i>GroupCnt</i>	03 00	Two repeating groups to follow
<i>ClOrdID</i>	4E 5A 31 56 37 47 4E 5F 61 67 65 6E 63 79 00 00 00 00 00 00	NZ1V7GN_agency
<i>OrderID</i>	02 C0 91 A2 94 AB 78 04	2G4GYK000002 (base 36)
<i>Capacity</i>	43	C = Customer
<i>ClOrdID</i>	4E 5A 31 56 37 4B 46 5F 63 6F 6E 74 72 61 31 00 00 00 00 00	NZ1V7KF_contra1
<i>OrderID</i>	03 C0 91 A2 94 AB 78 04	2G4GYK000003 (base 36)
<i>Capacity</i>	46	F = Firm
<i>ClOrderID</i>	4E 5A 31 56 37 4E 48 5F 63 6F 6E 74 72 61 32 00 00 00 00 00	NZ1V7NH_contra2
<i>OrderID</i>	04 C0 91 A2 94 AB 78 04	2G4GYK000004 (base 36)
<i>Capacity</i>	46	F = Firm
<i>Symbol</i>	30 30 51 30 6B 41 00 00	00Q0kA

4.2.14 Cancel Rejected

A `Cancel Rejected` message is sent in response to a `Cancel Order` message to indicate that the cancellation cannot occur. `Cancel Rejected` messages are unsequenced.

Permitted return bitfields are described in 'Section 6.11 – Cancel Rejected'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x2B
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	Unsequenced application message. Sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>ClOrdID</i>	18	20	Text	The order whose cancel was rejected.
<i>CancelRejectReason</i>	38	1	Text	Reason for the order cancellation. See Order Reason Codes for a list of possible reasons.
<i>Text</i>	39	60	Text	Human readable text with more information about the reject reason.
<i>ReservedInternal</i>	99	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	100	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	101	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Cancel Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	63 00	99 bytes
<i>MessageType</i>	2B	Cancel Rejected
<i>MatchingUnit</i>	00	Unsequenced Message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced Message, sequence = 0
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00	ABC123
	00 00 00 00 00 00 00 00 00 00	
<i>CancelRejectReason</i>	4A	J
<i>Text</i>	54 4F 4F 20 4C 41 54 45 00 00	TOO LATE
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn Bitfields</i>	00	No optional fields

4.2.15 Order Execution

An `Order Execution` is sent for each fill on an order.

Rather than returning a monetary value indicating the rebate or charge for an execution, the *FeeCode* is an indication of a fee classification corresponding to an item on the venue's fee schedule.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

For executions involving complex orders (**EDGX or C2 only**), an Order Execution message will be generated for the complex order, with *MultilegReportingType* = 3, followed by Order Execution messages for each leg, with *MultilegReportingType* = 2. You must opt-in to receiving this optional field on Order Execution messages at login in order to receive this field.

The symbology used on executions for complex orders, including the legs, will **always** be Cboe symbology.

Permitted return bitfields are described in 'Section 6.12 – Order Execution'.

Field	Offset	Length	Data Type	Description								
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.								
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.								
<i>MessageType</i>	4	1	Binary	0x2C								
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH.								
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit.								
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).								
<i>ClOrdID</i>	18	20	Text	Order receiving the execution.								
<i>ExecID</i>	38	8	Binary	<div>Corresponds to <i>ExecID</i> (17) in Cboe FIX.</div> <div>Execution ID. Unique across all matching units on a given day. Note: <i>ExecIDs</i> will be represented on ODROP and FIXDROP ports as nine character, base 36 ASCII. Leading zeros should be added if the converted base 36 value is shorter than nine characters.</div> <div>Example conversion:</div> <table><tr><th>Decimal</th><th>Base 36</th></tr><tr><td>28294005440239</td><td>A1234B567</td></tr><tr><td>76335905726621</td><td>R248BC23H</td></tr><tr><td>728557228187</td><td>09AP05V2Z</td></tr></table>	Decimal	Base 36	28294005440239	A1234B567	76335905726621	R248BC23H	728557228187	09AP05V2Z
Decimal	Base 36											
28294005440239	A1234B567											
76335905726621	R248BC23H											
728557228187	09AP05V2Z											
<i>LastShares</i>	46	4	Binary	<div>Corresponds to <i>LastShares</i> (32) in Cboe FIX.</div> <div>Executed share quantity.</div>								
<i>LastPx</i>	50	8	Binary Price	<div>Corresponds to <i>LastPx</i> (31) in Cboe FIX.</div> <div>Price of this fill. Note the use of <i>Binary Price</i> type to represent positive and negative prices, which can occur with complex instruments.</div>								
<i>LeavesQty</i>	58	4	Binary	<div>Corresponds to <i>LeavesQty</i> (151) in Cboe FIX.</div> <div>Quantity still open for further execution. If zero, the order is complete.</div>								
<i>BaseLiquidity Indicator</i>	62	1	Alphanumeric	<div>Indicates whether the trade added or removed liquidity.</div> <div>A = Added Liquidity</div> <div>R = Removed Liquidity</div> <div>X = Routed to Another Market</div> <div>C = Auction/Uncrossing</div>								
<i>SubLiquidityIndicator</i>	63	1	Alphanumeric	<div>Cboe may add additional values without notice. Members must gracefully ignore unknown values.</div> <div>ASCII NUL (0x00) = No additional information</div>								

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				<p>S = Execution from order that set the NBBO B = Step Up Mechanism (EDGX Only) b = AIM (C1 and EDGX Only) q = QCC (C1 and EDGX Only) s = SAM (C1 Only) Effective on EDGX TBD</p>
<i>ContraBroker</i>	64	4	Alphanumeric	<p>Corresponds to <i>ContraBroker</i> (375) in Cboe FIX.</p> <p>Simple Instrument Fills Internally matched simple executions will identify the OCC clearing number of the contra on the execution. This includes leg fill reports (<i>MultilegReportingType</i>=2) that are sent as a result of a complex trade.</p> <p>Executions matched on the C1 trading floor will contain a value of "FBKR" for <i>ContraBroker</i> for the first reporter of a Broker to Broker floor trade otherwise, this will identify the OCC clearing number of the contra (C1 only).</p> <p>Complex Package Fills <i>ContraBroker</i> will be sent and populated on electronic, complex package fills (<i>MultilegReportingType</i>=3) when the contra side is also a complex order. When legging in to the simple books <i>ContraBroker</i> will be blank.</p> <p><i>ContraBroker</i> will be blank on complex package fills (<i>MultilegReportingType</i>=3) executed on the Cboe Options trading floor (C1 only).</p> <p>Routed Fills All externally matched (routed, <i>BaseLiquidityIndicator</i>=X) executions will identify the away exchange with the following possible values.</p> <p>AMEX = Routed to NYSE American ARCA = Routed to NYSE Arca BATS = Routed to Cboe BZX Options BOX = Routed to BOX CBOE = Routed to Cboe Options CTWO = Routed to C2 Options EDGX = Routed to Cboe EDGX Options EMLD = Routed to MIAX Emerald GMNI = Routed to Nasdaq GEMX ISE = Routed to Nasdaq ISE MERC = Routed to Nasdaq MRX MIAX = Routed to MIAX Options Exchange NOMX = Routed to Nasdaq NOBX = Routed to Nasdaq BX PERL = Routed to MIAX PEARL PHLX = Routed to Nasdaq PHLX</p>
<i>ReservedInternal</i>	68	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	69	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield^a</i>	70	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfield^a</i>		1	Binary	Last bitfield.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Optional fields...				
--------------------	--	--	--	--

Example Order Execution Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	53 00	83 bytes
<i>MessageType</i>	2C	Order Execution
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>ExecID</i>	01 F0 B7 D9 71 21 00 00	D19800001 (base 36)
<i>LastShares</i>	64 00 00 00	100 contracts
<i>LastPx</i>	08 E2 01 00 00 00 00 00	12.34
<i>LeavesQty</i>	14 00 00 00	20 contracts
<i>BaseLiquidityIndicator</i>	41	A = Added
<i>SubLiquidityIndicator</i>	00	(unset)
<i>ContraBroker</i>	43 46 45 00	BATS
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn</i>	03	Three bitfields to follow
<i>Bitfields</i>		
<i>ReturnBitfield1</i>	00	No bitfields from byte 1
<i>ReturnBitfield2</i>	00	No bitfields from byte 2
<i>ReturnBitfield3</i>	46	<i>ClearingFirm</i> , <i>ClearingAccount</i> , <i>OrderQty</i>
<i>ClearingFirm</i>	54 45 53 54	TEST
<i>ClearingAccount</i>	31 32 33 43	1234
<i>OrderQty</i>	78 00 00 00	120 contracts

4.2.16 Quote Execution

A *Quote Execution* message is used to indicate an execution has occurred on a resting quote.

This message may be expanded in length in the future with new fields added to the end. To maintain forward compatibility, be prepared to receive a message longer than the documented length and to gracefully ignore those extra fields.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x54
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>QuoteUpdateID</i>	18	16	Text	Echoed back from the most recent <i>Quote Update</i> request for this quote.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

OrderID	34	8	Binary	Order ID assigned by the matching engine								
ExecID	42	8	Binary	Corresponds to ExecID (17) in Cboe FIX. Execution ID. Unique across all matching units on a given day. Note: ExecIDs will be represented on FIXDROP ports as nine character, base 36 ASCII. Leading zeros should be added if the converted base 36 value is shorter than nine characters. Example conversion: <table><tr><th>Decimal</th><th>Base 36</th></tr><tr><td>28294005440239</td><td>A1234B567</td></tr><tr><td>76335905726621</td><td>R248BC23H</td></tr><tr><td>728557228187</td><td>09AP05V2Z</td></tr></table>	Decimal	Base 36	28294005440239	A1234B567	76335905726621	R248BC23H	728557228187	09AP05V2Z
Decimal	Base 36											
28294005440239	A1234B567											
76335905726621	R248BC23H											
728557228187	09AP05V2Z											
Symbol	50	6	Alphanumeric	Cboe native identifier								
ClearingFirm	56	4	Alpha	Echoed back from the original quote								
LastShares	60	4	Binary	Corresponds to LastShares (32) in Cboe FIX. Number of contracts being traded.								
LastPx	64	8	Binary Price	Corresponds to LastPx (31) in Cboe FIX. Price of this fill.								
LeavesQty	72	4	Binary	Corresponds to LeavesQty (151) in Cboe FIX. Quantity still open for further execution. If zero, the order is complete.								
ContraTrader	76	4	Alphanumeric	Displays the EFID (ClearingFirm) of the contra side firm.								
ContraCapacity	80	1	Alphanumeric	Capacity of the contra for this execution.								
Side	81	1	Alpha	1 = Buy 2 = Sell								
BaseLiquidity Indicator	82	1	Alpha	Indicates whether the trade added or removed liquidity. A = Added Liquidity R = Removed Liquidity C = Auction/Uncrossing								
SubLiquidityIndicator	83	1	Alpha	Cboe may add additional values without notice. Members must gracefully ignore unknown values. ASCII NUL (0x00) = No additional information S = Execution from order that set the NBBO B = Step Up Mechanism (EDGX Only) b = Bats Auction Mechanism (EDGX Only) q = QCC (C1 and EDGX Only) s = SAM (C1 Only) Effective on EDGX TBD								
FeeCode	84	2	Alphanumeric	Corresponds to FeeCode (9882) in Cboe FIX.								
MarketingFeeCode	86	2	Alphanumeric	Corresponds to MarketingFeeCode (5937) in Cboe FIX. EDGX Only. Will be blank on other Exchanges.								

Example Quote Execution Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	56 00	86 bytes
<i>MessageType</i>	54	Quote Execution

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>QuoteUpdateID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>ExecID</i>	01 F0 B7 D9 71 21 00 00	D19800001 (base 36)
<i>Symbol</i>	30 30 36 69 70 41	006ipA
<i>ClearingFirm</i>	41 42 43 44	ABCD
<i>LastShares</i>	64 00 00 00	100 contracts
<i>LastPx</i>	70 17 00 00 00 00 00 00	0.60
<i>LeavesQty</i>	00 00 00 00	0 (order done)
<i>ContraTrader</i>	41 42 43 44	ABCD
<i>ContraCapacity</i>	43	C = Customer
<i>Side</i>	31	1 = Buy
<i>BaseLiquidity Indicator</i>	41	A = Added
<i>SubLiquidityIndicator</i>	4E	N = Normal
<i>FeeCode</i>	41 42	AB
<i>MarketingFeeCode</i>	58 59	XY

4.2.17 Trade Cancel or Correct

Used to relay a trade which has been cancelled (busted) or corrected (price or size change only). The *CorrectedPrice* and optional *CorrectedSize* fields will be set to 0 for cancelled trades and to the new trade price and/or size for corrected trades. Trade Cancel or Correct **can be sent for same day as well as previous day trades.**

Trade cancels or corrections to complex instruments will result in individual Trade Cancel or Correct messages being sent for each leg. No cancels or corrections will be sent for complex instruments.

Permitted return bitfields are described in 'Section 6.13 – Trade Cancel or Correct'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x2D
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>ClOrdID</i>	18	20	Text	<i>ClOrdID</i> of the order whose fill is being cancelled or corrected.
<i>OrderID</i>	38	8	Binary	Corresponds to <i>OrderID</i> (37) in Cboe FIX. Order whose fill is being cancelled or corrected.
<i>ExecRefID</i>	46	8	Binary	Corresponds to <i>ExecRefID</i> (19) in Cboe FIX. Refers to the <i>ExecID</i> of the fill being cancelled or corrected.
<i>Side</i>	54	1	Alphanumeric	Side of the order.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>BaseLiquidity Indicator</i>	55	1	Alphanumeric	Indicates whether the trade added or removed liquidity. A = Added Liquidity R = Removed Liquidity X = Routed to Another Market C = Auction/Uncrossing
<i>ClearingFirm</i>	56	4	Alpha	Echoed back from the original order.
<i>ClearingAccount</i>	60	4	Text	Echoed back from the original order.
<i>LastShares</i>	64	4	Binary	Number of shares of the trade being cancelled.
<i>LastPx</i>	68	8	Binary Price	Price of the trade being cancelled. Note the use of <i>Binary Price</i> type to represent positive and negative prices, which can occur with complex instruments.
<i>CorrectedPrice</i>	76	8	Binary Price	For trade corrections, this is the new trade price. For trade breaks, this is set to 0.
<i>OrigTime</i>	84	8	DateTime	Corresponds to <i>OrigTime</i> (42). The date and time of the original trade, in GMT.
<i>ReservedInternal</i>	92	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	93	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	94	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Trade Cancel or Correct Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	76 00	118 bytes
<i>MessageType</i>	2D	Trade Cancel or Correct
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderID</i>	05 10 1E B7 5E 39 2F 02	171WC1000005 (base 36)
<i>ExecRefID</i>	01 F0 B7 D9 71 21 00 00	D19800001 (base 36)
<i>Side</i>	31	Buy
<i>BaseLiquidity Indicator</i>	41	A = Added
<i>ClearingFirm</i>	54 45 53 54	TEST
<i>ClearingAccount</i>	00 00 00 00	(empty)
<i>LastShares</i>	64 00 00 00	100 contracts
<i>LastPx</i>	70 17 00 00 00 00 00 00	0.60
<i>CorrectedPrice</i>	00 00 00 00 00 00 00 00	0 (cancelled)
<i>OrigTime</i>	E0 BA 75 95 15 4C EB 11	1,291,209,373,757,324,000
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn Bitfields</i>	04	Four bitfields to follow
<i>ReturnBitfield1</i>	00	No fields from byte 1
<i>ReturnBitfield2</i>	01	<i>Symbol</i>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>ReturnBitfield3</i>	00	No fields from byte 3
<i>ReturnBitfield4</i>	17	<i>MaturityDate</i> , <i>StrikePrice</i> , <i>PutOrCall</i> , <i>OpenClose</i>
<i>Symbol</i>	30 30 51 30 6B 41 00 00	00Q0kA
<i>MaturityDate</i>	EF DB 32 01	2011-03-19
<i>StrikePrice</i>	98 AB 02 00 00 00 00 00	17.50
<i>PutOrCall</i>	31	1 = Call
<i>OpenClose</i>	4F	O = Open

4.2.18 Purge Rejected

A *Purge Rejected* message is sent in response to a *Purge Orders* message to indicate that the mass cancellation cannot occur. *Purge Rejected* messages are unsequenced.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x48
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	Unsequenced application message. Sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>PurgeRejectReason</i>	18	1	Text	Reason for a purge rejection. See Order Reason Codes for a list of possible reasons.
<i>Text</i>	19	60	Text	Human readable text with more information about the reject reason.
<i>ReservedInternal</i>	79	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturnBitfields</i>	80	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield₁</i>	81	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfield_n</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Purge Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	72 00	114 bytes
<i>MessageType</i>	48	Purge Rejected
<i>MatchingUnit</i>	00	Unsequenced Message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced Message, sequence = 0
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>PurgeRejectReason</i>	41	A

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>Text</i>	41 44 4D 49 4E 00 00 00 00 00	ADMIN
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn Bitfields</i>	0F	15 bitfields to follow
<i>ReturnBitfield1</i>	00	No fields from byte 1
<i>ReturnBitfield2</i>	00	No fields from byte 2
<i>ReturnBitfield3</i>	00	No fields from byte 3
<i>ReturnBitfield4</i>	00	No fields from byte 4
<i>ReturnBitfield5</i>	00	No fields from byte 5
<i>ReturnBitfield6</i>	00	No fields from byte 6
<i>ReturnBitfield7</i>	00	No fields from byte 7
<i>ReturnBitfield8</i>	00	No fields from byte 8
<i>ReturnBitfield9</i>	00	No fields from byte 9
<i>ReturnBitfield10</i>	00	No fields from byte 10
<i>ReturnBitfield11</i>	00	No fields from byte 11
<i>ReturnBitfield12</i>	00	No fields from byte 12
<i>ReturnBitfield13</i>	00	No fields from byte 13
<i>ReturnBitfield14</i>	00	No fields from byte 14
<i>ReturnBitfield15</i>	08	<i>MassCancelID</i>
<i>MassCancelID</i>	54 45 53 54 00 00 00 00 00 00	TEST
	00 00 00 00 00 00 00 00 00 00	

4.2.19 Reset Risk Acknowledgment

Response to a `Reset Risk` request.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x57
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	Unsequenced application message. Sequence number will be set to 0.
<i>RiskStatusID</i>	10	16	Text	Unique identifier for this Reset Risk request. Response message will have this corresponding identifier.
<i>RiskResetResult</i>	26	1	Text	<space> = Ignored; exceeds 1 reset per second Y = Success F = Rejected; exceeds firm reset limit C = Rejected; exceeds Custom Group ID limit D = Rejected; automatic risk resets are disabled E = Rejected; empty <i>ResetRisk</i> field I = Rejected; Incorrect data center S = Rejected; exceeds risk root reset limit

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				U = Rejected; invalid <i>RiskRoot</i> c = Rejected; invalid <i>EFID/ClearingFirm</i> y = Rejected; in replay Additional reject values may be added in the future with no notice.
--	--	--	--	---

Example Risk Reset Acknowledgment Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	19 00	25 bytes
<i>MessageType</i>	57	Risk Reset Acknowledgement
<i>MatchingUnit</i>	00	Unsequenced Message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced Message, sequence = 0
<i>RiskStatusID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00	ABC123
<i>RiskResetResult</i>	00	Y = Success

4.2.20 Mass Cancel Acknowledgment

A Mass Cancel Acknowledgment is an unsequenced message sent when a Cancel Order or Purge Orders message requesting a mass cancellation has completed cancelling all individual orders.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x36
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	Unsequenced application. Message. Sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time in the order entry gateway when the final matching engine event was received to complete the mass cancel.
<i>MassCancelID</i>	18	20	Text	Copied from the <i>MassCancelID</i> passed on the original Cancel Order or Purge Orders. This field corresponds to <i>MassCancelID</i> (7695) in Cboe FIX.
<i>CancelledOrder Count</i>	38	4	Binary	Number of orders cancelled. This field corresponds to <i>CancelledOrderCount</i> (7696) in Cboe FIX.
<i>ReservedInternal</i>	42	1	Binary	Reserved for Cboe internal use.

Example Mass Cancel Acknowledgment Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA	Start of message bytes.
<i>MessageLength</i>	29 00	41 bytes
<i>MessageType</i>	36	Mass Cancel Acknowledgment
<i>MatchingUnit</i>	00	Unsequenced Message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced Message, sequence = 0
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>MassCancelID</i>	41 42 43 31 32 33 00 00 00 00	ABC123
	00 00 00 00 00 00 00 00 00 00	
<i>CancelledOrderCount</i>	63 00 00 00	99 orders were cancelled
<i>ReservedInternal</i>	00	Ignore

4.2.21 Complex Instrument Accepted (C1, C2, and EDGX Only)

The `Complex Instrument Accepted` is used to indicate acceptance of a complex strategy. The leg order sent back may differ from the originating request; *RevisedLegs* will indicate if the leg order has been altered from the original request.

Permitted return bitfields are described in 'Section 6.14 – Complex Instrument Accepted'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x4D
<i>MatchingUnit</i>	5	1	Binary	The matching unit which created this message. Matching units in BOE correspond to matching units on Multicast PITCH.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message. Distinct per matching unit.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>ClOrdID</i>	18	20	Text	Echoed back from the original request.
<i>Symbol</i>	38	8	Alphanumeric	The complex instrument id.
<i>RevisedLegs</i>	46	1	Alphanumeric	Indicates if the legs on the created complex strategy have been reordered from the original request. If the legs were reordered, the order of the Open-Close fields on a <code>New Complex Order</code> must be the order returned by the exchange, not the order from the original request. 1 = Legs were not reordered 2 = Legs were reordered
<i>NoOfSecurities</i>	47	4	Binary	Corresponds to <i>NoOfSecurities</i> (8641) in Cboe FIX. Indicates the number of securities created by the member in the trading session.
<i>ReservedInternal</i>	51	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturnBitfields</i>	52	1	Binary	Number of bitfields to follow.
<i>ReturnBitfieldⁱ</i>	53	1	Binary	Bitfield identifying fields to follow.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>NoLegs</i>		1	Binary	Echoed back from the original request.
Repeating Group <i>ComplexLeg</i> must occur the number of times specified in <i>NoLegs</i> . Each field occurs in each group, in order as shown below. Optional fields occur only if corresponding bits in bitfields are set.				

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>LegSymbol</i>	8	Alphanumeric	Corresponds to <i>LegSymbol</i> (600) in Cboe FIX. Entire Cboe format symbol or OSI Root. Must send <i>LegCFICode</i>, <i>LegMaturityDate</i>, and <i>LegStrikePrice</i> if using OSI format.
<i>LegCFICode</i>	6	Alphanumeric	Corresponds to <i>LegCFICode</i> (608) in Cboe FIX. CFI Code for leg. Required if <i>LegSymbol</i> is in OSI format. OP = Options Put OC = Options Call E = Equity
<i>LegMaturityDate</i>	4	Date	Corresponds to <i>LegMaturityDate</i> (611) in Cboe FIX. Required if <i>LegSymbol</i> is in OSI format.
<i>LegStrikePrice</i>	8	Binary Price	Corresponds to <i>LegStrikePrice</i> (612) in Cboe FIX. Option strike price. System maximum is 99,999,999. Must be non-negative. Required if <i>LegSymbol</i> is in OSI format.
<i>LegRatioQty</i>	4	Binary	Corresponds to <i>LegRatioQty</i> (623) in Cboe FIX. Ratio of number of contracts in this leg per order quantity. Must be between 1 and 99,999.
<i>LegSide</i>	1	Alphanumeric	Corresponds to <i>LegSide</i> (624) in Cboe FIX. 1 = Buy 2 = Sell
<i>Optional fields...</i>			Optional fields as set in the bitmap. Note, optional fields that occur in the repeating groups appear above, repeating per group, not within this block.

Example Complex Instrument Accepted Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	7C 00	124 bytes
<i>MessageType</i>	4D	Complex Instrument Accepted
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>Symbol</i>	5A 4E 4B 38 46 43 00 00	ZNK8FC
<i>RevisedLegs</i>	30	Legs accepted as sent
<i>NoOfSecurities</i>	04 00 00 00	Four complex strategies created by sender
<i>NumberOfReturn Bitfields</i>	0D	13 bitfields to follow
<i>ReturnBitfield1</i>	00	No fields from byte 1
<i>ReturnBitfield2</i>	00	No fields from byte 2
<i>ReturnBitfield3</i>	00	No fields from byte 3
<i>ReturnBitfield4</i>	00	No fields from byte 4
<i>ReturnBitfield5</i>	00	No fields from byte 5

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>ReturnBitfield6</i>	00	No fields from byte 6
<i>ReturnBitfield7</i>	00	No fields from byte 7
<i>ReturnBitfield8</i>	00	No fields from byte 8
<i>ReturnBitfield9</i>	00	No fields from byte 9
<i>ReturnBitfield10</i>	00	No fields from byte 10
<i>ReturnBitfield11</i>	00	No fields from byte 11
<i>ReturnBitfield12</i>	00	No fields from byte 12
<i>ReturnBitfield13</i>	06	<i>LegCFIcode</i> , <i>LegMaturityDate</i> , <i>LegStrikePrice</i>
<i>NoLegs</i>	02	Two legs
<i>LegSymbol</i>	4D 53 46 54 00 00 00 00	MSFT
<i>LegCFIcode</i>	4F 43 00 00 00 00	OC = Option Call
<i>LegMaturityDate</i>	EF DB 32 01	2011-03-19
<i>LegStrikePrice</i>	98 AB 02 00 00 00 00 00	17.50
<i>LegRatioQty</i>	02 00 00 00	Ratio of 2
<i>LegSide</i>	31	Buy
<i>LegSymbol</i>	4D 53 46 54 00 00 00 00	MSFT
<i>LegCFIcode</i>	4F 50 00 00 00 00	OP = Option Put
<i>LegMaturityDate</i>	F6 DB 32 01	2011-03-26
<i>LegStrikePrice</i>	30 E6 02 00 00 00 00 00	19.00
<i>LegRatioQty</i>	01 00 00 00	Ratio of 1
<i>LegSide</i>	32	Sell

Example Minimal Complex Instrument Accepted Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	47 00	71 bytes
<i>MessageType</i>	4D	Complex Instrument Accepted
<i>MatchingUnit</i>	03	Matching Unit 3
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>CIOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>Symbol</i>	5A 4E 4B 38 46 43 00 00	ZNK8FC
<i>RevisedLegs</i>	30	Legs accepted as sent
<i>NoOfSecurities</i>	04 00 00 00	Four complex strategies created by sender
<i>NumberOfReturn Bitfields</i>	00	No bitfields follow
<i>NoLegs</i>	02	Two legs
<i>LegSymbol</i>	30 30 51 30 6B 41 00 00	00Q0kA
<i>LegRatioQty</i>	02 00 00 00	Ratio of 2
<i>LegSide</i>	31	Buy
<i>LegSymbol</i>	30 30 51 33 6B 43 00 00	00Q3kC
<i>LegRatioQty</i>	01 00 00 00	Ratio of 1
<i>LegSide</i>	32	Sell

4.2.22 Complex Instrument Rejected (C1, C2, and EDGX Only)

The Complex Instrument Rejected message is used to indicate that a requested complex strategy has been rejected. Complex Instrument Rejected messages are unsequenced.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Permitted return bitfields are described in 'Section 6.15 – Complex Instrument Rejected'.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x4E
<i>MatchingUnit</i>	5	1	Binary	Unsequenced application message. Matching unit will be set to 0.
<i>SequenceNumber</i>	6	4	Binary	Unsequenced application message. Sequence number will be set to 0.
<i>TransactionTime</i>	10	8	DateTime	The time the event occurred in the Cboe Matching Engine (not the time the message was sent).
<i>CIOrdID</i>	18	20	Text	Echoed back from the original request.
<i>OrderRejectReason</i>	38	1	Text	Reason for an order rejection. See Order Reason Codes for a list of possible reasons.
<i>Text</i>	39	60	Text	Human readable text with more information about the reject reason.
<i>NoOfSecurities</i>	99	4	Binary	Indicates the number of securities created by the member in this trading session.
<i>ReservedInternal</i>	103	1	Binary	Reserved for Cboe internal use.
<i>NumberOfReturn Bitfields</i>	104	1	Binary	Number of bitfields to follow.
<i>ReturnBitfield¹</i>	105	1	Binary	Bitfield identifying fields to return.
...				
<i>ReturnBitfieldⁿ</i>		1	Binary	Last bitfield.
<i>Optional fields. . .</i>				

Example Complex Instrument Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes
<i>MessageLength</i>	67 00	103 bytes
<i>MessageType</i>	4E	Complex Instrument Rejected
<i>MatchingUnit</i>	0	Unsequenced message, unit = 0
<i>SequenceNumber</i>	00 00 00 00	Unsequenced message, sequence = 0
<i>TransactionTime</i>	E0 FA 20 F7 36 71 F8 11	1,294,909,373,757,324,000
<i>CIOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>OrderRejectReason</i>	44	D
<i>Text</i>	44 75 70 6C 69 63 61 74 65 20 43 6C 4F 72 64 49 44 00	Duplicate CIOrdID

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

	00 00 00 00 00 00 00 00 00 00	
<i>NoOfSecurities</i>	04 00 00 00	Four complex strategies created by sender
<i>ReservedInternal</i>	00	Ignore
<i>NumberOfReturn</i>	00	No bitfields follow
<i>Bitfields</i>		

4.2.23 Floor Trade Notification (C1 Only)

TPHs having in-person Market Makers on the Cboe trading floor may optionally receive Floor Trade Notification messages. TPHs must request the Enable Floor Trade Notifications port attribute be enabled for one or more floor acronyms in order to receive these messages. TPHs are encourage to use Floor Trade Confirmation messages to respond to Floor Trade Notification messages if they agree with the terms of the trade. Alternatively, an Add Floor Trade message may be used to enter their version of the floor trade. If the floor trade notification is not known to the Market Maker (for example, if the TPH is misidentified as a contra party to the floor trade), the message can be disregarded; a response is not required. TPHs configured to be automatically endorsed to floor trades will not receive a Floor Trade Notification; only an Order Executed message.

Field	Offset	Length	Data Type	Description								
StartOfMessage	0	2	Binary	Must be 0xBA 0xBA.								
MessageLength	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the StartOfMessage field.								
MessageType	4	1	Binary	0x62								
MatchingUnit	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.								
SequenceNumber	6	4	Binary	The sequence number for this message.								
ExecID	10	8	Binary	<p>Corresponds to ExecID (17) in Cboe FIX.</p> <p>Execution ID. Unique across all matching units on a given day. Note: ExecIDs will be represented on ODROP and FIXDROP ports as nine character, base 36 ASCII. Leading zeros should be added if the converted base 36 value is shorter than nine characters.</p> <p>Example conversion:</p> <table><tr><th>Decimal</th><th>Base 36</th></tr><tr><td>28294005440239</td><td>A1234B567</td></tr><tr><td>76335905726621</td><td>R248BC23H</td></tr><tr><td>728557228187</td><td>09AP05V2Z</td></tr></table>	Decimal	Base 36	28294005440239	A1234B567	76335905726621	R248BC23H	728557228187	09AP05V2Z
Decimal	Base 36											
28294005440239	A1234B567											
76335905726621	R248BC23H											
728557228187	09AP05V2Z											
Symbol	18	8	Alphanumeric	<p>Corresponds to Symbol (55) in Cboe FIX.</p> <p>Entire Cboe format symbol or OSI symbol if using long format.</p>								
PutOrCall	26	1	Alphanumeric	<p>Corresponds to PutOrCall (201) in Cboe FIX.</p> <p>0 = Put 1 = Call</p> <p>NULL (0x00) filled if using Cboe format symbol.</p>								
StrikePrice	27	8	Binary Price	<p>Corresponds to StrikePrice (202) in Cboe FIX.</p> <p>Strike Price for option, 0 – 999,999.99</p>								

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

				NULL (0x00) filled if using Cboe format symbol.
<i>MaturityDate</i>	31	4	Date	Corresponds to <i>MaturityMonth</i> (200) and <i>MaturityDay</i> (205) in Cboe FIX. NULL (0x00) filled if using Cboe format symbol.
<i>OrderQty</i>	35	4	Binary	Corresponds to <i>OrderQty</i> (38) in Cboe FIX. System limit is 999,999 contracts.
<i>Price</i>	39	8	Binary Price	Corresponds to <i>Price</i> (44) in Cboe FIX. Execution price.
<i>Side</i>	47	1	Alphanumeric	Corresponds to <i>Side</i> (54) in Cboe FIX. 1 = Buy 2 = Sell
<i>ContraTrader</i>	48	4	Alphanumeric	Displays the Contra Trader floor acronym.
<i>FloorTraderAcronym</i>	52	3	Alpha	Floor Acronym of participant submitting trade.
<i>TradeTime</i>	55	8	DateTime	Trade time
<i>TradeThroughAlertType</i>	63	1	Alphanumeric	Corresponds to <i>TradeThroughAlertType</i> (21098) in Cboe FIX. Indication of a type of trade through. 0 = No trade through 1 = NBBO 2 = BBO (local best bid or offer) 3 = SBBO (market quote of complex derived by legs) 4 = Book trade through (trade through customer size) 5 = Due Dilligence trade through
<i>PriceType</i>	64	1	Alphanumeric	Corresponds to <i>PriceType</i> (423) in Cboe FIX. 1 = Percentage, when trading FLEX percentage instruments* 2 = (Default) Price per unit (contract) * Percentage pricing for FLEX orders is only available for index products.
<i>Reserved</i>	65	15	Reserved	Reserved

Example Floor Trade Notification Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	4E 00	78 bytes
<i>MessageType</i>	62	Floor Trade Notification
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ExecID</i>	01 F0 B7 D9 71 21 00 00	D19800001 (base 36)
<i>Symbol</i>	30 30 36 69 70 41 00 00	006ipA
<i>PutorCall</i>	00	
<i>StrikePrice</i>	00 00 00 00 00 00 00 00	
<i>MaturityDate</i>	00 00 00 00	

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>OrderQty</i>	64 00 00 00	100
<i>Price</i>	C8 32 00 00 00 00 00 00	1.30
<i>Side</i>	31	1 = Buy
<i>ContraTrader</i>	41 41 41	AAA
<i>FloorTraderAcronym</i>	42 42 42	BBB
<i>TradeTime</i>	68 23 4A 8B 27 12 B4 15	1,563,894,931,654,321,000
<i>TradeThroughAlertType</i>	30	0 = No trade through
<i>PriceType</i>	02	2 = Price per unit
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	Reserved

4.2.24 Add Floor Trade Rejected (C1 Only)

The Add Floor Trade Rejected message is used to indicate that a requested Add Floor Trade has been rejected. Add Floor Trade Rejected messages are unsequenced.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x5F
<i>MatchingUnit</i>	5	1	Binary	Always 0.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>ClOrdID</i>	10	20	Text	Echoed back from the original request.
<i>Symbol</i>	30	8	Alphanumeric	Corresponds to <i>Symbol</i> (55) in Cboe FIX. Entire Cboe format symbol or OSI symbol if using long format.
<i>PutOrCall</i>	38	1	Alphanumeric	Corresponds to <i>PutOrCall</i> (201) in Cboe FIX. 0 = Put 1 = Call NULL (0x00) filled if using Cboe format symbol.
<i>StrikePrice</i>	39	8	Binary Price	Corresponds to <i>StrikePrice</i> (202) in Cboe FIX. Strike Price for option, 0 – 999,999.99 NULL (0x00) filled if using Cboe format symbol.
<i>MaturityDate</i>	47	4	Date	Corresponds to <i>MaturityMonth</i> (200) and <i>MaturityDay</i> (205) in Cboe FIX. NULL (0x00) filled if using Cboe format symbol.
<i>MultilegReportingType</i>	51	1	Alphanumeric	Echoed back from the original request.
<i>ComboOrder</i>	52	1	Alpha	Echoed back from the original request.
<i>Account</i>	53	16	Text	Echoed back from the original request.
<i>ClearingOptionalData</i>	69	16	Text	Echoed back from the original request.
<i>ClearingAccount</i>	85	4	Text	Echoed back from the original request..
<i>CMTANumber</i>	89	4	Binary	Echoed back from the original request.
<i>FloorTraderAcronym</i>	93	3	Alpha	Echoed back from the original request.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>Side</i>	96	1	Alphanumeric	Echoed back from the original request.
<i>OrderQty</i>	97	4	Binary	Echoed back from the original request.
<i>Price</i>	101	8	Binary Price	Echoed back from the original request.
<i>TransactionTime</i>	109	8	DateTime	Echoed back from the original request.
<i>OpenClose</i>	117	1	Alphanumeric	Echoed back from the original request.
<i>TradeTime</i>	118	8	DateTime	Echoed back from the original request.
<i>ContraTrader</i>	126	4	Alphanumeric	Echoed back from the original request.
<i>Reserved</i>	130	16	Reserved	Reserved
<i>RejectText</i>	146	60	Text	Human readable text with more information about the reject reason.

Example Add Floor Trade Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	CC 00	204 bytes
<i>MessageType</i>	5F	Add Floor Trade Rejected
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>Symbol</i>	30 30 36 69 70 41 00 00	006ipA
<i>PutorCall</i>	00	
<i>StrikePrice</i>	00 00 00 00 00 00 00 00	
<i>MaturityDate</i>	00 00 00 00	
<i>MultilegReportingType</i>	31	1 = Single leg instrument
<i>ComboOrder</i>	4E	N = No
<i>Account</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	
<i>ClearingOptionalData</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	
<i>ClearingAccount</i>	41 42 43 00	ABC
<i>CMTANumber</i>	00 00 00 00	
<i>FloorTraderAcronym</i>	41 41 41	AAA
<i>Side</i>	31	1 = Buy
<i>OrderQty</i>	64 00 00 00	100 contracts
<i>Price</i>	C8 32 00 00 00 00 00 00	1.30
<i>TransactionTime</i>	00 5C DB E2 27 12 B4 15	1,563,894,933,123,456,000
<i>OpenClose</i>	4F	O = Open
<i>TradeTime</i>	68 23 4A 8B 27 12 B4 15	1,563,894,931,654,321,000
<i>ContraTrader</i>	57 58 59	WXY
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	Reserved
<i>RejectText</i>	41 3A 20 46 6C 6F 6F 72 54 72 61 64 65 72 41 63 72 6F 6E 79 6D 3D 41 41 41 20 64 6F 65 73 20 6E 6F 74 20 68 61 76 65 20 61 20 66 6C 6F 6F 72 20 70 65 72 6D 69 74 00 00 00 00 00 00	A:FloorTraderAcronym=AAA does not have a floor permit

4.2.25 Floor Trade Confirmation Rejected (C1 Only)

The Floor Trade Confirmation Rejected message is used to indicate that a requested Floor Trade Confirmation has been rejected. Floor Trade Confirmation Rejected messages are unsequenced.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x5E
<i>MatchingUnit</i>	5	1	Binary	Always 0.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>ClOrd</i>	10	20	Text	Echoed back from the original request.
<i>ExecID</i>	30	8	Binary	Echoed back from the original request.
<i>Symbol</i>	38	8	Alphanumeric	Corresponds to <i>Symbol</i> (55) in Cboe FIX. Entire Cboe format symbol or OSI symbol if using long format.
<i>PutOrCall</i>	46	1	Alphanumeric	Corresponds to <i>PutOrCall</i> (201) in Cboe FIX. 0 = Put 1 = Call NULL (0x00) filled if using Cboe format symbol.
<i>StrikePrice</i>	47	8	Binary Price	Corresponds to <i>StrikePrice</i> (202) in Cboe FIX. Strike Price for option, 0 – 999,999.99 NULL (0x00) filled if using Cboe format symbol.
<i>MaturityDate</i>	55	4	Date	Corresponds to <i>MaturityMonth</i> (200) and <i>MaturityDay</i> (205) in Cboe FIX. NULL (0x00) filled if using Cboe format symbol.
<i>TransactionTime</i>	59	8	DateTime	Echoed back from the original request.
<i>PriceType</i>	67	1	Alphanumeric	Corresponds to <i>PriceType</i> (423) in Cboe FIX. 1 = Percentage, when trading FLEX percentage instruments* 2 = (Default) Price per unit (contract) * Percentage pricing for FLEX orders is only available for index products.
<i>Reserved</i>	68	15	Reserved	Reserved
<i>RejectText</i>	83	60	Text	Human readable text with more information about the reject reason.

Example Floor Trade Confirmation Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	8D 00	141 bytes
<i>MessageType</i>	5E	Floor Trade Confirmation Rejected
<i>MatchingUnit</i>	00	Always 0 for inbound messages
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00	ABC123
	00 00 00 00 00 00 00 00 00 00	
<i>ExecID</i>	00 00 00 00 00 00 00 00 00	
<i>Symbol</i>	30 30 36 69 70 41 00 00	006ipA
<i>PutOrCall</i>	00	
<i>StrikePrice</i>	00 00 00 00 00 00 00 00 00	
<i>MaturityDate</i>	00 00 00 00	
<i>TransactionTime</i>	68 23 4A 8B 27 12 B4 15	1,563,894,931,654,321,000
<i>PriceType</i>	02	2 = Price per unit
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00	Reserved
	00 00 00 00 00	
<i>RejectText</i>	41 3A 20 45 78 65 63 49 64 3A	A: ExecId: ExecutionId empty
	20 45 78 65 63 75 74 69 6F 6E	
	49 64 20 65 6D 70 74 79 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	
	00 00 00 00 00 00 00 00 00 00	

4.2.26 Delete Floor Trade Rejected (C1 Only)

The Delete Floor Trade Rejected message is used to indicate that a requested Delete Floor Trade has been rejected. Delete Floor Trade Rejected messages are unsequenced.

Field	Offset	Length	Data Type	Description
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.
<i>MessageType</i>	4	1	Binary	0x60
<i>MatchingUnit</i>	5	1	Binary	Always 0.
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.
<i>ClOrdID</i>	10	20	Text	Echoed back from the original request.
<i>ExecID</i>	30	8	Binary	Echoed back from the original request.
<i>Symbol</i>	38	8	Alphanumeric	Corresponds to <i>Symbol</i> (55) in Cboe FIX. Entire Cboe format symbol or OSI symbol if using long format.
<i>PutOrCall</i>	46	1	Alphanumeric	Corresponds to <i>PutOrCall</i> (201) in Cboe FIX. 0 = Put 1 = Call NULL (0x00) filled if using Cboe format symbol.
<i>StrikePrice</i>	47	8	Binary Price	Corresponds to <i>StrikePrice</i> (202) in Cboe FIX. Strike Price for option, 0 – 999,999.99 NULL (0x00) filled if using Cboe format symbol.
<i>MaturityDate</i>	55	4	Date	Corresponds to <i>MaturityMonth</i> (200) and <i>MaturityDay</i> (205) in Cboe FIX. NULL (0x00) filled if using Cboe format symbol.
<i>Side</i>	59	1	Alphanumeric	Echoed back from the original request.
<i>Reserved</i>	60	16	Reserved	Reserved

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>RejectText</i>	76	60	Text	Human readable text with more information about the reject reason.
-------------------	----	----	------	--

Example Delete Floor Trade Rejected Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	86 00	134 bytes
<i>MessageType</i>	60	Delete Floor Trade Rejected
<i>MatchingUnit</i>	00	Always 0
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00	ABC123
<i>ExecID</i>	01 F0 B7 D9 71 21 00 00	D19800001 (base 36)
<i>Symbol</i>	30 30 36 69 70 41 00 00	006ipA
<i>PutorCall</i>	00	
<i>StrikePrice</i>	00 00 00 00 00 00 00 00	
<i>MaturityDate</i>	00 00 00 00	
<i>Side</i>	31	1=Buy
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	Reserved
<i>RejectText</i>	55 6E 6B 6E 6F 77 6E 20 73 79 6D 62 6F 6C 00	Unknown symbol

4.2.27 Delete Floor Trade Acknowledgement (C1 Only)

A Delete Floor Trade Acknowledgment is an unsequenced message sent when a Delete Floor Trade message requesting has completed.

Field	Offset	Length	Data Type	Description								
<i>StartOfMessage</i>	0	2	Binary	Must be 0xBA 0xBA.								
<i>MessageLength</i>	2	2	Binary	Number of bytes for the message, including this field but not including the two bytes for the <i>StartOfMessage</i> field.								
<i>MessageType</i>	4	1	Binary	0x61								
<i>MatchingUnit</i>	5	1	Binary	Always 0 for inbound (Member to Cboe) messages.								
<i>SequenceNumber</i>	6	4	Binary	The sequence number for this message.								
<i>ClOrdID</i>	10	20	Text	Echoed back from the original request.								
<i>ExecID</i>	30	8	Binary	<p>Corresponds to <i>ExecID</i> (17) in Cboe FIX.</p> <p>Execution ID. Unique across all matching units on a given day. Note: <i>ExecIDs</i> will be represented on ODROP and FIXDROP ports as nine character, base 36 ASCII. Leading zeros should be added if the converted base 36 value is shorter than nine characters.</p> <p>Example conversion:</p> <table><tr><th>Decimal</th><th>Base 36</th></tr><tr><td>28294005440239</td><td>A1234B567</td></tr><tr><td>76335905726621</td><td>R248BC23H</td></tr><tr><td>728557228187</td><td>09AP05V2Z</td></tr></table>	Decimal	Base 36	28294005440239	A1234B567	76335905726621	R248BC23H	728557228187	09AP05V2Z
Decimal	Base 36											
28294005440239	A1234B567											
76335905726621	R248BC23H											
728557228187	09AP05V2Z											
<i>Reserved</i>	68	16	Reserved	Reserved								

Example Delete Floor Trade Acknowledgement Message:

Field Name	Hexadecimal	Notes
<i>StartOfMessage</i>	BA BA	Start of message bytes.
<i>MessageLength</i>	24 00	82 bytes
<i>MessageType</i>	61	Delete Floor Trade Acknowledgement
<i>MatchingUnit</i>	00	Always 0
<i>SequenceNumber</i>	64 00 00 00	Sequence number 100
<i>ClOrdID</i>	41 42 43 31 32 33 00 00 00 00 00 00 00 00 00 00 00 00 00 00	ABC123
<i>ExecID</i>	01 F0 B7 D9 71 21 00 00	D19800001 (base 36)
<i>Reserved</i>	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	Reserved

5 Input Bitfields Per Message

Legend:

- R** Indicates that the field must be specified for a message
- Indicates that the field can be specified for a message
- Indicates that the field cannot be requested for a message
- (Blank) Indicates that the field is not used by Cboe Options and cannot be specified for a message

Input messages that containing invalid fields (i.e., Blank) will be rejected. In the case of rejected input messages, the associated `Reject` message sent back to the customer will contain a 'RejectReason' code non-optional field (See **Order Reason Codes**) and a 'Text' non-optional field containing descriptive text.

5.1 New Order

Byte	Bit	Field	
1	1	ClearingFirm	•
	2	ClearingAccount	•
	4	Price	•
	8	ExecInst	•
	16	OrdType	•
	32	TimeInForce	•
	64	MinQty	•
	128	MaxFloor	•
2	1	Symbol	R
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	R
	128	RoutingInst	•
3	1	Account	•
	2	DisplayIndicator	•
	4	MaxRemovePct	•
	8	DiscretionAmount	
	16	PegDifference	
	32	PreventMatch	•
	64	LocateReqd	
	128	ExpireTime	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	RiskReset	•
	16	OpenClose	•
	32	CMTANumber	•
	64	TargetPartyID	•
	128	(Reserved)	
5	1	SessionEligibility	•
	2	AttributedQuote	•
	4	BookingType	
	8	ExtExecInst	
	16	ClientID	
	32	InvestorID	
	64	ExecutorID	
	128	OrderOrigination	

Byte	Bit	Field	
6	1	DisplayRange	•
	2	StopPx	•
	4	RoutStrategy	•
	8	RouteDeliveryMethod	•
	16	ExDestination	•
	32	EchoText	•
	64	AuctionId	•
	128	RoutingFirmID	•
7	1	AlgorithmicIndicator	
	2	CustomGroupID	•
	4	ClientQualifiedRole	
	8	InvestorQualifiedRole	
	16	ExecutorQualifiedRole	
	32	CtiCode	
	64	ManualOrderIndicator	
	128	OperatorId	
8	1	(Reserved)	
	2	(Reserved)	
	4	ClearingOptionalData	•
	8	ClientIDAttr	•
	16	FrequentTraderID	•
	32	Compression	•
	64	FloorDestination	•
	128	FloorRoutingInst	•
9	1	OrderOrigin	•
	2	ORS	•
	4	PriceType	•
	8	(Reserved)	
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

5.2 New Order Cross (C1 and EDGX Only)

Byte	Bit	Field	
1	1	Symbol	R
	2	MaturityDate	•
	4	StrikePrice	•
	8	PutOrCall	•
	16	ExecInst	•
	32	AttributedQuote	•
	64	TargetPartyID	•
	128	PreventMatch	•
2	1	AutoMatch	•
	2	AutoMatchPrice	•
	4	LastPriority	•
	8	Account	•
	16	CMTANumber	•
	32	ClearingAccount	•
	64	RoutingFirmID	•
	128	ClearingOptionalData	•

Byte	Bit	Field	
3	1	ClientIDAttr	•
	2	EquityTradePrice	•
	4	EquityTradeSize	•
	8	EquityTradeVenue	•
	16	EquityTransactTime	•
	32	EquityBuyClearingFirm	•
	64	EquitySellClearingFirm	•
	128	SessionEligibility	•
4	1	Compression	•
	2	ORS	•
	4	FrequentTraderID	•
	8	(Reserved)	
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

5.3 New Complex Order (C1, C2 and EDGX Only)

Byte	Bit	Field	
1	1	ClearingFirm	•
	2	ClearingAccount	•
	4	Price	•
	8	OrdType	•
	16	TimeInForce	•
	32	Symbol	•
	64	Capacity	•
	128	RoutingInst	•
2	1	Account	•
	2	PreventMatch	•
	4	ExpireTime	•
	8	CMTANumber	•
	16	TargetPartyID	•
	32	AttributedQuote	•
	64	EchoText	•
	128	AuctionId	•
3	1	RoutingFirmID	•
	2	DrillThruProtection	•
	4	RiskReset	•
	8	CustomGroupID	•
	16	LegSide	
	32	EquityPartyID	•
	64	(Reserved)	
	128	ClearingOptionalData	•

Byte	Bit	Field	
4	1	ClientIDAttr	•
	2	FrequentTraderID	•
	4	SessionEligibility	•
	8	MaxFloor	•
	16	DisplayRange	•
	32	ComboOrder	•
	64	Compression	•
	128	EquityExDestination	•
5	1	EquityLegShortSell	•
	2	FloorDestination	•
	4	FloorRoutingInst	•
	8	MultiClassSprd	•
	16	OrderOrigin	•
	32	ORS	•
	64	PriceType	•
	128	StrategyID	•
6	1	(Reserved)	
	2	ExecInst	•
	4	TiedHedge	•
	8	(Reserved)	
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

5.4 New Order Cross Multileg (C1 and EDGX Only)

Byte	Bit	Field	
1	1	Symbol	R
	2	(Reserved)	
	4	(Reserved)	
	8	(Reserved)	
	16	ExecInst	•
	32	AttributedQuote	•
	64	TargetPartyID	•
	128	PreventMatch	•
2	1	AutoMatch	•
	2	AutoMatchPrice	•
	4	LastPriority	•
	8	Account	•
	16	CMTANumber	•
	32	ClearingAccount	•
	64	RoutingFirmID	•
	128	ClearingOptionalData	•
3	1	ClientIDAttr	•
	2	EquityTradePrice	•
	4	EquityTradeSize	•
	8	EquityTradeVenue	•
	16	EquityTransactTime	•
	32	EquityBuyClearingFirm	•
	64	EquitySellClearingFirm	•
	128	SessionEligibility	•
Byte	Bit	Field	
4	1	EquityPartyId	•
	2	EquityLegShortSell	•
	4	Reserved	
	8	Reserved	
	16	DrillThruProtection	•
	32	PriceType	
	64	EquityExDestination	•
	128	Compression	•
5	1	ORS	•
	2	FrequentTraderID	•
	4	(Reserved)	
	8	(Reserved)	
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

5.5 Cancel Order

Byte	Bit	Field	
1	1	ClearingFirm	•
	2	MassCancelLockout	•
	4	MassCancel	•
	8	RiskRoot	•
	16	MassCancelID	•
	32	RoutingFirmID	•
	64	ManualOrderIndicator	
	128	OperatorID	
2	1	MassCancelInst	•
	2	(Reserved)	
	4	(Reserved)	
	8	(Reserved)	
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

ClearingFirm is required for service bureau ports.

5.6 Modify Order

Byte	Bit	Field	
1	1	ClearingFirm	•
	2	(Reserved)	
	4	OrderQty	R
	8	Price	R
	16	OrdType	•
	32	CancelOrigOnReject	•
	64	ExecInst	•
	128	Side	–
2	1	MaxFloor	•
	2	StopPx	•
	4	RoutingFirmID	•
	8	ManualOrderIndicator	
	16	OperatorId	
	32	FrequentTraderID	•
	64	(Reserved)	
	128	(Reserved)	

(R) Both *OrderQty* and *Price* must be present on all *Modify Order* requests. Messages sent without both fields will be rejected.

ClearingFirm is required for service bureau ports.

5.7 Purge Orders

Byte	Bit	Field	
1	1	ClearingFirm	•
	2	MassCancelLockout	•
	4	MassCancelInst	•
	8	RiskRoot	•
	16	MassCancelID	•
	32	RoutingFirmID	•
	64	ManualOrderIndicator	
	128	OperatorId	
2	1	Symbol	
	2	SymbolSfx	
	4	(Reserved)	
	8	(Reserved)	
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

ClearingFirm is required for service bureau ports.

5.8 New Complex Instrument (**C1, C2, and EDGX Only**)

Byte	Bit	Field	
1	1	<i>LegCFIcode</i>	•
	2	<i>LegMaturityDate</i>	•
	4	<i>LegStrikePrice</i>	•
	8	<i>ClearingFirm</i>	•
	16	<i>(Reserved)</i>	
	32	<i>(Reserved)</i>	
	64	<i>(Reserved)</i>	
	128	<i>(Reserved)</i>	

6 Return Bitfields Per Message

Legend:

- R** Indicates that the field must be specified for a message
- Indicates that the field can be specified for a message
- Indicates that the field cannot be requested for a message
- (Blank) Indicates that the field is not used by Cboe Options and cannot be specified for a message

Input messages that containing invalid fields (i.e., Blank) will be rejected. In the case of rejected input messages, the associated `Reject` message sent back to the customer will contain a 'RejectReason' code non-optional field (See **Order Reason Codes**) and a 'Text' non-optional field containing descriptive text.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

6.1 Order Acknowledgment

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	•
	32	TimeInForce	•
	64	MinQty	•
	128	MaxRemovePct	•
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	–
3	1	Account	•
	2	ClearingFirm	•
	4	ClearingAccount	•
	8	DisplayIndicator	•
	16	MaxFloor	•
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	ClOrdIdBatch	
	32	CorrectedSize	•
	64	PartyID	
	128	AccessFee	
5	1	OrigClOrdID	•
	2	LeavesQty	•
	4	LastShares	•
	8	LastPx	•
	16	DisplayPrice	•
	32	WorkingPrice	•
	64	BaseLiquidityIndicator	•
	128	ExpireTime	•
6	1	SecondaryOrderID	•
	2	CCP	
	4	ContraCapacity	•
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	•
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	•
	4	StopPx	•
	8	RoutingInst	•
	16	RouteStrategy	•
	32	RouteDeliveryMethod	•
	64	ExDestination	•
	128	TradeReportRefID	
9	1	MarketingFeeCode	•
	2	TargetPartyID	•
	4	AuctionId	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossId	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorId	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	•

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	•
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomId	
	16	SecondaryExecId	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyId	•
	4	(Reserved)	
	8	MassCancelId	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	•
16	1	FrequentTraderID	•
	2	SessionEligibility	•
	4	ComboOrder	•
	8	Compression	•
	16	FloorDestination	•
	32	FloorRoutingInst	•
	64	MultiClassSprd	•
	128	OrderOrigin	•
17	1	PriceType	•
	2	StrategyID	•
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.2 Cross Order Acknowledgment (C1 and EDGX only)

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	–
	32	TimeInForce	–
	64	MinQty	–
	128	MaxRemovePct	–
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	–
3	1	Account	•
	2	ClearingFirm	–
	4	ClearingAccount	•
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	ClOrdIdBatch	
	32	CorrectedSize	–
	64	PartyID	
	128	AccessFee	
5	1	OrigClOrdId	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	–
	4	StopPx	–
	8	RoutingInst	–
	16	RouteStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	–
	2	TargetPartyID	•
	4	AuctionID	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	•
	128	CrossPrioritization	•
10	1	CrossId	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	–
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorId	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	•

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomId	
	16	SecondaryExecId	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyId	•
	4	(Reserved)	
	8	MassCancelId	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	•
16	1	FrequentTraderID	•
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	•
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.3 Order Rejected

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	•
	32	TimeInForce	•
	64	MinQty	•
	128	MaxRemovePct	•
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	–
3	1	Account	•
	2	ClearingFirm	•
	4	ClearingAccount	•
	8	DisplayIndicator	•
	16	MaxFloor	•
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	CIOrdIdBatch	
	32	CorrectedSize	•
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	•
	2	CCP	
	4	ContraCapacity	•
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	•
	4	StopPx	•
	8	RoutingInst	•
	16	RoutStrategy	•
	32	RouteDeliveryMethod	•
	64	ExDestination	•
	128	TradeReportRefID	
9	1	MarketingFeeCode	•
	2	TargetPartyID	•
	4	AuctionID	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossID	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorID	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomID	
	16	SecondaryExecID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyID	•
	4	(Reserved)	
	8	MassCancelID	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	•
16	1	FrequentTraderID	•
	2	SessionEligibility	•
	4	ComboOrder	•
	8	Compression	•
	16	FloorDestination	•
	32	FloorRoutingInst	•
	64	MultiClassSprd	•
	128	OrderOrigin	•
17	1	PriceType	•
	2	StrategyID	•
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.4 Cross Order Rejected (C1 and EDGX Only)

Byte	Bit	Field	
1	1	Side	–
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	–
	32	TimeInForce	–
	64	MinQty	–
	128	MaxRemovePct	–
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	–
	128	ContraTrader	–
3	1	Account	–
	2	ClearingFirm	–
	4	ClearingAccount	–
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	–
	16	ClOrdIdBatch	
	32	CorrectedSize	–
	64	PartyID	
	128	AccessFee	
5	1	OrigClOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	–
	4	StopPx	–
	8	RoutingInst	–
	16	RouteStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	–
	2	TargetPartyID	•
	4	AuctionID	–
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	–
	64	CrossType	•
	128	CrossPrioritization	•
10	1	CrossID	•
	2	AllocQty	–
	4	GiveUpFirmID	–
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	–
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorID	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomID	
	16	SecondaryExecID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyID	•
	4	(Reserved)	
	8	MassCancelID	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	•
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	•
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.5 Order Modified

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	•
	32	TimeInForce	•
	64	MinQty	•
	128	MaxRemovePct	•
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	–
	128	ContraTrader	–
3	1	Account	•
	2	ClearingFirm	•
	4	ClearingAccount	•
	8	DisplayIndicator	•
	16	MaxFloor	•
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	–
	2	StrikePrice	–
	4	PutOrCall	–
	8	OpenClose	–
	16	ClOrdIdBatch	
	32	CorrectedSize	–
	64	PartyID	
	128	AccessFee	
5	1	OrigClOrdID	•
	2	LeavesQty	•
	4	LastShares	•
	8	LastPx	•
	16	DisplayPrice	•
	32	WorkingPrice	•
	64	BaseLiquidityIndicator	•
	128	ExpireTime	•
6	1	SecondaryOrderID	•
	2	CCP	
	4	ContraCapacity	•
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	•
	4	StopPx	•
	8	RoutingInst	•
	16	RoutStrategy	•
	32	RouteDeliveryMethod	•
	64	ExDestination	•
	128	TradeReportRefID	
9	1	MarketingFeeCode	•
	2	TargetPartyID	•
	4	AuctionID	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossID	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorID	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomID	
	16	SecondaryExecID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyID	–
	4	(Reserved)	
	8	MassCancelID	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	•
	2	SessionEligibility	–
	4	ComboOrder	•
	8	Compression	•
	16	FloorDestination	•
	32	FloorRoutingInst	•
	64	MultiClassSprd	•
	128	OrderOrigin	•
17	1	PriceType	•
	2	StrategyID	•
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

6.6 Order Restated

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	•
	32	TimelnForce	•
	64	MinQty	•
	128	MaxRemovePct	•
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	–
3	1	Account	•
	2	ClearingFirm	•
	4	ClearingAccount	•
	8	DisplayIndicator	•
	16	MaxFloor	•
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	CIOrdIdBatch	
	32	CorrectedSize	•
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	•
	2	LeavesQty	•
	4	LastShares	•
	8	LastPx	•
	16	DisplayPrice	•
	32	WorkingPrice	•
	64	BaseLiquidityIndicator	•
	128	ExpireTime	•
6	1	SecondaryOrderID	•
	2	CCP	
	4	ContraCapacity	•
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	•
	4	StopPx	•
	8	RoutingInst	•
	16	RoutStrategy	•
	32	RouteDeliveryMethod	•
	64	ExDestination	•
	128	TradeReportRefID	
9	1	MarketingFeeCode	•
	2	TargetPartyID	•
	4	AuctionId	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossId	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorId	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomId	
	16	SecondaryExecId	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyId	–
	4	(Reserved)	
	8	MassCancelId	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	•
16	1	FrequentTraderID	•
	2	SessionEligibility	–
	4	ComboOrder	•
	8	Compression	•
	16	FloorDestination	•
	32	FloorRoutingInst	•
	64	MultiClassSprd	•
	128	OrderOrigin	•
17	1	PriceType	•
	2	StrategyID	•
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

6.7 User Modify Rejected

Byte	Bit	Field	
1	1	Side	–
	2	PegDifference	
	4	Price	–
	8	ExecInst	–
	16	OrdType	–
	32	TimeInForce	–
	64	MinQty	–
	128	MaxRemovePct	–
2	1	Symbol	–
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	–
	128	ContraTrader	–
3	1	Account	–
	2	ClearingFirm	–
	4	ClearingAccount	–
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	–
	128	PreventMatch	–
4	1	MaturityDate	–
	2	StrikePrice	–
	4	PutOrCall	–
	8	OpenClose	–
	16	CIOrdIdBatch	
	32	CorrectedSize	–
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	–
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	–
	4	StopPx	–
	8	RoutingInst	–
	16	RoutStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	–
	2	TargetPartyID	–
	4	AuctionID	–
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	–
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossId	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorId	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomId	
	16	SecondaryExecId	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyId	–
	4	(Reserved)	
	8	MassCancelId	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	–
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	–
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	–
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.8 Order Cancelled

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	•
	32	TimeInForce	•
	64	MinQty	•
	128	MaxRemovePct	•
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	–
3	1	Account	•
	2	ClearingFirm	•
	4	ClearingAccount	•
	8	DisplayIndicator	•
	16	MaxFloor	•
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	ClOrdIdBatch	
	32	CorrectedSize	•
	64	PartyID	
	128	AccessFee	
5	1	OrigClOrdID	•
	2	LeavesQty	•
	4	LastShares	•
	8	LastPx	•
	16	DisplayPrice	•
	32	WorkingPrice	•
	64	BaseLiquidityIndicator	•
	128	ExpireTime	•
6	1	SecondaryOrderID	•
	2	CCP	
	4	ContraCapacity	•
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	•
	4	StopPx	•
	8	RoutingInst	•
	16	RoutStrategy	•
	32	RouteDeliveryMethod	•
	64	ExDestination	•
	128	TradeReportRefID	
9	1	MarketingFeeCode	•
	2	TargetPartyID	•
	4	AuctionID	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossID	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorID	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFICode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomID	
	16	SecondaryExecID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyID	•
	4	(Reserved)	
	8	MassCancelID	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	•
	2	SessionEligibility	–
	4	ComboOrder	•
	8	Compression	•
	16	FloorDestination	•
	32	FloorRoutingInst	•
	64	MultiClassSprd	•
	128	OrderOrigin	•
17	1	PriceType	•
	2	StrategyID	•
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.9 Cross Order Cancelled (C1 and EDGX Only)

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	–
	32	TimelnForce	–
	64	MinQty	–
	128	MaxRemovePct	–
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	–
3	1	Account	•
	2	ClearingFirm	•
	4	ClearingAccount	–
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	CIOrdIdBatch	
	32	CorrectedSize	–
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	–
	4	StopPx	–
	8	RoutingInst	–
	16	RoutStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	–
	2	TargetPartyID	•
	4	AuctionId	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	•
	128	CrossPrioritization	•
10	1	CrossId	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	–
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorId	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomId	
	16	SecondaryExecId	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyId	•
	4	(Reserved)	
	8	MassCancelId	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	•
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	•
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.10 Cancel Rejected

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	•
	32	TimeInForce	•
	64	MinQty	•
	128	MaxRemovePct	•
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	–
3	1	Account	–
	2	ClearingFirm	–
	4	ClearingAccount	–
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	–
	128	PreventMatch	–
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	CIOrdIdBatch	
	32	CorrectedSize	•
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	–
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	•
	4	StopPx	•
	8	RoutingInst	–
	16	RoutStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	•
	2	TargetPartyID	•
	4	AuctionID	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossID	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorID	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomID	
	16	SecondaryExecID	–
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
15	1	(Reserved)	
	2	EquityPartyID	–
	4	(Reserved)	
	8	MassCancelID	•
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	–
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	–
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	–
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.11 Order Execution

Byte	Bit	Field	
1	1	Side	•
	2	PegDifference	
	4	Price	•
	8	ExecInst	•
	16	OrdType	•
	32	TimeInForce	•
	64	MinQty	•
	128	MaxRemovePct	•
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	•
3	1	Account	•
	2	ClearingFirm	•
	4	ClearingAccount	•
	8	DisplayIndicator	•
	16	MaxFloor	•
	32	DiscretionAmount	
	64	OrderQty	•
	128	PreventMatch	•
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	ClOrdIdBatch	
	32	CorrectedSize	•
	64	PartyID	
	128	AccessFee	
5	1	OrigClOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	•
	8	AttributedQuote	•
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	•
	2	EchoText	•
	4	StopPx	•
	8	RoutingInst	•
	16	RoutStrategy	•
	32	RouteDeliveryMethod	•
	64	ExDestination	•
	128	TradeReportRefID	
9	1	MarketingFeeCode	•
	2	TargetPartyID	•
	4	AuctionID	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	•
	128	CrossPrioritization	•
10	1	CrossID	•
	2	AllocQty	•
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorID	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	•

Byte	Bit	Field	
13	1	CumQty	•
	2	DayOrderQty	•
	4	DayCumQty	•
	8	AvgPx	•
	16	DayAvgPx	•
	32	PendingStatus	
	64	DrillThruProtection	•
	128	MultilegReportingType	•
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomID	
	16	SecondaryExecID	•
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyID	•
	4	(Reserved)	
	8	MassCancelID	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	•
16	1	FrequentTraderID	•
	2	SessionEligibility	–
	4	ComboOrder	•
	8	Compression	•
	16	FloorDestination	•
	32	FloorRoutingInst	•
	64	MultiClassSprd	•
	128	OrderOrigin	•
17	1	PriceType	•
	2	StrategyID	•
	4	(Reserved)	
	8	TradeThroughAlertType	•
	16	SenderLocationID	•
	32	FloorTraderAcronym	•
	64	(Reserved)	
	128	(Reserved)	

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

6.12 Trade Cancel or Correct

Byte	Bit	Field	
1	1	Side	–
	2	PegDifference	
	4	Price	–
	8	ExecInst	–
	16	OrdType	–
	32	TimeInForce	–
	64	MinQty	–
	128	MaxRemovePct	–
2	1	Symbol	•
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	•
	128	ContraTrader	–
3	1	Account	–
	2	ClearingFirm	–
	4	ClearingAccount	–
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	–
	128	PreventMatch	–
4	1	MaturityDate	•
	2	StrikePrice	•
	4	PutOrCall	•
	8	OpenClose	•
	16	CIOrdIdBatch	
	32	CorrectedSize	•
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	–
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	•
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	–
	4	StopPx	–
	8	RoutingInst	–
	16	RoutStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	•
	2	TargetPartyID	•
	4	AuctionID	•
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	•
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossID	•
	2	AllocQty	–
	4	GiveUpFirmID	•
	8	RoutingFirmID	•
	16	WaiverType	
	32	CrossExclusionIndicator	•
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorID	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFICode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomID	
	16	SecondaryExecID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyID	–
	4	(Reserved)	
	8	MassCancelID	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	–
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	–
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	–
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.13 Purge Rejected

Byte	Bit	Field	
1	1	Side	–
	2	PegDifference	
	4	Price	–
	8	ExecInst	–
	16	OrdType	–
	32	TimeInForce	–
	64	MinQty	–
	128	MaxRemovePct	–
2	1	Symbol	–
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	–
	128	ContraTrader	–
3	1	Account	–
	2	ClearingFirm	–
	4	ClearingAccount	–
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	–
	128	PreventMatch	–
4	1	MaturityDate	–
	2	StrikePrice	–
	4	PutOrCall	–
	8	OpenClose	–
	16	CIOrdIdBatch	
	32	CorrectedSize	–
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	–
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	–
	4	StopPx	–
	8	RoutingInst	–
	16	RoutStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	–
	2	TargetPartyID	–
	4	AuctionID	–
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	–
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossID	–
	2	AllocQty	–
	4	GiveUpFirmID	–
	8	RoutingFirmID	–
	16	WaiverType	
	32	CrossExclusionIndicator	–
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorID	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFICode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomID	
	16	SecondaryExecID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyID	–
	4	(Reserved)	
	8	MassCancelID	●
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	–
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	–
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	–
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.14 Complex Instrument Accepted (C1, C2 and EDGX Only)

Byte	Bit	Field	
1	1	Side	–
	2	PegDifference	
	4	Price	–
	8	ExecInst	–
	16	OrdType	–
	32	TimelnForce	–
	64	MinQty	–
	128	MaxRemovePct	–
2	1	Symbol	–
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	–
	128	ContraTrader	–
3	1	Account	–
	2	ClearingFirm	–
	4	ClearingAccount	–
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	–
	128	PreventMatch	–
4	1	MaturityDate	–
	2	StrikePrice	–
	4	PutOrCall	–
	8	OpenClose	–
	16	CIOrdIdBatch	
	32	CorrectedSize	–
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	–
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	–
	4	StopPx	–
	8	RoutingInst	–
	16	RoutStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	–
	2	TargetPartyID	–
	4	AuctionID	–
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	–
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossId	–
	2	AllocQty	–
	4	GiveUpFirmID	–
	8	RoutingFirmID	–
	16	WaiverType	
	32	CrossExclusionIndicator	–
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorId	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	•
	2	LegMaturityDate	•
	4	LegStrikePrice	•
	8	RoomId	
	16	SecondaryExecId	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyId	–
	4	(Reserved)	
	8	MassCancelId	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	–
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	–
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	–
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

6.15 Complex Instrument Rejected (C1, C2 and EDGX Only)

Byte	Bit	Field	
1	1	Side	–
	2	PegDifference	
	4	Price	–
	8	ExecInst	–
	16	OrdType	–
	32	TimelnForce	–
	64	MinQty	–
	128	MaxRemovePct	–
2	1	Symbol	–
	2	SymbolSfx	
	4	Currency	
	8	IdSource	
	16	SecurityId	
	32	SecurityExchange	
	64	Capacity	–
	128	ContraTrader	–
3	1	Account	–
	2	ClearingFirm	–
	4	ClearingAccount	–
	8	DisplayIndicator	–
	16	MaxFloor	–
	32	DiscretionAmount	
	64	OrderQty	–
	128	PreventMatch	–
4	1	MaturityDate	–
	2	StrikePrice	–
	4	PutOrCall	–
	8	OpenClose	–
	16	CIOrdIdBatch	
	32	CorrectedSize	–
	64	PartyID	
	128	AccessFee	
5	1	OrigCIOrdID	–
	2	LeavesQty	–
	4	LastShares	–
	8	LastPx	–
	16	DisplayPrice	–
	32	WorkingPrice	–
	64	BaseLiquidityIndicator	–
	128	ExpireTime	–
6	1	SecondaryOrderID	–
	2	CCP	
	4	ContraCapacity	–
	8	AttributedQuote	–
	16	ExtExecInst	
	32	BulkOrderIds	
	64	BulkRejectReasons	
	128	PartyRole	

Byte	Bit	Field	
7	1	SubLiquidityIndicator	–
	2	TradeReportTypeReturn	
	4	TradePublishIndReturn	
	8	Text	
	16	Bid	
	32	Offer	
	64	LargeSize	
	128	LastMkt	
8	1	FeeCode	–
	2	EchoText	–
	4	StopPx	–
	8	RoutingInst	–
	16	RouteStrategy	–
	32	RouteDeliveryMethod	–
	64	ExDestination	–
	128	TradeReportRefID	
9	1	MarketingFeeCode	–
	2	TargetPartyID	–
	4	AuctionID	–
	8	OrderCategory	
	16	LiquidityProvision	
	32	CmtaNumber	–
	64	CrossType	–
	128	CrossPrioritization	–
10	1	CrossId	–
	2	AllocQty	–
	4	GiveUpFirmID	–
	8	RoutingFirmID	–
	16	WaiverType	
	32	CrossExclusionIndicator	–
	64	PriceFormation	
	128	ClientQualifiedRole	
11	1	ClientID	
	2	InvestorID	
	4	ExecutorID	
	8	OrderOrigination	
	16	Algo	
	32	DeferralReason	
	64	InvestorQualifiedRole	
	128	ExecutorQualifiedRole	
12	1	CtiCode	
	2	ManualOrderIndicator	
	4	OperatorId	
	8	TradeDate	
	16	ClearingPrice	
	32	ClearingSize	
	64	ClearingSymbol	
	128	ClearingOptionalData	–

Byte	Bit	Field	
13	1	CumQty	–
	2	DayOrderQty	–
	4	DayCumQty	–
	8	AvgPx	–
	16	DayAvgPx	–
	32	PendingStatus	
	64	DrillThruProtection	–
	128	MultilegReportingType	–
14	1	LegCFIcode	–
	2	LegMaturityDate	–
	4	LegStrikePrice	–
	8	RoomId	
	16	SecondaryExecId	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	
15	1	(Reserved)	
	2	EquityPartyId	–
	4	(Reserved)	
	8	MassCancelId	–
	16	(Reserved)	
	32	(Reserved)	
	64	(Reserved)	
	128	ClientIDAttr	–
16	1	FrequentTraderID	–
	2	SessionEligibility	–
	4	ComboOrder	–
	8	Compression	–
	16	FloorDestination	–
	32	FloorRoutingInst	–
	64	MultiClassSprd	–
	128	OrderOrigin	–
17	1	PriceType	–
	2	StrategyID	–
	4	(Reserved)	
	8	TradeThroughAlertType	–
	16	SenderLocationID	–
	32	(Reserved)	
	64	(Reserved)	
	128	(Reserved)	

7 List of Optional Fields

The following are descriptions of optional fields which may be sent or received.

Field	Length	Data Type	Description
<i>Account</i>	16	Text	<p>Corresponds to <i>Account</i> (1) in Cboe FIX.</p> <p>Reflected back on execution reports associated with this order and also passed through to the OCC in the Optional Data field (16 characters) and Customer ID field (max 10 characters). May be made available in the Member's clearing file. A maximum of 10 characters will be passed through to the OCC Customer ID Field but up to 16 characters will be maintain internally. Allowed characters are alphanumeric and colon.</p> <p><i>Account</i> (1) will only be mapped to the OCC via the Customer ID field (max 10 characters) and the new <i>ClearingOptionalData</i> (9324) field will be mapped to the OCC via the Optional Data field (16 characters).</p>
<i>AllocQty</i>	4	Binary	<p>Corresponds to <i>AllocQty</i> (80) in Cboe FIX.</p> <p>Number of contracts for this party.</p> <p>C1 and EDGX only.</p>
<i>AttributedQuote</i>	1	Alphanumeric	<p>Optional. Allows for an order to be attributed to a firm's Executing Broker ID in Cboe market data feeds. The order may also be included with attributed summary information displays related to quote/trade information on the Cboe website. Must opt-in to support through the Cboe Trade Desk.</p> <p>On a New Order Cross and New Order Cross Multileg this field is only applicable to the Agency order.</p> <p>N = Do not attribute firm Executing Broker ID to this order (Default)</p> <p>Y = Attribute firm Executing Broker ID to this order</p> <p>C = Attribute <i>ClientID</i> only.</p> <p>Z = Attribute both <i>ClearingFirm</i> (EFID) and <i>ClientID</i>.</p>
<i>AuctionId</i>	8	Binary	<p>Corresponds to <i>AuctionId</i> (9370) in Cboe FIX.</p> <p>Auction order identifier supplied by Cboe. This identifier corresponds to the identifiers used in Cboe market data products.</p> <p>C1, C2, and EDGX only.</p>
<i>AutoMatch</i>	1	Alphanumeric	<p>Corresponds to <i>AutoMatch</i> (9040) in Cboe FIX.</p> <p>Better-priced responses will be matched by the Contra side. Indicates the type of Auto Match the Contra Order will use. Mutually exclusive with <i>LastPriority</i>. Limit type Auto Match orders require <i>AutoMatchPrice</i> to be supplied.</p> <p>0 = Disabled (Default)</p> <p>1 = Market</p> <p>2 = Limit</p> <p>C1 and EDGX only.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>AutoMatchPrice</i>	8	Binary Price	<p>Corresponds to <i>AutoMatchPrice</i> (9044) in Cboe FIX.</p> <p>Sets the limit price at which the Contra Order will Auto Match. Required if <i>AutoMatch</i> = 2 (Limit). Ignored otherwise. Must be non-negative.</p> <p>1 = Buy 2 = Sell</p> <p>C1 and EDGX only.</p>
<i>AvgPx</i>	8	Binary Price	<p>Corresponds to <i>AvgPx</i> (6) in Cboe FIX.</p> <p>Average price of executions for this order weighted by trade size. Zero if <i>CumQty</i> field is zero or if <i>MultilegReportingType</i> = 2.</p>
<i>BaseLiquidityIndicator</i>	1	Alphanumeric	<p>Indicates whether the trade added or removed liquidity.</p> <p>A = Added Liquidity R = Removed Liquidity X = Routed to Another Market C = Auction/Uncrossing</p>
<i>CancelOrigOnReject</i>	1	Alpha	<p>Corresponds to <i>CancelOrigOnReject</i> (9619) in Cboe FIX.</p> <p>Indicates handling of original order on failure to modify.</p> <p>N = Leave original order alone Y = Cancel original order if modification fails</p>
<i>Capacity</i>	1	Alpha	<p>Corresponds to <i>OrderCapacity</i> (47) in Cboe FIX.</p> <p>The capacity of the order.</p> <p>C = Customer M = Market Maker F = Firm U = Professional Customer N = Non-Cboe Market Maker B = Broker-Dealer J = Joint Back Office L = Non-Trading Permit Holder Affiliate (C1 and C2 only)</p>
<i>ClearingAccount</i>	4	Text	<p>Corresponds to <i>OnBehalfOfSubID</i> (116) and <i>ClearingAccount</i> (440) in Cboe FIX.</p> <p>Supplemental identifier. Recorded and made available in execution reports. Available via Drop feeds.</p> <p>When <i>Capacity</i> is set to a value of M or N for Market Maker, this field should be filled with the desired market maker ID. When using CMTA, this value is the Market Maker ID for the CMTA member instead of the Cboe member executing the trade. This field will be sent to the OCC.</p> <p>If <i>Capacity</i> is set to something besides Market Maker, this field can be blank or filled out with an optional string that is passed through to the OCC.</p>
<i>ClearingFirm</i>	4	Alpha	<p>Corresponds to <i>OnBehalfOfCompID</i> (115) Cboe FIX.</p> <p>EFID that will clear the trade. Port attribute value of 'Default EFID' is used if not provided.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>ClearingOptionalData</i>	16	Text	Corresponds to <i>ClearingOptionalData</i> (9324) in Cboe FIX. This field will be reflected back on execution reports , FIX DROP ports and it will be passed through to the OCC in the Optional Data field.
<i>ClientIDAttr</i>	4	Text	Corresponds to <i>ClientID</i> (109) Cboe FIX. User defined identifier for quote attribution.
<i>CMTANumber</i>	4	Binary	Corresponds to <i>CMTANumber</i> (439) in Cboe FIX. CMTA Number of the firm that will clear the trade. Must be specified for CMTA orders and left unspecified for non-CMTA orders.
<i>ComboOrder</i>	1	Alpha	Corresponds to <i>ComboOrder</i> (22005) in Cboe FIX. Declare the order as a Combo (for regulatory relief if trading SPX on the floor). N = (Default) No Y = Yes C1 only.
<i>Compression</i>	1	Alpha	Corresponds to <i>Compression</i> (22006) in Cboe FIX. Order is a compression trade. N = (Default) No Y = Yes C1 only.
<i>ContraCapacity</i>	1	Alphanumeric	Capacity of the contra for this execution. See <i>Capacity</i> for allowed values.
<i>ContraTrader</i>	4	Alphanumeric	Corresponds to <i>ContraTrader</i> (337) in Cboe FIX. Only present on local book trades, not present on routed trades. <u>Simple Instrument Fills</u> Displays the EFID (Contra <i>ClearingFirm</i>) of the contra side firm. This includes leg fill reports (<i>MultilegReportingType</i> =2) that are sent as a result of a complex trade. For Cboe Options floor trades, displays the Contra Floor Acronym (C1 only). <u>Complex Package Fills</u> <i>ContraTrader</i> will be sent and populated on electronic, complex package fills (<i>MultilegReportingType</i> =3) when the contra side is also a complex order. When legging in to the simple books <i>ContraTrader</i> will be blank. <i>ContraTrader</i> will also be blank on complex package fills executed on the Cboe Options trading floor (C1 only).
<i>CorrectedSize</i>	4	Binary	Corresponds to <i>CorrectedSize</i> (6655) in Cboe FIX. Number of shares after trade adjustment.
<i>CrossExclusion Indicator</i>	1	Alpha	Corresponds to <i>CrossExclusionIndicator</i> (6438) in Cboe FIX. N = Contracts were executed in auction against Contra party or against a resting order when auction was initiated Y = Contracts were executed in auction against another party. C1 and EDGX only.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>CrossId</i>	20	Text	<p>Corresponds to <i>CrossID</i> (548) in Cboe FIX.</p> <p>Day-unique identifier for the cross order chosen by the client. Characters in the ASCII range 33-126 are allowed, except for comma, semicolon and pipe.</p> <p>C1 and EDGX only.</p>
<i>CrossType</i>	1	Alphanumeric	<p>Corresponds to <i>CrossType</i> (549) in Cboe FIX.</p> <p>Type of auction order being submitted. This indicates the type of auction that will be initiated upon order entry.</p> <p>1 = Automated Improvement Mechanism ("AIM") 2 = Qualified Contingent Cross ("QCC") 3 = Solicitation Cross ("SAM") (C1 only) Effective on EDGX TBD</p>
<i>CrossPrioritization</i>	1	Alphanumeric	<p>Corresponds to <i>CrossPrioritization</i> (550) in Cboe FIX.</p> <p>Indicates which side of the cross order will be prioritized for execution. This identifies the Agency side.</p> <p>1 = Buy 2 = Sell</p> <p>C1 and EDGX only.</p>
<i>CumQty</i>	4	Binary	<p>Corresponds to <i>CumQty</i> (14) in Cboe FIX</p> <p>Cumulative quantity of contracts executed for the order over the life of the order, which may be multiple business days in the case of persisting GTC/GTD orders.</p>
<i>CustomGroupID</i>	2	Binary	<p>Corresponds to <i>CustomGroupID</i> (7699) in Cboe FIX for <i>New Order</i> and <i>Purge Orders</i> messages.</p> <p>Used to group orders for use in <i>Purge Orders</i> where multiple orders can be cancelled by specifying a list of <i>CustomGroupIDs</i>.</p>
<i>DayAvgPx</i>	8	Binary Price	<p>Corresponds to <i>DayAvgPx</i> (426) in Cboe FIX.</p> <p>Applicable to persisting GTC/GTD orders only. Average price per contract of executions on current business date. Zero if <i>DayCumQty</i> is zero.</p>
<i>DayCumQty</i>	4	Binary	<p>Corresponds to <i>DayCumQty</i> (425) in Cboe FIX.</p> <p>Applicable to persisting GTC/GTD orders only. Cumulative quantity of contracts executed for the order during the current business day.</p>
<i>DayOrderQty</i>	4	Binary	<p>Corresponds to <i>DayOrderQty</i> (424) in Cboe FIX.</p> <p>Applicable to persisting GTC/GTD orders only. Contracts remaining to be filled for the order at the beginning of the current business day (i.e., <i>OrderQty</i> – <i>CumQty</i> at the end of the previous business day).</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>DisplayIndicator</i>	1	Alphanumeric	<p>Corresponds to <i>DisplayIndicator</i> (9479) in Cboe FIX.</p> <p>V = Default. As determined by port level setting (default to S)</p> <p>S = Display Price Sliding (this is to override a opt-out of Display Price Sliding at the port level (BZX only))</p> <p>L = Display Price Sliding, but reject if order crosses NBBO on entry (BZX only)</p> <p>M = Multiple Display Price Sliding (BZX only)</p> <p>P = Price Adjust</p> <p>m = Multiple Price Adjust</p> <p>R = Reject the order if it cannot be booked and displayed without adjustment.</p> <p>N = NoRescrapeAtLimit (BZX only)</p> <p>See 'Display Indicator Features' for more details on sliding options.</p>
<i>DisplayPrice</i>	8	Binary Price	<p>Only present when order is fully or partially booked. If the order has to be displayed at a less aggressive price for some reason, then that price will be reported here, otherwise equals <i>Price</i>.</p>
<i>DisplayRange</i>	4	Binary	<p>Corresponds to <i>DisplayRange</i> (8020) in Cboe FIX.</p> <p>Used for random replenishment of reserve orders. Random replenishment establishes a range of possible values for the order quantity that is to be displayed. For example, if MaxFloor = 2,000, and DisplayRange = 200, the displayed quantity will be selected from one of the following values: 1,800, 1,900, 2,000, 2,100, or 2,200. Must be specified in round lots.</p>
<i>DrillThruProtection</i>	8	Binary Price	<p>Corresponds to <i>DrillThruProtection</i> (6253) in Cboe FIX.</p> <p>Amount sender is willing to trade through the SNBBO. A zero price provides full SNBBO protection. The price should be entered as a non-negative value.</p> <p>Exchange default values are 3% of the opposite of the SNBBO, with a minimum value of \$0.02 and a maximum of \$0.10 for the default value. Values provided on a New Complex Order message do not have a minimum or maximum.</p> <p>C1, C2, and EDGX only.</p>
<i>EchoText</i>	64	Text	<p>Corresponds to <i>Text</i> (58) in Cboe FIX.</p> <p>Free format text string. May be echoed back on Cboe to Member messages.</p>
<i>EquityBuyClearingFirm</i>	4	Text	<p>Corresponds to <i>EquityBuyClearingFirm</i> (22014) in Cboe FIX.</p> <p>Clearing firm on buy side of the equity trade associated with a QCC trade.</p> <p>Valid when <i>CrossType</i> = '2'.</p> <p>C1 and EDGX only.</p>
<i>EquityExDestination</i>	1	Alphanumeric	<p>Corresponds to <i>EquityExDestination</i> (22016) in Cboe FIX.</p> <p>Valid when an equity symbol is present in the complex instrument.</p> <p>Exchange venue to which equity leg matching will be submitted. Supported values are:</p> <p>C = Cowen (default)</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

			Additional targets planned after C1 migration. If buyer and seller do not match venues, then the equity match will be reported to Cowen ("C"). C1 and EDGX only.
<i>EquityLegShortSell</i>	1	Alphanumeric	Corresponds to <i>EquityLegShortSell</i> (22624) in Cboe FIX. 5 = Sell Short (for stock leg) 6 = Sell Short Exempt (for stock leg) C1 and EDGX only.
<i>EquityPartyId</i>	4	Alpha	Corresponds to <i>EquityPartyId</i> (22008) in Cboe FIX. MPID used to clear the equity leg being cleared via the Exchange. C1 and EDGX only.
<i>EquitySellClearingFirm</i>	4	Text	Corresponds to <i>EquitySellClearingFirm</i> (22015) in Cboe FIX. Clearing firm on sell side of the equity trade associated with a QCC trade. Valid when <i>CrossType</i> = '2'. C1 and EDGX only.
<i>EquityTradePrice</i>	8	Binary Price	Corresponds to <i>EquityTradePrice</i> (22011) in Cboe FIX. Price at which the equity associated with a QCC trade. Valid when <i>CrossType</i> = '2'. C1 and EDGX only.
<i>EquityTradeSize</i>	4	Binary	Corresponds to <i>EquityTradeSize</i> (22012) in Cboe FIX. Number of shares executed in the equity associated with a QCC trade. Valid when <i>CrossType</i> = '2'. C1 and EDGX only.
<i>EquityTradeVenue</i>	1	Text	Corresponds to <i>EquityTradeVenue</i> (22013) in Cboe FIX. Exchange venue where equity associated with a QCC traded. Valid when <i>CrossType</i> (549) = '2'. A = NYSE American B = Nasdaq BX C = NYSE National I = Investors Exchange J = Cboe EDGA Exchange K = Cboe EDGX Exchange M = CHX N = NYSE P = NYSE Arca Q = Nasdaq X = Nasdaq PSX Y = Cboe BYX Exchange Z = Cboe BZX Exchange C1 and EDGX only.
<i>EquityTransactTime</i>	8	DateTime	Corresponds to <i>EquityTransactTime</i> (22060) in Cboe FIX.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

			Time of equity trade associated with a QCC trade. Valid when <i>CrossType</i> = '2'. C1 and EDGX only.
<i>ExDestination</i>	1	Text	Corresponds to <i>ExDestination</i> (100) in Cboe FIX. Used to specify the designated away venue for <i>RoutStrategy</i> = DIRC. A = NYSE ARCA E = NASDAQ ISE F = MIAX P = MIAX PEARL D = MIAX Emerald G = EDGX Options H = C2 K = BOX N = NASDAQ S = NASDAQ BX U = NYSE AMERICAN W = Cboe Options (C1) X = Nasdaq PHLX Z = BZX Options g = Nasdaq GEMX m = Nasdaq MRX
<i>ExecInst</i>	1	Text	Corresponds to <i>ExecInst</i> (18) in Cboe FIX. 1 = Not held. Must be routed to the floor. (C1 only) f = Intermarket Sweep (Directed or Cboe) r = Settlement Liquidity ¹ (C1 only) G = All or None (AON) (C1 and EDGX only) s = Sweep ² (C1 and EDGX only) ASCII NULL (0x00) = no special handling ¹ Requires <i>TimeInForce</i> = 2 and <i>Price</i> . ² Used for New Order Cross and New Order Cross Multileg only. Requires <i>CrossType</i> = 1 (AIM).
<i>ExpireTime</i>	8	DateTime	Corresponds to <i>ExpireTime</i> (126) in Cboe FIX. Required for <i>TimeInForce</i> = 6 orders, specifies the date-time (in UTC) that the order expires.
<i>FeeCode</i>	2	Alphanumeric	Corresponds to <i>FeeCode</i> (9882) in Cboe FIX. Indicates fee associated with an execution. Fee codes are published in the pricing schedule. New fee codes may be sent with little or no notice. Members are encouraged to code their systems to accept unknown fee codes.
<i>FloorDestination</i>	4	Text	Corresponds to <i>FloorDestination</i> (22100) in Cboe FIX. Specifies a default PAR workstation (ex. W001) to route to on the floor (or "PARO" to route to the Floor PAR Official of the underlying symbol) if not specified on inbound messages. C1 only.
<i>FloorRoutingInst</i>	1	Alphanumeric	Corresponds to <i>FloorRoutingInst</i> (22303) in Cboe FIX.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

			<p>D = Direct (do not attempt to process electronically)¹ E = Electronic only X = Route to floor if unable to process electronically¹ <blank> = Port level default</p> <p>The default value for any given port can be changed by requesting an update to the "Default FloorRoutingInst" port attribute.</p> <p>¹When <i>FloorRoutingInst</i> is 'D' or 'X', <i>RoutingInst</i> must be set to 'B' or 'R' for simple orders; for complex or FLEX instruments <i>RoutingInst</i> must be set to 'B'.</p> <p>C1 only.</p>
<i>FrequentTraderID</i>	6	Text	<p>Corresponds to <i>FrequentTraderId</i> (21097) in CFE FIX.</p> <p>Identifies the frequent trader program in which the order is participating.</p> <p>C1 only.</p>
<i>GiveUpFirmID</i>	4	Alpha	<p>Corresponds to <i>GiveupFirmID</i> (9946) in Cboe FIX.</p> <p>For the Agency Side, this field must equal the value of <i>ClearingFirm</i> (EFID). Each Contra allocation will use this field instead of <i>ClearingFirm</i> for clearing information.</p> <p>C1 and EDGX only.</p>
<i>LastPriority</i>	1	Alphanumeric	<p>Corresponds to <i>LastPriority</i> (9849) in Cboe FIX.</p> <p>When enabled, allocation will go to other participants' responses before requiring the Contra Order to satisfy remaining contracts of the Agency Order. Mutually exclusive with <i>AutoMatch</i>.</p> <p>0 = Disabled (Default) 1 = Enabled</p> <p>C1 and EDGX only.</p>
<i>LastPx</i>	8	Binary Price	<p>Corresponds to <i>LastPx</i> (31) in Cboe FIX.</p> <p>Price of this fill.</p>
<i>LastShares</i>	4	Binary	<p>Corresponds to <i>LastShares</i> (32) in Cboe FIX.</p> <p>Executed share quantity.</p>
<i>LeavesQty</i>	4	Binary	<p>Corresponds to <i>LeavesQty</i> (151) in Cboe FIX.</p> <p>Quantity still open for further execution. If zero, the order is complete.</p>
<i>LegCFIcode</i>	6	Alphanumeric	<p>Corresponds to <i>LegCFIcode</i> (608) in Cboe FIX.</p> <p>CFI Code for leg. Required if <i>LegSymbol</i> is in OSI format.</p> <p>OP = Options Put OC = Options Call E = Equity (C1 only)</p> <p>C1, C2, and EDGX only.</p>
<i>LegMaturityDate</i>	4	Date	<p>Corresponds to <i>LegMaturityDate</i> (611) in Cboe FIX.</p> <p>Required if <i>LegSymbol</i> is in OSI format.</p> <p>C1, C2, and EDGX only.</p>
<i>LegStrikePrice</i>	8	Binary Price	<p>Corresponds to <i>LegStrikePrice</i> (612) in Cboe FIX.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

			<p>Option strike price. System maximum is 999,999.99. Must be non-negative.</p> <p>Required if <i>LegSymbol</i> is in OSI format.</p> <p>C1, C2, and EDGX only.</p>
<i>MarketingFeeCode</i>	2	Alphanumeric	<p>Corresponds to <i>MarketingFeeCode</i> (5937) in Cboe FIX.</p> <p>P = Penny Pilot N = Non-Penny Pilot X = Not Eligible for Marketing Fees</p> <p>C1 and EDGX only.</p>
<p><i>MassCancel</i></p> <p><i>Legacy method to be deprecated at date TBD</i></p>	1	Alphanumeric	<p>Corresponds to <i>MassCancel</i> (7693) in Cboe FIX.</p> <p>Indicates that a mass cancellation is being performed.</p> <p>1 or 3 = Cancel all orders that match <i>RiskRoot</i> or <i>CustomGroupID</i>, regardless of <i>ClearingFirm</i>. 2 or 4 = Cancel all orders that match the given <i>RiskRoot</i> or <i>CustomGroupID</i> and <i>ClearingFirm</i>.</p> <p>Values 3 and 4 are similar to 1 and 2, respectively, but individual <i>Order Cancelled</i> messages will not be sent for each order cancelled. Instead, a <i>Mass Cancel Acknowledgement</i> message with <i>MassCancelID</i> and <i>CancelledOrderCount</i> will be sent once all cancels have been processed.</p> <p>For <i>Purge Orders</i> messages, the <i>Mass Cancel Acknowledgement</i> message may always be requested by sending a <i>MassCancelID</i> in the <i>Purge Order</i> message, regardless of the value of the <i>MassCancel</i> field.</p> <p><i>MassCancel</i> requests will not cancel initiating orders for AIM Auctions.</p>
<i>MassCancelID</i>	20	Text	<p>Corresponds to <i>MassCancelID</i> (7695) in Cboe FIX.</p> <p>Copied from the <i>MassCancelID</i> passed on the original <i>Cancel Order</i> or <i>Purge Order</i> message.</p>
<i>MassCancelInst</i>	16	Text	<p>Corresponds to <i>MassCancelInst</i> (7700) in Cboe FIX. Used for specification of <i>Purge Orders</i> functionality and optionally used for specification of <i>Mass Cancel</i> functionality associated with the <i>Cancel Order</i> message.</p> <p>At least one character must be provided (<i>Clearing Firm Filter</i>). Contiguous characters must be specified up to total length. Truncated/unspecified characters will default to values indicated (D) below.</p> <p>1st Character: Clearing Firm Filter</p> <p>A = No filtering by clearing firm relationship is performed. F = All orders that were sent under the clearing relationship specified in <i>ClearingFirm</i> optional field. If "F" specified and the <i>ClearingFirm</i> field is not provided, the <i>Mass Cancel</i> or <i>Purge Orders</i> will be rejected. If "F" specified and the <i>ClearingFirm</i> field is provided but is blank (NULL), the <i>Mass Cancel</i> or <i>Purge Orders</i> will be treated like "A", and no filtering by clearing firm relationship is performed.</p> <p>2nd Character: Acknowledgement Style</p> <p>M = (D) <i>Order Cancelled</i> messages are sent for each cancelled order. If "M" is set and the <i>MassCancelID</i></p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

			<p>optional field is specified, the <i>MassCancelID</i> value is ignored.</p> <p>S = A single Mass Cancel Acknowledgement message is sent once all cancels have been processed. The <i>MassCancelID</i> optional field must be specified or the Mass Cancel or Purge Orders will be rejected.</p> <p>B = Both individual Order Cancelled and Mass Cancel Acknowledgement messages will be sent. Also requires <i>MassCancelID</i> optional field to be specified or the Mass Cancel or Purge Orders will be rejected.</p> <p>3rd Character: Lockout Instruction</p> <p>N = (D) No lockout</p> <p>L = Lockout until corresponding a risk reset is received. Lockout can be used only with Clearing Firm Filter set to "F", otherwise the Mass Cancel or Purge Orders will be rejected. Lockout will apply to all new orders for the <i>ClearingFirm</i> (and <i>ProductName</i> or <i>CustomGroupIDs</i>, if specified), regardless of other filtering in the Purge Orders or Cancel Order message.</p> <p>4th Character: Instrument Type Filter (C1, C2, and EDGX Only) Value will be ignored on BZX Options.</p> <p>B = (D) Cancel both single leg and complex orders</p> <p>S = Cancel single leg orders only</p> <p>C = Cancel complex orders only</p> <p>5th Character: GTC Order Filter</p> <p>C = (D) Cancel GTC and GTD orders</p> <p>P = Don't cancel (preserve) GTC and GTD orders</p> <p>If the <i>RiskRoot</i> optional field is specified, it must contain a valid symbol (e.g., "MSFT"), in which case only orders associated with the specified <i>RiskRoot</i> will be cancelled.</p> <p>A self-imposed lockout can be released using the <i>RiskReset</i> field of the New Order or New Complex Order message or by sending a Reset Risk message. If <i>RiskRoot</i> optional field is specified, a symbol level reset is required, otherwise a firm level reset is required to release a lockout. For more information, refer to the 'Cboe Risk Management Specification'.</p>
<i>MassCancelLockout</i>	1	Alphanumeric	<p>Corresponds to <i>MassCancelLockout</i> (7697) in Cboe FIX.</p> <p>0 = No Lockout</p> <p>1 = Lockout</p> <p>Members may initiate a new self-imposed order lockout in conjunction with a mass cancel for all resting orders and inflight orders. The value of 1 is only applicable in conjunction with <i>MassCancel</i> values of 2 and 4; other usage results in a reject.</p>
<i>MaturityDate</i>	4	Date	<p>Corresponds to <i>MaturityMonth</i> (200) and <i>MaturityDay</i> (205) in Cboe FIX.</p>
<i>MaxFloor</i>	4	Binary	<p>Corresponds to <i>MaxFloor</i> (111) in Cboe FIX.</p> <p>Portion of <i>OrderQty</i> to display. The balance is reserve. 0 displays the entire quantity. The displayed quantity of each order at a price level is decremented first. When displayed</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

			<p>quantity is fully decremented, it is reloaded up to <i>MaxFloor</i> from reserve.</p> <p>Default = 0</p> <p>An order with a <i>MaxFloor</i> greater than 0 will be rejected for Cboe proprietary classes (such as DJX, RUT, SPX, XSP, and VIX).</p>
<i>MaxRemovePct</i>	1	Binary	<p>Corresponds to <i>MaxRemovePct</i> (9618) in Cboe FIX.</p> <p>For Post Only At Limit (RoutingInst = Q), what percentage of the order quantity which remains after price improvement may be removed at the limit.</p> <p>Must be 0 for non-Post Only At Limit orders.</p> <p>0 = Don't Remove any shares at limit price 100 = Remove any amount at limit price</p> <p>BZX only.</p>
<i>MinQty</i>	4	Binary	<p>Corresponds to <i>MinQty</i> (110) in Cboe FIX.</p> <p>Minimum fill quantity for IOC orders which only interact with liquidity on the target book. Ignored for other orders.</p>
<i>MultiClassSprd</i>	1	Alpha	<p>Corresponds to <i>MultiClassSprd</i> (22004) in Cboe FIX.</p> <p>Indicates an option is part of a multi-class spread.</p> <p>N = (Default) No Y = Yes</p> <p>C1 only.</p>
<i>MultilegReportingType</i>	1	Alphanumeric	<p>Corresponds to <i>MultilegReportingType</i> (442) in Cboe FIX</p> <p>Indicates the type of Order Execution message.</p> <p>1 = Single-leg instrument 2 = Individual leg of multi-leg instrument 3 = Entire multi-leg instrument package</p> <p>C1, EDGX and C2 only.</p>
<i>NoOfSecurities</i>	4	Binary	<p>Corresponds to <i>NoOfSecurities</i> (8641) in Cboe FIX.</p> <p>Indicates the number of securities created by the member in this trading session.</p> <p>C1, C2, and EDGX only.</p>
<i>OpenClose</i>	1	Alphanumeric	<p>Corresponds to <i>OpenClose</i> (77) in Cboe FIX.</p> <p>Indicates status of client position in the option.</p> <p>O = Open C = Close N = None*</p> <p>*Orders with a <i>Capacity</i> of M or N will not be required to specify <i>OpenClose</i> on their orders. A value of N may optionally be specified unless the series is limited to closing only.</p> <p>If the series is limited to closing only transactions an order with <i>Capacity</i> of M or N will only be permitted to submit <i>OpenClose</i> = O if the order has a <i>TimeInForce</i> of IOC (3) or <i>RoutingInst</i> of Post Only (P) or <i>PostingInstruction</i> of P or R.</p>
<i>OrderOrigin</i>	3	Alphanumeric	<p>Corresponds to <i>OrderOrigin</i> (9465) in Cboe FIX.</p> <p>Floor acronym of Market Maker on whose behalf this order is being entered by a floor broker.</p> <p>C1 only.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>OrderQty</i>	4	Binary	Corresponds to <i>OrderQty</i> (38) in Cboe FIX. Order quantity. System limit is 999,999 contracts.
<i>OrdType</i>	1	Alphanumeric	Corresponds to <i>OrdType</i> (40) in Cboe FIX. 1 = Market 2 = Limit (default) 3 = Stop 4 = Stop Limit Market implies <i>TimeInForce</i> of IOC (3). Stop/Stop Limit orders must be set to <i>TimeInForce</i> = "0" (DAY), "1" (GTC), or "6" (GTD).
<i>OrigClOrdID</i>	20	Text	Corresponds to <i>OrigClOrdID</i> (41) in Cboe FIX.
<i>OrigCrossID</i>	20	Text	Corresponds to <i>OrigCrossID</i> (551) in Cboe FIX.
<i>ORS</i>	1	Alpha	Corresponds to <i>ORS</i> (22003) in Cboe FIX. Order router subsidy eligibility (used for billing purposes). N = (Default) No Y = Yes C1 only.
<i>PreventMatch</i>	3	Alpha	Corresponds to <i>PreventMatch</i> (7928) in Cboe FIX. Three characters: 1st character - MTP Modifier: N = Cancel Newest O = Cancel Oldest B = Cancel Both S = Cancel Smallest D = Decrement larger / Cancel Smaller d = Same as D above, but only decrement <i>LeavesQty</i> . Do not restate <i>OrderQty</i> . 2nd character - Unique ID Level: F = Prevent Match at Firm(Member) Level M = Prevent Match at EFID Level 3rd character - Trading Group ID (optional): Member specified alphanumeric value 0-9, A-Z, or a-z. The Unique ID level (character 2) of both orders must match to prevent a trade. If specified on both orders, Trading Group ID (character 3) must match to prevent a trade. The MTP Modifier (character 1) of the inbound order will be honored, except that if the inbound order specifies Decrement and the resting order does not, and the resting order is larger, then both orders will be cancelled. This exception is to protect the order entry software for the resting order from receiving an unexpected restatement message. If order entry software is prepared to handle unexpected restatement messages, this exception may be override at the port level by requesting "Allow MTP Decrement Override" functionality. Uses of MTP Modifier D or d and users of "Allow MTP Decrement Override" functionality must be prepared to receive an <i>Order Restated</i> message that decrements <i>LeavesQty</i> (and, for method D, <i>OrdQty</i> as well). On a <i>New Order Cross</i> , only N and O are supported for the MTP modifier. MTP instructions on AIM orders will be used to

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

			<p>prevent executions against AIM responses only; they will permit executions against resting or unrelated orders. Responses may only employ N (Cancel Newest) in which case the response will be cancelled and the auction order will continue.</p> <p>On a <i>New Order Cross</i>, this field is only applicable to the Agency order.</p>
<i>Price</i>	8	Binary Price	<p>Corresponds to <i>Price</i> (44) in Cboe FIX.</p> <p>Limit price.</p> <p>Required for limit orders (<i>OrdType</i> = 2). If specified on market order (<i>OrdType</i> = 1), the order will be rejected.</p> <p>This field is also used to specify an optional cap price for pegged orders.</p> <p>For complex orders, net pricing of the strategy. Four implied decimal places. EDGX and C2 only</p> <p><i>Buy orders:</i></p> <ul style="list-style-type: none"> • Positive value, Debit • Negative value, Credit • Even order, 0 (Zero) <p><i>Sell orders:</i></p> <ul style="list-style-type: none"> • Positive value, Credit • Negative value, Debit • Even order, 0 (Zero)
<i>PriceType</i>	1	Alphanumeric	<p>Corresponds to <i>PriceType</i> (423) in Cboe FIX.</p> <p>0 = Fixed cabinet trade price 2 = (Default) Price per unit (contract) 3 = Fixed amount (cash spread pricing) – only for complex orders routed to the floor</p> <p>C1 only.</p>
<i>PutOrCall</i>	1	Alphanumeric	<p>Corresponds to <i>PutOrCall</i> (201) in Cboe FIX.</p> <p>0 = Put 1 = Call</p>
<i>RevisedLegs</i>	1	Alphanumeric	<p>Indicates if the legs on the created complex strategy have been reordered from the original request.</p> <p>If the legs were reordered, the order of the <i>OpenClose</i> fields on a <i>New Complex Order</i> must be the order returned by the exchange, not the order from the original request.</p> <p>1 = Legs were not reordered 2 = Legs were reordered</p> <p>C1, C2, and EDGX only.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>RiskReset</i>	8	Text	<p>Corresponds to <i>RiskReset</i> (7692) in Cboe FIX.</p> <p>For use by customers using Cboe's Risk Management tools to reset or release EFID Group, EFID, Risk Root or Custom Group ID level lockout conditions resulting from risk profile trips or self-imposed lockouts issued via <i>Cancel Order</i> or <i>Purge Orders</i> messages.</p> <p>Single Character Values:</p> <p>S = Risk Root level risk/lockout reset F = EFID level risk/lockout reset C = CustomGroupID lockout reset G = EFID Group level risk/lockout reset</p> <p>Values may be combined together to allow for resets of multiple risk trips or self-imposed lockouts in a single message. For example, "GS", "SC", "FC", and "SFC" are all acceptable values.</p> <p>When a resting or inbound order is executed and a Risk Root level risk profile limit is reached, resting orders on the associated Risk Root will be cancelled and inbound orders on the Risk Root will be rejected until this field is filled with the value S on a subsequent <i>New Order</i> or <i>New Complex Order</i> message corresponding to a symbol on the same Risk Root. All active Risk Root level rules in the risk profile are reset at this time. Individual rules cannot be reset on their own.</p> <p>If an EFID-level rule is tripped, this tag can be filled with the value "F" to reset all EFID-level rules. While this will reset EFID-level rules, it is possible that both EFID and Risk Root level rules are currently tripped. Setting this field to "F" will not clear Risk Root-level rules and the order may still be rejected. To clear both Risk Root and EFID-level rules, set this field to "SF" to reset all associated Risk Root and EFID-level lockouts.</p> <p>If orders have been locked out at the <i>CustomGroupID</i> level, inbound orders for the locked <i>CustomGroupID</i> will be rejected until this field is filled with the value C on a <i>New Order</i> or <i>New Complex</i> order that uses the locked <i>CustomGroupID</i>.</p> <p>EFID and EFID Group resets are not allowed by default. Customers should contact the Cboe Trade Desk to reset these limits or request a change to the "EFID Risk Reset" port setting using the Logical Port Request form.</p> <p>For more information, refer to the 'Cboe US Options Risk Management Specification'.</p>
<i>RiskRoot</i>	6	Text	<p>Corresponds to <i>Symbol</i> (55) in Cboe FIX.</p> <p>The underlying symbol.</p>
<i>RouteDeliveryMethod</i>	3	Text	<p>Corresponds to <i>RouteDeliveryMethod</i> (9350) in Cboe FIX.</p> <p>RTI = Route to improve (default if not specified). Ability to receive price improvement will take priority over speed of execution.</p> <p>RTF = Route to Fill. Speed of execution will take priority over potential price improvement.</p> <p>Only applicable to <i>RouteStrategy</i> = ROUT</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>RoutingFirmID</i>	4	Alpha	<p>Corresponds to <i>RoutingFirmID</i> (7933) in Cboe FIX.</p> <p>Used to optionally convey the routing firm of the order. If supplied, value must be a valid member EFID.</p> <p>May be combined with <i>MassCancel</i> values 2 or 4, or <i>MassCancelInst</i> with Firm Filter set to "F" in a mass cancel request.</p> <p>C1, C2, and EDGX only.</p>
<i>RoutingInst</i>	4	Text	<p>Corresponds to <i>RoutingInst</i> (9303) in Cboe FIX.</p> <p>1st character: B = Book Only (not routable, will remove from local book) P = Post Only (not routable)¹ Q = Post Only at Limit (removes liquidity that improves upon limit price and up to <i>MaxRemovePct</i> of remaining <i>OrdQty</i> at limit price) (BZX only) R = Routable S = Super Aggressive – Cross or Lock (order will be removed from the book and routed to any quote that is locking or crossing the order) X = Aggressive – Cross Only (order will be removed from the book and routed to any quote that is crossing the order)</p> <p>2nd character (C1 and EDGX only): L = Do Not Expose order via Step-Up Mechanism (SUM) S = Expose order via Step Up Mechanism (SUM)²</p>
<i>RoutingInst</i> (Complex)	4	Text	<p>Corresponds to <i>RoutingInst</i> (9303) in Cboe FIX.</p> <p>1st character: B = Book Only (will remove from local book), allowed to interact with both single-leg and other complex orders. D = Complex Book Only, allowed to interact with other complex orders only³. P = Post Only (adds liquidity only)</p> <p>2nd character: L = Do Not Expose order via Complex Options Auction (COA) S = Expose order via Complex Options Auction (COA)⁴</p> <p>C1, C2, and EDGX only.</p>
<i>RoutStrategy</i>	6	Text	<p>Corresponds to <i>RoutStrategy</i> (9400) in Cboe FIX.</p> <p>All exchanges: ROUT = Book + Street DIRC⁵ = Book + Directed IOC or Directed ISO if <i>ExecInst</i> = f SWPA = (default) Book + Sweep Street</p>

¹ Post Only orders on EDGX with DisplayIndicator (Fix Tag 9479) = R will be cancelled back even if they would be immediately executable with price improvement.

² Routable Orders identified with *RoutingInst* = R, RS, S, SS, X or XS, and *RoutStrategy* = ROUT, and *AuctionId* not supplied, or Non-Routable Orders identified with *RoutingInst* = BS and *ExecInst* not f and *TimeInForce* not 4 and *MinQty* not supplied will participate in the Step-Up Mechanism (SUM) before routing, booking, or cancelling back.

³ Only valid with *TimeInForce* values of 0 (Day) or 3 (IOC), otherwise order will be rejected.

⁴ All non-IOC Complex Orders will be eligible for Complex Options Auction (COA) unless otherwise specified.

⁵ Field *ExDestination* must be populated with *RoutStrategy* = DIRC. Must be specified when sending non-book only ISO, otherwise the order will be rejected.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>SecondaryExecID</i>	8	Binary	<p>Field indicates whether a fill or partial fill is a complex instrument fill or a single leg fill that comprises a complex execution.</p> <ul style="list-style-type: none"> • If SecondaryExecID (527) is not present, the fill is a single leg fill only. • If SecondaryExecID (527) is present and is the same as the ExecID (17) the fill represents a complex execution for which associated single leg fills will follow. • Single leg fills associated with a complex execution will contain a SecondaryExecID (527) of the associated complex execution. <p>C1, C2, and EDGX only.</p>
<i>SecondaryOrderID</i>	8	Binary	<p>Corresponds to <i>SecondaryOrderID</i> (198) in Cboe FIX.</p> <p>Denotes an alternative <i>OrderID</i> which is present on Cboe market data feeds (for example, to hide that a reserve (iceberg) order has reloaded). Or, <i>OrderID</i> of the contra side of a prevented match.</p>
<i>SenderLocationID</i>	1	Alphanumeric	<p>Corresponds to <i>SenderLocationID</i> (142) in Cboe FIX.</p> <p>F = Floor</p> <p><blank> = (or not present) for electronic execution.</p> <p>C1 only.</p>
<i>SessionEligibility</i>	1	Alpha	<p>Corresponds to <i>TradingSessionID</i> (22017) in Cboe FIX.</p> <p>A = Order participates in both Global and Regular Trading Hours (C1, C2, and EDGX only)</p> <p>R = (default) Order participates in Regular Trading Hours</p>
<i>Side</i>	1	Alphanumeric	<p>Corresponds to <i>Side</i> (54) in Cboe FIX.</p> <p>1 = Buy</p> <p>2 = Sell</p>
<i>StopPx</i>	8	Binary Price	<p>Corresponds to <i>StopPx</i> (99) in Cboe FIX.</p> <p>Stop price. Required if <i>OrdType</i> = 3 (Stop) or 4 (Stop Limit). Stop and Stop Limit orders will only be triggered off Last Sale Eligible trades.</p>
<i>StrategyID</i>	1	Alphanumeric	<p>Corresponds to <i>StrategyID</i> (22002) in Cboe FIX.</p> <p>Used to declare when a strategy is used.</p> <p>C = Conversion</p> <p>R = Reversal</p> <p>M = Merger</p> <p>S = Short stock interest</p> <p>J = Jelly roll</p> <p>C1 only.</p>
<i>StrikePrice</i>	8	Binary Price	<p>Corresponds to <i>StrikePrice</i> (202) in Cboe FIX.</p> <p>Strike Price for option, 0 – 999,999.99</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>SubLiquidityIndicator</i>	1	Alphanumeric	<p>Additional information about an execution. Cboe may add additional values without notice. Members must gracefully ignore unknown values.</p> <p>ASCII NUL (0x00) = No Additional Information S = Execution from order that set the NBBO B = Step Up Mechanism U = Market Turner (C1 Only) b = AIM (C1 and EDGX Only) C = Carried D = Done For Day q = QCC (C1 and EDGX Only) s = SAM (C1 Only) Effective on EDGX TBD</p>
<i>Symbol</i>	8	Alphanumeric	<p>Corresponds to <i>Symbol</i> (55) in Cboe FIX.</p> <p>Entire Cboe format symbol</p>
<i>TargetPartyID</i>	4	Alpha	<p>Corresponds to <i>TargetPartyID</i> (1462) in Cboe FIX.</p> <p>A valid Parent ID of the Directed Market Maker (EDGX only) or Preferred Market Maker (C1 only). Required for directed orders.</p> <p>On a New Order Cross, this field is only applicable to the Agency order.</p> <p>C1 and EDGX only.</p>
<i>TiedHedge</i>	1	Alpha	<p>Corresponds to <i>TiedHedge</i> (22018) in Cboe FIX.</p> <p>Order is a tied hedge.</p> <p>N = (Default) No Y = Yes</p> <p>C1 only.</p>
<i>TimeInForce</i>	1	Alphanumeric	<p>Corresponds to <i>TimeInForce</i> (59) in Cboe FIX.</p> <p>0 = Day - (Default) Expires at end of market day. 1 = GTC* - Remains in system until executed, cancelled or option expires. 2 = At the Open - Will remain queued and only interact in the 'Cboe Opening Process' (BZX, C2, and EDGX only) or the Cboe Opening Auction (C1 only). 3 = IOC - Portion not filled immediately is cancelled. Market orders are implicitly IOC for non-complex orders. 4 = FOK - An IOC where the entire size must be filled, else the order will be cancelled back. Not compatible with Step-Up Mechanism (SUM). 6 = GTD* - Expires at specified <i>ExpireTime</i> for a specified day. 7 = At the Close - Orders held for execution until 180 seconds before series is scheduled to close.</p> <p><i>*Bulk Quoting Ports will only support TimeInForce values of Day or GTD with a same day expiration on C1, C2, and EDGX.</i></p>
<i>TradeThroughAlertType</i>	1	Alphanumeric	<p>Corresponds to <i>TradeThroughAlertType</i> (21098) in Cboe FIX.</p> <p>Indication of a type of trade through.</p> <p>0 = No trade through 1 = NBBO 2 = BBO (local best bid or offer) 3 = SBBO (market quote of complex derived by legs) 4 = Book trade through (trade through customer size) 5 = Due Dilligence trade through</p> <p>C1 only.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

<i>WorkingPrice</i>	8	Binary Price	Corresponds to <i>WorkingPrice</i> (9690) in Cboe FIX. Only present when order is fully or partially booked. If price had to be adjusted to a less aggressive value for some reason, then the adjusted price will be reported here, otherwise equals price.
---------------------	---	--------------	--

8 Reason Codes

8.1 Order Reason Codes

The following is a list of all order related reason codes used by Cboe. These reason codes are used in a variety of contexts (order cancellations and order rejections). All reasons are not valid in all contexts. Cboe may add additional reason codes without notice. Members must gracefully ignore unknown values.

- A = Admin
- D = Duplicate identifier (e.g., CIOrdID)
- H = Halted
- I = Incorrect data center
- J = Too late to cancel
- K = Order rate threshold exceeded
- L = Order would lock or Cross NBBO
- M = Order size exceeded
- N = Ran out of liquidity to execute against
- O = *CIOrdID* doesn't match a known order
- P = Can't modify an order that is pending fill
- Q = Waiting for first trade
- R = Routing Unavailable
- T = Fill would trade through the NBBO
- U = User requested
- V = Would wash
- W = Add liquidity only order would remove
- X = Order expired
- Y = Symbol not supported
- Z = Unforeseen reason
- c = Only Close transactions accepted
- f = Risk management EFID or Custom Group ID level
- m = Market access risk limit exceeded
- o = Max open orders count exceeded
- r = Reserve reload
- s = Risk management risk root level
- w = Would remove on unslide
- x = Crossed market
- y = Order received by Cboe during replay
- z = Session End
- + = Risk management EFID Group level

8.2 Quote Reason Codes

The following is a list of all quote reason codes used by Cboe. All reasons are not valid in all contexts. Cboe may add additional reason codes without notice. Members must gracefully ignore unknown values.

- C = Invalid EFID (*ClearingFirm*)
- D = Invalid *WashId*
- E = Invalid *SessionEligibility*
- F = Not enabled for quotes
- I = Incorrect data center
- L = Invalid *QuoteCnt*
- M = Symbols not on same matching engine
- P = Invalid *PostingInstruction*
- Q = Invalid *QuoteUpdateID*
- R = Risk root does not match across quotes
- S = Symbol not found
- W = Invalid *WashPreventType*
- a = Admin
- c = Invalid *Capacity*
- d = Close only
- f = Risk management EFID or Custom Group ID level
- m = Invalid *WashMethod*
- o = Invalid Open/Close
- p = Risk management risk root level
- r = Invalid Remove
- s = Invalid *Side*
- u = Sybmol range unreachable
- y = Quote received by Cboe during replay

9 List of Message Types

9.1 Member to Cboe

Message Name	Level	Type	Sequenced
Login Request	Session	0x37	No
Logout Request	Session	0x02	No
Client Heartbeat	Session	0x03	No
New Order	Application	0x38	Yes
New Order Cross	Application	0x41	Yes
New Complex Order	Application	0x4B	Yes
New Order Cross Multileg	Application	0x5A	Yes
Cancel Order	Application	0x39	Yes
Modify Order	Application	0x3A	Yes
Quote Update	Application	0x55	Yes
Reset Risk	Application	0x56	Yes
Quote Update (Short)	Application	0x59	Yes
Purge Orders	Application	0x47	Yes
New Complex Instrument	Application	0x4C	Yes

9.2 Cboe to Member

Message Name	Level	Type	Sequenced
Login Response	Session	0x24	No
Logout	Session	0x08	No
Server Heartbeat	Session	0x09	No
Replay Complete	Session	0x13	No
Order Acknowledgment	Application	0x25	Yes
Cross Order Acknowledgment	Application	0x43	Yes
Order Rejected	Application	0x26	No
Cross Order Rejected	Application	0x44	No
Order Modified	Application	0x27	Yes
Order Restated	Application	0x28	Yes
User Modify Rejected	Application	0x29	No
Order Cancelled	Application	0x2A	Yes
Cross Order Cancelled	Application	0x46	Yes
Cancel Rejected	Application	0x2B	No
Order Execution	Application	0x2C	Yes
Trade Cancel or Correct	Application	0x2D	Yes
Purge Rejected	Application	0x48	No
Mass Cancel Acknowledgment	Application	0x36	No
Complex Instrument Accepted	Application	0x4D	Yes
Complex Instrument Rejected	Application	0x4E	No
Quote Update Acknowledgment	Application	0x51	Yes
Quote Restated	Application	0x52	Yes
Quote Cancelled	Application	0x53	Yes
Quote Execution	Application	0x54	Yes
Risk Reset Acknowledgment	Application	0x57	No
Quote Update Rejected	Application	0x58	No

10 Port Attributes

The table below lists BOE port attributes that are configurable on the port or firm level. Changes to these attributes can be made by contacting the Cboe Trade Desk. Port Attribute changes made intra-day by the Cboe Trade Desk will not affect existing quotes or orders. In order for the desired intra-day port attribute to be applied to existing quotes or orders, you must first cancel or send a quote with zero price and size and then re-enter the order or quote.

Attribute	Default	Description
Allowed Clearing Executing Firm ID(s) *	All EFIDS	Executing Firm ID(s) allowed for trading on the port.
Default Executing Firm ID	None	Default Executing Firm ID to use if none is sent on a New Order or New Complex Order.
Allow Test Symbols Only	Disabled	Allow or disallow orders in non-test symbols
Allow ISO *	Yes	Allow or disallow ISO orders.
Allow Directed ISO *	Yes	Allow or disallow ISO orders directed to other market centers.
Default Routing Instruction +	9303=RS 9350=RTI 9400=SWPA	Specifies a default value for routing. Fields can be overridden at the order level. The defaults are <i>RoutingInst</i> = RS, <i>RouteDeliveryMethod</i> = RTI, and <i>RoutStrategy</i> = SWPA.
Maximum Order Size *	25,000	Maximum order quantity
Maximum Order Dollar Value *	Unlimited	Maximum dollar value per order.
Default Price Sliding	BZX = S EDGX/C2 = P	Default price sliding behavior. See <i>DisplayIndicator</i> for details.
Cancel on Disconnect	All	<p>Cancels open orders upon order handler session disconnect; both graceful and ungraceful. If Cancel On Disconnect is set, open orders in Symbols that are not in Closed state at the time of the disconnect are cancelled.</p> <p>All = Cancel Day and GTC/GTD orders Day = Cancel only Day orders None = Disabled</p> <p>BOE Quoting ports require Cancel on Disconnect set to All or Day. Default will be used if not specified.</p>
Cancel on ME Disconnect	All	<p>Controls whether orders are cancelled or preserved on a Matching Unit failover and provides for the ability to preserve GTC/GTD orders. In any event, if a failover takes longer than 5 minutes, all orders are cancelled (including GTC/GTD Orders).</p> <p>All = Cancel Day and GTC/GTD orders Day = Cancel only Day orders None = Disabled</p> <p>BOE Bulk Quoting ports require Cancel on ME Disconnect set to All or Day. Default will be used if not specified.</p>
Market Maker Reject if Cancel on Disconnect disabled	No	Rejection of Market Maker or Away-Market Maker orders if Cancel on Disconnect is not enabled. Non-Market Maker capacity order swill be unaffected with this confuration.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Attribute	Default	Description
Send Trade Breaks [^]	No	Enables sending of Trade Cancel or Correct messages.
Default MTP Value ^{*^+}	None	Specifies default value for <i>PreventMatch</i> .
Allow MTP Decrement Override ^{*^}	No	Overrides the exception that requires both the resting and inbound order to be marked as "Decrement".
Allow Sponsored Participant MTP Control ^{*^}	No	Allow Sponsored Participant to override port default for match trade prevention by using <i>PreventMatch</i> on the order level.
Cancel on Reject ⁺	No	Cancels an order upon a cancel or modify reject.
Cancel on Regulatory Halt	All (BZX and EDGX Only) None (C1 and C2 Only)	Cancels open orders upon receipt of a Regulatory Halt. All = Cancel Day and GTC/GTD orders Day = Cancel only Day orders None = Disabled
Fat Finger Protection ^{*\$}	BZX/EDGX = None C2 = See Web Portal Port Controls Specification for defaults	Orders entered through the NBBO by a specified percentage or dollar based limit price tolerance will be rejected. Limits may be different for different price ranges and price ranges may vary across markets. Please see the 'Web Portal Port Controls Specification' for complete details.
Reject Orders on DROP Port Disconnect [*]	No	If all associated Standard FIX DROP ports associated with an order entry session experience disconnection, new orders will be rejected until at least one Standard FIX DROP port session has been reestablished. Note this parameter does not apply to Order-By-Order drop ports (ODROP).
Reject Orders on DROP Port Timeout (seconds) [*]	30 seconds	Only applicable if "Reject Orders on DROP Port Disconnect" has been enabled. When the last Standard FIX DROP port associated with an order entry session has disconnected, begin rejecting orders on the order entry session if a Standard FIX DROP session has not been reestablished within this timeout. Minimum value allowed is 0 seconds.
Cancel Open Orders on DROP Port Disconnect [*]	None	Only applicable if "Reject Orders on DROP Port Disconnect" has been enabled. When the last Standard FIX DROP port associated with an order handler session has disconnected, open orders, associated with the session are cancelled. All = Cancel Day and GTC/GTD orders Day = Cancel only Day orders None = Disabled Note this parameter applies to Standard FIX DROP ports and not Order-By-Order DROP ports (ODROP).

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Attribute	Default	Description
Carried Order Restatements	No	<p>If the Carried Order Restatements port attribute is set, unsolicited <i>Order Acknowledgement</i> messages representing GTC/GTD orders loaded by the system at startup will be sent after the Login Response message and before any other messages for each product.</p> <p>Note that Carried Orders are restated to customers using the <i>Order Acknowledgement</i> messages with <i>BaseLiquidityIndicator=A</i> and <i>SubLiquidityIndicator=C</i>.</p> <p>Note that any changes made to any port attribute will not be enforced on carried GTC orders. Members who wish to apply updated port attributes to resting GTC orders must cancel those orders, and then resubmit them following the effective time of the port attribute change.</p>
Done For Day Restatements	No	<p>If the Done For Day Restatements port attribute is set, unsolicited <i>Order Acknowledgement</i> messages representing GTC/GTD orders that will be carried into the next session will be sent after the end of the trading session and before the system is recycled.</p> <p>Note that Done For Day Restatements are restated to customers using the <i>Order Acknowledgement</i> messages with <i>BaseLiquidityIndicator=A</i> and <i>SubLiquidityIndicator=D</i>.</p>
Notional Cutoff Aggregation Methods *\$	None	<p>Gross exposure = CBB + CBO + CEB + CEO Net exposure = (CEO + CBO) – (CEB + CBB) </p> <p>On a given port, Cboe will calculate and track four values:</p> <p>CBB = Cumulative Notional Booked Bid Value <i>The sum of limit price x size for all booked sell limit orders.</i></p> <p>CBO = Cumulative Notional Booked Offer Value <i>The sum of limit price x size for all booked sell limit orders.</i></p> <p>CEB = Cumulative Notional Executed Bid Value <i>The sum of size x trade price for all executed buy orders</i></p> <p>CEO = Cumulative Notional Executed Sell Value <i>The sum of size x trade price on all executed sell orders</i></p>
Gross Daily Risk Limit Order Notional Cutoff *\$	None	Results in rejections for limit orders when gross exposure of limit orders exceeds this value for this port. Maximum whole dollar value of \$1 billion/port.
Gross Daily Risk Market Order Notional Cutoff *\$	None	Results in rejections for market orders when gross exposure of limit orders exceeds this value for this port. Maximum whole dollar value of \$1 billion/port.
Net Daily Risk Limit Order Notional Cutoff *\$	None	Results in rejections for limit orders when net exposure of limit orders exceeds this value for this port. Maximum whole dollar value of \$1 billion/port.
Net Daily Risk Market Order Notional Cutoff *\$	None	Results in rejections for market orders when net exposure of limit orders exceeds this value for this port. Maximum whole dollar value of \$1 billion/port.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Attribute	Default	Description
Default Attributed Quote **	X	<p>Default value for <i>AttributedQuote</i>. May override at order level.</p> <p>C† = Attribute <i>ClientIDAttr</i> only (C1 only) N = Don't Attribute (may override at order level) Y = Attribute EFID only Z = Attribute EFID and <i>ClientIDAttr</i> X* = (Default) Never Attribute (may not be overridden at order level)</p> <p>*On EDGX and BZX, this setting may only be changed after executing Attribution Addendum to Exchange User Agreement.</p>
Crossed Market Cancel / Reject §	No	<p>Reject new orders when the NBBO in the security is crossed. Routable orders will have any remaining quantity cancelled back when the order returns to the book. Order modifications which cause a loss in priority will result in a cancel of the original order if the NBBO is crossed upon receipt of the modify request.</p> <p>Quotes are always accepted, even in a crossed market.</p>
Duplicative Order Protection Time Threshold §	None	Time window, in seconds, for Duplicative Order Protection Check
Duplicative Order Protection Order Count Threshold §	None	Number of orders with the same <i>ClearingFirm</i> , <i>Price</i> , <i>OrdQty</i> , and <i>Symbol</i> that must be seen within the Duplicative Order Time Threshold to initiate Duplicative Order Protection Action.
Duplicative Order Protection Action §	1	<p>Action taken when Duplicative Order Protection criteria is met:</p> <p>1 = Not enabled. 2 = Reject new orders for the remainder of Duplicative Order Time Threshold. 3 = Disable port for <i>ClearingFirm</i>. Must call Cboe Trade Desk to reenable.</p>
EFID Risk Reset	Disabled	<p>Configures how risk may be reset after a risk trip.</p> <p>Disabled = (Default). Will require manually resetting all EFID Group and EFID-Level Risk trips by contacting the Trade Desk. Enabled = Will allow EFID Group and EFID-level Risk resets using <i>RiskReset</i> of "F" or "G".</p>
Port Order Rate Threshold	5,000 msgs/s	<p>The maximum allowed message rate on the session. When the first non-session level message is received, a one second window begins. During the second no more than 4,999 additional non-session level messages will be allowed within that window. If the rate is exceeded, all new orders in the time window are rejected, modifies are treated as cancels, and cancels are processed.</p> <p>Maximum value is 5,000 msgs/sec.</p> <p>For Bulk Quoting ports, the default threshold is unlimited.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

Attribute	Default	Description
Symbol Order Rate Threshold	5,000 msgs/s	Functions the same as the Port Order Rate Threshold, but is calculated at the symbol level. It is capped by the Port Order Rate Threshold. Maximum value is 5,000 msgs/sec. For Bulk Quoting ports, the default threshold is unlimited.
Default <i>Account</i>	None	Default <i>Account</i> to be used if none is sent on inbound messages. Allows 16 characters or less (ASCII 33-126) but a max of 10 characters will be passed through to the OCC Customer ID Field.
Default <i>ClearingOptionalData</i>	None	Default <i>ClearingOptionalData</i> to be used if none is sent on inbound messages. Allows 16 characters or less (ASCII 33-126).
Default <i>FloorRoutingInst</i> * (C1 only)	E	D = Direct. Do not attempt to process electronically E = Electronic only X = Route to floor if unable to process electronically. * When <i>FloorRoutingInst</i> is "D" or "X", <i>RoutingInst</i> (9303) must be set to "B" or "R" for simple orders; for complex or FLEX instruments <i>RoutingInst</i> (9303) must be set to "B".
Default <i>FloorDestination</i> (C1 only)	None	Specifies a default PAR workstation (ex. W001) to route to on the floor (or "PARO" to route to the Floor PAR Official of the underlying symbol) if not specified on inbound messages. 4 characters or less (ASCII 33-126).
Default <i>EquityPartyID</i> (C1 only)	None	Default <i>EquityPartyID</i> to be used if none is specified on inbound messages.
Default <i>ClientIDAttr</i>	None	Default <i>ClientIDAttr</i> to be used if none is specified on inbound messages.
Enable Market Maker Floor Trade Notifications (C1 only)	No	Enables Market Maker Floor Trade Notifications for specific Market Maker acronyms on a port.
Market Maker Floor Trade Notification Symbology (C1 only)	Cboe	Specifies the symbology used on Market Maker Floor Trade Notifications. Cboe = Six character Cboe Symbol ID OSI = OSI Symbology (<i>PutOrCall</i> , <i>StrikePrice</i> , and <i>MaturityDate</i> will be returned) FLEX orders will always be returned using Cboe Symbology.

* Sponsored Participants require written approval from Sponsors to update these settings on ports associated with a Sponsor's MPID.

+ Port attribute can be overridden on an order-by-order basis.

^ Requires certification.

§ Not supported for quotes.

11 Support

Please email questions or comments regarding this specification to tradedesk@cboe.com.

Revision History

Date	Description
June 16, 2014	<i>Version 2.0.2</i> First public release of US Options BOE Version 2 specification.
July 1, 2014	<i>Version 2.0.3</i> Added Hours of Operations section. Corrected Cancel on Disconnect options.
July 3, 2014	<i>Version 2.0.4</i> Added field descriptions for <i>FeeCode</i> and <i>EchoText</i> .
July 7, 2014	<i>Version 2.0.5</i> Removed all return bits from <i>User Modify Rejected V2</i> messages. No optional return fields are allowed. Corrected a number of optional return bits. Added <i>RoutingInst</i> , <i>RoutStrategy</i> , <i>RouteDeliveryMethod</i> , and <i>ExDestination</i> as optional return bits (byte 8).
July 9, 2014	<i>Version 2.0.6</i> Corrected instances where <i>ContraCapacity</i> and <i>CorrectedSize</i> may be requested as optional return fields.
August 15, 2014	<i>Version 2.0.7</i> Added field descriptions for <i>RoutStrategy</i> , <i>ExDestination</i> , and <i>StopPx</i> .
August 22, 2014	<i>Version 2.0.8</i> Added Super Aggressive When Odd Lot <i>RoutingInst</i> value.
August 26, 2014	<i>Version 2.0.9</i> Added Reason Code of <i>w</i> (Would Remove on Unslide).
August 28, 2014	<i>Version 2.0.10</i> Corrected <i>Bulk Order V2</i> input bitelds.
September 3, 2014	<i>Version 2.0.11</i> Removed <i>SymbolSfx</i> from allowed fields for <i>New Order V2</i> . Removed <i>DiscretionAmount</i> and <i>PartyID</i> from allowed return bitfields for a number of messages. Corrected data type for <i>AcceptedCount</i> and <i>RejectedCount</i> to be Binary (not Text). Corrected data type for <i>BulkOrderRejectReasons</i> and <i>OrderRejectReason</i> to be Text (not Binary). Removed <i>AccessFee</i> from allowed return bitelds for <i>Order Restated V2</i> . Added clarification on <i>BulkOrderIDs</i> , <i>AskOrderID</i> , and <i>BidOrderID</i> . Added clarification on <i>BulkRejectReasons</i> , <i>AskRejectReason</i> and <i>BidRejectReason</i> .
September 8, 2014	<i>Version 2.0.12</i> Removed <i>ContraBroker</i> from List of Optional fields.
September 9, 2014	<i>Version 2.0.13</i> Removed <i>AccessFee</i> from <i>Order Execution V2</i> allowed return bitfields.
October 10, 2014	<i>Version 2.0.14</i> Claried ability to reuse <i>ClOrdId</i> with <i>Modify Orders</i> when daily limit trading risk controls are enabled.
November 13, 2014	<i>Version 2.0.15</i> Corrected <i>New Order V2</i> input bitelds to note that <i>DisplayIndicator</i> is permitted.

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

January 8, 2015	<p><i>Version 2.0.16</i></p> <p>Corrected <code>Order Execution V2</code> return bitfields to note that <i>SubLiquidityIndicator</i> is not allowed – it's already available in the message body.</p> <p>Minor correction of <i>PreventMatch</i> text (no functional change).</p>
February 19, 2015	<p><i>Version 2.0.17</i></p> <p>Added new <i>Capacity</i> values of N, B, and J, effective June 1, 2015.</p>
June 10, 2015	<p><i>Version 2.0.18</i></p> <p>Added Reason Code value of T.</p>
June 23, 2015	<p><i>Version 2.1.0</i></p> <p>Updated for EDGX Options.</p> <p>Added new fields <i>TargetPartyID</i> and <i>MarketingFeeCode</i>. Updated descriptions to note which fields are BZX Options or EDGX Options specific.</p>
June 23, 2015	<p><i>Version 2.1.1</i></p> <p>Added Duplicative Order Protection port attributes.</p>
October 26, 2015	<p><i>Version 2.1.2</i></p> <p>Added reason code of T.</p> <p>Updated <i>DisplayIndicator</i> description to note that, per EDGX Options Exchange rules, Display Price Sliding may not be combined with the Post Only instruction.</p>
October 27, 2015	<p><i>Version 2.1.3</i></p> <p>Added EDGX as possible <i>ContraBroker</i> value.</p>
October 31, 2015	<p><i>Version 2.1.4</i></p> <p>Corrected values for <i>MarketingFeeCode</i>.</p> <p>Changed text to note that <i>TargetPartyID</i> is simply copied back on all response messages.</p>
November 11, 2015	<p><i>Version 2.1.5</i></p> <p>Updated Pre-Market Queuing Session time to 7:30am, beginning December 11, 2015, pending SEC approval.</p>
December 24, 2015	<p><i>Version 2.1.6</i></p> <p>Updated description of <i>TargetPartyID</i> and <i>Capacity</i> for revised directed order functionality.</p> <p>Added Firm Risk Reset port attribute.</p> <p>Updated description of <i>ClearingFirm</i>.</p>
January 19, 2016	<p><i>Version 2.1.7</i></p> <p>Added Mercury as possible <i>ExDestination</i> and <i>ContraBroker</i> value.</p>
February 17, 2016	<p><i>Version 2.1.8</i></p> <p>Updated for new branding.</p>
February 25, 2016	<p><i>Version 2.1.9</i></p> <p>Added new <i>RestatementReason</i> value of P.</p>
March 23, 2016	<p><i>Version 2.1.10</i></p> <p>Updated description of <i>RoutStrategy</i> to state that routable ISOs must be sent using DIRC.</p> <p>Updated the minimum value of “Reject Orders on DROP Port Timeout” to be 0 seconds.</p>
May 16, 2016	<p><i>Version 2.1.11</i></p> <p>Added new field <i>AuctionID</i> and added S as a possible second character for <i>RoutingInst</i>, along with information about the Step-Up Mechanism (SUM).</p> <p><i>AuctionID</i> replaced <i>EffectiveTime</i> in <code>New Order V2</code> and all of the return bitfields.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

June 10, 2016	<i>Version 2.1.12</i> Display Price Sliding support eliminated for EDGX Options effective July 11, 2016.
June 28, 2016	<i>Version 2.1.13</i> Added new <i>SubLiquidityIndicator</i> of B for Step Up Mechanism.
August 3, 2016	<i>Version 2.1.14</i> WAIT orders will be eliminated upon migration of BZX Options to its next generation matching engine. Refer to Release Notes on Bats' public web site for deployment schedule.
August 17, 2016	<i>Version 2.1.15</i> Corrected <i>ExDestination</i> value of EDGX Options to be G.
September 2, 2016	<i>Version 2.2.0</i> Add new message types and fields to support cross orders (EDGX Only). Includes New Order Cross, Cross Order Acknowledgment, Cross Order Rejected, Cross Order Cancelled, and supporting fields. Effective 11/11/2016.
October 4, 2016	<i>Version 2.2.1</i> Add <i>RoutingFirmID</i> as a valid field for single order messages.
November 11, 2016	<i>Version 2.2.2</i> Added new <i>SubLiquidityIndicator</i> of b for Bats Auction Mechanism. Updated Display Price Sliding to indicate it is BZX only . Added clarification that <i>ClearingAccount</i> is required when <i>Capacity</i> is M or N.
December 15, 2016	<i>Version 2.2.3</i> Removed <i>RoutingInst</i> value of C (Book Only WAIT order). Clarified which <i>RoutingInst</i> values are allowed for Bulk Orders. Added port param for rejecting MM capacity orders if Cancel on Disconnect is disabled.
January 24, 2017	<i>Version 2.2.4</i> Added support for MIAX Pearl routing. Added 2 (Qualified Contingent Cross) as an acceptable <i>CrossType</i> for New Order Cross messages.
January 27, 2017	<i>Version 2.2.5</i> Added new message types and fields to support purge ports. Includes Purge Orders V2, Purge Rejected V2, and supporting fields. Modified New Order V2 message input bitfields to include the optional <i>CustomGroupID</i> field. Effective Date March 1, 2017. Added <i>RoutingFirmID</i> to Modify Order V2 and Cancel Order V2 messages.
February 27, 2017	<i>Version 2.2.6</i> Correct <i>MassCancel</i> field description in Purge Orders V2 message examples from lockout to single ack.
March 2, 2017	<i>Version 2.2.7</i> Add new field type <i>Date</i> .
March 22, 2017	<i>Version 2.2.8</i> Remove Suppress Cancels on Sessions Close port attribute.
March 22, 2017	<i>Version 2.2.9</i> Add descriptions of port attributes "Allow Test Symbols Only", "Port Order Rate Threshold", and "Symbol Order Rate Threshold".

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

May 11, 2017	<p><i>Version 2.3.0</i></p> <p>Add new message types and fields to support complex orders (EDGX Only). Includes New Complex Order, New Complex Instrument, Complex Instrument Accepted, Complex Instrument Rejected, and supporting fields. Effective 10/23/2017.</p>
June 13, 2017	<p><i>Version 2.3.1</i></p> <p>Removed support for <i>TimeInForce</i> value of 4 (Fill-or-Kill) on complex orders. Added clarification of valid <i>TimeInForce</i> values used with <i>RoutingInst</i> value of D on complex orders. Corrected options for port attribute "Cancel on Disconnect".</p>
July 7, 2017	<p><i>Version 2.3.2</i></p> <p>Corrected field type and size of <i>RevisedLegs</i>. Fixed naming inconsistency of <i>AttributedQuote</i> sometimes being called <i>AttributedOrder</i>. Claried symbology use on Order Execution V2 messages for complex orders.</p>
July 25, 2017	<p><i>Version 2.3.3</i></p> <p>Added <i>SecondaryExecId</i> to Order Execution V2. Added new Mass Cancel/Purge Request specication style using <i>MassCancelInst</i> field Effective 10/23/2017.</p>
July 28, 2017	<p><i>Version 2.3.4</i></p> <p>Updated description of use of <i>MassCancelInst</i> field in Purge Orders V2 message Effective 10/23/2017.</p>
August 3, 2017	<p><i>Version 2.3.5</i></p> <p>Added <i>RiskReset</i> and <i>CustomGroupId</i> to New Complex Order message.</p>
August 7, 2017	<p><i>Version 2.3.6</i></p> <p>Corrected size of <i>NoOfSecurities</i> field in message description and examples.</p>
August 9, 2017	<p><i>Version 2.3.7</i></p> <p>Added <i>ClearingFirm</i> optional field to New Complex Instrument message.</p>
August 14, 2017	<p><i>Version 2.3.8</i></p> <p>Corrected Purge Orders message biteld ordering and added <i>RoutingFirmID</i>.</p>
September 1, 2017	<p><i>Version 2.4.0</i></p> <p>Removed references to V2 as the V1 specification was deprecated. Added C2-specific references. Updated Cancel on Disconnect, Cancel on ME Disconnect, Cancel on DROP Port Disconnect and Cancel on Regulatory Halt to all provide GTC filtering.</p>
September 15, 2017	<p><i>Version 2.4.1</i></p> <p>Added support for C2 Feature Pack 1. Available in Certification effective 9/15/17 and in Production effective 10/13/17.</p>
October 5, 2017	<p><i>Version 2.4.2</i></p> <p>Updated explanatory text for <i>MassCancelInst</i> lockout behavior. <i>TimeInForce</i> = 2 (At the open) is supported effective 10/23/17. Updated C2 Feature Pack 1 effective date from 10/6/17 to 10/13/17. Removed introduction of <i>ContraTrader</i> and <i>ContraBroker</i> and depriication of <i>ContraCapacity</i> from C2 Feature Pack 1 release. Removed <i>Side</i> and <i>OrderQty</i> from the New Complex Instrument example.</p>
October 17, 2017	<p><i>Version 2.4.3</i></p> <p>Updated <i>Symbol</i> in Complex Instrument Accepted message to indicate this is the complex instrument id. Cboe branding/logo changes.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

November 7, 2017	<p><i>Version 2.4.4</i></p> <p>Updated to indicate that Bulk Order Acknowledgements are unsequenced. Corrected various spelling errors, field name and case inconsistencies. Updated Return Order Bitfields for Cross Order Acknowledgement, Cross Order Rejected and Cross Order Cancelled. Added C2 Feature Pack 2 enhancements for <i>ContraTrader</i> and <i>ContraBroker</i> values effective on 12/8/17.</p>
December 6, 2017	<p><i>Version 2.4.5</i></p> <p>Corrected Cross Order Cancelled message type to 0x46. Updated effective date of C2 Feature Pack 2 to 12/15/17.</p>
December 15, 2017	<p><i>Version 2.4.6</i></p> <p>Updated effective date of C2 Feature Pack 2 to 01/05/18 Corrected length of <i>DrillThruProtection</i> field. It is eight bytes.</p>
December 27, 2017	<p><i>Version 2.4.7</i></p> <p>Added Done For Day Restatement functionality. Protocol feature section 1.6.2 added to describe the feature. Done For Day Restatements port attribute added to enable and disable feature, which defaults to disabled. Default for Carried Order Restatements changed from enabled to disabled. Updated <i>Modify Order</i> message to clarify when an order loses time priority.</p>
January 12, 2018	<p><i>Version 2.4.8</i></p> <p>Fixed incorrect <i>GroupCnt</i> and <i>MessageLength</i> in Bulk Order example. Added GTC/GTD persistence across trading sessions to BZX and EDGX (Effective in EDGX on 1/26/18 and BZX on 2/2/18).</p>
January 24, 2018	<p><i>Version 2.4.9</i></p> <p>Removed reference to EFID needing to be registered in the underlying and <i>Capacity</i> needing to be set to 'M' in order to send Bulk Orders for C2 in section 4.1.6. GTCs and GTDs that expire on a future date cannot be sent on Bulk Order Ports. Added 'L' reason code to the list of reason codes in Section 8.</p>
January 30, 2018	<p><i>Version 2.4.10</i></p> <p>Added Post Only restriction for Bulk Order message on EDGX Options effective 3/23/18.</p>
February 20, 2018	<p><i>Version 2.5.0</i></p> <p>Update GTC/GTD functionality to allow order cancelation after trading sessions ends.</p>
March 21, 2018	<p><i>Version 2.5.1</i></p> <p>Updated OSI Root to Underlying symbology for EDGX Options (effective 6/11/18) and BZX (effective 6/25/18) Options. Removed <i>AllocQty</i> as an available return bitfield on Trade Cancel or Correct message.</p>
March 26, 2018	<p><i>Version 2.5.2</i></p> <p>Updating <i>RoutStrategy</i> (9400) default behavior to 'SWPA' for EDGX on 04/13/18 and BZX on 04/19/18.</p>
April 4, 2018	<p><i>Version 2.5.3</i></p> <p>Removed Post Only as a valid RoutingInst for Complex Orders on C2. Changed Default Attributed Quote on EDGX to Never.</p>
April 10, 2018	<p><i>Version 2.5.4</i></p> <p><i>CumQty</i> to be populated on leg fills related to complex executions (effective 4/27/18).</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

April 26, 2018	<p><i>Version 2.6.0</i></p> <p>Added optional fields to the <code>Purge Rejected</code> message to accommodate optional return of the <code>MassCancelld</code> field from the associated <code>Purge Request</code> message (Effective 6/29/18).</p> <p>Added <code>RestatementReason = S</code> for Ship and Post restatements.</p>
May 23, 2018	<p><i>Version 2.6.1</i></p> <p>Defined <code>StrikePrice</code> in the List of Optional Fields.</p> <p>Corrected the definition of <code>LegStrikePrice</code> to an eight byte, Binary Price field.</p> <p>Corrected OSI to Underlying Symbology effective dates.</p> <p>Additional clarification regarding valid <code>RoutingInst</code> values for BOE Bulk on EDGX and C2.</p>
May 30, 2018	<p><i>Version 2.6.2</i></p> <p><code>MassCancelld</code> moved to bit 8 from bit 1 in byte 15 of the Return Bitfields for a <code>Purge Rejected</code> message.</p>
June 29, 2018	<p><i>Version 2.6.3</i></p> <p>Updated <code>MassCancelInst</code> to indicate that 4th character is applicable to both C2 and EDGX. Added detail for 5th character, which was missing from the BOE specification.</p> <p>Corrected example for <code>Purge Rejected</code> message.</p>
August 7, 2018	<p><i>Version 2.6.4</i></p> <p>Updated information about mass cancel message rate limitations (effective 08/15/18).</p>
September 20, 2018	<p><i>Version 2.6.5</i></p> <p>For <code>Cancel Rejected</code> message added <code>MassCancelld</code> as an optional bitfield. (effective 9/14/18)</p> <p>Updated Bulk Port Order information to indicate that simple and complex auction responses are now accepted over Bulk Order Ports. (effective 10/5/18).</p>
October 8, 2018	<p><i>Version 2.7.0</i></p> <p>Added support for new message types and fields to support new quoting interface.</p> <p>Added effective dates for deprecating <code>Bulk Order</code> message type.</p> <p>Added support for <code>Risk Reset</code> message.</p>
October 19, 2018	<p><i>Version 2.7.1</i></p> <p>Added "R" Quote Reject Reason.</p> <p>Added support for C1 Migration Feature Pack 1, including support for complex reserve orders, <code>ClearingOptionalData</code> and EFID Group level risk functionality. Available in Certification effective 11/2/18 and in Production effective 11/29/18.</p>
October 26, 2018	<p><i>Version 2.7.2</i></p> <p>Added <code>Side</code> as a required field for <code>Quote Cancelled</code> and <code>Quote Restated</code> messages.</p>
November 5, 2018	<p><i>Version 2.7.3</i></p> <p>Clarifications added to the liquidity removal behavior for BOE Bulk/Quoting ports effective with C1 Feature Pack 2.</p> <p>Added Complex Post Only value of 'P' to <code>RoutingInst</code> (effective in EDGX and C2 TBD).</p>
November 9, 2018	<p><i>Version 2.7.4</i></p> <p>Added support for short form <code>Quote Update</code> message effective with C1 Feature Pack 2.</p>
November 16, 2018	<p><i>Version 2.8.0</i></p> <p>New message types, references, and fields in support of Cboe Options migration to Bats Tech.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

November 20, 2018	<p><i>Version 2.8.1</i></p> <p>Added <i>SubLiquidityIndicator</i> values for QCC and SAM.</p> <p>Updated definition for the value 'K' of Quote Restated message <i>RestatementReason</i> field.</p> <p><i>TradingSessionID</i> was named incorrectly and has been replaced by <i>SessionEligibility</i>. This field corresponds to Tag 336 in Cboe FIX. Allowed values have been changed as well as associated input and return bits.</p> <p>For <i>Reset Risk</i> message, corrected <i>RiskRoot</i> field length to 6.</p> <p>For <i>Bulk Order</i> message example, corrected <i>OsiRoot</i> to <i>RiskRoot</i>.</p> <p>Corrected name of optional field from <i>OsiRoot</i> to <i>RiskRoot</i>.</p>
November 27, 2018	<p><i>Version 2.8.2</i></p> <p>Added additional <i>RiskResetResult</i> values.</p> <p>Added "r = invalid remove" <i>QuoteResult</i> value.</p> <p>Noted that <i>Capacity</i> changes will not be honored when modifying a quote.</p> <p>Updated Default Attributed Quote port attribute for Cboe Options Exchange.</p> <p>Corrected <i>New Order Cross Multileg</i> message type to 0x5A.</p> <p>Updated effective date for Complex Post only to TBD.</p>
December 6, 2018	<p><i>Version 2.8.3</i></p> <p>Added <i>QuoteReason</i> codes D, m, u, and W.</p> <p>Removed incorrect <i>MaxFloor</i> and <i>DisplayRange</i> bit fields from <i>New Order Cross Multileg</i>.</p> <p>Updated port attribute details for <i>Cancel on Regulatory Halt</i> to indicate Cancel All is default for BZX and EDGX and Cancel None is default for C1 and C2.</p> <p>Added note to the optional fields, <i>Attributed Quote</i> and <i>ClientIDAttr</i>, indicating values available in C1 Feature Pack 4.</p> <p>Added note to <i>Default Attributed Quote</i> and <i>Default ClientIDAttr</i> port attributes indicating values available in C1 Feature Pack 4.</p>
December 20, 2018	<p><i>Version 2.8.4</i></p> <p>For <i>Reset Risk Acknowledgement</i> message, added <i><space>=Ignored</i> value to <i>RiskResetResult</i> field.</p> <p>Updated <i>New Order Cross Multileg</i>, <i>Price</i> field description to remove "Must be non-negative".</p> <p>Updated optional field <i>ExecInst</i> description to indicate it is used for <i>New Order Cross Multileg</i>.</p> <p>"Invalid Remove" quote result was incorrectly identified as 's' and was updated to be 'r' in <i>Quote Update Acknowledgement</i> message.</p> <p>Attributing by <i>ClientIDAttr</i> requires a value of "C" rather than "X" for the <i>AttributedQuote</i> field.</p> <p>Clarified use case and allowable granularity for <i>SendTime</i> on <i>Quote Update</i> message.</p>
January 11, 2019	<p><i>Version 2.8.5</i></p> <p>Updated description of <i>FloorDestination</i>.</p> <p>Corrected default value <i>Default FloorRoutingInst</i> port attribute to 'E' for Electronic only.</p> <p>Regarding <i>Login Response</i>, clarified that while a subset of units can be provided in the <i>Login Request</i>, all units will be provided in the <i>Login Response</i>.</p> <p>Added support for MIAX Emerald routing (effective 03/01/19).</p> <p>Added Floor Routing protocol feature for C1.</p> <p>Added support for Not Held orders (<i>ExecInst</i> (18) = 1) for C1.</p> <p>Updated descriptions for <i>Cancel on Disconnect</i> and <i>Cancel on ME Disconnect</i> Port Attributes for Bulk Quoting Ports.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

January 17, 2019	<p><i>Version 2.8.6</i></p> <p>Updated description of intra-day changes made to Port Attributes. For the <i>Quote Update Acknowledgement</i> message, removed "J" as a value for <i>QuoteResult</i> as it was replaced by newer rejection values. Added effective date for Complex Post only (EDGX 01/30/19 , C2 02/06/19).</p>
February 06, 2019	<p><i>Version 2.8.7</i></p> <p>Added Order Reason Code 'z' to section 8.1. Market orders are implicitly IOC for non-complex orders only. Added Simple Order Auction information related to BAM/AIM, SUM, and QCC for C1 Feature Pack 5.</p>
February 19, 2019	<p><i>Version 2.8.8</i></p> <p>Support added for Floor Representation restatements. Additional Protocol Feature added. Added <i>SessionEligibility</i> of "A" to <i>Quote Update</i> message. Updated reference to <i>SessionEligibility</i> FIX Tag, from 336 to 22017.</p>
March 1, 2019	<p><i>Version 2.8.9</i></p> <p>Added new value of 'f = Unsolicited Floor Action' to <i>RestatementReason</i> field on <i>Order Restated</i> message. Updated New Complex Order message type to not support legging in to the simple book on cross product spreads.</p>
March 13, 2019	<p><i>Version 2.8.10</i></p> <p>Updated effective date for SAM auctions to 04/29/19.</p>
March 18, 2019	<p><i>Version 2.8.11</i></p> <p>Added note identifying deprecation of <i>RestatementReason</i> 'Q' = <i>Liquidity</i> on <i>RestatementReason</i> field. Added notes identifying tags supporting AON Orders effective in C1 Feature Pack 6.</p>
March 29, 2019	<p><i>Version 2.9.0</i></p> <p>Removed Bulk Order message types and optional fields. Updated defaults for Cancel on Regulatory Halt port attribute. Replaced all references to BAM with AIM. Added <i>TiedHedge</i> optional field to New Complex Order message. Moved <i>FrequentTraderID</i> to the repeating group of New Order Cross and New Order Cross Multileg messages. Updated GTH trading hours to end at 9:15 a.m. ET. Renamed Late-Limit-On-Open orders to Settlement Liquidity orders.</p>
April 16, 2019	<p><i>Version 2.9.1</i></p> <p>Added clarification setting and using Match Trade Prevention (MTP) with BOE Bulk Quoting Ports and <i>Quote Update</i> messages.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

May 2, 2019	<p><i>Version 2.9.2</i></p> <p>Added <i>EquityPartyId</i> to Return Bitfields for Order Acknowledgement, Cross Order Acknowledgement, Order Rejected, Cross Order Rejected, Order Cancelled, Cross Order Cancelled and Order Execution messages.</p> <p>Added <i>EquityPartyId</i> to the Input Bitfields for New Complex Order and New Order Cross Multileg.</p> <p>Added clarification to <i>MassCancelInst</i> behavior when the Clearing Firm Filter is set to 'F'.</p> <p>Updated instructions for handling of <i>LegPositionEffect</i> for complex symbols with an equity leg.</p> <p>Updated GTH and added SessionEligibility field on QuoteUpdate message for C2 and EDGX, effective with C1 Feature Pack 7.</p> <p>Added note indicating reserve orders (<i>MaxFloor</i> greater than 0) will be rejected for Cboe proprietary classes, effective with C1 Feature Pack 7.</p> <p>Updated effective date for SAM auctions to TBD.</p>
May 15, 2019	<p><i>Version 2.9.3</i></p> <p>Added clarification to the Bulk Quote port order acceptance table on page 10.</p> <p>Added <i>PostingInstruction</i> values of 'N' and 'R' on the Quote Update and Quote Update Short messages. Added note indicating Quote Update Acknowledgement and Quote Cancelled messages will be unsequenced effective 07/08/19.</p>
May 31, 2019	<p><i>Version 2.9.4</i></p> <p>Added <i>SubLiquidityIndicator</i> value of "U" for Market Turner on C1.</p> <p>Corrections to New Complex Order example.</p>
June 14, 2019	<p><i>Version 2.9.5</i></p> <p>Added <i>QuoteResult</i> values of a, c, v, and V to Quote Update Acknowledgement message.</p> <p>Corrected corresponding FIX Tag value for <i>EquityTransactTime</i>.</p> <p>Added note indicating New Order Cross Multileg message will be supported on EDGX, effective on EDGX with C1 Feature Pack 8.</p> <p>Added <i>TimeInForce</i> optional field value of '7 = At the Close ', effective on BZX, C2, and EDGX with C1 Feature Pack 8.</p>
June 28, 2019	<p><i>Version 2.9.6</i></p> <p>Added notes indicating <i>EquityExDestination</i>, <i>EquityLegShortSell</i>, and <i>EquityPartyID</i> optional fields will be effective on EDGX with C1 Feature Pack 9.</p> <p>Add clarification to Quote Update Acknowledgement messages and Quote Cancelled message regarding messages changing to unsequenced effective 07/08/19.</p>
July 10, 2019	<p><i>Version 2.9.7</i></p> <p>Clarified preferred use of underlying symbol when specifying RiskRoot field.</p> <p>Updated effective date for C-AIM on EDGX to TBD.</p>
July 16, 2019	<p><i>Version 2.9.8</i></p> <p>Clarified statement regarding availability of Quote related messages over ODROP and FIXDROP as Quote Execution messages will be the only Quote related messages available.</p>

Cboe Options Exchanges
BOE Specification (Version 2.10.5)

July 31, 2019	<p><i>Version 2.10.0</i></p> <p>Added Add Floor Trade, Add Floor Trade Rejected, Floor Trade Confirmation, Floor Trade Confirmation Rejected, Delete Floor Trade, Delete Floor Trade Rejected and Delete Floor Trade Acknowledgement message types for C1 only.</p> <p>Added <i>TradeThroughAlertType</i> and <i>SenderLocationID</i> optional return bitfields for Order Execution message only for C1 only.</p> <p>Corrected <i>MessageType</i> hexadecimal value to 0x28 in Order Restated message example.</p> <p>Added Enable Floor Trade Notifications and Floor Trade Notification Symbology in the Port Attributes section.</p>
August 9, 2019	<p><i>Version 2.10.1</i></p> <p>Added clarification for <i>OpenClose field</i> in New Order Cross and Add Floor Trade messages for orders with OrderCapacity of M or N.</p> <p>Changed Return Bitfield <i>EquityNBBOProtect</i> to "Reserved".</p> <p>Updated notes for <i>FloorRoutingInst</i> to indicate that when <i>FloorRoutingInst</i> is "D" or "X", <i>RoutingInst</i> must be set to "B" or "R" for simple orders; for complex or FLEX instruments <i>RoutingInst</i> must be set to "B".</p> <p>Updated effective date for C-AIM on EDGX to 8/22/19.</p>
August 23, 2019	<p><i>Version 2.10.2</i></p> <p>Added <i>FloorTraderAcronym</i> as and optional return bit (byte 17) for the Order Execution message.</p> <p>Removed language indicating Cabinet and Sub-cabinet orders can have a <i>TimelnForce</i>(59) value of "GTD" or "IOC" since GTD and IOC orders cannot route to the floor.</p> <p>Updated <i>Order Modified</i> Return Bitfield to indicate Symbol field on second byte can be specified for a message.</p> <p>Clarified <i>ContraBroker</i> and <i>ContraTrader</i> to provide detail about what information will be provided for trades on the Cboe Options trading floor and for complex trades.</p>
August 30, 2019	<p><i>Version 2.10.3</i></p> <p>Removed note indicating a new <i>OrderID</i> will be assigned for an existing quote on a quote update.</p> <p>Added clarification to <i>Crossed Market Cancel/Reject</i> port setting indicating quotes are always accepted, even in a crossed market.</p>
September 5, 2019	<p><i>Version 2.10.4</i></p> <p>FLEX symbols are always returned using Cboe Symbology on MMTNs.</p> <p>Series restricted to closing only will accept opening transactions from both M and N capacities.</p>
September 18, 2019	<p><i>Version 2.10.5</i></p> <p>Removed "3=Entire multi-leg instrument package" from <i>MultilegReportingType</i> in Add Floor Trade message as this value is not valid.</p> <p>Added <i>PriceType</i> field to Floor Trade Confirmation, Floor Trade Notification, and Floor Trade Confirmation Rejected.</p> <p>Clarification added for rejects related to an invalid <i>ExecInst</i> value. If a value is supported on one message type, but invalid for another message type, then that will result in a reject.</p> <p>Self imposed risk lockouts will impact ability to send new orders or quotes, but not impact the ability to modify or cancel resting orders or quotes that are still live.</p>