



Cboe Titanium Cboe Global Indices Feed Specification

Introduction

The CBOE Streaming Market publishes index data using the message format defined in this document. Data is transmitted using the IP Multicast network protocol. To connect to the CFN network, refer to the [Cboe Titanium Cboe Futures Exchange Connectivity Manual](#).

System Overview

CBOE Streaming Market distributes index values. A **feed** is a set of one or more data channels. A **channel** consists of two Multicast groups in a primary/secondary architecture where the data is duplicated on the two Multicast groups for redundancy

Communication is one way only with no mechanism for retransmission. Messages are encoded using a mix of ASCII characters and binary data in the format defined in this document. The templates and message structures defined in this document are static and will not change over the course of the trading day, nor even in most software releases. Clients can expect sufficient advanced notice on any changes to these templates or message structures.

Hours of Operation

Messages will be published during these hours.

Table. Normal Market Hours (CT)

CHANNEL	DISSEMINATION TIME	CONNECTIVITY/HEARTBEATING
---------	--------------------	---------------------------

CHANNEL	DISSEMINATION TIME	CONNECTIVITY/HEARTBEATING
Cboe Global Indices Feed Main	24×6 (Sunday - Friday)	24×7
MSCI	8:30 a.m. - 7:15 p.m. (Monday - Friday)	
FTSE		
INAV		
MSTAR	24×6 (Sunday - Friday)	
CCCY	24×7	
CGI	2:00 a.m. - 7:15 p.m. (Monday - Friday)	
Cboe Global Indices Definition Feed	24×7 with periodic dissemination on a 15-minute interval maximum*	

*Any changes to the 15-minute maximum dissemination interval will be communicated in a future notice.

Data Feed and Message Overview

Data Feed Overview

The feed consists of one data channel. General characteristics of the feed include the following:

- The channel is duplicated and sent to 2 different multicast groups and ports over 2 networks in a primary / secondary configuration. Data sent to the primary and secondary multicast groups for each channel is identical.
- There are no retransmissions. Index values are computed and transmitted at regular intervals.
- A sequence number is sent for each message. This can be used to identify missed messages.
- Messages are placed into blocks (packets) for delivery which allows for multiple messages per block. The maximum block size is 1000 bytes.
- The message structures, field names and field values are based as much as possible on the FIX 5.0 SP2 standard. However, messages are encoded using a proprietary ASCII + binary format, and FIX tags are not transmitted in the data stream. The FIX format was used for the convenience of those familiar with the FIX

standard, so messages are defined in terms of FIX field names and FIX tags. Some user-defined fields were necessary for those fields not in the FIX specification, and some modifications to standard FIX fields are implemented for efficiency reasons.

Template ID Name Description

Table. Template ID Name Description

TEMPLATE ID NAME	DESCRIPTION
Index Value	Index value messages contain the values associated with a calculated index. For some indices, a bid and ask value may also be calculated which is like the index value but is calculated from bid and ask prices instead of last sale prices. Index values are benchmark values upon which tradable products may be based, but an index itself is not tradable. Index value messages are not sent using classKey and security IDs like other CSM feeds. Index values do not have a security definition associated with them, instead the index symbol is sent in every index value message.
Heartbeats	Heartbeat/line integrity messages are transmitted every 5 seconds. These messages may be used to determine a channel is working during times when market data is not transmitted on the feed (such as pre-market or post-market times).
Contributor Value	Contributor Value messages are used in conjunction with the Cboe Contributor API specification and contain values with associated times for a given symbol. For some symbols, the bid and ask value may also be populated.
Index Summary	Index Summary messages are used in conjunction with the Cboe Contributor API specification and provide either the open or close details and associated effective date for a given index. Bid and ask values may also be populated but are not required. Index Summary messages are not required and should not be assumed to be provided with Index Value messages.
Index Value with Status	Index Value With Status messages contain the values associated with a calculated index. Index values are benchmark values upon which tradable products may be based, but an index itself is not tradable. These index values contain a status describing if the value is indicative or not. Valid entry types also include close and settlement markers within the message.
Index Definition	Index Definition messages published in the Cboe Global Indices Definition Feed (CGIDF) contains index information including an index's current status (active, inactive, or deleted), channel name, current trading date, data source, and description. Index Definition messages published through the CGIDF can be used optionally in support

TEMPLATE ID NAME	DESCRIPTION
	of and in conjunction with the information provided across all other Cboe Global Indices Feed Channels.

Message Templates, Field Data Types and Data Encoding

Message Templates

Messages for the Cboe Streaming Market are described in this document in tabular text format and as an XML template. Templates define the content and characteristics of the messages to be encoded or decoded. Firms are encouraged to write software capable of using the XML templates to decode data from the CBOE Streaming Market.

XML templates are used to specify the structure, data types, field names, and FIX tags of a message:

Table. XML Based Template Example

<template name="MDIncRefresh" id="0">	Start of new template
<string name="MessageType" id="35" byteLength="1" value="X" />	Defines a String Data Type Field. The ID which represents the FIX Tag is not transferred on the wire.
<uInt32 name="MsgSeqNum" id="34" />	
<sequence name="MDEntries">	Defines the start of a repeating group
<length name="NoMDEntries" id ="268"/>	Length of repeating group
<string name="Symbol" id="55"/>	
<uInt32 name="Quantity" id="53 />	
</sequence>	End repeating group
</template>	End template

Template IDs

Each message structure is defined with a unique template ID. A template ID is a binary integer value stored as the first byte of every message identifying the message structure.

Template IDs are assigned from a common pool for the CBOE Streaming Market, so there may be gaps in numbering when either specification is updated. Numbers are assigned sequentially as they are needed for new message structures and old template ids are retired when new versions of the feed are launched.

Table. CBOE Streaming Market Templates and IDs

TEMPLATE NAME	TEMPLATE ID	ASSIGNED IN VERSION
Heartbeat	16	1.0
Index Value	22	1.0
Contributor Value	23	1.3.4
Index Summary	24	1.3.4
Index Value with Status	25	1.4.5
Index Definition	26	1.4.5

Field Data Types and Data Encoding

Fields defined in messages for the CBOE Streaming Market will have one of the following data types and methods of encoding:

- STRING
- SYMBOL
- INTEGER and LENGTH
- DECIMAL
- SEQUENCE

STRING Field

Strings are ASCII character arrays or single-byte characters. There are two types of string fields: Single Byte String and Character Array String. These string types are encoded as follows:

STRING TYPE	BYTELENGTH ATTRIBUTE	ENCODING	EXAMPLE
Single Byte String	=1	The string's length=1. The field is encoded as one byte.	MDEntryType field has byteLength="1". For example - "1" (Ask - see MD Entry Type) is encoded as the ASCII character 1 .
Character Array String	>1	The string's length is fixed. The field is encoded as a binary length byte, followed by the characters of the string.	EffectiveBusinessDate field has byteLength="8". For example - "20230815" is encoded as binary 0x08 followed by the ASCII characters 20230815 .
	Absent	The string's length is variable. The field is encoded as a binary length byte, followed by the characters of the string.	The Channel field byteLength attribute is absent. For example - "CGI" is encoded as 0x03 followed by the ASCII characters CGI . "MSTAR" is encoded as 0x05 followed by the ASCII characters MSTAR .

SYMBOL Field

Symbol field is encoded as a Character Array String field with byte length absent (variable length), but has a maximum length of 12 characters.

INTEGER and LENGTH Fields

Integer and Length fields are big endian binary encodings of numeric values. The **byteLength** attribute in a template field definition can act as a modifier to restrict the number of bytes used to encode the integer value. Unsigned integers are encoded as zero or positive-only values. The top-most bit is part of the magnitude of the

value. Signed integers are encoded as two's-complement binary values with the top-most bit as the sign bit. **Length** fields are unsigned integer values used to indicate the length of a **Sequence** field.

The table below shows the types of integer or length fields.

Table. Types of Integers / Length Fields

INTEGER FIELD TYPE	BYTE LENGTH	ENCODING	EXAMPLE
uint32	1	8 bit unsigned integer	<code><uint32 name="MDPriceLevel" id="1023" byteLength="1"/></code>
uint32	4 or omitted	32 bit unsigned integer	<code><uint32 name="MDEntrySize" id="271" byteLength="4"/></code>
uint64	8 or omitted	64 bit unsigned integer	<code><uint64 name="SendingTime" id="52"/></code>
int32	1	8 bit signed integer	<code><int32 name="MDPriceLevel" id="1023" byteLength="1"/></code>
int32	4 or omitted	32 bit signed integer	<code><int32 name="MDEntrySize" id="271"/></code>
int64	8 or omitted	64 bit signed integer	<code><int64 name="SendingTime" id="52" byteLength="8"></code>
length	1	8 bit unsigned integer	<code><length name="NoMDEntries" id="268" byteLength="1"/></code>

The table below shows the minimum and maximum values for different integer data types.

Table. Integer Data Type Min / Max Values

TYPE	MIN	MAX
uint32 with byteLength="1"	0	255
uint32	0	4,294,967,295
uint64	0	18,446,744,073,709,551,615
int32 with byteLength="1"	-128	127
int32	-2,147,483,648	2,147,483,647
int64	- 9,223,372,036,854,775,808	9,223,372,036,854,775,807

TYPE	MIN	MAX
length with byteLength="1"	0	255

DECIMAL Field

A decimal field is used to represent a floating point number as exponent and mantissa. The exponent is a signed 8 bit integer used to express precision and the mantissa is a signed 32 bit integer used to express the value. The numerical value is obtained by multiplying the mantissa with the base-10 power of the exponent expressed as: $\text{number} = \text{mantissa} * 10^{\text{exp}}$. The exponent and mantissa is decoded as a single, composite field.

Decimal fields are 5 bytes in length. The first byte is the exponent, and the remaining 4 bytes are the mantissa. For example, the number 0.90 is encoded as FE0000005A.

$\text{FE (exponent)} == -2, 0000005A \text{ (mantissa)} == 90, \text{value} == 90 * 10^{-2} == 90 * 0.01 == 0.90$

SEQUENCE Field

A sequence is a repeating group of fields. A length field encoded as an unsigned int immediately precedes the fields contained in the sequence. The length field is defined in a template with a special attribute of *<length*, and it can be modified with *byteLength* attribute. If *byteLength= "1"*, the encoded length field is a single 8-bit unsigned byte. All sequences transmitted to the CBOE Streaming Market use a single 8-bit unsigned length and can be no longer than 255 entries.

Sequences are encoded as follows:

Table. Encoded Sequences

Length	Group #1	Group #1	...	Group #1	Group #2	Group #2	...	Group #2	...
Field	Field #1	Field #2	...	Field #N	Field #1	Field #2	...	Field #N	...

Below is an example sequence with 2 MDentries elements:

Table. Example Sequence with 2 MDentries Elements

FIELD	LENGTH IN BYTES	VALUE	COMMENTS
NoMDentries	1	2	Length of MDentries Sequence

FIELD	LENGTH IN BYTES	VALUE	COMMENTS
MDEntryType	1	'0'	Bid entry
MDEntryPx	5	FE0000000A	FE == -2 exponent, 0000000A == 10 mantissa, value == 0.10
MDEntryType	1	'1'	Ask entry
MDEntryPx	4	FE00000010	FE == -2 exponent, 00000010 == 16 mantissa, value == 0.16

Packet and Message Header Format

All messages are sent in Multicast packets. Each packet consists of a packet header and one or more messages.

Table. Packet (Block) Format

PACKET HEADER					CONTENTS
Version	Length	Sending Time	Number of messages	First Msg Seq #	Messages...

Packet Header

Each packet has a packet header appearing once at the beginning of the packet. The packet header has the following structure:

Table. Packet Header

FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
Version	ulnt32	1	The version associated with the contents and format of this header. Currently, this will be a constant value of 1.
Length	ulnt32	2	Length of the packet including this length field and the version. Note this is a 2 byte length.
Sending Time	ulnt64	8	The time this packet was sent. It applies to all messages in this packet.

FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
Number of messages	uInt32	1	The number of messages in this packet.
First Msg Seq #	uInt32	4	The sequence number on the first message in this packet.

The version of a packet indicates the format of the packet. This may be incremented in future releases to indicate a change in the format of the packet. Initially, it is set to the number 1.

The Packet Length is encoded as a 2 byte (16 bit) unsigned integer including the length of the version, the 2 byte Packet Length itself, and the remainder of the packet.

The Sending Time is the time the CBOE Streaming Market application published the packet on the feed. The sending time is the millisecond timestamp from midnight, January 1, 1970 UTC.

The "First Msg Seq #" is the sequence number of the first message of this packet, and the "Number of Messages" indicates the total number of messages contained in the packet.

For verification of data at the channel level, one could compute the expected "first msg seq #" of the next packet by adding the number of messages to the current packet's "first msg seq #".

Message Header

A packet contains multiple messages. Each message is preceded by a message header common to all messages.

Table. Message Format

MESSAGE HEADER				CONTENTS		
TEMPLATE DEFINED FIELDS						
Length	Template ID	Msg Type	Msg Seq #	Field #1	...	Field #N

Table. Message Header

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Message Length	uInt32	2	The length of this message including the 2 bytes for this length field.

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Template ID	uInt32	1	The Template ID is for decoding the message. See CBOE Streaming Market Templates and IDs Table
35	MessageType	String	1	See Message Types Table
34	MsgSeqNum	uInt32	4	Sequence Number

The **Message Length** is encoded as a 2 byte (16 bit) unsigned integer including itself, the remainder of the message, and all Message Header fields.

The **Template ID** defines the specific structure of the message.

The **Message Type** defines the market data message type compliant to the FIX standard.

The message sequence number is a consecutively increasing number from the previous message. The first message in a packet will start with one number greater than the last message in the previous packet.

Table. Message Types

VALUE	MESSAGE TYPE
X	Contributor Value Index Summary Index Value Index Value with Status
D	Index Definition Message
0	Heartbeat

Note: Per specifications, message types can be shared; therefore, the body of the message is determined based on the template_id provided.

Message Sequence Numbers

Every packet has a "first" sequence number in the header. This is the number associated with the first message in the packet. Each subsequent message in the packet has a sequence number one greater than the previous message. The next packet will have a starting sequence number one more than the last message in the previous packet except for the start of the trading day's session and in the event of a Cboe system failure. When the session is started the sequence number will be reset to 1. During a Cboe system failure the sequence number

can reset to a lower value than was previously seen prior to the failure. In either case, the sequence number will again increase by one for each message.

Each channel of a feed has its own sequence number associated with it starting with sequence number 1. Verification of message sequence numbering must be done for each individual channel.

Firms must ensure that the sequence numbers maintain continuity. Any deviation from an expected sequence number must be considered as an error condition. Firms are required to take appropriate recovery action any time an unexpected sequence number is detected.

Recovery from Unexpected Message Sequence Numbers

Each message sent on a channel causes its **MsgSeqNumber** to increment by one. To detect missing data at the channel-level, compare each incoming **MsgSeqNumber** with the last received **MsgSeqNumber + 1**. If the incoming **MsgSeqNumber** is not equal to the (last received **MsgSeqNumber + 1**), data is missing from the channel.

Regardless of whether missing data is detected or not, the **MsgSeqNumber** of the incoming message should be stored associated with the channel so subsequent missing data can be detected.

When missing data is detected at the channel-level, all market data for products received over that channel should be treated as "suspect", meaning their market data may be incorrect. At the time missing data is detected on a channel, there is no way to know which index's data is missing, therefore all indexes received from that channel must be treated as though the market data for those indexes may be incorrect.

Indexes marked as suspect or possibly incorrect should remain in that state until an index value message for that index is received. Use it to update the suspect index's market data and mark the index's market data as no longer suspect.

Messages

Heartbeat Message (Line Integrity Message) - Template ID 16

Heartbeat messages contain only a standard header. The heartbeat will repeat at a regular interval.

Table. Heartbeat Message Structure

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Standard Header			See Message Types Table MessageType = "0" (zero)

Table. Heartbeat Template

<template	name="Heartbeat"	id="16"			>
<string	name="MessageType"	id="35"	byteLength="1"	value="0"	/>
<uint32	name="MSgSeqNum"	id="34"	byteLength="4"		/>
</template>					

Index Value - Template ID 22

Index value messages contain the values associated with a calculated index. They are transmitted when an index is calculated.

Market data associated with the index are contained in MDEntries with an MDEntryType indicating the kind of market data. The **Index Value** message may include any of the following MDEntryTypes. (See [Market Data Entry Types](#).)

- Index Value
- Bid
- Ask

At least one MDEntry with MDEntryType == Index Value will always be present in the **Index Value** message. For indices where a Bid and Ask index value is calculated, MDEntryTypes Bid and Ask will be present. For indices where Bid and Ask is not calculated, MDEntryTypes for Bid and Ask are omitted.

Table. Index Value Message Structure

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Standard Header			See Message Types Table MessageType = X

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
55	Symbol	symbol		Index Symbol / iNAV Symbol / Cryptocurrency
268	NoMDEntries	length	1	Number of MDEntries in this message. Will not exceed 255
Repeating Group - Fields Repeat NoMDEntries times				
269	MDEntryType	single byte string	1	Entry Type. See MD Entry Type Table 0=Bid 1=Ask 3=Index Value
270	MDEntryPx	decimal	5	Value associated with MDEntryType

Table. Index Value Template

<template	name="IndexValue"	id="22"			>
string	name="MessageType"	id="35"	byteLength="1"	value="X"	/>
<uint32	name="MsgSeqNum"	id="34"	byteLength="4"		/>
<symbol	name="Symbol"	id="55"			/>
<sequence	name="MDEntries"				>
<length	name="NoMDEntries"	id="268"	byteLength="1"		/>
< string	name="MDEntryType"	id="269"	byteLength="1"		/>
<decimal	name="MDEntryPx"	id="270"	byteLength="5"		/>
</sequence>					
</template>					

Contributor Value Message - Template ID 23

Contributor Value messages contain values associated with a given symbol or index. They are transmitted when received by Cboe.

At least one MDEntry with MDEntryType == Index Value will always be present in the **Contributor Value** message. For indices where a Bid and Ask index value is calculated, MDEntryTypes Bid and Ask will be present. For indices where Bid and Ask is not calculated, MDEntryTypes for Bid and Ask are omitted.

Table. Contributor Value Message Structure

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Standard Header			See Message Types Table MessageType = X
60	TransactTime	Unit64	8	Time that data was calculated or produced from client. Applies only to this message within the packet
55	Symbol	symbol		Index Symbol/iNAV Symbol / Cryptocurrency
268	NoMDEntries	length	1	Number of MDEntries in this message. Will not exceed 255
Repeating Group - Fields Repeat NoMDEntries times				
269	MDEntryType	single byte string	1	Entry Type. See MD Entry Type Table 0=Bid 1=Ask 3=Index Value
270	MDEntryPx	decimal	5	Value associated with MDEntryType.

Table. Contributor Value Template

<template	name="ContributorValue"	id="23"			>
<string	name="MessageType"	id="35"	byteLength="1"	value="X"	/>
<uint32	name="MsgSeqNum"	id="34"	byteLength="4"		/>
<uint64	name="TransactTime"	id="60"	byteLength="8"		/>
<symbol	name="Symbol"	id="55"			/>

<sequence	name="MDEntries"				>
<length	name="NoMDEntries"	id="268"	byteLength="1"		/>
<string	name="MDEntryType"	id="269"	byteLength="1"		/>
<decimal	name="MDEntryPx"	id="270"	byteLength="5"		/>
</sequence>					
</template>					

Index Summary - Template ID 24

Index Summary messages contain values associated with start or end of day values. An effective date is included for reference. Bid and ask fields are optional.

At least one MDEntry with MDEntryType == Index Value will always be present in the **Index Summary** message. For indices where a Bid and Ask index value is calculated, MDEntryTypes Bid and Ask will be present. For indices where Bid and Ask is not calculated, MDEntryTypes for Bid and Ask are omitted.

Table. Index Summary Message Structure

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Standard Header			See Message Types Table MessageType = X
60	TransactTime	Unit64	8	Time that data was calculated or produced from client. Applies only to this message within the packet
2400	EffectiveBusinessDate	string	8	YYYYMMDD format
20000	SummaryType	single byte string	1	Type of summary message. "1" SOD "2" EOD
55	Symbol	symbol		Index Symbol / iNAV Symbol / Cryptocurrency

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
268	NoMDEntries	length	1	Number of MDEntries in this message. Will not exceed 255
Repeating Group - Fields Repeat NoMDEntries times				
269	MDEntryType	single byte string	1	Entry Type. See MD Entry Type Table 0=Bid 1=Ask 3=Index Value
270	MDEntryPx	decimal	5	Value associated with MDEntryType

Table. Index Summary Template

<template	name="IndexSummary"	id="24"			>
< string	name="MessageType"	id="35"	byteLength="1"	value="X"	/>
<uint32	name="MsgSeqNum"	id="34"	byteLength="4"		/>
<uint64	name="TransactTime"	id="60"	byteLength="8"		/>
<string	name="EffectiveBusinessDate"	id="2400"	byteLength="8"		/>
<length	name="SummaryType"	id="20000"	byteLength="1"		/>
<symbol	name="Symbol"	id="55"			/>
<sequence	name="MDEntries"				>
<length	name="NoMDEntries"	id="268"	byteLength="1"		/>
<string	name="MDEntryType"	id="269"	byteLength="1"		/>
<decimal	name="MDEntryPx"	id="270"	byteLength="5"		/>
</sequence>					
</template>					

Index Value With Status - Template ID 25

Index Value With Status messages contain the values associated with a calculated index. They are transmitted when an index is calculated.

Market data associated with the index are contained in MDEntries with an MDEntryType indicating the type of market data. The **Index Value With Status** message may include any of the following MDEntryTypes. See [Market Data Entry Types](#).

- Bid
- Ask
- Index Value
- Close Value
- Settlement / EDSP Price

If **MDEntryType** == Index Value, the message may also have a Bid/Ask value but will not have a Settlement/EDSP or CloseMDEntryType, the message will not contain any other MDEntrytypes.

Table. Index Value with Status Message Structure

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Standard Header			See Message Types Table MessageType =X
20001	Index Status	single byte string	1	N=Normal I=Indicative
55	Symbol	symbol		Index Symbol/iNAVSymbol
268	NoMDEntries	length	1	Number of MDEntries in this message. Will not exceed 255.
Repeating Group - Fields Repeat NoMDEntries times				

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
269	MDEntryType	single byte string	1	Entry Type. See Market Data Entry Types 0=Bid 1=Ask 3=Index Value 5=Close Value 6=Settlement / EDSP Price
270	MDEntryPx	decimal	5	Value associated with MDEntryType

Table. Index Value with Status Template

<template	name="IndexValueWithStatus"	id="25"			>
< string	name="MessageType"	id="35"	byteLength="1"	value="X"	/>
<uint32	name="MsgSeqNum"	id="34"	byteLength="4"		/>
<length	name="IndexStatus"	id="20001"	byteLength="1"		/>
<symbol	name="Symbol"	id="55"			/>
<sequence	name="MDEntries"				>
<length	name="NoMDEntries"	id="268"	byteLength="1"		/>
<string	name="MDEntryType"	id="269"	byteLength="1"		/>
<decimal	name="MDEntryPx"	id="270"	byteLength="5"		/>
</sequence>					
</template>					

Index Definition Message - Template ID 26

An **Index Definition** message will be published for every index within each cycle, repeating on a regular interval no longer than 15 minutes. Messages within each cycle will be published at a rate of 4 per second

(subject to change). Any index status changes occurring during an in-progress cycle will be reflected in the next cycle.

Clients are required to capture at Current Record Number = 1 to receive the complete series of **Index Definition** messages.

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Standard Header			See Message Types Table MessageType=D
	Current Record Number	uint32	4	Clients should begin capturing data beginning at 1.
911	Total Number of Records	uint32	4	Total number of updates within loop.
	Symbol	symbol		External index symbol.
	Description	string	Variable	Description of the index.
	Date	string	10	YYYY-MM-DD format.
	Status	uint32	1	Status of Index: 1 = Active - loaded and a business day 2 = Inactive - loaded and not a business day 3 = Deleted - no longer distributed (removed from the feed after '30' days)
	Agent Classification	two byte string	2	Originating source of the index: <blank> = Not Specified CO = Cboe CC = Cboe Custom MS = Morningstar TP = Third-party MC = Morningstar Customer
Repeating Group				

FIELD ID	FIELD NAME	TYPE	LENGTH (BYTES)	COMMENTS
	Channel	string	Variable	Sequence Group of the following types: MAIN = Cboe Global Indices Feed Main CGI = Strategy, Benchmark, and Custom Indices MSCI = MSCI INAV = Intraday Net Asset Values FTSE = FTSE Russell MSTAR = Morningstar CCCY = Crypto Currency

Market Data Entry Types

Table. MD Entry Type

MARKET DATA ENTRY TYPE (MDENTRYTYPE)	MARKET DATA ENTRY NAME
0	Bid
1	Ask
3	Index Value
5	Close
6	Settlement / EDSP Price

Appendix A - Multicast Group and Port Information

Please contact [Cboe NOC](#) for access to the Cboe Global Indices Feed platform certification, production, and DR environments.

DATA CHANNEL	LOCATION	TYPE	RP	SOURCE IP	IP	PORT
Cboe Global Indices Feed Main	NY5 Prod DC	Primary	74.115.128.168	174.136.169.32/29	224.0.131.168	30201
		Secondary	74.115.128.169	174.136.169.40/29	233.130.124.168	30201
	DR DC	Primary	170.137.16.130	170.137.16.192/29	233.182.199.8	31201
	NY5 Cert DC	Primary	74.115.128.166	174.136.160.32/29	224.0.74.176	32201
MSCI	NY5 Prod DC	Primary	74.115.128.168	174.136.169.32/29	224.0.131.169	30201
		Secondary	74.115.128.169	174.136.169.40/29	233.130.124.169	30201
	DR DC	Primary	170.137.16.130	170.137.16.192/29	233.182.199.9	31201
	NY5 Cert DC	Primary	74.115.128.166	174.136.160.32/29	224.0.74.177	32201
FTSE	NY5 Prod DC	Primary	74.115.128.168	174.136.169.32/29	224.0.131.170	30201
		Secondary	74.115.128.169	174.136.169.40/29	233.130.124.170	30201
	DR DC	Primary	170.137.16.130	170.137.16.192/29	233.182.199.10	31201
	NY5 Cert DC	Primary	74.115.128.166	174.136.160.32/29	224.0.74.178	32201
CCCY	NY5 Prod DC	Primary	74.115.128.168	174.136.169.32/29	224.0.131.171	30201
		Secondary	74.115.128.169	174.136.169.40/29	233.130.124.171	30201
	DR DC	Primary	170.137.16.130	170.137.16.192/29	233.182.199.11	31201
	NY5 Cert DC	Primary	74.115.128.166	174.136.160.32/29	224.0.74.179	32201
INAV	NY5 Prod DC	Primary	74.115.128.168	174.136.169.32/29	224.0.131.172	30201
		Secondary	74.115.128.169	174.136.169.40/29	233.130.124.172	30201
	DR DC	Primary	170.137.16.130	170.137.16.192/29	233.182.199.12	31201
	NY5 Cert DC	Primary	74.115.128.166	174.136.160.32/29	224.0.74.180	32201

DATA CHANNEL	LOCATION	TYPE	RP	SOURCE IP	IP	PORT
MSTAR	NY5 Prod DC	Primary	74.115.128.168	174.136.169.32/29	224.0.131.173	30201
		Secondary	74.115.128.169	174.136.169.40/29	233.130.124.173	30201
	DR DC	Primary	170.137.16.130	170.137.16.192/29	233.182.199.13	31201
	NY5 Cert DC	Primary	74.115.128.166	174.136.160.32/29	224.0.74.181	32201
CGI	NY5 Prod DC	Primary	74.115.128.168	174.136.169.32/29	224.0.131.175	30201
		Secondary	74.115.128.169	174.136.169.40/29	233.130.124.175	30201
	DR DC	Primary	170.137.16.130	170.137.16.192/29	233.182.199.15	31201
	NY5 Cert DC	Primary	74.115.128.166	174.136.160.32/29	224.0.74.183	32201
Cboe Global Indices Definition Feed	NY5 Prod DC	Primary	74.115.128.168	174.136.169.32/29	224.4.7.0	30201
		Secondary	74.115.128.169	174.136.169.40/29	234.170.137.0	30201
	DR DC	Primary	170.137.16.130	170.137.16.192/29	224.4.7.128	31201
	NY5 Cert DC	Primary	74.115.128.166	174.136.160.32/29	234.170.137.128	32201

Appendix B - Packet Example, Replay Data, and Bandwidth Requirements

Understanding the Hex Data Diagrams

Hexadecimal printouts of data from a channel are included in the following examples. Each example is in a similar format.

Table. Example Format

OFFSET		HEXADECIMAL		DATA 4 BYTES PER GROUP ASCII REPRESENTATION	
00000000	CD580000	00030000	0134C8E5	A8992B6C	.X.....4....+
00000010	031FFE00	00006600	00006401	00	f...d..

The first column of numbers is the zero-based byte offset of the first hex byte on that line, expressed as a hexadecimal offset. The next 4 columns of data are hexadecimal values for the bytes, with 4 bytes per group. Spaces are for formatting purposes only. Characters between pipes (|) are ascii representations of the hex data. Periods indicate non-printable values.

The first 16 bytes of each hex dump is the packet header.

Packet Header Example

Table. Packet Header Hex Dump

00000000	01038B00	000135A6	B387070B	00000000	5.....
----------	----------	----------	----------	----------	-------------

Table. Packet Header Decoded

SendTime(02/22 14:14:37.831)
BlkVersion(1) BlkSize(907) MsgsInBlock(11) FirstMsgSeq(0)

Index Message Example

Table. Index Hex Dump

00000000	01002F00	00015023	AC595A01	00000002	../...P#.YZ.....
00000010	001F1658	00000002	034F4558	0333FE00	...X.....0EX.3..
00000020	014B6030	FE00014B	4E31FE00	014B71	.K`0...KN1...Kq

Table. Index Decoded

Message#(1) MsgSize(31)

TemplateId(22)	TemplateName(IndexValue)	AppMsg: IndexValue	Type: X
FieldType	FieldName	Id	Value
sbSTRING:	MessageType	35	X
UINT32:	MsgSeqNum	34	2
STRING:	Symbol	55	OEX
SEQUENCE:	NoMDEntries	268	Len=3
MSG_GROUP NumElems: 2			
sbSTRING:	MDEntryType	269	3
uDECIMAL:	MDEntryPx	270	848.32
MSG_GROUP NumElems: 2			
sbSTRING:	MDEntryType	269	0
uDECIMAL:	MDEntryPx	270	848.14
MSG_GROUP NumElems: 2			
sbSTRING:	MDEntryType	269	1
uDECIMAL:	MDEntryPx	270	848.49

Heartbeat Message

Table. Heartbeat Hex Dump

00000000	01001800	000135A7	00C6C901	00000F95	5.....
00000010	00081030	00000F95			...0....

Table. Heartbeat Decoded

Message#(1) MsgSize(8)

TemplateId(16)	AppMsg: Heartbeat	Type: 0	
FieldType	FieldName	Id	Value
sbSTRING:	MessageType	35	0
UINT32:	MsgSeqNum	34	3989

Support

Questions regarding this document can be directed to the Cboe Operations Support Center (OSC) at 312.786.7635 or indexsupport@cboe.com. The latest version of this document can be found on the [Indices microsite](#).

Revision History

DATE	VERSION	DESCRIPTION OF CHANGE
09/17/15	1.0	New document
12/07/15	1.1	Updated the cover page to reference indices
12/10/15	1.2	Updated MD-EntryType table reference.
06/07/16	1.2	Updated the Index Options market hours start time from 5:00 a.m. to 2:00 a.m.
08/30/17	1.3	Updated Appendix A - Multicast Group and Port Information. Include FTSE, Cryptocurrency, and INAV.
09/01/17	1.3.1	Updated primary and secondary multicast group IPs for new Cboe Global Indices Feed platform.
10/17/17	1.3.2	Cboe branding/logo changes.
02/06/18	1.3.3	Updated date for parallel testing over 5 channels.
02/28/22	1.3.4	Added notes to support Contributor API protocol (effective 05/01/22).
03/11/22	1.3.5	Updated comments for Symbol field (55) to "Index Symbol/iNAV Symbol".
06/01/22	1.4	CSMI rebranded to Cboe Global Indices Feed. All references are updated (effective 06/02/22). MSTAR and MSTARC channels added to Multicast Group and Port Information.
06/14/22	1.4.1	Updated MSTARC Secondary IP Address.

DATE	VERSION	DESCRIPTION OF CHANGE
06/30/22	1.4.2	Minor updates to "Index Value" message and "Contributor Value" message references.
07/26/22	1.4.3	Minor formatting updates.
08/08/22	1.4.4	Updated hours of operation.
02/28/23	1.4.5	Added new CGI Index Channel and Index Values with Status messages.
03/13/23	1.4.6	Added new Cboe Global Indices Definition Feed Channel and new Index Definition message (effective 03/27/23).
03/16/23	1.4.7	Updated Index Definition "MessageType=D". Updated Index Definition publication rate to 4 per second. Updated section 5.5 to indicate that if MDEntryType == 'Index Value', the message may also have a Bid/Ask value but will not have 'Settlement/EDSP' or 'Close' prices.
04/14/23	1.4.8	Updated CGI NY5 cert IP address. Updated CGI dissemination end time to 10:30 a.m. CT.
08/16/23	1.4.9	Updated Symbol field character length. Updated Character Array String information. In Channel field of Index Definition message, updated CSMI to "Cboe Global Indices Feed Main=Main" and updated CGI to "CGI=Strategy, Benchmark, and Custom Indices".
03/13/24	1.4.10	Added new agent classifications MC and MS to Index Definition message (effective 06/23/24). Updated CGI dissemination end time to 7:15 p.m.
07/12/24	1.4.11	Removed references to MSTARC.
01/15/25	1.4.12	Updated with Cboe Titanium branding. Updated Cboe Global Indices Feed Main hours of operation to 24x6 (Sunday - Friday). Renamed Message Overview section to Template ID Name Description . Minor formatting updates.
05/16/25	1.4.13	Minor formatting updates to String Field .



©2026 Cboe Exchange, Inc. All rights reserved.

About

[About Us](#)

[Careers](#)

[Cboe Empowers](#)

[Corporate Stewardship](#)

[Hours & Holidays](#)

[Investor Relations](#)

[Press Releases](#)

[Public Policy](#)

Legal

[Accessibility](#)

[Biometric Information Privacy Policy](#)

[California Notice at Collection](#)

[Copyright, Trademark & Patents](#)

[Disclaimers](#)

[Email Management](#)

[Notice of Financial Incentive](#)

[OCC & Investor Protection](#)

[Privacy Statement](#)

[Terms & Conditions](#)

[Use of Content](#)

[Your Privacy Choices](#) 

[Do Not Sell or Share My Personal Information](#)