DEUTSCHE BÖRSE GROUP

Deutsche Börse Group's T7

FIX LF Interface

Derivatives Message Reference

Release 14.1

FIX LF Version	14.1
FIX LF Subversion	D0001
Build Version	141.440.0.ga-141004040-43
Date	19 February 2026

Deutsche Börse Group's T7 Release 14.1
FIX LF Interface
Derivatives Message Reference

Deutsche Börse Group

Build 141.440.0.ga-141004040-43

Disclaimer

© Deutsche Börse Group 2026

This content is for informational purposes only. None of the information constitutes investment advice or an offer to sell or the solicitation of an offer to buy any contract, share or other financial instrument. This content is only for use as general information and all descriptions, examples and calculations contained are for illustrative purposes only.

Deutsche Börse AG, Frankfurter Wertpapierbörse (FWB®, the Frankfurt Stock Exchange), Eurex Frankfurt AG, Eurex Deutschland and Eurex Clearing AG do not represent that the information in this publication is comprehensive, complete or accurate and exclude liability for any consequence resulting from acting upon the contents of this or another publication, in so far as no willful violation of obligations took place or, as the case may be, no injury to life, health or body arises or claims resulting from the Product Liability Act are affected.

Securities traded on the Frankfurt Stock Exchange and Eurex derivatives (other than EURO STOXX 50® Index Futures contracts, EURO STOXX® Select Dividend 30 Index Futures contracts, STOXX® Europe 50 Index Futures contracts, STOXX® Europe 600 Index Futures contracts, STOXX® Europe Large/Mid/Small 200 Index Futures contracts, EURO STOXX® Banks Sector Futures contracts, STOXX® Europe 600 Banks/Industrial Goods & Services/Insurance/Media/Personal & Household Goods/Travel & Leisure/Utilities Futures contracts, DAX® Futures contracts, MDAX® Futures contracts, TecDAX® Futures contracts, SMIM® Futures contracts, SLI Swiss Leader Index® Futures contracts, Eurex inflation/commodity/weather/property and interest rate derivatives) are currently not available for offer, sale or trading in the United States nor may they be offered, sold or traded by persons to whom US tax laws apply.

The fund shares listed in XTF Exchange Traded Funds® are admitted for trading on the Frankfurt Stock Exchange. Users of this information service who legally reside outside Germany are herewith advised that sale of the fund shares listed in XTF Exchange Traded Funds may not be permitted in their country of residence. The user makes use of the information at their own risk.

Legal validity of this disclaimer

In the event that individual parts of or formulations contained in this text are not, or are no longer, legally valid (either in whole or in part), the content and validity of the remaining parts of the document are not affected.

Trademarks

The names and designations listed under www.deutsche-boerse.com/disclaimer are registered trademarks of Deutsche Börse AG or an affiliate of Deutsche Börse Group.

The names and trademarks listed there do not represent a complete list and, as well as all other trademarks and protected rights mentioned in this publication, are subject unreservedly to the applicable trademark law in each case and are not permitted to be used without the express permission of the registered owner. The simple fact that this publication mentions them does not imply that trademarks are not protected by the rights of third parties.

Information on trademarks of Stoxx Ltd. and ISS STOXX Index GmbH are available under www.stoxx.com/trademarks.

EEX® is a registered trademark of European Energy Exchange AG.

TRADEGATE® is a registered trademark of Tradegate AG Wertpapierhandelsbank.

Flexible is better.® is a registered trademark of Axioma, Inc.

Contents

1 List of Abbreviations **4**

2 Introduction **5**

3 Change Log **5**
3.1 T7 Release 14.1 – Version 1 (FIX LF 14.1 - D0001) . . . 5

4 Message Formats **5**
4.1 Data Types . . . 6

5 Overview of Supported Message Types **8**

6 Message Header and Trailer **9**
6.1 Header . . . 9
6.2 Trailer . . . 11

7 Administrative Messages **12**
7.1 Session Logon . . . 13
7.2 Session Logout . . . 15
7.3 Heartbeat . . . 16
7.4 Test Request . . . 17
7.5 Resend Request . . . 18
7.6 Reject . . . 19
7.7 Sequence Reset . . . 20

8 Application Messages **21**
8.1 User Request . . . 22
8.2 User Response . . . 23
8.3 User Notification . . . 24
8.4 New Order Single . . . 25
8.5 New Order Multileg . . . 31
8.6 Order Cancel/Replace Request . . . 37
8.7 Multileg Order Cancel/Replace Request . . . 43
8.8 Order Cancel Request . . . 49
8.9 Execution Report . . . 52
8.10 Order Mass Action Request . . . 61
8.11 User Order Mass Action Report . . . 65
8.12 Business Message Acknowledgment . . . 68
8.13 Business Message Reject . . . 69
8.14 Security Definition Request . . . 71
8.15 Security Definition Response . . . 74
8.16 Cross Request . . . 77
8.17 Quote Request . . . 79
8.18 Trading Session Status . . . 82
8.19 User Party Entitlements Update Report . . . 83
8.20 User Party Action Report . . . 85
8.21 User Party Risk Limits Update Report . . . 87
8.22 User Party Risk Limits Request . . . 89
8.23 User Party Risk Limits Report . . . 91
8.24 CLIP Enter Request . . . 93
8.25 CLIP Delete Request . . . 101
8.26 CLIP Response . . . 104
8.27 Session Details List . . . 106
8.28 Trade Capture Report . . . 107

9 Occurrences **117**

9.1 OrderAttributeGrp . . . 117
9.2 Parties . . . 118
9.3 RequestingParties . . . 123
9.4 RootParties . . . 124
9.5 TargetParties . . . 125
9.6 TrdCapRptSideGrp . . . 126
9.7 ValueChecksGrp . . . 128

Contents

1 List of Abbreviations

Please find a list of all the abbreviations used in the document.

FIX	Financial Information eXchange
TCP/IP	Transmission Control Protocol / Internet Protocol
TES	T7 Entry Service
GUI	Graphical User Interface
EMS	Execution Management System
OMS	Order Management system

2 Introduction

The Deutsche Börse Group's T7 is the industry-leading, multi-asset trading platform of the Deutsche Börse Group, its affiliates and partners.

The system has best-in-class performance and is scalable to support markets of any size. It can be customized to support different types of markets.

The T7 FIX LF interface is intended for participants that require a standard FIX connection to the exchange and supports all T7 market types.

The document "T7 FIX LF Manual" provides the description of the main concepts for all supported market types (cash and derivatives).

The purpose of this document is to provide all message formats for the derivatives market part of the FIX LF interface.

In addition to this document two corresponding XML files, the QuickFix Engine dictionary and a message reference file including message and field descriptions are published.

The FIX LF interface will make use of the FIX 4.4 version only.

3 Change Log

3.1 T7 Release 14.1 – Version 1 (FIX LF 14.1 - D0001)

Changes to the T7 Release – 14.0 Version 1:

- added valid value *SPONSORED_ACCESS(105)* to field *OrderOrigination* in messages CLIP Enter Request (U29), Multileg Order Cancel/Replace Request (AC), New Order Multileg (AB), New Order Single (D), Order Cancel/Replace Request (G), Order Cancel Request (F), Trade Capture Report (AE), Order Mass Action Request (UCA)
- updated description of message Quote Request (R)
- updated cardinality of structure *RegulatoryTradeIDGrp* in message Trade Capture Report (AE)
- removed valid value *DELTA_NEUTRAL_TRADE_AT_MARKET(1017)* in field *TrdType* from message Trade Capture Report (AE)
- added field *RiskLimitGroupStatus* in message User Party Risk Limits Report (UCM)
- added valid value *Pretrade_Risk_Limit_Exceeded(10016)* to field *BusinessRejectReason* in message Business Message Reject (j)

4 Message Formats

The following chapters provide details on the administrative and application messages used by FIX LF. Additionally, information on data types is provided.

The interface version used by the participant needs to be provided during Logon in *DefaultCstmApplVerID (1408)*; the corresponding response message will return the interface version, which the FIX LF Gateway currently uses, in the same field.

The interface version will allow the participant to recognize that FIX LF has changed. The build number shows to which FIX LF XML file, and the FIX LF message reference belongs to.

4.1 Data Types

FIX LF supports the following data types:

Data Type	Description
STRING	Alphanumeric free format strings containing characters from the following set: \x20,\x23-\x25, \x28-\x2A, \x2C-\x3B, \x3F, \x41-\x5F, \x61-\x7B, \x7D,\x7E.
INT (based on STRING)	Sequence of digits without commas or decimals and optional leading sign character.
FLOAT (based on STRING)	Sequence of digits with optional decimal point and leading sign character.
CHAR (based on STRING)	Single character value, can include any alphanumeric character.
BOOLEAN (based on CHAR)	Char field containing either 'Y' or 'N'.
MULTIPLEVALUESSTRING (based on STRING)	String containing one or more space delimited char fields.
LOCALMKTDATE (based on STRING)	Date of Local Market in YYYYMMDD format.
CURRENCY (based on STRING)	ISO currency code (3 characters).
LENGTH (based on INT)	Length of the FIX LF message in bytes. Value must be positive.
SEQNUM (based on INT)	Message sequence number. Value must be positive.
NUMINGROUP (based on INT)	Number of entries in a repeating group. Value must be positive.
QTY (based on FLOAT)	FLOAT (15.4) field with 15 digits before decimal point and at most 4 significant decimal places.
PRICE (based on FLOAT)	FLOAT (11.8) field representing a price with 11 digits before decimal point and at most 8 significant decimal places.
AMT (based on FLOAT)	FLOAT (11.8) field representing a prices times a quantity with 11 digits before decimal point and at most 8 significant decimal places.
UTCTIMESTAMP (based on STRING)	Time/date combination in YYYYMMDD-HH:MM:SS[.sssssssss] format. The milli/micro/nanosecond part is optional. The FIX LF gateway provides timestamps in seconds only.

Data Type	Description
PERCENTAGE (based on FLOAT)	FLOAT (3.7) field representing a percentage with 3 digits before decimal point and at most 7 significant decimal places.

5 Overview of Supported Message Types

The following message formats are based on:

- Interface Version: 14.1
- Build Number: 141.440.0.ga-141004040-43

Additionally, FIX LF clients implementing interface version '14.0' will be supported. Please refer to chapter Change Log for details regarding interface changes between the FIX LF versions '14.0' and '14.1'.

6 Message Header and Trailer

6.1 Header

Tag	Field Name	Req'd	Data Type	Description
8	BeginString	Y	STRING	Identifies beginning of new message and protocol version. Value: FIX.4.4 — Description: VERSION 44
9	BodyLength	Y	LENGTH	Message length, in bytes, forward to the CheckSum field.
35	MsgType	Y	STRING (1-4)	Defines the message type. Valid values are listed after this table.
34	MsgSeqNum	Y	SEQNUM	Message sequence number
43	PossDupFlag	N	BOOLEAN	Indicates possible retransmission of message with this sequence number. The valid value 'Y' can only be set by FIX LF. N — Original transmission Y — Possible duplicate
49	SenderCompID	Y	STRING	Assigned identifier of the party sending the message.
52	SendingTime	Y	UTCTIMESTAMP	Time of message transmission.
56	TargetCompID	Y	STRING	Assigned identifier of the party receiving the message. For requests the field must be set to the XMIC code (e.g. XETR) the related FIX LF session belongs to. For responses/notification the field is set to the client's compID.
97	PossResend	N	BOOLEAN	Indicates that message may contain information that has been sent under another sequence number. The valid value 'Y' can only be set by FIX LF. N — Original transmission Y — Possible Resend
122	OrigSendingTime	N	UTCTIMESTAMP	Required if PossDupFlag (43) = "Y".

Valid Values of MsgType (datatype STRING(1-4))

Valid Value	Description
0	Heartbeat
1	Test Request
2	Resend Request
3	Reject
4	Sequence Reset
5	Logout
8	Execution Report
A	Logon
D	New Order Single Request
F	Order Cancel Request
G	Order Cancel/Replace Request
AB	New Order Multileg Request
AC	Multileg Order Cancel/Replace Request
AE	Trade Capture Report
BE	User Request
BF	User Response
UBZ	User order mass action report
UCA	User order mass action request
UCB	User Notification
UCL	User Party Risk Limits Request
UCM	User Party Risk Limits Report
U6	Session Details List
h	Trading Session Status
j	Business Message Reject
UCZ	User Party Entitlements Update Report
UDI	User Party Action Report
UCR	User Party Risk Limits Update Report
U27	Security Status Definition Request
f	Security Status
c	Security Definition Request
d	Security Definition
UDS	Cross Request
UDT	Cross Request Ack
U29	CLIP Enter Request
U30	CLIP Cancel Request
U31	CLIP Response
U28	Business Message Ack
R	Quote Request
S	Quote

6.2 Trailer

Tag	Field Name	Req'd	Data Type	Description
10	CheckSum	Y	INT	Three byte, simple checksum.

7 Administrative Messages

Overview of messages contained in this section:

FIX Message	MsgType
Session Logon	A
Session Logout	5
Heartbeat	0
Test Request	1
Resend Request	2
Reject	3
Sequence Reset	4

7.1 Session Logon

The Logon message allows the client to connect to the FIX Gateway. It is also used by the FIX Gateway to confirm the logon.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='A' />				
98	EncryptMethod	Y	INT	Method of encryption. Value: 0 — None/other
108	HeartBtInt	Y	INT	Heartbeat interval (seconds). The value must be greater than or equal to 30.
554	Password	N	STRING	Password. Valid charachters 0-9, A-Z, a-z, \x21, \x23, \x24, \x25, \x26, \x2A, \x2B, \x2D, \x2F, \x3D, \x40, \x5F
141	ResetSeqNumFlag	N	BOOLEAN	Logon requests with ResetSeqNumFlag (141) set to Y will trigger a reset of Sequence numbers at the participant side only. The Sequence numbering for the messages generated from FIX Gateway will remain unchanged. Value: N — No; Y — Yes, reset Sequence numbers
1600	FIXEngineName	N	STRING (1-30)	Provides the name of the infrastructure component being used for session level communication. Normally this would be the FIX Engine or FIX Gateway product name. This field is optional in the messages sent to the FIX Gateway.
1601	FIXEngineVersion	N	STRING (1-30)	Provides the version of the infrastructure component. This field is optional in the messages sent to the FIX Gateway.
1602	FIXEngineVendor	N	STRING (1-30)	Provides the name of the vendor providing the infrastructure component. This field is optional in the messages sent to the FIX Gateway.
1603	ApplicationSystem-Name	N	STRING (1-30)	Provides the name of the application system being used to generate FIX application messages. This will normally be a trading system, OMS, or EMS. This field is optional in the messages sent to the FIX Gateway.
1604	ApplicationSystem-Version	N	STRING (1-30)	Provides the version of the application system being used to initiate FIX application messages. This field is optional in the messages sent to the FIX Gateway.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>1605</td><td>ApplicationSystem-Vendor</td><td>N</td><td>STRING (1-30)</td><td>Provides the vendor of the application system. This field is optional in the messages sent to the FIX Gateway.</td></tr>
<tr><td>1408</td><td>DefaultCstmApplVer-ID</td><td>Y</td><td>STRING (1-30)</td><td>FIX LF version as documented in the section 5 Overview of Supported Message Types</td></tr>
<tr><td>28763</td><td>DefaultCstmApplVer-SubID</td><td>N</td><td>STRING (1-5)</td><td>Interface subversion. Identifies interface changes within one T7 release. Response only.
<table><tr><th>Value</th><th>Description</th></tr><tr><td>D0001</td><td>Derivatives subversion 0001</td></tr><tr><td>D0002</td><td>Derivatives subversion 0002</td></tr><tr><td>D0003</td><td>Derivatives subversion 0003</td></tr><tr><td>D0004</td><td>Derivatives subversion 0004</td></tr><tr><td>D0005</td><td>Derivatives subversion 0005</td></tr></table></td></tr>
<tr><td>339</td><td>TradSesMode</td><td>N</td><td>INT</td><td>Trading Session Mode. Response only.
<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Development</td></tr><tr><td>2</td><td>Simulation</td></tr><tr><td>3</td><td>Production</td></tr><tr><td>4</td><td>Acceptance</td></tr><tr><td>5</td><td>Disaster Recovery</td></tr></table></td></tr>
<tr><td>1685</td><td>ThrottleInst</td><td>Y</td><td>INT</td><td>Instructs the gateway how to handle throttled transactions. Recommended value for backoffice sessions is 0.
<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>Reject if throttle limit exceeded</td></tr><tr><td>1</td><td>Queue if throttle limit exceeded (queuing time limited)</td></tr><tr><td>2</td><td>Queue if throttle limit exceeded (queuing time unlimited)</td></tr></table></td></tr>
<tr><td>28790</td><td>ThrottleMaxQueue-Time</td><td>N</td><td>INT</td><td>Maximum queuing time of requests in milliseconds. Value must be > 0, if ThrottleInst $= 1$, otherwise field must not be set.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

7.2 Session Logout

The Logout message initiates or confirms the termination of a FIX session.It is also used by the FIX Gateway to reject the FIX session logon.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td colspan="5"><Header with MsgType='5' /></td></tr>
<tr><td>58</td><td>Text</td><td>N</td><td>STRING
(1-128)</td><td>Free format text string.</td></tr>
<tr><td>1409</td><td>SessionStatus</td><td>N</td><td>INT</td><td>Session status.<table><tr><th>Value</th><th>Description</th></tr><tr><td>4</td><td>Session logout complete</td></tr><tr><td>5</td><td>Invalid user name or password</td></tr></table></td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

7.3 Heartbeat

The Heartbeat message may be used by the client and the FIX Gateway to monitor the status of the communication link during periods of inactivity.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='0' />				
112	TestReqID	N	STRING	Identifier included in Test Request message to be returned in resulting Heartbeat.
<Trailer />				

7.4 Test Request

The Test Request message is used to trigger a heartbeat message from the opposing application.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='1' />				
112	TestReqID	Y	STRING	Identifier included in Test Request message to be returned in resulting Heartbeat.
<Trailer />				

7.5 Resend Request

The Resend Request is used by the client and the FIX Gateway to initiate the retransmission of messages in a recovery scenario.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='2' />				
7	BeginSeqNo	Y	SEQNUM	Message Sequence number of first message in range to be resent.
16	EndSeqNo	Y	SEQNUM	Message Sequence number of last message in range to be resent.
<Trailer />				

7.6 Reject

The Reject message is used by the FIX Gateway when a message is received but cannot be properly processed due to a session-level rule violation.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='3' />				
45	RefSeqNum	Y	SEQNUM	Reference message Sequence number.
58	Text	N	STRING (1-128)	Free format text string.
371	RefTagID	N	INT	The tag number of the FIX field being referenced.
372	RefMsgType	Y	STRING	The MsgType (35) of the FIX message being referenced.
373	SessionRejectReason	N	INT	Code to identify reason for a session-level Reject message.
25023	ReturnCode	N	INT	Return code.
<Trailer />				

Value	Description
0	Invalid tag number
1	Required tag missing
2	Tag not defined for this message type
3	Undefined tag
4	Tag specified without value
5	Value is incorrect for this tag
6	Incorrect data format for value
7	Decryption problem
8	Signature problem
9	CompID Problem
10	Sending time accuracy problem
11	Invalid msgtype
12	XML Validation Error
13	Tag appears more than once
14	Tag specified out of required order
15	Repeating group fields out of order
16	Incorrect NumInGroup count for repeating group
17	Non 'data' value includes field delimiter
18	Invalid/Unsupported Application Version
99	Other

7.7 Sequence Reset

The Sequence Reset message has two modes: Gap Fill mode is used in response to a Resend Request when one or more messages must be skipped over. Reset mode specifies an arbitrarily higher new Sequence number after an uncoverable application failure.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='4' />				
123	GapFillFlag	N	BOOLEAN	Indicates that the Sequence Reset message is replacing administrative or application messages which will not be resent. Value: N — Sequence Reset, Ignore Msg Seq Num Value: Y — Gap Fill Message, Msg Seq Num Field Valid
36	NewSeqNo	Y	SEQNUM	New Sequence number.
<Trailer />				

8 Application Messages

Overview of messages contained in this section:

FIX Message	MsgType
User Request	BE
User Response	BF
User Notification	UCB
New Order Single	D
New Order Multileg	AB
Order Cancel/Replace Request	G
Multileg Order Cancel/Replace Request	AC
Order Cancel Request	F
Execution Report	8
Order Mass Action Request	UCA
User Order Mass Action Report	UBZ
Business Message Acknowledgment	U28
Business Message Reject	j
Security Definition Request	c
Security Definition Response	d
Cross Request	UDS
Quote Request	R
Trading Session Status	h
User Party Entitlements Update Report	UCZ
User Party Action Report	UDI
User Party Risk Limits Update Report	UCR
User Party Risk Limits Request	UCL
User Party Risk Limits Report	UCM
CLIP Enter Request	U29
CLIP Delete Request	U30
CLIP Response	U31
Session Details List	U6
Trade Capture Report	AE

8.1 User Request

Each trader needs to logon/logoff to/from T7 via the User Request message.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='BE' />				
553	Username	Y	INT	User ID
554	Password	N	STRING	Password. Valid charachters 0-9, A-Z, a-z, \x21, \x23, \x24, \x25, \x26, \x2A, \x2B, \x2D, \x2F, \x3D, \x40, \x5F
923	UserRequestID	Y	STRING (1-20)	Unique identifier for a User Request.
924	UserRequestType	Y	INT	Indicates the action required by a User Request Message. Value: 1 = Log on user; 2 = Log off user
<Trailer />				

8.2 User Response

The User Response message is used to confirm the trader logon/logoff.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='BF' />				
553	Username	Y	INT	User ID
923	UserRequestID	Y	STRING (1-20)	Unique identifier for a User Request.
926	UserStatus	Y	INT	Indicates the status of a user. Value: 1 = Logged in; 2 = Not logged in
<Trailer />				

8.3 User Notification

The User Notification message is used to send information of an unsolicited trader logoff or send information of legal notifications.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UCB' />				
<UsernameGrp>, cardinality: unrestricted, record counter: NoUsernames (809)				
553	>Username	N	INT	User ID
</UsernameGrp>				
58	Text	N	STRING (1-128)	Free format text string.
926	UserStatus	Y	INT	Indicates the status of a user. Value: 7 – Forced user logout by exchange 10 – User stopped 11 – User released
<Trailer />				

8.4 New Order Single

The New Order Single message is used by the client to submit an order for single leg securities.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='D' />				
<Parties>, cardinality: 1-11, record counter: NoPartyIDs (453), containing occurrences: beneficiary, client_id, entering_trader, location_id, order_origination_firm, position_account, takeup_firm, execution_identifier_human, execution_identifier_algo, investment_identifier_human, investment_identifier_algo*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D – Proprietary custom code Value: P – Short code identifier
452	>PartyRole	Y	INT	Party Role. Value: 3 – Client ID Value: 12 – Executing trader Value: 13 – Order origination firm Value: 32 – Beneficiary Value: 36 – Entering trader Value: 38 – Position account Value: 75 – Location ID Value: 96 – Take-up (trading) firm Value: 122 – Investment decision maker
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 – Algorithm Value: 24 – Natural person

Tag	Field Name	Req'd	Data Type	Description
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 – Person
</Parties>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M – Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. Value: 1 – Simple Instrument; 2 – Standard Option Strategy; 3 – Non-standard Option Strategy; 4 – Volatility Strategy; 5 – Futures Spread; 6 – Inter Product Spread; 7 – Standard Future Strategy; 8 – Pack and Bundle; 9 – Strip; 10 – Flexible Simple Instrument (used only for TES trades); 13 – Non-standard Volatility Strategy; 14 – Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. Value: MLEG – Multileg Instrument

Tag	Field Name	Req'd	Data Type	Description
762	SecuritySubType	N	INT(10)	Strategy type. Required for Product-Complex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				
<TrdgSesGrp>, cardinality: 0-1, record counter: NoTradingSessions (386)				
336	>TradingSessionID	Y	INT	Identifier for trading session. Value: 1 = Day
625	>TradingSessionSubID	Y	INT	This field marks orders for a special trading phase. Value: 2 = Opening auction; 4 = Closing auction; 8 = Auction only
</TrdgSesGrp>				
<MtchgInst>, cardinality: 0-1, record counter: NoMatchInst (1624)				
1625	>MatchInst	Y	INT	Matching Instruction for the order. Value: 2 = Do not match
28744	>MatchInstCrossID	Y	INT(10)	Numeric identifier. Contains the Self Match Prevention ID.
</MtchgInst>				
<OrderAttributeGrp>, cardinality: 0-2, record counter: NoOrderAttributes (2593), containing occurrences: liquidity_provision_activity_order, risk_reduction_order				
2594	>OrderAttributeType	N	INT	Type of order attribute. Value: 2 = Liquidity Provision Activity Order; 3 = Risk Reduction Order
2595	>OrderAttributeValue	N	CHAR	Value associated with the order attribute type specified in OrderAttributeType (2594). Value: Y = Attribute is set.
</OrderAttributeGrp>				

Tag	Field Name	Req'd	Data Type	Description
<ValueChecksGrp>, cardinality: 2, record counter: NoValueChecks (1868), containing occurrences: price_check, notional_value_check**				
1869	>ValueCheckType	Y	INT	Type of value to be checked. Value: 1 – Price check Value: 2 – Notional value check
1870	>ValueCheckAction	Y	INT	Action to be taken for the ValueCheckType (1869). ValueCheckAction (1870) = '2' (Best effort) is only possible, if ValueCheckType (1869) = '1' (Price check). Value: 0 – Do not check Value: 1 – Check Value: 2 – Best effort
</ValueChecksGrp>				
1	Account	N	STRING (2)	Account.
11	ClOrdID	Y	STRING (1-20)	Unique customer defined order request identifier
18	ExecInst	N	MULTIPLE-VALUESTRING	Instructions for order handling. Value: 6 – Participate don't initiate (Book or cancel)
38	OrderQty	Y	QTY	Total Order Quantity.
40	OrdType	Y	CHAR	Order type. Value: 1 – Market Value: 2 – Limit Value: 3 – Stop Value: 4 – Stop limit
44	Price	N	PRICE	Limit price.
54	Side	Y	CHAR	Side Value: 1 – Buy Value: 2 – Sell
25007	FreeText1	N	STRING (1-12)	First free-format text field for trader-specific or customer-related comments.

Tag	Field Name	Req'd	Data Type	Description
59	TimeInForce	N	CHAR	Execution and trading restriction parameters. Will be defaulted to "0" (Day) if missing. Value: 0 Day; 1 Good till Cancel; 3 Immediate or Cancel; 6 Good till Date
77	PositionEffect	Y	CHAR	Indicates whether the resulting position after a trade should be an opening position or closing position. Value: O Open; C Close
99	StopPx	N	PRICE	Stop price.
432	ExpireDate	N	LOCALMKT-DATE	Date of order expiration.
1031	CustOrderHandling-Inst	N	CHAR	Rate identifier in accordance with the FIA guidelines. Value: W Desk; Y Electronic; C FCM-provided screen; G FCM API or FIX; H Algo Engine; D Default; * More values
1724	OrderOrigination	N	INT	Direct market access identifier. Value: 5 Direct market access; 105 Sponsored access
1815	TradingCapacity	Y	INT	Trading capacity. Value: 1 Customer (Agency); 5 Principal (Proprietary); 6 Market Maker

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>2964</td><td>SelfMatchPrevention-Instruction</td><td>N</td><td>INT</td><td>Indicate the instruction for SMP<table><tr><th>Value</th><th>Description</th></tr><tr><td>100</td><td>Reject cross on business unit level</td></tr><tr><td>101</td><td>Reject cross on market level</td></tr></table></td></tr>
<tr><td>31625</td><td>CrossMatchInstruction</td><td>N</td><td>INT</td><td>Indicate the instruction for SMP. Applicable only when MatchInstCrossID (28744) is set. When CrossMatchInstruction is not set the default value is defined by the exchange<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Cancel incoming order</td></tr><tr><td>2</td><td>Cancel resting order</td></tr><tr><td>3</td><td>Reduce/Cancel both incoming and resting order</td></tr></table></td></tr>
<tr><td>2404</td><td>ComplianceText</td><td>N</td><td>STRING (1-20)</td><td>Provide additionals compliance information.</td></tr>
<tr><td>25008</td><td>FreeText2</td><td>N</td><td>STRING (1-12)</td><td>Second free-format text field for trader-specific or customer-related comments.</td></tr>
<tr><td>25009</td><td>FreeText3</td><td>N</td><td>STRING (1-12)</td><td>Third free-format text field for trader-specific or customer-related comments.</td></tr>
<tr><td>25241</td><td>PartyEndClient-Identification</td><td>N</td><td>STRING (1-20)</td><td>End client identifier.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.5 New Order Multileg

The New Order Multileg message is provided to submit orders for securities that are made up of multiple securities, known as "legs".

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='AB' />				
<Parties>, cardinality: 1-11, record counter: NoPartyIDs (453), containing occurrences: beneficiary, client_id, entering_trader, execution_identifier_human, execution_identifier_algo, investment_identifier_human, investment_identifier_algo, location_id, order_origination_firm, position_account, takeup_firm*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D – Proprietary custom code Value: P – Short code identifier
452	>PartyRole	Y	INT	Party Role. Value: 3 – Client ID Value: 12 – Executing trader Value: 13 – Order origination firm Value: 32 – Beneficiary Value: 36 – Entering trader Value: 38 – Position account Value: 75 – Location ID Value: 96 – Take-up (trading) firm Value: 122 – Investment decision maker
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 – Algorithm Value: 24 – Natural person

Tag	Field Name	Req'd	Data Type	Description
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 – Person
</Parties>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M – Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. Value: 1 – Simple Instrument; 2 – Standard Option Strategy; 3 – Non-standard Option Strategy; 4 – Volatility Strategy; 5 – Futures Spread; 6 – Inter Product Spread; 7 – Standard Future Strategy; 8 – Pack and Bundle; 9 – Strip; 10 – Flexible Simple Instrument (used only for TES trades); 13 – Non-standard Volatility Strategy; 14 – Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. Value: MLEG – Multileg Instrument

Tag	Field Name	Req'd	Data Type	Description
762	SecuritySubType	N	INT(10)	Strategy type. Required for Product-Complex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				
<LegOrdGrp>, cardinality: unrestricted, record counter: NoLegs (555)				
2680	>LegAccount	Y	STRING (2)	Leg-specific account.
564	>LegPositionEffect	Y	CHAR	Leg-specific field used to indicates whether the leg is submitted to open or close a position. Value: O = Open; C = Close
</LegOrdGrp>				
<MtchgInst>, cardinality: 0-1, record counter: NoMatchInst (1624)				
1625	>MatchInst	Y	INT	Matching Instruction for the order. Value: 2 = Do not match
28744	>MatchInstCrossID	Y	INT(10)	Numeric identifier. Contains the Self Match Prevention ID.
</MtchgInst>				
<OrderAttributeGrp>, cardinality: 0-2, record counter: NoOrderAttributes (2593), containing occurrences: liquidity_provision_activity_order, risk_reduction_order				
2594	>OrderAttributeType	N	INT	Type of order attribute. Value: 2 = Liquidity Provision Activity Order; 3 = Risk Reduction Order
2595	>OrderAttributeValue	N	CHAR	Value associated with the order attribute type specified in OrderAttributeType (2594). Value: Y = Attribute is set.
</OrderAttributeGrp>				
<ValueChecksGrp>, cardinality: 2, record counter: NoValueChecks (1868), containing occurrences: price_check, notional_value_check**				

Tag	Field Name	Req'd	Data Type	Description
1869	>ValueCheckType	Y	INT	Type of value to be checked. Value: 1 = Price check; 2 = Notional value check
1870	>ValueCheckAction	Y	INT	Action to be taken for the ValueCheckType (1869). ValueCheckAction (1870) = '2' (Best effort) is only possible, if ValueCheckType (1869) = '1' (Price check). Value: 0 = Do not check; 1 = Check; 2 = Best effort
</ValueChecksGrp>				
11	ClOrdID	Y	STRING (1-20)	Unique customer defined order request identifier
18	ExecInst	N	MULTIPLE-VALUESTRING	Instructions for order handling. Value: 6 = Participate don't initiate (Book or cancel)
38	OrderQty	Y	QTY	Total Order Quantity.
40	OrdType	Y	CHAR	Order type. Value: 2 = Limit
44	Price	Y	PRICE	Limit price.
54	Side	Y	CHAR	Side Value: 1 = Buy; 2 = Sell
25007	FreeText1	N	STRING (1-12)	First free-format text field for trader-specific or customer-related comments.
59	TimeInForce	N	CHAR	Execution and trading restriction parameters. Will be defaulted to "0" (Day) if missing. Value: 0 = Day; 1 = Good till Cancel; 3 = Immediate or Cancel; 6 = Good till Date

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>432</td><td>ExpireDate</td><td>N</td><td>LOCALMKT-DATE</td><td>Date of order expiration.</td></tr>
<tr><td>1031</td><td>CustOrderHandling-Inst</td><td>N</td><td>CHAR</td><td>Rate identifier in accordance with the FIA guidelines.<table><tr><th>Value</th><th>Description</th></tr><tr><td>W</td><td>Desk</td></tr><tr><td>Y</td><td>Electronic</td></tr><tr><td>C</td><td>FCM-provided screen</td></tr><tr><td>G</td><td>FCM API or FIX</td></tr><tr><td>H</td><td>Algo Engine</td></tr><tr><td>D</td><td>Default</td></tr><tr><td>*</td><td>More values</td></tr></table></td></tr>
<tr><td>1724</td><td>OrderOrigination</td><td>N</td><td>INT</td><td>Direct market access identifier.<table><tr><th>Value</th><th>Description</th></tr><tr><td>5</td><td>Direct market access</td></tr><tr><td>105</td><td>Sponsored access</td></tr></table></td></tr>
<tr><td>1815</td><td>TradingCapacity</td><td>Y</td><td>INT</td><td>Trading capacity.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Customer (Agency)</td></tr><tr><td>5</td><td>Principal (Proprietary)</td></tr><tr><td>6</td><td>Market Maker</td></tr></table></td></tr>
<tr><td>2964</td><td>SelfMatchPrevention-Instruction</td><td>N</td><td>INT</td><td>Indicate the instruction for SMP<table><tr><th>Value</th><th>Description</th></tr><tr><td>100</td><td>Reject cross on business unit level</td></tr><tr><td>101</td><td>Reject cross on market level</td></tr></table></td></tr>
<tr><td>31625</td><td>CrossMatchInstruction</td><td>N</td><td>INT</td><td>Indicate the instruction for SMP. Applicable only when MatchInstCrossID (28744) is set. When CrossMatchInstruction is not set the default value is defined by the exchange<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Cancel incoming order</td></tr><tr><td>2</td><td>Cancel resting order</td></tr><tr><td>3</td><td>Reduce/Cancel both incoming and resting order</td></tr></table></td></tr>
<tr><td>2404</td><td>ComplianceText</td><td>N</td><td>STRING (1-20)</td><td>Provide additionals compliance information.</td></tr>
<tr><td>25008</td><td>FreeText2</td><td>N</td><td>STRING (1-12)</td><td>Second free-format text field for trader-specific or customer-related comments.</td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
25009	FreeText3	N	STRING (1-12)	Third free-format text field for trader-specific or customer-related comments.
25241	PartyEndClient-Identification	N	STRING (1-20)	End client identifier.
<Trailer />				

8.6 Order Cancel/Replace Request

The Order Cancel/Replace Request is used to modify an existing order.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='G' />				
<Parties>, cardinality: 1-11, record counter: NoPartyIDs (453), containing occurrences: beneficiary, client_id, entering_trader, execution_identifier_human, execution_identifier_algo, investment_identifier_human, investment_identifier_algo, location_id, order_origination_firm, position_account, takeup_firm*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D – Proprietary custom code Value: P – Short code identifier
452	>PartyRole	Y	INT	Party Role. Value: 3 – Client ID Value: 12 – Executing trader Value: 13 – Order origination firm Value: 32 – Beneficiary Value: 36 – Entering trader Value: 38 – Position account Value: 75 – Location ID Value: 96 – Take-up (trading) firm Value: 122 – Investment decision maker
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 – Algorithm Value: 24 – Natural person

Tag	Field Name	Req'd	Data Type	Description
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 – Person
</Parties>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M – Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. Value: 1 – Simple Instrument; 2 – Standard Option Strategy; 3 – Non-standard Option Strategy; 4 – Volatility Strategy; 5 – Futures Spread; 6 – Inter Product Spread; 7 – Standard Future Strategy; 8 – Pack and Bundle; 9 – Strip; 10 – Flexible Simple Instrument (used only for TES trades); 13 – Non-standard Volatility Strategy; 14 – Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. Value: MLEG – Multileg Instrument

Tag	Field Name	Req'd	Data Type	Description
762	SecuritySubType	N	INT(10)	Strategy type. Required for Product-Complex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				
<TrdgSesGrp>, cardinality: 0-1, record counter: NoTradingSessions (386)				
336	>TradingSessionID	Y	INT	Identifier for trading session. Value: 1 — Day
625	>TradingSessionSubID	Y	INT	This field marks orders for a special trading phase. Value: 2 — Opening auction; 4 — Closing auction; 8 — Auction only
</TrdgSesGrp>				
<MtchgInst>, cardinality: 0-1, record counter: NoMatchInst (1624)				
1625	>MatchInst	Y	INT	Matching Instruction for the order. Value: 2 — Do not match
28744	>MatchInstCrossID	Y	INT(10)	Numeric identifier. Contains the Self Match Prevention ID.
</MtchgInst>				
<OrderAttributeGrp>, cardinality: 0-1, record counter: NoOrderAttributes (2593), containing occurrences: liquidity_provision_activity_order				
2594	>OrderAttributeType	N	INT	Type of order attribute. Value: 2 — Liquidity Provision Activity Order
2595	>OrderAttributeValue	N	CHAR	Value associated with the order attribute type specified in OrderAttributeType (2594). Value: Y — Attribute is set.
</OrderAttributeGrp>				
<ValueChecksGrp>, cardinality: 1-3, record counter: NoValueChecks (1868)				

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>1869</td><td>>ValueCheckType</td><td>Y</td><td>INT</td><td>Type of value to be checked.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Price check</td></tr><tr><td>2</td><td>Notional value check</td></tr></table></td></tr>
<tr><td>1870</td><td>>ValueCheckAction</td><td>Y</td><td>INT</td><td>Action to be taken for the ValueCheckType (1869). ValueCheckAction (1870) = '2' (Best effort) is only possible, if ValueCheckType (1869) = '1' (Price check).<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>Do not check</td></tr><tr><td>1</td><td>Check</td></tr><tr><td>2</td><td>Best effort</td></tr></table></td></tr>
<tr><td colspan="5"></ValueChecksGrp></td></tr>
<tr><td>1</td><td>Account</td><td>N</td><td>STRING (2)</td><td>Account.</td></tr>
<tr><td>11</td><td>ClOrdID</td><td>Y</td><td>STRING (1-20)</td><td>Unique customer defined order request identifier</td></tr>
<tr><td>18</td><td>ExecInst</td><td>N</td><td>MULTIPLE-VALUESTRING</td><td>Instructions for order handling.<table><tr><th>Value</th><th>Description</th></tr><tr><td>6</td><td>Participate don't initiate (Book or cancel)</td></tr></table></td></tr>
<tr><td>38</td><td>OrderQty</td><td>Y</td><td>QTY</td><td>Total Order Quantity.</td></tr>
<tr><td>40</td><td>OrdType</td><td>Y</td><td>CHAR</td><td>Order type.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Market</td></tr><tr><td>2</td><td>Limit</td></tr><tr><td>3</td><td>Stop</td></tr><tr><td>4</td><td>Stop limit</td></tr></table></td></tr>
<tr><td>41</td><td>OrigClOrdID</td><td>Y</td><td>STRING (1-20)</td><td>ClOrdID (11) of the last successfully processed task (request) referring to the specific order.</td></tr>
<tr><td>44</td><td>Price</td><td>N</td><td>PRICE</td><td>Limit price.</td></tr>
<tr><td>54</td><td>Side</td><td>Y</td><td>CHAR</td><td>Side<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Buy</td></tr><tr><td>2</td><td>Sell</td></tr></table></td></tr>
<tr><td>25007</td><td>FreeText1</td><td>N</td><td>STRING (1-12)</td><td>First free-format text field for trader-specific or customer-related comments.</td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
59	TimeInForce	N	CHAR	Execution and trading restriction parameters. Will be defaulted to "0" (Day) if missing. Value: 0 Day; 1 Good till Cancel; 3 Immediate or Cancel; 6 Good till Date
77	PositionEffect	Y	CHAR	Indicates whether the resulting position after a trade should be an opening position or closing position. Value: O Open; C Close
99	StopPx	N	PRICE	Stop price.
432	ExpireDate	N	LOCALMKT-DATE	Date of order expiration.
1031	CustOrderHandling-Inst	N	CHAR	Rate identifier in accordance with the FIA guidelines. Value: W Desk; Y Electronic; C FCM-provided screen; G FCM API or FIX; H Algo Engine; D Default; * More values
1724	OrderOrigination	N	INT	Direct market access identifier. Value: 5 Direct market access; 105 Sponsored access
1815	TradingCapacity	Y	INT	Trading capacity. Value: 1 Customer (Agency); 5 Principal (Proprietary); 6 Market Maker

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>2964</td><td>SelfMatchPrevention-Instruction</td><td>N</td><td>INT</td><td>Indicate the instruction for SMP<table><tr><th>Value</th><th>Description</th></tr><tr><td>100</td><td>Reject cross on business unit level</td></tr><tr><td>101</td><td>Reject cross on market level</td></tr></table></td></tr>
<tr><td>31625</td><td>CrossMatchInstruction</td><td>N</td><td>INT</td><td>Indicate the instruction for SMP. Applicable only when MatchInstCrossID (28744) is set. When CrossMatchInstruction is not set the default value is defined by the exchange<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Cancel incoming order</td></tr><tr><td>2</td><td>Cancel resting order</td></tr><tr><td>3</td><td>Reduce/Cancel both incoming and resting order</td></tr></table></td></tr>
<tr><td>2404</td><td>ComplianceText</td><td>N</td><td>STRING (1-20)</td><td>Provide additionals compliance information.</td></tr>
<tr><td>25008</td><td>FreeText2</td><td>N</td><td>STRING (1-12)</td><td>Second free-format text field for trader-specific or customer-related comments.</td></tr>
<tr><td>25009</td><td>FreeText3</td><td>N</td><td>STRING (1-12)</td><td>Third free-format text field for trader-specific or customer-related comments.</td></tr>
<tr><td>25241</td><td>PartyEndClient-Identification</td><td>N</td><td>STRING (1-20)</td><td>End client identifier.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.7 Multileg Order Cancel/Replace Request

The Multileg Order Cancel/Replace Request is used to modify a multileg order (previously submitted using the New Order Multileg messsage).

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='AC' />				
<Parties>, cardinality: 1-11, record counter: NoPartyIDs (453), containing occurrences: beneficiary, client_id, entering_trader, execution_identifier_human, execution_identifier_algo, investment_identifier_human, investment_identifier_algo, location_id, order_origination_firm, position_account, takeup_firm*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D – Proprietary custom code Value: P – Short code identifier
452	>PartyRole	Y	INT	Party Role. Value: 3 – Client ID Value: 12 – Executing trader Value: 13 – Order origination firm Value: 32 – Beneficiary Value: 36 – Entering trader Value: 38 – Position account Value: 75 – Location ID Value: 96 – Take-up (trading) firm Value: 122 – Investment decision maker
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 – Algorithm Value: 24 – Natural person

Tag	Field Name	Req'd	Data Type	Description
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 – Person
</Parties>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M – Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. Value: 1 – Simple Instrument; 2 – Standard Option Strategy; 3 – Non-standard Option Strategy; 4 – Volatility Strategy; 5 – Futures Spread; 6 – Inter Product Spread; 7 – Standard Future Strategy; 8 – Pack and Bundle; 9 – Strip; 10 – Flexible Simple Instrument (used only for TES trades); 13 – Non-standard Volatility Strategy; 14 – Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. Value: MLEG – Multileg Instrument

Tag	Field Name	Req'd	Data Type	Description
762	SecuritySubType	N	INT(10)	Strategy type. Required for Product-Complex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				
<LegOrdGrp>, cardinality: unrestricted, record counter: NoLegs (555)				
2680	>LegAccount	Y	STRING (2)	Leg-specific account.
564	>LegPositionEffect	Y	CHAR	Leg-specific field used to indicates whether the leg is submitted to open or close a position. Value: O = Open; C = Close
</LegOrdGrp>				
<MtchgInst>, cardinality: 0-1, record counter: NoMatchInst (1624)				
1625	>MatchInst	Y	INT	Matching Instruction for the order. Value: 2 = Do not match
28744	>MatchInstCrossID	Y	INT(10)	Numeric identifier. Contains the Self Match Prevention ID.
</MtchgInst>				
<OrderAttributeGrp>, cardinality: 0-1, record counter: NoOrderAttributes (2593), containing occurrences: liquidity_provision_activity_order				
2594	>OrderAttributeType	N	INT	Type of order attribute. Value: 2 = Liquidity Provision Activity Order
2595	>OrderAttributeValue	N	CHAR	Value associated with the order attribute type specified in OrderAttributeType (2594). Value: Y = Attribute is set.
</OrderAttributeGrp>				
<ValueChecksGrp>, cardinality: 2, record counter: NoValueChecks (1868), containing occurrences: price_check, notional_value_check**				

Tag	Field Name	Req'd	Data Type	Description
1869	>ValueCheckType	Y	INT	Type of value to be checked. Value: 1 = Price check; 2 = Notional value check
1870	>ValueCheckAction	Y	INT	Action to be taken for the ValueCheckType (1869). ValueCheckAction (1870) = '2' (Best effort) is only possible, if ValueCheckType (1869) = '1' (Price check). Value: 0 = Do not check; 1 = Check; 2 = Best effort
</ValueChecksGrp>				
11	ClOrdID	Y	STRING (1-20)	Unique customer defined order request identifier
18	ExecInst	N	MULTIPLE-VALUESTRING	Instructions for order handling. Value: 6 = Participate don't initiate (Book or cancel)
38	OrderQty	Y	QTY	Total Order Quantity.
40	OrdType	Y	CHAR	Order type. Value: 2 = Limit
41	OrigClOrdID	Y	STRING (1-20)	ClOrdID (11) of the last successfully processed task (request) referring to the specific order.
44	Price	Y	PRICE	Limit price.
54	Side	Y	CHAR	Side Value: 1 = Buy; 2 = Sell
25007	FreeText1	N	STRING (1-12)	First free-format text field for trader-specific or customer-related comments.

Tag	Field Name	Req'd	Data Type	Description
59	TimeInForce	N	CHAR	Execution and trading restriction parameters. Will be defaulted to "0" (Day) if missing. Value: 0 = Day; 1 = Good till Cancel; 3 = Immediate or Cancel; 6 = Good till Date
432	ExpireDate	N	LOCALMKT-DATE	Date of order expiration.
1031	CustOrderHandling-Inst	N	CHAR	Rate identifier in accordance with the FIA guidelines. Value: W = Desk; Y = Electronic; C = FCM-provided screen; G = FCM API or FIX; H = Algo Engine; D = Default; * = More values
1724	OrderOrigination	N	INT	Direct market access identifier. Value: 5 = Direct market access; 105 = Sponsored access
1815	TradingCapacity	Y	INT	Trading capacity. Value: 1 = Customer (Agency); 5 = Principal (Proprietary); 6 = Market Maker
2964	SelfMatchPrevention-Instruction	N	INT	Indicate the instruction for SMP Value: 100 = Reject cross on business unit level; 101 = Reject cross on market level

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>31625</td><td>CrossMatchInstruction</td><td>N</td><td>INT</td><td>Indicate the instruction for SMP. Applicable only when MatchInstCrossID (28744) is set. When CrossMatchInstruction is not set the default value is defined by the exchange
<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Cancel incoming order</td></tr><tr><td>2</td><td>Cancel resting order</td></tr><tr><td>3</td><td>Reduce/Cancel both incoming and resting order</td></tr></table></td></tr>
<tr><td>2404</td><td>ComplianceText</td><td>N</td><td>STRING (1-20)</td><td>Provide additionals compliance information.</td></tr>
<tr><td>25008</td><td>FreeText2</td><td>N</td><td>STRING (1-12)</td><td>Second free-format text field for trader-specific or customer-related comments.</td></tr>
<tr><td>25009</td><td>FreeText3</td><td>N</td><td>STRING (1-12)</td><td>Third free-format text field for trader-specific or customer-related comments.</td></tr>
<tr><td>25241</td><td>PartyEndClient-Identification</td><td>N</td><td>STRING (1-20)</td><td>End client identifier.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.8 Order Cancel Request

The Order Cancel Request is used to delete an existing order.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='F' />				
<Parties>, cardinality: 1-5, record counter: NoPartyIDs (453), containing occurrences: entering_trader, execution_identifier_human, execution_identifier_algo, investment_identifier_human, investment_identifier_algo*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D – Proprietary custom code Value: P – Short code identifier
452	>PartyRole	Y	INT	Party Role. Value: 12 – Executing trader Value: 36 – Entering trader Value: 122 – Investment decision maker
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 – Algorithm Value: 24 – Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).

Tag	Field Name	Req'd	Data Type	Description
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 — Person
</Parties>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M — Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. Value: 1 — Simple Instrument 2 — Standard Option Strategy 3 — Non-standard Option Strategy 4 — Volatility Strategy 5 — Futures Spread 6 — Inter Product Spread 7 — Standard Future Strategy 8 — Pack and Bundle 9 — Strip 10 — Flexible Simple Instrument (used only for TES trades) 13 — Non-standard Volatility Strategy 14 — Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. Value: MLEG — Multileg Instrument
762	SecuritySubType	N	INT(10)	Strategy type. Required for ProductComplex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				

Tag	Field Name	Req'd	Data Type	Description
11	ClOrdID	Y	STRING (1-20)	Unique customer defined order request identifier
37	OrderID	N	INT(20)	Exchange Order ID generated by the T7 system.
41	OrigClOrdID	N	STRING (1-20)	ClOrdID (11) of the last successfully processed task (request) referring to the specific order.
1724	OrderOrigination	N	INT	Direct market access identifier. Value: 5 – Direct market access; 105 – Sponsored access
2404	ComplianceText	N	STRING (1-20)	Provide additionals compliance information.
<Trailer />				

8.9 Execution Report

The Execution Report message is used to confirm the receipt of an order, confirm changes to an existing order, transmit all active orders, relay fill information.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td colspan="5"><Header with MsgType='8' /></td></tr>
<tr><td colspan="5"><Parties>, cardinality: 0-10, record counter: NoPartyIDs (453), containing occurrences: beneficiary, entering_firm, entering_trader, executing_trader, executing_unit, location_id, order_origination_firm, position_account, session_ID, takeup_firm</td></tr>
<tr><td>448</td><td>>PartyID</td><td>Y</td><td>STRING (1-35)</td><td>Party identifier/code.</td></tr>
<tr><td>447</td><td>>PartyIDSource</td><td>Y</td><td>CHAR</td><td>Identifies class or source of the PartyID (448) value. Required if PartyID is specified.<table><tr><th>Value</th><th>Description</th></tr><tr><td>D</td><td>Proprietary custom code</td></tr></table></td></tr>
<tr><td>452</td><td>>PartyRole</td><td>Y</td><td>INT</td><td>Party Role.<table><tr><th>Value</th><th>Description</th></tr><tr><td>7</td><td>Entering firm</td></tr><tr><td>12</td><td>Executing trader</td></tr><tr><td>13</td><td>Order origination firm</td></tr><tr><td>32</td><td>Beneficiary</td></tr><tr><td>36</td><td>Entering trader</td></tr><tr><td>38</td><td>Position account</td></tr><tr><td>55</td><td>Session ID</td></tr><tr><td>59</td><td>Executing unit</td></tr><tr><td>75</td><td>Location ID</td></tr><tr><td>96</td><td>Take-up (trading) firm</td></tr></table></td></tr>
<tr><td>2376</td><td>>PartyRoleQualifier</td><td>N</td><td>INT</td><td>Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages.<table><tr><th>Value</th><th>Description</th></tr><tr><td>22</td><td>Algorithm</td></tr><tr><td>24</td><td>Natural person</td></tr></table></td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 – Person
</Parties>				
<InstrmtLegExecGrp>, cardinality: unrestricted, record counter: NoLegs (555)				
600	>LegSymbol	Y	STRING (1-10)	Product identifier of the leg security (only applicable for underlying leg). Use "[N/A]" for option legs.
602	>LegSecurityID	N	INT(20)	Multileg instrument's individual security's SecurityID.
2680	>LegAccount	N	STRING (2)	Leg-specific account.
564	>LegPositionEffect	N	CHAR	Leg-specific field used to indicates whether the leg is submitted to open or close a position. Value: O – Open; C – Close
637	>LegLastPx	N	PRICE	Execution price assigned to a leg of a multileg instrument.
1418	>LegLastQty	N	QTY	Fill quantity for the leg instrument.
1893	>LegExecID	N	INT	Private identifier of a leg match event, which can be reconciled with the field SideTradeID (1506) in the User/TradeCaptureReport (UAE/AE). Private identifier of a leg match event, which can be reconciled with the field SideTradeID (1506) in the UserTradeCaptureReport (UAE). Private identifier of a leg match event, which can be reconciled with the field SideTradeID (1506) in the TradeCaptureReport (AE).

Tag	Field Name	Req'd	Data Type	Description
624	>LegSide	N	CHAR	The side of this individual leg (multileg security). Value: 1 = Buy; 2 = Sell
</InstrmtLegExecGrp>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M = Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. Value: 1 = Simple Instrument; 2 = Standard Option Strategy; 3 = Non-standard Option Strategy; 4 = Volatility Strategy; 5 = Futures Spread; 6 = Inter Product Spread; 7 = Standard Future Strategy; 8 = Pack and Bundle; 9 = Strip; 10 = Flexible Simple Instrument (used only for TES trades); 13 = Non-standard Volatility Strategy; 14 = Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. Value: MLEG = Multileg Instrument

Tag	Field Name	Req'd	Data Type	Description
762	SecuritySubType	N	INT(10)	Strategy type. Required for Product-Complex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				
<MtchgInst>, cardinality: 0-1, record counter: NoMatchInst (1624)				
1625	>MatchInst	Y	INT	Matching Instruction for the order. Value: 2 — Description: Do not match
28744	>MatchInstCrossID	Y	INT(10)	Numeric identifier. Contains the Self Match Prevention ID.
</MtchgInst>				
1	Account	N	STRING (2)	Account.
11	ClOrdID	N	STRING (1-20)	Unique customer defined order request identifier
14	CumQty	Y	QTY	Cumulated executed quantity.
17	ExecID	Y	STRING (80)	The field provides a unique identifier and can be used for the identification of duplicate order messages.
18	ExecInst	N	MULTIPLE-VALUESTRING	Instructions for order handling. Value: H — Description: Reinstate on trading system failure (persistent) Value: Q — Description: Cancel on trading system failure (non-persistent) Value: 6 — Description: Participate don't initiate (Book or cancel)
31	LastPx	N	PRICE	Price level.
32	LastQty	N	QTY	Quantity executed in a fill or deleted in a SMP match
37	OrderID	Y	INT(20)	Exchange Order ID generated by the T7 system.
38	OrderQty	Y	QTY	Total Order Quantity.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>39</td><td>OrdStatus</td><td>Y</td><td>CHAR</td><td>Identifies current status of order.<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>New</td></tr><tr><td>1</td><td>Partially filled</td></tr><tr><td>2</td><td>Filled</td></tr><tr><td>4</td><td>Canceled</td></tr><tr><td>6</td><td>Pending cancel</td></tr><tr><td>8</td><td>Rejected</td></tr><tr><td>9</td><td>Suspended</td></tr><tr><td>A</td><td>Pending new</td></tr><tr><td>E</td><td>Pending replace</td></tr></table></td></tr>
<tr><td>40</td><td>OrdType</td><td>N</td><td>CHAR</td><td>Order type.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Market</td></tr><tr><td>2</td><td>Limit</td></tr><tr><td>3</td><td>Stop</td></tr><tr><td>4</td><td>Stop limit</td></tr></table></td></tr>
<tr><td>41</td><td>OrigClOrdID</td><td>N</td><td>STRING (1-20)</td><td>ClOrdID (11) of the last successfully processed task (request) referring to the specific order.</td></tr>
<tr><td>44</td><td>Price</td><td>N</td><td>PRICE</td><td>Limit price.</td></tr>
<tr><td>54</td><td>Side</td><td>Y</td><td>CHAR</td><td>Side of order.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Buy</td></tr><tr><td>2</td><td>Sell</td></tr></table></td></tr>
<tr><td>25007</td><td>FreeText1</td><td>N</td><td>STRING (1-12)</td><td>First free-format text field for trader-specific or customer-related comments.</td></tr>
<tr><td>59</td><td>TimeInForce</td><td>N</td><td>CHAR</td><td>Execution and trading restriction parameters. Will be defaulted to "0" (Day) if missing.<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>Day</td></tr><tr><td>1</td><td>Good till Cancel</td></tr><tr><td>3</td><td>Immediate or Cancel</td></tr><tr><td>6</td><td>Good till Date</td></tr></table></td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
77	PositionEffect	N	CHAR	Indicates whether the resulting position after a trade should be an opening position or closing position. Value: O = Open; C = Close
99	StopPx	N	PRICE	Stop price.
150	ExecType	Y	CHAR	Describes the specific ExecutionRpt while OrdStatus (39) will always identify the current order status. Value: 0 = New; 4 = Canceled; 5 = Replace; 6 = Pending cancel; 8 = Rejected; 9 = Suspended; A = Pending new; D = Restated; E = Pending replace; F = Trade; L = Triggered by system
151	LeavesQty	Y	QTY	Quantity open for further execution. If the OrdStatus (39) is Canceled, Expired, Calculated, or Rejected (in which case the order is no longer active) then LeavesQty could be 0, otherwise LeavesQty = OrderQty (38) - CumQty (14).
336	TradingSessionID	N	INT	Identifier for trading session. Value: 1 = Day
378	ExecRestatement-Reason	N	INT	Code to identify reason for an Execution Report message sent with ExecType=Restated or used when communicating an unsolicited cancel. Valid values are listed after this table.
432	ExpireDate	N	LOCALMKT-DATE	Date of order expiration.
527	SecondaryExecID	N	INT(10)	Assigned by the party which accepts the order. Can be used to provide the ExecID used by an exchange or executing system.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>574</td><td>MatchType</td><td>N</td><td>INT</td><td>The point in the matching process at which this trade was matched.<table><tr><th>Value</th><th>Description</th></tr><tr><td>4</td><td>Auto Match Incoming</td></tr><tr><td>5</td><td>Cross Auction</td></tr><tr><td>7</td><td>Call Auction</td></tr><tr><td>11</td><td>Auto Match Resting</td></tr><tr><td>13</td><td>Liquidity Improvement Cross</td></tr></table></td></tr>
<tr><td>625</td><td>TradingSessionSubID</td><td>N</td><td>INT</td><td>This field marks orders for a special trading phase.<table><tr><th>Value</th><th>Description</th></tr><tr><td>2</td><td>Opening auction</td></tr><tr><td>4</td><td>Closing auction</td></tr><tr><td>8</td><td>Auction only</td></tr></table></td></tr>
<tr><td>851</td><td>LastLiquidityInd</td><td>N</td><td>INT</td><td>Indicator to identify whether this fill was a result of a liquidity provider providing or liquidity taker taking the liquidity. Applicable only for OrdStatus of Partial or Filled.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Add Liquidity</td></tr><tr><td>2</td><td>Removed Liquidity</td></tr><tr><td>4</td><td>Auction (neither passive nor aggressive)</td></tr><tr><td>5</td><td>Triggered Stop Order</td></tr><tr><td>6</td><td>Triggered One-cancels-the-other Order</td></tr><tr><td>7</td><td>Triggered Market Order</td></tr></table></td></tr>
<tr><td>880</td><td>TrdMatchID</td><td>N</td><td>INT(10)</td><td>Identifier assigned to a trade by a matching system.</td></tr>
<tr><td>1815</td><td>TradingCapacity</td><td>N</td><td>INT</td><td>Trading capacity.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Customer (Agency)</td></tr><tr><td>5</td><td>Principal (Proprietary)</td></tr><tr><td>6</td><td>Market Maker</td></tr></table></td></tr>
<tr><td>2523</td><td>CrossedIndicator</td><td>N</td><td>INT</td><td>Indicator will be delivered in case of deletion or modification due to Self Match Prevention.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Cross rejected</td></tr></table></td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
2964	SelfMatchPrevention-Instruction	N	INT	Indicate the instruction for SMP Value: 100 – Reject cross on business unit level; 101 – Reject cross on market level
1823	Triggered	N	INT	Indicates if an order has been previously triggered. Value: 0 – Not triggered (Default); 1 – Triggered
2404	ComplianceText	N	STRING (1-20)	Provide additionals compliance information.
25008	FreeText2	N	STRING (1-12)	Second free-format text field for trader-specific or customer-related comments.
25009	FreeText3	N	STRING (1-12)	Third free-format text field for trader-specific or customer-related comments.
30060	UTransactTime	N	INT(20)	Transaction timestamp. Number of nanoseconds since Jan 1, 1970.
1031	CustOrderHandling-Inst	N	CHAR	Rate identifier in accordance with the FIA guidelines. Value: W – Desk; Y – Electronic; C – FCM-provided screen; G – FCM API or FIX; H – Algo Engine; D – Default; * – More values
<Trailer />				

Valid Values of ExecRestatementReason (datatype INT)

Valid Value	Description
1	GT renewal / restatement (no corporate action, order book restatement)
100	Unknown Order State
101	Order Added
102	Order Replaced
103	Order Canceled
105	Immediate or Cancel Order Canceled
108	Book Order executed
114	Order has been changed to IOC

117	Member has been disabled
122	Instrument State Change
135	Market Order Triggered
149	Closing Auction Only Order Activated
150	Closing Auction Only Order Inactivated
151	OAO Order activated
152	OAO Order inactivated
153	AAO Order activated
154	AAO Order inactivated
164	One-cancels-the-other Order Triggered
172	Stop Order Triggered
181	Ownership Changed
197	Order Cancellation Pending
199	Pending Cancellation Applied
212	Book Or Cancel Order Canceled
261	Panic Cancel
302	Market Order uncrossing
340	CLIP execution after improvement period
342	CLIP Cancellation
343	CLIP Request deleted by arrangement time out
344	CLIP Request deleted by arrangement validation
346	Cross order added
347	Cross order cancelled

8.10 Order Mass Action Request

The UserOrderMassActionRequest (UCA) will allow the deletion of multiple orders based on different filter criteria.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UCA' />				
<Parties>, cardinality: 1-5, record counter: NoPartyIDs (453), containing occurrences: entering_trader, execution_identifier_human, execution_identifier_algo, investment_identifier_human, investment_identifier_algo*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D – Proprietary custom code Value: P – Short code identifier
452	>PartyRole	Y	INT	Party Role. Value: 12 – Executing trader Value: 36 – Entering trader Value: 122 – Investment decision maker
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 – Algorithm Value: 24 – Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).

Tag	Field Name	Req'd	Data Type	Description
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 – Person
</Parties>				
<TargetParties>, cardinality: 0-2, record counter: NoTargetPartyIDs (1461), containing occurrences: target_executing_trader, target_session_ID				
1462	>TargetPartyID	Y	INT	PartyID value within an target party repeating group.
1463	>TargetParty-IDSource	Y	CHAR	PartyIDSource value within an target party repeating group. Value: D – Proprietary custom code
1464	>TargetPartyRole	Y	INT	PartyRole value within a target party repeating group. Value: 12 – Executing trader; 55 – Session ID
</TargetParties>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M – Marketplace-assigned identifier

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>1227</td><td>ProductComplex</td><td>N</td><td>INT</td><td>This field qualifies an instrument type on T7 Derivatives.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Simple Instrument</td></tr><tr><td>2</td><td>Standard Option Strategy</td></tr><tr><td>3</td><td>Non-standard Option Strategy</td></tr><tr><td>4</td><td>Volatility Strategy</td></tr><tr><td>5</td><td>Futures Spread</td></tr><tr><td>6</td><td>Inter Product Spread</td></tr><tr><td>7</td><td>Standard Future Strategy</td></tr><tr><td>8</td><td>Pack and Bundle</td></tr><tr><td>9</td><td>Strip</td></tr><tr><td>10</td><td>Flexible Simple Instrument (used only for TES trades)</td></tr><tr><td>13</td><td>Non-standard Volatility Strategy</td></tr><tr><td>14</td><td>Total Return Future Strategy</td></tr></table></td></tr>
<tr><td>167</td><td>SecurityType</td><td>N</td><td>STRING (1-4)</td><td>Indicates the type of security.<table><tr><th>Value</th><th>Description</th></tr><tr><td>MLEG</td><td>Multileg Instrument</td></tr></table></td></tr>
<tr><td>762</td><td>SecuritySubType</td><td>N</td><td>INT(10)</td><td>Strategy type. Required for ProductComplex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy</td></tr>
<tr><td colspan="5"></Instrument></td></tr>
<tr><td>11</td><td>ClOrdID</td><td>Y</td><td>STRING (1-20)</td><td>Unique customer defined order request identifier</td></tr>
<tr><td>1374</td><td>MassActionScope</td><td>Y</td><td>INT</td><td>Specifies the session scope of Order Mass Action Request.<table><tr><th>Value</th><th>Description</th></tr><tr><td>6</td><td>All orders for a specific session</td></tr><tr><td>7</td><td>All orders for the own session</td></tr><tr><td>100</td><td>All orders for all sessions</td></tr></table></td></tr>
<tr><td>44</td><td>Price</td><td>N</td><td>PRICE</td><td>Limit price.</td></tr>
<tr><td>54</td><td>Side</td><td>N</td><td>CHAR</td><td>Side<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Buy</td></tr><tr><td>2</td><td>Sell</td></tr></table></td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
1724	OrderOrigination	N	INT	Direct market access identifier. Value: 5 – Direct market access Value: 105 – Sponsored access
<Trailer />				

8.11 User Order Mass Action Report

This message informs about mass cancellation events.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UBZ' />				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M = Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. 1 = Simple Instrument 2 = Standard Option Strategy 3 = Non-standard Option Strategy 4 = Volatility Strategy 5 = Futures Spread 6 = Inter Product Spread 7 = Standard Future Strategy 8 = Pack and Bundle 9 = Strip 10 = Flexible Simple Instrument (used only for TES trades) 13 = Non-standard Volatility Strategy 14 = Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. Value: MLEG = Multileg Instrument
762	SecuritySubType	N	INT(10)	Strategy type. Required for ProductComplex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				

Tag	Field Name	Req'd	Data Type	Description
<Parties>, cardinality: 0-4, record counter: NoPartyIDs (453), containing occurrences: entering_trader, entering_firm, executing_trader, session_ID				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D — Description: Proprietary custom code
452	>PartyRole	Y	INT	Party Role. Value: 7 — Entering firm Value: 12 — Executing trader Value: 36 — Entering trader Value: 55 — Session ID
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 — Algorithm Value: 24 — Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 — Person
</Parties>				
<NotAffectedOrdersGrp>, cardinality: unrestricted, record counter: NoNotAffectedOrders (1370)				
1371	>NotAffectedOrderID	Y	INT(20)	Exchange Order ID of an order whose cancellation is pending.

Tag	Field Name	Req'd	Data Type	Description
1372	>NotAffOrigClOrdID	N	STRING (1-20)	FIX Client Order ID of an order whose cancellation is pending.
</NotAffectedOrdersGrp>				
11	ClOrdID	N	STRING (1-20)	Unique customer defined order request identifier
54	Side	N	CHAR	Side Value: 1 = Buy; 2 = Sell
44	Price	N	PRICE	Limit price.
30018	UExecInst	N	MULTIPLE-VALUESTRING	Cancellation scope for orders. Quotes are always cancelled by Mass Cancellation Events. 'No value' indicates no order cancellation. Value: H = Persistent Order; Q = Non-persistent Order
1369	MassActionReportID	Y	INT(20)	Transaction timestamp.
28721	MassActionReason	Y	INT	Reason for mass cancellation. Value: 0 = No special reason; 1 = Trading was stopped; 2 = Emergency; 3 = Market Maker Protection; 6 = Session loss or logout; 7 = Duplicate Session Login; 8 = Clearing Risk Control; 100 = Internal connection loss; 105 = Product State Halt; 106 = Product State Holiday; 107 = Instrument Suspended; 109 = Complex Instrument Deletion; 110 = Volatility Interruption; 111 = Product temporarily not tradeable; 117 = Member has been disabled
<Trailer />				

8.12 Business Message Acknowledgment

This message confirms the succesful processing of the referenced message.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='U28' />				
45	RefSeqNum	Y	SEQNUM	Reference message Sequence number.
372	RefMsgType	Y	STRING	The MsgType (35) of the FIX message being referenced.
30379	BusinessAckRefID	Y	STRING	The value of the business-level ID field on the message being referenced.
<Trailer />				

8.13 Business Message Reject

The Business Message Reject message indicates that an application message has been rejected.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='j' />				
45	RefSeqNum	N	SEQNUM	Reference message Sequence number.
58	Text	N	STRING (1-128)	Free format text string.
372	RefMsgType	Y	STRING	The MsgType (35) of the FIX message being referenced.
380	BusinessRejectReason	Y	INT	Code to identify reason for a Business Message Reject message. Valid values are listed after this table.
379	BusinessRejectRefID	N	STRING (1-20)	The value of the business-level ID field on the message being referenced.
<Trailer />				

Valid Values of BusinessRejectReason (datatype INT)

Valid Value	Description
0	Other
3	Unsupported message type
4	Application not available
5	Conditionally required field missing
6	Not Authorized
8	Throttle limit exceeded
102	Service temporarily not available
103	Service not available
105	Error converting response or broadcast
200	Internal technical error
210	Validation Error
211	User already logged in
217	Session login limit (per time interval) reached
223	User Entitlement Data time out
225	User login tries limit (per time interval) reached
226	Limit of outstanding session/user logins reached (per Business Unit)
227	Limit of outstanding session/user logins reached (per Session)
10000	Order not found
10001	Price not reasonable
10002	Duplicate Order (ClOrdID)
10003	another quote activation request is pending for the same Product / Instrument Type / Session-ID

10006	Stop buy price not reasonable
10007	Stop sell price not reasonable
10008	GFD order is not executable on current business day
10010	Throttle limit for creation of complex instrument exceeded
10011	Order maintenance not allowed in current state
10016	Pretrade Risk Limit exceeded

8.14 Security Definition Request

The Security Definition Request message is used to create a strategy on T7.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td colspan="5"><Header with MsgType='c' /></td></tr>
<tr><td colspan="5"><Parties>, cardinality: 1, record counter: NoPartyIDs (453), containing occurrences: entering_trader*</td></tr>
<tr><td>448</td><td>>PartyID</td><td>Y</td><td>STRING (1-35)</td><td>Party identifier/code.</td></tr>
<tr><td>447</td><td>>PartyIDSource</td><td>Y</td><td>CHAR</td><td>Identifies class or source of the PartyID (448) value. Required if PartyID is specified.<table><tr><th>Value</th><th>Description</th></tr><tr><td>D</td><td>Proprietary custom code</td></tr></table></td></tr>
<tr><td>452</td><td>>PartyRole</td><td>Y</td><td>INT</td><td>Party Role.<table><tr><th>Value</th><th>Description</th></tr><tr><td>36</td><td>Entering trader</td></tr></table></td></tr>
<tr><td>2376</td><td>>PartyRoleQualifier</td><td>N</td><td>INT</td><td>Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages.<table><tr><th>Value</th><th>Description</th></tr><tr><td>22</td><td>Algorithm</td></tr><tr><td>24</td><td>Natural person</td></tr></table></td></tr>
<tr><td>802</td><td>>NoPartySubIDs</td><td>N</td><td>INT</td><td>Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.</td></tr>
<tr><td>523</td><td>>PartySubID</td><td>N</td><td>STRING (1-6)</td><td>Firm or Trader Short Name, depending on the value of field PartySubIDType(803).</td></tr>
<tr><td>803</td><td>>PartySubIDType</td><td>N</td><td>INT</td><td>Type of PartySubID.<table><tr><th>Value</th><th>Description</th></tr><tr><td>2</td><td>Person</td></tr></table></td></tr>
<tr><td colspan="5"></Parties></td></tr>
<tr><td colspan="2"><Instrument></td><td>Y</td><td colspan="2"></td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M — Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. 1 Simple Instrument 2 Standard Option Strategy 3 Non-standard Option Strategy 4 Volatility Strategy 5 Futures Spread 6 Inter Product Spread 7 Standard Future Strategy 8 Pack and Bundle 9 Strip 10 Flexible Simple Instrument (used only for TES trades) 13 Non-standard Volatility Strategy 14 Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. Value: MLEG — Multileg Instrument
762	SecuritySubType	N	INT(10)	Strategy type. Required for ProductComplex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				
<InstrmtLegGrp>, cardinality: unrestricted, record counter: NoLegs (555)				
600	>LegSymbol	Y	STRING (1-10)	Product identifier of the leg security (only applicable for underlying leg). Use "[N/A]" for option legs.
602	>LegSecurityID	Y	INT(20)	Multileg instrument's individual security's SecurityID.

Tag	Field Name	Req'd	Data Type	Description
609	>LegSecurityType	Y	INT	Indicates type of security. Value: 1 = Multileg Instrument; 2 = Underlying Leg
623	>LegRatioQty	Y	INT	The ratio of quantity for this individual leg relative to the entire strategy.
624	>LegSide	Y	CHAR	The side of this individual leg (multileg security). Value: 1 = Buy; 2 = Sell
566	>LegPrice	N	PRICE	Price for leg of a multileg. See Price (44) field for description
</InstrmtLegGrp>				
320	SecurityReqID	Y	STRING (1-20)	Unique ID of a Security Definition Request.
28908	RelatedPx	N	PRICE	Basis Price or Custom Underlying Price for Total Return Future Strategy
321	SecurityRequestType	Y	INT	Type of Security Definition Request. Value: 1 = Request Security identity for the specifications provided
2404	ComplianceText	N	STRING (1-20)	Provide additionals compliance information.
<Trailer />				

8.15 Security Definition Response

The Security Definition message is used to accept the security defined in a Security Definition message.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td colspan="5"><Header with MsgType='d' /></td></tr>
<tr><td colspan="2"><Instrument></td><td>Y</td><td colspan="2"></td></tr>
<tr><td>55</td><td>Symbol</td><td>Y</td><td>STRING (1-10)</td><td>T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.</td></tr>
<tr><td>48</td><td>SecurityID</td><td>N</td><td>INT(20)</td><td>T7 instrument identifier.</td></tr>
<tr><td>22</td><td>SecurityIDSource</td><td>N</td><td>STRING (1)</td><td>Source of the securityID<table><tr><th>Value</th><th>Description</th></tr><tr><td>M</td><td>Marketplace-assigned identifier</td></tr></table></td></tr>
<tr><td>1227</td><td>ProductComplex</td><td>N</td><td>INT</td><td>This field qualifies an instrument type on T7 Derivatives.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Simple Instrument</td></tr><tr><td>2</td><td>Standard Option Strategy</td></tr><tr><td>3</td><td>Non-standard Option Strategy</td></tr><tr><td>4</td><td>Volatility Strategy</td></tr><tr><td>5</td><td>Futures Spread</td></tr><tr><td>6</td><td>Inter Product Spread</td></tr><tr><td>7</td><td>Standard Future Strategy</td></tr><tr><td>8</td><td>Pack and Bundle</td></tr><tr><td>9</td><td>Strip</td></tr><tr><td>10</td><td>Flexible Simple Instrument (used only for TES trades)</td></tr><tr><td>13</td><td>Non-standard Volatility Strategy</td></tr><tr><td>14</td><td>Total Return Future Strategy</td></tr></table></td></tr>
<tr><td>167</td><td>SecurityType</td><td>N</td><td>STRING (1-4)</td><td>Indicates the type of security.<table><tr><th>Value</th><th>Description</th></tr><tr><td>MLEG</td><td>Multileg Instrument</td></tr></table></td></tr>
<tr><td>762</td><td>SecuritySubType</td><td>N</td><td>INT(10)</td><td>Strategy type. Required for ProductComplex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy</td></tr>
<tr><td colspan="5"></Instrument></td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
<InstrmtLegGrp>, cardinality: unrestricted, record counter: NoLegs (555)				
600	>LegSymbol	Y	STRING (1-10)	Product identifier of the leg security (only applicable for underlying leg). Use "[N/A]" for option legs.
602	>LegSecurityID	Y	INT(20)	Multileg instrument's individual security's SecurityID.
609	>LegSecurityType	Y	INT	Indicates type of security. Value: 1 – Multileg Instrument; 2 – Underlying Leg
623	>LegRatioQty	Y	INT	The ratio of quantity for this individual leg relative to the entire strategy.
624	>LegSide	Y	CHAR	The side of this individual leg (multileg security). Value: 1 – Buy; 2 – Sell
566	>LegPrice	N	PRICE	Price for leg of a multileg. See Price (44) field for description
</InstrmtLegGrp>				
<MarketSegmentGrp>, cardinality: unrestricted, record counter: NoMarketSegments (1310)				
1148	>LowLimitPrice	N	PRICE	Allowable low limit price for the trading day. A key parameter in validating order price. Used as the lower band for validating order prices. Orders submitted with prices below the lower limit will be rejected.
1149	>HighLimitPrice	N	PRICE	Allowable high limit price for the trading day. A key parameter in validating order price. Used as the upper band for validating order prices. Orders submitted with prices above the upper limit will be rejected.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>1144</td><td>>ImpliedMarket-Indicator</td><td>Y</td><td>INT</td><td>Indicates that an implied market should be created for either the legs of a multileg instrument (Implied-in) or for the multileg instrument based on the existence of the legs (Implied-out). Determination as to whether implied markets should be created is generally done at the level of the multileg instrument. Commonly used in listed derivatives.<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>Not implied</td></tr><tr><td>3</td><td>Both Implied-in and Implied-out</td></tr></table></td></tr>
<tr><td>1377</td><td>>MultilegModel</td><td>Y</td><td>INT</td><td>Specifies the type of multileg order.<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>Predefined Multileg Security</td></tr><tr><td>1</td><td>User-defined Multleg Security</td></tr></table></td></tr>
<tr><td colspan="5"></MarketSegmentGrp></td></tr>
<tr><td>320</td><td>SecurityReqID</td><td>Y</td><td>STRING (1-20)</td><td>Unique ID of a Security Definition Request.</td></tr>
<tr><td>322</td><td>SecurityResponseID</td><td>Y</td><td>STRING</td><td>Identifier for the Security Definition message.</td></tr>
<tr><td>28908</td><td>RelatedPx</td><td>N</td><td>PRICE</td><td>Basis Price or Custom Underlying Price for Total Return Future Strategy</td></tr>
<tr><td>28614</td><td>NumberOfSecurities</td><td>Y</td><td>INT</td><td>Number of strategies that have been created oer session, product and business day.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.16 Cross Request

The Cross Request message is used for the publication of Cross Trade Announcements.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UDS' />				
<RootParties>, cardinality: 1, record counter: NoRootPartyIDs (1116), containing occurrences: root_entering_trader				
1117	>RootPartyID	Y	STRING (1-10)	Root party identifier.
1118	>RootPartyIDSource	Y	CHAR	Identifies class or source of the RootPartyID (1117) value. Value: D — Description: Proprietary custom code
1119	>RootPartyRole	Y	INT	Identifies the type role of the RootPartyID (1117) specified. Value: 36 — Description: Entering trader
</RootParties>				
<Instrument>		N		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M — Description: Marketplace-assigned identifier

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>1227</td><td>ProductComplex</td><td>N</td><td>INT</td><td>This field qualifies an instrument type on T7 Derivatives.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Simple Instrument</td></tr><tr><td>2</td><td>Standard Option Strategy</td></tr><tr><td>3</td><td>Non-standard Option Strategy</td></tr><tr><td>4</td><td>Volatility Strategy</td></tr><tr><td>5</td><td>Futures Spread</td></tr><tr><td>6</td><td>Inter Product Spread</td></tr><tr><td>7</td><td>Standard Future Strategy</td></tr><tr><td>8</td><td>Pack and Bundle</td></tr><tr><td>9</td><td>Strip</td></tr><tr><td>10</td><td>Flexible Simple Instrument (used only for TES trades)</td></tr><tr><td>13</td><td>Non-standard Volatility Strategy</td></tr><tr><td>14</td><td>Total Return Future Strategy</td></tr></table></td></tr>
<tr><td>167</td><td>SecurityType</td><td>N</td><td>STRING (1-4)</td><td>Indicates the type of security.<table><tr><th>Value</th><th>Description</th></tr><tr><td>MLEG</td><td>Multileg Instrument</td></tr></table></td></tr>
<tr><td>762</td><td>SecuritySubType</td><td>N</td><td>INT(10)</td><td>Strategy type. Required for Product-Complex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy</td></tr>
<tr><td colspan="5"></Instrument></td></tr>
<tr><td>38</td><td>OrderQty</td><td>Y</td><td>QTY</td><td>Total Order Quantity.</td></tr>
<tr><td>2404</td><td>ComplianceText</td><td>N</td><td>STRING (1-20)</td><td>Provide additionals compliance information.</td></tr>
<tr><td>2672</td><td>CrossRequestID</td><td>Y</td><td>INT(10)</td><td>Unique identifier for cross request. Uniqueness will be completely within the user's responsibility.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.17 Quote Request

The Quote Request message is used to request public quotes from market makers (T7 Cash, T7 Derivatives) and private quotes from specialists or issuers (T7 Cash). This message is commonly referred to as a Request For Quote (RFQ).

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='R' />				
<QuoteReqGrp>, cardinality: 1, record counter: NoRelatedSym (146)				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M – Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. 1 – Simple Instrument 2 – Standard Option Strategy 3 – Non-standard Option Strategy 4 – Volatility Strategy 5 – Futures Spread 6 – Inter Product Spread 7 – Standard Future Strategy 8 – Pack and Bundle 9 – Strip 10 – Flexible Simple Instrument (used only for TES trades) 13 – Non-standard Volatility Strategy 14 – Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. MLEG – Multileg Instrument

Tag	Field Name	Req'd	Data Type	Description
762	SecuritySubType	N	INT(10)	Strategy type. Required for Product-Complex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				
54	>Side	N	CHAR	Side Value: 1 = Buy; 2 = Sell
38	>OrderQty	N	QTY	Total Order Quantity.
*<Parties>, cardinality: 1, record counter: NoPartyIDs (453), containing occurrences: entering_trader**				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D = Proprietary custom code
452	>PartyRole	Y	INT	Party Role. Value: 36 = Entering trader
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 = Algorithm; 24 = Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>803</td><td>>PartySubIDType</td><td>N</td><td>INT</td><td>Type of PartySubID.<table><tr><td>Value</td><td>Description</td></tr><tr><td>2</td><td>Person</td></tr></table></td></tr>
<tr><td colspan="5"></Parties></td></tr>
<tr><td colspan="5"></QuoteReqGrp></td></tr>
<tr><td>131</td><td>QuoteReqID</td><td>Y</td><td>STRING (1-20)</td><td>Unique identifier of a quote request message. Must be INT(8) in case of a private quote.</td></tr>
<tr><td>2404</td><td>ComplianceText</td><td>N</td><td>STRING (1-20)</td><td>Provide additionals compliance information.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.18 Trading Session Status

The Trading Session Status message informs about session related events.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='h' />				
58	Text	N	STRING (1-128)	Free format text string.
336	TradingSessionID	Y	INT	Identifier for trading session. Value: 1 — Day
1368	TradSesEvent	Y	INT	Trading session event type. Value: 103 — End of restatement Value: 201 — Message transmission ended
340	TradSesStatus	Y	INT	State of the trading session. Value: 0 — Unknown Value: 2 — Open Value: 3 — Closed
1300	MarketSegmentID	N	INT(10)	Product identifier.
30060	UTransactTime	N	INT(20)	Transaction timestamp. Number of nanoseconds since Jan 1, 1970.
30075	UTradeDate	N	LOCALMKT-DATE	Date of trading session in YYYYMMDD format.
<Trailer />				

8.19 User Party Entitlements Update Report

User Party Entitlements Update Report. This message communicates risk control events related to the manual stop or release of trading functionality. Events will be generated on the Clearing back end and passed to the user by the T7 back end.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UCZ' />				
<Parties>, cardinality: 3-5, record counter: NoPartyIDs (453), containing occurrences: clearing_firm, entering_firm, executing_system, executing_unit*, executing_firm**				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D — Description: Proprietary custom code
452	>PartyRole	Y	INT	Party Role. 1 — Executing firm 4 — Clearing firm 7 — Entering firm 16 — Executing system 59 — Executing unit
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. 22 — Algorithm 24 — Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).

Tag	Field Name	Req'd	Data Type	Description
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 — Person
</Parties>				
75	TradeDate	N	LOCALMKT-DATE	Business date in YYYYMMDD format.
1324	ListUpdateAction	N	CHAR	Invocation or release of a control event. Value: A — Add (Invocation); D — Delete (Release)
1672	PartyDetailStatus	N	INT	Member status. Value: 0 — Active; 1 — Suspended
30060	UTransactTime	Y	INT(20)	Transaction timestamp. Number of nanoseconds since Jan 1, 1970.
1301	MarketID	Y	EXCHANGE	Market Identifier Code of the trading market according to ISO 10383.
<Trailer />				

8.20 User Party Action Report

User Party Action Report. This message communicates risk control events of type halt-trading and re-instate. Events will be entered via the T7 Admin GUI.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UDI' />				
<Parties>, cardinality: 1-2, record counter: NoPartyIDs (453), containing occurrences: executing_unit, executing_trader*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D — Description: Proprietary custom code
452	>PartyRole	Y	INT	Party Role. Value: 12 — Description: Executing trader Value: 59 — Description: Executing unit
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 — Description: Algorithm Value: 24 — Description: Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 — Description: Person
</Parties>				

Tag	Field Name	Req'd	Data Type	Description
*<RequestingParties>, cardinality: 1-3, record counter: NoRequestingPartyIDs (1657), containing occurrences: requesting_entering_firm, requesting_executing_system, requesting_executing_trader**				
1658	>RequestingPartyID	Y	STRING	Party identifier for the requesting party.
1659	>RequestingPartyIDSource	Y	CHAR	Identifies the source of the RequestingPartyID (1658) value. Value: D — Description: Proprietary custom code
1660	>RequestingPartyRole	Y	INT	Identifies the type or role of the RequestingPartyID (1658) specified. Value: 7 — Description: Entering firm Value: 12 — Description: Executing trader Value: 16 — Description: Executing system
</RequestingParties>				
2329	PartyActionType	N	INT	Party Action Type. Value: 1 — Description: Halt Trading Value: 2 — Description: Reinstate
30060	UTransactTime	Y	INT(20)	Transaction timestamp. Number of nanoseconds since Jan 1, 1970.
75	TradeDate	Y	LOCALMKTDATE	Business date in YYYYMMDD format.
1301	MarketID	Y	EXCHANGE	Market Identifier Code of the trading market according to ISO 10383.
<Trailer />				

8.21 User Party Risk Limits Update Report

User Party Risk Limits Update Report. This message communicates risk control events related to the Advanced Risk Protection functionality of T7 in case of a risk limit breach or release.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UCR' />				
<Parties>, cardinality: 3-5, record counter: NoPartyIDs (453), containing occurrences: clearing_firm, entering_firm, executing_system, executing_unit*, executing_firm**				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D — Description: Proprietary custom code
452	>PartyRole	Y	INT	Party Role. 1 — Executing firm 4 — Clearing firm 7 — Entering firm 16 — Executing system 59 — Executing unit
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. 22 — Algorithm 24 — Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>803</td><td>>PartySubIDType</td><td>N</td><td>INT</td><td>Type of PartySubID.<table><tr><td>Value</td><td>Description</td></tr><tr><td>2</td><td>Person</td></tr></table></td></tr>
<tr><td colspan="5"></Parties></td></tr>
<tr><td>75</td><td>TradeDate</td><td>Y</td><td>LOCALMKT-DATE</td><td>Business date in YYYYMMDD format.</td></tr>
<tr><td>25240</td><td>InventoryCheckType</td><td>N</td><td>INT</td><td>Indicator for checking open orders and quotes<table><tr><td>Value</td><td>Description</td></tr><tr><td>0</td><td>Do not check</td></tr><tr><td>1</td><td>Check</td></tr></table></td></tr>
<tr><td>1324</td><td>ListUpdateAction</td><td>N</td><td>CHAR</td><td>Invocation or release of a control event.<table><tr><td>Value</td><td>Description</td></tr><tr><td>A</td><td>Add (Invocation)</td></tr><tr><td>D</td><td>Delete (Release)</td></tr></table></td></tr>
<tr><td>1767</td><td>RiskLimitAction</td><td>N</td><td>INT</td><td>Risk protection action.<table><tr><td>Value</td><td>Description</td></tr><tr><td>0</td><td>Queue inbound</td></tr><tr><td>2</td><td>Reject</td></tr><tr><td>4</td><td>Warning</td></tr></table></td></tr>
<tr><td>30060</td><td>UTransactTime</td><td>Y</td><td>INT(20)</td><td>Transaction timestamp. Number of nanoseconds since Jan 1, 1970.</td></tr>
<tr><td>1301</td><td>MarketID</td><td>Y</td><td>EXCHANGE</td><td>Market Identifier Code of the trading market according to ISO 10383.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.22 User Party Risk Limits Request

The User Party Risk Limits Request is used to inquire pre-trade risk limits. These limits can be defined for on-book trading on product and user risk group level.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UCL' />				
<Parties>, cardinality: 1-2, record counter: NoPartyIDs (453), containing occurrences: entering_trader, executing_unit*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D — Description: Proprietary custom code
452	>PartyRole	Y	INT	Party Role. Value: 36 — Description: Entering trader Value: 59 — Description: Executing unit
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 — Description: Algorithm Value: 24 — Description: Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 — Description: Person
</Parties>				

Tag	Field Name	Req'd	Data Type	Description
1300	MarketSegmentID	Y	INT(10)	Product identifier.
1533	RiskLimitPlatform	Y	INT	The area to which risk limit is applicable. Scope of Pre-Trade risk limits. Value: 0 — Description: On-Book
1666	RiskLimitRequestID	Y	STRING (1-20)	Unique identifier for the User Party Risk Limits Request.
28775	RiskLimitGroup	N	STRING (1-3)	User Pre-Trade risk group
<Trailer />				

8.23 User Party Risk Limits Report

The User Party Risk Limits Report message is used as the application level response to a User Party Risk Limits Request.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='UCM' />				
<PartyRiskLimitsGrp>, cardinality: unrestricted, record counter: NoPartyRiskLimits (1677)				
<PartyDetailGrp>, cardinality: 1, record counter: NoPartyDetails (1671)				
1691	>PartyDetailID	Y	STRING (1-5)	The identification of the party.
1692	>PartyDetailIDSource	Y	CHAR	Source of the identifier of the PartyDetailID (1691) specified. Value: D — Description: Proprietary custom code
1693	>PartyDetailRole	Y	INT	PartyRole value within a target party repeating group. Value: 59 — Description: Executing unit
1672	>PartyDetailStatus	Y	INT	Member status. Value: 0 — Description: Active Value: 1 — Description: Suspended
</PartyDetailGrp>				
<RiskLimitsGrp>, cardinality: 1, record counter: NoRiskLimits (1669)				
<RiskLimitTypesGrp>, cardinality: 1-64, record counter: NoRiskLimitTypes (1529)				
1530	>RiskLimitType	Y	INT	Specifies the type of risk limit. Value: 4 — Description: Long Limit Value: 5 — Description: Short Limit
1533	>RiskLimitPlatform	Y	INT	The area to which risk limit is applicable. Scope of Pre-Trade risk limits. Value: 0 — Description: On-Book

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>28776</td><td>>RiskLimit-RequestingPartyRole</td><td>Y</td><td>INT</td><td>Requesting party role for a pre-trade risk limit.

<table><tr><th>Value</th><th>Description</th></tr><tr><td>4</td><td>Clearing firm</td></tr><tr><td>22</td><td>Exchange</td></tr><tr><td>59</td><td>Executing unit</td></tr></table></td></tr>
<tr><td>28778</td><td>>RiskLimitViolation-Indicator</td><td>Y</td><td>INT</td><td>Indicator for a pre-trade risk limit violation.
<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>No</td></tr><tr><td>1</td><td>Yes</td></tr></table></td></tr>
<tr><td>28775</td><td>>RiskLimitGroup</td><td>N</td><td>STRING (1-3)</td><td>User Pre-Trade risk group</td></tr>
<tr><td>28777</td><td>>RiskLimitQty</td><td>N</td><td>QTY</td><td>Risk limit quantity.</td></tr>
<tr><td>25205</td><td>>NettingCoefficient</td><td>N</td><td>FLOAT</td><td>Weighting factor used in the Extended PTRL consumption calculation. Default value is 1.0000 for trading members and 0.0000 for clearing members.</td></tr>
<tr><td>28779</td><td>>RiskLimitOpenQty</td><td>N</td><td>QTY</td><td>Open quantity for orders or TES trades.</td></tr>
<tr><td>28905</td><td>>ActivationDate</td><td>N</td><td>LOCALMKT-DATE</td><td>Business date when change is active</td></tr>
<tr><td>28780</td><td>>RiskLimitNet-PositionQty</td><td>N</td><td>QTY</td><td>Net position quantity for a requested pre-trade risk limit scope.</td></tr>
<tr><td>31763</td><td>>RiskLimitGroup-Status</td><td>N</td><td>INT</td><td>RiskLimitGroup status.
<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>Active</td></tr><tr><td>1</td><td>Suspend</td></tr></table></td></tr>
<tr><td colspan="5"></RiskLimitTypesGrp></td></tr>
<tr><td colspan="5"></RiskLimitsGrp></td></tr>
<tr><td colspan="5"></PartyRiskLimitsGrp></td></tr>
<tr><td>1300</td><td>MarketSegmentID</td><td>Y</td><td>INT(10)</td><td>Product identifier.</td></tr>
<tr><td>1666</td><td>RiskLimitRequestID</td><td>Y</td><td>STRING (1-20)</td><td>Unique identifier for the User Party Risk Limits Request.</td></tr>
<tr><td>1667</td><td>RiskLimitReportID</td><td>Y</td><td>INT</td><td>Numeric identifier for the User Party Risk Limits Report.</td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.24 CLIP Enter Request

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='U29' />				
<RootParties>, cardinality: 1-3, record counter: NoRootPartyIDs (1116), containing occurrences: root_entering_trader, root_contra_trader, root_contra_firm*				
1117	>RootPartyID	Y	STRING (1-10)	Root party identifier.
1118	>RootPartyIDSource	Y	CHAR	Identifies class or source of the RootPartyID (1117) value. Value: D — Description: Proprietary custom code
1119	>RootPartyRole	Y	INT	Identifies the type role of the RootPartyID (1117) specified. 17 — Contra firm 36 — Entering trader 37 — Contra trader
</RootParties>				
<CrossRequestSideGrp>, cardinality: 1-2, record counter: NoSides (552)				
<Parties>, cardinality: 0-11, record counter: NoPartyIDs (453), containing occurrences: client_id, investment_identifier_human, investment_identifier_algo, executing_trader, location_id, order_origination_firm, beneficiary, takeup_firm, position_account, execution_identifier_human, execution_identifier_algo				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. D — Proprietary custom code P — Short code identifier
452	>PartyRole	Y	INT	Party Role. 3 — Client ID 12 — Executing trader 13 — Order origination firm 32 — Beneficiary 38 — Position account 75 — Location ID 96 — Take-up (trading) firm 122 — Investment decision maker

Tag	Field Name	Req'd	Data Type	Description
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 = Algorithm; 24 = Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 = Person
</Parties>				
<OrderAttributeGrp>, cardinality: 0-2, record counter: NoOrderAttributes (2593), containing occurrences: liquidity_provision_activity_order, risk_reduction_order				
2594	>OrderAttributeType	N	INT	Type of order attribute. Value: 2 = Liquidity Provision Activity Order; 3 = Risk Reduction Order
2595	>OrderAttributeValue	N	CHAR	Value associated with the order attribute type specified in OrderAttributeType (2594). Value: Y = Attribute is set.
</OrderAttributeGrp>				
<MtchgInst>, cardinality: 0-1, record counter: NoMatchInst (1624)				
1625	>MatchInst	Y	INT	Matching Instruction for the order. Value: 2 = Do not match

Tag	Field Name	Req'd	Data Type	Description
28744	>MatchInstCrossID	Y	INT(10)	Numeric identifier. Contains the Self Match Prevention ID.
</MtchgInst>				
11	>ClOrdID	N	STRING (1-20)	Unique customer defined order request identifier
2964	>SelfMatch-PreventionInstruction	N	INT	Indicate the instruction for SMP Only applicable for CrossRequestType(28771) = 1(Cross Announcement) Value: 100 – Reject cross on business unit level Value: 101 – Reject cross on market level
31625	>CrossMatch-Instruction	N	INT	Indicate the instruction for SMP. Applicable only when MatchInstCrossID (28744) is set. When CrossMatchInstruction is not set the default value is defined by the exchange Only applicable for CrossRequestType(28771) = 1(Cross Announcement) Value: 1 – Cancel incoming order Value: 2 – Cancel resting order Value: 3 – Reduce/Cancel both incoming and resting order
28773	>MaximumPrice	N	PRICE	Maximum Price Only applicable for CrossRequestType(28771) = 2(Liquidity Improvement Cross)
979	>InputSource	N	INT	Role on/for a message Only applicable for CrossRequestType(28771) = 2(Liquidity Improvement Cross) Value: 1 – Client Broker Value: 2 – Proprietary Broker
54	>Side	Y	CHAR	Side Value: 1 – Buy Value: 2 – Sell

Tag	Field Name	Req'd	Data Type	Description
1815	>TradingCapacity	Y	INT	Trading capacity. Value: 1 = Customer (Agency); 5 = Principal (Proprietary); 6 = Market Maker
77	>PositionEffect	N	CHAR	Indicates whether the resulting position after a trade should be an opening position or closing position. Value: O = Open; C = Close
1031	>CustOrderHandling-Inst	N	CHAR	Rate identifier in accordance with the FIA guidelines.
1724	>OrderOrigination	N	INT	Direct market access identifier. Value: 5 = Direct market access; 105 = Sponsored access
1	>Account	N	STRING (2)	Account.
25007	>FreeText1	N	STRING (1-12)	First free-format text field for trader-specific or customer-related comments.
25008	>FreeText2	N	STRING (1-12)	Second free-format text field for trader-specific or customer-related comments.
25009	>FreeText3	N	STRING (1-12)	Third free-format text field for trader-specific or customer-related comments.
28774	>SideComplianceText	N	STRING (1-20)	Free format string, can include characters, numbers, punctuation and many special characters
25241	>PartyEndClient-Identification	N	STRING (1-20)	End client identifier.
</CrossRequestSideGrp>				
<SideCrossLegGrp>, cardinality: 0-40, record counter: NoCrossLegs (1829)				

Tag	Field Name	Req'd	Data Type	Description
25153	>LegInputSource	Y	INT	Role on/for a message - Client Broker(1) and Proprietary Broker(2) for CrossRequestType(28771) = 2(Liquidity Improvement Cross); Buy side(3) and Sell side(4) for CrossRequestType(28771) = 1(Cross Announcement) Value: Description 1: Client Broker 2: Proprietary Broker 3: Buy side 4: Sell side
564	>LegPositionEffect	Y	CHAR	Leg-specific field used to indicates whether the leg is submitted to open or close a position. Value: Description O: Open C: Close
2680	>LegAccount	N	STRING (2)	Leg-specific account.
</SideCrossLegGrp>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: Description M: Marketplace-assigned identifier

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>1227</td><td>ProductComplex</td><td>N</td><td>INT</td><td>This field qualifies an instrument type on T7 Derivatives.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Simple Instrument</td></tr><tr><td>2</td><td>Standard Option Strategy</td></tr><tr><td>3</td><td>Non-standard Option Strategy</td></tr><tr><td>4</td><td>Volatility Strategy</td></tr><tr><td>5</td><td>Futures Spread</td></tr><tr><td>6</td><td>Inter Product Spread</td></tr><tr><td>7</td><td>Standard Future Strategy</td></tr><tr><td>8</td><td>Pack and Bundle</td></tr><tr><td>9</td><td>Strip</td></tr><tr><td>10</td><td>Flexible Simple Instrument (used only for TES trades)</td></tr><tr><td>13</td><td>Non-standard Volatility Strategy</td></tr><tr><td>14</td><td>Total Return Future Strategy</td></tr></table></td></tr>
<tr><td>167</td><td>SecurityType</td><td>N</td><td>STRING (1-4)</td><td>Indicates the type of security.<table><tr><th>Value</th><th>Description</th></tr><tr><td>MLEG</td><td>Multileg Instrument</td></tr></table></td></tr>
<tr><td>762</td><td>SecuritySubType</td><td>N</td><td>INT(10)</td><td>Strategy type. Required for ProductComplex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy</td></tr>
<tr><td colspan="5"></Instrument></td></tr>
<tr><td colspan="5"><ValueChecksGrp>, cardinality: 0-2, record counter: NoValueChecks (1868), containing occurrences: price_check, notional_value_check</td></tr>
<tr><td>1869</td><td>>ValueCheckType</td><td>Y</td><td>INT</td><td>Type of value to be checked.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Price check</td></tr><tr><td>2</td><td>Notional value check</td></tr></table></td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
1870	>ValueCheckAction	Y	INT	Action to be taken for the ValueCheckType (1869). ValueCheckAction (1870) = '2' (Best effort) is only possible, if ValueCheckType (1869) = '1' (Price check). Value: 0 – Do not check; 1 – Check; 2 – Best effort
</ValueChecksGrp>				
44	Price	Y	PRICE	Limit price.
38	OrderQty	Y	QTY	Total Order Quantity.
548	CrossID	N	INT(10)	User defind CLIP arrangement ID.
2672	CrossRequestID	Y	INT(10)	Unique identifier for cross request. Uniqueness will be completely within the user's responsibility.
28771	CrossRequestType	Y	INT	Type of the Cross Request. Value: 1 – Cross Announcement; 2 – Liquidity Improvement Cross
549	CrossType	N	INT	Type of cross being submitted to a market. Only applicable for CrossRequestType(28771) = 1(Cross Announcement) Value: 2 – Immediate-or-cancel-cross; 3 – One sided cross - unfilled quantity remains active after crossing
550	CrossPrioritization	N	INT	Priorization of a cross order Only applicable for CrossRequestType(28771) = 1(Cross Announcement) Value: 1 – Buy side is prioritized; 2 – Sell side is prioritized

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>25130</td><td>SideDisclosure-Instruction</td><td>N</td><td>INT</td><td>Instruction to show side. Only supported for CrossRequestType(28771) = 2(Liquidity Improvement Cross)<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>No</td></tr><tr><td>1</td><td>Yes</td></tr></table></td></tr>
<tr><td>25131</td><td>PriceDisclosure-Instruction</td><td>N</td><td>INT</td><td>Instruction to show price. Only supported for CrossRequestType(28771) = 2(Liquidity Improvement Cross)<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>No</td></tr><tr><td>1</td><td>Yes</td></tr></table></td></tr>
<tr><td>25136</td><td>OrderQtyDisclosure-Instruction</td><td>N</td><td>INT</td><td>Instruction to show total quantity. Only supported for CrossRequestType(28771) = 2(Liquidity Improvement Cross)<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>No</td></tr><tr><td>1</td><td>Yes</td></tr></table></td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.25 CLIP Delete Request

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='U30' />				
<Parties>, cardinality: 1-5, record counter: NoPartyIDs (453), containing occurrences: entering_trader, execution_identifier_human, execution_identifier_algo, investment_identifier_human, investment_identifier_algo*				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.
447	>PartyIDSource	Y	CHAR	Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Value: D – Proprietary custom code Value: P – Short code identifier
452	>PartyRole	Y	INT	Party Role. Value: 12 – Executing trader Value: 36 – Entering trader Value: 122 – Investment decision maker
2376	>PartyRoleQualifier	N	INT	Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages. Value: 22 – Algorithm Value: 24 – Natural person
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 – Person

Tag	Field Name	Req'd	Data Type	Description
</Parties>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M — Marketplace-assigned identifier
1227	ProductComplex	N	INT	This field qualifies an instrument type on T7 Derivatives. 1 Simple Instrument 2 Standard Option Strategy 3 Non-standard Option Strategy 4 Volatility Strategy 5 Futures Spread 6 Inter Product Spread 7 Standard Future Strategy 8 Pack and Bundle 9 Strip 10 Flexible Simple Instrument (used only for TES trades) 13 Non-standard Volatility Strategy 14 Total Return Future Strategy
167	SecurityType	N	STRING (1-4)	Indicates the type of security. MLEG — Multileg Instrument
762	SecuritySubType	N	INT(10)	Strategy type. Required for ProductComplex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy
</Instrument>				
11	ClOrdID	N	STRING (1-20)	Unique customer defined order request identifier
37	OrderID	N	INT(20)	Exchange Order ID generated by the T7 system.

Tag	Field Name	Req'd	Data Type	Description
2672	CrossRequestID	Y	INT(10)	Unique identifier for cross request. Uniqueness will be completely within the user's responsibility.
<Trailer />				

8.26 CLIP Response

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='U31' />				
<CrossRequestAckSideGrp>, cardinality: 1-2, record counter: NoSides (552)				
37	>OrderID	Y	INT(20)	Exchange Order ID generated by the T7 system.
11	>ClOrdID	N	STRING (1-20)	Unique customer defined order request identifier
979	>InputSource	N	INT	Role on/for a message Value: 1 = Client Broker; 2 = Proprietary Broker
54	>Side	Y	CHAR	Side Value: 1 = Buy; 2 = Sell
</CrossRequestAckSideGrp>				
<Instrument>		Y		
55	Symbol	Y	STRING (1-10)	T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.
48	SecurityID	N	INT(20)	T7 instrument identifier.
22	SecurityIDSource	N	STRING (1)	Source of the securityID Value: M = Marketplace-assigned identifier

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>1227</td><td>ProductComplex</td><td>N</td><td>INT</td><td>This field qualifies an instrument type on T7 Derivatives.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Simple Instrument</td></tr><tr><td>2</td><td>Standard Option Strategy</td></tr><tr><td>3</td><td>Non-standard Option Strategy</td></tr><tr><td>4</td><td>Volatility Strategy</td></tr><tr><td>5</td><td>Futures Spread</td></tr><tr><td>6</td><td>Inter Product Spread</td></tr><tr><td>7</td><td>Standard Future Strategy</td></tr><tr><td>8</td><td>Pack and Bundle</td></tr><tr><td>9</td><td>Strip</td></tr><tr><td>10</td><td>Flexible Simple Instrument (used only for TES trades)</td></tr><tr><td>13</td><td>Non-standard Volatility Strategy</td></tr><tr><td>14</td><td>Total Return Future Strategy</td></tr></table></td></tr>
<tr><td>167</td><td>SecurityType</td><td>N</td><td>STRING (1-4)</td><td>Indicates the type of security.<table><tr><th>Value</th><th>Description</th></tr><tr><td>MLEG</td><td>Multileg Instrument</td></tr></table></td></tr>
<tr><td>762</td><td>SecuritySubType</td><td>N</td><td>INT(10)</td><td>Strategy type. Required for Product-Complex (1227) = 2=Standard Option Strategy, 4=Volatility Strategy, 6=Inter Product Spread, 7=Standard Future Strategy, 8=Pack and Bundle, 14 = Total Return Future Strategy</td></tr>
<tr><td colspan="5"></Instrument></td></tr>
<tr><td>17</td><td>ExecID</td><td>Y</td><td>STRING (80)</td><td>The field provides a unique identifier and can be used for the identification of duplicate order messages.</td></tr>
<tr><td>2672</td><td>CrossRequestID</td><td>N</td><td>INT(10)</td><td>Unique identifier for cross request. Uniqueness will be completely within the user's responsibility.</td></tr>
<tr><td>25244</td><td>ImpliedCheckPrice-Indicator</td><td>N</td><td>INT</td><td>Indicates whether a option strategy synthetic BBO is used for the price improvement check<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>No</td></tr><tr><td>1</td><td>Yes</td></tr></table></td></tr>
<tr><td colspan="5"><Trailer /></td></tr>
</table>

8.27 Session Details List

Session Details List provides a list of all trading sessions of the own business unit.

Tag	Field Name	Req'd	Data Type	Description
<Header with MsgType='U6' />				
<SessionGrp>, cardinality: unrestricted, record counter: NoSessions (28734)				
28766	>GatewaySessionID	Y	INT(10)	Identifier of an T7 session ID.
28730	>SessionMode	Y	INT	The session type. Value: 0 = ETI High Frequency session; 1 = ETI Low Frequency session; 2 = T7 GUI session; 3 = FIX LF session
28735	>SessionSubMode	Y	INT	The session subtype. Value: 0 = Regular Trading session; 4 = Sponsored Access Trading session
28767	>SecondarySessionID	N	STRING	FIX session CompID. Set only for FIX LF sessions.
20359	>PartyIDSponsored-AccessUnit	N	INT(10)	Sponsored Acces Unit ID.
22359	>PartySponsored-AccessUnit	N	STRING (1-30)	Sponsored Acces Unit Name.
</SessionGrp>				
30060	UTransactTime	Y	INT(20)	Transaction timestamp. Number of nanoseconds since Jan 1, 1970.
<Trailer />				

8.28 Trade Capture Report

The Trade Capture Report message is used to report trades and trade reversals via FIX Back-office sessions.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td colspan="5"><Header with MsgType='AE' /></td></tr>
<tr><td colspan="2"><Instrument></td><td>Y</td><td colspan="2"></td></tr>
<tr><td>55</td><td>Symbol</td><td>Y</td><td>STRING (1-10)</td><td>T7 product identifier. Cash only: Field must bet set to '[N/A]' in FIX requests where the ISIN is used as instrument identifier.</td></tr>
<tr><td>48</td><td>SecurityID</td><td>N</td><td>INT(20)</td><td>T7 instrument identifier.</td></tr>
<tr><td>22</td><td>SecurityIDSource</td><td>N</td><td>STRING (1)</td><td>Source of the securityID<table><tr><th>Value</th><th>Description</th></tr><tr><td>M</td><td>Marketplace-assigned identifier</td></tr></table></td></tr>
<tr><td>1227</td><td>ProductComplex</td><td>N</td><td>INT</td><td>This field qualifies an instrument type on T7 Derivatives.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Simple Instrument</td></tr><tr><td>2</td><td>Standard Option Strategy</td></tr><tr><td>3</td><td>Non-standard Option Strategy</td></tr><tr><td>4</td><td>Volatility Strategy</td></tr><tr><td>5</td><td>Futures Spread</td></tr><tr><td>6</td><td>Inter Product Spread</td></tr><tr><td>7</td><td>Standard Future Strategy</td></tr><tr><td>8</td><td>Pack and Bundle</td></tr><tr><td>9</td><td>Strip</td></tr><tr><td>10</td><td>Flexible Simple Instrument (used only for TES trades)</td></tr><tr><td>13</td><td>Non-standard Volatility Strategy</td></tr><tr><td>14</td><td>Total Return Future Strategy</td></tr></table></td></tr>
<tr><td>167</td><td>SecurityType</td><td>N</td><td>STRING (1-4)</td><td>Indicates the type of security.<table><tr><th>Value</th><th>Description</th></tr><tr><td>MLEG</td><td>Multileg Instrument</td></tr></table></td></tr>
<tr><td>762</td><td>SecuritySubType</td><td>N</td><td>INT(10)</td><td>Strategy type.</td></tr>
<tr><td colspan="5"></Instrument></td></tr>
<tr><td colspan="5"><RegulatoryTradeIDGrp>, cardinality: 0-1, record counter: NoRegulatoryTradeIDs (1907)</td></tr>
<tr><td>1903</td><td>>RegulatoryTradeID</td><td>N</td><td>STRING</td><td>Trading Venue Transaction Identifier (TVTIC).</td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
1906	>RegulatoryTrade-IDType	N	INT	Specifies the type of trade identifier provided in RegulatoryTradeID (1903). Value: 5 — Trading venue transaction identifier (TVTIC)
</RegulatoryTradeIDGrp>				
<SRQSRelatedTradeIDGrp>, cardinality: 0-1, record counter: NoSRQSRelatedTradeIDs (25174)				
25152	>SRQSRelatedTrade-ID	N	INT(10)	Provides together with the NegotiationID a link to the corresponding Xetra/Eurex Enlight deal.
</SRQSRelatedTradeIDGrp>				
<RootParties>, cardinality: 1, record counter: NoRootPartyIDs (1116), containing occurrences: root_execution_venue				
1117	>RootPartyID	Y	STRING (1-10)	Root party identifier.
1118	>RootPartyIDSource	Y	CHAR	Identifies class or source of the RootPartyID (1117) value. Value: G — Market identifier code
1119	>RootPartyRole	Y	INT	Identifies the type role of the RootPartyID (1117) specified. Value: 73 — Execution venue
</RootParties>				
*<TrdCapRptSideGrp>, cardinality: 1, record counter: NoSides (552), containing occurrences: Side1**				
54	>Side	Y	CHAR	Side of trade. Value: 1 — Buy; 2 — Sell
1009	>SideLastQty	N	QTY	Used to indicate the quantity on one of a multi-sided Trade Capture Report.
1506	>SideTradeID	N	INT(10)	Used to represent the trade ID for each side of the trade assigned by an intermediary.
<Parties>, cardinality: 0-23, record counter: NoPartyIDs (453)				
448	>PartyID	Y	STRING (1-35)	Party identifier/code.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>447</td><td>>PartyIDSource</td><td>Y</td><td>CHAR</td><td>Identifies class or source of the PartyID (448) value. Required if PartyID is specified.<table><tr><th>Value</th><th>Description</th></tr><tr><td>D</td><td>Proprietary custom code</td></tr><tr><td>P</td><td>Short code identifier</td></tr></table></td></tr>
<tr><td>452</td><td>>PartyRole</td><td>Y</td><td>INT</td><td>Party Role.<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Executing firm</td></tr><tr><td>3</td><td>Client ID</td></tr><tr><td>4</td><td>Clearing firm</td></tr><tr><td>7</td><td>Entering firm</td></tr><tr><td>12</td><td>Executing trader</td></tr><tr><td>13</td><td>Order origination firm</td></tr><tr><td>16</td><td>Executing system</td></tr><tr><td>17</td><td>Contra firm</td></tr><tr><td>21</td><td>Clearing organization</td></tr><tr><td>32</td><td>Beneficiary</td></tr><tr><td>36</td><td>Entering trader</td></tr><tr><td>37</td><td>Contra trader</td></tr><tr><td>38</td><td>Position account</td></tr><tr><td>55</td><td>Session ID</td></tr><tr><td>59</td><td>Executing unit</td></tr><tr><td>75</td><td>Location ID</td></tr><tr><td>96</td><td>Take-up (trading) firm</td></tr><tr><td>122</td><td>Investment decision maker</td></tr></table></td></tr>
<tr><td>2376</td><td>>PartyRoleQualifier</td><td>N</td><td>INT</td><td>Indicates the nature of value submitted in the field PartyID (448). PartyRoleQualifier (2376) = 21 (Specialist) and 22 (Algorithm) are only possible together with PartyIDSource (447) = 'D'. PartyRoleQualifier (2376) = 24 (Natural person) is only possible together with PartyIDSource (447) = 'P'. PartyRoleQualifier (2376) = 21 (Specialist) is not allowed in request messages.<table><tr><th>Value</th><th>Description</th></tr><tr><td>22</td><td>Algorithm</td></tr><tr><td>24</td><td>Natural person</td></tr></table></td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
802	>NoPartySubIDs	N	INT	Number of PartySubIDs. Only one entry. Only in combination with PartyRole (452) = 7 (Entering firm), 12 (Executing trader) and 36 (Entering trader) possible.
523	>PartySubID	N	STRING (1-6)	Firm or Trader Short Name, depending on the value of field PartySubIDType(803).
803	>PartySubIDType	N	INT	Type of PartySubID. Value: 2 – Person
</Parties>				
25027	>PartyIDClearingUnit	N	STRING	Party ID Clearing Unit.
1	>Account	N	STRING (2)	Account.
77	>PositionEffect	N	CHAR	Indicates whether the resulting position after a trade should be an opening position or closing position. Value: O – Open; C – Close
25007	>FreeText1	N	STRING (1-12)	First free-format text field for trader-specific or customer-related comments.
1115	>OrderCategory	N	CHAR	Defines the type of interest behind a trade (fill or partial fill). Value: 1 – Order; 2 – Quote
1444	>SideLiquidityInd	N	INT	Indicates whether the order added or removed liquidity. Field is used only for on-book trades. Value: 1 – Added Liquidity (passive); 2 – Removed Liquidity (aggressive); 4 – Auction (neither passive nor aggressive)
1851	>StrategyLinkID	N	INT(10)	Identifier that links all trades resulting from a match step of a strategy order.
37	>OrderID	N	INT(20)	Exchange Order ID generated by the T7 system.
11	>ClOrdID	N	STRING (1-20)	Unique customer defined order request identifier

Tag	Field Name	Req'd	Data Type	Description
40	>OrdType	N	CHAR	Order type. Value: 1 Market; 2 Limit; 3 Stop; 4 Stop limit
44	>Price	N	PRICE	Limit price.
151	>LeavesQty	N	QTY	Quantity open for further execution. If the OrdStatus (39) is Canceled, Expired, Calculated, or Rejected (in which case the order is no longer active) then LeavesQty could be 0, otherwise LeavesQty = OrderQty (38) - CumQty (14).
14	>CumQty	N	QTY	Cumulated executed quantity.
<OrderAttributeGrp>, cardinality: 0-2, record counter: NoOrderAttributes (2593)				
2594	>OrderAttributeType	N	INT	Type of order attribute. Value: 2 Liquidity Provision Activity Order; 3 Risk Reduction Order
2595	>OrderAttributeValue	N	CHAR	Value associated with the order attribute type specified in OrderAttributeType (2594). Value: Y Attribute is set.
</OrderAttributeGrp>				
1031	>CustOrderHandlingInst	N	CHAR	Rate identifier in accordance with the FIA guidelines. Value: W Desk; Y Electronic; C FCM-provided screen; G FCM API or FIX; H Algo Engine; D Default; * More values
25008	>FreeText2	N	STRING (1-12)	Second free-format text field for trader-specific or customer-related comments.
25009	>FreeText3	N	STRING (1-12)	Third free-format text field for trader-specific or customer-related comments.
28585	>SideLastPx	N	PRICE	Fill price for the original Eurex strategy. Only provided in case of a multileg instrument.

Tag	Field Name	Req'd	Data Type	Description
32999	>FeeIdntCode	N	STRING (15)	This field indicates the Fee Code associated with the transaction.
</TrdCapRptSideGrp>				
30	LastMkt	Y	EXCHANGE	Operating MIC. Market Identifier Code of the trading market according to ISO 10383.
31	LastPx	Y	PRICE	Price level.
32	LastQty	Y	QTY	Quantity executed.
75	TradeDate	Y	LOCALMKT-DATE	Business date in YYYYMMDD format.
442	MultiLegReporting-Type	N	CHAR	This field indicates if the Trade Capture Report results from a single leg or multileg order. Value: 1 – Single leg; 2 – Individual leg of a multileg security
571	TradeReportID	Y	INT	Unique identifier of the Trade Capture Report.
574	MatchType	N	INT	The point in the matching process at which this trade was matched. Value: 3 – Confirmed Trade Report; 4 – Auto Match Incoming; 5 – Cross Auction; 7 – Call Auction; 11 – Auto Match Resting; 13 – Liquidity Improvement Cross
700	ReversalIndicator	N	BOOLEAN	Reversal Indicator for TES Trades. Value: N – No reversal; Y – Reversal
748	TotNumTradeReports	N	INT(10)	Number of leg executions of the original strategy order.
810	UnderlyingPx	N	PRICE	Underlying price associated with a derivative instrument.

<table>
<tr><th>Tag</th><th>Field Name</th><th>Req'd</th><th>Data Type</th><th>Description</th></tr>
<tr><td>828</td><td>TrdType</td><td>Y</td><td>INT</td><td>Identifier of the trade type.<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>Regular Trade (on-book)</td></tr><tr><td>1</td><td>Block Trade</td></tr><tr><td>12</td><td>Exchange for Swap (EFS)</td></tr><tr><td>1000</td><td>Vola Trade</td></tr><tr><td>1001</td><td>Exchange for physical (EFP) Fin trade</td></tr><tr><td>1002</td><td>Exchange for physical (EFP) Index Future trade</td></tr><tr><td>1004</td><td>Trade at market</td></tr><tr><td>1006</td><td>Xetra/Eurex EnLight triggered trade</td></tr><tr><td>1007</td><td>QTPIP Block Trade</td></tr></table></td></tr>
<tr><td>830</td><td>TransferReason</td><td>Y</td><td>INT</td><td>Reason trade is being transferred<table><tr><th>Value</th><th>Description</th></tr><tr><td>1</td><td>Owner</td></tr><tr><td>2</td><td>Clearer</td></tr></table></td></tr>
<tr><td>856</td><td>TradeReportType</td><td>Y</td><td>INT</td><td>Type of Trade Report.<table><tr><th>Value</th><th>Description</th></tr><tr><td>0</td><td>Submit</td></tr><tr><td>1</td><td>Alleged</td></tr><tr><td>5</td><td>No/Was (Replaced)</td></tr><tr><td>7</td><td>(Locked-In) Trade Break</td></tr></table></td></tr>
<tr><td>880</td><td>TrdMatchID</td><td>N</td><td>INT(10)</td><td>Identifier assigned to a trade by a matching system.</td></tr>
<tr><td>1003</td><td>TradeID</td><td>Y</td><td>INT(10)</td><td>The unique ID assigned to the trade entity once it is received or matched by the exchange or central counterparty.</td></tr>
<tr><td>1011</td><td>MessageEventSource</td><td>Y</td><td>INT</td><td>Receiver of a message.<table><tr><th>Value</th><th>Description</th></tr><tr><td>200</td><td>On-Book Trade Notification</td></tr><tr><td>201</td><td>TES Trade Notification</td></tr></table></td></tr>
<tr><td>1126</td><td>OrigTradeID</td><td>N</td><td>INT(10)</td><td>Used to preserve original trade id when original trade is being referenced in a subsequent trade transaction such as a transfer.</td></tr>
</table>

Tag	Field Name	Req'd	Data Type	Description
1390	TradePublishIndicator	N	INT	Indicates if a trade should be or has been published via a market publication service. Value: 2 = Deferred Publication; 3 = Published
1596	ClearingTradePrice	N	PRICE	Clearing price.
1649	RelatedSymbol	N	INT(10)	Product identifier of the originating Eurex strategy.
1650	RelatedSecurityID	N	INT(20)	Instrument identifier of the original Eurex strategy.
1724	OrderOrigination	N	INT	Direct market access identifier. Value: 5 = Direct market access; 105 = Sponsored access
1815	TradingCapacity	N	INT	Trading capacity. Value: 1 = Customer (Agency); 5 = Principal (Proprietary); 6 = Market Maker
2489	PackageID	N	INT(10)	Identifier for a TES trade.
25161	BasketTrdMatchID	N	INT(20)	Basket ID assigned by the T7 system. The field will be populated for TES trades that are part of a basket.
25248	OrigBasketTrdMatchID	N	INT(20)	Original Basket ID assigned by the T7 system. The field will be populated for TES trades that are part of a basket.
25162	BasketSideTradeReportID	N	STRING (1-20)	Individual Basket ID assigned by the approver of a basket. The field will be set for TES trades that are part of a basket if the field was populated when the basket was approved.
25182	BasketPartyContraFirm	N	STRING (1-20)	Counterparty information for TES trades that are part of a basket.
25247	OptionalEarlyTerminationIndicator	N	INT	Indicates whether the counterparties have the right for early termination Value: 0 = No; 1 = Yes

Tag	Field Name	Req'd	Data Type	Description
28586	OrderSide	N	CHAR	Side of the order in the original T7 strategy. Value: 1 = Buy; 2 = Sell
28587	RelatedProduct-Complex	N	INT	Instrument type in the original Eurex strategy. Value: 2 = Standard Option Strategy; 3 = Non-standard Option Strategy; 4 = Volatility Strategy; 5 = Futures Spread; 6 = Inter Product Spread; 7 = Standard Future Strategy; 8 = Pack and Bundle; 9 = Strip; 13 = Non-standard Volatility Strategy; 14 = Total Return Future Strategy
28610	MatchSubType	N	INT	Indicates the call auction type the trade originates from. Field is used only for on-book trades. Value: 1 = Opening auction; 2 = Closing auction; 3 = Intraday auction; 4 = Circuit breaker auction; 6 = Outside BBO (CLIP matching outside BBO)
28736	ClearingTradeQty	N	QTY	Quantity used for clearing.
28750	MultilegPriceModel	N	INT	Price decomposition method for legs of a complex instrument. Value: 0 = Standard (leg level prices provided by system); 1 = User defined (leg level prices provided by user)
28758	NegotiationID	N	INT(10)	ID of a Xetra/Eurex EnLight negotiation.
28899	BasketProfileID	N	INT(10)	Basket Profile ID.

Tag	Field Name	Req'd	Data Type	Description
2788	TradeAggregation-TransType	N	INT	TES Trade Aggregation Identifier. Value: 0 — New
30060	UTransactTime	Y	INT(20)	Transaction timestamp. Number of nanoseconds since Jan 1, 1970.
<Trailer />				

9 Occurrences

9.1 OrderAttributeGrp

This section contains all occurrences of structure "OrderAttributeGrp".

liquidity_provision_activity_order
Flag to indicate liquidity provision.

- OrderAttributeType = LIQUIDITY_PROVISION_ACTIVITY_ORDER (mandatory)
- OrderAttributeValue = ATTRIBUTE_IS_SET (mandatory)

risk_reduction_order
Flag to indicate risk reduction.

- OrderAttributeType = RISK_REDUCTION_ORDER (mandatory)
- OrderAttributeValue = ATTRIBUTE_IS_SET (mandatory)

9.2 Parties

This section contains all occurrences of structure "Parties".

beneficiary
Beneficiary Account. The field PartyID must have a length of 9 and the first character must not be a space (0x20)

- PartyID (mandatory)
- PartyRole = BENEFICIARY (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

clearing_firm
Clearing firm information.

- PartyID (mandatory)
- PartyRole = CLEARING_FIRM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

clearing_organization
Clearing organization information.

- PartyID (mandatory)
- PartyRole = CLEARING_ORGANIZATION (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

clearing_unit
Party ID Clearing Unit.

- PartyID (mandatory)
- PartyRole = CLEARING_FIRM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

client_id
Client Identifier (short code). Note that leading zeros will be removed.

- PartyID (mandatory)
- PartyRole = CLIENT_ID (mandatory)
- PartyIDSource = SHORT_CODE_IDENTIFIER (mandatory)

entering_firm
Entering Entity ID. PartyID 1 = Participant, 2 = Market Supervision

- PartyID (mandatory)
- PartyRole = ENTERING_FIRM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

entering_trader
Entering User ID.

- PartyID (mandatory)
- PartyRole = ENTERING_TRADER (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

executing_firm
Executing firm information.

- PartyID (mandatory)
- PartyRole = EXECUTING_FIRM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

executing_system
Executing system information (1 = Clearing System, 2 = T7 Trading System).

- PartyID (mandatory)
- PartyRole = EXECUTING_SYSTEM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

executing_trader
Executing trader information.

- PartyID (mandatory)
- PartyRole = EXECUTING_TRADER (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- PartySubIDType = PERSON (optional)

executing_unit
Executing unit information.

- PartyID (mandatory)
- PartyRole = EXECUTING_UNIT (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

execution_identifier_algo
Execution identifier algorithm. To be used mutually exclusive with 'execution_identifier_human'

- PartyID (mandatory)
- PartyRole = EXECUTING_TRADER (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- PartyRoleQualifier = ALGORITHM (mandatory)

execution_identifier_human
Execution identifier human. To be used mutually exclusive with 'execution_identifier_algorithm'

- PartyID (mandatory)
- PartyRole = EXECUTING_TRADER (mandatory)
- PartyIDSource = SHORT_CODE_IDENTIFIER (mandatory)
- PartyRoleQualifier = NATURAL_PERSON (mandatory)

investment_identifier_algo
Investment identifier algorithm. To be used mutually exclusive with 'investment_identifier_human'

- PartyID (mandatory)
- PartyRole = INVESTMENT_DECISION_MAKER (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- PartyRoleQualifier = ALGORITHM (mandatory)

investment_identifier_human
Investment identifier human. To be used mutually exclusive with 'investment_identifier_algorithm'

- PartyID (mandatory)
- PartyRole = INVESTMENT_DECISION_MAKER (mandatory)
- PartyIDSource = SHORT_CODE_IDENTIFIER (mandatory)
- PartyRoleQualifier = NATURAL_PERSON (mandatory)

location_id
Location ID information. Origin country code to identify the region from which the transaction originates.

- PartyID (mandatory)
- PartyRole = LOCATION_ID (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

order_origination_firm
Executing firm information. The field PartyID must have a length of 7 with the last 4 characters set to spaces (0x20)

- PartyID (mandatory)
- PartyRole = ORDER_ORIGINATION_FIRM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

position_account
Flexible account identifier.

- PartyID (mandatory)
- PartyRole = FLEXIBLE_ACCOUNT_IDENTIFIER (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

session_ID
Session ID.

- PartyID (mandatory)
- PartyRole = SESSION_ID (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

settlement_account
Settlement Account.

- PartyID (mandatory)
- PartyRole = SETTLEMENT_ACCOUNT (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

settlement_firm
Settlement Firm.

- PartyID (mandatory)
- PartyRole = SETTLEMENT_FIRM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

settlement_location
Settlement location information.

- PartyID (mandatory)
- PartyRole = SETTLEMENT_LOCATION (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

settlement_unit
Party ID Settlement Unit.

- PartyID (mandatory)
- PartyRole = SETTLEMENT_FIRM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

takeup_firm
Take-up trading firm information.

- PartyID (mandatory)
- PartyRole = TAKEUP_FIRM (mandatory)
- PartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

9.3 RequestingParties

This section contains all occurrences of structure "RequestingParties".

requesting_entering_firm
Requesting entering firm information.

- RequestingPartyID (mandatory)
- RequestingPartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- RequestingPartyRole = ENTERING_FIRM (mandatory)

requesting_executing_system
Requesting executing system information.

- RequestingPartyID (mandatory)
- RequestingPartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- RequestingPartyRole = EXECUTING_SYSTEM (mandatory)

requesting_executing_trader
Requesting executing trader information.

- RequestingPartyID (mandatory)
- RequestingPartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- RequestingPartyRole = EXECUTING_TRADER (mandatory)

9.4 RootParties

This section contains all occurrences of structure "RootParties".

root_contra_firm
The identifier of the member counterparty institution

- RootPartyID (mandatory)
- RootPartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- RootPartyRole = CONTRA_FIRM (mandatory)

root_contra_trader
The identifier of the trader counterparty

- RootPartyID (mandatory)
- RootPartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- RootPartyRole = CONTRA_TRADER (mandatory)

root_entering_trader
Entering User ID

- RootPartyID (mandatory)
- RootPartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)
- RootPartyRole = ENTERING_TRADER (mandatory)

root_execution_venue
Execution venue (segment MIC).

- RootPartyID (mandatory)
- RootPartyIDSource = MARKET_IDENTIFIER_CODE (mandatory)
- RootPartyRole = EXECUTION_VENUE (mandatory)

9.5 TargetParties

This section contains all occurrences of structure "TargetParties".

target_executing_trader
Executing trader information.

- TargetPartyID (mandatory)
- TargetPartyRole = EXECUTING_TRADER (mandatory)
- TargetPartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

target_session_ID
Session ID.

- TargetPartyID (mandatory)
- TargetPartyRole = SESSION_ID (mandatory)
- TargetPartyIDSource = PROPRIETARYCUSTOMCODE (mandatory)

9.6 TrdCapRptSideGrp

This section contains all occurrences of structure "TrdCapRptSideGrp".

Side1
Side 1 information.

- Side (mandatory)
- SideLastQty (optional)
- SideTradeID (mandatory)
- Parties (mandatory)
  - occurrences:
    - clearing_firm (mandatory)
    - clearing_organization (mandatory)
    - executing_trader (mandatory)
    - executing_firm (mandatory)
    - executing_unit (mandatory)
    - session_ID (optional)
    - order_origination_firm (optional)
    - beneficiary (optional)
    - position_account (optional)
    - takeup_firm (optional)
    - settlement_location (mandatory)
    - settlement_account (mandatory)
    - settlement_firm (mandatory)
    - client_id (optional)
    - execution_identifier_human (optional)
    - execution_identifier_algo (optional)
    - investment_identifier_human (optional)
    - investment_identifier_algo (optional)
  - PartyID (mandatory)
  - PartyIDSource (mandatory)
  - PartyRole (mandatory)
  - PartyRoleQualifier (optional)
  - NoPartySubIDs (optional)
  - PartySubID (optional)
  - PartySubIDType (optional)
- PartyIDClearingUnit (optional)

- Account (optional)
- PositionEffect (optional)
- FreeText1 (optional)
- OrderCategory (optional)
- SideLiquidityInd (optional)
- StrategyLinkID (optional)
- OrderID (optional)
- OrdType (optional)
- Price (optional)
- LeavesQty (optional)
- CumQty (optional)
- OrderAttributeGrp (optional)
  - OrderAttributeType (optional)
  - OrderAttributeValue (optional)
- CustOrderHandlingInst (optional)
- FreeText2 (optional)
- FreeText3 (optional)
- SideLastPx (optional)
- FeeIdntCode (optional)

9.7 ValueChecksGrp

This section contains all occurrences of structure "ValueChecksGrp".

notional_value_check
Notional value validation.

- ValueCheckType = NOTIONAL_VALUE_CHECK (mandatory)
- ValueCheckAction (mandatory)

price_check
Price validation.

- ValueCheckType = PRICE_CHECK (mandatory)
- ValueCheckAction (mandatory)