

Cboe Titanium Cboe Japan Equities FIX Specification

Version 1.0.13

June 9, 2025

This content is owned or licensed by Cboe Global Markets, Inc. or its affiliates (“Cboe”) and protected by copyright under U.S. and international copyright laws. Other than for internal business purposes, you may not copy, reproduce, distribute, publish, display, perform, modify, create derivative works, transmit, or in any way exploit the content, sell or offer it for sale, use the content to construct any kind of database, or alter or remove any copyright or other notice from copies of the content.

Contents

1 Introduction 4
1.1 Overview 4
1.2 Data Types 4
1.2.1 Timestamps 4
1.2.2 Prices 4
1.3 Hours of Operation 4
1.4 Protocol Features 4
1.4.1 Architecture 4
1.4.2 Maximum Open Order Limits 5

2 Protocol 6
2.1 Message Format 6
2.2 Sequence Numbers 6
2.3 Version Compatibility 6

3 Sessions 7
3.1 Connectivity and Certification 7
3.2 Logon 8
3.3 Heartbeat 8
3.4 Test Request 9
3.5 Resend Request 9
3.6 Reject 9
3.7 Sequence Reset 10
3.8 Logout 10

4 FIX Messages 10
4.1 Standard Message Header 10
4.2 Standard Message Trailer 12
4.3 Cboe Specific Fields 13
4.4 Order Protocol – Participant to Cboe 14
4.4.1 New Order Single 14
4.4.2 Order Cancel Request 19
4.4.3 Order Cancel/Replace Request 20
4.5 Order Protocol – Cboe to Participant 23
4.5.1 Execution Report 23
4.5.2 Cancel Reject 29
4.5.3 Trade Cancel/Correct 29
4.5.4 Trading Session Status 30
4.6 Purge Port Protocol – Participant to Cboe 31
4.6.1 Purge Request 31
4.7 Purge Port Protocol – Cboe to Participant 34

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

4.7.1 Purge Acknowledgement 34
4.7.2 Purge Reject 34

5 Order Types and Features 35
5.1 Iceberg Order 35
5.1.1 New Iceberg Order 35
5.1.2 Reloading Iceberg Order 35
5.2 Peg Orders 36
5.2.1 Midpoint Peg Order 36
5.2.2 Primary Peg Order 36
5.2.3 Market Peg Order 36
5.2.4 Peg Order Fields 36
5.2.5 Peg Suspended and Resumed 37

6 Implementation Notes 39
6.1 Automatic Cancel on Disconnect or Malfunction 39

7 FIX Drop 40
7.1 Standard FIX Trade Drop 40
7.2 Order by Order FIX Drop 40
7.3 FIX Drop Port Attributes 40

8 FIX Port Attributes 41

9 Contact Information 43

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

1 Introduction

1.1 Overview

Cboe participants use a subset of the FIX 4.2 protocol for order entry and drop copies.

It is assumed the reader is familiar with the FIX 4.2 protocol as described at http://www.fixprotocol.org. This document describes the differences between the Cboe implementation and the FIX 4.2 standard.

1.2 Data Types

1.2.1 Timestamps

All FIX timestamps are UTC as per the FIX standard. Participants are expected to synchronize their clocks with an external time source.

Timestamps in messages from Cboe Japan will have microsecond or nanosecond formatting ("YYYY-MM-DD HH:MM:SS.ssssss" or "YYYY-MM-DD HH:MM:SS.ssssss000", respectively), depending on the configuration of port attribute "Nanosecond Timestamp Granularity".

Timestamps on messages to Cboe Japan may have any precision in UTC format but will be treated by Cboe Japan at no finer than microsecond precision.

1.2.2 Prices

Participants should program their systems to allow execution prices to be returned with up to four decimals for orders. Orders having invalid tick sizes will be rejected. Orders having prices greater than ¥ 99,999,999 will be rejected.

1.3 Hours of Operation

Refer to the website for the Cboe Japan holiday schedule and trading hours.

Orders are rejected if they are received outside the hours Cboe Japan is available for trading.

1.4 Protocol Features

The exchange does not guarantee messages sent by Members to the exchange, including through protocols such as TCP. Members are responsible to monitor the status of the messages they send to the exchange.

1.4.1 Architecture

Each FIX order handler process allows a single TCP connection from a participant. Connection attempts from unknown source IP ranges will be blocked to prevent unauthorized access to FIX ports. The Cboe Japan Trade Desk should be contacted if a firm desires to connect from a new source IP range.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

Each FIX order handler will connect, using a proprietary UDP protocol, to all matching units (a matching unit is a subsystem which handles orders and trades for a range of symbols).

1.4.2 Maximum Open Order Limits

Cboe Japan limits the maximum number of open orders allowed on a FIX port to 300,000 per port. New orders will be rejected once this limit is breached until the number of open orders drops back below the limit.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

2 Protocol

2.1 Message Format

FIX messages are ASCII formatted. Participants will be provided with a *SenderCompId* and *SenderSubId* that must be sent on every message. The *TargetCompId* for all messages the Participant sends is 'CXJA' for the Alpha/Match marketplace and 'CXJS' for the Select marketplace.

All messages the Participant receives will have the Sender and Target fields swapped.

2.2 Sequence Numbers

Sequence numbers, both inbound and outbound, will be reset to 1 each night during the down time.

Messages are processed in sequence order. Behind sequence messages (other than Sequence Reset – Reset) cause immediate logout. Ahead of sequence messages (other than a Resend Request) trigger a message recovery via a Resend Request.

2.3 Version Compatibility

Cboe uses the FIX 4.2 session protocol.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

3 Sessions

The following session messages are supported in both directions:

Message	Type	Comment
Logon	A	Begin session (or resume a broken session).
Heartbeat	0	
Test Request	1	
Resend Request	2	
Reject	3	Malformed message or improper session level handling.
Sequence Reset	4	Both Gap Fill (*GapFillFlag*=Y) and Reset.
Logout	5	Used to gracefully close session.

3.1 Connectivity and Certification

IP Address	Address to connect to.	Supplied by Cboe.
TCP Port	Port to connect to.	Supplied by Cboe.
SenderCompID	Sent in every FIX message to Cboe.	Supplied by Cboe.
SenderSubID	Sent in every FIX message to Cboe.	Supplied by Cboe.
TargetCompID	Sent in every FIX message to Cboe.	'CXJA' (Alpha/Match) 'CXJS' (Select)
TargetSubID	Sent in every FIX message to Cboe.	'TEST' for test/certification system. 'PROD' for production.

For information on connectivity options to Cboe, refer to the Cboe Japan Connectivity Manual.

All new participants must pass certification before they will be permitted to enter orders in the production marketplace. Certain new order types and options will also require certification before they may be utilized. Contact the Cboe Japan Trade Desk for more information.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

3.2 Logon

Tag	Field Name	Req'd	Description
35	*MsgType*	Y	A
108	*HeartbeatInterval*	Y	Client Heartbeat Interval (in seconds).

The Logon must be the first message sent by the participant after the TCP connection is established. EncryptMethod is ignored (FIX level encryption is not supported).

Cboe will wait one second after a Logon is received to ensure no Resend Request messages are in flight from the Participant. A Heartbeat will be sent to indicate the one-second wait period has ended. **Participants should not send any orders prior to receiving this first Heartbeat from Cboe.**

The IP Address of the participant, the *SenderCompId*, *SenderSubId, TargetCompId*, and *TargetSubId* ('TEST'/'PROD') will be validated. If validation fails, the connection will be dropped without a Reject (to avoid corrupting the participant's sequence in the case that the participant merely mistakenly connected to the wrong port).

If connection is unexpectedly broken, upon reconnection the participant may receive a login reply with a sequence number greater than expected. This means in-flight messages were missed (likely important Execution Reports). The participant should issue a Resend Request to retrieve the missed messages.

Similarly, Cboe will issue a Resend Request to the participant for messages it missed. Participants may wish to send gap fill messages in place of new orders to avoid re-submission of potentially stale orders.

HeartbeatInterval must be specified by the participant in the Logon message. This value will be clamped between 5 and 300 seconds and returned in the logon reply message. Cboe recommends using as low a value as the reliability and latency of your connectivity allows.

3.3 Heartbeat

Tag	Field Name	Req'd	Description
35	*MsgType*	Y	0
112	*TestReqID*	N	Required in response to a Test Request.

A Heartbeat message should be sent if the agreed upon *HeartbeatInterval* has elapsed since the last message sent. If any message has been sent during the preceding *HeartbeatInterval* a Heartbeat message need not be sent.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

3.4 Test Request

Tag	Field Name	Req'd	Description
35	*MsgType*	Y	1
112	*TestReqID*	Y	Auto-generated request ID.

If a *HeartbeatInterval* + 1 seconds have elapsed since the last message received, a Test Request should be issued. If another *HeartbeatInterval* + 1 seconds elapse without receiving a message, the TCP connection should be dropped. This ensures a broken TCP connection will be detected even if the TCP stack does not notice (this has been observed to happen in WAN environments, particularly when a VPN is involved).

3.5 Resend Request

Tag	Field Name	Req'd	Description
35	*MsgType*	Y	2
7	*BeginSeqNo*	Y	Auto-generated request ID.
16	*EndSeqNo*	Y	0 means + infinity

A Resend Request message should be processed even if it is received ahead of sequence. Only after resending the requested range (all marked *PossDup*='Y', including any gap fills) should Resend Request be issued in the opposite direction.

As discussed in the FIX 4.2 specification, it is possible to send an open or closed sequence range in a Resend Request (an open range uses sequence zero as the *EndSeqNo*). Cboe will honor either type of request but will always issue Resend Requests with a closed sequence range.

3.6 Reject

Tag	Field Name	Req'd	Description
35	*MsgType*	Y	3
45	*RefSeqNum*	Y	*MsgSeqNum* of rejected message.
371	*RefTagID*	N	
372	*RefMsgType*	N	
373	*SessionRejectReason*	N	
58	*Text*		

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

Session level rejects indicate violations of the session protocol or missing (or bogus) fields. These are expected during development and certification while the participant is being adapted for Cboe but should be extremely rare in production. Application layer rejects (Order Rejects or Cancel Rejects) are normal.

3.7 Sequence Reset

Tag	Field Name	Req'd	Description
35	*MsgType*	Y	4
36	*NewSeqNo*	Y	*Next expected sequence number.*
123	*GapFillFlag*	N	Sequence Reset – Gap Fill messages (*GapFillFlag*='Y') must be received in sequence. Any messages (including any Gap Fills) sent in response to a Resend Request should have PossDup='Y'. Sequence Reset – Reset (*GapFillFlag* not 'Y') is used only as a last resort, and always by human intervention, to allow an otherwise hopelessly confused session to be resumed. In these cases, all chance at automatic message recovery is lost.

3.8 Logout

Tag	Field Name	Req'd	Description
35	*MsgType*	Y	5
58	*Text*	N	*Indicates reason for Logout.*

Either side may issue a Logout to gracefully close the session. The side issuing the Logout should process messages normally until it sees the logout reply, and then break the TCP connection.

4 FIX Messages

4.1 Standard Message Header

Tag	Field Name	Req'd	Description
8	*BeginString*	Y	FIX.4.2 Must be first field in message.
9	*BodyLength*	Y	Length of message following *BodyLength* field up to and including the delimiter preceding the *CheckSum* field.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

			Must be second field in message.
35	*MsgType*	Y	Must be third field in message. 0 = Heartbeat 1 = TestRequest 2 = ResendRequest 3 = Reject 4 = SequenceReset 5 = Logout 8 = ExecutionReport 9 = OrderCancelReject A = Logon D = NewOrderSingle F = OrderCancelRequest G = OrderCancelReplaceRequest h = TradingSessionStatus UCC = Trade Cancel/Correct
49	*SenderCompID*	Y	ID of sender: Assigned by Cboe for messages sent to Cboe. (*TargetCompID* for messages from Cboe)
50	*SenderSubID*	Y	Sub ID of sender: Assigned by Cboe for messages sent to Cboe. (*TargetSubID* for messages from Cboe)
56	*TargetCompID*	Y	ID of destination: 'CXJA' for messages sent to the Alpha/Match marketplace. 'CXJS' for messages sent to the Select marketplace. (*SenderCompID* for messages from Cboe)

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

57	*TargetSubID*	Y	Sub ID of destination: 'TEST' for messages sent to Cboe test/certification system. 'PROD' for messages sent to Cboe production system. (*SenderSubID* for messages from Cboe)
34	*MsgSeqNum*	Y	Sequential sequence number for session.
43	*PossDupFlag*	N	N = (Default) Y = Indicates a message resend and should be used during FIX Replay. Cboe will reject all inbound orders with 'Y'.
52	*SendingTime*	Y	UTC date-time that message was sent.
122	*OrigSendingTime*	N	For messages with *PossDupFlag*='Y', indicates time that message was first sent.

4.2 Standard Message Trailer

A standard trailer terminates each message.

Tag	Field Name	Description
10	*CheckSum*	Modulo 256 *CheckSum* of all characters in message up to and including the delimiter preceding the *CheckSum* field. Three digits with leading zeroes if necessary.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

4.3 Cboe Specific Fields

The following FIX fields are specific to Cboe:

Tag	Field Name	Description
7695	*MassCancelID*	Refer to definition in the Purge Request Section 4.6.1, Purge Acknowledgement Section 4.7.1, and Purge Rejected Section 4.7.2 for more details.
7696	*CancelledOrderCount*	Refer to definition in the Purge Acknowledgement Section 4.7.1 for more details.
7698	*RiskGroupIDCnt*	Refer to definition in the Purge Request Section 4.6.1 for more details.
7699	*RiskGroupID*	Refer to definition in the New Order Single Section 4.4.1, Purge Request Section 4.6.1, and Execution Report Section 4.5.1 for more details.
7700	*MassCancelInst*	Refer to definition in the Purge Request Section 4.6.1 for more details.
9688	*OrigCompID*	Refer to definition in the Execution Report Section 4.5.1 for more details.
9689	*OrigSubID*	Refer to definition in the Execution Report Section 4.5.1 for more details.
9690	*WorkingPrice*	Refer to definition in the Execution Report Section 4.5.1 for more details.
7699	*RiskGroupID*	Refer to definition in the New Order Single Section 4.4.1 for more details.
7713	*NoTradeFeat*	Refer to definition in the New Order Single Section 4.4.1 for more details.
7714	*NoTradeKey*	Refer to definition in the New Order Single Section 4.4.1 for more details.
7903	*PreventedTradePx*	Refer to definition in the Execution Report Section 4.5.1 for more details.
7904	*PreventedTradeQty*	Refer to definition in the Execution Report Section 4.5.1 for more details.
7905	*PreventedTradeLiquidityIndicator*	Refer to definition in the Execution Report Section 4.5.1 for more details.
8004	*VWAPSessionID*	Refer to definition in the New Order Single Section 4.4.1 for more details.
8060	*OrderClassification*	Refer to definition in the New Order Single Section 4.4.1 for more details.
8105	*Pullback*	Refer to definition in the New Order Single Section 4.4.1 for more details.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

8214	*MarginTransactionType*	Refer to definition in the New Order Single Section 4.4.1 for more details.
9303	*RoutingInst*	Refer to definition in the New Order Single Section 4.4.1 for more details.
9617	*ModifySequence*	Refer to definition in the Execution Report Section 4.5.1 for more details.
9619	*CancelOrigOnReject*	Refer to definition in the Order Cancel/Replace Section 4.4.3 for more details.
9620	*CorrectedPrice*	Refer to definition in the Trade Cancel/Correct Section 4.5.3 for more details.
9730	*TradeLiquidityIndicator*	Refer to definitions in the Execution Report Section 4.5.1 and Trade Cancel/Correct Section 4.5.3 for more details. **IMPORTANT:** *TradeLiquidityIndicator* was Tag 9882 in the Chi-X Japan FIX specification. All Cboe markets use Tag 9730 for *TradeLiquidityIndicator* and Tag 9882 for *FeeCode*.
9882	*FeeCode*	Refer to definition in the Execution Report Section 4.5.1 for more details. **IMPORTANT:** *TradeLiquidityIndicator* was Tag 9882 in the Chi-X Japan FIX specification. All Cboe markets use Tag 9730 for *TradeLiquidityIndicator* and Tag 9882 for *FeeCode*.

4.4 Order Protocol – Participant to Cboe

Participants use the messages in this section to enter, amend, and cancel orders.

4.4.1 New Order Single

Tag	Field Name	Req'd	Description
35	Standard Message Header	Y	*MsgType*='D'
97	*PossResend*	N	N = (default) indicates a new order. Y = indicates an application level resend and is not supported. The message will be logged, but effectively ignored. For reasons of economy, Cboe does not track (in primary storage) the *ClOrdID* values of orders that are no longer live.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

			For reasons of performance, Cboe does not access secondary storage to enforce unique *ClOrdID* values against orders that are no longer live. Without full duplicate *ClOrdID* value enforcement, it is not possible to safely implement the full behavior specified in the FIX 4.2 Protocol for *PossResend* (97) ='Y'.
1	*Account*	N	Used by a trading participant or a broker service provider to provide a broker cross reference. Reflected back on Execution Reports associated with this order. 10 characters or less. Characters in ASCII range 33-126 are allowed. Available via Standard FIX Drop on an opt-in basis at the port level. Available by default on Order by Order FIX Drop.
11	*ClOrdId*	Y	Day-unique ID chosen by client. 20 characters or less. Characters in ASCII range 33-126 are allowed, except for double-quote (34), comma (44), "at" symbol (64), semicolon (59), and pipe (124). If the *ClOrdId* matches a live order it will be rejected as duplicate (unless *PossResend* (97) = 'Y', see above). **Note: Cboe only enforces the uniqueness of *ClOrdID* values among currently live orders. However, we *strongly* recommend keeping *ClOrdID* values day unique.**
18	*ExecInst*	N	Single value only (with no trailing space) For more details on each order type, see Peg Orders. All values not defined below are ignored. P = Market Peg (peg Buy [Sell] to PBBO Offer [Bid], one tick within PBBO) R = Primary Peg (peg Buy [Sell] to PBBO Bid [Offer], one tick within PBBO) M = Midpoint (peg to PBBO Midpoint)
21	*HandInst*	Y	Instruction for order handling. 1 = Automated execution order, private, no Broker intervention

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

22	*IDSource*	N	Identifies the symbology presented in the *Symbol* (55) tag. 3 = QUICK (default) 5 = RIC
38	*OrderQty*	Y	Number of shares for order, 1 to 999,999,999.
40	*OrdType*	Y	1 = Market 2 = Limit P = Pegged Market will reject unless *VWAPSessionID*(8004) is present. Pegged will reject unless: • *ExecInst* (18) = P, R, or M.
44	*Price*	Y	Limit (or cap) Price. If *OrdType* (40) is • 1 (Market) – Price is ignored (if present). • 2 (Limit) – Required Limit Price. Rejected if price is finer than the minimum trading increment for the stock. • P (Pegged) – Optional Cap Price. Rejected if price is finer than the minimum trading increment for the stock.
47	*OrderCapacity*	Y	The capacity for the order. A = Agency P = Principal
54	*Side*	Y	1 = Buy 2 = Sell 5 = Sell Short (client affirms ability to borrow) 6 = Sell Short Exempt
55	*Symbol*	Y	Symbol (upper case alphanumeric) conforming to the symbology declared in *IDSource*(22).
59	*TimeInForce*	N	0 = DAY (default) 3 = IOC (portion not filled immediately is cancelled). 4 = FOK (an IOC where the entire size must be filled, else the order will be cancelled back). 6 = GTD (expires at earlier of specified *ExpireTime* or end of day). • VWAP orders must be DAY or IOC • Pullback orders must be DAY or GTD

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

60	*TransactTime*	Y	Time order initiated/released. Required by FIX 4.2, but not used by Cboe.
110	*MinQty*	N	Minimum fill quantity is accepted only for VWAP orders (orders having *VWAPSessionID*(8004) populated). Multiple consecutive fills may be created such that their combined size satisfies the *MinQty* requirement. Rejected if it is not an integer multiple of the standard trading unit. When the remaining size (*LeavesQty*) on an order is less than the defined *MinQty*, then *MinQty* is set to the *LeavesQty*.
111	*MaxFloor*	N	Portion of *OrderQty* to display. Used for iceberg orders. Rejected if it is not an integer multiple of the standard trading unit. Iceberg orders are Limit orders (40=2) and require *MaxFloor* > 0 if specified. For iceberg orders, this is the displayed quantity. The balance is reserve. The displayed quantity of each order at a price level is decremented first. **Ignored** if order is IOC or VWAP.
126	*ExpireTime*	N	Required for *TimeInForce* (59) = '6' (GTD) orders, specifies the UTC Date/Time timestamp when the order expires. GTD orders will expire at the earlier of the end of the current trading day and the *ExpireTime*.
211	*PegDifference*	N	Signed currency value up to one decimal place is added to the result of the peg calculation. Ignored if *OrdType*(40) is not P (Pegged).
544	*CashMargin*	N	Indicates the type of cash or margin order. 1 = Cash (default) 2 = Margin Open 3 = Margin Close **Rejected** if any other value is specified. **Ignored** if order is VWAP.
7699	*RiskGroupID*	N	Optional Member specified ID for the order. Cancellation by RiskGroupID available using 'Purge Port' only. Integer 1-65535.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

7713	*NoTradeFeat*	N	Defines how to handle Match Trade Prevention (MTP) scenarios. If not specified, the port default is used. U = No Match Trade Protection, *NoTradeKey* (7714) will be ignored. N = Cancel Newest O = Cancel Oldest B = Cancel Both S = Cancel Smallest D = Decrement larger/Cancel Smaller d = Same as 'D', but only decrement *LeavesQty*. Do not restate *OrderQty*. If the older and newer orders in a self-matching trade have conflicting instructions, the instruction of the newer order will be honored, except if the inbound order specifies Decrement and the resting order does not, and the resting order is larger, then both orders will be cancelled. This exception protects the order entry software for the resting order from receiving an unexpected restatement message.
7714	*NoTradeKey*	N	Interactions of orders from the same participant with the same *NoTradeKey* (7714) value will be managed by the newer order's *NoTradeFeat* (7713) instruction. Ignored if *NoTradeFeat* (7713)=U. Up to 10 printable ASCII characters (in the inclusive range 32..126).
8004	*VWAPSessionID*	N	DAY = Full day VWAP session AM = AM VWAP session PM = PM VWAP session Omitted for continuous trading. If present, then: • *ExecInst*(18) is ignored • *Price*(44) must be 1 (Market) • *TimeInForce*(59) must be DAY (0) or IOC (3) • *MaxFloor*(111) is ignored • *CashMargin*(544) is ignored • *NoTradeFeat*(7714) is ignored • *RoutingInst*(9303) is ignored • *MarginTransactionType*(8214) is ignored **Ignored** in the Select market.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

8060	*OrderClassification*	N	Specify the order classification as a single alphanumeric character. Suggested values: 1 = Non Low Latency trading (Auto) 2 = Non Low Latency trading (Manual) 3 = Market Making Strategy 4 = Arbitrage Strategy 5 = Directional Strategy 6 = Other Strategy
8105	*Pullback*	N	P = Pullback Cancels back if the working price locks or crosses the effective TSE quote. **Rejected** unless *TimeInForce* (59) = 0 (DAY) or 6 (GTD). **Ignored** unless sent to the Alpha marketplace.
8214	*MarginTransactionType*	N	Specifies if a margin order is a Negotiable or a Standardized. 1 = Negotiable 2 = Standardized Required if *CashMargin* (544) = 2 (Margin Open) or 3 (Margin Close), otherwise ignored.
9303	*RoutingInst*	N	P = Post Only (never take liquidity). Rejected unless *OrdType*(40) = 2 (Limit) and *TimeInForce*(59) is 0 (DAY) or 6 (GTD).
	Standard Message Trailer	Y	

4.4.2 Order Cancel Request

Request to cancel an order.

Tag	Field Name	Req'd	Description
35	Standard Message Header	Y	*MsgType*='F'
97	*PossResend*	N	N = (**default**) indicates a new cancel.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

			Y = Indicates an application level unsolicited resend. If *ClOrdID* has not yet been seen, the cancel is treated as normal. If *ClOrdID* already exists, the resent cancel is ignored.
11	*ClOrdID*	Y	Day-unique ID chosen by client. 20 characters or less. Characters in ASCII range 33-126 are allowed, except for double-quote (34), comma (44), "at" symbol (64), semicolon (59), and pipe (124). Duplicate order *ClOrdID*s will be rejected (or ignored if *PossResend*='Y').
37	*OrderID*	N	*OrderID* supplied by Cboe on the order acknowledgement. Optional but recommended for performance. *OrigClOrdID* must be sent if *OrderID* is not.
41	*OrigClOrdID*	N	*ClOrdID* of the order to cancel. *OrderID* must be sent if *OrigClOrdID* is not.
54	*Side*	N	**Ignored**
55	*Symbol*	N	**Ignored**
60	*TransactTime*	N	Time cancel initiated/released. Required by FIX 4.2 but not used by Cboe.
	Standard Message Trailer	Y	

4.4.3 Order Cancel/Replace Request

Request to modify an order. Only *Price*, *OrderQty*, and *MaxFloor* (Iceberg orders only) may be adjusted. Modifies will result in a loss of time priority unless the modification involves only one or more of the following:

- a decrease in *OrderQty*
- a change to *MaxFloor*

Changes in *OrderQty* result in an adjustment of the current order's *OrderQty*. The new *OrderQty* does not directly replace the current order's *LeavesQty*. Rather, a delta is computed from the current *OrderQty* and the replacement *OrderQty*. This delta is then applied to the current *LeavesQty*. If the resulting *LeavesQty* is less than or equal to zero, the order is cancelled. This results in safer behavior when the modification request overlaps partial fills for the current order, leaving the Participant in total control of the share exposure of the order.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

MaxFloor may only be changed for Iceberg orders. A change in *MaxFloor* takes effect on the next reserve reload (iceberg refresh). It may not be changed for Hidden order types (Pegged or VWAP).

Other fields **will be ignored**, and the value from the original order will be re-used.

The `Cancel/Replace` message will only be accepted if the original order can be successfully removed. Requests which cannot be processed will be rejected using the `Cancel Reject` message. The `Cancel Reject` message will provide the *ClOrdID* and *OrigClOrdID* values which were specified on the `Cancel/Replace` message for identification.

A `Cancel/Replace` should not be issued until the ack for the previous `Cancel/Replace` has been received for that order (or the acknowledgement for the first `Cancel/Replace Request`). The FIX handler will reject a new `Cancel/Replace` if it has not seen the ack for the prior `Cancel/Replace` message from the Matching Engine.

Tag	Field Name	Req'd	Description
35	Standard Message Header	Y	*MsgType*='G'
97	*PossResend*	N	Y = Indicates an application level resend. If the *ClOrdID* does not indicate an already pending Cancel/Replace, the Cancel is treated as normal. If *ClOrdID* does indicate an already pending Cancel/Replace then the resent Cancel/Replace is ignored. N = (default) indicates a new Cancel/Replace.
11	*ClOrdId*	Y	Day-unique ID chosen by client. 20 characters or less. Characters in ASCII range 33-126 are allowed, except for double-quote (34), comma (44), "at" symbol (64), semicolon (59), and pipe (124). Duplicate order *ClOrdID*s will be rejected[1] (or ignored if *PossResend*='Y').
18	*ExecInst*	N	**Ignored** – value preserved from original order
37	*OrderId*	N	*OrderId* supplied by Cboe on the order acknowledgement. Optional but recommended for performance. *OrigClOrdID* must be sent if *OrderId* is not. In the case of multiple changes to a single order, this will be the *OrderId* from the most recent acknowledgement.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

38	*OrderQty*	Y	Number of shares for order. This will modify the *OrderQty* of the current order; it does **not** directly set the remaining quantity.
40	*OrdType*	N	**Ignored** – Value preserved from original order.
41	*OrigClOrdID*	Y	*ClOrdID* of the order to replace. In the case of multiple changes to a single order, this will be the *ClOrdID* of the **most recent** accepted change.
44	*Price*	N	Limit price for limit order. Cap price for pegged orders.
47	*OrderCapacity*	N	**Ignored** – value preserved from original order
54	*Side*	N	**Ignored** – value preserved from original order
55	*Symbol*	N	**Ignored** – value preserved from original order
59	*TimeInForce*	N	**Ignored** – value preserved from original order
60	*TransactTime*	Y	Time Cancel/Replace initiated/released.
111	*MaxFloor*	N	Portion of *OrderQty* to display. The balance is reserve. See description in New Order Single. Invalid values for the order type will cause the Cancel/Replace to be rejected. Takes effect on the next reserve order reload or priority losing event. A value of zero will be ignored. If *MaxFloor* is to be removed completely, then the order should be cancelled and a new order sent.
126	*ExpireTime*	N	**Ignored** – value preserved from original order
211	*PegDifference*	N	**Ignored** – value preserved from original order
7713	*NoTradeFeat*	N	**Ignored** – value preserved from original order
7714	*NoTradeKey*	N	**Ignored** – value preserved from original order
9619	*CancelOrigOnReject*	N	N = Leave original order alone. Y = Cancel original order if replacement fails (an unsolicited Cancel report will be sent for original order in this case). Default is configurable per port ('N' if not configured).
	Standard Message Trailer	Y	

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

[1] Cancel/Replace messages that merely reduce *OrderQty* may be overlapped if the existing *ClOrdID* is re-used.

4.5 Order Protocol – Cboe to Participant

4.5.1 Execution Report

This section contains all possible fields sent in Execution Reports. Not all fields are sent on each Execution Report. Additional or unexpected FIX fields on all FIX messages should be ignored.

Tag	Field Name	Req'd	Description
35	Standard Message Header	Y	*MsgType*='8'
1	*Account*	N	Copied from order.
6	*AvgPx*	Y	Average price of executions for this order weighted by trade size. Zero if *CumQty* is zero.
11	*ClOrdID*	Y	*ClOrdID* of the order being accepted, executed or rejected. -or- *ClOrdID* of the cancel or replace request. -or- *ClOrdID* of the order subject to unsolicited cancel (*OrigClOrdID* will not be present).
14	*CumQty*	Y	Cumulative quantity of shares executed for this order.
17	*ExecID*	Y	Day-unique id of execution message.
18	*ExecInst*	N	Copied from order.
20	*ExecTransType*	Y	0 = New 2 = Correction. Used to provide confirmed trading price for VWAP trades. 3 = Status. Used to provide peg suspensions (150=9) and order restatements (150=D).
22	*IDSource*	Y	Copied from order, otherwise default value.
29	*LastCapacity*	N	Present on Fill and Partial Fill messages. 1 = Agent 2 = Cross as agent 3 = Cross as principal 4 = Principal

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

31	*LastPx*	N	Price of this fill (zero for non-fills). For VWAP Order Execution, this is the indicative price. For VWAP Price Restatement, this is the final VWAP trade price.
30	*LastMkt*	N	Present on Fill and Partial Fill messages. Supported MIC code values are as follows: `CHIJ` = (Alpha – continuous book) `CHIS` = (Select) `CHIV` = (Match - VWAP) `KAIX` = (BIDS trade – drop only)
32	*LastShares*	N	Quantity of shares traded on this fill (zero for non-fills).
37	*OrderId*	Y	*OrderId* (supplied by Cboe).
38	*OrderQty*	Y	Copied from order.
39	*OrdStatus*	Y	Status of order. `0` = New `1` = Partially Filled `2` = Filled `4` = Canceled `5` = Replaced `6` = Pending Cancel `8` = Rejected `9` = Suspended `B` = Calculated `E` = Pending Replace For FIX Drop, only '1' or '2' will be sent and will always equal *ExecType* (150). For Order by Order FIX Drop, all execution information will be sent.
40	*OrdType*	N	Copied from order.
41	*OrigClOrdID*	N	ClOrdID of the order being cancelled or replaced (for a solicited `Order Cancel`, or `Cancel/Replace`, otherwise not present).
44	*Price*	N	Copied from order.
47	*OrderCapacity*	N	Copied from order.
54	*Side*	Y	Copied from order.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

55	*Symbol*	Y	Copied from order.
58	*Text*	N	If present, indicates reason for reject or cancel. Format is one letter reason code followed by colon and space followed by free form text message. (e.g., 'N: No Liquidity at price'). The specific text the system delivers may vary from the text listed below, to provide clarification of the reject reason. **Reason codes are one of the following:** A = Admin C = Capacity undefined D = Duplicate identifier (e.g., *ClOrdID*) F = Failed to Quote H = Halted J = Too late to cancel K = Order rate threshold exceeded L = Order would lock or cross PBBO M = Order size exceeded N = Ran out of liquidity to execute against O = *ClOrdID* doesn't match a known order S = Short sale price violation T = Fill would trade through the NBBO U = User requested V = Would wash X = Order expired W = Add liquidity only order would remove Y = Symbol not supported Z = Unforeseen reason o = Max open orders count exceeded r = Reserve reload x = Crossed market y = Order received by Cboe during replay
59	*TimeInForce*	N	Copied from order.
60	*TransactTime*	Y	UTC date-time that transaction occurred.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

76	*ExecBroker*	N	**(Present only on CXJ Alpha Drop Ports, only for BIDS trades)**
109	*ClientID*	N	**(Present only on CXJ Alpha Drop Ports, only for BIDS trades)**
110	*MinQty*	N	Copied from order.
111	*MaxFloor*	N	Copied from order.
126	*ExpireTime*	N	Copied from order if *TimeInForce* is GTD (6).
150	*ExecType*	Y	Reason for this Execution Report: `0` = New (acknowledgement of new order) `1` = Partial Fill `2` = Fill `4` = Canceled `5` = Replaced `8` = Rejected `9` = Suspended `D` = Restated For Standard FIX Drop, only '1' or '2' will be sent and will always equal *OrdStatus* (39). For Order by Order FIX Drop, all execution information will be sent. Refer to section 7.2.
151	*LeavesQty*	Y	Quantity of shares still open for further execution. Will be zero if order is dead, otherwise will be *OrderQty* (38) – *CumQty* (14). **Note:** It is possible for *LeavesQty* to be zero when *ExecType* (150) = '5', indicating the order is dead.
198	*SecondaryOrderID*	N	Present on a Match Trade Prevention (MTP) triggered cancel/restatement, on a reserve reload restatement, and on a Cancel/Replace acknowledgement that increases the size of a reserve order. Contra side Cboe *OrderId* of prevented match (MTP), or Cboe PITCH *OrderId* for displayed portion of reserve order after reload, or Cboe PITCH *OrderId* for the displayed portion of a reserve order after a Cancel/Replace increased the size of the reserve order.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

378	*ExecRestatementReason*	N	Only present when 150=D. 4 = Iceberg display size refreshed 5 = Partial Reduce due self-match trade prevention result based on *NoTradeFeat* (7713) C = Confirmed price for VWAP trade
544	*CashMargin*	N	Copied from order if present.
7699	*RiskGroupID*	N	Copied from order if present.
7713	*NoTradeFeat*	N	Copied from order if present.
7714	*NoTradeKey*	N	Copied from order if present.
7903	*PreventedTradePx*	N	Provided if cancel or cancel/replace is the result of Match Trade Prevention (MTP). Indicates the trade price attempted when MTP was triggered.
7904	*PreventedTradeQty*	N	Provided if cancel or cancel/replace is the result of Match Trade Prevention (MTP). Indicates the trade quantity attempted when MTP was triggered.
7905	*PreventedTradeLiquidityIndicator*	N	Provided if cancel or cancel/replace is the result of Match Trade Prevention (MTP). Indicates the liquidity of the order attempted when MTP was triggered. A = Added liquidity R = Removed liquidity
8004	*VWAPSessionID*	N	Copied from order if present.
8060	*OrderClassification*	N	Copied from order if present.
8101	*ToSTNetTOrderID*	N	Order Acceptance Number in ToSTNeT for this fill. **(Present only on CXJ Alpha Drop Ports, only for BIDS trades)**
8102	*ToSTNeTExecutionID*	N	Execution Notice number in ToSTNeT for this fill. **(Present only on CXJ Alpha Drop Ports, only for BIDS trades)**
8105	*Pullback*	N	Copied from order if present.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

8106	*ToSTNeTTransactTime*	N	Transaction time in ToSTNeT (expressed as GMT) for this fill. **(Present only on CXJ Alpha Drop Ports, only for BIDS trades)**
8214	*MarginTransactionType*	N	Copied from order if present.
9303	*RoutingInst*	N	Copied from order if present.
9617	*ModifySequence*	N	FIX Drop only. Base 36 number of times order has been replaced.
9688	*OrigCompID*	Y	FIX Drop and ODROP only. *TargetCompID* of original FIX exec report.
9689	*OrigSubID*	Y	FIX Drop and ODROP only. *TargetSubID* of original FIX exec report.
9690	*WorkingPrice*	N	The price at which the order is effective on the book. Only present on Accepted, Replaced, or Restated and only when order is fully or partially booked.
9730	*TradeLiquidityIndicator*	Y	Present for acknowledgements and fills (150=0, 150=1 or 150=2). Recommended mapping to FIX Tag 851 provided: A = Trade Added Liquidity (851=1) R = Trade Removed Liquidity (851=2) **Match Trade Prevention (MTP)** For participants that opt-in to Report MTP Fields functionality (at firm or port level), the liquidity add and remove values may be presented on an MTP triggered cancel/restatement. **IMPORTANT:** *TradeLiquidityIndicator* was Tag 9882 in the Chi-X Japan FIX specification. All Cboe markets use Tag 9730 for *TradeLiquidityIndicator* and Tag 9882 for *FeeCode*.
9882	*FeeCode*	N	Specific fee code associated with execution. See the Fee Schedule for the respective market for possible values. **IMPORTANT:** *TradeLiquidityIndicator* was Tag 9882 in the Chi-X Japan FIX specification. All Cboe markets use Tag 9730 for *TradeLiquidityIndicator* and Tag 9882 for *FeeCode*.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

	Standard Message Trailer	Y	

4.5.2 Cancel Reject

Rejects a Cancel, Cancel/Replace, or Trade Cancel request.

When a Cancel/Replace is rejected, by default the original order is left alive. A Cancel Reject should not be used as a sign that the original order has been cancelled. Even if the *CancelOrigOnReject* = *'Y'* option is being used, a separate "unsolicited" cancel will be sent to close out the original order.

Tag	Field Name	Req'd	Description
35	Standard Message Header	Y	*MsgType*='9'
1	*Account*	N	Copied from `Cancel` or `Cancel/Replace` request.
11	*ClOrdID*	Y	*ClOrdID* from the `Cancel` or `Cancel/Replace` request.
37	*OrderId*	Y	*OrderId* of order that failed to be cancelled or replaced. Represents the originating/initial order in an order chain. 'NONE' if *CxlRejReason* is Unknown (1).
39	*OrdStatus*	Y	`Cancel` or `Cancel/Replace` request: Order Status of order that failed to be cancelled or replaced. `Trade Cancel Report`: 8 = Rejected
41	*OrigClOrdID*	Y	*ClOrdID* of the order that failed to be cancelled or replaced.
58	*Text*	N	Free form text message.
102	*CxlRejReason*	N	`0` = Too late to cancel. `1` = Unknown order. `3` = Already pending cancel or pending replace.
434	*CxlRejResponseTo*	Y	This reject is in response to a: `1` = Cancel `2` = Cancel/Replace
	Standard Message Trailer	Y	

4.5.3 Trade Cancel/Correct

Sends a Trade Cancel/Correct message from Cboe for a trade break (i.e., trade cancel). Cboe Japan does not currently support trade corrections.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

Trade Cancel/Correct (UCC) is an optional message enabled by default at the port level. Trade cancels and corrections do not alter live order state.

Tag	Field Name	Req'd	Description
35	Standard Message Header	Y	*MsgType*='UCC'
11	*ClOrdID*	Y	*ClOrdID* of the original trade being cancelled/corrected.
17	*ExecID*	Y	Day-unique id of execution message.
19	*ExecRefID*	Y	Refers to the *ExecID* of the message being cancelled or corrected.
20	*ExecTransType*	Y	1 = Trade Cancel 2 = Trade Correct
31	*LastPx*	Y	Price on the original trade being cancelled/corrected.
32	*LastShares*	Y	Quantity of shares on the original trade being cancelled/corrected.
37	*OrderId*	Y	*OrderId* of the original trade being cancelled/corrected.
42	*OrigTime*	Y	UTC date-time of original trade.
54	*Side*	Y	Copied from original trade being cancelled/corrected.
55	*Symbol*	Y	Copied from original trade being cancelled/corrected (available in FIX Drop).
60	*TransactTime*	Y	UTC date-time of cancel/correct.
9620	*CorrectedPrice*	N	New trade price.
9730	*TradeLiquidityIndicator*	Y	Copied from original trade being cancelled/corrected.
9882	*FeeCode*	N	Only for Trade Corrects. Corrected fee code.
	Standard Msg Trailer	Y	

4.5.4 Trading Session Status

Unsolicited "trading session status" message will be sent at the scheduled open and closing times of the Cboe Japan market.

Tag	Field Name	Req'd	Description
35	Standard Message Header	Y	*MsgType*='h'

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

58	*Text*	N	Free form text message.
325	*UnsolicitedIndicator*	Y	Always 'Y' (unsolicited)
336	*TradingSessionID*	Y	Always 'TYO'
339	*TradeSesMod*	Y	Trading session mode: 2 = Simulation 3 = Production
340	*TradeSesStatus*	Y	Status of the trading session: 2 = Open 3 = Closed
	Standard Message Trailer	Y	

4.6 Purge Port Protocol – Participant to Cboe

A Purge Port may be created using either FIX or BOE protocol.

4.6.1 Purge Request

Request to cancel a group of orders or a single order across **all** the participant's sessions. A `Purge Request` is accepted only on dedicated FIX Purge Ports.

A participant may choose to implement one or more filters:

1. *Trading Firm* Filter – optionally cancel based on the trading firm ID. Set using first character of *MassCancelInst* (7700) and sending *OnBehalfOfCompID* (115). This will optionally cancel orders entered on a port configured with an MPID matching this value. Firms having a single MPID may specify their firm ID as used in *SenderCompID* (49).
2. *Symbol* Filter – optionally cancel based on symbol. Set by sending a valid symbol in the *Symbol* (55) field. Cannot be combined with *RiskGroupID* or *OrderId* filters.
3. *RiskGroupID* Filter – optionally cancel based on *RiskGroupID* (7699). A maximum of 10 *RiskGroupID*s may be included on a single `Purge Request` message. Set by populating *RiskGroupIDCnt* (7698) to a non-zero value. Cannot be combined with *Symbol* or *OrderId* filters.
4. *OrderId* Filter – optionally cancel a single order across all sessions by sending the *OrderId* (37) supplied by Cboe on the order acknowledgement. Cannot be combined with *Symbol* or *RiskGroupID* filters.

A participant may use the second character of *MassCancelInst* (7700) to set the acknowledgement style. If a single `Purge Acknowledgement` is selected, then *MassCancelID* (7695) must be sent.

The system limits the rate at which identical `Purge Request` messages can be submitted to the system. Requests are restricted to twenty (20) messages per second per port.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

An identical purge message is defined as a message having all of the same *RiskGroupID* (7699) and *Symbol* (55) field values as a previously received message.

Tag	Field Name	Req'd	Description
35	Standard Message Header	Y	*MsgType*='F'
97	*PossResend*	N	Y = Indicates an application level unsolicited resend. If *ClOrdID* has not yet been seen, the cancel is treated as normal. If *ClOrdID* already exists, the resent cancel is ignored. N = (default) indicates a new cancel.
60	*TransactTime*	Y	Time cancel initiated/released. Required by FIX 4.2 but not used by Cboe.
115	*OnBehalfOfCompID*	N	The trading firm identifier for cancellation by Firm filter.
7700	*MassCancelInst*	Y	At least one character must be provided (PID Filter). Contiguous characters must be specified up to total length. Truncated (unspecified) characters will default to values indicated below. ***1st Character : Firm Filter*** A = No filtering by trading firm is performed. F = All orders that were sent on a port configured with the "" as under the specified Firm Identifier in *SenderCompID* (49). Note only one firm can be killed by a drop port (the *SenderCompID* (49) firm), so this filter is not meaningful and can always be specified as 'A'). ***2nd Character : Acknowledgement Style*** M = (default) Individual Execution Reports are sent for each cancelled order. S = Single `Purge Acknowledgement` sent once all cancels have been processed. Single `Purge Acknowledgement` will contain *MassCancelId (7695)* and *CancelledOrderCount (7696)*. *MassCancelId* (7695) must be specified or the `Purge Request` will be rejected. B = Both individual `Execution Reports` and single `Purge Acknowledgement`. Also

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

			requires *MassCancelId* (7695) to be specified or the `Purge Request` will be rejected.
7695	*MassCancelID*	N	*MassCancelID* – This field will be echoed back in the resulting `Purge Acknowledgement` when second character of *MassCancelInst* (7700) is set to 'S' or 'B'. Purge requests containing a currently outstanding *MassCancelID* will be rejected. *MassCancelID* cannot end with a space. Maximum length 20 (extra characters will be ignored).
55	*Symbol*	N	*Symbol* (upper case). Limits cancellations to only orders with the specified symbol.
7698 *Repeating Group*	*RiskGroupIDCnt*	N	Number of repeating *RiskGroupIDs* (7699) included in this message. Integer 0-10.
➔ 7699	*RiskGroupID*	N	*RiskGroupID* (7699) to cancel. Only present if *RiskGroupIDCnt* (7698) is non-zero. Number of repeating groups must match number specified in *RiskGroupIDCnt* (7698). Integer 1-65535.
37	*OrderID*	N	To cancel a single order, enter the *OrderID* supplied by Cboe on the order acknowledgement. In the case of multiple changes to a single order, this will be the *OrderId* from the most recent acknowledgement.
	Standard Message Trailer	Y	

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

4.7 Purge Port Protocol – Cboe to Participant

4.7.1 Purge Acknowledgement

A response to a `Purge Request` will only be sent when the *MassCancelID* (7695) is populated on a `Purge Request`. This includes cases where the Acknowledgement Style of *MassCancelInst* is 'S' or 'B'.

Tag	Field Name	Description
35	Standard Message Header	*MsgType*='8'
20	*ExecTransType*	`3 =` Status
150	*ExecType*	Reason for this execution report: `M =` Mass Cancel Complete
7695	*MassCancelID*	Copied from original `Purge Request`.
7696	*CancelledOrderCount*	Number of orders cancelled from a `Purge Request` with the specified *MassCancelID*.

4.7.2 Purge Reject

Rejects a `Purge Request`.

Tag	Field Name	Description
35	Standard Message Header	*MsgType*='9'
39	*OrdStatus*	`8 =` Rejected
434	*CxlRejResponseTo*	`1 =` Cancel
102	*CxlRejReason*	`2 =` Broker Option
58	*Text*	Free form text message with additional reject information.
7695	*MassCancelID*	*MassCancelID* from the `Purge Request`
	Standard Message Trailer	

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

5 Order Types and Features

The following provides clarifying information to enable Participants to successfully enter orders in the Cboe Japan markets.

This is not meant to be an exhaustive list of all FIX tags accompanying an order type, but an effort to identify the key tags and provide information regarding certain order types and features. Please refer to the New Order section above for field description details.

5.1 Iceberg Order

Iceberg orders (also referred to as Reserve Orders in Cboe documentation) are orders having both a displayed quantity and a non-visible, reserve quantity that is replenished when the displayed quantity is fully executed.

5.1.1 New Iceberg Order

Users may specify the precise amount of the order to be replenished with *MaxFloor*(111) once the displayed size is fully executed.

Tag	Field Name	Req'd	Comments
54	*Side*	Y	-
38	*OrderQty*	Y	-
111	*MaxFloor*	Y	-
40	*OrdType*	Y	2 = Limit
44	*Price*	Y	-
59	*TimeInForce*	N	-
126	*ExpireTime*	N	-

5.1.2 Reloading Iceberg Order

When the displayed quantity of an Iceberg order is fully executed, it is reloaded with a new displayed quantity of *MaxFloor*(111) and re-inserted at the same price level but losing time priority. The reloaded order maintains the same *OrderId* at the order entry, DROP, and regulatory reporting but uses a new *OrderId* on the market data feeds to avoid leaking information about the Iceberg. This new *OrderId* is provided to the Participant in *SecondaryOrderID*(198).

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

5.2 Peg Orders

Cboe Japan supports the following types of Peg Orders: Primary Pegs, Market Pegs, and Midpoint Pegs. Note that pegged orders are not supported in the Select market.

All Peg Orders have the following characteristics:

- A resting peg order may remove liquidity when re-priced by a TSE quote movement.
- A Peg Order will not execute if the TSE is crossed.
    - An aggressive Peg Order will be rejected.
    - A resting Peg Order will be suspended when the TSE quote is crossed and will resume its prior state once the TSE quote is no longer crossed.

5.2.1 Midpoint Peg Order

A Midpoint Peg Order is an order that maintains a price at the midpoint of the TSE quote spread plus the peg offset.

A Midpoint Peg Order is specified with *ExecInst*=M.

5.2.2 Primary Peg Order

A Primary Peg Order is an order that maintains a price relative the same or passive side of the TSE quote spread. A Primary Peg Buy Order maintains a price relative to the TSE Best Bid (plus any peg difference). A Primary Peg Sell Order maintains a price relative to the TSE Best Offer (plus any peg difference).

A Primary Peg Order is specified with *ExecInst*=R.

5.2.3 Market Peg Order

A Market Peg Order is an order that maintains a price relative to the opposite or aggressive side of the TSE quote spread. A Market Peg Buy Order maintains a price relative to the TSE Best Offer (plus any peg difference) and a Market Peg Sell Order maintains a price relative to the TSE Best Bid (plus any peg difference).

A Primary Peg Order is specified with *ExecInst*=P.

5.2.4 Peg Order Fields

The following fields are relevant to Peg Orders.

Tag	Field Name	Req'd	Comments
18	*ExecInst*	Y	P = Market Peg (peg Buy [Sell] to TSE Offer [Bid] R = Primary Peg (peg Buy [Sell] to TSE Bid [Offer] M = Midpoint (peg to TSE Midpoint)
54	*Side*	Y	-

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

38	*OrderQty*	Y	-
40	*OrdType*	Y	P = Peg
44	*Price*	N	Cap Price
59	*TimeInForce*	N	-
211	*PegDifference*	N	

5.2.5 Peg Suspended and Resumed

When Cboe Japan detects that the primary exchange for a symbol has halted, all peg orders for that symbol will be unbooked until primary exchange trading resumes.

5.2.5.1 Peg Order Suspension

Cboe Japan will notify participants when their peg orders become suspended via Execution Reports having:

Tag	Field Name	Req'd	Comments
11	*ClOrdID*	Y	Copied from order
20	*ExecTransType*	Y	0 = New
37	*OrderId*	Y	Copied from order
39	*OrdStatus*	Y	9 = Suspended
60	*TransactTime*	Y	UTC date-time that transaction occurred.
150	*ExecType*	Y	9 = Suspended

5.2.5.2 Peg Order Resumed

Cboe Japan will notify participants when their suspended peg orders resume tradable status via Execution Reports having:

Tag	Field Name	Req'd	Comments
11	*ClOrdID*	Y	Copied from order
20	*ExecTransType*	Y	3 = Status
37	*OrderId*	Y	Copied from order
39	*OrdStatus*	Y	(*OrdStatus* prior to suspension)
60	*TransactTime*	Y	UTC date-time that transaction occurred.
150	*ExecType*	Y	D = Restated

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

378	*ExecRestatementReason*	Y	3 = Peg repricing

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

6 Implementation Notes

6.1 Automatic Cancel on Disconnect or Malfunction

If no messages have been received from the client for two heartbeat intervals, the client will be treated as disconnected. Open orders will be handled as defined by the "cancel on disconnect" setting for the port. This is done to prevent orders from being stuck in an unknown state in the event of telecommunications failure. Participants should choose their heartbeat interval carefully based on the latency and reliability of their telecommunications channel. The minimum supported interval is 5 seconds, and this is also the recommended interval if the latency and reliability of your telecommunications channel support it. Execution Reports for automatically cancelled orders are available upon reconnection. This should be rare, but all open orders may also be cancelled in the event of a complete or partial system malfunction.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

7 FIX Drop

Cboe offers two types of FIX Drop ports (Standard FIX Trade Drop and Order by Order FIX Drop). Both port types do not accept orders. Their purpose is to provide real time information about order flow. They may be configured to send order flow based on various combinations of information relating to specific ports.

7.1 Standard FIX Trade Drop

Standard FIX Drop ports only send execution information (i.e., Execution Reports where *ExecType* (150) is Partially Filled (1) or Filled (2), and (optionally) Trade Cancel/Correct messages (*MsgType*=UCC). Refer to the Execution Report section above for details on standard execution reports.

7.2 Order by Order FIX Drop

Order by Order FIX Drop ports are designed to send more than execution information.

All order message types are supported including, but not limited to Acknowledgements (150=0), Partially Filled (150=1), Filled (150=2), Cancelled (150=4), Replaced (150=5), Rejected (150=8), Order Cancel Rejects (35=9), Restated (150=D), and optionally (if configured at the port level) Trade Breaks (35=UCC). If the Rejects/Cancels are due to incomplete clearing information, they may be unavailable on Order by Order FIX Drop ports.

Reject messages will be sent which originate from a FIX order entry session. However, rejects originating from a BOE order entry session will be suppressed.

Users of Order by Order FIX Drop must always be prepared to receive new/unknown FIX tag and FIX tag values for BOE/FIX ports being monitored. Cboe reserves the right to add new FIX tags and to update values distributed on Order by Order FIX Drop with no notice.

7.3 FIX Drop Port Attributes

Both types of FIX Drop ports can be configured with the following feature:

Attribute	Default	Description
Unique Wash Execution Ids	No	Appends a '.B' or '.S' to *ExecID* (17) on all trades.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

8 FIX Port Attributes

The table below lists FIX port attributes that are configurable on the port or firm level. Changes to these attributes can be made by sending a written request to TradeDeskJP@cboe.com.

Attribute	Default	Description
HST code	(none)	Identifies the high speed trader using this port.
Designated as DLP	No	Applicable only to the Select market. "No" – all order must be IOC or FOK "Yes" – all orders must be Post Only
Default RiskGroupID	No	Default value for *RiskGroupID* (7699).
Enable Pegs	Yes	Allow or disallow all pegged orders.
Enable Primary Pegs	Yes	Allow or disallow primary peg orders.
Enable Market Pegs	Yes	Allow or disallow market peg orders.
Enable Midpoint Pegs	Yes	Allow or disallow midpoint peg orders.
Allow Test Symbols Only	No	Allow or disallow orders in non-test symbols.
Maximum Notional Value Per Order	No	Maximum notional value allowed on any individual order (acceptable value 1 - 10,000,000,000).
Maximum Order Lot Size	9,999,999	Maximum number of lots allowed per order.
Cancel on ME Disconnect	Yes	When set to "No", allows orders to remain open on a Matching Unit failover. When set to "Yes", all open orders associated with a session are immediately cancelled in the event of loss of connectivity to a Matching Unit. If a failover takes longer than five minutes, all orders are cancelled unconditionally.
Cancel on Disconnect	*Option #1*	Options for cancelling orders because of a session disconnect: • Cancel All Open Orders (continuous book and Market-On-Close orders) • Do Not Cancel Any Open Orders
Send Trade Breaks	No	Enables or disables Trade Break Messages (35=UCC).
Default *NoTradeFeat*	N (cancel newest)	Specifies default value for *NoTradeFeat* (7713).
Default *NoTradeKey*	Blank	Specifies default value for *NoTradeKey* (7714).
Concatenate *CompId* and *SubId*	No	Requires all FIX traffic to contain concatenated (combined) *CompId* and *SubIds*.
Cancel on Reject	No	Cancels an order upon a cancel or modify reject for that order.
Cancel on Halt	No	Cancel open orders for a symbol upon a halt.
Unique Wash Execution Ids	No	Appends a '.B' or '.S' to *ExecID* (17) on all trades.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

Nanosecond Timestamp Granularity	No	Display nanosecond level timestamp granularity for Timestamp fields in messages from Cboe. These tags default to microsecond granularity. If enabled, time format is: YYYYMMDD-HH:MM:SS.ssssss000
Reject Orders on Drop Port Disconnect*	No	Allows a participant to associate one or more drop port(s) to an order entry port(s). Once the association has been established, if no drop ports associated with an order entry port are connected, reject orders on the order entry port until at least one of the drop port session connections have been established.
Reject Orders on DROP Port Timeout (s)*	30	Only applicable for sessions where "Reject Orders on Drop Port Disconnect" is enabled. When the last associated drop port for the order entry session has disconnected, the reject/cancel actions will be taken on the order entry session if an associated drop port has not reestablished its connection in the defined time. Minimum value allowed is 20.
Cancel Open Orders on Drop Port Disconnect*	No	Only applicable for sessions where "Reject Orders on Drop Port Disconnect" has been enabled. If all drop ports associated with an order entry port become disconnected, cancel all open orders on the order entry port.
Port Order Rate Threshold	Default = 4000 msgs/sec Maximum allowed = 4000 msgs/sec	The maximum allowed message rate on the session. When the first non-administrative message is received, a one second window begins. During the second no more than 3,999 additional non-administrative messages will be allowed within that window. If the rate is exceeded, all new orders in the time window are rejected, modifies are treated as cancels, and cancels are processed.
Test Symbol Order Rate Threshold	Default = 10 msgs/sec	The maximum allowed test symbol message rate on the session. Behaves identically to "Port Order Rate Threshold" above.
Reject Continuous Trading	Default = No	Reject all orders except for VWAP orders.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

9 Contact Information

Please direct questions or comments regarding this specification to TradeDeskJP@cboe.com.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

Revision History

Document Version	Date	Description
1.0.0	22/12/16	Initial version supporting Cboe/CXJ integration.
1.0.1	23/02/10	Removed "3 = Peg Repricing" from *ExecRestatementReason* (378) in Execution Report (section 4.5.1) since it is never populated by CXJ. Removed custom tag *NoselfTradeOrderNum* (8175) from Execution Report, as tag 198 already provides this information on an order cancellation. Removed an incorrect reference to "dollar" currency type in Section 8.
1.0.2	23/05/01	Removed invalid reference to Trade Reports in section 1.2.2. Added *IDSource* (22), *ExecBroker* (76), *ClientID* (109), *ToSTNetTOrderID* (8101), *ToSTNeTExecutionID* (8102), and *ToSTNeTTransactTime* (8106) to Execution Report. Added *OrderID* (37) as an optional field on a `Purge Request`.
1.0.3	23/05/30	Added detail to Timestamp data type in section 1.2.1. Added detail to Price data type in section 1.2.2. Added *OrdStatus* = '6' and 'E' and removed '3' in Execution Report. Removed *ExecType* = '3' in Execution Report. Removed invalid reference to matching units in `Purge Request`.
1.0.4	23/06/29	Updated *TargetCompID* to 'CXJA' for Alpha and 'CXJS' for Select. Removed unused value '6' from *ExecRestatementReason* (378). Added port attribute "Reject Continuous Trading". Added detail to *Trading Firm* filter in `Purge Request`. Added detail regarding the use of *OnBehalfOfCompID* (115) in `Purge Request`. Corrected default setting for *CancelOrigOnReject* (9619) in `Order Cancel/Replace Request`.
1.0.5	23/07/18	Updated "Cancel on ME Disconnect" port attribute default to "Yes".
1.0.6	23/07/25	Updated Section 3.8 "Logout" description.
1.0.7	23/08/15	Updated *ExecID* description in Execution Report. Updated "Send Trade Breaks" port attribute default to "No".
1.0.8	23/08/22	Added *Text*(58) reason code 'W' in Execution Report.
1.0.9	24/02/26	Removed "under review" yellow-highlight comment from *Text* (58) in Execution Report. Updated section 1.4 to include latency expectations as well as Members' responsibility to monitor the status of the messages they send to the exchange.
1.0.10	24/07/05	Updated Maximum Notional Value Per Order FIX Port Attribute.
1.0.11	25/01/15	Updated with Cboe Titanium branding.
1.0.12	25/05/01	Updated *ExecInst* (18) description in New Order Single to PBBO.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved

1.0.13	25/06/09	Updated "Maximum Notional Value Per Order" port attribute to 1 - 10,000,000,000.

© 2025 Cboe Global Markets, Inc. or one or more of its affiliates.
All Rights Reserved