Japannext JNX

FIX Trading Specification (Bonds)

Version 2.00

DISCLAIMER

© 2025 Japannext Co., Ltd. All rights reserved. The material provided herein is for informational purposes only. Japannext Co., Ltd. reserves the right to revise the document and to make changes without notice. Japannext Co., Ltd. has no responsibilities or warranties and excludes all liability (including for negligence) in relation to the present material to the extent allowed by applicable laws.

Last updated: December 4, 2025

Japannext JNX

1 Introduction 4
2 Overview 4
3 Service Configuration 4
4 Fault Redundancy 4
5 FIX Protocol 4
6 Data Types and Required Fields 5
6.1 Required fields 5
7 Limitations 6
8 Order and Trade Identifiers 6
8.1 Client Order ID 6
8.2 Order ID 6
8.3 Trade Match ID 6
8.4 Execution ID 7
9 FIX Session Management 7
10 FIX Messages 7
10.1 Standard Header – Incoming Messages 7
10.2 Standard Header – Outgoing Messages 8
10.3 Standard Trailer 8
10.4 Administrative Messages 9
10.4.1 Logon 9
10.4.2 Heartbeat 9
10.4.3 Test Request 9
10.4.4 Resend Request 9
10.4.5 Reject 9
10.4.6 Sequence Reset 10
10.4.7 Logout 10
10.5 Application Messages 10
10.5.1 New Order Single 10
10.5.2 Execution Report – Order Rejected 12
10.5.3 Execution Report – Order Accepted 13
10.5.4 Execution Report – Order Status 14
10.5.5 Order Cancel Request 15
10.5.6 Order Cancel Reject 16
10.5.7 Execution Report – Order Canceled 16
10.5.8 Order Cancel Replace Request 17

10.5.9 Order Cancel Replace Reject 18
10.5.10 Execution Report – Order Replaced 19
10.5.11 Execution Report – Trade 20
10.5.12 Business Message Reject 22
10.5.13 Trading Session Status 22
11 Appendix 23
11.1 FIX Message Format Structure 23
11.2 Example 23
12 Revision History 24

1 Introduction

This document explains access to the **bonds trading services** of **Japannext PTS** via the **FIX** protocol. It describes the service configuration and specifies both administrative and application messages.

For further information and inquiries regarding trading services, and for questions concerning connectivity, contact Japannext Technical Support at ito@japannext.co.jp.

2 Overview

FIX is an industry-standard, message-based protocol widely used by financial institutions to implement electronic exchange of securities transactions. FIX enables clients to access different markets and liquidity pools operated by Japannext, enter new orders, modify and cancel existing orders, and receive execution reports, all in real time.

FIX messages are encapsulated by TCP/IP as the point-to-point transport layer.

3 Service Configuration

Access to the Japannext PTS bonds trading services can be configured to accept and maintain multiple FIX sessions per client. However, only one active connection is allowed per FIX session. In addition, each FIX session is throttled at a predetermined rate.

The **Cancel on Disconnect** feature can be activated upon request for any client FIX session. If **Cancel on Disconnect** is active, all open orders created during a FIX session that is subsequently disconnected for any reason are automatically withdrawn. For every withdrawn order, an unsolicited cancellation message is sent to the client upon reconnection. **Cancel on Disconnect** is performed on a best-effort basis.

4 Fault Redundancy

Japannext PTS provides a single connection point per FIX session. All instances of a robust FIX client application must maintain sequence numbers as defined by the FIX protocol. In case of connectivity failure, the client instance must reconnect to the same destination. A timeout of at least one second is required between reconnection attempts. Japannext PTS handles IP address migration during service failover on its side.

5 FIX Protocol

The messaging described in this specification complies with the **FIX 4.2** protocol standard (https://www.fixtrading.org/standards/fix-4-2/).

This specification follows the standard FIX specification as closely as possible. However, in limited cases, fields and field values have been extended by backporting from the **FIX 4.4** specification.

6 Data Types and Required Fields

Field data types in this specification are the same as those defined in the standard FIX specification. However, this specification places additional restrictions on certain field values. All field values are stated in the message specification details.

6.1 Required fields

The **Req'd** column of each message definition table specifies field requirements as follows:

- **Y**: standard FIX specification fields **required** in this specification
- **–**: standard FIX specification fields **not required** in this specification
- **R**: fields not specified in the standard FIX specification but **required** in this specification

7 Limitations

This specification limits the lengths of the following fields.

Tag	Field name	Data type	Field limit
1	**Account**	String	10 characters
6	**AvgPx**	Price	6 whole number digits, 6 decimal places
11	**ClOrdID**	String	32 characters
14	**CumQty**	Qty	9 whole number digits
17	**ExecID**	String	20 characters
31	**LastPx**	Price	6 whole number digits, 3 decimal places
32	**LastShares**	Qty	9 whole number digits
37	**OrderID**	String	20 characters
38	**OrderQty**	Qty	9 whole number digits
41	**OrigClOrdID**	String	32 characters
44	**Price**	Price	6 whole number digits, 3 decimal places
50	**SenderSubID**	String	30 characters for incoming messages 4 characters for outgoing messages
55	**Symbol**	String	9 digits
57	**TargetSubID**	String	4 characters for incoming messages 30 characters for outgoing messages
109	**ClientID**	String	9 digits
110	**MinQty**	Qty	9 whole number digits
151	**LeavesQty**	Qty	9 whole number digits
336	**TradingSessionID**	String	20 characters
375	**ContraBroker**	String	12 characters
880	**TrdMatchID**	String	20 characters

8 Order and Trade Identifiers

8.1 Client Order ID

ClOrdID validation for uniqueness is not guaranteed. New orders are only checked against open orders for duplication.

8.2 Order ID

OrderID is set to the unique reference number assigned to the order by the trading system. An **OrderID** originally assigned to an order may be replaced with a new unique **OrderID** during the order's lifetime.

8.3 Trade Match ID

TrdMatchID is set to the unique reference number assigned to the trade by the trading system.

8.4 Execution ID

ExecID uniqueness is guaranteed only per FIX session.

9 FIX Session Management

FIX sessions are uniquely defined by the **SenderCompID** and **TargetCompID**. Any attempt to establish an additional FIX session using the same **SenderCompID** and **TargetCompID** is rejected.

At logon, clients are identified by their **SenderCompID**. Clients must log on to the service using the logon message. Once logged on, clients must send heartbeat messages to keep their session active.

In case of connection loss, clients are required to again log on using the next transmitted sequence numbers while also handling any potential message loss in a FIX protocol-compliant manner.

IP addresses, port numbers, and **CompIDs** are issued upon application completion.

10 FIX Messages

10.1 Standard Header – Incoming Messages

Tag	Field name	Data type	Req'd	Comments
8	**BeginString**	String	Y	Identifies beginning of new message and protocol version. Always first field in message. Value is 'FIX.4.2'.
9	**BodyLength**	int	Y	Message length, in bytes, from start of MsgType (35) field up to and including the delimiter preceding the CheckSum (10) field. Always second field in message.
35	**MsgType**	String	Y	Defines message type. Always third field in message.
34	**MsgSeqNum**	int	Y	Integer message sequence number.
43	**PossDupFlag**	Boolean	-	Indicates possible retransmission of message having the MsgSeqNum sequence number. Values: Y = Possible duplicate N = Original transmission
49	**SenderCompID**	String	Y	Identifies the firm sending messages. Assigned by Japannext.
50	**SenderSubID**	String	-	Identifies specific message originator.
52	**SendingTime**	UTC Timestamp	Y	Time of message transmission (always expressed in UTC).
56	**TargetCompID**	String	Y	Identifies receiving firm. Assigned by Japannext.
57	**TargetSubID**	String	-	Identifies specific individual or unit intended to receive the message. Assigned by Japannext. If this field is omitted, the default value for the session is used. Value: DJGB = JGB Market

97	**PossResend**	Boolean	-	Indicates that message may contain information sent under another sequence number. Values: Y = Possible resend N = Original transmission
115	**OnBehalfOfCompID**	String	-	Identifies firm from which message originates if message delivered by third party. Assigned by Japannext. Note: SenderCompID (49) specifies the third-party firm identifier.
122	**OrigSendingTime**	UTC Timestamp	-	Original time of message transmission (always expressed in UTC).

10.2 Standard Header – Outgoing Messages

Tag	Field name	Data type	Req'd	Comments
8	**BeginString**	String	Y	Identifies beginning of new message and protocol version. Always first field in message. Value is 'FIX.4.2'.
9	**BodyLength**	int	Y	Message length, in bytes, from start of MsgType (35) field up to and including the delimiter preceding the CheckSum (10) field. Always second field in message.
35	**MsgType**	String	Y	Defines message type. Always third field in message.
34	**MsgSeqNum**	int	Y	Integer message sequence number.
49	**SenderCompID**	String	Y	Identifies the firm sending the message. Assigned by Japannext.
50	**SenderSubID**	String	-	Identifies specific message originator. Assigned by Japannext. Values: DJGB = JGB Market
52	**SendingTime**	UTC Timestamp	Y	Time of message transmission (always expressed in UTC).
56	**TargetCompID**	String	Y	Identifies receiving firm. Assigned by Japannext.
57	**TargetSubID**	String	-	Identifies specific individual or unit intended to receive the message.
122	**OrigSendingTime**	UTC Timestamp	-	Original time of message transmission (always expressed in UTC).
128	**DeliverToCompID**	String	-	Identifies firm targeted to receive message if message delivered by third party. Assigned by Japannext. Note: TargetCompID specifies the third-party firm identifier.

10.3 Standard Trailer

Tag	Field name	Data type	Req'd	Comments
10	**CheckSum**	String	Y	Three-byte simple checksum. Always defined as three characters. Always last field in message.

10.4 Administrative Messages

10.4.1 Logon

Tag	Field name	Data type	Req'd	Comments
Standard header				MsgType (35) = A
98	**EncryptMethod**	int	Y	Encryption method. Not supported. Value: 0 = None / other
108	**HeartBtInt**	int	Y	Heartbeat interval (seconds). Recommended value is '30'.
141	**ResetSeqNumFlag**	Boolean	-	Indicates whether both sides of the FIX session should reset sequence numbers. Values: Y = Yes, reset sequence numbers N = No, do not reset sequence numbers
Standard trailer				

10.4.2 Heartbeat

Tag	Field name	Data type	Req'd	Comments
Standard header				MsgType (35) = 0
112	**TestReqID**	String	-	Required when heartbeat is result of a Test Request message.
Standard trailer				

10.4.3 Test Request

Tag	Field name	Data type	Req'd	Comments
Standard header				MsgType (35) = 1
112	**TestReqID**	String	Y	Identifier to be returned in resulting Heartbeat.
Standard trailer				

10.4.4 Resend Request

Tag	Field name	Data type	Req'd	Comments
Standard header				MsgType (35) = 2
7	**BeginSeqNo**	int	Y	Message sequence number of first message in range to be re-sent.
16	**EndSeqNo**	int	Y	Message sequence number of last message in range to be re-sent.
Standard trailer				

10.4.5 Reject

Tag	Field name	Data type	Req'd	Comments
Standard header				MsgType (35) = 3
45	**RefSeqNum**	int	Y	MsgSeqNum (34) of rejected message.
58	**Text**	String	-	Reject reason details.

371	**RefTagID**	int	-	Tag number of FIX field being referenced.
372	**RefMsgType**	String	-	MsgType (35) of FIX message being referenced.
373	**SessionRejectReason**	int	-	Reason for session-level Reject message. Values: 0 = Invalid tag number 1 = Required tag missing 2 = Tag not defined for this message type 3 = Undefined tag 4 = Tag specified without a value 5 = Value is incorrect (out of range) for this tag 6 = Incorrect data format for value 9 = CompID problem 10 = SendingTime (52) accuracy problem 11 = Invalid MsgType (35)
Standard trailer				

10.4.6 Sequence Reset

Tag	Field name	Data type	Req'd	Comments
Standard header				MsgType (35) = 4
36	**NewSeqNo**	int	Y	New sequence number.
123	**GapFillFlag**	Boolean	-	Indicates replacing administrative or application messages which will not be re-sent. Values: Y = Gap Fill message, MsgSeqNum (34) field valid N = Sequence Reset, ignore MsgSeqNum (34)
Standard trailer				

10.4.7 Logout

Tag	Field name	Data type	Req'd	Comments
Standard header				MsgType (35) = 5
58	**Text**	String	-	Logout reason details.
Standard trailer				

10.5 Application Messages

10.5.1 New Order Single

Tag	Field name	Data type	Req'd	Comments
Standard header – Incoming				MsgType (35) = D
1	**Account**	String	-	Account mnemonic. Assigned by firm.
11	**ClOrdID**	String	Y	Unique identifier of order. Assigned by firm.
18	**ExecInst**	Multiple ValueString	-	One or more space-delimited instructions for order handling. Values: 6 = Participate, don't initiate (post-only) x = Ignore notional value checks

21	**HandlInst**	char	-	Instructions for order handling on broker side. Value: 1 = Automated execution order, private, no broker intervention
38	**OrderQty**	Qty	R	Order quantity.
40	**OrdType**	char	Y	Order type. Value: 2 = Limit
44	**Price**	Price	R	Yield per bond. Required for limit orders, OrdType (40) = 2 (Limit).
47	**Rule80A**	char	-	Capacity of firm placing order. Absence of this field interpreted as 'Principal'. Values: A = Agency P = Principal
54	**Side**	char	Y	Side of order. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Value is the Securities Identification Code Committee (SICC) code.
59	**TimeInForce**	char	-	How long order remains in effect. Absence of this field interpreted as 'Day'. Values: 0 = Day 3 = Immediate or Cancel (IOC) 4 = Fill or Kill (FOK)
60	**TransactTime**	UTC Timestamp	Y	Time order request initiated.
109	**ClientID**	String	-	Identifier of order entry firm. Omit unless specifying client MPID.
110	**MinQty**	Qty	-	Minimum quantity of order to be executed. Applicable only when TimeInForce (59) = 3 (Immediate or Cancel).
423	**PriceType**	int	R	Price type. Value: 9 = Yield
Standard trailer				

10.5.2 Execution Report – Order Rejected

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = 8
1	**Account**	String	-	Account mnemonic. Assigned by firm.
6	**AvgPx**	Price	Y	Calculated average yield of all fills on this order.
11	**ClOrdID**	String	R	Unique identifier of order. Assigned by firm.
14	**CumQty**	Qty	Y	Total number of bonds filled.
17	**ExecID**	String	Y	Unique identifier of execution message. Assigned by Japannext.
20	**ExecTransType**	char	Y	Transaction type. Value: 0 = New
37	**OrderID**	String	Y	Unique identifier of order. Assigned by Japannext. Value is 'NONE' if OrdRejReason (103) ≠ 6 (Duplicate Order).
38	**OrderQty**	Qty	R	Quantity ordered.
39	**OrdStatus**	char	Y	Current status of order. Values: 0 = New 1 = Partially filled 2 = Filled 4 = Canceled 5 = Replaced 6 = Pending cancel 8 = Rejected A = Pending new E = Pending replace
40	**OrdType**	char	R	Order type. Value: 2 = Limit
44	**Price**	Price	R	Yield per bond entered.
47	**Rule80A**	char	R	Capacity of firm placing order. Values: A = Agency P = Principal
54	**Side**	char	Y	Side of order. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Value is the Securities Identification Code Committee (SICC) code.
58	**Text**	String	-	Reject reason details.
59	**TimeInForce**	char	R	How long order remains in effect. Values: 0 = Day 3 = Immediate or Cancel (IOC) 4 = Fill or Kill (FOK)

103	**OrdRejReason**	int	R	Reason for order rejection. Values: 0 = Broker / trading venue option 1 = Unknown symbol 2 = Trading venue closed 3 = Order exceeds limit 6 = Duplicate order (e.g., duplicate ClOrdID (11)) 8 = Stale order 11 = Unsupported order characteristic 12 = Surveillance option 13 = Incorrect quantity 16 = Price exceeds current price band 99 = Other
109	**ClientID**	String	-	Identifier of order entry firm, if specified.
110	**MinQty**	Qty	-	Minimum quantity of order to be executed.
150	**ExecType**	char	Y	Denotes specific Execution Report. Value: 8 = Rejected
151	**LeavesQty**	Qty	Y	Amount of bonds open for further execution.
423	**PriceType**	int	R	Price type. Value: 9 = Yield
Standard trailer				

10.5.3 Execution Report – Order Accepted

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = 8
1	**Account**	String	-	Account mnemonic. Assigned by firm.
6	**AvgPx**	Price	Y	Calculated average price of all fills on this order. Value is '0'.
11	**ClOrdID**	String	R	Unique identifier of order. Assigned by firm.
14	**CumQty**	Qty	Y	Total number of bonds filled. Value is '0'.
17	**ExecID**	String	Y	Unique identifier of execution message. Assigned by Japannext.
20	**ExecTransType**	char	Y	Transaction type. Value: 0 = New
37	**OrderID**	String	Y	Unique identifier of order. Assigned by Japannext.
38	**OrderQty**	Qty	R	Quantity accepted.
39	**OrdStatus**	char	Y	Current status of order. Value: 0 = New
40	**OrdType**	char	R	Order type. Value: 2 = Limit
44	**Price**	Price	R	Price per bond accepted.
47	**Rule80A**	char	R	Capacity of firm placing order. Values: A = Agency P = Principal

54	**Side**	char	Y	Side of order. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Value is the Securities Identification Code Committee (SICC) code.
59	**TimeInForce**	char	R	How long order remains in effect. Values: 0 = Day 3 = Immediate or Cancel (IOC) 4 = Fill or Kill (FOK)
60	**TransactTime**	UTC Timestamp	R	Time when transaction represented by this message occurred.
109	**ClientID**	String	-	Identifier of order entry firm, if specified.
110	**MinQty**	Qty	-	Minimum quantity of order to be executed.
150	**ExecType**	char	Y	Denotes specific Execution Report. Value: 0 = New
151	**LeavesQty**	Qty	Y	Amount of bonds open for further execution. Value is same as that of OrderQty (38).
423	**PriceType**	int	R	Price type. Value: 9 = Yield
Standard trailer				

10.5.4 Execution Report – Order Status

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = 8
1	**Account**	String	-	Account mnemonic. Assigned by firm.
6	**AvgPx**	Price	Y	Calculated average yield of all fills on this order.
11	**ClOrdID**	String	R	Unique identifier of order. Assigned by firm.
14	**CumQty**	Qty	Y	Total number of bonds filled.
17	**ExecID**	String	Y	Unique identifier of execution message. Assigned by Japannext.
20	**ExecTransType**	char	Y	Transaction type. Value: 3 = Status
37	**OrderID**	String	Y	Unique identifier of order. Assigned by Japannext.
38	**OrderQty**	Qty	R	Quantity accepted.
39	**OrdStatus**	char	Y	Current status of order. Values: 0 = New 1 = Partially filled 2 = Filled 4 = Canceled 5 = Replaced 6 = Pending cancel 8 = Rejected A = Pending new E = Pending replace

40	**OrdType**	char	R	Order type. Value: 2 = Limit
44	**Price**	Price	R	Price per bond accepted.
47	**Rule80A**	char	R	Capacity of firm placing order. Values: A = Agency P = Principal
54	**Side**	char	Y	Side of order. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Value is the Securities Identification Code Committee (SICC) code.
59	**TimeInForce**	char	R	How long order remains in effect. Values: 0 = Day 3 = Immediate or Cancel (IOC) 4 = Fill or Kill (FOK)
109	**ClientID**	String	-	Identifier of order entry firm, if specified.
110	**MinQty**	Qty	-	Minimum quantity of order to be executed.
150	**ExecType**	char	Y	Denotes specific Execution Report. Value: I = Order Status
151	**LeavesQty**	Qty	Y	Amount of bonds open for further execution.
423	**PriceType**	int	R	Price type. Value: 9 = Yield
Standard trailer				

10.5.5 Order Cancel Request

Tag	Field name	Data type	Req'd	Comments
Standard header - Incoming				MsgType (35) = F
11	**ClOrdID**	String	Y	Unique identifier of order. Assigned by firm.
38	**OrderQty**	Qty	R	Value ignored. Recommended value is current total order quantity (incl. amount already executed for this chain of orders).
41	**OrigClOrdID**	String	Y	ClOrdID (11) of previous order (not initial order). Assigned by firm.
54	**Side**	char	Y	Side of order. Must match original side. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Must match original symbol. Value is the Securities Identification Code Committee (SICC) code.
60	**TransactTime**	UTC Timestamp	Y	Time order request initiated.
Standard trailer				

10.5.6 Order Cancel Reject

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = 9
11	**ClOrdID**	String	Y	Unique identifier of order. Assigned by firm.
37	**OrderID**	String	Y	Unique identifier of order. Assigned by Japannext. Value is 'NONE' if CxlRejReason (102) = 1 (Unknown order).
39	**OrdStatus**	char	Y	Current status of order. Values: 0 = New 1 = Partially filled 2 = Filled 4 = Canceled 5 = Replaced 6 = Pending cancel 8 = Rejected A = Pending new E = Pending replace
41	**OrigClOrdID**	**String**	Y	ClOrdID (11) of previous order (not initial order). Assigned by firm.
58	**Text**	String	-	Reject reason details.
102	**CxlRejReason**	int	R	Cancel rejection reason. Values: 0 = Too late to cancel 1 = Unknown order 3 = Order already in Pending Cancel or Pending Replace status 6 = Duplicate ClOrdID (11) received 99 = Other
434	**CxlRejResponseTo**	char	Y	Type of request triggering Cancel Reject response. Value: 1 = Order Cancel Request
Standard trailer				

10.5.7 Execution Report – Order Canceled

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = 8
1	**Account**	String	-	Account mnemonic. Assigned by firm.
6	**AvgPx**	Price	Y	Calculated average yield of all fills on this order.
11	**ClOrdID**	String	R	Unique identifier of order. Assigned by firm.
14	**CumQty**	Qty	Y	Total number of bonds filled.
17	**ExecID**	String	Y	Unique identifier of execution message. Assigned by Japannext.
20	**ExecTransType**	char	Y	Transaction type. Value: 0 = New
37	**OrderID**	String	Y	Unique identifier of order. Assigned by Japannext.
38	**OrderQty**	Qty	R	Quantity accepted.

39	**OrdStatus**	char	Y	Current status of order. Value: 4 = Canceled
40	**OrdType**	char	R	Order type. Value: 2 = Limit
41	**OrigClOrdID**	String	-	ClOrdID (11) of previous order (not initial order). Assigned by firm.
44	**Price**	Price	R	Price per bond accepted.
47	**Rule80A**	char	R	Capacity of firm placing order. Values: A = Agency P = Principal
54	**Side**	char	Y	Side of order. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Value is the Securities Identification Code Committee (SICC) code.
59	**TimeInForce**	char	R	How long order remains in effect. Values: 0 = Day 3 = Immediate or Cancel (IOC) 4 = Fill or Kill (FOK)
60	**TransactTime**	UTC Timestamp	R	Time when transaction represented by this message occurred.
109	**ClientID**	String	-	Identifier of order entry firm, if specified.
110	**MinQty**	Qty	-	Minimum quantity of order to be executed.
150	**ExecType**	char	Y	Denotes specific Execution Report. Value: 4 = Canceled
151	**LeavesQty**	Qty	Y	Amount of bonds open for further execution. Value is '0'.
378	**ExecRestatement Reason**	int	-	Reason for unsolicited cancel. Values: 2 = Verbal change 7 = Cancel on system failure 12 = Cancel on connection loss 99 = Other 100 = Trade prevention
423	**PriceType**	int	R	Price type. Value: 9 = Yield
Standard trailer				

10.5.8 Order Cancel Replace Request

Tag	Field name	Data type	Req'd	Comments
Standard header - Incoming				MsgType (35) = G
11	**ClOrdID**	String	Y	Unique identifier of order. Assigned by firm.
18	**ExecInst**	Multiple ValueString	-	One or more space-delimited instructions for order handling. Values: 6 = Participate, don't initiate (post-only) x = Ignore notional value checks

21	**HandlInst**	char	-	Instructions for order handling on broker side. Value: 1 = Automated execution order, private, no broker intervention
38	**OrderQty**	Qty	R	New intended total order quantity (incl. amount already executed for order chain).
40	**OrdType**	char	Y	Order type. Value: 2 = Limit
41	**OrigClOrdID**	String	Y	ClOrdID (11) of previous order (not initial order). Assigned by firm.
44	**Price**	Price	R	Yield per bond. Required for limit orders (i.e., OrdType = 2 (Limit)).
47	**Rule80A**	char	-	Capacity of firm placing order. Absence of this field interpreted as 'Principal'. Must match original order capacity. Values: A = Agency P = Principal
54	**Side**	char	Y	Side of order. Must match original side. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Must match original symbol. Value is the Securities Identification Code Committee (SICC) code.
59	**TimeInForce**	char	-	How long order remains in effect. Absence of this field interpreted as 'Day'. Values: 0 = Day 3 = Immediate or Cancel (IOC) 4 = Fill or Kill (FOK)
60	**TransactTime**	UTC Timestamp	Y	Time order request initiated.
110	**MinQty**	Qty	-	Minimum quantity of order to be executed. Applicable only if TimeInForce (59) = 3 (Immediate or Cancel).
423	**PriceType**	int	R	Price type. Value: 9 = Yield
Standard trailer				

10.5.9 Order Cancel Replace Reject

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = 9
11	**ClOrdID**	String	Y	Unique identifier of order. Assigned by firm.
37	**OrderID**	String	Y	Unique identifier of order. Assigned by Japannext. Value is 'NONE' if CxlRejReason (102) = 1 (Unknown order).

39	**OrdStatus**	char	Y	Current status of order. Values: 0 = New 1 = Partially filled 2 = Filled 4 = Canceled 5 = Replaced 6 = Pending Cancel 8 = Rejected A = Pending New E = Pending Replace
41	**OrigClOrdID**	String	Y	ClOrdID (11) of previous order (not initial order). Assigned by firm.
58	**Text**	String	-	Reject reason details.
102	**CxlRejReason**	int	R	Cancel rejection reason. Values: 0 = Too late to cancel 1 = Unknown order 2 = Broker / trading venue option 3 = Order already in Pending Cancel or Pending Replace status 6 = Duplicate ClOrdID (11) received 8 = Price exceeds current price band 99 = Other
434	**CxlRejResponseTo**	char	Y	Type of request triggering Cancel Reject response. Value: 2 = Order Cancel/Replace Request
Standard trailer				

10.5.10 Execution Report – Order Replaced

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = 8
1	**Account**	String	-	Account mnemonic. Assigned by firm.
6	**AvgPx**	Price	Y	Calculated average yield of all fills on this order.
11	**ClOrdID**	String	R	Unique identifier of order. Assigned by firm.
14	**CumQty**	Qty	Y	Total number of bonds filled.
17	**ExecID**	String	Y	Unique identifier of execution message. Assigned by Japannext.
20	**ExecTransType**	char	Y	Transaction type. Value: 0 = New
37	**OrderID**	String	Y	Unique identifier of order. Assigned by Japannext.
38	**OrderQty**	Qty	R	Quantity accepted.
39	**OrdStatus**	char	Y	Current status of order. Values: 1 = Partially filled 2 = Filled 5 = Replaced
40	**OrdType**	char	R	Order type. Values: 2 = Limit

41	**OrigClOrdID**	String	R	ClOrdID (11) of previous order (not initial order). Assigned by firm.
44	**Price**	Price	R	Yield per bond accepted.
47	**Rule80A**	char	R	Capacity of firm placing order. Values: A = Agency P = Principal
54	**Side**	char	Y	Side of order. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Value is the Securities Identification Code Committee (SICC) code.
59	**TimeInForce**	char	R	How long order remains in effect. Values: 0 = Day 3 = Immediate or Cancel (IOC) 4 = Fill or Kill (FOK)
60	**TransactTime**	UTC Timestamp	R	Time when transaction represented by this message occurred.
109	**ClientID**	String	-	Identifier of order entry firm, if specified.
110	**MinQty**	Qty	-	Minimum quantity of order to be executed.
150	**ExecType**	char	Y	Denotes specific Execution Report. Value: 5 = Replaced
151	**LeavesQty**	Qty	Y	Amount of bonds open for further execution.
423	**PriceType**	int	R	Price type. Value: 9 = Yield
Standard trailer				

10.5.11 Execution Report – Trade

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = 8
1	**Account**	String	-	Account mnemonic. Assigned by firm.
6	**AvgPx**	Price	Y	Calculated average yield of all fills on this order.
11	**ClOrdID**	String	R	Unique identifier of order. Assigned by firm.
14	**CumQty**	Qty	Y	Total number of bonds filled.
17	**ExecID**	String	Y	Unique identifier of execution message. Assigned by Japannext.
20	**ExecTransType**	char	Y	Transaction type. Value: 0 = New
31	**LastPx**	Price	R	Yield of this (last) fill.
32	**LastShares**	Qty	R	Number of bonds bought/sold on this (last) fill.
37	**OrderID**	String	Y	Unique identifier of order. Assigned by Japannext.
38	**OrderQty**	Qty	R	Quantity accepted.

39	**OrdStatus**	char	Y	Current status of order. Values: 1 = Partially filled 2 = Filled 6 = Pending Cancel E = Pending Replace
40	**OrdType**	char	R	Order type. Value: 2 = Limit
44	**Price**	Price	R	Price per bond accepted.
47	**Rule80A**	char	R	Capacity of firm placing order. Values: A = Agency P = Principal
54	**Side**	char	Y	Side of order. Values: 1 = Buy 2 = Sell
55	**Symbol**	String	Y	Ticker symbol. Value is the Securities Identification Code Committee (SICC) code.
59	**TimeInForce**	char	R	How long order remains in effect. Values: 0 = Day 3 = Immediate or Cancel (IOC) 4 = Fill or Kill (FOK)
60	**TransactTime**	UTC Timestamp	R	Time when transaction represented by this message occurred.
109	**ClientID**	String	-	Identifier of order entry firm, if specified.
110	**MinQty**	Qty	-	Minimum quantity of order to be executed.
150	**ExecType**	char	Y	Denotes specific Execution Report. Values: 1 = Partial fill 2 = Fill
151	**LeavesQty**	Qty	Y	Amount of bonds open for further execution.
375	**ContraBroker**	String	R	Identifier for trade counterparty. Value is the PSMS code per JASDEC definition.
382	**NoContraBrokers**	int	R	Number of ContraBroker (375) entries. Value is '1'.
423	**PriceType**	int	R	Code to represent the price type. Value: 9 = Yield
851	**LastLiquidityInd**	int	R	Identifies whether fill is a result of a liquidity provider maker or taker. Values: 1 = Added liquidity 2 = Removed liquidity
880	**TrdMatchID**	String	R	Identifier assigned to a trade by a matching system.
Standard trailer				

10.5.12 Business Message Reject

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = j
45	**RefSeqNum**	int	-	MsgSeqNum (34) of rejected message.
58	**Text**	String	-	Reject reason details.
372	**RefMsgType**	String	Y	MsgType (35) of FIX message being referenced.
379	**BusinessRejectRefID**	String	-	ClOrdID (11) of FIX message being referenced.
380	**BusinessRejectReason**	int	Y	Reason for a Business Message Reject message. Values: 0 = Other 3 = Unsupported Message Type 5 = Conditionally Required Field Missing
Standard trailer				

10.5.13 Trading Session Status

Tag	Field name	Data type	Req'd	Comments
Standard header - Outgoing				MsgType (35) = h
336	**TradingSessionID**	String	Y	Identifier for trading session.
339	**TradSesMode**	int	R	Trading session mode. Values: 1 = Testing 3 = Production
340	**TradSesStatus**	int	Y	State of the trading session. Values: 1 = Halted 2 = Open 3 = Closed
Standard trailer				

11 Appendix

11.1 FIX Message Format Structure

- A FIX message is a sequence of **string-based fields**.
- Each field consists of a **tag–value pair** in the format of **<tag>=<value>**.
- Fields are **delimited** by the non-printable ASCII Start of Heading (**SOH**) control character (0x01).
- Messages are **terminated** by the SOH character.

Note: For **readability purposes**, FIX messages may be presented with spaces or other ASCII characters, such as the vertical line (|) or circumflex (^), in place of the SOH character. For **transmission**, however, the SOH character is always used.

11.2 Example

(with vertical line delimiter)

- 8=FIX.4.4|9=117|35=AD|34=2|49=A|50=1|52=20100219-14:33:32.258|56=B|57=M|263=1|568=1|569=0|580=1|75=20100218|60=20100218-00:00:00.000|10=202|

12 Revision History

Date	Version	Description
2025-11-27	2.00	Document format has been revamped. Section numbers changed to accommodate new format. Amended BodyLength (9) field description: "from start of message" » "from start of MsgType (35) field". "bond code per SICC definition" changed to "Securities Identification Code Committee (SICC) code". Other parts of the text have been reworded to improve readability. Appendix added. No other factual changes made to technical content.
2017-11-21	1.2	Added Data Type column to message definition tables. Added values for boolean fields. Changed order of fields listed in header to group first three required fields. Add parenthesized tag numbers to field names appearing in comments of message definition tables. Differentiated between Incoming and Outgoing standard headers in Application Messages. Price (44) is marked as required 'R' in Execution Reports.
2017-08-31	1.1	Decreased Account (1) field's length limitation from 16 to 10. Decreased ExecID (17) field's length limitation from 30 to 20. Increased SenderSubID (50) field's length limitation from 10 to 30 for incoming messages. Decreased TargetSubID (57) field's length limitation from 10 to 4 for incoming messages. Added TrdMatchID (880) to field length limitations table with value 20. Removed OrderID (37) field from Order Cancel Replace Request and Order Cancel Request messages.
2016-12-05	1.0	Initial revision.