

BATS Chi-X Europe FIX Specification

Version 2.76

14 July, 2015

BATS Trading Limited is a Recognised Investment Exchange regulated by the Financial Conduct Authority. BATS Trading Limited is an indirect wholly-owned subsidiary of BATS Global Markets, Inc. and is a company registered in England and Wales with Company Number 6547680 and registered office at 10 Lower Thames Street, London EC3R 6AF. This document has been established for informational purposes only. None of the information concerning the services or products described in this document constitutes advice or a recommendation of any product or service. To the extent that the information provided in this document constitutes a financial promotion as defined by section 21 of the Financial Services and Markets Act 2000, it is only directed at persons who qualify as a Professional Client or Eligible Counterparty. Persons who do not qualify should not act or rely upon it.

Contents

1 Overview **4**

1.1 Hours of Operation . . . 4
1.2 Timestamps . . . 4
1.3 Symbology . . . 4
1.4 Tick Sizes . . . 5
1.5 Hidden Orders . . . 5
1.6 BATS Dark Pool . . . 5
1.7 Access Fees Returned on Execution Reports . . . 6
1.8 Service Bureau Configuration . . . 6
1.9 Order Price Collars . . . 6
1.10 Reserve (Iceberg) Orders . . . 6
1.11 Peg Order Pricing . . . 7
1.12 Routing (Parallel-D and Parallel-2D) . . . 7
1.13 BATS Plus . . . 7
1.14 BATS DRTOnly . . . 7
1.15 Interbook Order Types . . . 7
1.16 Dark Lit Orders . . . 8
1.17 Account Field . . . 8

2 BATS Chi-X Europe Specific FIX Fields **9**

3 FIX Session Protocol **13**

3.1 Sequence Numbers . . . 13
3.2 Logon . . . 13
3.3 Heartbeat . . . 13
3.4 Test Request . . . 14
3.5 Resend Request . . . 14
3.6 Reject . . . 14
3.7 Sequence Reset . . . 14
3.8 Logout . . . 14

4 Standard FIX Message Header and Trailer **15**

4.1 Header . . . 15
4.2 Trailer . . . 15

5 FIX Application Messages — Participant to BATS **16**

5.1 New Order — Single . . . 16
5.1.1 Notes on Pegged Orders . . . 21
5.2 Order Cancel Request . . . 21
5.3 Order Cancel/Replace Request . . . 22
5.4 Trade Capture Report . . . 24

6 FIX Application Messages — BATS to Participant **29**
6.1 Execution Report . . . 29
6.2 Cancel Reject . . . 33
6.3 Trade Cancel/Correct . . . 34
6.4 Trade Capture Report Ack . . . 35
6.5 Trade Capture Report . . . 37

7 Example Messages and Message Flow **39**
7.1 Trade Capture Report Cancellations . . . 39
7.2 Trade Capture Report Amendments . . . 40
7.3 Deferred Publication Trade Reports . . . 41
7.4 ETR Matched Trade Report . . . 43
7.5 Withdrawing an ETR Matching Instruction . . . 44
7.6 Withdrawing an ETR Matched Cancellation Instruction . . . 45
7.7 ETR Matched Trade Report with Consideration and Tolerance . . . 46
7.8 ETR Matched Trade Report with Price and Tolerance . . . 46
7.9 Third Party Confirmed Trades . . . 47

8 Common Session Level Issues **48**
8.1 Ordered Message Processing . . . 48
8.2 Logon . . . 48
8.3 Message Recovery . . . 48
8.4 Resend Request . . . 49
8.5 Sequence Reset – Gap Fill . . . 49

9 FIX Drop **51**
9.1 Standard FIX Drop . . . 51
9.2 Order By Order FIX Drop . . . 51
9.3 Port Options . . . 51

10 FIX Differences Between US and Europe **52**

11 Support **54**

Revision History **54**

1 Overview

This document describes BATS Chi-X Europe's (hereafter, "BATS") interpretation and implementation of the FIX 4.2 specification. BATS uses a subset of the FIX 4.2 protocol for order entry and drop copies. It is assumed that the reader is familiar with the FIX 4.2 protocol as described by the FIX Protocol Organisation.

BATS operates separate pairs of integrated and dark order books. These are distinguished by the identifiers BXE and CXE. The functionality described in this document applies equally to BXE and CXE FIX sessions.

1.1 Hours of Operation

Refer to the BATS Chi-X Europe website for hours of operation.

All orders are live upon acceptance by BATS. Orders are rejected if they are received outside the hours BATS is available for trading. BATS does not support maintaining orders for multiple days (GTC orders). All open orders are canceled on close of the market. Participants will receive an execution report for every open order with *ExecType* (150) = `4` (Canceled).

1.2 Timestamps

All FIX timestamps are GMT as per the FIX standard. Participants are expected to synchronise their clocks with an external time source.

1.3 Symbology

BATS accepts three symbologies: Uniform Symbology, RIC and ISIN. Different symbologies may be used on different orders, but it is recommended that Participants use the same symbology for all orders.

If using Uniform Symbology to identify a stock, the Participant:

- **must** set *Symbol* (55) to the Uniform Symbology symbol;
- *may optionally* set the *SecurityExchange* (207); and,
- *may optionally* set the *Currency* (15).

If using ISIN to identify a stock, the Participant:

- **must** set *IDSource* (22) to ISIN (4);
- **must** set *SecurityID* (48) to the ISIN;
- **must** set *SecurityExchange* (207) to note the market in which the ISIN trades;
- **must** set the *Currency* (15) field to identify the currency in which the stock is traded; and,
- *may optionally* set the *Symbol* (55).

If using RIC to identify a stock, the Participant:

- **must** set *IDSource* (22) to RIC (5);
- **must** set *SecurityID* (48) to the RIC;
- *may optionally* set the *SecurityExchange* (207);
- *may optionally* set the *Currency* (15) field; and,
- *may optionally* set the *Symbol* (55).

If using ISIN or RIC to identify a stock in *SecurityID* (48), and opting to also send *Symbol* (55), the *Symbol* (55) may be specified as the Uniform Symbology symbol, the *SecurityID* (48), the RIC or the Ticker code.

A RIC in either *SecurityID* (48) or *Symbol* (55), may be supplied as either a BATS or primary market RIC.

When specifying an optional value as noted above, the value specified must match the value in BATS' symbol database. Otherwise, the order will be rejected.

Execution reports will always respond with the same symbology as was sent in the corresponding New Order Single message.

For additional information about BATS' symbology, see the BATS Chi-X Europe Market Guide.

1.4 Tick Sizes

The minimum price increment, or tick size, is generally the same as that on the primary market. Tick size is subject to change. Orders entered which violate the tick size will be rejected. Midpoint peg orders are not tick size validated and may execute at a price that is one-half the tick size. Where the mathematical mid price has more than four decimal places then the match mid price will be rounded up to four decimal places.

Trade Capture Reports do not need the reported or settlement price to be on a tick size boundary. Should the price specified exceed seven decimal places, it will be truncated to such.

1.5 Hidden Orders

BATS allows Participants to place hidden orders which are not represented on its market data feed. Hidden orders include pegged orders and orders which have the *DisplayIndicator* (9479) = `I` (Invisible). MiFID regulations require that orders with a notional value less than the Large In Scale (LIS) *must* be displayed unless routed to the BATS Dark Pool.[1]

BATS will reject any order submitted which violates this regulation. Where no LIS value is specified in the MiFID regulations, Participants may only submit hidden orders with a notional value greater than the value specified by BATS in its reference data unless routed to the BATS Dark Pool. BATS will reject any order submitted which violates this.

Notional value is calculated differently depending upon order type:

Limit:	*Price* (44) × *OrderQty* (38)
Buy primary peg, sell market peg:	(PBBO bid + *PegDifference* (211)) × *OrderQty* (38)
Sell primary peg, buy market peg:	(PBBO ask + *PegDifference* (211)) × *OrderQty* (38)
Midpoint peg:	(PBBO midpoint + *PegDifference* (211)) × *OrderQty* (38)

More information on the MiFID ESMA database can be found at the ESMA MiFID website.

1.6 BATS Dark Pool

The BATS Dark Pool is a separate book which allows matching of dark liquidity based at a midpoint reference price. Separate BATS Dark Pools are operated for BXE and CXE ports. Orders placed into the BATS Dark Pool do not need to be Large In Scale (LIS). BATS Dark Pool orders only interact with other BATS Dark Pool orders. Quotes for BATS Dark Pool orders are not represented on any market data feed. Matches in the BATS Dark Pool are represented as trades on BATS' market data feeds and may be differentiated.

Orders destined for the BATS Dark Pool must be midpoint peg orders[2]. The *RoutingInst* (9303) must be set to one of the following:

`BD`: Routes only to the BATS Dark Pool.

`BA`: Routes to the BATS Dark Pool if midpoint and not LIS, or to the integrated book otherwise. Non-midpoint peg orders may also be sent with BA and will always route to the integrated book.

A limit price may be specified on a BATS Dark Pool order using the *Price* (44) field. If set, execution still only occurs at the midpoint. When the midpoint is a more aggressive price than the limit price, the order will not be available for execution.

[1] Field *RoutingInst* (9303) = BD or BA.
[2] *ExecInst* (18) = M.

1.7 Access Fees Returned on Execution Reports

The access fee or rebate associated with each fill is calculated to five decimal places and returned on each execution report. Negative numbers indicate liquidity rebates. Participants should program their systems to read, validate, and pass along this field in order to avoid making software changes to their systems when BATS' fee schedule changes. The sum of the access fees and rebates received during a month provide an indication to the access fees charged or rebated on the Participant's monthly bill. Hitting new volume tiers or subscribing to alternative fee schedules will mean that a Participant's monthly bill will differ.

Drop copy ports do not accept orders and send execution reports where *ExecType* (150) is Partially Filled (1) or Filled (2). Drop ports for sponsored access may be configured to also send execution reports where *ExecType* (150) is New (0), Canceled (4), or Replaced (5). Drop copy ports may be configured to send various combinations of Participant and clearing identifiers.

1.8 Service Bureau Configuration

Service Bureaus require special configuration. *OnBehalfOfCompID* (115) must be set for Order, Cancel, and Cancel/Replace messages sent to BATS. Orders with an unknown *OnBehalfOfCompID* (115) will be rejected. *ClOrdID* (11) values are required to be unique only within a given *OnBehalfOfCompID* (115). Execution Reports, Cancel Rejects and trade capture related messages sent by BATS will have the *DeliverToCompID* (128) set. **Orders must be canceled or replaced using the same *OnBehalfOfCompID* (115) as was sent on the original order.**

1.9 Order Price Collars

BATS uses market data from the primary exchange for each symbol. This primary best bid and offer (PBBO) is used to create an order price collar. Executions will not be allowed to occur a set percentage above the PBBO best ask quote or a set percentage below the PBBO best bid quote. If an order matches against a resting order, but is outside the price collar, the incoming order will be rejected with reason "price exceeds cross range".

If the primary exchange is not in continuous trading (e.g., is in auction or has closed), the order price collar will be a percentage of the last regular on-book trade price on the primary exchange. If there has not yet been a trade on the primary exchange today, then no collar is in effect.

The percentage value(s) used for order price collars is/are defined in the Participant Manual.

1.10 Reserve (Iceberg) Orders

BATS allows the use of *MaxFloor* (111) for entering reserve (iceberg) orders. On reload, BATS' market data feeds show a new OrderID in order to hide the fact that the order is a reserve order.

A port- or firm-level attribute may be enabled which will cause an execution report with *ExecType* (150) = `D` (Restated) to be sent each time an order is reloaded, specifying the new OrderID as will be seen on the market data feeds in *SecondaryOrderID* (198).

The *OrderID* (37) remains constant for the lifetime of the order. Only the *SecondaryOrderID* (198) will change.

Here is a timeline showing an order and its OrderIDs as seen by the Participant and the market data feeds.

#	***OrderID* (37)**	***SecondaryOrderID* (198)**	**Displayed Order ID**	**Notes**
1	`1C3M03000008`	—	`1C3M03000008`	Initial order entry.
2	`1C3M03000008`	`1C3M0300000E`	`1C3M0300000E`	Order reloaded.
3	`1C3M03000008`	`1C3M0300000Q`	`1C3M0300000Q`	Order reloaded again.

1.11 Peg Order Pricing

Pegged orders are priced using the primary best bid and offer (PBBO). If the primary exchange is not in continuous trading (e.g., is in auction or is not currently open), resting pegged orders are temporarily suspended from trading. They will become executable again as soon as the primary exchange is back in continuous trading. Newly entered pegged orders will go into a suspended state immediately.

1.12 Routing (Parallel-D and Parallel-2D)

Orders marked with an appropriate *RoutingInst* (9303) [3] will be eligible for routing to other market centers if BATS does not offer an equal or better price. Executions for routed orders may be trade reported on the market where the execution occurred and not necessarily on the BATS market data feeds. Notification of each routed execution at another market will be sent to the Participant FIX handler which submitted the routed order.

In the event that another market offers a better price, but BATS' connectivity to that market is down and the market in question is otherwise functioning properly, orders which would route to a better quote on that market (but cannot) will be canceled back.

If a market with a better quote is experiencing technical difficulties, BATS may, at its discretion, cease routing to that market and allow orders to post on the BATS book.

Routable orders can route to displayed venues and liquidity partners[4]. BATS will only route to a market if it is in normal, electronic trading. BATS will not route to a primary exchange's auction.

The routing order types and the markets which BATS routes to are subject to change; contact the Trade Desk or your Account Manager for details.

1.13 BATS Plus

Orders marked *RoutingInst* (9303) = `Y`, will be eligible for routing to a single, specified destination.

The resultant trade reporting, market data and FIX excecution reports detail will be the same as for Routable (1.12). Other market centres will not be considered, even if they offer a better price than BATS or the specified destination.

Some Primary exchanges may not be available with BATS Plus Primary[5]. Contact the Trade Desk or your Account Manager for details.

1.14 BATS DRTOnly

Orders marked *RoutingInst* (9303) = `L`, will be eligible for routing to selected liquidity partners after exhausting liquidity on the BATS books.

1.15 Interbook Order Types

Dark Sweep and Lit Sweep are interbook order types designed to be a simple solution for multi-book access between BXE and CXE.

Orders marked *RoutingInst* (9303) = `U` will be eligible for dark book sweeping. Dark Sweep orders are first sent to the dark book associated with the book of entry before moving on to the other book if there is a partial execution.

Orders marked *RoutingInst* (9303) = `W` will be eligible for lit book sweeping. Lit Sweep orders are sent to the lit book with the best price available. Orders work between books and associated price levels. In the

[3] 1st character of *RoutingInst* (9303) is `R` (Smart Routing)
[4] See *ExecInst* (18) = `u, v and w` for details.
[5] *RoutingInst* (9303) = `Y`

event that the same price is available on both order books, the order will be sent to the book of entry first.

Orders marked *RoutingInst* (9303) = `X` will be eligible for sequential lit book sweeping. The order executes on the book of entry up to the order limit, any residual is sent to the other book and continues to be filled up to the limit. Any un-filled portion is cancelled back or posted on the book of entry.

1.16 Dark Lit Orders

Orders marked *RoutingInst* (9303) = `u`[6] will match on both the lit and dark books on a price/priority basis. Any residual quantity will rest on the lit book (for limit orders) or be cancelled (immediate or cancel orders). There may be limitations as to the markets supported; refer to the Participant Manual or contact the BATS Trade Desk for details.

1.17 Account Field

This field can carry two pieces of information.

Firstly a Central Counterparty (CCP) Account Type prefix.

If this field begins with **H:**, allocate to the house account at the CCP.

If this field begins with **C:**, allocate to the client account at the CCP.

When not prefixed, the *OrderCapacity* (47) is used to determine which CCP account to use. If needed, this can be overridden with explicit configuration by BATS. Non-prefixed or absent accounts would be allocated to *House* account. All CCPs support this feature.

Secondly is a trading account name/number.

With configuration, this can passed to CCPs which support this feature (LCH.Clearnet currently does not). This part must be 16 characters or less. The trading account is configurably available via Drop.

[6] See *RoutingInst* (9303) = `u` for details.

2 BATS Chi-X Europe Specific FIX Fields

The following FIX fields are specific to BATS Chi-X Europe:

Tag	Name	Description
6655	*CorrectedSize*	UCC trade correction message, this holds the corrected size.
7570	*RptTime*	Indicates the time at which a deferred trade report will be automatically published. Where *RptTime* falls outside of the systems operating time, the report will be published during operating hours on the next trading day. When no deferral is requested, or when the trade does not qualify for a deferral, any time returned will match *TransactTime* (60).
7772	*CentralCounterparty*	Only present on trades. The CCP handling the trade: EMCF = European Multilateral Clearing Facility LCHL = LCH.Clearnet XCLR = SIX x-clear ECCP = EuroCCP NONE = Clearing Suppressed for self match. Returned on trades if the participant has selected a Preferred CCP. The FIX port can be configured to always return this optional field.
7928	*PreventParticipant Match*	Participant Trade Prevention: 3 characters (not space separated): 1st character - PTP Modifier: `N` = Cancel Newest `O` = Cancel Oldest `B` = Cancel Both `D` = Decrement Larger[7] / Cancel Smaller `d` = Same as `D` above, but only decrement *LeavesQty* (151). Do not restate *OrderQty* (38). 2nd character - Unique ID Level: `F` = Prevent Match at Participant Level `M` = Prevent Match at Trading Firm Level `P` = Prevent Match at Port Owner Level 3rd character - Trading Group ID (optional): Member specified alphanumeric value 0-9, A-Z, or a-z. The Unique ID level (character 2) of both orders must match to prevent a trade. If specified on both orders, Trading Group ID (character 3) must match to prevent a trade. The PTP Modifier (character 1) of the inbound order will be honored, except that if the inbound order specified Decrement and the resting order does not, and the resting order is larger, then both orders will be canceled. This exception is to protect the order entry software for the resting order from receiving an unexpected restatement message.

[7] Users of PTP modifier `D` must be prepared to receive a FIX Restatement execution report (*ExecType* (150) = `D`) that includes both *OrderQty* (38) and *LeavesQty* (151).

9303	*RoutingInst*	**BATS Only** orders – up-to 2 characters (not space separated): `B` = BATS Only ***(default)*** `P` = BATS Only — Post Only (will reject rather than remove visible liquidity) `Q` = BATS Only — Post Only At Limit (remove shares that **improve** upon limit price and up to *MaxRemovePct* (9618) of remaining *OrderQty* (38) **at** limit price) `U` = Dark Sweep (interbook) `u` = Dark Lit Sweep (best-price) `W` = Lit Sweep (interbook, best-price) `X` = Lit Sweep (interbook, sequential) `BD` = BATS Dark Book Only (hidden midpoint peg orders only) `BA` = BATS Automatic Dark Routed (routes to BATS Integrated Book if order is Large In Scale (LIS) or is not a midpoint order, otherwise routes midpoint non-LIS orders to BATS Dark Book) `BP` = BATS Periodic Auction Book Post Only does not mix with *TimeInForce* (59) = `3` (IOC). If a *RoutingInst* is not specified a default value of `B` is implied (BATS Only). *continued...*

9303 (cont.)	*RoutingInst* (cont.)	**Order Routing** – up-to 4 characters (not space separated): 1st character - Specifies the target destination: `R` = Smart Route to visible markets (see 3rd character) `L` = BATS+ DRTOnly [8] `Y` = BATS+ Primary Listing Exchange [9] 2nd character - Used to enable/disable Re-Route On Lock/Cross: `N` = Do not Re-Route ***(default)*** `C` = Re-Route only if another market **crosses** the limit `L` = Re-Route only if another market **locks or crosses** the limit 3rd character - Specifies the routing strategy: `N` = Use default strategy ***(default)*** `D` = Parallel-D `2` = Parallel-2D 4th character - Specifies the resting book: `I` = Rest on BATS Integrated Book ***(default)*** `D` = Rest on BATS Dark Book Resting Book does not mix with *TimeInForce* (59) = `3` (IOC). In order to specify values for the 2nd , 3rd and/or 4th character the prior characters MUST be populated with a valid value. ASCII NULs (0x00) in the 2nd , 3rd or 4th character positions will imply the default value from their respective position. For example, if *RoutingInst* (9303) = `R` a value of `RNNI` is implied (All visible markets/No re-route/Default strategy/Rest on integrated book). BATS Plus Primary and DRTOnly directed order types do not allow re-routing or strategy selection. The 2nd and 3rd characters should always be set to their default value of `N` if the optional 4th character is used to rest on the dark book e.g. `LNND`. If the 1st character is `R` (Smart Routing) the *ExecInst* (18) can be used to provide limited control over external venue selection. [10] Re-route is not currently supported for dark resting orders (4th = `D`). As the default RoutingInst value is subject to change with little or no notice it is recommended you specify values for all 4 character positions if you wish to maintain maximum control of your routing decisions. *For more information regarding the various routing strategies available on BATS refer to* `http://www.batstrading.co.uk/features/`
9479	*DisplayIndicator*	`X` = Displayed Order (default) `I` = Invisible Invisible orders must meet the MiFID CESR requirements for Large in Scale (LIS) unless routed to the BATS Dark Book.

[8] *RoutingInst* (9303) = `PL` is *deprecated* but still valid
[9] *RoutingInst* (9303) = `PP` is *deprecated* but still valid
[10] see *ExecInst* (18) = `u, v or w`

9617	*ModifySequence*	**Drop only.** Base 36 number of times order has been replaced.
9618	*MaxRemovePct*	For Post Only At Limit (*RoutingInst* (9303) = `Q`), what percentage of the order quantity which remains after price improvement may be removed at the limit price.
9619	*CancelOrigOnReject*	`N` = Leave original order alone (default) `Y` = Cancel original order if replacement fails Default may be configured per port.
9620	*CorrectedPrice*	UCC trade correction message, this holds the corrected price.
9621	*MTFAccessFee*	Only present on trades. Indication of access fee for this fill (up to five decimal places, negative for rebates).
9688	*OrigCompID*	**Drop only.** *TargetCompID* (56) of original FIX execution report. Drop port must be configured to send this optional field.
9689	*OrigSubID*	**Drop only.** *TargetSubID* (57) of original FIX execution report. Drop port must be configured to send this optional field.
9730	*TradeLiquidity Indicator*	Only present on trades. `A` = Added Liquidity `R` = Removed Liquidity `AD` = Added Liquidity for the BATS Dark Pool `RD` = Removed Liquidity from the BATS Dark Pool `RT` = Removed Liquidity from the BATS Dark Pool by IOC order `AI` = Added Hidden Liquidity that was price improved `AK` = Added Liquidity from the hidden (reserve) portion of an iceberg order `X` = Routed to Another Market `C` = Auction `P` = Periodic Auction To allow for future expansion of this field, please ignore values with an unknown character in the 2nd position.

3 FIX Session Protocol

BATS uses the FIX 4.2 session protocol. FIX 4.4 is possible should the firm dedicate the port for trade reporting purposes. The Participant will be provided with a *SenderCompID* (49) and *SenderSubID* (50) that must be sent on every message. The *TargetCompID* (56) for all messages the Participant sends will be `BATS` on BXE ports, or `CHIX` on CXE sessions. The *TargetSubID* (57) is `TEST` for the BATS test system and `PROD` for the BATS production system. All messages the Participant receives will have the sender and target fields swapped, as per the FIX specification.

The following session messages are supported in both directions:

Message	Type	Comment
Logon	`A`	Begin session (or resume a broken session)
Heartbeat	`0`	
Test Request	`1`	
Resend Request	`2`	
Reject	`3`	Malformed message or improper session level handling
Sequence Reset	`4`	Both Gap Fill (*GapFillFlag* (123) = `Y`) and Reset
Logout	`5`	used to gracefully close session

3.1 Sequence Numbers

Sequence numbers, both inbound and outbound, will be reset to one each night during the down time.

Messages are processed in sequence order. Behind sequence messages (other than Sequence Reset — Reset) cause immediate logout. Ahead of sequence messages (other than a Resend Request) trigger a message recovery via a Resend Request.

3.2 Logon

The logon must be the first message sent by the Participant after the TCP connection is established. *EncryptMethod* (98) is ignored (FIX level encryption is not supported).

The IP address of the Participant, the *SenderCompID* (49), *SenderSubID* (50), *TargetCompID* (56) (`BATS` or `CHIX`) and *TargetSubID* (57) (`TEST` or `PROD`) will be validated. If validation fails, the connection will be dropped without a reject (to avoid corrupting the Participant's sequence in the case that the Participant merely mistakenly connected to the wrong port).

If the connection is unexpectedly broken, upon reconnection, the Participant may receive a login reply with a sequence number greater than expected. This means that in-flight messages were missed (likely important execution reports). The Participant should issue a Resend request to retrieve the missed messages.

Similarly, BATS will issue a Resend Request to the Participant for messages that it missed. The Participant may wish to send gap fill messages in place of new orders to avoid submission of potentially stale orders.

HeartBtInt (108) must be specified by the Participant in the Logon message. This value will be clamped between five and 300 seconds and returned in the Logon reply message. We recommend using as low a value as the reliability and latency of your telecommunications channel will allow.

3.3 Heartbeat

A Heartbeat message should be sent if the agreed upon *HeartBtInt* (108) has elapsed since the last message sent. If any message has been sent during the preceding *HeartBtInt* (108), a Heartbeat message need not be sent.

3.4 Test Request

If *HeartBtInt* + 1 seconds have elapsed since the last message received, a Test Request should be issued. If another *HeartBtInt* + 1 seconds go by without receiving a message, the TCP connection should be dropped. This ensures that a broken TCP connection will be detected even if the TCP stack doesn't notice (this has been observed to happen in WAN environments, particularly when a VPN is involved).

3.5 Resend Request

A Resend Request message should be processed even if it is received ahead of sequence. Only after resending the requested range (all marked *PossDup* (43) = `Y`), including any gap fills) should Resend Request be issued in the opposite direction.

As discussed in the FIX 4.2 specification, it is possible to send an open or closed sequence range in a Resend Request (an open range uses sequence zero as the *EndSeqNo* (16)). BATS will honor either type of request, but will always issue Resend Requests with a closed sequence range.

3.6 Reject

Session level rejects (*MsgType* (35) = `3`) are used to indicate violations of the session protocol, or missing (or mangled) fields. These are to be expected during development and certification while the Participant's systems are being adapted for BATS, but should be extremely rare in production. Application layer rejects (like Order Reject and Cancel Reject) are normal and should be handled separately. See FIX Application Messages - BATS to Participant (p. 29) for more details.

3.7 Sequence Reset

Sequence Reset — Gap Fill messages (*GapFillFlag* (123) = `Y`) must be received in sequence. Any messages (including Gap Fills) sent in response to a Resend Request should have *PossDup* (43) = `Y`.

Sequence Reset — Reset (*GapFillFlag* (123) ≠ `Y`) is used only as a last resort, and always by human intervention, to allow an otherwise hopelessly confused session to be resumed. In these cases, all chances at automatic message recovery are lost.

3.8 Logout

Either side may issue a logout to gracefully close the session. The side that issues the logout should process messages normally until it sees the logout reply, and then break the TCP connection. BATS will typically only request logout after the scheduled end of FIX session.

4 Standard FIX Message Header and Trailer

4.1 Header

Tag	Name	Description
8	*BeginString*	`FIX.4.2` or `FIX.4.4` Must be the first field in the message. FIX 4.4 only available if the port is dedicated for trade reporting purposes.
9	*BodyLength*	Length of message following *BodyLength* field up to and including the delimiter preceding the *CheckSum* (10) field. Must be the second field in the message.
35	*MsgType*	Must be the third field in the message.
34	*MsgSeqNum*	Sequential sequence number for the session.
43	*PossDupFlag*	Indicates a message resent from the admin level (has a duplicate sequence number). Defaults to `N`.
49	*SenderCompID*	ID of sender. Assigned by BATS for messages sent to BATS. (*TargetCompID* (56) for messages from BATS.)
52	*SendingTime*	GMT date and time that message was sent. If enabled at the port or firm level, timestamps will be sent with microsecond resolution.
56	*TargetCompID*	ID of destination. `BATS` for messages sent to BXE (BATS) ports. `CHIX` for messages sent to CXE (Chi-X) ports. (*SenderCompID* (49) for messages from BATS.)
57	*TargetSubID*	Sub ID of destination. `TEST` for messages sent to the BATS test system. `PROD` for messages sent to the BATS production system. (*SenderSubID* (50) for messages from BATS.)
97	*PossResend*	Possible resend flag. BATS has special handling for the *PossResend* for New Order Single messages. See New Order — Single below.
115	*OnBehalfOfCompID*	Service bureau use. Identifies end-client on messages **to** BATS. Must be identifier known to BATS. May be used by non-service bureau to specify which clearing arrangement to use if multiple are configured.
116	*OnBehalfOfSubID*	End-client sub identifier. Four characters, alphanumeric, otherwise not validated. Recorded and returned in *DeliverToSubID* (129). Available via Drop.
122	*OrigSendingTime*	For messages with *PossDupFlag* (43) = `Y`, indicates time that message was first sent. If enabled at the port or firm level, timestamps will be sent with microsecond resolution.
128	*DeliverToCompID*	Service bureau use. Identifies end-client on message **from** BATS. Must be BATS approved identifier.
129	*DeliverToSubID*	Returns *OnBehalfOfSubID* (116) optionally sent by client.

4.2 Trailer

Tag	Name	Description
10	*CheckSum*	Modulo 256 checksum of all characters in the message up to and including the delimiter preceding the *CheckSum* field. Three digits with leading zeroes if necessary.

5 FIX Application Messages — Participant to BATS

5.1 New Order — Single

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `D`
97	*PossResend*	`N` = indicates a new order (default) `Y` = indicates an application level resend and **is not supported** For reasons of economy, BATS does not track (in primary storage), the *ClOrdID* (11) values of orders that are no longer live. For reasons of performance, BATS does not access secondary storage to enforce unique *ClOrdID* (11) values against orders that are no longer live. Without full duplicate *ClOrdID* (11) value enforcement, it is not possible to safely implement the full behavior specified in the FIX 4.2 protocol for *PossResend* = `Y`. To remain economical, fast, *and* safe, all New Order — Single messages with *PossResend* = `Y` will be simply ignored.
1	*Account*	Optional. Returned on execution reports associated with this order. 16 characters or less (ASCII 33–126). **H:** and **C:** prefix can be used to specify which CCP Account to use. **If configured by BATS**: *House* or *Client* CCP account can be defaulted, regardless of *OrderCapacity* (47). Also the value supplied can be passed to the CCP and made available on the Drop feed.
11	*ClOrdID*	Day-unique ID chosen by client. 20 characters or less. Characters in ASCII range 33–126 are allowed, except for comma, semicolon, and pipe. If the *ClOrdID* matches a live order, it will be rejected as duplicate (unless *PossResend* (97) = `Y`; see above). **Note: BATS only enforces the uniqueness of *ClOrdID* values among currently live orders. However, we *strongly* recommend that you keep your ClOrdID values day unique.**
15	*Currency*	Required if *IDSource* (22) = `4` (ISIN). If *Currency* (15) is included when other symbology is used, it must match the currency expected by BATS for the given symbol.

18	*ExecInst*	**Single value only (with no trailing space).** P = Market Peg (peg buy to PBBO offer, peg sell to PBBO bid) R = Primary Peg (peg buy to PBBO bid, peg sell to PBBO offer) M = Midpoint (peg to PBBO midpoint) L = Alternate Midpoint (less aggressive of midpoint and 1 tick inside PBBO) for Periodic Auction Orders:[11] M = Midpoint (peg to BATS EBBO midpoint) G = Guarded Midpoint (peg to BATS EBBO midpoint but suspend order if primary market quote becomes one-sided or disappears) for Smart Order Routing: u = BATS + External Dark Only v = BATS + External Dark + Lit (default for routable orders) w = BATS + External Lit Only **NOTE: Values L and G differ in meaning from standard FIX 4.2.** All other values are ignored. Midpoint pegged orders (M and L) are implicitly hidden (*DisplayIndicator* (9479) = I).
22	*IDSource*	Values supported by BATS: 4 = ISIN 5 = RIC Required if *Symbol* (55) is not set.
38	*OrderQty*	Number of shares for the order. System-wide limit is 99,999,999 shares.
40	*OrdType*	1 = Market 2 = Limit P = Pegged During continuous trading Market (1) implies *TimeInForce* (59) = 3 (IOC). Pegged requires *ExecInst* (18) = L, M, P, or R. Pegged orders may not be routable.
44	*Price*	Limit price.
47	*OrderCapacity*	A = Agency P = Principal (default) R = Riskless
48	*SecurityID*	ISIN, or RIC if *IDSource* (22) is set.
54	*Side*	1 = Buy 2 = Sell
55	*Symbol*	Security symbol. See Symbology (p. 4) for additional notes.

[11] *RoutingInst* (9303)=BP

59	*TimeInForce*	`0` = Day `1` = GTC (allowed, but treated as Day) `2` = AtTheOpen `3` = IOC `6` = GTD (expires at earlier of specified *ExpireTime* (126) or end of day) `7` = AtTheClose `8` = Good For Auction (only valid if *RoutingInst* (9303) = BP)
60	*TransactTime*	Time order initiated/released. Required by FIX 4.2 but not used by BATS.
110	*MinQty*	**Optional** minimum[12] fill quantity for BATS Only hidden, BATS Dark Pool or IOC orders. **Ignored** if order is not BATS Only hidden, BATS Dark Pool, or IOC. **Default** is zero.
111	*MaxFloor*	Portion of *OrderQty* (38) to display. The balance is reserve. `0` displays entire quantity (default). The displayed quantity of each order at a price level is decremented first. When displayed quantity is fully decremented, it is reloaded up to *MaxFloor* from reserve. May opt-in at the firm or port level to receive a restatement execution report on each reserve reload, allowing a Participant to know the new OrderID as represented on BATS' market data feeds.
126	*ExpireTime*	Required for *TimeInForce* (59) = `6` (GTD) orders, specifies the date and time (in GMT) that the order expires.
207	*SecurityExchange*	Required when *IDSource* (22) = `4` (ISIN).
211	*PegDifference*	**Optional signed** value up to four decimal places[13] is **added** to the result of peg calculation. Default is `0`. Must be ≥ 0 for sell orders. Must be ≤ 0 for buy orders. Must be zero (or not specified) for midpoint peg or non-pegged orders.
439	*ClearingFirm*	Firm that will clear trade. Optional. Note: shares storage with *OnBehalfOfCompID* (115). If both fields are set, they must be equal.
440	*ClearingAccount*	Supplemental identifier. Optional. Recorded and returned in execution reports. Available via Drop. Note: shares storage with *OnBehalfOfSubID* (116). If both fields are set, then *OnBehalfOfSubID* (116) takes precedence for Service Bureau connections and *ClearingAccount* takes precedence for other connections.

[12] Once resting all fills will exceed the minimum. On entry and user modification, the behaviour is configurable on the port and can apply to the **total** fill size, which may be made up of several **consecutive** smaller fills.

[13] *PegDifference* is rounded (down for buy, up for sell) to fit the tick size.

7928	*PreventParticipant Match*	Participant Trade Prevention: 3 characters (not space separated): 1st character - PTP Modifier: `N` = Cancel Newest `O` = Cancel Oldest `B` = Cancel Both `D` = Decrement Larger[14] / Cancel Smaller `d` = Same as `D` above, but only decrement *LeavesQty* (151). Do not restate *OrderQty* (38). 2nd character - Unique ID Level: `F` = Prevent Match at Participant Level `M` = Prevent Match at Trading Firm Level `P` = Prevent Match at Port Owner Level 3rd character - Trading Group ID (optional): Member specified alphanumeric value 0-9, A-Z, or a-z. The Unique ID level (character 2) of both orders must match to prevent a trade. If specified on both orders, Trading Group ID (character 3) must match to prevent a trade. The PTP Modifier (character 1) of the inbound order will be honored, except that if the inbound order specified Decrement and the resting order does not, and the resting order is larger, then both orders will be canceled. This exception is to protect the order entry software for the resting order from receiving an unexpected restatement message.
9303	*RoutingInst*	**BATS Only** orders – up-to 2 characters (not space separated): `B` = BATS Only ***(default)*** `P` = BATS Only — Post Only (will reject rather than remove visible liquidity) `Q` = BATS Only — Post Only At Limit (remove shares that **improve** upon limit price and up to *MaxRemovePct* (9618) of remaining *OrderQty* (38) **at** limit price) `U` = Dark Sweep (interbook) `u` = Dark Lit Sweep (best-price) `W` = Lit Sweep (interbook, best-price) `X` = Lit Sweep (interbook, sequential) `BD` = BATS Dark Book Only (hidden midpoint peg orders only) `BA` = BATS Automatic Dark Routed (routes to BATS Integrated Book if order is Large In Scale (LIS) or is not a midpoint order, otherwise routes midpoint non-LIS orders to BATS Dark Book) `BP` = BATS Periodic Auction Book Post Only does not mix with *TimeInForce* (59) = `3` (IOC). If a *RoutingInst* is not specified a default value of `B` is implied (BATS Only). *continued...*

[14]Users of PTP modifier `D` must be prepared to receive a FIX Restatement execution report (*ExecType* (150) = `D`) that includes both *OrderQty* (38) and *LeavesQty* (151).

9303 (cont.)	*RoutingInst* (cont.)	**Order Routing** – up-to 4 characters (not space separated): 1st character - Specifies the target destination: `R` = Smart Route to visible markets (see 3rd character) `L` = BATS+ DRTOnly [15] `Y` = BATS+ Primary Listing Exchange [16] 2nd character - Used to enable/disable Re-Route On Lock/Cross: `N` = Do not Re-Route ***(default)*** `C` = Re-Route only if another market **crosses** the limit `L` = Re-Route only if another market **locks or crosses** the limit 3rd character - Specifies the routing strategy: `N` = Use default strategy ***(default)*** `D` = Parallel-D `2` = Parallel-2D 4th character - Specifies the resting book: `I` = Rest on BATS Integrated Book ***(default)*** `D` = Rest on BATS Dark Book Resting Book does not mix with *TimeInForce* (59) = `3` (IOC). In order to specify values for the 2nd , 3rd and/or 4th character the prior characters MUST be populated with a valid value. ASCII NULs (0x00) in the 2nd , 3rd or 4th character positions will imply the default value from their respective position. For example, if *RoutingInst* (9303) = `R` a value of `RNNI` is implied (All visible markets/No re-route/Default strategy/Rest on integrated book). BATS Plus Primary and DRTOnly directed order types do not allow re-routing or strategy selection. The 2nd and 3rd characters should always be set to their default value of `N` if the optional 4th character is used to rest on the dark book e.g. `LNND`. If the 1st character is `R` (Smart Routing) the *ExecInst* (18) can be used to provide limited control over external venue selection. [17] Re-route is not currently supported for dark resting orders (4th = `D`). As the default RoutingInst value is subject to change with little or no notice it is recommended you specify values for all 4 character positions if you wish to maintain maximum control of your routing decisions. *For more information regarding the various routing strategies available on BATS refer to* `http://www.batstrading.co.uk/features/`
9479	*DisplayIndicator*	`X` = Displayed Order (default) `I` = Invisible Invisible orders must meet the MiFID CESR requirements for Large in Scale (LIS) unless routed to the BATS Dark Book.

[15] *RoutingInst* (9303) = `PL` is *deprecated* but still valid
[16] *RoutingInst* (9303) = `PP` is *deprecated* but still valid
[17] see *ExecInst* (18) = `u, v or w`

9618	*MaxRemovePct*	For Post Only At Limit (*RoutingInst* (9303) = `Q`), what percentage of the order quantity which remains after price improvement may be removed at the limit price.
9688	*OrigCompID*	**Drop only.** *TargetCompID* (56) of original FIX execution report. Drop port must be configured to send this optional field.
9689	*OrigSubID*	**Drop only.** *TargetSubID* (57) of original FIX execution report. Drop port must be configured to send this optional field.
	Standard Message Trailer	

5.1.1 Notes on Pegged Orders

Midpoint pegged orders (*ExecInst* (18) = M or L) are implicitly hidden. Midpoint peg orders may execute between the minimum price increment of a stock, except for those stocks which are quoted at a 0.0001 increment. In that case, the peg price will be the less aggressive rounded price (rounded down for buys, rounded up for sells). Midpoint pegs may not use *PegDifference* (211).

Peg orders are prioritised behind non-pegged orders at each price and display level. With regard to hidden peg orders, regular peg orders (*ExecInst* (18) = R or P) have a higher priority than midpoint peg orders ranked at the same price.

Pegged orders will be automatically suspended from execution if BATS loses receipt of market data for any reason or if the primary exchange halts the symbol (including for non-regulatory reasons, such as a volatility interrupt).

5.2 Order Cancel Request

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `F`
97	*PossResend*	`N` = indicates a new cancel (default) `Y` = indicates an application level resend. If *ClOrdID* (11) has not yet been seen, the cancel is treated as normal. If *ClOrdID* (a)lready exists, the resent cancel is ignored.
1	*Account*	Optional. Reflected back on Pending Cancel Execution Report or Cancel Reject associated with this cancel. 16 characters of less (ASCII 33–126). Configurably available via Drop.
11	*ClOrdID*	Day-unique cancel ID chosen by client. 20 characters or less. Characters in ASCII range 33–126 are allowed, except for commma, semicolon, and pipe. Duplicate *ClOrdID*s will be rejected (or ignored if *PossResend* (97) = `Y`.
15	*Currency*	Required if *IDSource* (22) = `4` (ISIN). If *Currency* (15) is included when other symbology is used, it must match the currency expected by BATS for the given symbol.
22	*IDSource*	Values supported by BATS: `4` = ISIN `5` = RIC Required if *Symbol* (55) is not set.
37	*OrderID*	Order identifier supplied by BATS on the order acknowledgement. (Optional, but recommended for performance.)
38	*OrderQty*	Number of shares for the order. Must match original order.

41	*OrigClOrdID*	*ClOrdID* of the order to cancel.
48	*SecurityID*	ISIN, or RIC if *IDSource* (22) is set.
54	*Side*	`1` = Buy `2` = Sell
55	*Symbol*	Security symbol. See Symbology (p. 4) for additional notes.
60	*TransactTime*	Time cancel initiated/released. Required by FIX 4.2 but not used by BATS.
207	*SecurityExchange*	Required when *IDSource* (22) = `4` (ISIN).
	Standard Message Trailer	

5.3 Order Cancel/Replace Request

Only *Price* (44), *OrderQty* (38), and *OrdType* (40) may be adjusted. Any change in *Price* or increase in *OrderQty* will result in the order losing its time priority. *OrdType* may be adjusted from Limit to Market (but not from Limit to Peg or Peg to Limit).

Other fields (including *ExecInst* (18)) will be ignored, and the value from the original order will be reused.

Changes in *OrderQty* result in an adjustment of the current order's *OrderQty*. The new *OrderQty* does **not** directly replace the current order's *LeavesQty* (151). Rather, a delta is computed from the current *OrderQty* and the replacement *OrderQty*. This delta is then applied to the current *LeavesQty*. If the resulting *LeavesQty* is less than or equal to zero, the order is canceled. This results in safer behavior when the replace request overlaps partial fills for the current order, leaving the Participant in total control of the share exposure of the order.

MaxFloor (111) is preserved from the original order and applied to the new size.

A Cancel/Replace should not be issued until the acknowledgment for the previous Cancel/Replace has been received for that order (or the New Order acknowledgment for the first Cancel/Replace). The FIX handler will reject a new Cancel/Replace if it has not seen the prior Cancel/Replace from the Matching Engine.

Cancel/Replace requests that merely reduce *OrderQty* may be overlapped if the existing *ClOrdID* is reused, as long as the trading identifer has not been opted-in to daily limit trading risk controls. This is the only case where reuse of the existing *ClOrdID* is allowed.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `G`
97	*PossResend*	`N` = indicates a new cancel/replace (default) `Y` = indicates an application level resend. If the *ClOrdID* does not indicate an already pending cancel/replace, the cancel/replace is treated as normal. If *ClOrdID* does indicate an already pending cancel/replace, then the resent cancel/replace is ignored.
1	*Account*	Optional. Returned on execution reports associated with this order. 16 characters or less (ASCII 33–126). **H:** and **C:** prefix can be used to specify which CCP Account to use. **If configured by BATS**: *House* or *Client* CCP account can be defaulted, regardless of *OrderCapacity* (47). Also the value supplied can be passed to the CCP and made available on the Drop feed.

11	*ClOrdID*	Day-unique ID chosen by client. 20 characters or less. Characters in ASCII range 33–126 are allowed, except for comma, semicolon, and pipe. If the *ClOrdID* matches a live order, it will be rejected as duplicate (unless *PossResend* (97) = `Y`; see above). **Note: BATS only enforces the uniqueness of *ClOrdID* values among currently live orders. However, we *strongly* recommend that you keep your ClOrdID values day unique.**
15	*Currency*	Required if *IDSource* (22) = `4` (ISIN). If *Currency* (15) is included when other symbology is used, it must match the currency expected by BATS for the given symbol.
22	*IDSource*	Values supported by BATS: `4` = ISIN `5` = RIC Required if *Symbol* (55) is not set.
37	*OrderID*	Order identifier supplied by BATS on the order acknowledgement. In the case of multiple changes to a single order, this should be the *OrderID* from the most recent acknowledgement.
38	*OrderQty*	Number of shares for the order. This will modify the *OrderQty* of the current order, it does **not** directly set the remaining quantity.
40	*OrdType*	`1` = Market `2` = Limit `P` = Pegged During continuous trading Market (`1`) implies *TimeInForce* (59) = `3` (IOC). Pegged requires *ExecInst* (18) = `L`, `M`, `P`, or `R`. Pegged orders may not be routable.
41	*OrigClOrdID*	*ClOrdID* of the order to replace. In the case of multiple changes to a single order, this will be the *ClOrdID* of the most recently accepted change.
44	*Price*	Limit price.
48	*SecurityID*	ISIN, or RIC if *IDSource* (22) is set.
54	*Side*	`1` = Buy `2` = Sell
55	*Symbol*	Security symbol. See Symbology (p. 4) for additional notes.
60	*TransactTime*	Time cancel/replace initiated/released. Required by FIX 4.2 but not used by BATS.
207	*SecurityExchange*	Required when *IDSource* (22) = `4` (ISIN).
9619	*CancelOrigOnReject*	`N` = Leave original order alone (default) `Y` = Cancel original order if replacement fails Default may be configured per port.
	Standard Message Trailer	

5.4 Trade Capture Report

The Trade Capture Report is used to submit a Negotiated Trade. The report must contain both sides of the trade (*NoSides* (552) = 2).

The models supported are as described in the FIX 5.0 (SP2) specification in the *Two-Party Reporting*, *One-Party Report for Matching* and *Confirmed Trade Reporting* workflow diagrams of the Trade Capture Reporting section.

Whilst we make use of FIX 4.4 and FIX 5.0 messages/tags, these are handled as extensions and operate over a FIX 4.2 session. If a port is dedicated to the use of trade reporting, there is an option to utilise a FIX 4.4 session.

When a new trade report is accepted, a *TradeID* is returned in the corresponding Trade Capture Report confirmation messages. Where applicable, such trade reports may be cancelled, amended or released by specifying the *TradeID*.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `AE`
15	*Currency*	Required if *IDSource* (22) = `4` (ISIN). If *Currency* (15) is included when other symbology is used, it must match the currency expected by BATS for the given symbol.
18	*ExecInst*	Optional. Single value only (with no trailing space). The only valid value is: `M` = Midpoint (peg to midpoint of local book only) If set the *LastPx* is optional and is ignored. May not be used if specifying *TransactTime*.
22	*IDSource*	Values supported by BATS: `4` = ISIN `5` = RIC Required if *Symbol* (55) is not set.
31	*LastPx*	Price of this fill (zero for non-fills). May be excluded if using *GrossTradeAmt*.
32	*LastShares*	Quantity of shares traded on this fill (zero for non-fills).
48	*SecurityID*	ISIN, or RIC if *IDSource* (22) is set.
55	*Symbol*	Security symbol. See Symbology (p. 4) for additional notes.
60	*TransactTime*	Optional. Specifies the time at which the trade was arranged.
63	*SettlType*	Optional. Indicates settlement period. If present, *SettlDate* (64) overrides this field. If *SettlType* (63) = `6`, then *SettlDate* (64) is required. If both *SettlType* (63) and *SettlDate* (64) are omitted, the default value is `0` (Regular). Supported values: `0` = Regular (default) `6` = Future This field may not be amended.

64	*SettlDate*	Optional. Specifies the date on which the trade is desired to settle. If present, this field overrides *SettlType* (63). This field is required if the value of *SettlType* (63) = `6` (Future). This field may not be amended using our standard interface, but the actual settlement date may be varied by the central counterparties (CCPs) due to operational requirements (eg. for symbols in a conditional trading status).
75	*TradeDate*	Optional. Specifies the date on which the trade was arranged. If present, must be the current date and must must match the date component of *TransactTime* (60).
150	*ExecType*	Must be `F` = Trade
207	*SecurityExchange*	Required when *IDSource* (22) = `4` (ISIN).
381	*GrossTradeAmt*	Total amount traded, expressed in units of currency. Only considered when *LastPx* is not specified.
487	*TradeReportTransType*	Specifies whether this trade report is new, a cancellation, an amendment or a release. Unilateral trades reported under the service may be cancelled or amended by the participant. Trades that are currently being delayed from publication can be released for immediate publication. Defaults to 'new' if unspecified. `0` = New `1` = Cancel `2` = Replace `3` = Release
571	*TradeReportID*	Day-unique ID chosen by client. 20 characters or less. Characters in ASCII range 33–126 are allowed, except for comma, semicolon, and pipe. If the *TradeReportID* matches a live trade report (one that has been acked, but not confirmed or declined), it will be rejected as duplicate. **Note: BATS only enforces the uniqueness of *TradeReportID* values among currently live trade reports. However, we *strongly* recommend that you keep your TradeReportID values day unique.**
572	*TradeReportRefID*	Contains the *TradeReportRefID* (572) of the trade capture report ack that should now be withdrawn
574	*MatchType*	Where *VenueType* (1430) = `0` (off book), this field models the MMT Level 2 'Trading Mode' field, and must be `3` = Trade Reporting (On-Exchange).
730	*SettlPrice*	Optional. Price at which the price should settle at. If specified, any risk controls will be applied against this price. This field may not be amended.
820	*TradeLinkID*	Third Party Trade Identifier used for optional matching with counterparty. 30 characters or less. Characters in ASCII range 33–126 are allowed, except for comma, semicolon, and pipe.

828	*TrdType*	This field corresponds to the MMT Level 3.1 field 'Transaction Category'. `0` = Regular Trade (aka Plain-Vanilla Trade) `30` = Special price (aka Trade with Conditions) `61` = Give-up / Give-in trade `62` = Dark Trade `63` = Technical Trade
829	*TrdSubType*	This optional field corresponds to the MMT Level 3.3 field 'Crossing Trade Indicator'. Agency Cross trades may be indicated by setting *TrdSubType* (829) = `37`. Other values are invalid.
855	*SecondaryTrdType*	This optional field corresponds to the MMT Level 3.5 field 'Benchmark Indicator'. Benchmark trades may be indicated by setting *SecondaryTrdType* (855) = `64`. Other values are invalid.
856	*TradeReportType*	This field controls pending state of the trade report. `0` = (Submit) for all new trade reports `6` = (Trade Report Cancel) to cancel any acknowledged, but not confirmed trade reports entered where *TradeHandlingInst* (1123) = `2`
1003	*TradeID*	Used to specify a previously reported trade to be amended or cancelled. Mandatory when *TradeReportTransType* (487) = `1, 2 or 3`, must be absent when *TradeReportTransType* (487) = `0`.
1115	*OrderCategory*	This field corresponds to the MMT Level 3.2 field 'Negotiated Transaction Indicator', and is used by the participant to indicate that the trade was a Negotiated Transaction as per the BATS Rules. For all trade reports reported on-exchange, the value must be `3`. `3` = Privately Negotiated Trade
1116	*NoRootPartyIDs*	When *TradeHandlingInst* (1123) = `0`, must always be `1`
1117	*RootPartyID*	When *TradeHandlingInst* (1123) = `0`, the third party responsible for submitting the pre-matched trade. Must be an identifier (4 uppercase letters) known to BATS.
1118	*RootPartyIDSource*	When *TradeHandlingInst* (1123) = `0`, must always be `D` (Proprietary / Custom Code)
1119	*RootPartyRole*	When *TradeHandlingInst* (1123) = `0`, specifies the role of the third party to the trade. At this time, only the following values are valid: `6` = IntroducingFirm
1123	*TradeHandlingInstr*	Used to specify the trade reporting model used. `0` (Confirmed Trade) `1` (Two-Party Report) `2` (One Party Report for Matching)

1390	*TradePublishIndicator*	This field corresponds to the MMT Level 4 field 'Publication Mode', and is used by the participant to request that the publication be delayed. It is ignored if the trade does not qualify for delayed publication. This field may not be amended, however trades currently being delayed may be released prior to their maximum delay duration using *TradeReportTransType* (487) = `3`. Supported values: `0` = Do Not Publish `1` = Publish trade (immediately) `2` = Deferred Publication When using *TradeHandlingInstr* (1123) = `2`, the only acceptable value is *TradePublishIndicator* (1390) = `0`.
1430	*VenueType*	Must be `O` = Off Book. This field models the MMT Level 1 field 'Market Mechanism'.
1838	*NoTradePriceConditions*	Optional. If present, must have the value 1, and indicates the presence of a single *TradePriceCondition* (1839) field.
1839	*TradePriceCondition*	Optional. Used to indicate that the ex/cum dividend state of the trade. This field corresponds to the MMT Level 3.6 'Ex/Cum Dividend Indicator'. Supported values are: `0` = Cum Dividend `2` = Ex Dividend
2405	*ExecMethod*	Optional. Used to indicate that the method by which the trade was executed. This field corresponds to the proposed MMT Level 3.7 'Offbook Automated Liquidity Indicator'. The following values are supported: `0` = Unspecified (default) `1` = Manual `2` = Automated
9128	*Tolerance*	Maximum allowed delta (in terms of consideration, expressed in the traded currency), that the trade is prepared to match against counterparty.
552	*NoSides*	Must always be `2`

Repeating Group *TrdCapRptSideGrp* must occur the number of times specified in *NoSides* (552)

54	*Side*	Must be first field in repeating-group `1` = Buy `2` = Sell
1	*Account*	Optional. Reflected back on Trade Capture Report confirmed and declined messages. **H:** and **C:** prefix can be used to specify which CCP Account to use. 16 characters of less (ASCII 33–126).
453	*NoPartyIDs*	Must always be `1`
448	*PartyID*	The end-client responsible for the trade. Must be an identifier (4 uppercase letters) known to BATS.
447	*PartyIDSource*	Must always be `D` (Proprietary / Custom Code)
452	*PartyRole*	Specifies the role of the party to the trade. At this time, only the following values are valid: `1` = ExecutingFirm (if used, must be set on both sides. Is not permitted for bilateral trades, except for Trade Confirmations) `7` = EnteringFirm (the party reporting the trade. Should not be used in the second leg) `17` = ContraFirm (the party the trade is alleged against)
528	*OrderCapacity*	Optional. `A` = Agency `P` = Principal (default) `R` = Riskless
625	*TradingSessionSubID*	This field must not be supplied on trade reports to BATS. This field models the MMT Level 2 'Trading Mode' field for scenarios where *VenueType* (1430) is not '`O`' (off book), which is not permitted.

	Standard Message Trailer	

6 FIX Application Messages — BATS to Participant

6.1 Execution Report

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `8`
1	*Account*	Copied from order, if present. (Available on Drop via optional port configuration)
6	*AvgPx*	Average fill price.
11	*ClOrdID*	*ClOrdID* of the order being accepted, executed, or rejected. –or– *ClOrdID* of the cancel or replace **request**. –or– *ClOrdID* of the order subject to unsolicited cancel (*OrigClOrdID* (41) will not be present).
14	*CumQty*	Cumulative quantity of shares executed for this order.
15	*Currency*	Copied from order, if present.
17	*ExecID*	Day-unique ID of execution message.
18	*ExecInst*	Copied from order, if present.
20	*ExecTransType*	`0` = New
22	*IDSource*	Copied from order, if present.
30	*LastMkt*	Segment MIC of this fill, if the port is configured to send this tag.
31	*LastPx*	Price of this fill (zero for non-fills).
32	*LastShares*	Quantity of shares traded on this fill (zero for non-fills).
37	*OrderID*	Order identifier supplied by BATS.
38	*OrderQty*	Copied from order.
39	*OrdStatus*	State of order. `0` = New `1` = Partially Filled `2` = Filled `4` = Canceled `5` = Replaced `6` = Pending Cancel `8` = Rejected `A` = Pending Ack `E` = Pending Replace
41	*OrigClOrdID*	*ClOrdID* of the order being canceled or replaced (for a solicited cancel or cancel/replace, otherwise not present).
44	*Price*	Copied from order.
48	*SecurityID*	Copied from order, if present.
54	*Side*	Copied from order.
55	*Symbol*	Copied from order, if present.

58	*Text*	If present, indicates reason for the message. Format is one letter reason code followed by colon and space followed by free form text message. Reason codes are: `A` = Admin `D` = Duplicate *ClOrdID* `H` = Halted `K` = Order Rate Threshold Exceeded `L` = Price Exceeds Cross Range `N` = Ran Out of Liquidity to Execute Against `O` = *ClOrdID* Doesn't Match a Known Order `P` = Can't Modify an Order That is Pending Fill `Q` = Waiting For First Trade `R` = Routing Unavailable `T` = Routing order would trade through an away destination `U` = User Requested `V` = Would Wash `W` = Add Liquidity Only Order Would Remove `X` = Order Expired `Y` = Symbol Not Supported `Z` = Unforseen Reason `l` = Large in Scale `r` = Reserve Reload `m` = Market Access Risk Limit Exceeded `o` = Max Open Orders Count Exceeded `p` = Static Collar Breach `s` = Symbol Level Risk Management
59	*TimeInForce*	Copied from order.
60	*TransactTime*	Time transaction occurred. If enabled at the port or firm level, timestamps will be sent with microsecond resolution.
63	*SettlType*	**Drop only.** Only relevant if *ExecType* (150) = `F` and the original trade report utilised a non-standard settlement date. In this case, the relevant date will also be included in *SettlDate* (64).
64	*SettlDate*	**Drop only.** Only relevant if *ExecType* (150) = `F` and the original trade report utilised *SettlType* (63) ≠ `0`, in which case, the relevant date will be included in *SettlDate* (64); or, if the original trade report specified a *SettlDate* (64).
103	*OrdRejReason*	Optionally set when *ExecType* (150) = `8` (Rejected). `0` = Broker Option `1` = Unknown Symbol `2` = Exchange Closed `3` = Order Exceeds Limit `5` = Unknown Order `6` = Duplicate Order `8` = Stale Order
111	*MaxFloor*	Copied from order.
126	*ExpireTime*	Copied from order if *TimeInForce* (59) = `6` (GTD).

150	*ExecType*	Reason for this execution report. `0` = New (acknowledgement of new order) `1` = Partial Fill `2` = Fill `4` = Canceled `5` = Replaced `8` = Rejected `D` = Restated For **Drop only**, if optionally configured, the following value is also supported: `F` = Trade
151	*LeavesQty*	Quantity of shares still open for further execution. Will be zero if order is dead, otherwise will be *OrderQty* − *CumQty*. **Note**: It is possible for *LeavesQty* to be zero when *ExecType* (150) = `5` indicating that the order is dead.
198	*SecondaryOrderID*	Must request opt-in at firm or port level to receive this field. Present on Prevent Participant Match triggered cancel/restatement. Denotes the BATS *OrderID* (37) of contra side of prevented match. Present on a restatement execution report for reload of a reserve (iceberg) order. Denotes the new BATS OrderID which will be present on BATS' market data feeds.
207	*SecurityExchange*	Copied from order, if present.
375	*ContraBroker*	Only present on trades. Indicates the market of execution. A value of `LP` identifies an execution from an external liquidity provider, all other markets are identified by their ISO Market Identification Code (MIC)[18][19]
378	*ExecRestatement Reason*	Required when *ExecType* (150) = `D` (Restated). `4` = Broker option; optionally sent during reload of a reserve (iceberg) order `5` = Partial decline of *OrderQty*
382	*NoContraBrokers*	Only present on trades. Always `1`.
439	*ClearingFirm*	Copied from order, if present.
440	*ClearingAccount*	Copied from order, if present.
730	*SettlPrice*	**Drop only.** Only relevant if *ExecType* (150) = `F` and the original trade report utilised *SettlPrice* (730). This represents the price at which the trade will settle at.
7772	*CentralCounterparty*	Only present on trades. The CCP handling the trade: EMCF = European Multilateral Clearing Facility LCHL = LCH.Clearnet XCLR = SIX x-clear ECCP = EuroCCP NONE = Clearing Suppressed for self match. Returned on trades if the participant has selected a Preferred CCP. The FIX port can be configured to always return this optional field.
9621	*MTFAccessFee*	Only present on trades. Indication of access fee for this fill (up to five decimal places, negative for rebates).

[18] ISO 10383, see http://www.iso15022.org/MIC/homepageMIC.htm for details
[19] for historical reasons a local execution for an order entered into the BXE book is identified with a value of `BATS`

9730	*TradeLiquidity Indicator*	Only present on trades. `A` = Added Liquidity `R` = Removed Liquidity `AD` = Added Liquidity for the BATS Dark Pool `RD` = Removed Liquidity from the BATS Dark Pool `RT` = Removed Liquidity from the BATS Dark Pool by IOC order `AI` = Added Hidden Liquidity that was price improved `AK` = Added Liquidity from the hidden (reserve) portion of an iceberg order `X` = Routed to Another Market `C` = Auction `P` = Periodic Auction To allow for future expansion of this field, please ignore values with an unknown character in the 2nd position.
	Standard Message Trailer	

6.2 Cancel Reject

Rejects a Cancel or Cancel/Replace request.

When a Cancel/Replace is rejected, by default, the original order is left alive. A Cancel Reject should not be used as a sign that the original order has been canceled. Even if the *CancelOrigOnReject* (9619) = `Y` option is being used, a separate "unsolicited" cancel will be sent to close out the original order.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `9`
1	*Account*	Copied from Cancel or Cancel/Replace request.
11	*ClOrdID*	*ClOrdID* from the Cancel or Cancel/Replace request.
37	*OrderID*	*OrderID* of the order that failed to be canceled or replaced. `NONE` if *CxlRejReason* (102) = `1` (Unknown Order).
39	*OrdStatus*	State of order that failed to be canceled or replaced.
41	*OrigClOrdID*	*ClOrdID* of the order that failed to be canceled or replaced.
58	*Text*	Free-form text message.
102	*CxlRejReason*	`0` = Too Late to Cancel `1` = Unknown Order `3` = Already Pending Cancel or Pending Replace
434	*CxlRejResponseTo*	`1` = Cancel `2` = Cancel/Replace
	Standard Message Trailer	

6.3 Trade Cancel/Correct

Trade Cancel/Correct (UCC) is an optional message that must be enabled at the port level. It may be enabled for current-day only or for all cancels and corrections. Only the price and size of a trade may be corrected, all other details remain the same. Trade cancels and corrections do not alter live order state.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `UCC`
11	*ClOrdID*	*ClOrdID* of the order whose trade is being canceled or corrected.
15	*Currency*	Copied from order if *IDSource* (22) = `4` (ISIN).
17	*ExecID*	Day-unique ID of execution message.
19	*ExecRefID*	Refers to the *ExecID* (17) of the execution being canceled or corrected.
20	*ExecTransType*	`1` = Cancel `2` = Correct
22	*IDSource*	Copied from order being canceled or corrected, if present.
30	*LastMkt*	*LastMkt* on the original trade being canceled or corrected, if the port is configured to send this tag.
31	*LastPx*	Price on the original trade being canceled or corrected.
32	*LastShares*	Quantity of shares on the original trade being canceled or corrected.
37	*OrderID*	*OrderID* of the order whose trade is being canceled or corrected.
42	*OrigTime*	Date and time of the original trade, in GMT.
48	*SecurityID*	Copied from original order being canceled or corrected if *IDSource* (22) = `4` (ISIN), or `5` (RIC) was used.
54	*Side*	Copied from trade being canceled or corrected.
55	*Symbol*	Copied from original order being canceled or corrected.
60	*TransactTime*	Date and time of the cancel or correction. If enabled at the port or firm level, timestamps will be sent with microsecond resolution.
63	*SettlType*	**Drop only.** *SettlType* on the original trade being canceled or corrected, if relevant.
64	*SettlDate*	**Drop only.** *SettlDate* on the original trade being canceled or corrected, if relevant.
207	*SecurityExchange*	Copied from order being canceled or corrected if *IDSource* (22) = `4` (ISIN) was used.
439	*ClearingFirm*	Copied from trade being canceled or corrected, if present.
440	*ClearingAccount*	Copied from trade being canceled or corrected, if present.
730	*SettlPrice*	**Drop only.** *SettlPrice* on the original trade being canceled or corrected, if relevant.
6655	*CorrectedSize*	The corrected size of the trade. Only set if *ExecTransType* (20) = `2` (Trade Correct).
9620	*CorrectedPrice*	The corrected price of the trade. Only set if *ExecTransType* (20) = `2` (Trade Correct).
9730	*TradeLiquidity Indicator*	Copied from trade being canceled or corrected.
	Standard Message Trailer	

6.4 Trade Capture Report Ack

The Trade Capture Report Ack is sent by BATS to acknowledge the receipt of a Trade Capture Report. It is a technical-level ack, the Trade/Cancel/Amend is not considered to have fully succeeded until a Trade Capture Report is sent with with *TradeReportType* (856) of `2` (Accept).

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `AR`
15	*Currency*	Copied from the incoming `TradeCaptureReport`, if present.
22	*IDSource*	Copied from the incoming `TradeCaptureReport`, if present.
31	*LastPx*	Copied from the incoming `TradeCaptureReport`, if present. If *GrossTradeAmt* was used instead of *LastPx*, the value here will be indicative. Price is adjusted for allowed precision.
32	*LastShares*	Copied from the incoming `TradeCaptureReport`.
48	*SecurityID*	Copied from the incoming `TradeCaptureReport`, if present.
55	*Symbol*	Copied from the incoming `TradeCaptureReport`, if present.
58	*Text*	If present, indicates reason for the message. Format is one letter reason code followed by colon and space followed by free form text message. Reason codes are: `A` = Admin `D` = Duplicate *TradeReportID* `H` = Halted `U` = User Requested `Y` = Symbol Not Supported `X` = Expired `Z` = Unforseen Reason `m` = Market Access Risk Limit Exceeded `o` = Max Open Trade Count Exceeded
60	*TransactTime*	Copied from the `TradeCaptureReport` if present, or defaulted by BATS.
63	*SettlType*	Omitted if relevant value is `0` (Regular). Otherwise, will be `6` (Future) with the relevant date included in *SettlDate* (64).
64	*SettlDate*	Copied from incoming `TradeCaptureReport`, if present.
75	*TradeDate*	Copied from the `TradeCaptureReport` if present, or defaulted by BATS.
150	*ExecType*	Copied from the incoming `TradeCaptureReport`.
207	*SecurityExchange*	Copied from the incoming `TradeCaptureReport`, if present.
381	*GrossTradeAmt*	Copied from the incoming `TradeCaptureReport`, if present and valid.
487	*TradeReportTransType*	Copied from the incoming `TradeCaptureReport`.
571	*TradeReportID*	Copied from the incoming `TradeCaptureReport`.
572	*TradeReportRefID*	Unique identifier for the trade report as provided by BATS
574	*MatchType*	Copied from the incoming `TradeCaptureReport`.
730	*SettlPrice*	Copied from the incoming `TradeCaptureReport`, if present.
820	*TradeLinkID*	Copied from the incoming `TradeCaptureReport`, if present.
828	*TrdType*	Copied from the incoming `TradeCaptureReport`.
829	*TrdSubType*	Copied from the incoming `TradeCaptureReport`, if present.
855	*SecondaryTrdType*	Copied from the incoming `TradeCaptureReport`, if present.
856	*TradeReportType*	Copied from the incoming `TradeCaptureReport`.
939	*TrdRptStatus*	Will be `0` (Accepted) or `1` (Rejected)
1003	*TradeID*	Copied from the incoming `TradeCaptureReport`, if present.
1115	*OrderCategory*	Copied from the incoming `TradeCaptureReport`, if present.
1116	*NoRootPartyIDs*	Copied from the incoming `TradeCaptureReport`, if present.
1117	*RootPartyID*	Copied from the incoming `TradeCaptureReport`, if present.

1118	*RootPartyIDSource*	Copied from the incoming `TradeCaptureReport`, if present.
1119	*RootPartyRole*	Copied from the incoming `TradeCaptureReport`, if present.
1123	*TradeHandlingInstr*	Copied from the incoming `TradeCaptureReport`.
1390	*TradePublishIndicator*	Copied from the incoming `TradeCaptureReport`.
1430	*VenueType*	Copied from the incoming `TradeCaptureReport`.
1838	*NoTradePriceConditions*	Copied from the incoming `TradeCaptureReport`.
1839	*TradePriceCondition*	Copied from the incoming `TradeCaptureReport`.
2405	*ExecMethod*	Copied from the incoming `TradeCaptureReport`, if present.
9128	*Tolerance*	Copied from the incoming `TradeCaptureReport`, if present.
552	*NoSides*	Copied from the incoming `TradeCaptureReport`.
Repeating Group *TrdCapRptSideGrp* must occur the number of times specified in *NoSides* (552)		
...	...	Entire block copied from incoming TradeCaptureReport, although order may be adjusted
9688	*OrigCompID*	**Drop only.** *TargetCompID* (56) of original FIX TradeCaptureReport from BATS to the Participant. Drop port must be configured to send this optional field.
9689	*OrigSubID*	**Drop only.** *TargetSubID* (57) of original FIX TradeCaptureReport from BATS to the Participant. Drop port must be configured to send this optional field.
	Standard Message Trailer	

6.5 Trade Capture Report

The Trade Capture Report is sent from BATS to the participant in order to confirm that a Trade Capture Report has been fully processed. It is a business-level confirmation as distinct from the technology level acknowledgement sent as a Trade Capture Report Ack.

The majority of the fields in this message are copied from the incoming `TradeCaptureReport`. When using the *One-Party Report for Matching* model, it is important to note that the majority of these fields will be sourced from the party reporting the sell leg. Also on this model, the *Account*1 field for the contra leg will not be populated.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `AE`
15	*Currency*	Copied from the incoming `TradeCaptureReport`, if present.
22	*IDSource*	Copied from the incoming `TradeCaptureReport`, if present.
30	*LastMkt*	Segment MIC of this fill, if the port is configured to send this tag.
31	*LastPx*	Traded Price.
32	*LastShares*	Copied from the incoming `TradeCaptureReport`.
48	*SecurityID*	Copied from the incoming `TradeCaptureReport`, if present.
55	*Symbol*	Copied from the incoming `TradeCaptureReport`, if present.
58	*Text*	If present, indicates reason for the message. Format is one letter reason code followed by colon and space followed by free form text message. Reason codes are: `A` = Admin `D` = Duplicate *TradeReportID* `H` = Halted `U` = User Requested `Y` = Symbol Not Supported `X` = Expired `Z` = Unforseen Reason `m` = Market Access Risk Limit Exceeded `o` = Max Open Trade Count Exceeded
60	*TransactTime*	Copied from the `TradeCaptureReport` if present, or defaulted by BATS.
63	*SettlType*	Omitted if relevant value is `0` (Regular). Otherwise, will be `6` (Future) with the relevant date included in *SettlDate* (64).
64	*SettlDate*	Copied from incoming `TradeCaptureReport`, if present.
75	*TradeDate*	Copied from the `TradeCaptureReport` if present, or defaulted by BATS.
150	*ExecType*	Copied from the incoming `TradeCaptureReport`.
207	*SecurityExchange*	Copied from the incoming `TradeCaptureReport`, if present.
375	*ContraBroker*	`BATS`: Trade Reported on BATS (BXE) book `CHIX`: Trade Reported on Chi-X (CXE) book
487	*TradeReportTransType*	Copied from the incoming `TradeCaptureReport`.
571	*TradeReportID*	Unique identifier for the trade report confirm as provided by BATS
572	*TradeReportRefID*	Contains the *TradeReportID* (571) of the original trade capture report to which this message relates
573	*MatchStatus*	Will be `0` (Matched) for confirm, and `1` (Unmatched) for a decline
574	*MatchType*	Copied from the incoming `TradeCaptureReport`.
730	*SettlPrice*	Copied from the incoming `TradeCaptureReport`, if present.
820	*TradeLinkID*	Copied from the incoming `TradeCaptureReport`, if present.
828	*TrdType*	Copied from the incoming `TradeCaptureReport`.
829	*TrdSubType*	Copied from the incoming `TradeCaptureReport`, if present.

855	*SecondaryTrdType*	Copied from the incoming `TradeCaptureReport`, if present.
856	*TradeReportType*	Will be `2` (Accept) for a confirm, `3` (Decline) for a decline and `0` (Submit) for an unsolicited change.
1003	*TradeID*	ID representing the trade, as seen on outbound market data. Allocated by BATS. Required to amend, cancel or release a report.
1115	*OrderCategory*	Copied from the incoming `TradeCaptureReport`, if present.
1116	*NoRootPartyIDs*	Copied from the incoming `TradeCaptureReport`, if present.
1117	*RootPartyID*	Copied from the incoming `TradeCaptureReport`, if present.
1118	*RootPartyIDSource*	Copied from the incoming `TradeCaptureReport`, if present.
1119	*RootPartyRole*	Copied from the incoming `TradeCaptureReport`, if present.
1123	*TradeHandlingInst*	Copied from the incoming `TradeCaptureReport`.
1390	*TradePublishIndicator*	Will be 2 (Deferred Publication) if deferment is requested and the trade is eligible for such. Otherwise, copied from the incoming `TradeCaptureReport`.
1430	*VenueType*	Copied from the incoming `TradeCaptureReport`.
1838	*NoTradePriceConditions*	Copied from the incoming `TradeCaptureReport`, if present.
1839	*TradePriceCondition*	Copied from the incoming `TradeCaptureReport`, if present.
2405	*ExecMethod*	Copied from the incoming `TradeCaptureReport`, if present.
7570	*RptTime*	Indicates the time at which a deferred trade report will be automatically published. Where *RptTime* falls outside of the systems operating time, the report will be published during operating hours on the next trading day. When no deferral is requested, or when the trade does not qualify for a deferral, any time returned will match *TransactTime* (60).
552	*NoSides*	Copied from the incoming `TradeCaptureReport`. **Drop only.** When *TradeHandlingInst* (1123) = `0` and the configured third party requires counterparty anonymisation, will be limited to the number of sides your Drop profile permits you access.

Repeating Group *TrdCapRptSideGrp* must occur the number of times specified in *NoSides* (552)

...	...	Entire block copied from incoming TradeCaptureReport, although order may be adjusted
7772	*CentralCounterparty*	The CCP handling this trade leg for a confirm, and not present for a decline: EMCF = European Multilateral Clearing Facility LCHL = LCH.Clearnet XCLR = SIX x-clear ECCP = EuroCCP NONE = Clearing Suppressed for self match.

9688	*OrigCompID*	**Drop only.** *TargetCompID* (56) of original FIX TradeCaptureReport from BATS to the Participant. Drop port must be configured to send this optional field.
9689	*OrigSubID*	**Drop only.** *TargetSubID* (57) of original FIX TradeCaptureReport from BATS to the Participant. Drop port must be configured to send this optional field.
	Standard Message Trailer	

7 Example Messages and Message Flow

7.1 Trade Capture Report Cancellations

Below illustrates an example of key elements of the message flow for cancellation of previously confirmed trade captures.

Participant to BATS:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeID* (1003) = `ABCD1234` - The TradeID for the confirmed trade report
- *TradeReportTransType* (487) = `1` - Cancel

BATS to Participant (Technical Ack) - if rejected:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `1` - Rejected
- *Text* (58) = `Reason for reject`

BATS to Participant (Technical Ack) - if accepted:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `0` - Accepted

BATS to Participant - if cancellation is declined:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `3` - Decline
- *Text* (58) = `Reason for decline`

BATS to Participant - if cancellation is confirmed:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `2` - Accept

7.2 Trade Capture Report Amendments

Below illustrates an example of key elements of the message flow for amendment of previously confirmed trade captures.

Participant to BATS:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeID* (1003) = `ABCD1234` - The TradeID for the confirmed trade report
- *TradeReportTransType* (487) = `2` - Replace

BATS to Participant (Technical Ack) - if rejected:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `1` - Rejected
- *Text* (58) = `Reason for reject`

BATS to Participant (Technical Ack) - if accepted:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `0` - Accepted

BATS to Participant - if amendment is declined:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `2` - Replace
- *TradeReportType* (856) = `3` - Decline
- *Text* (58) = `Reason for decline`

BATS to Participant - if amendment is confirmed:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `2` - Replace
- *TradeReportType* (856) = `2` - Accept

7.3 Deferred Publication Trade Reports

Below illustrates an example of key elements of the message flow for deferred publication of trades captures.

Participant to BATS:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradePublishIndicator* (1390) = `2` - Deferred Publication
- *TransactTime* (60) = `Time of Trade` - As long as this is within the acceptable deferment period, the trade will not be regarded as late

BATS to Participant (Technical Ack) - if rejected:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `1` - Rejected
- *Text* (58) = `Reason for reject`

BATS to Participant (Technical Ack) - if accepted:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `0` - Accepted

BATS to Participant - if report is declined:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `3` - Decline
- *Text* (58) = `Reason for decline`

BATS to Participant - if report is confirmed and deferment permitted:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `2` - Accept
- *TradePublishIndicator* (1390) = `2` - Deferred Publication

BATS to Participant - if report is confirmed and deferment is not permitted:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `2` - Accept
- *TradePublishIndicator* (1390) = `1` - Publish trade (immediately)
- *Text* (58) = `A: Trade accepted, but ineligible for deferment` - Exact text may vary

Then, once the Participant would like the deferred trade released to the market (note - this may be immediately if the Participant has held onto the trade for the deferment period).

Participant to BATS:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeID* (1003) = `ABCD1234` - The TradeID for the confirmed trade report
- *TradeReportTransType* (487) = `3` - Release

BATS to Participant (Technical Ack) - if rejected:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `1` - Rejected

- *Text* (58) = `Reason for reject`

BATS to Participant (Technical Ack) - if accepted:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `0` - Accepted

BATS to Participant - if release is declined:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `3` - Release
- *TradeReportType* (856) = `3` - Decline
- *Text* (58) = `Reason for decline`

BATS to Participant - if release is confirmed:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `3` - Release
- *TradeReportType* (856) = `2` - Accept

7.4 ETR Matched Trade Report

Below illustrates an example of an ETR submitted for matching with a counterparty. In this case, you might be the ABCD party.

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `1234`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `0` - Submit
- *TradeHandlingInstr* (1123) = `2` - ETR Matching
- *TradePublishIndicator* (1390) = `0` - Do not publish
- *NoSides* (552) = `2`
- *Side* (54) = `1` - Buy
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `ABCD`
- *PartyRole* (452) = `7` - EnteringFirm
- *Side* (54) = `2` - Sell
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `XYZZ`
- *PartyRole* (452) = `17` - ContraFirm

Then, the counterparty (XYZZ in this case), would enter a similar report, but with party information reversed (except for PartyRoles):

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `1234`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `0` - Submit
- *TradeHandlingInstr* (1123) = `2` - ETR Matching
- *TradePublishIndicator* (1390) = `0` - Do not publish
- *NoSides* (552) = `2`
- *Side* (54) = `2` - Sell
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `XYZZ`
- *PartyRole* (452) = `7` - EnteringFirm
- *Side* (54) = `1` - Buy
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `ABCD`
- *PartyRole* (452) = `17` - ContraFirm

7.5 Withdrawing an ETR Matching Instruction

Below illustrates an example of an ETR submitted for matching with a counterparty.

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `YOUR1234`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `0` - Submit
- *TradeHandlingInstr* (1123) = `2` - ETR Matching

When we acknowledge your matching instruction, you will receive a message similar to:

- *MsgType* (35) = `AR` - Trade Capture Report Ack
- *TradeReportID* (571) = `YOUR1234`
- *TradeReportRefID* (572) = `BATS1234`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `0` - Submit
- *TradeHandlingInstr* (1123) = `2` - ETR Matching

Should you need to withdraw the matching instruction, you should send in a trade report similar to:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `YOUR3456`
- *TradeReportRefID* (572) = `BATS1234`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `6` - TradeReportCancel
- *TradeHandlingInstr* (1123) = `2` - ETR Matching

If successful, you will then receive an acknowledgement of your withdrawal request:

- *MsgType* (35) = `AR` - Trade Capture Report Ack
- *TradeReportID* (571) = `YOUR3456`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `6` - TradeReportCancel
- *TradeHandlingInstr* (1123) = `2` - ETR Matching

Followed by a decline of your original report:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `BATS1234`
- *TradeReportRefID* (572) = `YOUR1234`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `3` - Decline
- *TradeHandlingInstr* (1123) = `2` - ETR Matching
- *Text* (58) = `U: A Message` - 'U' indicates User

7.6 Withdrawing an ETR Matched Cancellation Instruction

Below illustrates an example of an ETR cancellation instruction submitted for matching with a counterparty.

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `YOUR1234`
- *TradeID* (1003) = `0001234567`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `0` - Submit
- *TradeHandlingInstr* (1123) = `2` - ETR Matching

When we acknowledge your cancellation instruction, you will receive a message similar to:

- *MsgType* (35) = `AR` - Trade Capture Report Ack
- *TradeReportID* (571) = `YOUR1234`
- *TradeReportRefID* (572) = `BATS1234`
- *TradeID* (1003) = `0001234567`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `0` - Submit
- *TradeHandlingInstr* (1123) = `2` - ETR Matching

Should you need to withdraw the cancellation instruction, you should send in a trade report similar to:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `YOUR3456`
- *TradeReportRefID* (572) = `BATS1234`
- *TradeID* (1003) = `0001234567`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `6` - TradeReportCancel
- *TradeHandlingInstr* (1123) = `2` - ETR Matching

If successful, you will then receive an acknowledgement of your withdrawal request:

- *MsgType* (35) = `AR` - Trade Capture Report Ack
- *TradeReportID* (571) = `YOUR3456`
- *TradeID* (1003) = `0001234567`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `6` - TradeReportCancel
- *TradeHandlingInstr* (1123) = `2` - ETR Matching

Followed by a decline of your original instruction:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `BATS1234`
- *TradeReportRefID* (572) = `YOUR1234`
- *TradeID* (1003) = `0001234567`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `3` - Decline
- *TradeHandlingInstr* (1123) = `2` - ETR Matching
- *Text* (58) = `U: A Message` - 'U' indicates User

7.7 ETR Matched Trade Report with Consideration and Tolerance

Below illustrates an example of an ETR submitted for matching with a counterparty, where a consideration is specified instead of a price and a tolerance is allowed.

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeReportID* (571) = `1234`
- *TradeReportTransType* (487) = `0`
- *TradeReportType* (856) = `0`
- *VenueType* (1430) = `O` - Off Book
- *MatchType* (574) = `3` - trade reporting (on-exchange)
- *TrdType* (828) = `60` - Technical Trade
- *TradeHandlingInstr* (1123) = `2` - ETR Matching
- *Currency* (15) = `GBX`
- *LastShares* (32) = `100000`
- *GrossTradeAmt* (381) = `10000000000` - GBX 10B or GBP 100M
- *Tolerance* (9128) = `1000` - GBX 1000 or GBP 10
- *NoSides* (552) = `2`
- *Side* (54) = `1` - Buy
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `ABCD`
- *PartyRole* (452) = `7` - EnteringFirm
- *Side* (54) = `2` - Sell
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `XYZZ`
- *PartyRole* (452) = `17` - ContraFirm

7.8 ETR Matched Trade Report with Price and Tolerance

Below illustrates an example of an ETR submitted for matching with a counterparty, where a price is specified rather than consideration and a tolerance is allowed.

- *TradeHandlingInstr* (1123) = `2` - ETR Matching
- *Currency* (15) = `GBX`
- *LastShares* (32) = `100000`
- *LastPrice* (31) = `100000` - yielding consideration of GBP 100M
- *Tolerance* (9128) = `1000` - GBX 1000 or GBP 10

7.9 Third Party Confirmed Trades

Below illustrates an example of key elements of the message flow when confirmed trades are reported via a third party (whether a broker or a vendor). Generally, participants will only see these variants of messages if utilising ODROP as the original incoming message will be sent by the third party.

Information on sides of the trade that the customer does not have authorisation to view may be anonymised should the third party require such.

Participant to BATS:

- *MsgType* (35) = `AE`
- *TradeHandlingInstruction* (1123) = `0` - Confirmed
- *NoRootPartyIDs* (1116) = `1`
- *RootPartyID* (1117) = `3PBV` - A code that identifies the third party
- *RootPartyIDSource* (1118) = `D` - Proprietary / Custom Code
- *RootPartyRole* (1119) = `6` - IntroducingFirm
- *NoSides* (552) = `2`
- *Side* (54) = `1` - Buy
- *PartyID* (448) = `PTY1` - A code that identifies the first party to the trade
- *Side* (54) = `2` - Sell
- *PartyID* (448) = `PTY2` - A code that identifies the second party to the trade

BATS to Participant - if confirmed:

- *MsgType* (35) = `AE`
- *TradeHandlingInstruction* (1123) = `0` - Confirmed
- *TradeReportType* (856) = `2` - Accept
- *TradeID* (1003) = `ABCD1234` - The TradeID for the confirmed trade report
- *NoRootPartyIDs* (1116) = `1`
- *RootPartyID* (1117) = `3PBV` - A code that identifies the third party
- *RootPartyIDSource* (1118) = `D` - Proprietary / Custom Code
- *RootPartyRole* (1119) = `6` - IntroducingFirm
- *NoSides* (552) = `2`
- *Side* (54) = `1` - Buy
- *PartyID* (448) = `PTY1` - A code that identifies the first party to the trade
- *Side* (54) = `2` - Sell
- *PartyID* (448) = `PTY2` - A code that identifies the second party to the trade
- *MsgType* (35) = `AE`

8 Common Session Level Issues

BATS uses FIX 4.2 as specified by the FPL Document Version 4.2 (with Errata 20010501) with business level extensions as described in this document. The session level of the FPL specification is followed as closely as possible.

The version with errata cleared up many session level ambiguities present in the earlier version 4.2 (March 1, 2000). The following sections emphasize a few common problem areas in implementations of the FIX session protocol.

Typographical conventions:

- Anchor locations in the FPL document are shown in blue.
- Text in **bold** was emphasized in the original FPL specification.
- Emphasis added by BATS is shown in purple.
- Notes added by BATS are shown in green.

8.1 Ordered Message Processing

From Financial Information Exchange Protocol/FIX Message Format and Delivery/Ordered Message Processing:

> The FIX protocol assumes complete ordered delivery of messages between parties. Implementers should consider this when designing message gap fill processes. Two options exist for dealing with gaps, either request all messages subsequent to the last message received or ask for the specific message missed while maintaining an ordered list of all newer messages. For example, if the receiver misses the second of five messages, the application could ignore messages 3 through 5 and generate a resend request for messages 2 through 5, **or**, preferably 2 through 0 (where 0 represents infinity). Another option would involve saving messages 3 through 5 and resending only message 2. In both cases, messages 3 through 5 should not be processing before message 2.

8.2 Logon

From Financial Information Exchange Protocol/Session Protocol/Logon:

> After the initiator has been authenticated, the acceptor will respond immediately with a confirming *Logon* message.

8.3 Message Recovery

From Financial Information Exchange Protocol/Session Protocol/Message Recovery:

> When the incoming sequence number does not match the expected number, corrective processing is required. Note that the SeqReset-**Reset** message ([BATS: this refers only to *GapFillFlag* (123) = `N`] used only to recover from a disaster scenario vs. normal resent request processing) is an exception to this rule as it should be processed without regards to its *MsgSeqNum* (34). **If the incoming message has a sequence number less than expected and the *PossDupFlag* (43) is not set, it indicates a serious error. It is strongly recommended that the session be terminated and manual intervention be initiated**. If the incoming sequence number is greater than expected, it indicates that messages were missed and retransmission of the messages is requested via the *Resend Request* (see earlier section, *Ordered Message Processing*).
>
> ...

If there are consecutive administrative messages to be resent, it is suggested that only one *SeqReset-GapFill* message be sent in their place. The sequence number of the *SeqReset-GapFill* message is the next expected outbound sequence number. The *NewSeqNo* (36) field of the GapFill message contains the sequence number of the highest administrative message in the group plus 1. For example, during a Resend operation there are 7 sequential administrative messages waiting to be resent. They start with sequence number 9 and end with sequence number 15. Instead of transmitting 7 GapFill messages (which is perfectly legal, but not network friendly), a *SeqReset-GapFill* message may be sent. **The sequence number of the Gap Fill message is set to 9 because the remote side is expecting that as the next sequence number.** The *NewSeqNo* (36) field of the Gap Fill message contains the number 16, because that will be the sequence number of the next message to be transmitted.

Sequence number checking is a vital part of FIX session management. However, a discrepancy in the sequence number stream is handled differently for certain classes of FIX messages. The table below lists the actions to be taken when the incoming sequence number is greater than the expected incoming sequence number.

> **NOTE: In all cases except the Sequence Reset – Reset message, the FIX session should be terminated if the incoming sequence number is less than expected and the *PossDupFlag* (43) is not set. A *Logout* message with some descriptive text should be sent to the other side before closing the session.**

Response by Message Type

Message Type	Action to Be Taken on Sequence # Mismatch
Logon	Must always be the first message transmitted. Authenticate and accept the connection. After sending a *Logon* confirmation back, send a *ResendRequest* if a message gap was detected in the *Logon* sequence number.

...

8.4 Resend Request

From Financial Information Exchange Protocol/Administrative Messages/Resend Request:

> Note: the sending application may wish to consider the message type when resending messages; e.g., if a new order is in the resend series and a significant time period has elapsed since its original inception, the sender may not wish to retransmit the order given the potential for changed market conditions. (The Sequence Reset-Gap Fill message is used to skip message that a sender does not wish to resend.)

8.5 Sequence Reset – Gap Fill

From Financial Information Exchange Protocol/Administrative Messages/Sequence Reset (Gap Fill):

> The sequence reset message is used by the sending application to reset the incoming sequence number on the opposing side. This message has two modes: "Sequence Reset – Gap Fill when *GapFillFlag* (123) is 'Y' and "Sequence Reset – Reset" when *GapFillFlag* (123) is 'N' or not present. The "Sequence Reset – Reset" mode should **only** be used to recover from a disaster situation which cannot e otherwise recovered via "Gap Fill" mode. The sequence reset message can be used in the following situations:

- During normal resend processing, the sending application may choose not to send a message (e.g., an aged order). The Sequence Reset – Gap Fill is used to mark the place of that message.
- During normal resend processing, a number of administrative messages are not resent, the Sequence Reset – Gap Fill message is used to fill the sequence gap created.

. . .

The sending application will initiate the sequence reset. **The message in all situations specifies the *NewSeqNo* (36) to reset as the value of the next sequence number immediately following the messages and/or sequence numbers being skipped.**

. . .

If the *GapFillFlag* (123) field is present (and equal to 'Y'), the *MsgSeqNum* (34) should conform to standard message sequencing rules (i.e., the *MsgSeqNum* (34) of the SeqReset-GapFill message should represent the beginning *MsgSeqNum* (34) in the gap fill range because the remote side is expecting that next message).

The sequence reset can only increase the sequence number. If a sequence reset is received attempting to decrease the next expected sequence number, the message should be rejected and treated as a serious error. It is possible to have multiple resend requests issued in a row (i.e., 5 to 10 followed by 5 to 11). If sequence number 8, 10, and 11 represent application messages while 5–7 and 9 represent administrative messages, the series of messages as a result of the resend request may appear as SeqReset-GapFill with *NewSeqNo* (36) of 8, message 8, SeqReset-GapFill with *NewSeqNo* (36) of 10, and message 10. This could then be followed by SeqReset-GapFill with *NewSeqNo* (36) of 8, message 8, SeqReset-GapFill with *NewSeqNo* (36) of 10, message 10, and message 11. One must be careful to ignore the duplicate SeqReset-GapFill which is attempting to lower the next expected sequence number. This can be detected by checking to see if its *MsgSeqNum* (34) is less than expected. If so, the SeqReset-GapFill is a duplicate and should be discarded.

9 FIX Drop

BATS offers two types of FIX Drop ports (Standard FIX Drop and Order by Order FIX Drop). Both port types do not accept orders. Their purpose is to provide real time information about order flow. They may be configured to send order flow based on various combinations of information relating to specific Participants, trading firm identifiers, and/or sessions. With proper authorisation (e.g., clearing or sponsored relationships), a single FIX Drop session can be used to obtain information about multiple Participants.

9.1 Standard FIX Drop

Standard FIX drop ports only send execution information on fills (i.e., execution reports where *ExecType* (150) = `1` (Partially Filled) or `2` (Filled)). It can also be configured to send execution reports for trades resulting from Trade Capture Reports (where *ExecType* (150) = `F` (Trade)) and Trade Cancel/Correction messages (where *MsgType* (35) = `UCC`) resulting from cancels/amends.

9.2 Order By Order FIX Drop

All order message types are supported including, but not limited to:

- *ExecType* (150) = `0`: Acknowledgments
- *ExecType* (150) = `1` or `2`: Partially Filled, Filled
- *ExecType* (150) = `4`: Canceled
- *ExecType* (150) = `5`: Replaced
- *ExecType* (150) = `8`: Rejected
- *MsgType* (35) = `9`: Order Cancel Reject
- *MsgType* (35) = `UCC`: Trade Cancel/Correction (optionally, if configured at the port level)
- *MsgType* (35) = `AE`: Trade Capture Report (optionally, if configured at the port level)

If rejects or cancels are due to incomplete or incorrect clearing information, they may be unavailable on Order by Order FIX Drop ports.

Users of Order by Order FIX Drop must always be prepared to receive new/unknown FIX tag and FIX tag values for BOE/FIX ports being monitored. BATS reserves the right to add new FIX tags and to update values distributed on Order by Order FIX Drop with no notice.

9.3 Port Options

Both types of FIX Drop ports can be optionally configured with the following features:

1. Choice of various BATS supported symbology types.
2. Sending of Trade Cancel/Correction (*MsgType* (35) = `UCC`) messages. Please note that enabling these messages will be dependent on enabling of trade cancels/corrections on the corresponding FIX order entry ports.
3. Enable unique wash execution identifiers.

10 FIX Differences Between US and Europe

This section describes, in detail, the differences between the FIX implementations of the BATS US Equities exchanges and BATS Chi-X Europe. The FIX session level implementation and supported messages are mostly identical between the US and Europe.

Trade Capture Reports

All messaging related to the use of Trade Capture Reports is only available in Europe.

Tick Sizes

In the United States, there is currently a single tick band for all symbols. Prices less than $1.00 have a tick size of $0.0001. Prices greater than $1.00 have a tick size of $0.01. In Europe, tick sizes vary by market, price, and symbol. Reference data files are available daily which enumerate the tick sizes.

Routing Instructions

The values which are common across the US and Europe are *RoutingInst* = `B`, `P`, `R`, `Q`.

Display Indicator

Values for the *DisplayIndicator* (9479) are different. Europe only defines *DisplayIndicator* (9479) = `X` (visible) and `I` (invisible). US Equities offers additional values for price sliding.

Bypass Hidden

The *BypassHidden* (9687) is not supported in Europe.

Trade Liquidity Indicator

Values for the *TradeLiquidityIndicator* (9730) are different. Values which are common across the US and Europe are *TradeLiquidityIndicator* (9730) = `A` (Added) and `R` (Removed). US Equities offers values for routing which Europe does not. Europe offers values for fills done in the BATS Dark Pool which the US does not.

Discretionary Orders

For regulatory reasons, discretionary orders, specified in the US with *DiscretionAmount* (9622), are not supported in Europe.

Sell Short

The sell short *Side* (54) = `5` value is not supported in Europe.

Execution Instruction

US Equities support *ExecInst* (18) values for intermarket sweep orders (`18=f`) and Dark Scan (`18=z`) which are not supported in Europe.

Working and Display Price Fields

The *WorkingPrice* (9690) and *InitialDisplayPrice* (9691) fields are not supported in Europe. These fields are relevant for price sliding which is only supported in the US.

Symbology

Europe allows specifying ISIN, RIC, or Uniform symbologies which require the use of *SecurityExchange* (207), *Currency* (15), *SecurityID* (48), *IDSource* (22), and/or *Symbol* (55). US Equities uses *Symbol* (55) and *SymbolSfx* (65) only.

Market Hours

Pre- and post-market trading are supported in the US, but not in Europe.

Central Counterparty

The optional reply field *CentralCounterparty* (7772) is only supported in Europe.

Contra Broker

The *ContraBroker* (375) tag will contain completely different values in Europe than in the US.

11 Support

Please email questions or comments regarding this specification to `tradedeskeurope@bats.com`.

Revision History

9 July 2008	Initial draft version.
16 July 2008	Europe URL and email address.
2 September 2008	Updated tick sizes. Removed references to *WorkingPrice* (9690). Removed wording that prices will be slid to a less aggressive amount if they do not fit the tick size for a symbol. Orders will be rejected if they do not fit the tick size. Added *DisplayIndicator* (9479) to "BATS Specific Fields" and to allowed fields for "New Order – Single". Added section entitled "Hidden Orders".
8 September 2008	Added information about the *Text* (58) that will be received in the event of an order which, if executed, would happen outside the allowed price collar. Added clarification that *OrdRejReason* (103) will not always be sent on order rejects.
1 October 2008	Adjusted price collar for allowed executions to be up to 20% away from the market.
11 November 2008	Added ability to allocate trades to house or client account regardless of order capacity by using the *Account* (1) field. Updated front page text to note FSA authorisation.
16 December 2008	Added information on how notional value is determined for different order types.
3 February 2009	Added details for new Trade Cancel/Correct (UCC) message type.
26 March 2009	Discretionary orders are no longer permitted.
27 March 2009	Added new order type Post Only At Limit (*RoutingInst* (9303) = `Q`) and new tag *MaxRemovePct* (9618).
9 July 2009	Added BATS Dark Pool routing. New values for *RoutingInst* (9303) and *TradeLiquidityIndicator* (9730).
15 July 2009	Added ability to post only to BATS Dark Pool.
16 July 2009	Added BATS Market On Close. New values for *ExecInst* (18), *OrdType* (40), *TimeInForce* (59), and *ExecType* (150).
23 July 2009	Added Participant Trade Prevention functionality. New tag of *PreventParticipantMatch* (7928). Added new section "FIX Differences Between US And Europe". Documented *OrdStatus* (39) = `A`. Only occurs on a Cancel/Replace reject if the FIX Handler is awaiting an acknowledgement on a new order from the Matching Engine.
30 July 2009	*RoutingInst* (9303) = `BA` or `PA` will now route any order which is not eligible for the BATS Dark Pool to the integrated book.
24 August 2009	Updates to participant match prevention.
9 September 2009	Removed reference to *WorkingPrice* (9690) which isn't used on BATS Chi-X Europe. Fixed wording about which symbology tags are required on cancel order messages.
7 October 2009	Central Counterparty updates.
19 October 2009	Clarified in the Execution Report that *TradeLiquidityIndicator* (9730) can also take on values `AD` and `RD` for executions which occur in the BATS Dark Pool.

23 October 2009	Noted that *ExecInst* (18) will be returned on Execution Reports if set on the original order.
19 November 2009	Version 2.0. Added new "FIX Drop" section. Numerous formatting changes. *ExecType* (150) = `3` (Done for Day) was listed as a possible value BATS would send, but it is not.
24 January 2010	Version 2.1. Removed *RoutingInst* (9303) = `PA` or PD. Added dark and onward routing. New values for *RoutingInst* (9303), *ExecInst* (18), *TradeLiquidityIndicator* (9730), *Text* (58) (reject message if routing is unavailable).
24 January 2010	Version 2.2. New values for *ContraBroker* (375).
18 February 2010	Version 2.3. Added Common Session Level Issues (§ 8, p. 48). Removed section about Market BBO and added Execution Collars (§ 1.9, p. 6) and Peg Order Pricing (1.11).
9 March 2010	Version 2.4. *RoutingInst* (9303) = `RL` or `RC` will re-route (RECYCLE) a booked order if another market locks or crosses the limit.
16 March 2010	Version 2.5. By default BATS Trading At Last orders are now visible unless explicitly hidden using *DisplayIndicator* (9479) = `I`. *OrdType* (40) values `1` (Market) and `2` (Limit) are now accepted during the TAL phase.
15 April 2010	Version 2.6 Removed order quantity limit of 999,999. The new limit is 99,999,999 shares, but may be lowered if requested by a Participant or Sponsor.
30 April 2010	Version 2.7 Added BATS Dark Self Cross (§ **??**, p. **??**). Added *CrossFlag* (77401). Added new value for *RoutingInst* (9303) (`BX` = BATS Dark Self Cross). New values for *TradeLiquidityIndicator* (9730) (`AM`, `RM`). New values for *ContraBroker* (375).
7 May 2010	Version 2.8 Added *PreventParticipantMatch* (7928) = `d`.
20 May 2010	Clarified that Post Only orders will only reject when removing visible liquidity.
1 June 2010	Version 2.9 Added BATS Plus (§ 1.13, p. 7) and Account Field (§ 1.17, p. 8) sections. Update (§ 1.12, p. 7) to clarify differences to BATS Plus. New values for *RoutingInst* (9309) and clarification of *Account* (1)
26 August 2010	Version 2.10 Fixed minor typographical errors.
27 August 2010	Version 2.11 Parallel-D routing strategy. New values for *RoutingInst* (9303).
12 October 2010	Version 2.12 Restatement execution reports may be optionally received on reserve reload, allowing Participants to know the new OrderID that will be shown on BATS' market data feeds. New initial character on *Text* (58) field of `r` indicating the restatement was sent due to reserve reload. See new section § 1.10, p. 6.
22 October 2010	Version 2.13 Midpoint peg orders may now have a limit price at one-half the tick size (§ 1.4, p. 5).

25 November 2010	Version 2.14 Parallel-2D routing strategy. New values for *RoutingInst* (9303). Added *Side* (54) to Trade Cancel/Correct (UCC) message type.
14 January 2011	Version 2.15 Noted that midpoint peg orders at half-tick sizes may only specify limit prices out to a maximum of four decimal places.
2 February 2011	Version 2.16 *OrdStatus* (39) = `C` was documented, but never sent in practice. Removed this value from the specification.
8 February 2011	Version 2.17 Noted that midpoint peg orders are not tick size validated.
22 March 2011	Version 2.18 Corrected various instances where MBBO was incorrectly referenced instead of PBBO.
5 April 2011	Version 2.19 Removed `1` and `2` from values which are communicated in *ExecTransType* (20) for execution reports. Removed *ExecRefID* (19) from execution reports as it is never sent. *AvgPx* (6) was missing from the execution report documentation.
14 April 2011	Version 2.20 Updated *RoutingInst* (9303) values of `R`, `RL`, and `RC` to note that Parallel-D is used, not CYCLE.
27 April 2011	Version 2.21 Added new value `AI` for *TradeLiquidityIndicator* (9730).
26 May 2011	Version 2.22 *Symbol* (55) may now be sent as the RIC or Ticker of the stock identified by *SecurityID* (48). Added new values `ECCP` and `NONE` for *FIXCentralCounterparty* (7772).
31 May 2011	Version 2.23 Added new value `RT` for *TradeLiquidityIndicator* (9730).
29 June 2011	Version 2.24 Noted that, if opted into at the firm or port level, *TransactTime* (60) will be sent with microsecond resolution.
30 June 2011	Version 2.25 Noted that *ClearingFirm* (439) is optional.
7 July 2011	Version 2.26 Noted that, if opted into at the firm or port level, *SendingTime* (52) and *OrigSendingTime* (122) will be sent with microsecond resolution.
25 Jul 2011	Version 2.27 Added optional 4th character to *RoutingInst* (9303) used to select the resting book for routed orders. The BATS Plus *RoutingInst* values of `PP` and `PL` have been deprecated in favour of `Y` and `L` which provide backwards compatibility with the US specification.
10 Oct 2011	Version 2.28 Removed all references to MOC/TAL.
27 Oct 2011	Version 2.29 Added reason code of 'm' to *Text* (58)
7 November 2011	Version 2.30 Clarified wording for *MinQty* (110) to note that it is usable with BATS Dark Pool orders. Added BATS Select.
13 December 2011	Version 2.31 Added reason code of 'T' to *Text* (58)

4 January 2012	Version 2.32 Added reason code of 'o' to *Text* (58). Noted that BATS reserves the right to add new FIX tags and to update values distributed on Order by Order FIX Drop with no notice.
19 January 2012	Version 2.33 Updated to reflect the new BATS Chi-X Europe name. Clarified `CHIX` as a valid value for both *ContraBroker* (375) and *TargetCompID* (56) on CXE ports.
5 March 2012	Version 2.34 Pegged orders are now temporarily suspended rather than cancelled when the exchange is not in continous trading.
23 April 2012	Version 2.35 Clarity around session level reject messages (*MsgType* (35) = `3`).
21 May 2012	Version 2.36 Renamed BATS Select to BATS DRTOnly and clarified use of the 2nd and 3rd characters of tag *RoutingInst* (9303).
28 May 2012	Version 2.37 Updated *PreventMemberMatch* (7928) to include a 3rd character for Trading Group ID.
26 October 2012	Version 2.38 Added Lit Sweep and Dark Sweep interbook order types.
9 November 2012	Version 2.39 Clarified contents of tag *ContraBroker* (375).
21 November 2012	Version 2.40 Added Lit Sweep (Sequential) interbook order type.
7 December 2012	Version 2.41 Added SubLiquidityIndictor value K
19 December 2012	Version 2.42 Added TradeCaptureReport and associated message types. Removed BATS Dark Self Cross order type.
15 February 2013	Version 2.43 Enhancements to Trade Capture Reports: *TrdType* (828) = `30` added, used to specify a 'special price' trade; *TrdType* (828) = `0` will now be used to specify regular (not 'special') priced trades, rather than `54`; *TransactTime* (60) and *TradeDate* (75) are no longer ignored.
25 March 2013	Version 2.44 Enhancements to Trade Capture Reports: *PartyRole* (452) = `7` added, used to specify the party reporting the trade; *PartyRole* (452) = `17` added, used to specify the party the trade is alleged against; *PartyId* (448) Relaxed requirement for both parties to be identical
17 May 2013	Version 2.45 Clarification of optional availability of Trade Capture Reports over FIX DROP ports
23 May 2013	Version 2.46 Rewording of FIX Differences Between US and Europe § 10, p. 52, following Recognised Investment Exchange status, to remove ambigious usage of the terms "the MTF" and "the Exchange".
31 May 2013	Version 2.47 Removal of references to the Cycle routing strategy which has been retired (Parallel-D and Parallel-2D replace it).
17 June 2013	Version 2.48 Enhancements to Trade Capture Reports: Support for cancels and amends. Added message flow section

28 June 2013	Version 2.49 Removal of SEDOL support. Clarified usage of *MinQty* (110) for BATS Dark Pool. Added Large In Scale reason code.
18 July 2013	Version 2.50 Added *CorrectedSize* (6655) for Trade Cancel/Correct messages. Made *OrderCapacity* (528) optional for Trade Capture Reports. Added various fields to the TradeCaptureReport that are available in the TRF to help normalise the two specifications. Adjusted behaviour of *TradeReportTransType* (487) and *TradeReportType* (856) in trade capture confirmations/declines. Added example message flow section for deferred publication trade reports.
20 August 2013	Version 2.51 Clarified behaviour of *TradeReportID* (571) for Participant submitted trade reports. Added *RptTime* (7570). Remove behaviour no longer valid now that we're past the ETR Cancel/Amend effective date
3 October 2013	Version 2.52 Remove 'Effective' notes now we're past their go live date
26 October 2013	Version 2.53 Clarification of optionally configured Trade Cancel/Correct messages over FIX DROP ports.
22 January 2014	Version 2.54 Removed *MTFAccessFee* (9621) from trade capture confirmations. Additional supported values for *TrdType* (828).
21 March 2014	Version 2.55 Addition of *ExecMethod* (2405) for trade captures.
28 March 2014	Version 2.56 Removed 'effective from' labels.
3 April 2014	Version 2.57 Allow the use of *TrdSubType* (829) and *SecondaryTrdType* (855) for trade reports. Clarification that *AccessFee* (9621) is indicative
20 May 2014	Version 2.58 Bug fix location of *SendingTime* (52) (should be session header). Clarified name of proposed MMT 3.7 field.
16 June 2014	Version 2.59 Increased the number of decimal places supported for Trade Capture Reports.
25 June 2014	Version 2.60 Added changes to Trade Capture messages effective with the BATS Chi-X Europe Q3 2014 release, being those that follow. *VenueType* (1430), *MatchType* (574) and *PublicationMode* (1390) become mandatory. Deprecated use of *VenueType* (1430) = `X` in favour of *VenueType* (1430) = `O`. Deprecated use of *PreviouslyReported* (570) in favour of values in *PublicationMode* (1390). Added support for *PublicationMode* (1390) = `0` (Do Not Publish). Deprecated use of *TrdType* (828) = `59` in favour of *TrdType* (828) = `62`. Deprecated use of *TrdType* (828) = `60` in favour of *TrdType* (828) = `63`. Deprecated use of *SecondaryTrdType* (855) = `58` in favour of *SecondaryTrdType* (855) = `64`. Moved *TradingSessionSubID* (625) into the repeating group. Added support for *OrderCategory* (1115).
25 July 2014	Version 2.61 Removed 'effective from 25th of July' labels. Addition of Dark Lit orders.
25 July 2014	Version 2.62 Removed deprecated content.
8 October 2014	Version 2.63 Refer to the Participant Manual for execution collar (aka order price collar) for the actual percentages used.

10 October 2014	Version 2.64 Clarified ability to reuse *ClOrdId* with MODIFY ORDERs when daily limit trading risk controls are enabled.
29 October 2014	Version 2.65 Clarified usage of *OrderCategory*. Added AtTheOpen and AtTheClose to *TimeInForce* for auctions.
10 November 2014	Version 2.66 Added new reject reason code.
27 November 2014	Version 2.67 Clarified usage of *PartyRole* (452) = `7`. Added new value `C` for *TradeLiquidityIndicator* (9730).
19 January 2015	Version 2.68 Clarified usage of *OrderCategory* (1115). Added missing reason code 'p'. Clarified usage of FIX 4.4 sessions. Added additional fields to TRADE CAPTURE REPORT ACK and BATS to Participant TRADE CAPTURE REPORT. Clarified side normalisation in BATS to Participant Trade Capture related messages. Added support for *GrossTradeAmt* (381). Changed *TradeHandlingInstr* (1123) in BATS to Participant TRADE CAPTURE REPORT to echo back supplied value.
2 March 2015	Version 2.70 EuroCCP NV clearing trade reports will now be truncated at the same level of precision as elsewhere. Add *TradeReportRefID* (572) to TRADE CAPTURE REPORT.
14 April 2015	Version 2.71 Clarification of *MinQty* (110) behaviour following "Minimum Execution Size" (MES) changes.
27 April 2015	Version 2.72 Remove 'Effective' notes now we're past their go live date
19 May 2015	Version 2.73 Added additional example messages for ETR Matching.
12 June 2015	Version 2.74 Added *PreventParticipantMatch* (7928) = `P` = Port Owner
13 June 2015	Version 2.75 Added support within TRADE CAPTURE REPORT messages for *SettlType* (63), *SettlDate* (64) and *SettlPrice* (730), as well as for DROP fed EXECUTION REPORT and TRADE CANCEL OR CORRECT messages. Added support for periodic auctions. Added support for *LastMkt* (30).
14 July 2015	Version 2.76 Clarify that settlement prices cannot be amended.