

BATS Chi-X Europe
TRF FIX Specification

Version 1.12
12th April 2014

BATS Trading Limited is a Recognised Investment Exchange regulated by the Financial Conduct Authority. BATS Trading Limited is an indirect wholly-owned subsidiary of BATS Global Markets, Inc. and is a company registered in England and Wales with Company Number 6547680 and registered office at 10 Lower Thames Street, London EC3R 6AF. This document has been established for informational purposes only. None of the information concerning the services or products described in this document constitutes advice or a recommendation of any product or service. To the extent that the information provided in this document constitutes a financial promotion as defined by section 21 of the Financial Services and Markets Act 2000, it is only directed at persons who qualify as a Professional Client or Eligible Counterparty. Persons who do not qualify should not act or rely upon it.

Contents

1 Overview **4**

1.1 Hours of Operation . . . 4
1.2 Timestamps . . . 4
1.3 Symbology . . . 4
1.4 Service Bureau Configuration . . . 5

2 FIX Session Protocol **6**

2.1 Sequence Numbers . . . 6
2.2 Logon . . . 6
2.3 Heartbeat . . . 6
2.4 Test Request . . . 7
2.5 Resend Request . . . 7
2.6 Reject . . . 7
2.7 Sequence Reset . . . 7
2.8 Logout . . . 7

3 Standard FIX Message Header and Trailer **8**

3.1 Header . . . 8
3.2 Trailer . . . 8

4 FIX Application Messages — Participant to BATS **9**

4.1 Trade Capture Report . . . 9
4.2 Example Trade Reporting Messages . . . 13
4.3 Quote . . . 15
4.4 QuoteCancel . . . 16

5 FIX Application Messages — BATS to Participant **17**

5.1 Trade Capture Report Ack . . . 17
5.2 Trade Capture Report . . . 18
5.3 Quote Status Report . . . 19

6 Example Message Flow **20**

6.1 Trade Capture Report Cancellations . . . 20
6.2 Trade Capture Report Amendments . . . 21
6.3 Deferred Publication Trade Reports . . . 22

7 Common Session Level Issues **24**

7.1 Ordered Message Processing . . . 24
7.2 Logon . . . 24
7.3 Message Recovery . . . 24
7.4 Resend Request . . . 25
7.5 Sequence Reset – Gap Fill . . . 25

8 Support **27**

Revision History **27**

1 Overview

This document describes BATS Chi-X Europe's (hereafter, "BATS") interpretation and implementation of the FIX specification for entry of trade reports into the BATS Chi-X Europe Trade Reporting Facility ("TRF").

It is assumed that the reader is familiar with the FIX protocol as described by the FIX Protocol Organisation. BATS supports FIX 4.2 or FIX 4.4 sessions, and a subset of the applicable FIX application messages for trade reporting.

TRF FIX sessions specified by this document allow participants to:

- Enter OTC trade reports using the 'Trade Capture Report' message.
- Enter and amend Systematic Internalizer one-sided or two-sided quotes using the 'Quote' message.
- Cancel SI quotes using the 'Quote Cancel' message, either on a per-symbol basis, or for all current quotes with a single message.
- Enter SI trade reports, using the 'Trade Capture Report' message.
- Receive technical and application level acknowledgements for trade reports via the Trade Capture Report Ack and Trade Capture Report messages.
- Receive application level acknowledgements for SI quotes, quote amendments and quote cancellations via the 'Quote Status Report' message.

1.1 Hours of Operation

Refer to the BATS Chi-X Europe website for hours of operation.

1.2 Timestamps

All FIX timestamps are GMT as per the FIX standard. Participants are expected to synchronise their clocks with an external time source.

1.3 Symbology

BATS accepts three symbologies: MTF Common Symbology (UMTF), RIC and ISIN. Different symbologies may be used on different trade reports, but it is recommended that Participants use the same symbology for all.

If using UMTF to identify a symbol, the Participant:

- **must** set *Symbol* (55) to the UMTF symbol;
- *may optionally* set the *SecurityExchange* (207); and,
- *may optionally* set the *Currency* (15).

If using ISIN to identify a symbol, the Participant:

- **must** set *IDSource* (22) to ISIN (4);
- **must** set *SecurityID* (48) to the ISIN;
- *may optionally* set *SecurityExchange* (207) to note the market in which the ISIN trades;
- **must** set the *Currency* (15) field to identify the currency in which the stock is traded; and,
- *may optionally* set the *Symbol* (55).

If using RIC to identify a symbol, the Participant:

- **must** set *IDSource* (22) to RIC (5);
- **must** set *SecurityID* (48) to the RIC;

- *may optionally* set the *SecurityExchange* (207);
- *may optionally* set the *Currency* (15) field; and,
- *may optionally* set the *Symbol* (55).

If using ISIN or RIC to identify a symbol in *SecurityID* (48), and opting to also send *Symbol* (55), the *Symbol* (55) may be specified as the UMTF symbol, the *SecurityID* (48), the RIC or the Ticker code.

A RIC in either *SecurityID* (48) or *Symbol* (55), may be supplied as either a BATS or primary market RIC.

When specifying an optional value as noted above, the value specified must match the value in BATS' symbol database. Otherwise, the order will be rejected (subject to notes on "unknown symbol handling" below).

Acknowledgement messages will always respond with the same symbology as was sent in the corresponding New Order Single message.

For trades reported using UMTF or RIC to identify a symbol, that symbol must be known to BATS, otherwise the trade report will be rejected. For trades reported using ISIN symbology, should the ISIN be unknown to BATS, the trade report will be accepted and enter "unknown symbol handling".

Should the ISIN be known to BATS, but the combination of ISIN and currency not be known to BATS, the trade report will be accepted and enter "unknown symbol handling".

Given a major currency for an known ISIN listed in a minor currency the currency will be automatically converted and the price scaled as appropriate.

For symbols that have more than one ISIN/currency combination the preferred listing will be used for OTC and SI trade reports.

Trade reports entering "unknown symbol handling" will not be distributed via market data, but will be made widely available from our website.

For additional information about BATS' symbology, see the BATS Chi-X Europe Market Guide.

1.4 Service Bureau Configuration

Service Bureaus require special configuration. *OnBehalfOfCompID* (115) must be set for messages sent to BATS. Reports with an unknown *OnBehalfOfCompID* (115) will be rejected. *TradeReportID* (571) values are required to be unique only within a given *OnBehalfOfCompID* (115). Corresponding acknowledgement messages sent by BATS will have the *DeliverToCompID* (128) set. **Trade reports or SI Quotes must be canceled or replaced using the same *OnBehalfOfCompID* (115) as was sent on the original message.**

2 FIX Session Protocol

BATS TRF sessions can use either FIX 4.2 or FIX 4.4 session protocols. The Participant will be provided with a *SenderCompID* (49) and *SenderSubID* (50) that must be sent on every message. The *TargetCompID* (56) for all messages the Participant sends will be `BATS`, while the *TargetSubID* (57) is `TEST` for the BATS test system and `PROD` for the BATS production system. All messages the Participant receives will have the sender and target fields swapped, as per the FIX specification.

The following session messages are supported in both directions:

Message	Type	Comment
Logon	`A`	Begin session (or resume a broken session)
Heartbeat	`0`	
Test Request	`1`	
Resend Request	`2`	
Reject	`3`	Malformed message or improper session level handling
Sequence Reset	`4`	Both Gap Fill (*GapFillFlag* (123) = `Y`) and Reset
Logout	`5`	used to gracefully close session

2.1 Sequence Numbers

Sequence numbers, both inbound and outbound, will be reset to one each night during the down time.

Messages are processed in sequence order. Behind sequence messages (other than Sequence Reset — Reset) cause immediate logout. Ahead of sequence messages (other than a Resend Request) trigger a message recovery via a Resend Request.

2.2 Logon

The logon must be the first message sent by the Participant after the TCP connection is established. *EncryptMethod* (98) is ignored (FIX level encryption is not supported).

The IP address of the Participant, the *SenderCompID* (49), *SenderSubID* (50), *TargetCompID* (56) (`BATS`) and *TargetSubID* (57) (`TEST` or `PROD`) will be validated. If validation fails, the connection will be dropped without a reject (to avoid corrupting the Participant's sequence in the case that the Participant merely mistakenly connected to the wrong port).

If the connection is unexpectedly broken, upon reconnection, the Participant may receive a login reply with a sequence number greater than expected. This means that in-flight messages were missed (likely important execution reports). The Participant should issue a Resend request to retrieve the missed messages.

Similarly, BATS will issue a Resend Request to the Participant for messages that it missed. The Participant may wish to send gap fill messages in place of new orders to avoid submission of potentially stale orders.

HeartBtInt (108) must be specified by the Participant in the Logon message. This value will be clamped between five and 300 seconds and returned in the Logon reply message. We recommend using as low a value as the reliability and latency of your telecommunications channel will allow.

The BATS FIX 4.4 session protocol does not implement the optional support for 'Logon Message NextExpectedMsgSeqNum Processing'.

2.3 Heartbeat

A Heartbeat message should be sent if the agreed upon *HeartBtInt* (108) has elapsed since the last message sent. If any message has been sent during the preceding *HeartBtInt* (108), a Heartbeat message need not be sent.

2.4 Test Request

If *HeartBtInt* + 1 seconds have elapsed since the last message received, a Test Request should be issued. If another *HeartBtInt* + 1 seconds go by without receiving a message, the TCP connection should be dropped. This ensures that a broken TCP connection will be detected even if the TCP stack doesn't notice (this has been observed to happen in WAN environments, particularly when a VPN is involved).

2.5 Resend Request

A Resend Request message should be processed even if it is received ahead of sequence. Only after resending the requested range (all market *PossDup* (43) = `Y`), including any gap fills) should Resend Request be issued in the opposite direction.

As discussed in the FIX 4.2 specification, it is possible to send an open or closed sequence range in a Resend Request (an open range uses sequence zero as the *EndSeqNo* (16)). BATS will honor either type of request, but will always issue Resend Requests with a closed sequence range.

2.6 Reject

Session level rejects (*MsgType* (35) = `3`) are used to indicate violations of the session protocol, or missing (or mangled) fields. These are to be expected during development and certification while the Participant's systems are being adapted for BATS, but should be extremely rare in production. Application layer rejects (via Trade Capture Ack, Trade Capture Report or Quote Status Report) are normal and should be handled separately. See FIX Application Messages - BATS to Participant (p. 17) for more details.

2.7 Sequence Reset

Sequence Reset — Gap Fill messages (*GapFillFlag* (123) = `Y`) must be received in sequence. Any messages (including Gap Fills) sent in response to a Resend Request should have *PossDup* (43) = `Y`.

Sequence Reset — Reset (*GapFillFlag* (123) $\neq$ `Y`) is used only as a last resort, and always by human intervention, to allow an otherwise hopelessly confused session to be resumed. In these cases, all chances at automatic message recovery are lost.

2.8 Logout

Either side may issue a logout to gracefully close the session. The side that issues the logout should process messages normally until it sees the logout reply, and then break the TCP connection. BATS will typically only request logout after the scheduled end of FIX session.

3 Standard FIX Message Header and Trailer

3.1 Header

Tag	Name	Description
8	*BeginString*	`FIX.4.2` or `FIX.4.4` Must be the first field in the message.
9	*BodyLength*	Length of message following *BodyLength* field up to and including the delimiter preceding the *CheckSum* (10) field. Must be the second field in the message.
35	*MsgType*	Must be the third field in the message.
34	*MsgSeqNum*	Sequential sequence number for the session.
43	*PossDupFlag*	Indicates a message resent from the admin level (has a duplicate sequence number). Defaults to `N`.
49	*SenderCompID*	ID of sender. Assigned by BATS for messages sent to BATS. (*TargetCompID* (56) for messages from BATS.)
56	*TargetCompID*	ID of destination. `BATS` for messages sent to TRF ports. (*SenderCompID* (49) for messages from BATS.)
57	*TargetSubID*	Sub ID of destination. `TEST` for messages sent to the BATS test system. `PROD` for messages sent to the BATS production system. (*SenderSubID* (50) for messages from BATS.)
97	*PossResend*	Possible resend flag. BATS does not support *PossResend* (97) = `Y` on the TRF system.
115	*OnBehalfOfCompID*	Service bureau use. Identifies end-client on messages **to** BATS. Must be identifier known to BATS.
116	*OnBehalfOfSubID*	End-client sub identifier. Four characters, alphanumeric, otherwise not validated. Recorded and returned in *DeliverToSubID* (129).
122	*OrigSendingTime*	For messages with *PossDupFlag* (43) = `Y`, indicates time that message was first sent. If enabled at the port or firm level, timestamps will be sent with microsecond resolution.
128	*DeliverToCompID*	Service bureau use. Identifies end-client on message **from** BATS. Must be BATS approved identifier.
129	*DeliverToSubID*	Returns *OnBehalfOfSubID* (116) optionally sent by client.

3.2 Trailer

Tag	Name	Description
10	*CheckSum*	Modulo 256 checksum of all characters in the message up to and including the delimiter preceding the *CheckSum* field. Three digits with leading zeroes if necessary.

4 FIX Application Messages — Participant to BATS

4.1 Trade Capture Report

The Trade Capture Report is used to submit OTC trade reports in a number of scenarios, including:

- Trade reports for the TDM service.
- Systematic Internalizer trade reports submitted under the "SI" service.
- Dark MTF trade reporting.

The model supported is as described in the FIX 5.0 (SP2) specification in the *Two-Party Reporting* workflow diagram of the Trade Capture Reporting section, for the specific case where there is a single counterparty.

Whilst we make use of FIX 4.4 and FIX 5.0 messages/tags, these are handled as extensions and operate over either a FIX 4.2 or FIX 4.4 session.

When a new trade report is accepted, a *TradeID* is returned in the corresponding Trade Report Acknowledgement and Trade Capture Report confirmation messages. Where applicable, such trade reports may be cancelled or amended by specifying the *TradeID*.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `AE`
15	*Currency*	Required if *IDSource* (22) = `4` (ISIN). If *Currency* (15) is included when other symbology is used, it must match the currency expected by BATS for the given symbol.
18	*ExecInst*	This field must not be supplied on trade reports to the TRF.
22	*IDSource*	Values supported by BATS TRF: `4` = ISIN `5` = RIC Required if *Symbol* (55) is not set.
31	*LastPx*	Traded price.
32	*LastShares*	Quantity of shares traded.
48	*SecurityID*	ISIN, or RIC if *IDSource* (22) is set.
55	*Symbol*	Security symbol. See Symbology (p. 4) for additional notes.
60	*TransactTime*	Optional. Indicates the date and time the trade took place.
75	*TradeDate*	Optional. If specified, must match the date component of *TransactTime* (60).
150	*ExecType*	Must be `F` = Trade
207	*SecurityExchange*	Used when *IDSource* (22) = `4` (ISIN) to identify a specific market. If present must be a valid Reuters exchange code or ISO MIC code. For TDM and SI trade reports, may optionally be left blank to use the primary line as designated by BATS.
487	*TradeReportTransType*	Specifies whether this trade report is new, a cancellation, an amendment or a release. Trades reported under the TDM service may be cancelled or amended by the participant. Trades that are currently being delayed from publication can be released for immediate publication. Defaults to 'new' if unspecified. `0` = New `1` = Cancel `2` = Replace `3` = Release

570	*PreviouslyReported*	Indicates this trade was previously reported. `N` or missing means it was not previously reported and should be printed on the market data feed. `Y` means it was previously reported and should not be printed.
571	*TradeReportID*	Day-unique ID chosen by client. 20 characters or less. Characters in ASCII range 33–126 are allowed, except for comma, semicolon, and pipe. If the *TradeReportID* matches a live trade report (one that has been acked, but not confirmed or declined), it will be rejected as duplicate. **Note: BATS only enforces the uniqueness of *TradeReportID* values among currently live trade reports. However, we *strongly* recommend that you keep your TradeReportID values day unique.**
574	*MatchType*	Where *VenueType* (1430) = `X` (off book), this field models the MMT Level 2 'Trading Mode' field, and takes the following values: `1` = Trade Reporting (Off-Exchange) `3` = Trade Reporting (On-Exchange) `9` = Trade Reporting (Systematic Internalizer)
625	*TradingSessionSubID*	Models the MMT Level 2 'Trading Mode' field for scenarios where *VenueType* (1430) is not '`X`' (off book). Use *MatchType* (574) instead, where *VenueType* (1430) = `X`. The following are valid values: `2` = Scheduled Opening Auction `4` = Scheduled Closing Auction `6` = Scheduled Intraday Auction `(9)` = Unscheduled Auction `3` = Continuous Trading `5` = Post Trading `(10)` = Out of Main Session Trading Note: Values 9 and 10 are not yet in a FIX standard, but have been proposed by the FPL EMEA Trade Data Standardisation Working Group for this purpose.
828	*TrdType*	This field corresponds to the MMT Level 3.1 field 'Transaction Category'. `0` = Regular Trade (aka Plain-Vanilla Trade) `30` = Special price (aka Trade with Conditions) `59` = Dark Trade `60` = Technical Trade `61` = Give-up / Give-in trade
829	*TrdSubType*	This optional field corresponds to the MMT Level 3.3 field 'Crossing Trade Indicator'. Agency Cross trades may be indicated by setting *TrdSubType* (829) = `37`. Other values are invalid.
855	*SecondaryTrdType*	This optional field corresponds to the MMT Level 3.5 field 'Benchmark Indicator'. Benchmark trades may be indicated by setting *SecondaryTrdType* (855) = `58`. Other values are invalid. Note: *SecondaryTrdType* (855) = `58` is not yet in a FIX standard, but has been proposed by the FPL EMA Trade Data Standardisation Working Group for this purpose.

856	*TradeReportType*	Must be `0` (Submit)
1003	*TradeID*	Used to specify a previously reported trade to be amended, cancelled or released. Mandatory when *TradeReportTransType* (487) = `1, 2 or 3`, must be absent when *TradeReportTransType* (487) = `0`.
1123	*TradeHandlingInstr*	Must be `1` (Two-Party Report)
1390	*TradePublishIndicator*	This field corresponds to the MMT Level 4 field 'Publication Mode', and is used by the participant to request that the publication be delayed. It is ignored if the trade does not qualify for delayed publication. This field may not be amended, however trades currently being delayed may be released prior to their maximum delay duration using *TradeReportTransType* (487) = `3`. Supported values: `1` = Publish trade (immediately) `2` = Deferred Publication *TradePublishIndicator* (1390) is optional, and defaults to `1`.
1430	*VenueType*	Indicates the type of venue on which this trade occurred. This field models the MMT Level 1 field 'Market Mechanism', and has the following possible values: `B` = Central Limit Order Book `Q` = Quote Driven Market `D` = Dark Order Book `X` = Off Book
1838	*NoTradePriceConditions*	If present, can only take value 1, and indicates the presence of a single *TradePriceCondition* (1839) field.
1839	*TradePriceCondition*	Optional. Used to indicate that the ex/cum dividend state of the trade. This field corresponds to the MMT Level 3.6 'Ex/Cum Dividend Indicator'. Supported values are: `0` = Cum Dividend `2` = Ex Dividend
2405	*ExecMethod*	Optional. Used to indicate that the method by which the trade was executed. This field corresponds to the proposed MMT Level 3.7 'Execution Method'. The following values are supported: `0` = Unspecified (default) `1` = Manual `2` = Automated
552	*NoSides*	Indicates the number of instances of the repeating group *TrdCapRptSideGrp* to follow.

Repeating Group *TrdCapRptSideGrp* must occur the number of times specified in *NoSides* (552)

54	*Side*	Must be first field in repeating-group `1` = Buy `2` = Sell `8` = Cross
1	*Account*	Optional. Reflected back on Trade Capture Report confirmed and declined messages. 16 characters or less (ASCII 33–126).
447	*PartyIDSource*	Must always be `D` (Proprietary / Custom Code)
452	*PartyRole*	Specifies the role of the party to the trade. At this time, this field is mandatory on trades reported to the TRF, and must be specified as *PartyRole* (452) = `7`.
453	*NoPartyIDs*	Must always be `1`
448	*PartyID*	The BATS Participant ID (4 uppercase letters).
528	*OrderCapacity*	Optional. `A` = Agency `P` = Principal (default) `R` = Riskless

	Standard Message Trailer	

4.2 Example Trade Reporting Messages

4.2.1 OTC Trade Reporting

Below illustrates an example of a standard off-book trade report. Firm ABCD is reporting an OTC sell to an unspecified party.

- *BeginString* (8) = `FIX.4.4`
- *BodyLength* (9) = `100` [1]
- *MsgType* (35) = `AE` - Trade Capture Report
- *MsgSeqNum* (34) = `7`
- *SenderCompID* (49) = `ABCD` - assigned by BATS
- *TargetCompID* (56) = `BATS`
- *SenderSubID* (50) = `0014` - assigned by BATS
- *TargetSubID* (57) = `TEST`
- *TradeReportID* (571) = `1234`
- *TradeReportTransType* (487) = `0`
- *TradeReportType* (856) = `0`
- *VenueType* (1430) = `X` - Off Book
- *MatchType* (574) = `1` - privately negotiated (off-book) trade
- *TrdType* (828) = `0` - Regular Trade
- *TradeHandlingInstr* (1123) = `1`
- *Currency* (15) = `GBX`
- *IDSource* (22) = `4`
- *SecurityID* (48) = `GB012345678`
- *SecurityExchange* (207) = `L`
- *LastShares* (32) = `5500`
- *LastPrice* (31) = `123`
- *NoSides* (552) = `1`
- *Side* (54) = `2` - Sell
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `ABCD`
- *PartyRole* (452) = `7`
- *CheckSum* (10) = `234` [1]

4.2.2 Dark MTF trade reports

Trade reports submitted by a regulated MTF operating a dark pool are expected to identify themselves as dark trades using *TrdType* (828) = `59`. Again, only one instance of *TrdCapRptSideGrp* is applicable, with *Side* (54) = `8` representing a cross, and *PartyID* (448) = `i`dentifying the Dark MTF.

- *VenueType* (1430) = `D` - Dark Order Book
- *TradingSessionSubID* (625) = `3` - Continuous Trading
- *TrdType* (828) = `59` - Dark Trade
- *NoSides* (552) = `1`
- *Side* (54) = `8` - Cross
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `ABCD` - representing the Dark MTF
- *PartyRole* (452) = `7`

[1] In these examples, *BodyLength* and *Checksum* example values have not been accurately computed.

4.2.3 Systematic Internaliser Trade Reporting

SI trades are identified with *MatchType* (574) = `9`. Such trade reports need only contain a single *TrdCapRptSideGrp*, confirming the systematic internaliser as the party, and specifying *Side* (54) = `8` to indicate a cross.

- *VenueType* (1430) = `X` - Off Book
- *MatchType* (574) = `9` - Systematic Internalizer
- *TrdType* (828) = `0` - Plain-vanilla trade
- *NoSides* (552) = `1`
- *Side* (54) = `8` - Cross
- *NoPartyIDs* (453) = `1`
- *PartyID* (448) = `ABCD` - representing the Systematic Internaliser
- *PartyRole* (452) = `7`

4.3 Quote

The Quote message may be used by Systematic Internalisers to maintain their quotes under their MiFID pre-trade transparency obligations.

Subsequent Quote messages may be sent to amend the firms quotes. Each Quote message should include a new, day-unique *QuoteID* field. A one-sided quote may be submitted by sending (for example) *BidPx* (132) = `0` and *BidSize* (134) = `0`. A Quote which omits the *BidPx* and *BidSize* fields will leave the bid-side quote unchanged. Sending *BidPx* without sending *BidSize*, or vice versa, is invalid (even if the included field is sent with value `0`).

Quotes may be cancelled by sending a QuoteCancel message, or a Quote message with zero sent for both price and size.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `S`
117	*QuoteID*	Mandatory unique ID chosen by client for a Quote or QuoteCancel. 18 characters or less. Characters in ASCII range 33–126 are allowed, except for comma, semicolon, and pipe. **Note: BATS only enforces the uniqueness of *QuoteID* values among currently live quotes. However, we *strongly* recommend that you keep your QuoteID values day unique.**
55	*Symbol*	Security symbol. See Symbology (p. 4) for additional notes.
48	*SecurityID*	ISIN, or RIC if *IDSource* (22) is set.
22	*IDSource*	Values supported by BATS TRF: `4` = ISIN `5` = RIC Required if *Symbol* (55) is not set.
207	*SecurityExchange*	Used when *IDSource* (22) = `4` (ISIN) to identify a specific market. If present must be a valid Reuters exchange code or ISO MIC code. For TDM and SI trade reports, may optionally be left blank to use the primary line as designated by BATS.
132	*BidPx*	Specifies the bid quote price. If omitted, indicates the bid quote is not to be changed, and *BidSize* (134) must also be omitted. If *BidPx* (132) = `0`, indicates the bid quote is to be cancelled, and *BidSize* (134) = `0` must also be present.
133	*OfferPx*	Specifies the offer quote price. If omitted, indicates the offer quote is not to be changed, and *OfferSize* (135) must also be omitted. If *OfferPx* (133) = `0`, indicates the offer quote is to be cancelled, and *OfferSize* (135) = `0` must also be present.
134	*BidSize*	The quantity of the bid quote. Must be zero when cancelling a quote.
135	*OfferSize*	The quantity of the offer (ask) quote. Must be zero when cancelling a quote.
15	*Currency*	Required if *IDSource* (22) = `4` (ISIN). If *Currency* (15) is included when other symbology is used, it must match the currency expected by BATS for the given symbol.
	Standard Message Trailer	

4.4 QuoteCancel

The QuoteCancel message may be used to cancel a previously accepted Quote message. One QuoteCancel message must be sent for each symbol which requires quotes to be cancelled. Alternatively, all quotes can be cancelled in one message, using *QuoteCancelType* (298) = `4`. QuoteCancel messages should contain a new *QuoteID*, unique for the day across all Quote and QuoteCancel messages.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `Z`
117	*QuoteID*	Mandatory unique ID chosen by client for a Quote or QuoteCancel. 18 characters or less. Characters in ASCII range 33–126 are allowed, except for comma, semicolon, and pipe. **Note: BATS only enforces the uniqueness of *QuoteID* values among currently live quotes. However, we *strongly* recommend that you keep your QuoteID values day unique.**
298	*QuoteCancelType*	Supported values: `1` = Cancel for Symbol `4` = Cancel for All Quotes This field is optional, and defaults to `1`. When *QuoteCancelType* (298) = `4`, the request will be acknowledged with one `QuoteStatusReport` message for each existing quote.
295	*NoQuoteEntries*	Must be 1 if *QuoteCancelType* (298) = `1` (Symbol), 0 if *QuoteCancelType* (298) = `4` (All).
Repeating Group *QuoteCancelRptGrp* must occur the number of times specified in *NoQuoteEntries* (295)		
55	*Symbol*	Security symbol. See Symbology (p. 4) for additional notes.
48	*SecurityID*	ISIN, or RIC if *IDSource* (22) is set.
22	*IDSource*	Values supported by BATS TRF: `4` = ISIN `5` = RIC Required if *Symbol* (55) is not set.
207	*SecurityExchange*	Used when *IDSource* (22) = `4` (ISIN) to identify a specific market. If present must be a valid Reuters exchange code or ISO MIC code. For TDM and SI trade reports, may optionally be left blank to use the primary line as designated by BATS.
15	*Currency*	Required if *IDSource* (22) = `4` (ISIN). If *Currency* (15) is included when other symbology is used, it must match the currency expected by BATS for the given symbol.
	Standard Message Trailer	

5 FIX Application Messages — BATS to Participant

5.1 Trade Capture Report Ack

The Trade Capture Report Ack is sent by BATS to acknowledge the receipt of a Trade Capture Report. It is a technical-level ack, the Trade/Cancel/Amend/Release is not considered to have fully succeeded until a Trade Capture Report is sent with *TradeHandlingInstr* (1123) of `0` (TradeConfirmation).

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `AR`
15	*Currency*	Copied from the incoming `TradeCaptureReport`, if present.
22	*IDSource*	Copied from the incoming `TradeCaptureReport`, if present.
48	*SecurityID*	Copied from the incoming `TradeCaptureReport`, if present.
55	*Symbol*	Copied from the incoming `TradeCaptureReport`, if present.
58	*Text*	If present, indicates reason for the message. Format is one letter reason code followed by colon and space followed by free form text message. Reason codes are: `A` = Admin `D` = Duplicate *TradeReportID* `m` = Market Access Risk Limit Exceeded `Y` = Symbol Not Supported `Z` = Unforseen Reason
60	*TransactTime*	Copied from the incoming `TradeCaptureReport`.
75	*TradeDate*	Copied from the incoming `TradeCaptureReport`.
150	*ExecType*	Copied from the incoming `TradeCaptureReport`.
207	*SecurityExchange*	Copied from the incoming `TradeCaptureReport`, if present.
487	*TradeReportTransType*	Copied from the incoming `TradeCaptureReport`.
571	*TradeReportID*	Copied from the incoming `TradeCaptureReport`.
574	*MatchType*	Copied from the incoming `TradeCaptureReport`.
625	*TradingSessionSubID*	Copied from the incoming `TradeCaptureReport`.
828	*TrdType*	Copied from the incoming `TradeCaptureReport`.
829	*TrdSubType*	Copied from the incoming `TradeCaptureReport`.
855	*SecondaryTrdType*	Copied from the incoming `TradeCaptureReport`.
856	*TradeReportType*	Copied from the incoming `TradeCaptureReport`.
939	*TrdRptStatus*	Will be `0` (Accepted) or `1` (Rejected)
1003	*TradeID*	Copied from the incoming `TradeCaptureReport`, if present.
1123	*TradeHandlingInstr*	Copied from the incoming `TradeCaptureReport`.
1390	*TradePublishIndicator*	Copied from the incoming `TradeCaptureReport`.
1430	*VenueType*	Copied from the incoming `TradeCaptureReport`.
1838	*NoTradePriceConditions*	Copied from the incoming `TradeCaptureReport`.
1839	*TradePriceCondition*	Copied from the incoming `TradeCaptureReport`.
2405	*ExecMethod*	Copied from the incoming `TradeCaptureReport`, if present.
	Standard Message Trailer	

5.2 Trade Capture Report

The 'Trade Capture Report' is sent from BATS to the participant in order to confirm that a Trade Capture Report has been fully processed. It is a business-level confirmation as distinct from the technology level acknowledgement sent as a 'Trade Capture Report Ack'.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `AE`
15	*Currency*	Copied from the incoming `TradeCaptureReport`, if present.
22	*IDSource*	Copied from the incoming `TradeCaptureReport`, if present.
31	*LastPx*	Traded price.
32	*LastShares*	Copied from the incoming `TradeCaptureReport`.
48	*SecurityID*	Copied from the incoming `TradeCaptureReport`, if present.
55	*Symbol*	Copied from the incoming `TradeCaptureReport`, if present.
58	*Text*	If present, indicates reason for the message. Format is one letter reason code followed by colon and space followed by free form text message. Reason codes are: `A` = Admin `D` = Duplicate *TradeReportID* `m` = Market Access Risk Limit Exceeded `Y` = Symbol Not Supported `Z` = Unforseen Reason
60	*TransactTime*	Copied from the incoming `TradeCaptureReport`.
75	*TradeDate*	Copied from the incoming `TradeCaptureReport`.
150	*ExecType*	Copied from the incoming `TradeCaptureReport`.
207	*SecurityExchange*	Copied from the incoming `TradeCaptureReport`, if present.
375	*ContraBroker*	`BATS`: Trade Reported on BATS TRF
487	*TradeReportTransType*	Copied from the incoming `TradeCaptureReport`.
570	*PreviouslyReported*	Copied from the incoming `TradeCaptureReport`.
571	*TradeReportID*	Unique identifier for the trade report confirm as provided by BATS
572	*TradeReportRefID*	Contains the TradeReportID of the original trade capture report to which this message relates
573	*MatchStatus*	Will be `0` (Matched) for confirm, and `1` (Unmatched) for a decline
574	*MatchType*	Copied from the incoming `TradeCaptureReport`.
625	*TradingSessionSubID*	Copied from the incoming `TradeCaptureReport`.
828	*TrdType*	Copied from the incoming `TradeCaptureReport`.
829	*TrdSubType*	Copied from the incoming `TradeCaptureReport`.
855	*SecondaryTrdType*	Copied from the incoming `TradeCaptureReport`.
856	*TradeReportType*	Will be `2` (Accept) for a confirm, `3` (Decline) for a decline and `0` (Submit) for an unsolicited change.
1003	*TradeID*	Id representing the trade, as seen on outbound market data. Allocated by BATS. Required to amend, cancel or release a report.
1123	*TradeHandlingInstr*	Will be `0` (Trade Confirmation)
1390	*TradePublishIndicator*	Will be 2 (Deferred Publication) if deferment is requested and the trade is eligible for such. Otherwise, will be 1 (Publish trade (immediately))
1430	*VenueType*	Copied from the incoming `TradeCaptureReport`.
1838	*NoTradePriceConditions*	Copied from the incoming `TradeCaptureReport`, if present.
1839	*TradePriceCondition*	Copied from the incoming `TradeCaptureReport`, if present.
2405	*ExecMethod*	Copied from the incoming `TradeCaptureReport`, if present.

7570	*RptTime*	Indicates the time at which a deferred trade report will be automatically published. Where *RptTime* falls outside of the systems operating time, the report will be published during operating hours on the next trading day. When no deferral is requested, or when the trade does not qualify for a deferral, any time returned will match *TransactTime* (60).
552	*NoSides*	Indicates the number of instances of the repeating group *TrdCapRptSideGrp* to follow.
Repeating Group *TrdCapRptSideGrp* must occur the number of times specified in *NoSides* (552)		
...	...	Entire block copied from incoming TradeCaptureReport
7772	*CentralCounterparty*	The CCP handling this trade leg for a confirm, and not present for a decline: NONE = No Clearing
	Standard Message Trailer	

5.3 Quote Status Report

A 'Quote Status Report' message is sent to the participant to acknowledge acceptance or otherwise of each 'Quote' or 'Quote Cancel' message.

Tag	Name	Description
	Standard Message Header	*MsgType* (35) = `AI`
117	*QuoteID*	Copied from the corresponding `Quote / QuoteCancel`, if applicable. Unsolicited QuoteStatus messages can be sent due to system events, and in such circumstances, *QuoteID* may be omitted.
55	*Symbol*	Copied from the incoming `Quote/QuoteCancel`, if present.
48	*SecurityID*	Copied from the incoming `Quote/QuoteCancel`, if present.
22	*IDSource*	Copied from the incoming `Quote/QuoteCancel`, if present.
207	*SecurityExchange*	Copied from the incoming `Quote/QuoteCancel`, if present.
15	*Currency*	Copied from the incoming `Quote/QuoteCancel`, if present.
132	*BidPx*	For valid Quote messages (*QuoteStatus* (297) = `0 or 1`), the new price and size fields are returned in the corresponding QuoteStatus message. These may be zero if there is no applicable quote on this side. Typically, these will match the values sent in the corresponding Quote, unless that Quote message opted to change one side of the quote only.
133	*OfferPx*	The quote's offer price, or zero. See *BidPx* (132) for more details.
134	*BidSize*	The quote's bid quantity, or zero. See *BidPx* (132) for more details.
135	*OfferSize*	The quote's offer quantity, or zero. See *BidPx* (132) for more details.
297	*QuoteStatus*	Indicates the acceptance or otherwise of a Quote or QuoteCancel message. `0`: Accepted - indicates acceptance of a Quote message. `1`: Cancelled - sent in respose to a successful QuoteCancel message. `5`: Rejected - sent in respose to a Quote or QuoteCancel message, indicating the message could not be accepted.
58	*Text*	If present, indicates a reason the applicable Quote or QuoteCancel message could not be accepted.
	Standard Message Trailer	

6 Example Message Flow

6.1 Trade Capture Report Cancellations

Below illustrates an example of key elements of the message flow for cancellation of previously confirmed trade captures.

Participant to BATS:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeID* (1003) = `ABCD1234` - The TradeID for the confirmed trade report
- *TradeReportTransType* (487) = `1` - Cancel

BATS to Participant (Technical Ack) - if rejected:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `1` - Rejected
- *Text* (58) = `Reason for reject`

BATS to Participant (Technical Ack) - if accepted:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `0` - Accepted

BATS to Participant - if cancellation is declined:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `3` - Decline
- *Text* (58) = `Reason for decline`

BATS to Participant - if cancellation is confirmed:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `1` - Cancel
- *TradeReportType* (856) = `2` - Accept

6.2 Trade Capture Report Amendments

Below illustrates an example of key elements of the message flow for amendment of previously confirmed trade captures.

Participant to BATS:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeID* (1003) = `ABCD1234` - The TradeID for the confirmed trade report
- *TradeReportTransType* (487) = `2` - Replace

BATS to Participant (Technical Ack) - if rejected:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `1` - Rejected
- *Text* (58) = `Reason for reject`

BATS to Participant (Technical Ack) - if accepted:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `0` - Accepted

BATS to Participant - if amendment is declined:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `2` - Replace
- *TradeReportType* (856) = `3` - Decline
- *Text* (58) = `Reason for decline`

BATS to Participant - if amendment is confirmed:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `2` - Replace
- *TradeReportType* (856) = `2` - Accept

6.3 Deferred Publication Trade Reports

Customers reporting trades subject to deferred publication have the option of performing the deferment within their own systems, or asking BATS to perform the deferment for them. To provide a consistent interface and to allow BATS to distinguish between deferment eligible trades that have been delayed in the Participant's system and large, deferment-ineligible trades that have been reported late, Participants must flag trade reports appropriately. All trade reports subject to deferment must be reported with *TradePublishIndicator* (1390) = `2` to indicate that the trade is believed to be deferment eligible and should not be regarded as late (unless reported after the end of eligible deferment period).

BATS will automatically hold onto the trade for the remainder of the eligible deferment period. To release the trade, follow the trade report with an immediate release (using *TradeReportTransType* (487) = `3`).

Below illustrates an example of key elements of the message flow for deferred publication of trades captures.

Participant to BATS:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradePublishIndicator* (1390) = `2` - Deferred Publication
- *TransactTime* (60) = `Time of Trade` - As long as this is within the acceptable deferment period, the trade will not be regarded as late

BATS to Participant (Technical Ack) - if rejected:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `1` - Rejected
- *Text* (58) = `Reason for reject`

BATS to Participant (Technical Ack) - if accepted:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `0` - Accepted

BATS to Participant - if report is declined:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `3` - Decline
- *Text* (58) = `Reason for decline`

BATS to Participant - if report is confirmed and deferment permitted:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `2` - Accept
- *TradePublishIndicator* (1390) = `2` - Deferred Publication

BATS to Participant - if report is confirmed and deferment is not permitted:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `0` - New
- *TradeReportType* (856) = `2` - Accept
- *TradePublishIndicator* (1390) = `1` - Publish trade (immediately)
- *Text* (58) = `A: Trade accepted, but ineligible for deferment` - Exact text may vary

Then, once the Participant would like the deferred trade released to the market (note - this may be immediately if the Participant has held onto the trade for the deferment period).

Participant to BATS:

- *MsgType* (35) = `AE` - Trade Capture Report
- *TradeID* (1003) = `ABCD1234` - The TradeID for the confirmed trade report
- *TradeReportTransType* (487) = `3` - Release

BATS to Participant (Technical Ack) - if rejected:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `1` - Rejected
- *Text* (58) = `Reason for reject`

BATS to Participant (Technical Ack) - if accepted:

- *MsgType* (35) = `AR`
- *TrdRptStatus* (939) = `0` - Accepted

BATS to Participant - if release is declined:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `3` - Release
- *TradeReportType* (856) = `3` - Decline
- *Text* (58) = `Reason for decline`

BATS to Participant - if release is confirmed:

- *MsgType* (35) = `AE`
- *TradeReportTransType* (487) = `3` - Release
- *TradeReportType* (856) = `2` - Accept

7 Common Session Level Issues

BATS uses FIX 4.2 or 4.4 as specified by the applicable FPL Documents (Version 4.2 with Errata 20010501 or Version 4.4 with Errata 20030618) with business level extensions as described in this document. The session level of the FPL specification is followed as closely as possible.

The errata for version 4.2 cleared up many session level ambiguities present in the earlier version 4.2 (March 1, 2000). The following sections emphasize a few common problem areas in implementations of the FIX session protocol.

Typographical conventions:

- Anchor locations in the FPL document are shown in blue.
- Text in **bold** was emphasized in the original FPL specification.
- Emphasis added by BATS is shown in purple.
- Notes added by BATS are shown in green.

7.1 Ordered Message Processing

From Financial Information Exchange Protocol/FIX Message Format and Delivery/Ordered Message Processing:

> The FIX protocol assumes complete ordered delivery of messages between parties. Implementers should consider this when designing message gap fill processes. Two options exist for dealing with gaps, either request all messages subsequent to the last message received or ask for the specific message missed while maintaining an ordered list of all newer messages. For example, if the receiver misses the second of five messages, the application could ignore messages 3 through 5 and generate a resend request for messages 2 through 5, **or**, preferably 2 through 0 (where 0 represents infinity). Another option would involve saving messages 3 through 5 and resending only message 2. In both cases, messages 3 through 5 should not be processing before message 2.

7.2 Logon

From Financial Information Exchange Protocol/Session Protocol/Logon:

> After the initiator has been authenticated, the acceptor will respond immediately with a confirming *Logon* message.

7.3 Message Recovery

From Financial Information Exchange Protocol/Session Protocol/Message Recovery:

> When the incoming sequence number does not match the expected number, corrective processing is required. Note that the SeqReset-**Reset** message ([BATS: this refers only to *GapFillFlag* (123) = `N`] used only to recover from a disaster scenario vs. normal resent request processing) is an exception to this rule as it should be processed without regards to its *MsgSeqNum* (34). **If the incoming message has a sequence number less than expected and the *PossDupFlag* (43) is not set, it indicates a serious error. It is strongly recommended that the session be terminated and manual intervention be initiated**. If the incoming sequence number is greater than expected, it indicates that messages were missed and retransmission of the messages is requested via the *Resend Request* (see earlier section, *Ordered Message Processing*).
>
> ...

If there are consecutive administrative messages to be resent, it is suggested that only one *SeqReset-GapFill* message be sent in their place. The sequence number of the *SeqReset-GapFill* message is the next expected outbound sequence number. The *NewSeqNo* (36) field of the GapFill message contains the sequence number of the highest administrative message in the group plus 1. For example, during a Resend operation there are 7 sequential administrative messages waiting to be resent. They start with sequence number 9 and end with sequence number 15. Instead of transmitting 7 GapFill messages (which is perfectly legal, but not network friendly), a *SeqReset-GapFill* message may be sent. **The sequence number of the Gap Fill message is set to 9 because the remote side is expecting that as the next sequence number.** The *NewSeqNo* (36) field of the Gap Fill message contains the number 16, because that will be the sequence number of the next message to be transmitted.

Sequence number checking is a vital part of FIX session management. However, a discrepancy in the sequence number stream is handled differently for certain classes of FIX messages. The table below lists the actions to be taken when the incoming sequence number is greater than the expected incoming sequence number.

> **NOTE: In all cases except the Sequence Reset – Reset message, the FIX session should be terminated if the incoming sequence number is less than expected and the *PossDupFlag* (43) is not set. A *Logout* message with some descriptive text should be sent to the other side before closing the session.**

Response by Message Type

Message Type	Action to Be Taken on Sequence # Mismatch
Logon	Must always be the first message transmitted. Authenticate and accept the connection. After sending a *Logon* confirmation back, send a *ResendRequest* if a message gap was detected in the *Logon* sequence number.

...

7.4 Resend Request

From Financial Information Exchange Protocol/Administrative Messages/Resend Request:

> Note: the sending application may wish to consider the message type when resending messages; e.g., if a new order is in the resend series and a significant time period has elapsed since its original inception, the sender may not wish to retransmit the order given the potential for changed market conditions. (The Sequence Reset-Gap Fill message is used to skip message that a sender does not wish to resend.)

7.5 Sequence Reset – Gap Fill

From Financial Information Exchange Protocol/Administrative Messages/Sequence Reset (Gap Fill):

> The sequence reset message is used by the sending application to reset the incoming sequence number on the opposing side. This message has two modes: "Sequence Reset – Gap Fill when *GapFillFlag* (123) is 'Y' and "Sequence Reset – Reset" when *GapFillFlag* (123) is 'N' or not present. The "Sequence Reset – Reset" mode should **only** be used to recover from a disaster situation which cannot e otherwise recovered via "Gap Fill" mode. The sequence reset message can be used in the following situations:

- During normal resend processing, the sending application may choose not to send a message (e.g., an aged order). The Sequence Reset – Gap Fill is used to mark the place of that message.
- During normal resend processing, a number of administrative messages are not resent, the Sequence Reset – Gap Fill message is used to fill the sequence gap created.

. . .

The sending application will initiate the sequence reset. **The message in all situations specifies the *NewSeqNo* (36) to reset as the value of the next sequence number immediately following the messages and/or sequence numbers being skipped.**

. . .

If the *GapFillFlag* (123) field is present (and equal to 'Y'), the *MsgSeqNum* (34) should conform to standard message sequencing rules (i.e., the *MsgSeqNum* (34) of the SeqReset-GapFill message should represent the beginning *MsgSeqNum* (34) in the gap fill range because the remote side is expecting that next message).

The sequence reset can only increase the sequence number. If a sequence reset is received attempting to decrease the next expected sequence number, the message should be rejected and treated as a serious error. It is possible to have multiple resend requests issued in a row (i.e., 5 to 10 followed by 5 to 11). If sequence number 8, 10, and 11 represent application messages while 5–7 and 9 represent administrative messages, the series of messages as a result of the resend request may appear as SeqReset-GapFill with *NewSeqNo* (36) of 8, message 8, SeqReset-GapFill with *NewSeqNo* (36) of 10, and message 10. This could then be followed by SeqReset-GapFill with *NewSeqNo* (36) of 8, message 8, SeqReset-GapFill with *NewSeqNo* (36) of 10, message 10, and message 11. One must be careful to ignore the duplicate SeqReset-GapFill which is attempting to lower the next expected sequence number. This can be detected by checking to see if its *MsgSeqNum* (34) is less than expected. If so, the SeqReset-GapFill is a duplicate and should be discarded.

8 Support

Please email questions or comments regarding this specification to `tradedeskeurope@bats.com`.

Revision History

3rd June 2013	Version 1.0 First non-draft release.
17th June 2013	Version 1.1 *QuoteID* is mandatory on Quote and QuoteCancel messages. *Symbol* is expected after *NoQuoteEntries*. Tweak to *TradeReportType* (856) values returned in Trade Capture Reports confirmed or declined. Added message flow section.
18th June 2013	Version 1.2 Refined some values under New/Cancel/Amend/Release scenario when confirming or declining to make more FIX compliant.
25th June 2013	Version 1.3 Clarified values for *TradePublishIndicator* on Trade Capture Confirmations.
28th June 2013	Version 1.4 Clarified example when requesting deferment of the publication of a trade that is not eligible for such. Added *CentralCounterparty* to Trade Capture Confirmation.
16th July 2013	Version 1.5 Updated values used in example messages to match current requirements. Tweak to *TradeReportType* (856) for unsolicited changes. Allow the use of *PreviouslyReported* (570) to ease migration.
20th August 2013	Version 1.6 Clarified behaviour of *TradeReportID* (571) for Participant submitted trade reports. Clarified expected messaging for Deferred publication trade reports. Clarified unknown symbol handling. Added *RptTime* (7570). Allow price and size fields to be omitted from Quote messages without cancelling the quote.
4th October 2013	Version 1.7 Updated symbology section to include ISIN/currency lookup, minor currency and preferred symbol handling.
29th October 2013	Version 1.8 Removed Broker Crossing Network suggestions.
21st March 2014	Version 1.9 Addition of *ExecMethod* (2405) for trade captures.
25th March 2014	Version 1.10 Clarification of *SecurityExchange* (207) usage for trade reports.
28th March 2014	Version 1.11 Removed 'effective from' labels.
12th April 2014	Version 1.12 Updated details on requirements for *QuoteID* (117).