

The Print Overlay display appears:

Print Overlay

Overlay : STATIONE
Library : OVLLIB

Type choices, press Enter.

Output queue *JOB
Library
Copies 1
Print fidelity *CONTENT

Name, *JOB
Name, *LIBL, *CURLIB
1-255
*CONTENT, *ABSOLUTE

F3=Exit F5=Refresh F12=Cancel

Bottom

The print overlay function allows you to print an overlay on an IPDS printer.

From this display, you can specify the name of an output queue, the number of copies, and print fidelity.

The following table describes the Print Overlay display.

Table 73. Print Overlay display fields

Field Name	Description
Overlay	Shows the name of the overlay to be printed.
Library	Shows the name of the library in which the overlay resides.
Output queue	Specifies the name of the output queue in which the spooled file will be created. The possible values are: *JOB Specifies the output queue specified in the job description associated with this job is used. This is the default value. output-queue-name Specify the name of the output queue to be used.
Library	Specifies the name of the library to locate the output queue. The possible predefined values are: *LIBL The library list is used to locate the output queue. *CURLIB The current library for the job is used to locate the output queue. If no library is specified as the current library for the job, library QGPL is used. library-name Specify the library where the output queue resides.
Copies	Specify the number of copies you want to print. The range of valid values is 1 to 255.