OpenUAS: Battery Handling and Safety

Logan Gross

September 8, 2018

Vant Battery

UAV: Open UAS

Preset Number: 3

Amps: 9000mAh

Discharge Rate: 60C

Cells: 3 (11.1 Volts total)

Full Power: 4.2 per Cell

Storage: 3.8 Volts per Cell

Minimum Charge: 3.0 Volts per Cell

Table 1: Collected Battery Data

Collected Battery Data						
Date	Reason of Use	Usage Time	Max and Min Volts Across Cells	Battery Damage	Back in Safety Case	Temp of Battery After Usage

Date	Reason of Use	Usage Time	Max and Min Volts Across Cells	Battery Damage	Back in Safety Case	Temp of Battery After Usage
Continuation of Collected Battery Data 1						

Date	Reason of Use	Usage Time	Max and Min Volts Across Cells	Battery Damage	Back in Safety Case	Temp of Battery After Usage
Continuation of Collected Battery Data 1						

Continuation of Collected Battery Data 1						
Date	Reason of Use	Usage Time	Max and Min Volts Across Cells	Battery Damage	Back in Safety Case	Temp of Battery After Usage

Date	Reason of Use	Usage Time	Max and Min Volts Across Cells	Battery Damage	Back in Safety Case	Temp of Battery After Usage

Continuation of Collected Battery Data 1

Date	Reason of Use	Usage Time	Max and Min Volts Across Cells	Battery Damage	Back in Safety Case	Temp of Battery After Usage
End of Table						

Continuation of Collected Battery Data 1