# xFusion iBMC Ansible Module V2.0.9 **User Guide**

Date 2023-03-30

#### Notice

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

## **Contents**

About This Document	V
1 Introduction	7
2 Installing and Uninstalling the Ansible Plug-in	10
2.1 Installing the Ansible Plug-in	10
2.2 Uninstalling the Ansible Plug-in	11
3 Configuring the Ansible Plug-in	13
3.1 Configuring /etc/ansible/hosts	13
3.2 Configuring the /group_vars/myhosts File	14
3.3 Configuring the SSL Certificate Authentication and TLS 1.2 Communication Mode	16
4 Using the Ansible Plug-in	19
4.1 Querying Basic Server Information	23
4.2 Configuring the Boot Device	23
4.2.1 Querying Boot Option Information	24
4.2.2 Setting the Boot Device	24
4.3 Managing the Power Supply	25
4.3.1 Querying PSU Status	26
4.3.2 Setting the Power Supply Status	26
4.4 Managing iBMC Users	27
4.4.1 Querying iBMC User Information (JSON File Generated)	27
4.4.2 Creating an iBMC User	28
4.4.3 Modify iBMC User Information	29
4.4.4 Deleting an iBMC User	31
4.5 Configuring iBMC Network Information	32
4.5.1 Querying iBMC Network Configuration (JSON File Generated)	33
4.5.2 Configuring iBMC Network Information	33
4.6 Managing the NTP Service	35
4.6.1 Querying NTP Service Information	
4.6.2 Configure NTP Settings	36
4.7 Managing the SNMP Trap Service	37
4.7.1 Querying SNMP Service Information (JSON File Generated)	
4.7.2 Configuring SNMP Trap	38

4.8 Importing or Exporting a Profile	40
4.8.1 Importing a Profile	40
4.8.2 Exporting the Profile	42
4.9 Upgrading Firmware	44
4.9.1 Querying Firmware Version (JSON File Generated)	45
4.9.2 Upgrading Firmware	45
4.9.2.1 Out-of-Band Firmware Upgrade	45
4.9.2.2 In-Band Firmware Upgrade	47
4.10 Configuring RAID	49
4.10.1 Querying RAID Configuration (JSON File Generated)	50
4.10.2 Deleting a RAID Array	50
4.10.3 Creating a RAID Array	51
4.10.4 Modifying RAID Configuration	53
4.11 Deploying the OS	55
4.11.1 Deploying the OS Using Smart Provisioning	55
4.12 BIOS Management	62
4.12.1 Querying BIOS Information (JSON File Generated)	62
4.12.2 Setting BIOS Information	63
4.12.3 Restoring Default BIOS Settings	64
4.13 Log Management	66
4.13.1 Collecting iBMC Logs in One-Click Mode	
4.13.2 Collecting SELs	67
4.13.3 Clearing SELs	69
4.14 Common Interface	70
4.15 Local File Transfer	
4.15.1 Uploading Local Files	
4.15.2 Downloading a File to a Local Computer	
4.16 Managing the HTTPS Server Root Certificate	74
4.16.1 Importing the Root Certificate of a Remote HTTPS Server	
4.16.2 Deleting the Root Certificate of a Remote HTTPS Server	
4.16.3 Importing a CRL of a Remote HTTPS Server	
4.17 Querying Security Service Information (JSON File Generated)	
4.18 Enabling or Disabling HTTPS File Server Certificate Verification	80
A FAQ	82
B Obtaining Technical Support	88
C Communication Matrix	89

## **About This Document**

## **Purpose**

This document describes how to install and uninstall the Ansible plug-in and how to use the plug-in to implement the information query, health status query, configuration, deployment, and firmware upgrade functions on server.

### **Intended Audience**

This document is intended for:

- Technical support engineers
- System maintenance engineers

## **Symbol Conventions**

The symbols that may be found in this document are defined as follows.

Symbol	Description
▲ DANGER	Indicates an imminently hazardous situation which, if not avoided, will result in death or serious injury.
<b>⚠ WARNING</b>	Indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.
<b>⚠</b> CAUTION	Indicates a potentially hazardous situation which, if not avoided, could result in minor or moderate injury.
NOTICE	Indicates a potentially hazardous situation which, if not avoided, could result in equipment damage, data loss, performance deterioration, or unanticipated results.
	NOTICE is used to address practices not related to personal injury.
Ш NОТЕ	Calls attention to important information, best practices, and tips.  NOTE is used to address information not related to personal injury, equipment damage, and environment deterioration.

## **Change History**

Issue	Date	Description
01	2023-03-30	This issue is the first official release.

## 1 Introduction

#### **Function**

Integrated in the Ansible software, Ansible plug-in is used to manage servers and connects to the iBMC through the Redfish interface. With this plug-in, you can query, configure, deploy, and upgrade the server.

It supports the following functions:

- Query basic information and health status of a server.
- Set the server boot device.
- Perform power control of the server.
- Manage iBMC users.
- Query and configure iBMC network settings.
- Query and configure the NTP service.
- Query and configure the SNMP service.
- Import or export the server profiles.
- Upgrade the out-of-band and in-band server firmware.
- Query and configure RAID settings.
- Deploy the server OS using ServiceCD 2.0 and Smart Provisioning.
- Manage BIOS (including querying and setting BIOS information and restoring default BIOS settings).
- Manage logs (including collecting iBMC logs in one-click mode, collecting SEL logs, and clearing SEL logs).
- Provide a common public interface.
- Upload local files.
- Download files to a local computer.
- Manage the HTTPS server root certificate.
- Query the security service information.
- Enable or Disable HTTPS file server certificate verification.

#### **NOTICE**

The Ansible plugin does not collect or process users' personal data.

## Servers Supported by Ansible Plug-in

Architecture	Туре	Model
x86	Rack server	RH2288H V3
		2488 V5
		2288H V5
		1288H V6
		2288H V6
		5288 V6
x86	Blade server	CH121 V3
		CH242 V3 DDR4
		CH121 V5
		CH242 V5
		CH121L V5
		MM921
		CX621
		CX320
x86	High-density server	XH622 V3
		XH321 V5
x86	Heterogeneous server	G560 V5

### **Matching Versions**

Software	Matching Versions	
iBMC	V6 server: V3.01.12.23 or later	
	V5 server: V325 or later	
	V3 server: V323 or later	
BIOS	V6 server: V66 or later	
	V5 server: V119 or later	
	V3 server: V513 or later	
Smart Provisioning	V118 or later, which can be downloaded from Smart Provisioning	

Software	Matching Versions	
ServiceCD2.0	V139 or later, which can be downloaded from FusionServer Tools	

# 2 Installing and Uninstalling the Ansible Plug-in

#### **Software Requirements**

- Ansible: 2.5.0 or later (2.10 and later versions are recommended)
- Python: 2.7 or later, 3.7 or later

#### ∩ NOTE

You need to install the requests-toolbelt dependency package (0.9.1 or later) in the Python environment to support some functions.

- 2.1 Installing the Ansible Plug-in
- 2.2 Uninstalling the Ansible Plug-in

## 2.1 Installing the Ansible Plug-in

**Step 1** Download the software package and verify the integrity.

- Obtain the Ansible plug-in installation package (for example, xFusion\_iBMC\_Ansible\_Module\_v2.0.8.zip) and its SHA256 verification file (for example, xFusion Ansible.sha256.sum) from GitHub.
- 2. Check the integrity of the Ansible plug-in software package (on Linux).
  - Go to the directory where the plug-in installation package and SHA256 verification file are stored.
  - b. Run the **sha256sum -c < (grep** software package name sha256 verification file name) command to verify the software package.

Example: sha256sum -c <(grep xFusion\_iBMC\_Ansible\_Module\_v2.0.8.zip xFusion Ansible.sha256.sum)

- Check whether the verification result is **OK**.
  - If yes, the software package has not been tampered with and can be used.
  - If no, the software package has been tampered with. Obtain a new software package.

Step 2 Log in to the Ansible server as the root user.

- **Step 3** Upload the installation package to the **root** user directory on the Ansible server.
- **Step 4** Go to the directory where the installation package of the Ansible plug-in is stored.
- **Step 5** Run the following command to decompress the software package of the Ansible plug-in:

#### unzip xFusion\_iBMC\_Ansible\_Module\_x.x.zip

**Step 6** Run the following command to go to the **xFusion\_iBMC\_Ansible\_Module** directory generated after the decompression:

#### cd xFusion iBMC Ansible Module

**Step 7** Run the following command to install the Ansible plug-in:

#### python install.py

#### 

After the installation is successful, the **ibmc\_ansible** folder is added to the **/home** directory. The **ibmc\_ansible** folder stores the SSL configuration file of the Ansible plug-in, and the **/home/ibmc\_ansible/examples** folder stores the YML sample file that needs to be configured for executing the Ansible plug-in.

----End

## 2.2 Uninstalling the Ansible Plug-in

- **Step 1** Log in to the Ansible server as the **root** user.
- **Step 2** Go to the directory where the installation package of the Ansible plug-in is stored.

```
cd xFusion iBMC Ansible Module/
```

**Step 3** Run the uninstallation command.

#### python uninstall.py

**Step 4** Enter **n** (not save) or **y** (save) when a message is displayed asking you whether to save the **.yml** file. In this example, the **.yml** file is not saved.

```
[root@localhost xFusion_iBMC_Ansible_Module]# python uninstall.py
start uninstalling xFusion_ibmc_ansible module
do you want to keep the yml files?(y/n)
n
```

**Step 5** Enter **n** (not save) or **y** (save) when a message is displayed asking you whether to save the log file and the files generated by the plug-in. In this example, the files are not saved.

```
[root@localhost xFusion_iBMC_Ansible_Module]# python uninstall.py
start uninstalling xFusion_ibmc_ansible module
do you want to keep the yml files?(y/n)
n
do you want to keep the log files and plug-in generation file?(y/n)
n
rm ibmc_ansible log successfully!
```

After the plug-in is uninstalled, a message is displayed, indicating that the uninstallation is successful.

```
[root@localhost xFusion_iBMC_Ansible_Module]# python uninstall.py
start uninstalling xFusion_ibmc_ansible module
do you want to keep the yml files?(y/n)
n
do you want to keep the log files and plug-in generation file?(y/n)
n
rm ibmc_ansible log successfully!
uninstalling xFusion_ibmc_ansible successfully!
```

----End

## **3** Configuring the Ansible Plug-in

#### **NOTICE**

Files in this section are created in encryption mode. For details about how to encrypt files, view or set encrypted files, and how to run configuration commands after files are encrypted, see A.1 How Do I Encrypt Files and View, Edit, and Execute Encrypted Files.

- 3.1 Configuring /etc/ansible/hosts
- 3.2 Configuring the /group\_vars/myhosts File
- 3.3 Configuring the SSL Certificate Authentication and TLS 1.2 Communication Mode

## 3.1 Configuring /etc/ansible/hosts

Step 1 Run the following command to create the /etc/ansible directory:

#### mkdir /etc/ansible

Step 2 Run the following command to switch to the /etc/ansible directory:

#### cd /etc/ansible

**Step 3** Run the following command to create the **hosts** file:

#### vi hosts

**Step 4** Write the myhost information to the **hosts** file.

```
[myhosts]
host0 ibmc_ip=192.168.2.20 host=xfusionserver0
host1 ibmc_ip=192.168.2.21 host=xfusionserver1
```

#### ----End

#### **NOTICE**

The names in the first column, for example **host0** and **host1**, cannot be the same. Otherwise, the command is executed only for the last server.

## 3.2 Configuring the /group\_vars/myhosts File

#### **NOTICE**

You can perform the configuration as the **root** user or a non-root user. A non-root user is recommended because sensitive data such as passwords is involved during the configuration.

Set parameters in the myhosts file in the

/home/user/ibmc\_ansible/examples/group\_vars directory (for non-root users) or /home/ibmc\_ansible/examples/group\_vars directory (for the root user). The parameters include the iBMC user name and password, SFTP/CIFS/SCP user name and password, SNMP community name, the administrator password required for OS deployment, and others.

#### 

/home/user/ibmc\_ansible/examples/group\_vars: Replace user with the actual non-root user name. In this example, the user is plugin.

#### **Procedure (Non-root User)**

- Step 1 Run the following command to switch to the plugin user:
  - su plugin
- **Step 2** Run the following command to copy the **ibmc\_ansible** folder from the **/home** directory to the **/home/plugin** directory.
  - cp -r /home/ibmc\_ansible/ /home/p/ugin/ibmc\_ansible/
- **Step 3** Run the following command to create the /home/plugin/ibmc\_ansible/examples/group\_vars directory:
  - mkdir /home/plugin/ibmc\_ansible/examples/group\_vars
- **Step 4** Run the following command to go to the /home/plugin/ibmc\_ansible/examples/group\_vars directory:
  - cd /home/plugin/ibmc ansible/examples/group vars
- **Step 5** Run the encryption command to create the **myhosts** file.
  - ansible-vault create myhosts

#### **NOTICE**

- Encrypted creation of the myhosts file is recommended because the file contains sensitive data such as passwords. When the file is created with encryption, you need to use the --ask-vault-pass command for decryption. For details, see A.1 How Do I Encrypt Files and View, Edit, and Execute Encrypted Files.
- You can also use the create myhosts command to create the file without encryption, which is not recommended due to sensitive data leakage risks.

#### **Step 6** Add the following information to the **myhosts** file:

```
# Here we define global variables for our server group, but if some servers
# require custom values place these variables in /etc/ansible/hosts to override
# for each individual host
#for create or modify ibmc account
account user: "account user"
account pswd: "account pswd"
# input the xfusion ibmc user and password
ibmc user: "ibmc user"
ibmc pswd: "ibmc pwd"
\sharp input the sftp user and password when we need to use the sftp service
sftp_user: "sftp_user"
sftp pswd: "sftp pwd"
# input the cifs user and password when we need to use the cifs service
cifs user: "cifs user"
cifs pswd: "cifs pwd"
# input the scp user and password when we need to use the scp service
scp user: "scp user"
scp_pswd: "scp_pwd"
# if you select SNMP Trap mode as V1 or V2C, you can set the community name
community: "community name"
# input the os password when you deploy the server os by sp
os pswd: "os pswd"
```

#### **Procedure (root User)**

----End

- Step 1 Run the following command to create the /home/ibmc\_ansible/examples/group\_vars directory: mkdir /home/ibmc\_ansible/examples/group\_vars
- **Step 2** Run the following command to go to the **/home/ibmc\_ansible/examples/group\_vars** directory:
  - cd /home/ibmc\_ansible/examples/group\_vars
- **Step 3** Run the encryption command to create the **myhosts** file.

#### ansible-vault create myhosts

#### **NOTICE**

- Encrypted creation of the myhosts file is recommended because the file contains sensitive data such as passwords. When the file is created with encryption, you need to use the --ask-vault-pass command for decryption. For details, see A.1 How Do I Encrypt Files and View, Edit, and Execute Encrypted Files.
- You can also use the create myhosts command to create the file without encryption, which is not recommended due to sensitive data leakage risks.

#### **Step 4** Add the following information to the **myhosts** file:

```
# Here we define global variables for our server group, but if some servers
# require custom values place these variables in /etc/ansible/hosts to override
# for each individual host
#for create or modify ibmc account
account_user: "account_user"
account_pswd: "account_pswd"
# input the xfusion ibmc user and password
ibmc user: "ibmc user"
ibmc_pswd: "ibmc_pwd"
# input the sftp user and password when we need to use the sftp service
sftp_user: "sftp_user"
sftp_pswd: "sftp_pwd"
# input the cifs user and password when we need to use the cifs service
cifs_user: "cifs_user"
cifs_pswd: "cifs_pwd"
# input the scp user and password when we need to use the scp service
scp_user: "scp_user"
scp pswd: "scp pwd"
# if you select SNMP Trap mode as V1 or V2C, you can set the community name
community: "community_name"
# input the os password when you deploy the server os by sp
os_pswd: "os_pswd"
```

#### ----End

## 3.3 Configuring the SSL Certificate Authentication and TLS 1.2 Communication Mode

#### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/set\_request\_cfg.yml file.

The force\_tls1\_2 parameter sets the TLS 1.2 communication mode. The default value is True, indicating that the TLS 1.2 communication mode is used forcibly. If "import ssl.PROTOCOL\_TLSv1\_2 exception" is generated after a command is executed when TLS 1.2 is enabled, you need to set force\_tls1\_2 to False.

#### **NOTICE**

Setting **force\_tls1\_2** to **False** may pose security risks. Exercise caution when performing this operation.

- The verify and certify parameters set the SSL certificate authentication function.
   If the certify parameter is not set, one of the following default certificate libraries is used. You need to import the CA certificate to the corresponding library first.
  - If the **certifi** certificate library is not installed, the system certificate library is used by default. For example:

#### /etc/pki/tls/certs/ca-bundle.crt

 If Python is used to install the certificate library, the certificate library is used by default. For example:

Python 2:

/usr/lib/python2.7/site-packages/certifi-2019.11.28-py2.7.egg/certifi/cac ert.pem

Python 3:

/usr/local/python3/lib/python3.7/site-packages/certifi-2020.6.20-py3.7.e gg/certifi/cacert.pem

#### **NOTICE**

Disabling SSL certificate authentication (**verify** is set to **False**) may pose security risks. Exercise caution when performing this operation.

• ciphers: cipher suite used when the Ansible plug-in functions as a client to establish sessions with the server.

#### **NOTICE**

Use a secure cipher suite. An insecure cipher suite may bring security risks.

```
[plugin@localhost examples]$ vi set_request_cfg.yml
---
- hosts: 127.0.0.1
connection: local
name: set request config
gather_facts: False
# verify: the requests module verify server certify or not; Available values: True,
False;
# certify: the certify use to verify the server, if this params do not set , requests
module will used the certificate
#which is in the certifi module or the system default certificate. Format:
```

```
/etc/pki/tls/certs/ca-bundle.crt
# force_tls1_2: force to use tls1.2 , the default value is true.
tasks:
    - name: set request config
    ibmc_set_redfish_request_cfg:
        force_tls1_2: False
        verify: False
        certify:
        ciphers:
"ECDHE-ECDSA-AES128-GCM-SHA256:ECDHE-ECDSA-AES256-GCM-SHA384:ECDHE-RSA-AES256-GCM-SHA384:ECDHE-RSA-AES128-GCM-SHA256:DHE-RSA-AES256-GCM-SHA384:ECDHE-RSA-AES128-GCM-SHA256:DHE-DSS-AES256-GCM-SHA384:ECDHE-RSA-CHACHA20-POLY13
```

#### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- Run the following command: ansible-playbook set\_request\_cfg.yml

#### □ NOTE

This command can be executed only by the root user.

The operation is successful if the following information is displayed:

# 4 Using the Ansible Plug-in

The command output varies with the Ansible version used. The command output provided in this section is for reference only.

#### NOTICE

- This section uses unencrypted files as an example. You are advised to encrypt files that contain sensitive data such as passwords. For details about how to encrypt files, view encrypted files, configure encrypted files, and run configuration commands after files are encrypted, see A.1 How Do I Encrypt Files and View, Edit, and Execute Encrypted Files.
- This document uses a non-root user **plugin** as an example. You need to replace **plugin** in the **/home/plugin/\*\*** directory with the actual login user.
- If the HTTPS certificate verification has been performed on the Ansible plug-in's matching iBMC versions, the Ansible plug-in cannot use the remote transmission over HTTPS. Use other protocols.

#### **Querying Help Information**

1. Run the following command to view all command module names of the Ansible plug-in. The following uses Python 3 as an example.

#### ansible-doc -l |grep ibmc

[plugin@localhost ~]\$ ansible-doc	-1  grep ibmc	
/usr/local/python3/lib/python3.7/site-packages/cryptography-3.1.1-py3.7-linux-x		
86_64.egg/cryptography/hazmat/bind	lings/openssl/binding.py:177:	
CryptographyDeprecationWarning: Ope	enSSL version 1.0.2 is no longer supported by the	
OpenSSL project, please upgrade. The next version of cryptography will drop support		
for it.		
utils.CryptographyDeprecationWar	ning,	
ibmc_ansible_show_version	Show xFusion iBMC ansible modules ver	
ibmc_clear_sel_logs	Clear SEL	
ibmc_collect_logs	Collect iBMC	
ibmc_collect_sel_logs	Collect iBMC SEL	
ibmc_common_api	Common	
ibmc_create_account	Create an ibmc	
ibmc_create_raid	Create vo	
ibmc_delete_account	Delete an ibmc	
ibmc delete https ca	delete http	

```
ibmc delete raid
ibmc deploy os by service cd
                                       deploy os by servic...
ibmc deploy os by sp
                                      deploy os b...
ibmc download file
                                      Download f...
ibmc get account
                                      Get ibmc user ...
ibmc_get_basic_info
                                      Get server informa...
ibmc get bios
                                     Get bios ...
ibmc get boot device
                                      get boot de...
ibmc get firmware info by sp
                                       get firmware ...
                                     Get ibmc ip ...
ibmc get ip
ibmc get ntp
                                     Get ntp ...
ibmc get power status
                                       get ibmc power ...
ibmc get raid
                                     Get raid ...
ibmc get security service information
                                       get security service informa..
ibmc get snmp trap
                                      Get snmp trap resource ...
ibmc https ca import
                                      import http...
ibmc https crl import
                                      import https...
ibmc inband fw update
                                      update inband firm...
ibmc modify account
                                      modify an ibmc ...
ibmc modify raid
                                      Modify vo...
ibmc outband fw update
                                       update outband firm...
ibmc profile export
                                      export the server pro...
ibmc profile import
                                      import the server pro...
ibmc reset bios
                                     Reset BIOS resource attrib ...
ibmc set_bios
                                     Set bios ...
ibmc set boot device
                                      Set boot de...
ibmc set https cert verification
                                      set https cert verifica...
ibmc set ip
                                     Set ibmc ip ...
ibmc set ntp
                                     Set ntp ...
ibmc set power
                                     manager server p...
ibmc set redfish request cfg
                                       set request co...
ibmc_set_snmp_trap
                                      Set snmp trap ...
ibmc upload file
                                      upload ...
```

Run the following command to query the help information about a command module:

#### ansible-doc Command module name

#### Example: ansible-doc ibmc\_get\_account

```
[plugin@localhost ~]$ ansible-doc ibmc_get_account
/usr/local/python3/lib/python3.7/site-packages/cryptography-3.1.1-py3.7-linux-x
86_64.egg/cryptography/hazmat/bindings/openssl/binding.py:177:
CryptographyDeprecationWarning: OpenSSL version 1.0.2 is no longer supported by the
OpenSSL project, please upgrade. The next version of cryptography will drop support
for it.
    utils.CryptographyDeprecationWarning,
> IBMC_GET_ACCOUNT
(/usr/local/python3/lib/python3.7/site-packages/ansible-2.9.9-py3.7.egg/ansible
/modules/i

    Get ibmc user info

    * This module is maintained by The Ansible Community
OPTIONS (= is mandatory):
    = ibmc ip
```

```
iBMC IP address
[Default: None]
iBMC user password used for authentication
[Default: None]
iBMC user name used for authentication
[Default: None]
METADATA:
status:
- preview
supported by: community
:...skipping...
> IBMC GET ACCOUNT
(/usr/local/python3/lib/python3.7/site-packages/ansible-2.9.9-py3.7.egg/ansible
Get ibmc user info
* This module is maintained by The Ansible Community
OPTIONS (= is mandatory):
= ibmc ip
iBMC IP address
[Default: None]
= ibmc pswd
iBMC user password used for authentication
[Default: None]
= ibmc user
iBMC user name used for authentication
[Default: None]
METADATA:
status:
- preview
supported by: community
EXAMPLES:
- name: get ibmc account
ibmc_get_account:
ibmc_ip: "{{    ibmc_ip }}"
```

```
ibmc_user: "{{ ibmc_user }}"
ibmc_pswd: "{{ ibmc_pswd }}"
```

#### **Querying Plug-in Version Information**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to view the version:

#### ansible-playbook -v show\_ibmc\_ansible\_version.yml

```
[plugin@localhost examples] ansible-playbook -v show ibmc ansible version.yml
/usr/local/python3/lib/python3.7/site-packages/cryptography-3.1.1-py3.7-linux-x
86 64.egg/cryptography/hazmat/bindings/openssl/binding.py:177:
CryptographyDeprecationWarning: OpenSSL version 1.0.2 is no longer supported by the
OpenSSL project, please upgrade. The next version of cryptography will drop support
for it.
utils.CryptographyDeprecationWarning,
No config file found; using defaults
PLAY [show xFusion iBMC ansible modules version]
TASK [show xFusion iBMC ansible modules version]
***************
ok: [127.0.0.1] => {"changed": false, "msg": "xFusion iBMC ansible modules version
is 2.0.8"}
PLAY RECAP
127.0.0.1 : ok=1 changed=0 unreachable=0 failed=0
skipped=0 rescued=0 ignored=0
```

- 4.1 Querying Basic Server Information
- 4.2 Configuring the Boot Device
- 4.3 Managing the Power Supply
- 4.4 Managing iBMC Users
- 4.5 Configuring iBMC Network Information
- 4.6 Managing the NTP Service
- 4.7 Managing the SNMP Trap Service
- 4.8 Importing or Exporting a Profile
- 4.9 Upgrading Firmware
- 4.10 Configuring RAID
- 4.11 Deploying the OS
- 4.12 BIOS Management
- 4.13 Log Management
- 4.14 Common Interface

- 4.15 Local File Transfer
- 4.16 Managing the HTTPS Server Root Certificate
- 4.17 Querying Security Service Information (JSON File Generated)
- 4.18 Enabling or Disabling HTTPS File Server Certificate Verification

## 4.1 Querying Basic Server Information

#### **Function**

- Query the BMC version, BIOS version, CPLD version, Smart Provisioning version, serial number, asset label, server model, server health status, memory information and health status, CPU information and health status, drive information, and health status information.
- By default, a JSON file is generated. To generate a CSV file, set **csv\_format** in the **get\_basic\_info.yml** file to **True** before running the query command.

#### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- Run the following command to query the basic information about the server: ansible-playbook get\_basic\_info.yml

The command execution is successful if the following information is displayed:

The file (for example, **172.26.100.9\_BasicInfo.json**) generated after the query is saved in the **/home/**plugin**/ansible\_ibmc/report/basic\_info** directory by default. You are advised to export the file before viewing it.

## 4.2 Configuring the Boot Device

#### 

The MM921 management module and CX320/CX621 switch modules do not support this function.

#### **Function**

Query and set the boot device, boot parameter enabling status, and boot mode.

### 4.2.1 Querying Boot Option Information

#### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc ansible/examples
- 2. Run the following command to query the configuration of boot options: ansible-playbook get\_boot\_device.yml

#### ∩ NOTE

To view the query result in the command output, run the **ansible-playbook -vv get\_boot\_device.yml** command.

The command execution is successful if the following information is displayed:

You can view the query result in the **ansibleibmc.report** file in the **/home/plugin/ansible\_ibmc/report** directory, as shown in 3.

3. Run the following command to view the information:

```
cd /home/plugin/ansible_ibmc/report cat ansibleibmc.report
```

```
[2019-12-02 06:41:10 INFO] - 172.26.100.10 -- Get boot device info successful! The boot device info is: {'Boot': {u'BootSourceOverrideTarget': u'Hdd', u'BootSourceOverrideMode': u'UEFI', u'BootSourceOverrideEnabled': u'Continuous', u'BootSourceOverrideTarget@Redfish.AllowableValues': [u'None', u'Pxe', u'Floppy', u'Cd', u'Hdd', u'BiosSetup']}}
```

## 4.2.2 Setting the Boot Device

#### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/set\_boot\_device.yml file.

```
[plugin@localhost examples]$ vi set_boot_device.yml
---
- hosts: myhosts
connection: local
```

```
name: set boot device
gather_facts: False

# boot_target: Current boot device, Available values: Cd, None, Pxe, Floppy, Hdd,
BiosSetup.

# boot_enabled: Whether the boot settings are effective, Available values: Disabled,
Once, Continuous.

# boot_mode: Boot mode, Available values: UEFI, Legacy.

tasks:
    - name: set boot device
    ibmc_set_boot_device:
    ibmc_ip: "{{ ibmc_ip }}"
    ibmc_user: "{{ ibmc_user }}"
    ibmc_pswd: "{{ ibmc_user }}"
    boot_target: "Cd"
    boot_enabled: "Once"
    boot_mode: "Legacy"
```

#### Commands

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to configure the boot device.

#### ansible-playbook set\_boot\_device.yml

The command execution is successful if the following information is displayed:

## 4.3 Managing the Power Supply

#### □ NOTE

The MM921 management module and CX320/CX621 switch modules do not support this function.

#### **Function**

Query and set the power supply status.

## 4.3.1 Querying PSU Status

#### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc ansible/examples
- 2. Run the following command to query the power supply status.

#### ansible-playbook get\_power\_status.yml

The command execution is successful if the following information is displayed:

The query result is in the **ansibleibmc.report** file in **/home/plugin/ansible\_ibmc/report**.

3. Run the following command to view the information:

```
cd /home/p/ugin/ansible_ibmc/report cat ansibleibmc.report
```

```
[2019-12-02\ 06:38:32\ INFO\ ] - 172.26.100.10 -- get system power state successful! power status is :Off
```

## 4.3.2 Setting the Power Supply Status

#### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/set\_power.yml file.

```
[plugin@localhost examples]$ vi set_power.yml
---
- hosts: myhosts
  connection: local
  name: power manager
  gather_facts: False
#power_cmd: Available values:"poweron" "poweroff" "forcerestart" "gracefulshutdown"
"forcepowercycle" "nmi"
  tasks:
- name: power manager
  ibmc_set_power:
```

```
ibmc_ip: "{{ ibmc_ip }}"
ibmc_user: "{{ ibmc_user }}"
ibmc_pswd: "{{ ibmc_pswd }}"

power_cmd: "poweron"
```

#### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to configure the power supply status.

#### ansible-playbook set\_power.yml

The command execution is successful if the following information is displayed:

## 4.4 Managing iBMC Users

#### **Function**

TQuery, create, modify, or delete iBMC users.

### 4.4.1 Querying iBMC User Information (JSON File Generated)

#### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to query the iBMC user.

#### ansible-playbook get\_account.yml

The command execution is successful if the following information is displayed:

```
[plugin@localhost examples]$ ansible-playbook get_account.yml
PLAY [get ibmc Account]
```

The JSON file (for example, 172.26.100.9\_AccountInfo.json) generated after the query is saved in the /home/plugin/ansible\_ibmc/report/account\_info directory by default. You are advised to export the JSON file before viewing it.

## 4.4.2 Creating an iBMC User

#### **Parameter Configuration**

Modify the account\_user (new user name) and account\_pswd (user password)
parameters in the /home/plugin/ibmc\_ansible/examples/group\_vars/myhosts
file.

```
[plugin@localhost examples] $ vi
/home/plugin/ibmc ansible/examples/group vars/myhosts
# Here we define global variables for our server group, but if some servers
# require custom values place these variables in /etc/ansible/hosts to override
# for each individual host
#for create or modify ibmc account
account user: "account user"
account_pswd: "account_pswd"
# input the xfusion ibmc user and password
ibmc user: "ibmc user"
ibmc pswd: "ibmc pwd"
# input the sftp user and password when we need to use the sftp service
sftp_user: "sftp_user"
sftp pswd: "sftp pwd"
# input the cifs user and password when we need to use the cifs service
cifs user: "cifs user"
cifs pswd: "cifs pwd"
# input the scp user and password when we need to use the scp service
scp user: "scp user"
scp pswd: "scp pwd"
\# if you select SNMP Trap mode as V1 or V2C, you can set the community name
community: "community_name"
# input the os password when you deploy the server os by sp
os pswd: "os pswd"
```

Modify the /home/plugin/ibmc\_ansible/examples/create\_account.yml file.

```
[plugin@localhost examples]$ vi create_account.yml
---
- hosts: myhosts
connection: local
name: create ibmc Account
gather_facts: False
#roleid: role id; Available values: Administrator, Operator, Commonuser, Noaccess,
CustomRole1, CustomRole2, CustomRole3, CustomRole4
tasks:
- name: create ibmc Account
ibmc_create_account :
   ibmc_ip: "{{ ibmc_ip }}"
   ibmc_user: "{{ ibmc_user }}"
   ibmc_pswd: "{{ ibmc_pswd }}"
   new_account_user: "{{ account_user }}"
   new_account_pswd: "{{ account_pswd }}"
   roleid: "Administrator"
```

#### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc ansible/examples
- 2. Run the following command to create the iBMC user.

#### ansible-playbook create\_account.yml

The command execution is successful if the following information is displayed:

## 4.4.3 Modify iBMC User Information

#### **Parameter Configuration**

Modify the account\_user (new user name) and account\_pswd (new password)
parameters in the /home/plugin/ibmc\_ansible/examples/group\_vars/myhosts
file.

```
[plugin@localhost examples]$ vi
/home/plugin/ibmc_ansible/examples/group_vars/myhosts
# Here we define global variables for our server group, but if some servers
# require custom values place these variables in /etc/ansible/hosts to overr
# for each individual host
#for create or modify ibmc account
account_user: "account_user"
account_pswd: "account_pswd"
# input the xfusion ibmc user and password
ibmc user: "ibmc user"
ibmc pswd: "ibmc pwd"
\sharp input the sftp user and password when we need to use the sftp service
sftp user: "sftp user"
sftp pswd: "sftp pwd"
# input the cifs user and password when we need to use the cifs service
cifs user: "cifs user"
cifs pswd: "cifs pwd"
# input the scp user and password when we need to use the scp service
scp user: "scp user"
scp_pswd: "scp_pwd"
# if you select SNMP Trap mode as V1 or V2C, you can set the community name
community: "community name"
\ensuremath{\sharp} input the os password when you deploy the server os by sp
os pswd: "os pswd"
```

#### Modify the /home/plugin/ibmc\_ansible/examples/modify\_account.yml file.

```
[plugin@localhost examples] vi modify account.yml
- hosts: myhosts
connection: local
name: modify ibmc Account
gather facts: False
#roleid: role id; Available values: Administrator, Operator, Commonuser, Noacce
CustomRole1, CustomRole2, CustomRole3, CustomRole4
#locked: it must be False
#enable: Whether the user is enabled; Available values: True, False
#login interface:list of service the account can access, can be set to empty list
[]; Available values in list:Web, SNMP, IPMI, SSH, SFTP, Local, Redfish
#login rule: list of login rules, can be set to empty list []; Available values in
list:Rule1, Rule2, Rule3
#account insecure prompt enabled: enable or disable account insecure prompt;
Available values: True, False
- name: modify ibmc Account
ibmc modify account :
ibmc_ip: "{{    ibmc_ip }}"
ibmc_user: "{{ ibmc_user }}"
```

```
ibmc_pswd: "{{ ibmc_pswd }}"
  old_account_user: "test"
  new_account_user: "{{ account_user }}"
  new_account_pswd: "{{ account_pswd }}"
  roleid: "Administrator"
  locked: False
  enable: True
  login_interface:
    - Web
  login_rule:
    - Rule1
  account_insecure_prompt_enabled: True
```

#### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to modify the iBMC user.

#### ansible-playbook modify\_account.yml

The command execution is successful if the following information is displayed:

## 4.4.4 Deleting an iBMC User

#### **Parameter Configuration**

Modify the **delete\_account** parameter (user name to be deleted) in the **/home/plugin/ibmc\_ansible/examples/delete\_account.yml** file.

```
[plugin@localhost examples]$ vi delete_account.yml
---
- hosts: myhosts
  connection: local
  name: delete ibmc Account
  gather_facts: False
```

```
tasks:
- name: delete ibmc Account
ibmc_delete_account:
   ibmc_ip: "{{ ibmc_ip }}"
   ibmc_user: "{{ ibmc_user }}"
   ibmc_pswd: "{{ ibmc_pswd }}"
   delete_account: "test"
```

#### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to delete the iBMC user.

#### ansible-playbook delete\_account.yml

The command execution is successful if the following information is displayed:

## 4.5 Configuring iBMC Network Information

#### □ NOTE

The MM921 management module and CX320/CX621 switch modules do not support this function.

#### **Function**

- Query iBMC network information.
- Modify the IP enabling mode or IP address separately.

#### **NOTICE**

- Do not change the IP enabling mode and IP address at the same time. Otherwise, the modification fails.
- The IPv4 enabling mode and IPv6 enabling mode cannot be switched to each other.
   Otherwise, the server cannot be connected.

## 4.5.1 Querying iBMC Network Configuration (JSON File Generated)

#### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc ansible/examples
- 2. Run the following command to query the iBMC network information. ansible-playbook get\_ibmc\_ip.yml

The command execution is successful if the following information is displayed:

The JSON file (for example, 172.26.100.9\_iBMCIPInfo.json) generated after the query is saved in the /home/plugin/ansible\_ibmc/report/ibmc\_ip directory by default. You are advised to export the JSON file before viewing it.

## 4.5.2 Configuring iBMC Network Information

#### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/set\_ibmc\_ip.yml file.

```
[plugin@localhost examples]$ vi set_ibmc_ip.yml
---
- hosts: myhosts
  connection: local
  name: set ibmc ip
  gather_facts: False
# target_bmc_ip: ibmc_ip that you specify to set network information, and you can only choose from the group of hosts.
# ip version: Whether IPv4/IPv6 is enabled, Available values: IPv4, IPv6, IPv4AndIPv6.
```

```
# ipv4 addr: IPv4 address info.
# address: IPv4 address.
# subnet mask: Subnet mask of the IPv4 address.
# gateway: Gateway of the IPv4 address.
# address origin: How the IPv4 address is allocated. Available values: Static, DHCP.
# ipv6 addr: IPv6 address info.
# address: IPv6 address.
# prefix length: Prefix length of the IPv6 address, must be an integer, value range:
0 to 128.
# address origin: How the IPv6 address is allocated. Available values: Static, DHCPv6.
# ipv6 gateway: IPv6 gateway address of the iBMC network port.
# hostname: iBMC HostName. Contains a maximum of 64 characters, including only letters,
digits, and hyphens (-).
# Cannot start or end with a hyphen.
# domain name: Domain name. Contains a maximum of 67 characters. The format of FQDN
is hostname.domain name.
# For example, if hostname is "testhostname" and domain_name is "ibmc.com", then FQDN
is "testhostname.ibmc.com".
tasks:
- name: set ibmc ip
ibmc set ip:
ibmc ip: "{{ ibmc ip }}"
ibmc user: "{{ ibmc user }}"
ibmc pswd: "{{ ibmc pswd }}"
target bmc ip: "192.168.3.11"
ip version: "IPv4AndIPv6"
   ipv4 addr:
    - address: "192.168.2.10"
    subnet mask: "255.255.0.0"
    gateway: "192.168.0.1"
   address_origin: "Static"
   ipv6 addr:
   - address: "fc00:192::10"
        prefix length: 7
        address origin: "Static"
    ipv6 gateway: "fc00:192::1"
     hostname: "testhostname"
     domain name: "ibmc.com"
```

#### 

iBMC network information can be configured only for a single device. Batch configuration is not supported.


#### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to configure the iBMC network information.

#### ansible-playbook set\_ibmc\_ip.yml

The command execution is successful if the following information is displayed:

```
[plugin@localhost examples]$ ansible-playbook set_ibmc_ip.yml
PLAY [set ibmc ip]
```



## 4.6 Managing the NTP Service

#### 

The MM921 management module and CX320/CX621 switch modules do not support this function.

#### **Function**

- Query NTP service information.
- Enable or disable the NTP service, configure IP addresses of the preferred and alternate NTP servers, enable or disable server identity authentication, set the NTP address mode (IPv4/IPv6/Static), and minimum/maximum polling interval.

## 4.6.1 Querying NTP Service Information

#### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- Run the following command to query the NTP service information.

#### ansible-playbook get ntp.yml

The command execution is successful if the following information is displayed:

```
host0.domain.com : ok=1 changed=0 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0
```

## The query result is in the **ansibleibmc.report** file in **/home/plugin/ansible\_ibmc/report**.

3. Run the following command to view the information:

## cd /home/plugin/ansible\_ibmc/report cat ansibleibmc.report

```
[2019-12-02 06:42:10 INFO] - 172.26.100.10 -- Get NTP configuration resource info successful! The NTP configuration resource info is: {'NtpAddressOrigin': u'Static', 'ServiceEnabled': True, 'ServerAuthenticationEnabled': True, 'MinPollingInterval': 3, 'NTPKeyStatus': u'Uploaded', 'AlternateNtpServer': u'', 'PreferredNtpServer': u'172.26.207.1', 'MaxPollingInterval': 17}
```

## 4.6.2 Configure NTP Settings

#### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/set\_ntp.yml file.

```
[plugin@localhost examples]$ vi set_ntp.yml
- hosts: myhosts
connection: local
name: set ntp
gather facts: False
# service enabled: Enable or disable bmc ntp service, Available values: True, False.
# pre ntp server: Config preferred NtpServer, you can enter ipv4 ipv6 or domain name,
NTP Server will be blanked when set to an empty string.
# alt ntp server: Config alternate NtpServer, you can enter ipv4 ipv6 or domain name,
NTP Server will be blanked when set to an empty string.
# server_auth_enabled: Enable or disable Server Authentication service, Available
values: True, False.
# ntp address origin: Confiq Ntp Address Origin, Available values: IPv4, IPv6, Static.
\# min polling interval: Config Min Polling Interval time, must be an integer, in 3~17
and <= max polling interval.
\# max polling interval: Config Max Polling Interval time, must be an integer, in 3~17
and >= min polling interval.
tasks:
- name: set ntp
ibmc set ntp:
   ibmc ip: "{{ ibmc ip }}"
   ibmc user: "{{ ibmc user }}"
ibmc pswd: "{{ ibmc pswd }}"
service enabled: True
 pre ntp server: "192.168.2.10"
    alt ntp server: "192.168.2.20"
    server_auth_enabled: False
     ntp_address_origin: "Static"
     min polling interval: 3
     max polling interval: 17
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to configure the NTP:

### ansible-playbook set\_ntp.yml

The command execution is successful if the following information is displayed:

# 4.7 Managing the SNMP Trap Service

#### 

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

- Query SNMP trap service information.
- Set the trap enabling status, the SNMPv3 trap user name, reporting mode, host ID, community name, alarm severity, and trap server.

# 4.7.1 Querying SNMP Service Information (JSON File Generated)

### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to query the SNMP service information.

ansible-playbook get\_snmp\_trap.yml

The JSON file (for example, 172.26.100.9\_SNMPTrapInfo.json) generated after the query is saved in the /home/plugin/ansible\_ibmc/report/snmp\_trap directory by default. You are advised to export the JSON file before viewing it.

# 4.7.2 Configuring SNMP Trap

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/set\_snmp\_trap.yml file.

```
[plugin@localhost examples] vi set snmp trap.yml
- hosts: myhosts
connection: local
name: set snmp trap
gather facts: False
# service enabled: Whether trap is enabled, Available values: True, False.
# trap version: Trap version, Available values: V1, V2C, V3.
# trap_v3_user: SNMPv3 user name, valid only for trap version is V3.
# trap mode: Trap mode, Available values: OID, EventCode, PreciseAlarm.
# trap server identity: Host identifier, Available values: BoardSN, ProductAssetTag,
HostName.
# alarm severity: Severity levels of the alarm to be sent, Available values: Critical,
Major, Minor, Normal.
# trap servers: Can set one or more trap server, When all parameters of the trap
server are empty, it indicates that the trap server is not configured.
# trap_server_enabled: Whether the trap server is enabled, Available values: True,
# trap server address: Server address, you can enter ipv4 ipv6 or domain name.
# trap server port: Server port number, must be an integer, Available value range:
1 to 65535.
tasks:
- name: set snmp trap
ibmc set snmp trap:
ibmc ip: "{{ ibmc ip }}"
ibmc_user: "{{ ibmc_user }}"
  ibmc pswd: "{{ ibmc pswd }}"
   community: "{{ community }}"
service_enabled: True
trap_version: "V3"
```

```
trap_v3_user: "root"
trap mode: "OID"
    trap_server_identity: "HostName"
  alarm severity: "Normal"
   trap servers:
    - trap_server_enabled: True
       trap_server_address: "192.168.2.10"
       trap_server_port: 160
      - trap server enabled: True
      trap_server_address: "192.168.2.11"
      trap_server_port: 161
      - trap_server_enabled: False
      trap server address: "192.168.2.12"
       trap_server_port: 162
      - trap_server_enabled: False
       trap server address: "192.168.2.13"
       trap_server_port: 163
```

 Modify the community parameter in the /home/plugin/ibmc\_ansible/examples/group\_vars/myhosts file.

#### 

When trap\_version is set to V1 or V2C, set community in the /home/plugin/ibmc\_ansible/examples/group\_vars/myhosts file.

```
[plugin@localhost examples]$ vi
/home/plugin/ibmc_ansible/examples/group_vars/myhosts
# Here we define global variables for our server group, but if some servers
# require custom values place these variables in /etc/ansible/hosts to override
# for each individual host
#for create or modify ibmc account
account_user: "account user"
account pswd: "account pswd"
# input the xfusion ibmc user and password
ibmc user: "ibmc user"
ibmc pswd: "ibmc pwd"
# input the sftp user and password when we need to use the sftp service
sftp user: "sftp user"
sftp pswd: "sftp pwd"
# input the cifs user and password when we need to use the cifs service
cifs user: "cifs user"
cifs_pswd: "cifs_pwd"
# input the scp user and password when we need to use the scp service
scp user: "scp user"
scp pswd: "scp pwd"
# if you select SNMP Trap mode as V1 or V2C, you can set the community name
community: "community_name"
```

```
# input the os password when you deploy the server os by sp
os pswd: "os pswd"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to configure the SNMP trap:

### ansible-playbook set\_snmp\_trap.yml

The command execution is successful if the following information is displayed:

# 4.8 Importing or Exporting a Profile

### 

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

Imports and exports BIOS and iBMC profiles.

- The profile can be imported to the server locally or remotely.
- The profile on the server can be exported to the local environment or a remote path.

# 4.8.1 Importing a Profile

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/profile\_import.yml file.

When importing the file from the local host, set the parameters as follows:

- file\_name: name of the file to be imported.
- **local\_import**: local file path to be imported in the Ansible environment.

### When importing the file remotely, set the parameters as follows:

- file\_name: name of the file to be imported.
- remote\_file: file path to be imported in the remote directory.
  - **/tmp** directory of the iBMC.
  - Folder in the directory of the remote file server. The format of the file path is File transfer protocol: IIIP address of the remote file server/folder.
     Supported file transfer protocols include SFTP, HTTPS, NFS, CIFS, and SCP.
- **file server user**: user name for logging in to the remote file server.
- file\_server\_pswd: password for logging in to the remote file server.

#### For local import, set the parameters as follows:

```
[plugin@localhost examples]$ vi profile_import.yml
- hosts: myhosts
connection: local
name: import profile
gather facts: False
# file name: the file name you want to import
# local import: local file path of the Ansible environment to be imported.
# remote import: remote path for saving imported files. The file path can be /tmp on
the BMC; or a folder on a remote file server, the format is protocol://ip/folder
# protocols: Available values: sftp,https,nfs,cifs,scp
# file_server_user: remote file server user name
# file_server_pswd: remote file server password
tasks:
- name: import profile
ibmc profile import:
ibmc ip: "{{ ibmc ip }}"
ibmc_user: "{{ ibmc_user }}"
ibmc pswd: "{{ ibmc pswd }}"
     file name: "192.168.1.1 20210318045050 profile.xml"
     local import: "/home"
```

#### For remote import, set the parameters as follows:

```
[plugin@localhost examples]$ vi profile_import.yml

- hosts: myhosts
  connection: local
  name: import profile
  gather_facts: False

# file_name: the file name you want to import
# local_import: local file path of the Ansible environment to be imported.
# remote_import: remote path for saving imported files. The file path can be /tmp on the BMC; or a folder on a remote file server, the format is protocol://ip/folder
# protocols: Available values: sftp,https,nfs,cifs,scp
```

```
# file_server_user: remote file server user name
# file_server_pswd: remote file server password

tasks:
- name: import profile
  ibmc_profile_import:
    ibmc_ip: "{{ ibmc_ip }}"
    ibmc_user: "{{ ibmc_user }}"
    ibmc_pswd: "{{ ibmc_pswd }}"
    file_name: "192.168.1.1_20210318045050_profile.xml"
    remote_import: "sftp://192.168.1.1/data/"
    file_server_user: "{{sftp_user}}"
    file_server_pswd: "{{sftp_pswd}}"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to import the profile:

### ansible-playbook profile\_import.yml

The command execution is successful if the following information is displayed:

# 4.8.2 Exporting the Profile

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/profile\_export.yml file.

When exporting files to the Ansible environment, configure the following parameters:

- **file\_name**: name of the exported file. This parameter is optional. If this parameter is not set, the name of the exported file is *IP address\_profile.xml* by default.
- local\_export: local path for storing exported files in the Ansible environment.

### When exporting files to a remote path, configure the following parameters:

- **file\_name**: name of the exported file. This parameter is optional. If this parameter is not set, the name of the exported file is *IP address\_profile.xml* by default.
- remote\_export: remote path for storing exported files.
  - /tmp directory of the iBMC.
  - Folder in the directory of the remote file server. The format of the file path is File transfer protocol: IIIP address of the remote file server/folder.
     Supported file transfer protocols include SFTP, HTTPS, NFS, CIFS, and SCP.
- file\_server\_user: user name for logging in to the remote file server.
- file\_server\_pswd: password for logging in to the remote file server.

# When exporting files to the Ansible environment, configure the following parameters:

```
[plugin@localhost examples] $ vi profile export.yml
- hosts: myhosts
connection: local
name: import profile
gather facts: False
# file name: the file name you want to import
# local import: local file path of the Ansible environment to be imported.
# remote_import: remote path for saving imported files. The file path can be /tmp on
the BMC; or a folder on a remote file server, the format is protocol://ip/folder
    protocols: Available values: sftp, https, nfs, cifs, scp
# file server user: remote file server user name
# file server pswd: remote file server password
tasks:
- name: import profile
ibmc profile import:
ibmc ip: "{{ ibmc ip }}"
ibmc user: "{{ ibmc user }}"
   ibmc_pswd: "{{ ibmc_pswd }}"
     file name: "192.168.1.1 20210318045050 profile.xml"
     local export: "/home"
```

### When exporting files to a remote path, configure the following parameters:

```
[plugin@localhost examples]$ vi profile_export.yml

- hosts: myhosts
  connection: local
  name: import profile
  gather_facts: False

# file_name: the file name you want to import
# local_import: local file path of the Ansible environment to be imported.
```

```
# remote_import: remote path for saving imported files. The file path can be /tmp on
the BMC; or a folder on a remote file server, the format is protocol://ip/folder
# protocols: Available values: sftp,https,nfs,cifs,scp
# file_server_user: remote file server user name
# file_server_pswd: remote file server password

tasks:
- name: import profile
   ibmc_profile_import:
    ibmc_ip: "{{ ibmc_ip }}"
    ibmc_user: "{{ ibmc_user }}"
    ibmc_pswd: "{{ ibmc_pswd }}"
    file_name: "192.168.1.1_20210318045050_profile.xml"
    remote_export: "sftp://192.168.1.1/data/"
    file_server_user: "{{sftp_user}}"
    file_server_pswd: "{{sftp_pswd}}"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to export the profile:

### ansible-playbook profile\_import.yml

The command execution is successful if the following information is displayed:

# 4.9 Upgrading Firmware

### **Function**

Query firmware information.

- Upgrade the BMC, BIOS, and CPLD firmware.
- Upgrade the in-band firmware using Smart Provisioning.

# 4.9.1 Querying Firmware Version (JSON File Generated)

### □ NOTE

- After upgrading the in-band firmware using other tools, you need to restart Smart Provisioning to obtain the latest firmware version information.
- The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to guery the firmware version.

### ansible-playbook get\_firmware\_info\_by\_sp.yml

The command execution is successful if the following information is displayed:

The JSON file (for example, 172.26.100.9\_fwlnfo.json) generated after the query is saved in the /home/plugin/ansible\_ibmc/report/inband\_fw\_info directory by default. You are advised to export the JSON file before viewing it.

# 4.9.2 Upgrading Firmware

# 4.9.2.1 Out-of-Band Firmware Upgrade

# **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/update\_outband\_fw.yml file.

When using a local upgrade file, set the parameters as follows:

**local\_file**: path of the local upgrade file. The format is *directory/file name*, for example, **/home/cpldimage.hpm**.

When using a upgrade file in a remote path, set the parameters as follows:

- remote\_file: path of the upgrade file in the remote directory.
  - If a temporary directory of the iBMC is used, the directory must be /tmp, and
    a file name is required, for example tmp/cpldimage.hpm.
  - If a remote file server directory is used, the format of the file path is file transfer protocol://IP address of the remote file server/directory name/file name, for example, sftp://192.168.1.1/data/cpldimage.hpm.
    - Supported file transfer protocols include SFTP, HTTPS, NFS, CIFS, and SCP.
- file\_server\_user: user name for logging in to the remote file server.
- file\_server\_pswd: password for logging in to the remote file server.

#### ∩ NOTE

- The CX320 and CX621 switch modules support only SFTP, and the MM921 management module supports only SFTP and NFS.
- Before the upgrade, ensure that the hpm file in the firmware package has been uploaded to the corresponding directory on the file server. Obtain the firmware package as follows:
- Visit Support.
- 1. Click a server model.
- 2. Click the Software Download tab.
- 3. Select the patch version.
- 4. Download the required firmware package.

### When using a local upgrade file, set the configuration as follows:

```
[plugin@localhost examples]$ vi update_outband_fw.yml
---
- hosts: myhosts
connection: local
name: update outband fw
gather_facts: False

tasks:
- name: update outband fw
ibmc_outband_fw_update:
   ibmc_ip: "{{ ibmc_ip }}"
   ibmc_user: "{{ ibmc_user }}"
   ibmc_pswd: "{{ ibmc_pswd }}"
   local file: "/home/cpldimage.hpm"
```

### When using a upgrade file in a remote path, set the configuration as follows:

```
# protocols: Available values: sftp,https,nfs,cifs,scp
# file_server_user: remote file server user name
# file_server_pswd: remote file server password

tasks:
- name: update outband fw
  ibmc_outband_fw_update:
  ibmc_ip: "{{ ibmc_ip }}"
  ibmc_user: "{{ ibmc_user }}"
  ibmc_pswd: "{{ ibmc_pswd }}"
  remote_file: "sftp://192.168.1.1/data/cpldimage.hpm"
  file_server_user: "{{sftp_user}}"
  file_server_pswd: "{{sftp_pswd}}"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the upgrade command:

### ansible-playbook update\_outband\_fw.yml

The command execution is successful if the following information is displayed:

# 4.9.2.2 In-Band Firmware Upgrade

#### ☐ NOTE

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

Upgrade the in-band firmware using Smart Provisioning. For details about the supported servers and firmware, see the Smart Provisioning User Guide.

### **Parameter Configuration**

Modify the **image\_url** parameter in the **/home/plugin/ibmc\_ansible/examples/update\_inband\_fw.yml** file.

**image\_url**: specifies the path of the upgrade file. It is in the *File transfer* protocol://User name:Password@Server IP address/Directory/File name format. The file transfer protocols SFTP, HTTPS, NFS, CIFS, and SCP are supported.

#### 

Before the upgrade, ensure that the firmware upgrade package and the digital signature file have been uploaded to the corresponding directory on the file server. You can obtain the firmware upgrade package and digital signature file from FusionServer iDriver.

```
[plugin@localhost examples] vi update_inband_fw.yml
---
- hosts: myhosts
connection: local
name: update inband fw
gather_facts: False

tasks:
- name: update inband fw
ibmc_inband_fw_update:
   ibmc_ip: "{{ ibmc_ip }}"
   ibmc_user: "{{ ibmc_user }}"
   ibmc_pswd: "{{ ibmc_pswd }}"
   image_url:
- "sftp://172.26.200.11/data/NIC-LOM-X722-10GE_SFP-GE_Electrical-FW-3.33_0x80000f09.
zip"
   file_server_user: "{{sftp_user}}"
   file_server_pswd: "{{sftp_pswd}}"
```

Modify the user name and password of the file server in the **myhosts** file under /home/plugin/ibmc\_ansible/examples/group\_vars.

```
[plugin@localhost examples]$ vi
/home/plugin/ibmc_ansible/examples/group_vars/myhosts
---
# Here we define global variables for our server group, but if some servers
# require custom values place these variables in /etc/ansible/hosts to override
# for each individual host
#for create or modify ibmc account
account_user: "account_user"
account_pswd: "account_pswd"

# input the xfusion ibmc user and password
ibmc_user: "ibmc_user"
ibmc_pswd: "ibmc_pwd"

# input the sftp user and password when we need to use the sftp service
sftp_user: "sftp_user"
sftp_pswd: "sftp_pwd"
```

```
# input the cifs user and password when we need to use the cifs service
cifs_user: "cifs_user"
cifs_pswd: "cifs_pwd"

# input the scp user and password when we need to use the scp service
scp_user: "scp_user"
scp_pswd: "scp_pwd"

# if you select SNMP Trap mode as V1 or V2C, you can set the community name
community: "community_name"

# input the os password when you deploy the server os by sp
os pswd: "os pswd"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the upgrade command:

### ansible-playbook update\_inband\_fw.yml

The command execution is successful if the following information is displayed:

# 4.10 Configuring RAID

### 

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

- Configure only the RAID controller cards that support out-of-band management.
- Support the scenario where multiple RAID controller cards are configured.
- Query, configure, modify, and delete the information of the LSI SAS3108, Avago SAS3408iMR, Avago SAS3004iMR, and Avago SAS3508 RAID controller cards.

# 4.10.1 Querying RAID Configuration (JSON File Generated)

### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc ansible/examples
- Run the following command to query the RAID configuration: ansible-playbook get\_raid.yml

The command execution is successful if the following information is displayed:

The JSON file (for example, 172.26.100.9\_RAIDInfo.json) generated after the query is saved in the /var/log/ansible/ibmc/report/raid directory by default. You are advised to export the JSON file before viewing it.

# 4.10.2 Deleting a RAID Array

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/delete\_raid.yml file.

```
[plugin@localhost examples] vi delete_raid.yml
- hosts: myhosts
connection: local
name: delete raid
gather facts: False
# storage id: ID of the storage resource
# 1.Delete one RAID storage, Format: RAIDStorage+Controller_ID
# 2.Delete multiple RAID storage, Separated by commas, Format:
RAIDStorage+Controller ID1, RAIDStorage+Controller ID2,...
# 3.Delete all RAID storage, Format: all
# volume id: Volume resource ID
# 1.Delete one volume, Format: LogicalDrive+Volume ID
# 2.Delete multiple volume, Separated by commas, Format:
LogicalDrive+Volume_ID1,LogicalDrive+Volume_ID2,...
# 3.Delete all volume, Format: all
tasks:
- name: delete raid
```

```
ibmc_delete_raid:
   ibmc_ip: "{{ ibmc_ip }}"
   ibmc_user: "{{ ibmc_user }}"
   ibmc_pswd: "{{ ibmc_pswd }}"
   storage_id: "RAIDStorage0,RAIDStorage1"
   volume_id: "LogicalDrive0,LogicalDrive1"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to delete the RAID:

### ansible-playbook delete\_raid.yml

The command execution is successful if the following information is displayed:

# 4.10.3 Creating a RAID Array

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/create\_raid.yml file.

### NOTICE

Different RAID controller cards support different configurable parameters. For details, see the *V2 and V3 Server RAID Controller Card User Guide* or *V5 Server RAID Controller Card User Guide*.

```
[plugin@localhost examples]$ vi create_raid.yml
---
- hosts: myhosts
  connection: local
  name: create raid
  gather_facts: False
```

```
# storage id: ID of the storage resource. Format: RAIDStorage+Controller ID
# capacity_mbyte: Volume capacity, must be an integer, the size unit is MB. It is an
optional parameter
# stripe size: Stripe size of a volume, must be an integer. It is an optional parameter.
Available values: 65536, 131072, 262144, 524288, 1048576
# cachecade flag: Whether it is a CacheCade volume. It is an optional parameter, Available
values: True, False
# drives: Member disk list number. It is a mandatory parameter. Format: "1,2,.,N"
# volume raid level: RAID level of the volume. It is a mandatory parameter. Available
values: RAIDO, RAID1, RAID5, RAID6, RAID10, RAID50, RAID60
# volume name: Volume name. It is an optional parameter. A string of up to 15 bytes.
Value range: ASCII code corresponding to 0x20 to 0x7E
# df read policy: Default read policy of the volume. It is an optional parameter.
Available values: NoReadAhead, ReadAhead
# df write policy: Default write policy of the volume. It is an optional parameter.
Available values: WriteThrough, WriteBackWithBBU, WriteBack
# df cache policy: Default cache policy of the volume. It is an optional parameter.
Available values: CachedIO, DirectIO
# span num: Number of spans of the volume, must be an integer. It is an optional parameter
# 1.Set this parameter to 1 when creating a RAIDO, RAID1, RAID5, or RAID6 array.
# 2.Set this parameter to a value from 2 to 8 when creating a RAID10, RAID50, or RAID60
# access policy: Volume access policy. It is an optional parameter. Available values:
ReadWrite, ReadOnly, Blocked
# disk cache policy: Cache policy for member disks. It is an optional parameter.
Available values: Unchanged, Enabled, Disabled
# init mode: Volume initialization mode. It is an optional parameter. Available values:
UnInit, QuickInit, FullInit
tasks:
- name: create raid
ibmc create raid:
ibmc ip: "{{ ibmc ip }}"
   ibmc user: "{{ ibmc user }}"
  ibmc pswd: "{{ ibmc pswd }}"
volumes:
storage id: "RAIDStorage0"
capacity_mbyte: 1000
   stripe size: 65536
      cachecade flag: False
       drives: "0,1"
       volume raid level: "RAIDO"
       volume name: "volume name"
       df read policy: "NoReadAhead"
       df_write_policy: "WriteThrough"
       df_cache_policy: "CachedIO"
       span num: 1
       access_policy: "ReadWrite"
       disk_cache_policy: "Unchanged"
       init_mode: "UnInit"
```

1. Go to the /home/plugin/ibmc\_ansible/examples directory.

### cd /home/plugin/ibmc\_ansible/examples

2. Run the following command to create a RAID:

### ansible-playbook create\_raid.yml

The command execution is successful if the following information is displayed:

# 4.10.4 Modifying RAID Configuration

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/modify\_raid.yml file.

### NOTICE

Different RAID controller cards support different parameters. For details, see the V2 and V3 Server RAID Controller Card User Guide or V5 Server RAID Controller Card User Guide.

```
[plugin@localhost examples]$ vi modify_raid.yml
---
- hosts: myhosts
  connection: local
  name: modify raid
  gather_facts: False

# storage_id: ID of the storage resource. Format: RAIDStorage+Controller_ID
# volume_id: Volume resource ID. Format: LogicalDrive+Volume_ID
# volume_name: Volume name. It is an optional parameter. A string of up to 15 bytes.
Value range: ASCII code corresponding to 0x20 to 0x7E
# df_read_policy: Default read policy of the volume. It is an optional parameter.
Available values: NoReadAhead, ReadAhead
# df_write_policy: Default write policy of the volume. It is an optional parameter.
Available values: WriteThrough, WriteBackWithBBU, WriteBack
# df_cache_policy: Default cache policy of the volume. It is an optional parameter.
```

```
Available values: CachedIO, DirectIO
# boot enable: Whether it is the boot device. Available values: True.
# bgi enable: Whether background initialization is enabled. Available values: True,
False.
# access policy: Volume access policy. It is an optional parameter. Available values:
ReadWrite, ReadOnly, Blocked
# ssd cache enable: Whether the CacheCade volume is used as the cache. Available values:
# disk cache policy: Cache policy for member disks. It is an optional parameter.
Available values: Unchanged, Enabled, Disabled
tasks:
- name: modify raid
ibmc modify raid:
   ibmc ip: "{{ ibmc ip }}"
ibmc user: "{{ ibmc user }}"
ibmc pswd: "{{ ibmc pswd }}"
  volumes:
   storage id: "RAIDStorage0"
    volume_id: "LogicalDrive0"
    volume_name: "volume_name"
      df_read_policy: "NoReadAhead"
      df write policy: "WriteThrough"
      df_cache_policy: "CachedIO"
      boot enable: True
      bgi enable: False
      access_policy: "ReadWrite"
      ssd_cache_enable: False
      disk_cache_policy: "Unchanged"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to modify the RAID configuration:

### ansible-playbook modify\_raid.yml

# 4.11 Deploying the OS

### □ NOTE

- The MM921 management module and CX320/CX621 switch modules do not support this function.
- The RAID configuration is complete for the server, on which the OS is to be deployed.
- If ServiceCD2.0 is used, the logical drive on the server where the OS is to be deployed cannot exceed 2 TB. Otherwise, ServiceCD2.0 cannot identify the logical drive.

# 4.11.1 Deploying the OS Using Smart Provisioning

For details about the servers supported by Smart Provisioning, see the Smart Provisioning User Guide.

### 

The commands deploy\_centos7u3\_by\_sp.yml, deploy\_esxi65\_by\_sp.yml, and deploy\_win2012r2\_by\_sp.yml can be used. The following uses deploy\_centos7u3\_by\_sp.yml as an example.

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/deploy\_centos7u3\_by\_sp.yml file.

For details about the parameters, see Table 4-1.

```
[plugin@localhost examples] vi deploy_centos7u3_by_sp.yml
- hosts: myhosts
connection: local
name: ibmc deploy centos7u3 by sp
gather facts: False
#os_img: The os image path ; Format:
protocol://Username:Password@IPaddress/Folder/image file; Available protocol:
nfs, cifs, https
#OSType:Os type; Available values:RHEL6U9, RHEL6U10, RHEL7U3,RHEL7U4, RHEL7U5, RHEL7U6,
CentOS6U9, CentOS6U10, CentOS7U3, CentOS7U4, CentOS7U5, CentOS7U6, ESXi6.0, ESXi6.5,
# SLES11SP4, SLES12SP2, SLES12SP3, Ubuntu16.04, Ubuntu16.04.1, Ubuntu16.04.2, Win2016,
Win2016 Standard Desktop, Win2016 Standard Core, Win2016 Datacenter Desktop
# Win2016 Datacenter Core, Win2012 R2, Win2012 R2 Standard Desktop, Win2012 R2 Standard
Core, Win2012 R2 Datacenter Desktop, Win2012 R2 Datacenter Core
# EulerOSV2SP3
#InstallMode: OS Installation mode; Available values:Recommended, Customized
#Language: Available values: Please refer to the installation guide of the OS.
#TimeZone: Available values: Please refer to the installation guide of the OS.
#Keyboard: Available values: Please refer to the installation guide of the OS.
#BootType: Bios boot mode, This parameter is optional; Available values: UEFIBoot,
```

```
LegacyBoot, SecureBoot
#CDKey: key of the OS Installation, This parameter is optional
#RootPwd: Root user password, this parameter is mandatory;
# Windows: a sting of at least 6 characters.SUSE: a sting of at least 6 characters.
# Centos/Redhat/ EulerOS: a sting of at least 6 characters excluding #,$, and space.
# Ubuntu: a sting of at least 8 characters excluding #, $, and space.
# Vmware: a string of 7 to 40 characters. For the ESXi 6.7, the password must consist
of letters, digits, and special characters.
# (NOTE: Smart Provisioning supports special characters #, $ and spaces from V119.)
#HostName: Host Name, This parameter is optional Installation
#CheckFirmware: Whether to verify firmware. This parameter is optional; Available
values:True, False
#Partition: Partition information. This parameter is optional. Please refer to the
installation guide of the OS
#Software: Software list. This parameter is mandatory.Format:{ "FileName": "iBMA" }
#Autopart: Whether auto-partitioning is supported. Linux/VMware: true Window: false
#MediaType:Type of the media where the OS can be deployed. This parameter is optional;
Available values: SANBoot, Disk, USB
#AutoPosition: Whether the installation drive is automatically selected; Available
values:True
#NetCfg: Network config
tasks:
- name: ibmc deploy centos7u3 by sp
ibmc deploy_os_by_sp:
ibmc ip: "{{ ibmc ip }}"
ibmc user: "{{ ibmc user }}"
ibmc pswd: "{{ ibmc pswd }}"
os img: "nfs://172.26.200.11/data/centeros7u3.iso"
    os_config:
    InstallMode: "Recommended"
    OSType: "CentOS7U3"
      BootType: "UEFIBoot"
      CDKey: ""
      RootPwd: "{{ os pswd }}"
      HostName: "test"
      Language: "en_US.UTF-8"
      TimeZone: "America/New_York"
      Keyboard: "us"
      CheckFirmware: False
      Partition: []
      Autopart: True
      AutoPosition: True
      Software: []
      NetCfg:
         - Device:
             Name: "eth10086"
             MAC: "**:**:**:**:**
          IPv4Addresses:
             - Address: "192.168.2.44"
               SubnetMask: "255.255.0.0"
               Gateway: "192.168.2.1"
               AddressOrigin: "Static"
           IPv6Addresses:
             - Address: ""
               PrefixLength: ""
```

Gateway: ""
AddressOrigin: "Static"
NameServers:
- DNS: "192.168.2.1"
- DNS: "192.168.2.2"

### Table 4-1 Parameters

Parameter	Description	Value		
os_img	OS image path (mandatory).	Format: File Transfer Protocol://User name:Password@ Server IP address/Directory/File name The file transfer protocols SFTP,		
		HTTPS, NFS, CIFS, and SCP are supported.		
InstallMode	Installation mode (mandatory).	<ul><li>Recommended</li><li>Customized</li></ul>		
OSType	Type of the OS to be installed (mandatory).	Value: RHEL6U9, RHEL6U10, RHEL7U3, RHEL7U4, RHEL7U5, RHEL7U6, CentOS6U9, CentOS6U10, CentOS7U3, CentOS7U4, CentOS7U5, CentOS7U6, ESXi6.0, and ESXi6.5 ESXi6.7, SLES11SP4, SLES12SP2, SLES12SP3, Ubuntu16.04, Ubuntu16.04.1, Ubuntu16.04.2, Win2016, Win2016 Standard Desktop, Win2016 Standard Core, Win2016 Datacenter Desktop, Win2016 Datacenter Core, Win2012_R2, and Win2012_R2 Standard Desktop, Win2012_R2 Datacenter Desktop, Win2012_R2 Datacenter Core, EulerOSV2SP3		
BootType	BIOS boot mode (optional).	<ul><li>UEFIBoot</li><li>LegacyBoot</li><li>SecureBoot</li></ul>		
CDKey	OS installation key (optional).	<ul> <li>For the Windows or VMware OS, this parameter is optional and can be set to a 25-digit value with every five digits connected by a hyphen (-). The value can contain uppercase letters (A to Z), lowercase letters (a to z), and digits (0 to 9).</li> <li>For Linux, this parameter is left</li> </ul>		

Parameter	rameter Description Value			
		empty.		
RootPwd	Initial password of the administrator	Set this parameter in the myhosts file based on the following rules:		
	(mandatory).	<ul> <li>Windows: The parameter value must contain at least six digits.</li> </ul>		
		<ul> <li>SUSE: The parameter value must contain at least six digits.</li> </ul>		
		<ul> <li>CentOS, Red Hat and EulerOS:         The parameter value must contain at least six digits and cannot contain a "#", "\$", or space.     </li> </ul>		
		<ul> <li>Ubuntu: The password must contain at least 8 characters and cannot contain #, \$, or spaces.</li> </ul>		
		VMware OS: The parameter value must contain at least seven digits. For VMware ESXi 6.7, the parameter value must contain at least three types of characters, including letters, digits, and special characters and cannot exceed 40 digits.		
		NOTE Smart Provisioning V119 and later versions support the following special characters: #\$.		
HostName	Host name (optional).	The value contains a maximum of 15 characters, including uppercase letters (A to Z), lowercase letters (a to z), digits (0 to 9), and hyphens (-).		
		<ul> <li>For Linux, this parameter is optional and takes effect only after the network is configured.</li> </ul>		
		<ul> <li>For Windows, this parameter is optional.</li> </ul>		
		<ul> <li>For VMware OS, this parameter is optional and takes effect only after the network is configured.</li> </ul>		
Language	System language (mandatory).	The parameter is a string of characters. For details, see the installation guide of the OS.		
		<ul> <li>For Linux, this parameter is mandatory.</li> </ul>		
		<ul> <li>For Windows, this parameter is mandatory.</li> </ul>		

Parameter	Description	Value		
		For VMware OS, leave it blank.		
TimeZone	System time zone (mandatory).	<ul> <li>The parameter is a string of characters. For details, see the installation guide of the OS.</li> <li>For Linux, this parameter is mandatory.</li> <li>For Windows, this parameter is mandatory.</li> <li>For VMware OS, leave it blank.</li> </ul>		
Keyboard	System keyboard type (mandatory).	<ul> <li>The parameter is a string of characters. For details, see the installation guide of the OS.</li> <li>For Linux, this parameter is mandatory.</li> <li>For Windows, this parameter is mandatory.</li> <li>For VMware OS, leave it blank.</li> </ul>		
CheckFirmware	Specifies whether to verify firmware. This parameter is mandatory.	true     false		
Partition	Partition information (optional). The format is as follows: Partition: - Size: "64" FileSystem: "NTFS" Name: "C"	<ul> <li>Windows: The value of Name is a string of characters from C to Z. Set FileSystem to NTFS. The value of Size is greater than 32. If the value is max, the entire disk is used as the data disk.</li> <li>Linux: The value of Name cannot contain &lt;&gt; :&amp; or spaces, for example, I, Ihome, and swap. The value of FileSystem can be ext4, ext3, ext2, or xfs. The value of Size is greater than 0. The root partition size must be greater than 10, and the swap partition size must be greater than 1. If the value is max, the remaining space is allocated.</li> <li>The VMware OS does not support this function.</li> </ul>		
Autopart	Specifies whether automatic partitioning is supported (mandatory).	<ul> <li>For Linux and VMware OS, the value is true.</li> <li>For Windows, the value is false.</li> </ul>		
MediaType	Media type that supports system deployment (optional). If this	SANBoot: Deploy the OS on the SANBoot drive (only VMware 6.5.1 and VMware 6.7 are		

Parameter	Description	Value		
	parameter is not specified, the system is deployed on the local drive.	<ul> <li>supported).</li> <li>Disk: Deploy the OS on the drive.</li> <li>USB: Deploy the OS on the USB device (only VMware 6.5 is supported).</li> </ul>		
AutoPosition	Specifies whether auto-selection of the installation drive is supported (mandatory).	Value: <b>true</b> (The installation drive can only be automatically selected now.)		
Software	List of software to be installed (mandatory). The format is as follows: Software: - FileName: "iBMA"	iBMA		
NetCfg	Network configuration (optional).	[] or configure the following parameters:  NOTE  [] indicates that no device is specified and batch deployment is supported.  • Device: device network information.  - Name: name of the network port on the NIC of the server to be deployed.  - MAC: device MAC address.  • IPv4Addresses: IPv4 address information of the network port.  - Address: IPv4 address.  - SubnetMash: subnet mask.  - AddressOrigin: mode for obtaining the IPv4 address. It can be Static or DHCP.  - Gateway: IPv4 gateway address.  • IPv6Addresses: IPv6 address information of the network port.  - Address: IPv6 address.  - PrefixLength: prefix length of the IPv6 address.  - AddressOrigin: mode for obtaining the IPv6 address. It can be Static or DHCP.  - Gateway: IPv6 gateway		

Parameter	Description	Value	
		NOTE  This option is not supported by Ubuntu and VMware OS.	
		NameServers: IP address of the DNS server. It can be an IPv4 or IPv6 address.	

The example values of **OSType**, **Language**, **TimeZone**, and **Keyboard** are as follows:

OSType	Language	TimeZone	Keyboard
RHEL/CentOS/Eul erOS/Ubuntu	en_US.UTF-8	America/New_York	us
SLES	en_US	America/New_York	english-us
Windows	en-US	Eastern Standard Time	0x00000409

### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- Run the following deployment commands: ansible-playbook deploy\_centos7u3\_by\_sp.yml

[plugin@loca	lhost exampl	es]\$ <b>ansib</b>	le-playbook	deploy_centos7u3	B_by_sp.yml
PLAY [ibmc d	leploy centos	7u3 by sp]			
*****	*****	*****	******	* * * * * * * * * * * * * * * * * * * *	*******
****	****	*****	*****	******	******
TASK [ibmc d	leploy centos	7u3 by sp]			
*****	****	*****	*****	*****	******
*****	****	*****	*****	*****	*****
ok: [host1.d	lomain.com]				
PLAY RECAP					
*****	****	*****	*****	******	******
*****	****	*****	*****	******	******
*****	****	*****	* * * *		
host1.domain	.com	: ok=1	changed=0	unreachable=0	failed=0
skipped=0	rescued=0	ignored=0			

# 4.12 BIOS Management

### □ NOTE

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

Query and set BIOS information and restore the default BIOS settings.

# 4.12.1 Querying BIOS Information (JSON File Generated)

### (Optional) Parameter Settings

Modify the bios\_attribute parameter in the /home/plugin/ibmc\_ansible/examples/get\_bios.yml file.

**bios\_attribute**: Specifies the BIOS parameters to be queried. This parameter is optional. If this parameter is not specified, information about all BIOS parameters is displayed.

The *IP address\_BIOSInfo.json* file is generated and saved in the */home/plugin/ansible\_ibmc/report/bios/* folder.

### □ NOTE

- IP address\_BIOSInfo.json: Set the IP address to the configured server IP address.
- /home/plugin/ansible\_ibmc/report/bios/: Replace plugin with the actual user name.

```
[plugin@localhost examples]$ vi get_bios.yml
---
- hosts: myhosts
connection: local
name: get bios
gather_facts: False

# bios_attribute: User-specified BIOS attributes to be queried

tasks:
- name: get bios
   ibmc_get_bios:
   ibmc_ip: "{{ ibmc_ip }}"
   ibmc_user: "{{ ibmc_user }}"
   ibmc_pswd: "{{ ibmc_pswd }}"
   bios_attribute:
   - QuickBoot
   - QuietBoot
```

### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- Run the following command to query the BIOS information. ansible-playbook get\_bios.yml

#### The command execution is successful if the following information is displayed:

# 4.12.2 Setting BIOS Information

### **Parameter Configuration**

Modify the values of **Immediately** and **bios\_attribute** in the **/home/plugin/ibmc\_ansible/examples/set\_bios.yml** file.

Immediately: Specifies the effective time. The options are True and False. The
default value is False. True indicates that the server is restarted immediately for
the settings to take effect. False indicates that you need to restart the server for
the settings to take effect.

### **NOTICE**

Automatic server restart affects services. Exercise caution when performing this operation.

bios attribute: BIOS parameters to be set. This parameter is mandatory.

### □ NOTE

The following example describes how to set **QuickBoot** and **QuietBoot**. For details about configurable BIOS parameters, see the Server Purley Platform BIOS Parameter Reference.

```
[plugin@localhost examples]$ vi set_bios.yml
---
- hosts: myhosts
  connection: local
  name: set ibmc bios
  gather_facts: False
```

```
# Immediately: Whether to restart the system immediately for the configuration to take
effect: True, False
# bios_attribute: BIOS attributes set by the user

tasks:
- name: set ibmc bios
ibmc_set_bios:
ibmc_ip: "{{ ibmc_ip }}"
ibmc_user: "{{ ibmc_user }}"
ibmc_user: "{{ ibmc_pswd }}"
Immediately: False
bios_attribute:
    QuickBoot: Disabled
    QuietBoot: Enabled
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to set the BIOS information:

### ansible-playbook set\_bios.yml

The command execution is successful if the following information is displayed:

# 4.12.3 Restoring Default BIOS Settings

### **Parameter Configuration**

Modify the **Immediately** parameter in the **/home/plugin/ibmc\_ansible/examples/reset\_bios.yml** file.

**Immediately**: Specifies the effective time. The options are **True** and **False**. The default value is **False**.

- True: The server automatically restarts for the upgrade to take effect.
- False: You need to restart the server for the settings to take effect.

### **NOTICE**

Automatic server restart affects services. Exercise caution when performing this operation.

```
[plugin@localhost examples] $ vi reset_bios.yml

---
- hosts: myhosts
  connection: local
  name: reset ibmc bios
  gather_facts: False

# Immediately: Whether to restart the system immediately for the configuration to take
effect: True, False

tasks:
- name: reset ibmc bios
  ibmc_reset_bios :
   ibmc_ip: "{{ ibmc_ip }}"
  ibmc_user: "{{ ibmc_user }}"
  ibmc_pswd: "{{ ibmc_pswd }}"
  Immediately: False
```

#### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to reset the BIOS information:

### ansible-playbook reset\_bios.yml

# 4.13 Log Management

### 

The MM921 management module and CX320/CX621 switch modules do not support this function.

#### **Function**

Collect iBMC logs in one-click mode, collect SEL logs, and clear SEL logs.

# 4.13.1 Collecting iBMC Logs in One-Click Mode

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/collect\_ibmc\_logs.yml file.

- save\_mode: Files are stored on a remote file server or a local file server. To store
  files on a remote file server, set this parameter to sftp, https, nfs, cifs, or scp.
  For local storage, set this parameter to local.
- **file\_server\_ip**: IP address of the remote file server. This parameter is required when **save\_mode** is set to **sftp**, **https**, **nfs**, **cifs**, or **scp**.
- **file\_server\_user**: user name for logging in to the remote file server. This parameter is required when **save\_mode** is set to **sftp**, **https**, **cifs**, or **scp**.
- **file\_server\_pswd**: password for logging in to the remote file server. This parameter is required when **save\_mode** is set to **sftp**, **https**, **cifs**, or **scp**
- file\_name: log file name and path If only the file name is specified, the log file is saved in the /home/plugin/ansible\_ibmc/report/collect\_IBMC\_log/ directory by default. In the directory, plugin indicates the actual user name.

```
[plugin@localhost examples]$ vi collect_ibmc_logs.yml
---
- hosts: myhosts
  connection: local
  name: collect logs
  gather_facts: False

# save_mode: place to save logs: local, sftp, https, nfs, cifs, scp
# file_server_ip: ip address of file server, if save_mode is local, this parameter can be left blank.
# file_server_user: the user of file server
# file_server_pswd: the password of file server
# file_name: Log file storage path and file name
```

```
tasks:
- name: collect logs
ibmc_collect_logs :
   ibmc_ip: "{{ ibmc_ip }}"
   ibmc_user: "{{ ibmc_user }}"
   ibmc_pswd: "{{ ibmc_pswd }}"
   save_mode: "sftp"
   file_server_ip: "sftp_server_ip"
   file_server_user: "{{ sftp_user }}"
   file_server_pswd: "{{ sftp_pswd }}"
   file_name: "/usr/dump.tar.gz"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to collect iBMC logs in one-click mode: ansible-playbook collect\_ibmc\_logs.yml

The command execution is successful if the following information is displayed:

# 4.13.2 Collecting SELs

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/collect\_sel\_logs.yml file.

save\_mode: Files are stored on a remote file server or a local file server. To store
files on a remote file server, set this parameter to sftp, https, nfs, cifs, or scp.
For local storage, set this parameter to local.

- **file\_server\_ip**: IP address of the remote file server. This parameter is required when **save\_mode** is set to **sftp**, **https**, **nfs**, **cifs**, or **scp**.
- **file\_server\_user**: user name for logging in to the remote file server. This parameter is required when **save\_mode** is set to **sftp**, **https**, **cifs**, or **scp**.
- file\_server\_pswd: password for logging in to the remote file server. This
  parameter is required when save\_mode is set to sftp, https, cifs, or scp
- file\_name: log file name and path If only the file name is specified, the log file is saved in the /home/plugin/ansible\_ibmc/report/collect\_SEL\_log/ directory by default. In the directory, user indicates the actual user name.

```
[plugin@localhost examples] vi collect_sel_logs.yml
- hosts: myhosts
connection: local
name: collect sel logs
gather facts: False
# save mode: place to save logs: local, sftp, https, nfs, cifs, scp
# file server ip: ip address of file server, if save mode is local, this parameter
be left blank.
# file server user: the user of file server
# file server pswd: the password of file server
# file name: Log file storage path and file name
tasks:
- name: collect sel logs
ibmc collect sel logs :
ibmc ip: "{{ ibmc ip }}"
ibmc user: "{{ ibmc user }}"
ibmc pswd: "{{ ibmc pswd }}"
save mode: "local"
file_server_ip: "sftp_server_ip"
file_server_user: "{{ sftp_user }}"
file_server_pswd: "{{    sftp_pswd }}"
     file_name: "/home/plugin/SEL_log.tar.gz"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to collect SEL logs:

### ansible-playbook collect\_sel\_logs.yml

# 4.13.3 Clearing SELs

### **Procedure**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- Run the following command to clear SELs: ansible-playbook clear\_sel\_logs.yml

### 4.14 Common Interface

### 

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

A common public interface is provided. You can configure the URL and request body of the interface to implement all Redfish functions.

For details about Redfish, see the Server iBMC Redfish API Description.

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/common\_api.yml file.

- url: request URL. The path must start with /redfish, for example, /redfish/v1/Chassis/1/Oem/xFusion/Actions/Chassis.ControlIndicatorLED.
- request\_method: request method. The value can be patch, post, get, or delete.
- request\_body: request body. The request body is in JSON format, for example, '{"IndicatorLED":"Blinking", "Duration":50}'. This parameter cannot be set when the request\_method is set to get or delete.

```
[plugin@localhost examples] vi common_api.yml
- hosts: myhosts
connection: local
name: common api
gather facts: False
# url: request resource
# request_method: request method: GET, POST, PATCH, DELETE
# request body: request body content
tasks:
- name: common api
ibmc common api:
ibmc ip: "{{ ibmc ip }}"
   ibmc user: "{{ ibmc user }}"
   ibmc pswd: "{{ ibmc pswd }}"
   url: "/redfish/v1/Chassis/1/Oem/xFusion/Actions/Chassis.ControlIndicatorLED
request method: "POST"
    request_body: '{"IndicatorLED":"Blinking", "Duration":50}'
```

### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command:

#### ansible-playbook common api.yml

### 4.15 Local File Transfer

### 

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

Upload files from a local end and download files to a local end.

# 4.15.1 Uploading Local Files

### **Parameter Configuration**

Modify the **imgfile** parameter in the **/home/plugin/ibmc\_ansible/examples/upload\_file.yml** file.

**imgfile**: path and name of the local file to be uploaded. The format is *file path/file name*, for example, **/home/**plugin/**SOO.keytab**. The uploaded file is saved in the **/tmp/web** directory of the iBMC.

### □ NOTE

For details about the file types supported by the server, see the API Description > Operation on Update Service Resources > Uploading a File in the Server iBMC Redfish API Description.

```
[plugin@localhost examples]$ vi upload_file.yml
---
- hosts: myhosts
connection: local
```

```
name: file upload
gather facts: False
# imgfile: User-specified file to be uploaded, The format is file path/file name. After
the upload is successful, the file is placed in the /tmp/web on iBMC.
        # The file types allowed by the V3 board are as follows:
{"hpm", "cer", "pem", "cert", "crt", "pfx", "p12", "xml", "keys", "pub"}
        # The file types allowed by the V5 board are as follows:
{"hpm", "zip", "asc", "cer", "pem", "cert", "crt", "pfx", "p12", "xml", "keys", "pub", "
kevtab"}
# The maximum allowable hpm file of V3 single-board is 46M; the maximum allowable
hpm, zip, asc file of v5 single-board is 90M.
# The maximum allowable size of cer, pem, cert, crt, xml, p12, and keytab files
is 1M.
        # The maximum allowable size of pfx and keys files is 2M, and the maximum allowable
size of pub files is 2KB.
tasks:
- name: file upload
ibmc upload file :
ibmc_ip: "{{    ibmc_ip }}"
ibmc user: "{{ ibmc user }}"
ibmc pswd: "{{ ibmc pswd }}"
imgfile: "/home/plugin/SOO.keytab"
```

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to upload a local file:

### ansible-playbook upload\_file.yml

### 4.15.2 Downloading a File to a Local Computer

### **Parameter Configuration**

Modify the values of **file\_name** and **local\_path** in the **/home/plugin/ibmc\_ansible/examples/download\_file.yml** file.

- **file\_name**: name of the file to be downloaded from the iBMC. The file must be in the **/tmp/web** directory or its subdirectory.
  - For example, if the file path is /tmp/web/111.txt, set this parameter to 111.txt. If the file path is /tmp/web/\*\*\*/111.txt, set this parameter to /\*\*\*/111.txt.
- local\_path: local path for storing the file. If this parameter is not specified, the file
  is downloaded to the /home/plugin/ansible\_ibmc/report/download/ directory
  by default.

### □ NOTE

- plugin: Use the actual user name.
- After the file is downloaded, the file name is automatically changed. The IP address and time
  are added to the beginning of the original file name.

```
[plugin@localhost examples] vi download file.yml
- hosts: myhosts
connection: local
name: file download
gather facts: False
# file name: the name of the file to be downloaded, from /tmp/web of iBMC
# local path: local path for storing files, The default file save path is
/home/plugin/ansible ibmc/report/download/
tasks:
- name: file download
ibmc download file :
ibmc_ip: "{{    ibmc_ip }}"
   ibmc_user: "{{ ibmc_user }}"
   ibmc pswd: "{{ ibmc pswd }}"
    file name: "SOO.keytab"
    local path: "/home/plugin/"
```


### Commands

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to download the file:

### ansible-playbook download\_file.yml

The command execution is successful if the following information is displayed:

```
[plugin@localhost examples]$ ansible-playbook download_file.yml /usr/local/python3/lib/python3.7/site-packages/cryptography-3.1.1-py3.7-linux-x 86_64.egg/cryptography/hazmat/bindings/openssl/binding.py:177: CryptographyDeprecationWarning: OpenSSL version 1.0.2 is no longer supported by the OpenSSL project, please upgrade. The next version of cryptography will drop support for it.
```



# 4.16 Managing the HTTPS Server Root Certificate

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

You can import or delete the root certificate of the remote HTTPS server and import the revocation list of the root certificate of the remote HTTPS server.

∩ NOTE

Only the iBMC 3.01.12.20 or later versions support this function.

## 4.16.1 Importing the Root Certificate of a Remote HTTPS Server

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/https\_ca\_import.yml file.

- certpath: the path of the root certificate of the remote HTTPS server. The local path, iBMC's tmp directory, and remote path (for example, sftp://user:password@ip/path) are supported. Currently, the supported transfer protocols include HTTPS, SCP, SFTP, CIFS, and NFS. The file name extension can be .crt, .cer, or .pem.
- certID: ID of the root certificate authenticated by the remote HTTPS server. The
  value is an integer that ranges from 5 to 8. Certificates 5 to 8 are used for remote
  file transfer over HTTPS.

### **NOTICE**

If a certificate with the specified certificate ID has been imported, the new certificate will overwrite the old one. To prevent certificate conflicts, query the certificate ID before setting certID. For details, see 4.17 Querying Security Service Information (JSON File Generated).

- usage: certificate usage. The value is FileTransfer.
- import\_location: the location of the certificate to be imported. The value can be tmp (/tmp directory of the iBMC), local (local executor), or sftp/https/nfs/cifs/scp (remote file server).

### **NOTICE**

### Either CertID or usage must be set.

```
[plugin@localhost examples] vi https_ca_import.yml
- hosts: myhosts
connection: local
name: import https ca
gather facts: False
# certpath: certificate to be imported (including the path and file name).
# When the certificate is imported from a remote file server, the format is
protocol://file server ip/folder/file name
# The file name extension must be in (".crt", ".cer", ".pem").
# certID: ID of the root certificate used to authenticate the remote HTTPS server.
# - Available values: [5, 6, 7, 8].
# usage: certificate usage
# - Available values: "FileTransfer".
# import location: location of the certificate.
# If the certificate is stored in the tmp directory of the BMC, the value is tmp.
# If the certificate is stored in a local directory, the value is local.
# If the certificate is stored on a remote file server, the value is the file server
protocol.
   # - Available values: tmp, local, sftp, https, nfs, cifs, scp
# file server user: remote file server user name
# file_server_pswd: remote file server password
tasks:
- name: import https ca
ibmc https ca import:
ibmc ip: "{{ ibmc ip }}"
ibmc user: "{{ ibmc user }}"
ibmc_pswd: "{{ ibmc_pswd }}"
certpath: "/tmp/xFusionCA3.crt"
certID: 5
# usage: "FileTransfer"
import location: "tmp"
# file server user: "{{sftp user}}"
# file server pswd: "{{sftp pswd}}}"
```

server:

### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to import the root certificate of the remote HTTPS

### ansible-playbook https ca import.yml

The command execution is successful if the following information is displayed:

### 4.16.2 Deleting the Root Certificate of a Remote HTTPS Server

### **Parameter Configuration**

Modify the /home/plugin/ibmc ansible/examples/delete https ca.yml file.

certID: ID of the root certificate authenticated by the remote HTTPS server. The value is an integer that ranges from 5 to 8. Certificates 5 to 8 are used for remote file transfer over HTTPS.

### 

Before setting the certID, you can query the ID of the imported remote HTTPS server root certificate by referring to 4.17 Querying Security Service Information (JSON File Generated).

```
[plugin@localhost examples]$ vi delete_https_ca.yml
---
- hosts: myhosts
connection: local
name: delete https ca
gather_facts: False

# certID: ID of the root certificate used to authenticate the remote HTTPS server.
# - Available values: [5, 6, 7, 8].
```

```
tasks:
- name: delete https ca
  ibmc_delete_https_ca:
    ibmc_ip: "{{ ibmc_ip }}"
    ibmc_user: "{{ ibmc_user }}"
    ibmc_pswd: "{{ ibmc_pswd }}"
    certID: 6
```

### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to delete the root certificate of the remote HTTPS server:

### ansible-playbook delete\_https\_ca.yml

The command execution is successful if the following information is displayed:

## 4.16.3 Importing a CRL of a Remote HTTPS Server

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/https\_crl\_import.yml file.

- certpath: the path of the CRL of the root certificate of the remote HTTPS server.
   The local path, iBMC's tmp directory, and remote path (for example, sftp://user:password@ip/path) are supported. Currently, the supported transfer protocols include HTTPS, SCP, SFTP, CIFS, and NFS. The file name extension must be .crl.
- certID: ID of the root certificate object that issues the CRL. The value must be the certID value of an array member in the RootCertificate object returned when the

security service information is queried. For details about how to query security service information, see 4.17 Querying Security Service Information (JSON File Generated).

- usage: certificate usage. The value is FileTransfer.
- import\_location: the location of the remote HTTPS server's root certificate CRL to be imported. The value can be tmp (/tmp directory of the iBMC), local (local executor), or sftp/https/nfs/cifs/scp (remote file server).

### **NOTICE**

### Either CertID or usage must be set.

```
[plugin@localhost examples] vi https crl import.yml
- hosts: myhosts
connection: local
name: import https crl
gather facts: False
# certpath: the crl file to be imported (including the path and file name).
# When the certificate is imported from a remote file server, the format is
protocol://file server ip/folder/file name
# The file name extension must be .crl.
# certID: ID of the root certificate used to authenticate the remote HTTPS server.
# - Available values: [5, 6, 7, 8].
# usage: certificate usage
# - Available values: "FileTransfer".
# import location: location of the crl.
# If the crl file is stored in the tmp directory of the BMC, the value is tmp.
# If the crl file is stored in a local directory, the value is local.
# If the crl file is stored on a remote file server, the value is the file server
protocol.
   # - Available values: tmp, sftp, https, nfs, cifs, scp
# file server user: remote file server user name
# file server pswd: remote file server password
tasks:
- name: import https crl
ibmc https crl import:
ibmc ip: "{{ ibmc ip }}"
ibmc_user: "{{ ibmc_user }}"
ibmc pswd: "{{ ibmc pswd }}"
certpath: "/tmp/xFusionCA3.crl"
certID: 5
# usage: "FileTransfer"
import location: "tmp"
# file_server_user: "{{sftp_user}}"
# file_server_pswd: "{{sftp_pswd}}}"
```

### **Commands**

1. Go to the /home/plugin/ibmc\_ansible/examples directory.

### cd /home/plugin/ibmc\_ansible/examples

2. Run the following command to import the root certificate CRL of the remote HTTPS server:

### ansible-playbook https\_crl\_import.yml

The command execution is successful if the following information is displayed:

# 4.17 Querying Security Service Information (JSON File Generated)

#### **™** NOTE

The MM921 management module and CX320/CX621 switch modules do not support this function.

### **Function**

Query information about the security service supported by the server.

### Commands

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to query the security service information.

### ansible-playbook get\_security\_service\_information.yml

The command execution is successful if the following information is displayed:

```
[plugin@localhost examples]$ ansible-playbook

get_security_service_information.yml

/usr/local/python3/lib/python3.7/site-packages/cryptography-3.1.1-py3.7-linux-x
```

The *IP address\_*SecurityServiceInfo.json file is generated in the /home/plugin/ansible\_ibmc/report/security\_service/ directory and can be exported.

# 4.18 Enabling or Disabling HTTPS File Server Certificate Verification

### □ NOTE

The MM921 management module and CX320/CX621 switch modules do not support this function

### **Function**

Enable or disable HTTPS file server certificate verification.

Only the iBMC 3.01.12.20 or later versions support this function.

### **Parameter Configuration**

Modify the /home/plugin/ibmc\_ansible/examples/set\_https\_cert\_verification.yml file.

verify\_cmd: indicates whether to verify the certificate of the remote HTTPS file server. The options are **True** (enable HTTPS file server certificate verification) and **False** (disable HTTPS file server certificate verification).

```
[plugin@localhost examples]$ vi set_https_cert_verification.yml
---
- hosts: myhosts
  connection: local
  name: set https cert verification
  gather_facts: False
```

```
# verify_cmd: Configure the switch for enabling or disabling certificate verification
for the HTTPS remote file server.
    # Available values: True/False/off/on/yes/no/1/0

tasks:
    - name: set https cert verification
    ibmc_set_https_cert_verification:
    ibmc_ip: "{{ ibmc_ip }}"
    ibmc_user: "{{ ibmc_user }}"
    ibmc_pswd: "{{ ibmc_pswd }}"
    verify cmd: True
```

### **Commands**

- Go to the /home/plugin/ibmc\_ansible/examples directory.
   cd /home/plugin/ibmc\_ansible/examples
- 2. Run the following command to enable or disable HTTPS file server certificate verification:

### ansible-playbook set\_https\_cert\_verification.yml

The command execution is successful if the following information is displayed:



# A.1 How Do I Encrypt Files and View, Edit, and Execute Encrypted Files

Before running the encryption command **ansible-vault**, you can run the **ansible-vault** -h command to view the help information about the command.

```
[root@localhost ~]# ansible-vault -h
Usage: ansible-vault [create|decrypt|edit|encrypt|encrypt_string|rekey|view]
[options] [vaultfile.yml]
encryption/decryption utility for Ansible data files
Options:
--ask-vault-pass ask for vault password
-h, --help show this help message and exit
--new-vault-id=NEW VAULT ID
the new vault identity to use for rekey
--new-vault-password-file=NEW_VAULT_PASSWORD_FILE
new vault password file for rekey
--vault-id=VAULT IDS the vault identity to use
--vault-password-file=VAULT PASSWORD FILES
vault password file
-v, --verbose verbose mode (-vvv for more, -vvvv to enable
connection debugging)
--version show program's version number, config file location,
configured module search path, module location,
          executable location and exit
See 'ansible-vault <command> --help' for more information on a specific
command.
```

## A.1.1 How Do I Encrypt Files

- $\textbf{Step 1} \quad \textbf{Go to the /home/plugin/ibmc\_ansible/examples} \ \text{directory}.$ 
  - cd /home/plugin/ibmc\_ansible/examples
- **Step 2** Run the following command to encrypt a file:
  - ansible-vault encrypt File name

For example, to encrypt the **get\_basic\_info.yml** file:

Run the **ansible-vault encrypt get\_basic\_info.yml** command and enter the password as prompted.

```
[plugin@localhost examples]$ ansible-vault encrypt get_basic_info.yml

New Vault password:
```

**Step 3** Enter the password to be set and press **Enter**. The system prompts you to enter the password again.

```
[plugin@localhost examples]$ ansible-vault encrypt get_basic_info.yml
New Vault password:
Confirm New Vault password:
```

**Step 4** Enter the password again and press **Enter**. The system displays a message indicating that the file is encrypted successfully.

```
[plugin@localhost examples]$ ansible-vault encrypt get_basic_info.yml
New Vault password:
Confirm New Vault password:
Encryption successful
```

----End

### A.1.2 How Do I View Encrypted Files

Step 1 Go to the /home/plugin/ibmc\_ansible/examples directory.

cd /home/plugin/ibmc\_ansible/examples

**Step 2** Run the following command to view a file:

ansible-vault view File name

For example, to view the encrypted **get\_basic\_info.yml** file:

Run the **ansible-vault view get\_basic\_info.yml** command and enter the file password as prompted.

```
[plugin@localhost examples]$ ansible-vault view get_basic_info.yml
Vault password:
```

**Step 3** Enter the file password and view the file content.

```
[plugin@localhost examples]$ ansible-vault view get_basic_info.yml
Vault password:
---
- hosts: myhosts
  connection: local
  name: get bmc basic info
  gather_facts: False

# cvs_format: Whether to write the result to a CSV file. It is a mandatory parameter.
Available values: True, False

tasks:
- name: get bmc basic info
  ibmc_get_basic_info:
  ibmc_ip: "{{ ibmc_ip }}"
```

```
ibmc_user: "{{ ibmc_user }}"
ibmc_pswd: "{{ ibmc_pswd }}"
csv_format: True
```

----End

### A.1.3 How Do I Edit Encrypted Files

Step 1 Go to the /home/plugin/ibmc\_ansible/examples directory.

cd /home/plugin/ibmc\_ansible/examples

**Step 2** Run the following command to edit a file:

ansible-vault edit File name

For example, to edit the encrypted **get\_basic\_info.yml** file:

Run the **ansible-vault edit get\_basic\_info.yml** command and enter the file password as prompted.

```
[plugin@localhost examples]$ ansible-vault edit get_basic_info.yml
Vault password:
```

**Step 3** Enter the file password and edit the file content.

----End

# A.1.4 How Do I Run Configuration Commands After Files Are Encrypted?

Step 1 Go to the /home/plugin/ibmc ansible/examples directory.

cd /home/plugin/ibmc\_ansible/examples

**Step 2** Run the configuration command.

ansible-playbook -vv File name --ask-vault-pass

For example, to query the basic information about a server:

Run the **ansible-playbook -vv get\_basic\_info.yml --ask-vault-pass** command and enter the file password as prompted. The following uses Python 3 as an example.

```
[plugin@localhost examples] ansible-playbook -vv get_basic_info.yml --ask-vault-pass /usr/local/python3/lib/python3.7/site-packages/cryptography-3.1.1-py3.7-linux-x86_64.egg/cryptography/hazmat/bindings/openssl/binding.py:177:
CryptographyDeprecationWarning: OpenSSL version 1.0.2 is no longer supported by the OpenSSL project, please upgrade. The next version of cryptography will drop support for it.

utils.CryptographyDeprecationWarning,
ansible-playbook 2.9.9
config file = None
configured module search path = ['/root/.ansible/plugins/modules',
'/usr/share/ansible/plugins/modules']
ansible python module location =
/usr/local/python3/lib/python3.7/site-packages/ansible-2.9.9-py3.7.egg/ansible
executable location = /usr/local/python3/bin/ansible-playbook
```

```
python version = 3.7.5 (default, Nov 16 2020, 23:36:26) [GCC 4.8.5 20150623 (Red Hat
4.8.5-44)]
No config file found; using defaults
Vault password:
```

### **Step 3** Enter the file password to query the basic information about the server.

```
[plugin@localhost examples] ansible-playbook -vv get basic info.yml --ask-vault-pass
/usr/local/python3/lib/python3.7/site-packages/cryptography-3.1.1-py3.7-linux-x86
64.egg/cryptography/hazmat/bindings/openssl/binding.py:177:
CryptographyDeprecationWarning: OpenSSL version 1.0.2 is no longer supported by the
OpenSSL project, please upgrade. The next version of cryptography will drop support
for it.
utils.CryptographyDeprecationWarning,
ansible-playbook 2.9.9
config file = None
configured module search path = ['/root/.ansible/plugins/modules',
'/usr/share/ansible/plugins/modules']
ansible python module location =
/usr/local/python3/lib/python3.7/site-packages/ansible-2.9.9-py3.7.egg/ansible
executable location = /usr/local/python3/bin/ansible-playbook
python version = 3.7.5 (default, Nov 16 2020, 23:36:26) [GCC 4.8.5 20150623 (Red Hat
4.8.5-44)]
No config file found; using defaults
Vault password:
PLAYBOOK: get basic info.vml
1 plays in get_basic_info.yml
PLAY [get bmc basic info]
META: ran handlers
TASK [get bmc basic info]
task path: /home/ibmc_ansible/examples/get_basic_info.yml:10
ok: [host0] => {"ansible_facts": {"discovered_interpreter_python": "/usr/bin/python"},
"changed": false, "msg": "Get basic info successful! For more detail information, please
refer the report log:
/home/root/ansible ibmc/report/basic info/192.168.2.10 BasicInfo.json"}
META: ran handlers
META: ran handlers
PLAY RECAP
host0 : ok=1 changed=0 unreachable=0 failed=0 skipped=0
rescued=0 ignored=0
```

### ----End

# A.2 Message invalid upload file Is Displayed When the Root Certificate or CRL of the Local HTTPS Server Is Imported

### **Symptom**

The root certificate or CRL of the local HTTPS server fails to be imported, and the message **invalid upload file** is displayed, as shown in the following figure:

```
[plugin@localhost examples]$ ansible-playbook -v https_ca_import.yml
/usr/local/python3/lib/python3.7/site-packages/cryptography-3.1.1-py3.7-linux-x86
64.egg/cryptography/hazmat/bindings/openssl/binding.py:177:
CryptographyDeprecationWarning: OpenSSL version 1.0.2 is no longer supported by the
OpenSSL project, please upgrade. The next version of cryptography will drop support
utils.CryptographyDeprecationWarning,
No config file found; using defaults
PLAY [import https ca]
TASK [import https ca]
fatal: [host0]: FAILED! => {"ansible facts": {"discovered interpreter python":
"/usr/bin/python"}, "changed": false, "msg": "Import remote https server root ca failed!
The detailed information is as follows: Send request to upload the file failed! The
error code is: 400, The error info is: {'error': {'code': 'Base.1.0.GeneralError',
'Message': 'A general error has occurred. See ExtendedInfo for more information.',
'@Message.ExtendedInfo': [{'@odata.type': '#MessageRegistry.1.0.0.MessageRegistry',
'MessageId': 'iBMC.0.1.0.FirmwareUploadError', 'RelatedProperties': [], 'Message':
'An error occurred during the firmware upload process. Details: invalid upload file.',
'MessageArgs': [], 'Severity': 'Warning', 'Resolution': 'Locate the cause based on error
information, rectify the fault, and submit the request again.' }] }} "}
PLAY RECAP
                       : ok=0 changed=0 unreachable=0 failed=1 skipped=0
rescued=0 ignored=0
```

### **Solution**

- **Step 1** Check whether the certificate or CRL file is correct.
  - If yes, go to Step 2.
  - If no, use the correct certificate or CRL file and run the import command again.
- **Step 2** Upgrade the iBMC of the server to the latest version and run the import command again.

----End

**MOTE** 

If the fault persists, contact technical support.

# B Obtaining Technical Support

To obtain assistance, contact technical support as follows:

- Contact customer service center at support@xfusion.com.
- Contact technical support personnel.

# C Communication Matrix

Sou rce Dev ice	Sour ce IP Addr ess	Sou rce Por t Nu mb er	Desti natio n Devic e	Destin ation IP Addres s	Desti natio n Port Num ber	Prot oco I	Port Description	Destin ation Port Config urable	Authent ication Mode	Encr yptio n Mod e
Devi ce to whic h Ansi ble belo ngs.	The IP addre ss of the Ansib le virtua I ether net port.	Ran	iBMC	IP address of the iBMC virtual network port veth.	22	SS H	When the file transfer service is conducted, enable the SSH standard protocol port. Ansbile, as a client, accesses the device on the iBMC.	Not involve d.	User name/ passwor d	SSH