



BORATE PRESSURE TREATED WOOD FOR INTERIOR & EXTERIOR APPLICATIONS

Treated
by:



P.O. Box 34 • Chippewa Falls, WI 54729-0034

Tel: (715) 723-4100 • Fax: (715) 723-0861

Call Toll Free: (800) 236-9663

Email: pat@crossarm.com • www.crossarm.com

Product Features

- Lumber and Plywood are pressure treated with Disodium Octaborate Tetrahydrate (DOT) and **EnviroSafe Plus™** Polymer Binder.
- For use in accordance with ICC-AC62 (Interior & Exterior Applications), EPA Registration No. 79628-1 (Interior & Exterior Applications) and AWWA P5, UC2 (Interior Applications).
- **Virtually non-corrosive – Standard G60 and G90 Fasteners recommended.**
- Class A 10 Minute Flame Spread, Fire Retardant, based on ASTM E 84.
- Low toxicity – low risk to humans and other non-target animals.
- Stainable and Paintable immediately upon completion of installation.
- Odorless and non-volatile – no negative effects on indoor air quality.
- **Effective against termites (including Formosan), carpenter ants, carpenter beetles, silver fish, fleas, cockroaches and other household pests.**
- No color additives – wood retains natural color characteristics after treatment.
- Minimum wear on tools.
- No adverse effects on strength or elasticity of lumber.
- 40 Year Transferable Limited Warranty.

Product Applications

Framing Lumber • Studs • Sill Plates • Floor Joists • Roof Rafters
Trusses • Plywood • Sheathing • Furring Strips • Decking • Fencing
Pre-Fab Wall Systems • Moldings • Wood Trim • Flooring