OpenBazaar: Signed Catalogs, Sealed Orders, and Scriptless Two-Party Escrow for a Non-Custodial Marketplace

Brian Hoffman
OpenBazaar project

November 2026

Abstract

OpenBazaar is a peer-to-peer marketplace for ordinary physical and digital goods paid in bitcoin. The original system (developed from 2014, with its last substantial releases in 2020) published stores over IPFS, carried orders over libp2p, and protected buyers with a 2-of-3 multisignature escrow whose script and moderator key appeared on chain when it was spent. This paper presents a redesign of the network and argues which of its security and privacy properties hold, and under which assumptions.

Stores and listings are public, content-addressed records signed with BIP 340 Schnorr signatures over a canonical encoding, and carry the vendor's own content labels; third parties can publish signed label sets that buyers choose to follow, and all filtering happens on the buyer's device. Listings carry variants, stock, shipping services, coupons, and fiat prices that both nodes compute identically, and a buyer reviews a paid order with a per-order key named in the seller's signed receipt; nodes replicate reviews, so a seller cannot remove one. Orders are private letters sealed with HPKE to a single vendor. A client device talks only to its owner's node. The phone app embeds Tor to reach that node, and on the home network it can use a sealed channel instead. Payments go directly to the vendor, one transaction per seller. Moderated purchases use a scriptless escrow: a MuSig2 Taproot key-path output whose timeout and dispute spends are all presigned before funding. A dispute is settled by an adaptor signature whose completing secret is split between the favored party and a moderator half that the losing party verifiably encrypts to the moderator. The moderator never holds a signing key over the funds and cannot change any payout.

We state the threat model, specify the escrow protocol with the checks each party must run and its block-height timeline, argue the security properties, tabulate what every observer learns, and state the limitations and open problems, including a moderator-fee bias, the size of the verifiable encryption, and collusion between the moderator and one party. Measurements of a reference implementation show that catalog signing, verification, and order sealing cost well under a millisecond, and that the escrow's verifiable encryption costs about 50 KB and 50 ms per share.

1 Introduction

A marketplace has to do four things: let sellers publish what they offer, let buyers find it, carry an order from buyer to seller, and settle payment in a way both sides can accept. Hosted marketplaces do all four in one place. That place can see every order, hold every payment, and remove any seller. OpenBazaar's premise is that these functions can be split so that no single operator is needed for any of them, and so that the parties who must learn something (the seller who ships, the moderator who rules on a dispute) learn it only when they need to.

1.1 The original OpenBazaar

OpenBazaar began in 2014 as a prototype peer-to-peer market and was developed as `openbazaar-go` and a desktop client until late 2020 [40]. A node published its store as an IPFS directory addressed by IPNS [5]. Listings were signed by the node's identity key. Messages traveled over libp2p when both peers were online; when the recipient was offline, the sender stored the message on its own node or an external storage host and left a pointer in the distributed hash table. Search was a separate hosted index that nodes notified on publish. The wallet supported several cryptocurrencies. Moderated purchases used a 2-of-3 multisignature script over buyer, vendor, and moderator keys, with a default timeout of 1080 hours.

That design had strengths the redesign keeps: listings were signed and an order committed to a hash of the listing it bought, so later edits could not rewrite a deal; the moderator could not take funds alone. It also had properties the redesign changes:

- A store was available only while its own node, or a pinning service, was online.
- The libp2p peer identity was long-lived and observable, and peers dialed each other directly, so the network layer linked a store identity to IP addresses.
- The default search index was a single hosted service. Delisting from it removed a store from practical discovery.
- Spending a 2-of-3 P2SH or P2WSH output reveals the full script, including the moderator's public key, so every moderated purchase was recognizable on chain and attributable to its moderator.
- A phone could not run the daemon in the background, so a vendor without an always-on desktop missed orders.
- The multi-coin wallet made wallet maintenance the dominant engineering cost.

1.2 This paper

The redesign keeps the contract between buyer, vendor, and moderator and replaces the machinery underneath. Its main ideas are:

1. **A public catalog, private orders.** Store and listing records are public, signed, and content-addressed, and replicated by any node (§6). Orders are not catalog records; each is a letter sealed to one vendor and carried to that vendor's own mailbox (§8). Vendors label their own records, and buyers filter what they see on their own devices (§6.4).
2. **Seller-priced terms and receipt-locked reviews.** Listings carry variants, stock, shipping services, and prices in a fiat currency that both nodes compute the same way; a buyer reviews a paid order with a key made for that order, and nodes keep each other's reviews so a seller cannot drop one (§9).
3. **Clients that only talk to their own node.** The user-facing app sends marketplace requests to its owner's node, which verifies records and delivers letters (§5). A phone reaches that node as in §5.2.
4. **Direct, per-seller payments.** A buyer pays each vendor in a separate transaction, never batching two sellers together (§10).
5. **Scriptless two-party escrow with a bounded moderator.** The escrow output is an ordinary-looking Taproot key-path output. Every non-cooperative outcome is presigned by

both parties before the buyer funds it. The moderator only reveals one secret scalar that completes one of two presigned dispute outcomes (§11).

The contributions are: (i) a threat model for a marketplace with this split (§4); (ii) a precise description of the two-party escrow protocol, its message rounds, the checks each party and the moderator must run, and its block-height timeline (§11); (iii) argued security properties, each with its assumptions, and the attacks the checks exist to stop (§13); (iv) a table of what every party and observer learns (§14); and (v) measurements of a reference implementation (§15) and a statement of what the design does not achieve (§16).

A reference implementation in Rust, with a web and desktop client and a native phone app for iOS and Android, is available at `https://github.com/OpenBazaar/openbazaar-rs`. This paper describes what that implementation does.

2 Design Goals and Non-Goals

2.1 Goals

G1. No custody. No party other than the buyer and the vendor ever holds a key, or a set of keys, sufficient to move a buyer's payment. The moderator in particular holds no signing key over escrowed funds.

G2. Verifiable public catalog. Anyone can check that a listing was published by the store it names and has not been altered. A listing's address is derived from its content.

G3. Private orders. An order's contents, including any ship-to address, are readable only by the vendor it is addressed to. No public relay or index stores a record that a given buyer wrote to a given vendor.

G4. Bounded moderation. A moderator can choose between two payouts that buyer and vendor already signed. It cannot sign alone, redirect funds, change amounts, or learn about an order unless a party opens a dispute.

G5. Liveness without a platform. A buyer can recover escrowed funds from a vendor who disappears, and a vendor can collect from a buyer who stops responding, without anyone's cooperation beyond broadcasting a presigned transaction.

G6. Thin clients. A phone client embeds Tor so it can reach the node it is paired with. It does not hold spend keys, and it does not dial other vendors. A browser on the same machine talks to the node on a loopback address. Spending and chain watches stay on the node.

G7. Honest degradation. When a privacy mechanism is unavailable (no Tor, no Payjoin partner, no Lightning route), the system says so rather than silently falling back.

2.2 Non-goals

- **Anonymity against a global passive adversary.** We do not claim unlinkability against an adversary that observes most of the network. Section 14 states what such an adversary learns.
- **Hiding the catalog.** Listings are public by design. A market that cannot be discovered does not serve its purpose.

- **Hiding the ship-to address from the seller or the carrier.** A seller of a physical good must learn where to send it, and the carrier must deliver it. This is a ceiling on buyer privacy for physical goods, not a gap to be engineered away.
- **Deciding factual disputes cryptographically.** Whether a parcel contained the right item is a judgment by a person. The protocol bounds what that person can do with the funds; it does not replace the judgment.
- **Reputation.** A review or rating system is outside this paper.
- **Content policy.** The protocol is designed for ordinary goods. Policies for what may be listed, and the obligations of people who operate replicas or seeds, are outside the scope of this paper.

3 System Model and Actors

Devices. A *client* is the user-facing application: the native phone app, or the same screens in a desktop shell or a browser on the node machine. A *node* is a long-running process the user controls, on a computer that stays on, that holds keys, stores records, talks to other nodes, and watches the Bitcoin chain. A client is paired with exactly one node. The phone app embeds a Tor client and uses it to reach that node. On the same home network it uses a sealed channel and falls back to Tor when the channel does not answer. The phone does not dial other vendors, and it cannot reach the store when its node is unreachable.

Roles.

Buyer. Browses the catalog, sends a sealed order, and pays. For moderated purchases, funds the escrow output and holds a presigned refund.

Vendor. Publishes a signed store and listings, runs a node that opens sealed letters, ships, and collects payment. For moderated purchases, holds a presigned claim.

Moderator. Publishes a record of its keys, fee, payout script, and acceptance policy, and is named in a listing and in the signed escrow terms. Receives nothing unless a party opens a dispute. On a dispute, verifies a self-contained letter and reveals one secret scalar to the party it rules for. Paid a fixed fee by the dispute outcome.

Labeler. Publishes signed sets of content labels about stores and listings. Buyers choose which labelers to follow; a labeler cannot change or remove anyone's records.

Replica. A node that stores and serves catalog records it did not create, so that a store remains readable while its publisher is offline.

Seed. A node whose address ships with the software or is pasted by the user, used only to find other nodes. Seeds are untrusted for content: every record is verified against its signature.

External parties. The Bitcoin network and chain; a source of chain data for the node (its own Bitcoin node, compact block filters, or a block-explorer API); Tor relays; Lightning routing nodes and, for a vendor that uses one, a Lightning service provider; an exchange-rate source for fiat estimates; and, for physical goods, a parcel carrier.

Records and messages. A *store record* names a store key, a display name, a region, direct-payment strings, and the store's content rating. A *listing* names its store key, describes one offer, and carries the vendor's content label. A *label set* is a labeler's signed statement about stores and listings. An *order letter* is an HPKE ciphertext addressed to one vendor. *Escrow messages* are the three funding rounds and the release exchange between buyer and vendor. A *dispute letter* goes from one party to the moderator, and a *ruling* comes back.

Network assumptions. We assume the Bitcoin chain makes progress and that a transaction paying a sufficient fee rate is confirmed within a bounded number of blocks; the escrow windows in §11 are sized against this assumption. We do not assume synchronous delivery between buyer and vendor nodes.

4 Threat Model

We consider the adversaries in Table 1. For each, we state what it controls and whether defending against it is in scope. "In scope" means the design claims a property against that adversary under stated assumptions; "characterized" means we describe what the adversary achieves without claiming to prevent it.

Adversary	Capabilities	Scope
A1 Network observer	Sees, delays, and drops traffic on some links (a local network, an ISP, a single Tor relay).	In scope
A2 Malicious replica or seed	Serves, withholds, or reorders catalog records; lies about other nodes; logs who fetches what.	In scope for integrity; availability characterized
A3 Malicious counterparty	A buyer or vendor who deviates arbitrarily from the protocol, including going silent.	In scope
A4 Malicious moderator	Rules dishonestly, rules for both sides, refuses to rule, or logs disputes.	In scope for funds; ruling quality characterized
A5 Moderator colluding with one party	The moderator and either the buyer or the vendor act together.	Characterized
A6 Compromised device	Reads files or memory on a user's node or client.	Characterized
A7 Global passive adversary	Observes most network links and the chain.	Out of scope; characterized

Table 1: Adversaries considered.

A5 is inherent to any escrow with a third-party arbiter: if the arbiter and one party agree, the arbiter can rule for that party. The protocol limits A5 to choosing the presigned outcome that favors the colluding party; it cannot pay a third party or change amounts (§13). A6 is out of scope except for the at-rest encryption described in §7, whose limits we state. A7 is out of scope for anonymity, but §14 lists what it learns.

Cryptographic assumptions. Discrete logarithm hardness in the secp256k1 group, with hash functions modeled as random oracles for the Schnorr, MuSig2, and sigma-protocol arguments;




Figure 1: Components and data paths. A phone reaches its node over a sealed home-network channel or Tor. A sale's sealed letters go to the other node's loopback mail endpoint. The moderator is contacted only when a party opens a dispute.

collision resistance of SHA-256; IND-CCA2 security of HPKE base mode with the X25519/HKDF-SHA256/ChaCha20-Poly1305 suite [4]; and AEAD security of ChaCha20-Poly1305 [38]. The reference implementation uses established libraries (`libsecp256k1` through the `bitcoin` and `musig2` crates, the `hpke` crate, Arti for Tor). We assume these are correct; we did not audit them.

5 Architecture

Figure 1 shows the components. A user runs a client and a node. The node holds the keys, the wallet, the encrypted vault, the verified catalog, and the escrow state; it watches the chain and talks to other nodes. The client renders the catalog, the cart, and the order screens, and holds no keys.

5.1 The client-node boundary

A node listens only on a loopback address and refuses requests whose TCP peer is not a loopback address. On first start it creates a 256-bit random pairing token, stored in a file readable only by its owner. Requests that place orders, read or write the address book, or read the buyer's order list must carry the token. Cross-origin responses name only the client's origins, so a web page from another origin in the user's browser cannot read the token or call the node with it. A phone or another computer that manages the node from somewhere else uses the channel in §5.2.

This boundary protects against remote callers and against other web origins in the user's browser. It does not protect against another process running as the same user on the same machine, which can read the token file; we treat that as a compromised device (A6).

Nodes leave escrow letters for each other in a drop that takes no pairing token, since the sender is another node, not the owner's client. The drop only stores the bytes. A letter has effect only if it opens under one of the node's keys and parses as an escrow message for an escrow the node is in, and every message is then checked against the signed terms (§11).

Checkout refuses a body that names a destination: a field such as `peer`, `onion`, `seed`, `replica`, or `url`, or any string value containing `://` or `.onion`. The vendor on an order is the store that signed the listing the node already holds. Following another node's store is separate, and that request accepts only a loopback address (§8.5).

5.2 Remote devices

The owner can manage the node from the native phone app or from another computer. The node publishes an admin onion service with restricted discovery: only a paired device's Tor client key can find the service. The phone app embeds Tor and uses it for that path. It does not dial other vendors.

Each paired phone holds two hardware-backed keys. The device key signs requests. The watch key is accepted only for synchronization, so a background check can refresh without unlocking the device key. A request signature covers the node, the device, the time, a nonce, the method, the target, and a hash of the body. The node accepts a time within 120 seconds of its clock and accepts each nonce only once.

Pairing uses an eight-word secret or a QR code. Both sides display four emoji from the pairing transcript, and the device is added only when the owner approves it on the node. On the home network the app delivers requests through a channel sealed to the node key it pinned at pairing. If that channel does not answer, the app uses the admin onion. Removing a device drops it and its discovery key at once, and also drops devices that device had paired. The owner can move the node to a new onion address at the same time. Devices that remain learn the new address on their next request, and the old address is retired once they have moved or after seven days.

A device session does not spend. Every spend requires the wallet passphrase again. Push is off unless that device opts in. A wake-up carries no order contents, and the node sends one only after the operator names a gateway. This project runs no gateway, so the path stays empty until someone does. The iOS simulator build is arm64, and the App Store build is skipped until Apple signing secrets exist.

5.3 Deployment

A vendor runs a node that stays awake on a computer the vendor controls, publishes the catalog, accepts sealed letters on its loopback listener, and watches the chain. A buyer uses the same software. A phone pairs the native app with the owner's node (§5.2). A sale between two such nodes is §8.5. A moderator is a node like any other and needs to be online only to answer disputes.

6 Catalog and Replication

6.1 Records

A *store record* contains a display name, a region, two direct-payment strings (a BOLT 12 offer and a BIP 352 code), a content rating for the whole store, and the store's 32-byte x-only public key S, which is the store identifier. A *listing* contains S, a title, a category, a price in satoshis, a ship-from region, a description, a seller display name, a stock count, the date it was signed, whether it accepts a moderator, a kind (physical or digital), an optional shared product key, flat shipping in satoshis, the subtotal above which shipping is waived, and the vendor's content label. Neither record has a field for a legal name, an email address, a phone number, or a street address, and a node should refuse to sign or relay free-text fields that contain them.

6.2 Canonical encoding

Each record body is a fixed sequence of fields: a four-byte magic (`OBST` for stores, `OBLS` for listings, `OBLB` for label sets), a one-byte version, then fields in a fixed order. Integers are little-endian of fixed width. Strings are a two-byte little-endian length followed by UTF-8 bytes; blobs are a four-byte

length, capped at 8 MiB. The decoder rejects a wrong magic, an unknown version, invalid UTF-8, truncation, and trailing bytes. Because every variable-length field is length-prefixed and the field order is fixed, distinct records have distinct encodings, and a decoded record re-encodes to the same bytes. Appendix A gives the layouts. A new version adds fields at the end of the body; older versions remain decodable, so records signed before a field existed keep verifying.

6.3 Signatures and addresses

The signature is a BIP 340 Schnorr signature [56] over a tagged hash of the body:

$$\sigma = \mathsf{Sign}_s\big(\mathsf{H}_{\mathrm{tag}}(\mathit{body})\big), \quad \mathsf{H}_{\mathrm{tag}}(m) = \mathrm{SHA256}\big(\mathrm{SHA256}(\mathrm{tag}) \,\|\, \mathrm{SHA256}(\mathrm{tag}) \,\|\, m\big),$$

with tags `ob/store/v1`, `ob/listing/v1`, and `ob/labels/v1`, so a signature over one record type is not valid for another. Signing uses BIP 340's deterministic nonce derivation without auxiliary randomness. The signature is appended to the body. A listing can only be signed by the secret key of the store it names, and verification checks the signature against the S inside the listing body.

A listing's address is SHA256(*body*), computed over the body without the signature. An order commits to this address, so a vendor who later edits a listing (for example, raising the price) produces a new address and cannot claim that the buyer agreed to the new terms. A node refuses an order for an address that it has not verified.

6.4 Content labels and labelers

The network carries ordinary goods, but "ordinary" differs by buyer: some do not want to see weapons, alcohol, or adult material, and some jurisdictions restrict them. The design answers this with labels and filtering on the buyer's own device, not with a central moderator of the catalog.

Self-labels. Each listing carries a content rating (*general*, *sensitive*, or *adult*) and a 16-bit set of tags (nudity, violence, drugs, weapons, gambling; the other bits are reserved). The store record carries a rating that applies to everything the store sells. Both are inside the signed body, so a replica cannot strip or soften a label without breaking the signature, and a vendor who wants a different label must sign a new record (for a listing, at a new address).

Labelers. A *labeler* is a BIP 340 key that publishes numbered *label sets*. Each entry in a set names a target (a listing address or a store key) and either gives it a rating, a tag set, and a short reason code, or retracts the labeler's earlier label on that target. For each labeler and target, the entry in the highest-numbered set that names the target is the current one, so a later set may carry only changes, and a retraction leaves no label. Entries are sorted by target with no repeats, so one set has one encoding; a set is addressed by the hash of its body like a listing. A reason is a short code from a fixed alphabet, not free text, so a label set cannot be used to publish arbitrary statements about a vendor.

Filtering. A buyer chooses which labelers to follow; the follow list is private to the buyer's node. The client combines the store rating, the listing's self-label, the labels from followed labelers, and the buyer's own blocked words and hidden stores and listings, and decides to show, cover (show a placeholder the buyer can open), or hide each listing. When several rules apply, the strictest wins, and the client shows which source caused it. Safe mode is on by default and hides sensitive and adult listings; the buyer can relax each rule.

What labels do not do. A label changes only what one device shows. It does not remove a record from any replica, block an order, or bind other buyers. A vendor can mislabel its own goods; a labeler can label wrongly or selectively; and a buyer who follows no labeler relies only on self-labels and its own lists. The design accepts this: it gives buyers tools to filter without giving any party the power to delete. Fetching a labeler's sets reveals to whoever serves them that the node follows that labeler, so sets should be fetched through the same transport as catalog records.

6.5 What the signature does not give

A valid signature proves that the store key holder signed those bytes at some time. It does not prove that the listing is current or that a set of listings is complete. A replica can serve an older, validly signed version of a listing (an old price or stock count), and it can omit listings entirely, without either being detectable by signature checks alone. Addressing a listing by content hash makes an order unambiguous about which version it bought, but does not tell a buyer whether a newer version exists. A per-store sequence number or a signed index of current listings would address freshness and completeness (§16.2).

6.6 Replication

Every node stores the signed headers of the catalog it has seen, so that a store remains browsable while its publisher is offline, and images and files must be held by at least one replica before a listing counts as published. Because records are self-authenticating, a replica needs no trust for integrity: a client or node that receives a record from anyone checks the signature and the content hash. Replicas are trusted only for availability and see who fetches what (§14).

An open catalog invites spam. Each published header should carry a cost that receiving nodes check, such as a small bitcoin fee; the mechanism is open (§16.2). Without one, replication is limited to stores a node has chosen to follow or has received through a pasted link.

7 Identity and Keys

7.1 Key roles

Each user has one backup phrase, and the node derives a separate key for each role, so that a key used to sign the public catalog is never the key that spends coins. The phrase is a 12-word BIP 39 mnemonic [43] with BIP 32 derivation [55]:

Role	Derivation path
Spend wallet (BIP 86 Taproot [11])	`m/86'/c'/0'/{0,1}/*`
Store signing key	`m/1984'/c'/0'/0'`
Escrow key i	`m/1984'/c'/1'/i'`
Escrow mail key	`m/1984'/c'/2'/0'`
BIP 352 scan key	`m/352'/c'/0'/1'/0`
BIP 352 spend key	`m/352'/c'/0'/0'/0`

The coin type c is 0 on mainnet and 1 on test networks, and each network has its own data directory, so a phrase used on both never yields the same key on both. All role keys are pairwise distinct. Escrow keys are indexed, and the index is advanced and persisted before a key is used, so each escrow gets a new key and no key is reused across escrows. Labeler keys and moderator keys are role keys of the same kind, on their own paths, for users who act in those roles.

7.2 The mailbox key

Orders are sealed to an X25519 public key belonging to the vendor (§8). That key must be bound to the store, so that a buyer who verified a listing also knows which key to seal to. The binding is a field in the signed store record. The record can also carry an onion host; the node does not dial it for orders. The mailbox key is derived from the phrase on its own hardened path under `m/1984'` and is never the store signing scalar reinterpreted as an X25519 key: reusing one secret across two groups and two protocols has no known attack in this combination, but there is no reason to rely on that.

7.3 Encryption at rest

The node stores the buyer's address book, the buyer's own order records, the backup phrase, the wallet state, and the labeler follow list encrypted with ChaCha20-Poly1305 under a random 256-bit key and a random 96-bit nonce per write. The buyer's order record keeps the label of the address used (for example, "Home"), not the street.

This protects against the encrypted files being copied or synced on their own, for example by a backup tool that skips key files, and keeps addresses out of logs and the catalog. If the key is stored in the same data directory, it does not protect against anyone who can read that directory; wrapping it with an operating-system keystore or a passphrase does. It is not a defense against a compromised device (A6).

8 Order Sealing and Transport

An order is a private letter to one vendor, not a catalog record and not an event on a public relay. Figure 2 shows the flow.

8.1 Order contents

The order plaintext (magic `OBOD`, version 1) contains: the address of the first listing; its quantity; an options map of up to 16 string pairs, which carries the settlement type, the shipping charge, a delivery note for digital goods, and the address and quantity of any further listings from the same seller; the ship-to text (at most 1024 bytes) for physical goods; the payment rail; and a fresh X25519 public key R that the vendor uses to reply. The order body carries no long-term buyer identity key. The vendor learns who the buyer is only from what the buyer writes into the letter (for a physical good, the ship-to) and from the payment.

8.2 Sealing

The node seals the plaintext with HPKE [4] in base mode with the suite DHKEM(X25519, HKDF-SHA256) [31, 32], HKDF-SHA256, and ChaCha20-Poly1305 [38]. The recipient key is the vendor's mailbox key P_V; the HPKE `info` string is `openbazaar-tormail-order-v1`; the associated data is empty. The sealed letter is

$$\texttt{OBSL} \,\|\, \texttt{0x02} \,\|\, enc \,\|\, \mathrm{len}_{32}(ct) \,\|\, ct,$$

where enc is HPKE's 32-byte encapsulated ephemeral key. A vendor reply is sealed the same way to the buyer's per-order key R with `info openbazaar-tormail-reply-v1`. A later message in the same sale uses `openbazaar-tormail-message-v1`. Because R is generated per order and travels inside the




Figure 2: A sale between two nodes (§8.5). Steps 4, 6, and 10 are sealed letters to the other node's loopback mail endpoint. The seller shows step 8 because compact filters cannot see the mempool. A multi-seller checkout repeats the exchange once per seller.

ciphertext, no relay or mailbox needs to remember which buyer wrote to which vendor in order to route a reply.

HPKE stays in base mode, so the outer ciphertext does not name a long-term sender. Inside it, the plaintext is an authenticated letter (`OBLT`): a per-conversation sender key, a message id, the body, and a BIP 340 signature over the recipient key, the kind, the sender, the id, and the body, under the tag `ob/letter/v1`. The plaintext is zero-padded so the sealed letter is exactly 2 KiB, 8 KiB, or 64 KiB, header included. Replies use the 2 KiB and 8 KiB buckets. Any other size is refused. An observer who sees a letter at rest or in transit learns the bucket. The sender key stays inside the ciphertext, and the recipient pins it after the first letter of a conversation. Anyone who knows P_V can still produce a first letter the vendor will open. That is deliberate: a buyer has no long-term identity to show, and the vendor treats a new order as an offer that becomes real when it is paid. A mailbox can be filled with junk letters; it does not rate-limit.

8.3 Multi-seller checkout

A checkout may contain packages from several sellers. The node validates every package (each listing exists in the verified catalog, each package is one seller and each seller one package, moderated packages only contain listings that accept the moderator) before sealing anything, then seals one letter per seller to that seller's key. A seller learns only the lines in its own package. Each package gets its own payment instructions and its own payment (§10).

8.4 The mailbox

The vendor's node accepts letters into a mailbox directory without loading any secret: a letter is written to a temporary file and renamed to a random 128-bit identifier, so the identifier is not derived from the sender. Letters are opened later with the mailbox secret. A node that is compromised while the vendor is away therefore holds ciphertext, not orders, unless the mailbox secret is also stored on it.

8.5 A sale between two nodes

On first start the node asks for a wallet passphrase and then whether the owner is shopping or selling. That choice is stored on the node and is not part of a signed record. A buyer can open a store later. A seller names the store; the node signs the store record and signs each listing the seller creates, edits, or deletes. A listing can carry a 16-byte id that stays put across edits, up to eight image hashes, and an optional price in USD, EUR, GBP, or JPY beside the signed satoshi price. The seller's node keeps earlier addresses of its own listings, so an order that names an older address still prices. A buyer follows another node's store at a loopback address and keeps a signed copy of its records.

Checkout seals one order to the seller's mailbox key. The buyer's reply address travels inside the ciphertext. The order waits as "Awaiting seller" until the seller's node prices it: a fiat price at the seller's exchange rate at that moment, otherwise the signed satoshi price. The seller takes a fresh receive address and replies with the amount and the address, or declines. The buyer accepts a satoshi total only when it equals what checkout showed, and a fiat total only up to a quarter above that. A higher ask ends the order unpaid. After the first letter, each side accepts further letters in that sale only from the sender key it already pinned.

The buyer pays the address in the reply from the node wallet or from any other wallet. When the node wallet broadcasts a direct payment, it sends the seller a letter naming the transaction. Compact block filters have no view of the network mempool, so the seller does not see that incoming payment until a block includes it. Until the sale is paid, the seller's screen says "Payment sent, waiting for confirmation." The chain is what marks it paid: one confirmation on the test network and three on mainnet. The seller then ships a physical good with a carrier and tracking number, or sends the digital good's delivery text. The buyer confirms receipt, and both sides mark the sale completed. A sale to another node's store is direct bitcoin. The seller's node declines escrow and Monero on that order.

8.6 Transport

The buyer's node delivers each sealed letter to the mail endpoint of the store it followed, and the seller replies to the address the order carried. The node accepts those endpoints only as loopback HTTP addresses, the same restriction it places on escrow mail. The sender keeps each letter in an outbox and retries, from two seconds doubling up to fifteen minutes, and drops it after 24 hours. No third-party relay stores letters. A vendor whose node is never awake is a closed shop.

The letter library can dial a v3 onion service [53] and write one framed letter (`OBML`). The node does not use that path for orders or escrow, so a sale runs between nodes that can reach each other's loopback addresses. Carrying those letters over Tor, and over a mix network such as Nym [15, 45], is future work (§16.2). Remote management of the owner's own node does run over Tor (§5.2).

9 Commerce Terms, Stock, and Reviews

The records of §6 describe one item at one price. This section adds what a seller needs to sell the same thing in several sizes, ship it several ways, run a discount, and be reviewed, and states what each addition reveals. The seller's node is the only authority on stock and price at order time; every other party works from signed records and says "as of" when it shows them.

9.1 Listing terms

Version 6 of a listing carries the stable listing identifier, the images, and the optional fiat price of §8.5. Version 7 adds a *commerce block* to a fiat-priced listing:

- a condition grade (new, open box, like new, good, fair, for parts) with an optional note, a top-level category number, and up to 24 key/value specifics, where well-known keys such as a GTIN are checked;
- up to three option axes of up to 16 values each and up to 100 variants, each with a random 8-byte identifier kept across edits, a seller SKU, an optional price override, its own stock, an image index, and a weight;
- a compare-at price, a percentage sale with first and last days, up to four quantity tiers, a per-order maximum, a lot size, and an availability state (in stock, pre-order with a ship day, made to order in n days, or away);
- shipping: package weight and dimensions, handling days, a free-shipping threshold, up to six services each with a name, a price for the first item, a price for each extra item, a delivery estimate, and the regions it ships to; and an optional pickup area;
- a returns override.

The block is inside the signed body, so a replica cannot change a variant's price or stock. Every free-text field passes the same contact-and-location check as the rest of the record.

9.2 Order terms and the shared price

Order letters at version 3 carry *terms*: up to 20 lines, each naming a listing address, a variant identifier, a quantity, and optionally an offer the store signed for that line; one shipping service index (with a reserved value for pickup or digital delivery); a coupon code; and a per-order review key (§9.5). The first line must repeat the letter's listing and quantity, so a version-1 reader still sees a valid order.

Both nodes compute the price of a package with the same function. A line costs the variant price (or the listing price), less the sale percentage if the day falls inside the sale window, less the best quantity tier; an attached offer replaces that price. A coupon then comes off the lines it covers. Shipping uses the chosen service, charging the first item at its price and each further item at the extra-item price across all lines of the package, and is waived above the free-shipping threshold of the discounted subtotal. Every discount rounds down. The implementation's test vectors pin the function so that the client and node agree to the minor unit.

Fiat quotes. When the seller's node reads a version-3 letter, it prices the lines in the listing's currency with this function, converts the total to satoshis at its own rate, and replies with both. The buyer's node computes its own quote from the signed records, without the coupon, and refuses a seller quote whose fiat total is higher; it also refuses a satoshi amount more than a quarter above

its own estimate, which leaves room for rate movement between the two nodes' sources. A seller can therefore lower a price at order time (with a coupon) but not raise it.

Coupons. A coupon is a record signed by the store key: a code, a percentage or fixed discount, an optional minimum subtotal and list of listings, first and last days, and a maximum number of uses. Coupons are kept on the seller's node and not published. The buyer types the code into checkout, the letter carries it, and the seller's quote shows the discount before anything is paid. A withdrawn or exhausted code is refused when the letter arrives.

9.3 Stock

A signed listing can only say how many units the seller had when it was signed, and replicas serve it while the seller is offline. The seller's node keeps a shelf count per variant. When it reads an order, it checks the variant, the per-order maximum, availability, and the shelf, and holds the units for the payment window (one hour); if they are not there it declines before payment. A confirmed payment turns the hold into a sale and takes the units off the shelf; an unpaid hold lapses. Each watch round re-signs every listing whose shelf count no longer matches its signed stock, while the store key is unlocked, so the catalog catches up. If a payment arrives after its hold lapsed and the units were sold to someone else, the sale is marked oversold and the seller's reply says so; for a direct payment the seller refunds by hand. Clients show stock as of the seller's last update, since the record carries no publish time.

9.4 Local pickup

Pickup is off by default. A seller who allows it names an area that passes a region check: a short name with no comma, no digits, and at most three words, so that it names a city, state, or country rather than a street, and passes the contact-and-location check. Choosing pickup puts no address in the order; time and place are agreed in the order's sealed messages. Meeting in person shows each party to the other, which no protocol can prevent, and the client says so at checkout.

9.5 Reviews

A review should show that the reviewer paid for the item, without naming the reviewer, linking that reviewer's reviews, or letting the seller remove it.

Keys and receipts. For each order the buyer's node derives a review key from its letter root under a separate label, and puts the public key in the order terms, so the key is committed before the seller knows whether it will be reviewed well. When the payment confirms, the seller's node signs a *receipt* (`OBRC`) for each listing in the order: the store key, the listing identifier, the review key, and the month of payment (the first of the month). The receipt goes to the buyer in the seller's "paid" reply, or, if the store key was locked, with the next status reply after it is unlocked. The buyer's node keeps a receipt only if it verifies under the order's store key, names this order's review key, and names a listing in the order.

Reviews and replies. A *review* (`OBRV`) contains the receipt, one to five stars, at most 1,000 bytes of text that pass the contact-and-location check, and the day it was written, and is signed by the review key. Any node can check it: the receipt under the store key inside it, then the review under the receipt's review key. The buyer's node signs the review after a random wait of up to three days

and dates it the day it is signed, so the review's date is not the day the buyer pressed the button. A store may attach one *reply* (`OBRY`), signed by the store key, that names the review's hash; a newer reply from the store replaces its older one. The seller cannot change the review's text, because the review key signs it.

Publication. Every node keeps a pool of reviews and serves the whole pool to other nodes, without marking which reviews its own user wrote. When a review is signed, the buyer's node adds it to its pool and sends it to the seller's node and to every node it follows. In each replication round, a node also pulls the pools of the nodes it follows and keeps what verifies. A pool keeps one review per review key; a review leaves a pool only when the same key signs a newer one. A seller can therefore leave a review out of its own pool, but not out of the pools of nodes that already hold it, and a node that follows any of those nodes receives it. Since receipts can be minted for any store key, a node keeps up to 2,000 reviews for each store it carries and 2,000 in total for stores it does not.

Ratings. A buyer's node counts the reviews it holds for a store and for a listing and shows the average and the distribution of stars. There is no score across stores and no reviewer profile.

What this does not stop. The seller knows which of its orders received each receipt, so it knows which order wrote a review, as it already knew that order's ship-to. A seller can mint receipts for review keys it controls and review itself; nothing short of linking reviews to payments on chain would tell those apart, so a rating shows signed purchases, not independent buyers. A review reaches only the nodes that follow, directly or through others, a node that holds it. The receipt's month narrows the payment to a month on chain, not a day. Reviews travel between nodes the same way as other node-to-node traffic (§8.5), and a node only pulls what others already hold, so a node the buyer's node sends a review to learns that it came from that node; sending only to the seller and to followed nodes limits who learns this.

10 Payments

Moderated payment, and a sale between two nodes, are in bitcoin. A store on this node can also accept Monero for a direct payment; a sale to another node's store declines that rail, and escrow stays in bitcoin. There is no swap service, mixer, or ecash mint. Direct payment goes from the buyer to the vendor with no intermediary; moderated payment goes through the escrow of §11.

10.1 One payment per seller

A multi-seller checkout produces one order per seller, and each order is paid by its own transaction with exactly one recipient output and, if needed, one change output back to the buyer's own wallet. Two sellers are never paid in one transaction, because a transaction with outputs to two vendors would tell anyone watching the chain that the same person bought from both.

Separate transactions are necessary for unlinkability, not sufficient. If the wallet funds the second payment with the change from the first, the common-input-ownership and change heuristics [35] link the two payments. Choosing inputs so that the payments of one checkout do not share ancestry is still open: the node's own unconfirmed change is spendable, so one payment can fund the next.

10.2 On-chain direct payment

Each direct order receives a fresh receive address from the vendor's descriptor wallet (BIP 86 Taproot) and a BIP 21 [49] URI for the exact amount. The buyer can pay from its node's wallet or from any external wallet. The vendor's node watches that address and marks the order paid after one confirmation on the test network, or three on mainnet.

Compact block filters do not show the network mempool. A filter peer serves blocks. The node records an unconfirmed transaction when it broadcast that transaction itself, and an incoming payment stays invisible until a block includes it. When the buyer's node broadcasts a direct payment for a sale, it sends the seller a letter naming the transaction. Until a block pays the order, the seller shows "Payment sent, waiting for confirmation" (§8.5). The letter is not what marks the sale paid.

While that direct payment is still unconfirmed, the buyer can replace it with a higher fee. The replacement pays the same recipient the same amount. The added fee comes from the buyer's change, and the wallet may add more of the buyer's own inputs to cover it. The buyer enters the wallet passphrase again and a maximum fee. The node broadcasts the replacement only when its fee is within that cap. Escrow funding is a different rule: a funding transaction that signals replace-by-fee is rejected, so its transaction id cannot change under the presigned spends (§13).

Chain data. Every query to a block explorer such as an Esplora server [7] names a specific address. Whoever answers learns the full set of addresses the node watches, their timing, and, without Tor, the node's IP address, which together link a user's orders to each other and to a network location. Routing such queries over Tor hides the IP address but not the address set. Running one's own Bitcoin node, or using compact block filters [41, 42], hides both, and is the configuration the node uses unless the operator names an explorer. On the test network the node may ask a public explorer while no filter peer has answered, or while the filter scan has stalled. Mainnet does not, unless the operator turns that fallback on. A node using a public explorer should warn its user. An explorer can show an unconfirmed payment that filters cannot; the sale is still paid only after the confirmations above.

10.3 Lightning

Lightning [46] is a direct-payment rail only; escrow stays on chain. A mainnet node refuses it. The embedded Lightning node has no proxy, so its peers, a service provider, and its chain and gossip servers would see the node's IP address. The node therefore refuses Lightning flags at startup, refuses turning the rail on, returns the reason from status, refuses the other Lightning routes, signs the store record with the Lightning flag clear, and refuses Lightning at checkout even when a stored record still has the flag set. Test networks still run the rail. There is no mainnet service-provider default.

On a test network a store opts in through a flag in its signed store record. For each order the vendor's node issues a BOLT 11 invoice [47] for the order's exact amount with a fresh payment hash. The node marks the order paid when the payment settles. A buyer can pay from its own node or from any Lightning wallet. A sale to another node's store does not carry a Lightning invoice; the terms of that sale are the on-chain address in §8.5.

Inbound liquidity. A new vendor has no channel that can receive. The vendor names a Lightning service provider, or opens channels and names none. On the signet used for tests, the node can start with a public provider: the invoice routes through it, and when the first payment arrives

the provider opens a channel sized for the payment and keeps a fee (LSPS2 [33]). The provider is the vendor's configuration, not a party the network runs. Nothing selects a provider on mainnet. Invoices are per order rather than a BOLT 12 offer [48] in the store record, because a provider can open a just-in-time channel only for a payment it was told about in advance. The store record keeps its offer field for a vendor that already has inbound channels.

What it reveals. The invoice names the vendor's Lightning node key and the service provider. It carries no IP address. The provider sees the amount and time of every payment to the vendor and the channels it opens, and it must be online for a new channel to open; it does not see what was bought, by whom, or where it ships. The vendor's Lightning node key is derived from the seed on its own path, distinct from the store signing key. Every routing hop sees the amount it forwards and its neighbors [29]. Lightning peers and the provider see the IP address of a node that connects to them in the clear. That is why mainnet refuses the rail until those connections run over Tor.

10.4 Silent payments: BIP 352

The store record also carries a BIP 352 silent-payment code [3]. A silent-payment code lets a payer derive a fresh output for each payment from a static public code, so a single published code does not lead to address reuse, and a buyer can pay without first asking the vendor for an address. The vendor's node scans the chain for outputs to its code with the watch-only scan key, which stays on the node so that scanning does not hand the key to a public indexer. Scanning is expensive without a full node, which is part of why the recommended configuration runs one.

10.5 Payjoin: BIP 77

Payjoin v2 [23] lets a receiver add an input to the buyer's transaction through an asynchronous directory reached over Oblivious HTTP [54], which breaks the assumption that all inputs belong to the payer. Payment terms can carry a `pj=` endpoint for this. When Payjoin is used, the vendor learns which coins the buyer spent, and the buyer learns one of the vendor's coins.

10.6 What the chain shows

For an on-chain direct payment, a chain observer sees an ordinary transaction with one or two outputs. The amount is the listing price times quantity plus shipping. Prices are public, so an amount that matches a distinctive price can identify the listing that was bought, even though nothing else in the transaction refers to OpenBazaar. Round prices reduce this and do not remove it. For escrow, see §11.10.

11 Scriptless Escrow

A moderated purchase protects the buyer against non-delivery and the vendor against a buyer who will not release payment, with a moderator to decide disputes. The original OpenBazaar used a 2-of-3 multisignature script for this. The redesign keeps the economic model (a moderator together with one party can decide the outcome) and changes three things: the moderator holds no key over the funds; every outcome looks like an ordinary single-key Taproot spend; and the moderator can choose only between two payouts that buyer and vendor both signed before funding.

This section specifies the two-party protocol: the parties' messages, the checks each party and the moderator run, the transactions, and the timeline.

11.1 Notation

G generates the secp256k1 group of prime order n. Lowercase letters are scalars and uppercase letters are points. H_{tag} is a BIP 340 tagged hash.

- Long-term keys: buyer $(\bar{b}, \bar{B})$, vendor $(\bar{v}, \bar{V})$. Moderator: a signing key (k_s, K_s) for rulings and a separate encryption key (k, K) for shares.
- Per-order keys (b, B) and (v, V), fresh for every order: each party derives its key from its own seed at a fresh hardened BIP 32 index (§7). Alternatively, $b = \bar{b} + \mathsf{H}_{\text{ord}}(\bar{B}, s)$ for an order secret s that travels inside the sealed order letter.
- Aggregate key: $P = \mathsf{KeyAgg}(B, V)$ under BIP 327 [37] with the two keys sorted; output key $Q = P + \mathsf{H}_{\text{TapTweak}}(P)\,G$, the BIP 341 [57] tweak with no script tree. The funding output is P2TR with output key Q and value F.
- Moderator record $\mathcal{M} = (K_s, K, S_M, \varphi, \Pi_M)$: the moderator's two keys, payout script, fee, and acceptance policy, signed and published by the moderator.
- Terms $\tau = (B, V, \mathcal{M}, F, f, h_D, h_C, h_R, S_B, S_V)$: funding value F, network fee f, dispute deadline h_D, vendor claim height h_C, refund height h_R, and payout scripts for buyer and vendor. Both parties sign τ; the signed terms are τ^*.
- Outpoint o of the funding output.
- For a dispute branch favoring party $X \in \{B, V\}$, with $\bar{X}$ the other party: the *party half* t_X, $T_X = t_X G$, derived by X from its per-order secret key and the branch; the *moderator half* u_X, $U_X = u_X G$, sampled by $\bar{X}$; the adaptor point $Y_X = T_X + U_X$.
- $\mathsf{VEnc}_K(u; ctx)$: verifiable encryption of u to K, bound to context ctx (§11.9). $\pi^{\text{pok}}(t)$: Schnorr proof of knowledge of t.

11.2 Terms and transactions

Before any funding round, the parties agree on τ. The vendor proposes it, typically with a delivery window of about two weeks (h_D around 2,016 blocks above the tip) and ruling and claim windows of 144 blocks each.

11.3 Checks on the terms

Each party checks τ twice before round 1, under its own policy and under the moderator's policy Π_M carried in τ, and again at funding against its own view of the chain tip. A party that finds any check false aborts; nothing has been signed that could move funds. The attack each check stops is in §13.1.

(C1) *Moderator.* $\mathcal{M}$ equals, byte for byte, the moderator record the party already trusts, so its keys, payout script S_M, fee φ, and policy cannot be substituted by the counterparty.

(C2) *Keys.* The four keys B, V, K_s, K are distinct, and the moderator's ruling key differs from its encryption key.

(C3) *Heights in the future.* $0 < h_D < h_C < h_R$ are block heights; $h_C - h_D$ and $h_R - h_C$ are each at least 144 blocks; and, relative to the party's current tip, h_D is at least 1,008 blocks away and h_R at most 12,960 blocks away. Both bounds are checked again when funding is signed.




Figure 3: Escrow transaction graph. All five spends are key-path spends of the same output under the MuSig2 aggregate of the buyer's and vendor's per-order keys; the moderator's key is not part of Q. Four spends are presigned before funding; the release is signed cooperatively later. f is the network fee, φ the moderator fee, and a the 240-satoshi pay-to-anchor output, all fixed by the signed terms; lt is `nLockTime`.

(C4) *Payouts.* The three payout scripts S_B, S_V, S_M are distinct, each is a standard type (P2WPKH, P2WSH, P2TR, P2PKH, or P2SH), and each output in every spend is above that type's dust limit. The moderator payout is exactly (S_M, φ) from $\mathcal{M}$.

(C5) *Fees.* f is non-zero and below a cap (50,000 satoshis), and every presigned spend meets a fee floor (4 sat/vB) on its signed size. Every spend except the release carries an anchor output (below).

(C6) *Policy.* τ satisfies Π_M: the moderator's minimum funding value and minimum windows.

(C7) *Funding.* The funding transaction spends only native segwit inputs, none of which signals replace-by-fee, so its transaction id is final before anything is presigned; it creates exactly one output with key Q and value F at o.

From τ and o, each party derives the same five spends (Figure 3). Each has one input spending o with sequence `0xfffffffe` (so `nLockTime` is enforced) and is signed as a BIP 341 key-path spend with `SIGHASH_DEFAULT`:

Spend	`nLockTime`	**Outputs**	**When signed**
$\mathsf{tx}_{\mathrm{rel}}$ (release)	0	$F - f \to S_V$	cooperatively, after delivery
$\mathsf{tx}_{\mathrm{clm}}$ (vendor claim)	h_C	$F - f - a \to S_V$, $a \to \mathsf{A}$	presigned (buyer, round 3)
$\mathsf{tx}_{\mathrm{ref}}$ (buyer refund)	h_R	$F - f - a \to S_B$, $a \to \mathsf{A}$	presigned (vendor, round 2)
tx_{B} (buyer wins)	0	$F - f - a - \varphi \to S_B$, $\varphi \to S_M$, $a \to \mathsf{A}$	adaptor Y_B (vendor, round 2)
tx_{V} (vendor wins)	0	$F - f - a - \varphi \to S_V$, $\varphi \to S_M$, $a \to \mathsf{A}$	adaptor Y_V (buyer, round 3)

Here A is a keyless pay-to-anchor output and $a = 240$ satoshis; anyone can spend it to bump the parent's fee by child-pays-for-parent. The release is re-signed cooperatively whenever needed, so




Figure 4: Escrow timeline. The default after h_C is the vendor; the refund at h_R matters only if the vendor never claims. Window sizes are policy minimums checked by each party at funding against the current tip; the minimums are 1,008 blocks from the tip to h_D and 144 blocks for each later window.

it has no anchor. All five are version-2 transactions. A transaction with `nLockTime` h can first be mined in block $h + 1$.

11.4 Funding rounds

Let N denote a party's MuSig2 public nonces for the four presigned spends and $\mathsf{ps}(\cdot)$ a MuSig2 partial signature [36] (or partial adaptor signature, for tx_B and tx_V).

Round 0. Both parties sign τ.

Round 1, buyer → vendor. The buyer prepares, but does not sign or broadcast, a funding transaction from native segwit inputs that do not signal replace-by-fee, so its transaction id is fixed before signing and cannot change afterwards. It sends $\big(o,\ \mathsf{N}_B,\ T_B,\ \pi^{\mathrm{pok}}(t_B),\ \mathsf{VEnc}_K(u_V; ctx_V)\big)$. The buyer samples u_V because the buyer loses branch V.

Round 2, vendor → buyer. The vendor checks $\pi^{\mathrm{pok}}(t_B)$ and the encryption proof for U_V (it is the favored party in branch V, so it must be sure the moderator can reveal u_V). It replies $\big(\mathsf{N}_V,\ T_V,\ \pi^{\mathrm{pok}}(t_V),\ \mathsf{VEnc}_K(u_B; ctx_B),\ \mathsf{ps}_V(\mathsf{tx}_\mathrm{ref}),\ \mathsf{ps}_V(\mathsf{tx}_\mathrm{B}; Y_B)\big)$.

Round 3, buyer → vendor. The buyer checks $\pi^{\mathrm{pok}}(t_V)$ and the encryption proof for U_B, adds its own partial signatures, and verifies that the completed refund is a valid signature under Q for the exact outpoint and value, and that the buyer-wins pre-signature is valid for Y_B. Only after these checks may the buyer sign the funding transaction, and only after it has durably stored the refund. The buyer sends $\big(\mathsf{ps}_B(\mathsf{tx}_\mathrm{clm}),\ \mathsf{ps}_B(\mathsf{tx}_\mathrm{V}; Y_V)\big)$. The vendor completes the claim, verifies the vendor-wins pre-signature, and durably stores both.

Funding. The buyer signs and broadcasts the funding transaction. The vendor checks that a transaction creates exactly the agreed output at o, and ships only after it confirms.

Each party's state is consumed when it advances and cannot be copied, and secret nonces live only inside those states, so a nonce cannot be reused for two messages. The release uses fresh nonces generated later.

Why each piece is there.

- *Refund before funding.* The buyer never signs the funding transaction until it holds a refund that verifies against the aggregate key. A vendor who aborts after round 1 costs the buyer nothing.

- *Claim before refund.* The buyer presigns a claim at $h_C < h_R$, so a buyer who received the goods and stops responding loses at $h_C + 1$.
- *Proof of knowledge on T_X.* Without it, X could choose $T_X = T' - U_X$ for a T' whose discrete log it knows, making $Y_X = T'$ and letting X complete its own winning branch without the moderator.
- *Verifiable encryption of u_X.* Without it, the losing party $\bar{X}$ could encrypt a value that does not match U_X, and the moderator would be unable to rule for X.
- *Per-order keys.* A fresh key per order gives a different Q for every order between the same two parties, so funding outputs between repeat trading partners are not linkable by address.

11.5 Release

When the buyer is satisfied, the vendor sends a fresh public nonce for $\mathsf{tx}_{\mathrm{rel}}$, and the buyer returns its nonce and partial signature. The vendor aggregates them into a 64-byte signature and broadcasts. If the vendor loses its nonce, the buyer can sign again until the release confirms; once the buyer has signed a release, its own refund and dispute paths are closed. The moderator is not involved.

11.6 Disputes

Before h_D, either party X can ask the moderator to rule for it by sending a *dispute letter*, sealed to K and carried to the moderator's mailbox:

$$L_X = \big(\tau^*,\ o,\ F,\ \mathit{script}(Q),\ Q,\ X,\ \mathsf{tx}_{\mathrm{X}}\ \text{(unsigned)},\ T_X,\ \mathsf{VEnc}_K(u_X),\ \hat{\sigma}_X,\ \mathit{memo}\big)\ \text{signed by } X.$$

Here $\hat{\sigma}_X$ is the aggregated adaptor pre-signature on tx_{X} for Y_X. The letter is self-verifying: the moderator checks that the signed terms carry exactly its own published record and satisfy its published policy, checks the funding output at o against its own chain view, recomputes P, Q, the funding script, and tx_{X} from the terms and outpoint, checks that $\hat{\sigma}_X$ is a valid pre-signature on tx_{X} for $T_X + U_X$, checks the encryption proof, and checks X's signature over the letter. It refuses a letter that arrives after h_D by its own chain view. It then durably records the branch X for $(\mathsf{H}(\tau^*), o)$ and refuses any later letter for the other branch of the same escrow. Only then does it decrypt u_X. A letter whose exact bytes it has already verified skips the proof checks but not the deadline and chain checks.

If it rules for X, the moderator returns a *ruling* $(\mathsf{H}(\tau^*), Q, o, X, Y_X, u_X)$ signed with k_s. X computes $t_X + u_X$, completes $\hat{\sigma}_X$ into a valid BIP 340 signature, and broadcasts tx_{X}, which pays X and the moderator's fee.

A ruling for X is useless to $\bar{X}$, because $\bar{X}$ does not know t_X. A moderator that signs rulings for both branches of the same terms and outpoint produces two signed rulings that together are transferable proof of equivocation. An honest moderator's ruling store prevents this by accident. Deliberate equivocation is detectable, not preventable: both dispute outcomes are valid from height 0, so if both parties receive a ruling, the first to confirm wins.

11.7 Timeline

Figure 4 shows the heights.

- From funding until h_D, the vendor ships, the buyer receives, and either party may send a dispute letter.

- Between h_D and h_C, the moderator rules and the winner must confirm its outcome. A buyer who wins must confirm tx_{B} before $h_C + 1$, when $\mathsf{tx}_{\mathrm{clm}}$ also becomes valid.
- At $h_C + 1$, the vendor can claim. A vendor who never claims leaves the funds in the output until $h_R + 1$, when the buyer's refund becomes valid. If the vendor's claim is not confirmed by then, both are valid and the first to confirm wins.

The default outcome is therefore the vendor's. We considered and rejected a design in which the default flips to the buyer until the vendor posts a shipping attestation: without a trusted third party that observes shipping, such an attestation is not a cryptographic event, and a buyer who wants to cheat would decline to countersign it. The consequence is that a buyer who did not receive the goods must open a dispute before h_D.

11.8 Moderator fee

The moderator fee is an output of each dispute outcome and of nothing else, and it is fixed in the signed terms. It is collected only when the winner broadcasts the dispute outcome. A vendor who wins a ruling close to h_C can skip the fee by waiting for the fee-free claim; a buyer who wins cannot. This biases the moderator's income toward rulings for the buyer. §16 discusses two remedies.

11.9 Verifiable encryption of the moderator half

The moderator half u with $U = uG$ is encrypted bit by bit with exponential ElGamal under K. For each bit β_i of u ($i = 0, \ldots, 255$), the encryptor picks r_i and publishes $(A_i, C_i) = (r_i G,\ r_i K + \beta_i G)$ with a Cramer–Damgård–Schoenmakers OR proof [14] of two Chaum–Pedersen statements [9] showing that $\beta_i \in \{0, 1\}$. A Chaum–Pedersen proof then shows

$$\log_G\Big(\textstyle\sum_i 2^i A_i\Big) = \log_K\Big(\textstyle\sum_i 2^i C_i - U\Big),$$

which holds exactly when $\sum_i 2^i \beta_i \equiv u \pmod{n}$. Anyone with K and U can check the ciphertext; only the holder of k can decrypt, since $C_i - kA_i$ is either the identity or G. All challenges are tagged hashes over length-prefixed inputs and a 32-byte context that binds the proof to one escrow branch. This is the bitwise approach to verifiable encryption of a discrete logarithm [8, 52]. Its cost is size: one encrypted share is 49,761 bytes (§15).

11.10 What the chain shows

Every spend is a single-input Taproot key-path spend with one 64-byte signature. No script, no moderator key, and no multisignature structure appears on chain in any outcome, including a dispute. This is the main privacy improvement over the original 2-of-3 design. What remains visible:

- The funding amount F (price plus shipping plus fees), which can point to a listing with a distinctive price.
- The 240-satoshi pay-to-anchor output on the refund, claim, and dispute outcomes is distinctive: few ordinary wallet payments carry one, so these spends are recognizable as presigned contract spends. A cooperative release has no anchor and looks like an ordinary one-output Taproot spend.
- Dispute outcomes have three outputs, one of which is the fixed moderator fee φ. If a moderator reuses its payout script S_M, every dispute it rules on is linked on chain to it and to the others.

The moderator record fixes S_M, so a moderator reuses its payout script across all escrows under one record; a moderator that wants its fees unlinked must publish new records.

- The claim and refund carry non-zero `nLockTime` values at specific heights, and all spends signal no replace-by-fee. These are weak fingerprints, since many wallets set `nLockTime` near the current height.
- Timing: a spend shortly after funding versus one after h_C.

11.11 Fees and message size

Presigned transactions have fees fixed at funding, at or above the floor of (C5). If fee rates rise, the recipient of a refund, claim, or dispute outcome bumps it through the anchor output by child-pays-for-parent. The transactions are version 2 rather than TRUC (version 3) [58], so they do not get TRUC's protection against pinning; a third party who attaches a large low-fee child to the anchor can delay a bump. Each verifiable share is about 50 KB, so a dispute letter is close to the 64 KiB letter limit. A dispute letter carries the escrow terms and the claimant's memo, not the order plaintext: the moderator learns the ship-to only if the claimant chooses to include it.

12 Discovery and Search

12.1 Search on the device

Search runs over listing headers already held by the client: a case-insensitive substring match over title, category, ship-from region, kind, description, and seller name. The query is not sent anywhere, so neither the node, a replica, nor an index learns the search terms. The cost is that the client must hold the headers it searches. We measured this filter at 0.2 ms per query over 1,000 headers and 5 ms over 10,000 headers on a laptop (§15); 100,000 headers took 49–67 ms per query. Matching is literal; there is no ranking, stemming, or index. Results then pass through the buyer's content filter (§6.4), which also runs on the device.

12.2 Finding stores and nodes

The design treats every source of nodes as untrusted for content and only partly trusted for availability:

- A user can paste a store link (a store key plus an onion address). A store reached this way opens with an empty seed list.
- Seeds shipped with the software, and peers remembered from earlier sessions, are used to find replicas.
- Every record received from any of them is verified against its signature and content hash before use.

The node follows a store by a loopback URL and copies its signed records (§8.5). It does not dial a seed or an onion address to find stores. Because records are self-authenticating, a malicious seed or replica cannot forge or alter a listing. It can withhold records, serve stale ones (§6), or, if it controls all of a node's peers, present a partial view of the network: an eclipse attack [26]. Remembering peers across sessions, drawing peers from several independent sources, and preferring a pasted link over seed-supplied data are the mitigations; no Sybil defense [18] is designed beyond the publishing cost of §6.

12.3 Private search at scale

On-device search stops scaling when the catalog no longer fits on a phone. The next step in the design is private information retrieval (PIR) [10] against a periodic snapshot of the header catalog, so that a replica answers a query without learning which records were fetched. Single-server lattice-based schemes such as SimplePIR [27] make this plausible for databases of the relevant size. The scheme is not designed in detail (§16.2). Until then, a client that fetches individual records from a replica reveals its interest in those records to that replica.

13 Security Analysis

We state each property with its assumptions. The arguments are informal; a game-based or machine-checked proof is future work. The escrow properties (P1–P4) refer to the protocol of §11.

Assumption 1 (Escrow)**.** (a) MuSig2 with BIP 327 key aggregation is unforgeable [36], and adaptor pre-signatures do not let anyone without the adaptor secret produce a valid signature. (b) The proofs of knowledge, the bit proofs, and the DLEQ proof are sound in the random-oracle model. (c) Each party runs the protocol checks before advancing and keeps its own secret key. (d) The funding transaction spends only native segwit inputs that do not signal replace-by-fee and is never replaced, so its transaction id cannot change after the presigned spends are created. (e) A party who needs to broadcast a transaction gets it confirmed within the relevant window (at least 144 blocks) at the presigned fee rate or with a fee bump through the anchor output. (f) Each party durably stores the presigned spends it holds (the buyer's refund, the vendor's claim) before the step that makes them necessary, and the moderator durably stores its rulings.

Property 1 (No custody)**.** *No party other than the buyer and the vendor holds a key sufficient to spend the escrow output.*

Argument. The output key Q is a tweak of $\mathsf{KeyAgg}(B, V)$; the moderator's key K is not aggregated. Under Assumption 1(a), producing any valid signature under Q requires partial signatures from both b and v. Every spend that can exist was either presigned by both parties before funding or is signed by both cooperatively (the release).

Property 2 (Bounded moderator)**.** *A moderator, alone or with any outside party, cannot move the funds, and cannot cause any payout other than one of the two dispute outcomes whose outputs both parties signed.*

Argument. The moderator learns u_X for at most the branch it rules on. A completed signature on tx_X needs $t_X + u_X$ and the pre-signature $\hat{\sigma}_X$. The moderator does not know t_X, and by the proof of knowledge (Assumption 1(b)) X could not have chosen T_X to cancel U_X. The outputs of tx_X, including the moderator fee and payout scripts, are fixed by the signed terms and committed in its signature hash, so the moderator cannot redirect funds or change amounts. The terms carry exactly the moderator record each party already trusts, so a counterparty cannot substitute a different moderator, payout, or fee.

What the moderator can do: rule for the wrong party; refuse to rule, which leaves the parties to the claim and refund; or rule for both parties, which lets both broadcast and makes the outcome a race. The last is provable from two signed rulings over the same terms digest and outpoint, but not preventable by the parties; an honest moderator's ruling store refuses a second branch. A moderator colluding with one party (A5) can make that party win the dispute, which is the same economic trust as in a 2-of-3 escrow.

Property 3 (Buyer exit)**.** *If the vendor disappears after funding, the buyer recovers $F - f$ at height $h_R + 1$ without anyone's cooperation. If the vendor stays but does not deliver, the buyer recovers $F - f - \varphi$ provided it sends a dispute letter by h_D, the moderator rules for it, and the outcome confirms by h_C.*

Argument. The buyer holds a complete refund signature before it signs the funding transaction (refund before funding), and the refund needs nothing but height $h_R + 1$. If the vendor never broadcasts the claim, nothing else can spend the output before then except the release (which the buyer must sign) and the dispute outcomes (which need a ruling). For the second case, the buyer holds the pre-signature for tx_B and the moderator can reveal u_B because the buyer verified its encryption in round 3. *Limits:* against a vendor who stays online and does not deliver, the buyer depends on the moderator ruling in time; if the moderator does not, the vendor claims at $h_C + 1$. Both parties require h_D to lie at least a delivery window above the tip at funding, so a vendor cannot propose heights that are already past.

Property 4 (Vendor protection against a stalling buyer)**.** *If the buyer stops responding after funding, the vendor collects $F - f$ at height $h_C + 1$ without anyone's cooperation.*

Argument. The vendor holds a complete claim signature from round 3 with `nLockTime` $h_C < h_R$. The buyer's only competing unilateral spend is the refund, which is not valid until $h_R + 1$, and a buyer dispute needs a ruling. *Assumptions:* the vendor kept the claim (Assumption 1(f)) and confirms it inside the claim window (Assumption 1(e)). A vendor that loses the claim lets the buyer take the refund at $h_R + 1$.

Property 5 (Catalog integrity)**.** *A party that does not hold a store's secret key cannot produce a store record or listing that verifies under that store's key, and cannot alter a listing, or its content label, without changing its address. The same holds for a labeler's sets under the labeler's key.*

Argument. BIP 340 signatures are existentially unforgeable under the discrete-log assumption in the random-oracle model. The tagged hash separates record types. The canonical encoding is injective and rejects trailing bytes, so two different records cannot share a signed body. The listing address is SHA-256 of the body, so changing any field changes the address under collision resistance. *Limits:* no freshness and no completeness (§6).

Property 6 (Letter confidentiality)**.** *Only the holder of the vendor's mailbox secret can read an order letter, and only the holder of the buyer's per-order reply secret can read a reply.*

Argument. HPKE base mode is IND-CCA2 secure for the recipient under the Gap Diffie–Hellman assumption on X25519 and AEAD security of ChaCha20-Poly1305 [4]. Distinct `info` strings separate orders, replies, and escrow messages. *Assumption:* the buyer seals to the key in the vendor's signed store record (§7); a buyer who takes the key from anywhere else gives whoever supplied it the ability to read the letter.

13.1 Attacks the escrow checks stop

Each check in §11.3 exists because a protocol without it is attackable. We list the attacks.

Past or near heights. If a party accepted any $h_D < h_C < h_R$, a vendor could propose heights at or below the current tip: the buyer's dispute window would already be closed and the vendor's claim already valid, so the vendor could take the funds immediately after funding. Requiring $h_D \geq \mathit{tip} + 1008$ at funding, checked by both parties against their own view of the chain, and bounding h_R by a maximum lock time, prevents this.

Unspendable or substituted moderator payout. If the dispute outputs paid the moderator fee to any script the terms named, a vendor could name a non-standard script or a dust amount, making both dispute outcomes non-relayable, so that no ruling could ever be broadcast and the buyer's only exit became the refund after h_R; or the vendor could name its own script as the "moderator" payout and collect the fee on a buyer win. Every payout must be a standard type above dust, the three payout scripts must differ, and the moderator's script and fee must equal those in its published record. The moderator itself refuses letters whose terms name a different payout or fee.

Replayed rulings. If a ruling only named a branch, a ruling for the buyer in one escrow could be presented as the moderator's statement in another with the same moderator. Rulings sign the terms digest, the output key, the funding outpoint, the branch, and the adaptor point, and the moderator checks on its own chain view that the outpoint exists and pays the terms' output key and amount before ruling.

Ruling both ways. A stateless moderator that receives a dispute letter from each party could reveal both u_B and u_V, turning the escrow into a broadcast race. The moderator keeps a durable ruling store keyed by terms digest and outpoint and refuses a second branch; two signed rulings over the same digest and outpoint are a transferable proof of equivocation.

Fee pinning and stale fee rates. Presigned spends pay a fee fixed at funding time. If fee rates rise, a dispute outcome or refund could be stuck below the relay floor until the window closes. Every spend except the cooperative release carries a small pay-to-anchor output that either party can spend to attach a child paying more (CPFP); the presigned fee is bounded below by a floor and above by a cap so that neither party can burn the other's funds to fees.

Funding replacement. A replaced funding transaction would have a new transaction id and strand every presigned spend, including the buyer's refund. Funding inputs that signal replace-by-fee are rejected, and the buyer must not double-spend its own funding inputs.

Secret moderator policy. If the moderator's acceptance rules (minimum amount, minimum windows, fee) were private, a moderator could refuse a dispute on grounds neither party could check beforehand. The policy is part of the moderator record inside the signed terms, and both parties check the terms against it before funding.

13.2 Other attacks considered

Rogue keys. BIP 327 key aggregation weights each key with a coefficient that depends on all keys, which prevents a party from choosing its key to cancel the other's [34]. The party halves T_X are protected by proofs of knowledge, as above.

Nonce reuse. MuSig2 secret nonces are single-use: a party's state is consumed when it advances and cannot be copied, and the release draws new nonces, distinct from those of the dispute outcome that pays the same party the same amount.

Garbage moderator share. A losing party that encrypts a value not matching U_X is caught by the favored party's check before that party signs anything leading to funding.

Late dispute letters. The moderator refuses letters received after h_D, so a ruling always has the full ruling window before the vendor claim becomes valid. The moderator's notion of "received" is its own view of the chain height, and it applies that check even to letters it has verified before.

Denial of service on the moderator. Each letter carries a 50 KB share whose verification costs about 50 ms (§15). The moderator caches letters it has verified and does not repeat the verification on decryption, but an attacker can still send many distinct letters; rate limits per source and batched verification (§16.2) bound the cost.

Client impersonation on the same machine. A local process that can read the pairing token can act as the client (§5). A paired remote device can make the requests its key is allowed to make until the owner removes it. It cannot read the backup phrase, and a spend still requires the wallet passphrase (§5.2). A compromised device is out of scope (A6).

14 Privacy Analysis

Table 2 lists, for each party or observer, what it learns, what it does not, and which mechanism the second column relies on. Chain data comes from the node's own Bitcoin node or from compact block filters unless stated otherwise. A phone reaches its own node over the sealed home-network channel or over Tor (§5.2). Sale letters between two nodes go to a loopback address (§8.5).

Table 2: Who learns what.

Observer	Learns	Does not learn	Relies on
Seller	Items, quantities, and options in its own package; the ship-to for physical goods or the delivery note for digital goods; the payment and its amount; with Payjoin, the buyer's inputs; for a sale, the transaction id the buyer's node reports before a block.	The buyer's orders with other sellers; any long-term buyer identity (none is sent). The sale path dials only a loopback address, so it does not publish a buyer IP on the open internet.	One letter and one payment per seller; loopback mail (§8.5). Shared ancestry across one checkout is still open (§10).
Carrier	Ship-to, parcel, and delivery timing.	Price paid, payment method, other orders.	Nothing: this is the ceiling for physical goods.
Moderator, no dispute	That it is named in public listings.	That a given order used it; its key is not on chain.	Key-path escrow; the moderator is contacted only on a dispute.
Moderator, dispute	Signed terms (per-order keys, amounts, heights, payout scripts), the outpoint and therefore the on-chain funding and spends, and whatever the claimant puts in its memo.	The order contents and ship-to, unless the claimant includes them; other orders of either party.	Dispute letters carry no order plaintext; fresh per-order keys and payout scripts.

Observer	Learns	Does not learn	Relies on
Any node, from reviews	A store's reviews: stars, text, listing, the day each review was signed, and the month of payment; the seller's replies.	Who wrote a review; which reviews one buyer wrote; which node's user wrote a review it pulled, since every node serves its whole pool.	Per-order review keys; pools that mix every store's reviews; a delay of up to three days.
Node a buyer sends a review to	That the review came from the buyer's node, at the address that node connects from.	The buyer's other reviews, unless that node also receives them; the order or the ship-to.	Per-order review keys; sending only to the seller and followed nodes.
Seller, from reviews	Which of its orders wrote each review, since it signed that order's receipt.	Anything about the reviewer beyond that order.	Per-order review keys.
Labeler	That some node fetched its sets, and when, from the sample labeler or a loopback URL.	What buyers bought. The follow list stays on the buyer's node.	The private follow list.
Replica	Which records a node copies from a store it follows at a loopback address, and when.	Orders; search terms (search is on the device).	Signed copies of followed stores (§8.5).
Seed	Nothing from this node. It does not dial a seed.	Records, orders, and the node's address.	On-device catalog and followed stores.
Chain observer	Amounts and timing of every payment; for escrow, a single-key-looking Taproot output and spend; a dispute outcome with a fixed moderator fee; a pay-to-anchor output marking refund, claim, and dispute spends as contract spends; links through shared inputs or change. Prices are public, so a distinctive amount can identify a listing.	Moderator keys, escrow scripts, that a dispute occurred (beyond output pattern), ship-to.	Key-path escrow; Payjoin, where used.
Block explorer, if used	Every address the node watches, with timing; without Tor, the node's IP. This links all of a user's orders together.	Order contents.	Not using one: own node or compact block filters.
Tor relays	On the phone's path to its node, and on the admin onion: the guard learns that endpoint's IP and that it uses Tor. Rendezvous and middle relays learn neither end.	Sale-letter contents, which are not on this path.	Restricted-discovery onion service (§5.2).
Lightning hops	Forwarded amounts, timing, and adjacent channels. The payer learns the recipient's node key from the invoice. On mainnet this rail is refused (§10).	Order contents.	Blinded paths, on a test network.
Lightning service provider	On a test network, when the vendor names one: amount and time of every payment to that vendor, the channels it opens, and the vendor node's IP, because the connection is in the clear.	What was bought, the buyer, the ship-to. There is no mainnet provider, and mainnet does not run the rail.	The vendor's choice of provider, or its own channels and no provider.
Exchange-rate source	That a node asks for rates, and when.	What was bought; the node's IP, if asked over Tor.	Tor when a proxy is set; otherwise the request is in the clear.

Observer	Learns	Does not learn	Relies on
Local network or ISP	That the user runs Tor when the phone or the home node uses it. On the home network, requests to the node use a channel sealed to the node key and fall back to the admin onion when that channel does not answer. A client on the same machine uses loopback.	Order contents on the phone-to-node path.	Sealed home-network channel and Tor fallback (§5.2).
Push gateway	Nothing, until a device opts in and the operator names a gateway. Then the gateway learns a device token and the time of a content-free wake-up. This project runs no gateway, so nothing is sent until someone does.	Order contents, which node asked, and the node's address. The node reaches a gateway over Tor.	Opt-in per device (§5.2).
Global passive adversary	Can correlate the phone's Tor circuit with the home node's connection.	Letter contents. Sale letters between two nodes are on loopback.	Out of scope; a mixnet for letters (future).
Same-machine process	The pairing token, then everything the client can see.	—	Out of scope (A6).

The ship-to ceiling. For physical goods, the seller and the carrier learn where the buyer receives parcels. No protocol mechanism removes this, and we do not claim to. What the design does is keep the ship-to out of every other place: it is not in the catalog, not in any public record, not in the buyer's own order history on disk (which stores a label), and not in a dispute letter unless the buyer puts it there. It travels inside the sealed letter to the seller.

Linking a buyer's orders. Separate letters and separate transactions are necessary for unlinkability across sellers, not sufficient. Three channels can still link one buyer's orders: a block explorer, if the node uses one, which sees all watched addresses together; the chain, if payments share inputs or change; and timing, if a buyer places several orders at once and an observer sees them confirm together. The first is removed by using one's own chain data. The second is still open: the node will spend its own unconfirmed change (§10). The third is only partly addressed, by spacing payments.

15 Evaluation

We measured the operations whose cost determines whether the design is practical on ordinary hardware, using the reference implementation. All numbers are from one machine (Apple M2 Max laptop, 32 GB, macOS 26.7, Rust 1.94 release builds, Node.js 24.6), averaged over the stated number of repetitions after a warm-up. They are microbenchmarks of local computation; we did not measure anything over a network, Tor, or a phone. Table 3 lists them.

The share size follows from the format: one 33-byte point, 256 ciphertext pairs of two 33-byte points each, 256 OR-proofs of four 32-byte scalars each, and a 64-byte DLEQ proof: $33 + 256 \cdot (66 + 128) + 64 = 49{,}761$. An escrow funding exchange carries two shares (one per dispute branch), so about 100 KB, and a dispute letter carries one. Decryption tests each of the 256 bits against the identity and G; because the moderator verifies a letter once and caches the result, decryption costs a few milliseconds rather than a second full verification.

Operation	Result	Repetitions
Encoded listing (a paperback)	268 bytes	—
Encoded sample catalog (1 store, 38 listings)	9,940 bytes	—
Sign one listing (BIP 340)	101 μs	2,000
Verify one listing	48 μs	2,000
Verify the whole sample catalog	1.9 ms	200
Order plaintext with a four-line US ship-to	173 bytes	—
Sealed letter, smallest bucket	2 KiB	format
HPKE seal one order	115 μs	2,000
HPKE open one order	75 μs	2,000
Verifiable moderator share, size (by the serialization format)	49,761 bytes	—
Encrypt one share	44–50 ms	20, two runs
Verify one share	48–50 ms	20, two runs
Decrypt one already-verified share	5–8 ms	20, two runs
On-device search, 1,000 headers	0.2 ms/query	100
On-device search, 10,000 headers	5 ms/query	100
On-device search, 100,000 headers	49–67 ms/query	100, two runs

Table 3: Measured costs. Search headers were synthesized by repeating the sample headers with distinct titles; queries were a mix of matching and non-matching terms.

These numbers support three conclusions. Signing and verifying the catalog and sealing orders cost well under a millisecond each, so they are not a bottleneck. The seal and open times were measured on a short letter; a letter on the wire is one of the size buckets in §8. On-device search over tens of thousands of headers is interactive on a laptop; we have not measured it on a phone. The verifiable share dominates the escrow's cost in both bytes and time, which is why smaller proofs are the first item of future work (§16.2).

16 Limitations and Future Work

16.1 Limitations

We collect the limitations of the design, ordered roughly by how much they matter to a user.

1. **The moderator is trusted to rule, and to rule in time.** A moderator that does not rule leaves a non-delivered buyer to lose at $h_C + 1$. Equivocation is provable, not preventable.
2. **Moderator and party collusion.** A moderator colluding with one party decides the dispute for that party. This is the same economic trust as a 2-of-3 multisignature escrow, and the protocol does not reduce it; it only removes the moderator's ability to take funds for itself or redirect them. Reputation, published equivocation proofs, and moderator panels (below) are the only counterweights.
3. **Moderator fee bias.** The fee is paid only from a dispute outcome. A vendor who wins a ruling near h_C can wait for the fee-free claim, while a buyer who wins must broadcast tx_{B} and pay. In expectation the moderator is paid more for buyer wins than for vendor wins, an incentive toward ruling for the buyer. Two remedies preserve the rest of the protocol: put the moderator fee into the claim $\mathsf{tx}_{\mathrm{clm}}$ as well, at the cost of charging it on undisputed escrows that end by claim; or lock a separate fee bond at funding, paid to the moderator by any dispute outcome and refunded to its owner otherwise, at the cost of a second output and its own presigned spends. Neither is part of the protocol above.

4. **The buyer must act before h_D.** The default outcome after h_C is the vendor's, so a buyer who does not dispute non-delivery in time loses the payment.
5. **Proof size and verification cost.** Each verifiable share is about 50 KB and costs about 50 ms to verify. Funding carries two shares, and an attacker can make a moderator verify many letters. The cost is tolerable on a laptop and heavy on a phone.
6. **Presigned fees and pinning.** Presigned escrow spends have fees fixed at funding and rely on a child-pays-for-parent bump through the anchor. As version-2 transactions they lack TRUC's pinning protection, and a fee spike near h_C can let the vendor's claim race the buyer's dispute outcome.
7. **Escrow outcomes are recognizable.** The anchor output marks refund, claim, and dispute spends as contract spends, and a moderator that reuses its payout script links its disputes.
8. **No catalog freshness or completeness.** A replica can serve stale listings or omit them without detection.
9. **Amounts can identify listings.** Public prices let a chain observer guess what was bought from the payment amount.
10. **Letter sizes leak.** Letters are padded to a few size buckets, so an observer learns the bucket.
11. **Timing correlation.** Tor does not resist an adversary who can watch both a phone and its home node. Sale letters are on loopback, so they are visible to whoever can see those two machines. Letter timing can still be correlated with chain timing.
12. **Reviews show signed purchases, not independent buyers.** A seller can sign receipts for review keys it holds and review itself, and a review reaches only nodes connected to one that holds it.
13. **Labels are only advice.** Self-labels are only as honest as the vendor, and labelers only as good as the buyer's choice of them; nothing in the design removes content from the network.
14. **The device is trusted.** A process on the same machine can act as the client, and at-rest encryption is only as strong as the protection of its key.
15. **Informal analysis.** The security arguments in §13 are informal, and the protocol has had no external cryptographic review.

16.2 Future work

A change to the protocol, to payments, to the threat model, or to the seller's flow updates this paper in the same pull request. The paragraphs below are open problems. They are not behavior the nodes already have.

Smaller verifiable encryption. Bitwise ElGamal is simple and relies only on the discrete-log setting of secp256k1, but it is large. Batch verification of the 256 bit proofs would cut the moderator's verification cost substantially without changing the format. Verifiable encryption in a group with an easy discrete-log subgroup, such as the class-group or Paillier-based constructions used for two-party ECDSA and scriptless swaps [50], could reduce the share to a few kilobytes, at the cost of a second hardness assumption.

Moderator panels. Replacing the single moderator with a t-of-n panel that shares the decryption key with FROST-style key generation [30] would require collusion between a party and t moderators rather than one.

Fee neutrality. Choosing between the two fee remedies above, or finding one that charges the moderator fee exactly when a dispute was opened, is open.

Pinning-resistant presigned spends. Moving the presigned spends to TRUC transactions with an ephemeral anchor would give them the pinning protection that version-2 transactions lack.

Catalog freshness and spam. A per-store sequence number and a signed index of current listings would let a buyer detect stale and withheld records. A publishing cost that replicas check would make open replication safe against spam; its form (a small payment, a proof of a funded output, or a rate limit tied to store age) is not designed.

Private retrieval and transport. Private information retrieval for catalog records at scale, and carrying order letters over a mix network. Delivering those letters over a vendor onion service is the same open work: the letter library can dial an onion service, and the node does not, so a sale runs between nodes that can reach each other's loopback addresses.

Reputation. Reviews (§9.5) are the only reputation signal in the design. Three additions are not designed beyond their outline: moderators publishing signed dispute outcomes that say which party received the funds, with no addresses or identities; an optional seller bond, time-locked on chain, that a buyer can verify before ordering; and a new-store state that shows no stars until a store has verified sales and shows its first sales as moderated escrow. Each needs care so that a direct payment between a seller and itself does not count as a completed escrow sale.

Formal analysis. A game-based proof of the escrow properties, and a machine-checked model of the message rounds and timeline.

17 Related Work

Peer-to-peer marketplaces. The original OpenBazaar [40] used IPFS-style content addressing [5] for stores, Ricardian-style signed contracts [24] for orders, and 2-of-3 multisignature escrow with a moderator. This design keeps the signed-contract idea and replaces the rest: catalogs are signed records rather than a node's public content, orders are sealed letters rather than messages between online peers, and escrow is a two-party key with an encrypted moderator share rather than a moderator-held key. Particl [44] also runs a decentralized marketplace and uses two-party deposits in which both sides lock funds, which removes the moderator but requires the buyer and vendor to over-collateralize. Bisq [6] and Haveno [25] are peer-to-peer exchanges for currency trades rather than goods; they use 2-of-2 or 2-of-3 deposits with arbitrators and security deposits, and their arbitration roles inform our moderator design. Nostr's NIP-15 [39] defines marketplace stalls and products as signed events on relays [22]; it shares our signed-catalog model but carries orders as encrypted direct messages and has no escrow.

Earlier anonymous markets. Measurement studies of Silk Road and its successors [12, 51] document how centralized escrow, operator custody of funds, and server seizure shaped those markets. We cite them for the custody and single-operator lessons; OpenBazaar's scope is ordinary legal goods, and its privacy mechanisms are those any retail buyer has reason to want.

Payments. Lightning [46] and BOLT 12 offers [48] give fast payments whose privacy depends on routing and blinded paths; Kappos et al. [29] measure how much Lightning payments leak in practice. Silent payments (BIP 352) [3] let a payer derive a fresh output for a static public code; payjoin (BIP 78, BIP 77) [17, 23] breaks the common-input heuristic [35]. Lightning is a direct-payment rail with per-order invoices; offers, silent payments, and payjoin appear in this design as encoding or library code only (§10).

Escrow and signatures. The two-party key uses MuSig2 [36, 37], a successor to MuSig [34], on BIP 340/341 outputs [56, 57]. Adaptor signatures [1] let a completed signature reveal a secret, which is how the moderator's share finishes one branch. Discreet Log Contracts [19] use an oracle's signature as an adaptor secret to select among pre-signed outcomes; our moderator plays a similar role but is told the dispute only if one is raised and learns its secret through verifiable encryption rather than publishing an attestation. The verifiable encryption follows Stadler's publicly verifiable secret sharing [52], built from exponential ElGamal [20], Chaum–Pedersen equality proofs [9], and CDS OR-composition [14] under Fiat–Shamir [21]. Camenisch–Shoup verifiable encryption [8] gives much smaller proofs for discrete logarithms but needs a different group setting, and JugglingSwap [50] gives a segmented variant closer to ours. A threshold moderator panel could use FROST [13, 30].

Anonymous transport and private retrieval. Tor onion services [16, 53] hide the server's location; Johnson et al. [28] quantify what a realistic adversary learns about Tor users over time. Mix networks such as Loopix [45] and Nym [15] add cover traffic and delay to resist a global passive adversary, at a latency cost an order mailbox can afford. Oblivious HTTP [54] separates who asks from what is asked for a single request. Private information retrieval [10], now practical at the scale of a catalog index with SimplePIR [27], is the natural next step for discovery (§12). The replication design must also contend with eclipse [26] and Sybil [18] attacks, for which proof-of-work stamps [2] are one partial answer.

18 Conclusion

We have described a marketplace in which the public catalog contains only what a seller chooses to publish, a buyer's shipping address is sealed to one seller and never enters the catalog, filtering of what a buyer sees happens on the buyer's own device, payments are non-custodial, and escrow is a two-party key in which a moderator can decide a dispute without ever being able to take the funds. The escrow's safety rests on a short list of checks that each party runs before funding: the moderator record is the one it trusts, the heights lie in the future, every payout is standard and above dust, fees fit a floor and a cap and can be bumped, the funding cannot be replaced, and the refund is in hand before anything is signed. The moderator, in turn, binds each ruling to the signed terms and the funding output and never rules twice on one escrow.

The limits are as important as the mechanisms. The seller and the carrier must learn the ship-to. The chain records every payment. A network observer who can watch both ends can correlate timing. A moderator colluding with one party decides the dispute, and the moderator's

fee as designed rewards buyer wins more than vendor wins. The verifiable encryption that keeps the moderator honest costs 50 KB per share. What the design changes is who else learns these things, and that no party can hold the buyer's or seller's funds alone. The most important next steps are a fee-neutral moderator payment, smaller verifiable encryption, and an external review of the escrow protocol.

References

[1] Lukas Aumayr, Oguzhan Ersoy, Andreas Erwig, Sebastian Faust, Kristina Hostáková, Matteo Maffei, Pedro Moreno-Sanchez, and Siavash Riahi. Generalized channels from limited blockchain scripts and adaptor signatures. In *Advances in Cryptology – ASIACRYPT 2021*, volume 13091 of *LNCS*, pages 635–664. Springer, 2021.

[2] Adam Back. Hashcash – a denial of service counter-measure. `http://www.hashcash.org/papers/hashcash.pdf`, 2002.

[3] Josie Baker, Ruben Somsen, and Sebastian Falbesoner. BIP 352: Silent payments. Bitcoin Improvement Proposal, 2023.

[4] Richard Barnes, Karthikeyan Bhargavan, Benjamin Lipp, and Christopher A. Wood. Hybrid public key encryption. RFC 9180, 2022.

[5] Juan Benet. IPFS – content addressed, versioned, P2P file system. arXiv:1407.3561, 2014.

[6] Bisq contributors. Bisq: A decentralized bitcoin exchange network. `https://bisq.network`, source at `https://github.com/bisq-network/bisq`.

[7] Blockstream. Esplora: Block explorer and HTTP API. `https://github.com/Blockstream/esplora`.

[8] Jan Camenisch and Victor Shoup. Practical verifiable encryption and decryption of discrete logarithms. In *Advances in Cryptology – CRYPTO 2003*, volume 2729 of *LNCS*, pages 126–144. Springer, 2003.

[9] David Chaum and Torben Pryds Pedersen. Wallet databases with observers. In *Advances in Cryptology – CRYPTO '92*, volume 740 of *LNCS*, pages 89–105. Springer, 1992.

[10] Benny Chor, Oded Goldreich, Eyal Kushilevitz, and Madhu Sudan. Private information retrieval. In *Proceedings of the 36th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 41–50, 1995.

[11] Ava Chow. BIP 86: Key derivation for single key P2TR outputs. Bitcoin Improvement Proposal, 2021.

[12] Nicolas Christin. Traveling the Silk Road: A measurement analysis of a large anonymous online marketplace. In *Proceedings of the 22nd International Conference on World Wide Web (WWW)*, pages 213–224, 2013.

[13] Deirdre Connolly, Chelsea Komlo, Ian Goldberg, and Christopher A. Wood. The flexible round-optimized Schnorr threshold (FROST) protocol for two-round Schnorr signatures. RFC 9591, 2024.

[14] Ronald Cramer, Ivan Damgård, and Berry Schoenmakers. Proofs of partial knowledge and simplified design of witness hiding protocols. In *Advances in Cryptology – CRYPTO '94*, volume 839 of *LNCS*, pages 174–187. Springer, 1994.

[15] Claudia Diaz, Harry Halpin, and Aggelos Kiayias. The Nym network: The next generation of privacy infrastructure. Nym Technologies white paper, 2021.

[16] Roger Dingledine, Nick Mathewson, and Paul Syverson. Tor: The second-generation onion router. In *Proceedings of the 13th USENIX Security Symposium*, pages 303–320, 2004.

[17] Nicolas Dorier. BIP 78: A simple payjoin proposal. Bitcoin Improvement Proposal, 2019.

[18] John R. Douceur. The Sybil attack. In *Peer-to-Peer Systems: First International Workshop (IPTPS 2002)*, volume 2429 of *LNCS*, pages 251–260. Springer, 2002.

[19] Thaddeus Dryja. Discreet log contracts. `https://adiabat.github.io/dlc.pdf`, 2017.

[20] Taher ElGamal. A public key cryptosystem and a signature scheme based on discrete logarithms. *IEEE Transactions on Information Theory*, 31(4):469–472, 1985.

[21] Amos Fiat and Adi Shamir. How to prove yourself: Practical solutions to identification and signature problems. In *Advances in Cryptology – CRYPTO '86*, volume 263 of *LNCS*, pages 186–194. Springer, 1986.

[22] fiatjaf and Nostr contributors. NIP-01: Basic protocol flow description. Nostr Implementation Possibilities, `https://github.com/nostr-protocol/nips`.

[23] Dan Gould and Yuval Kogman. BIP 77: Async payjoin. Bitcoin Improvement Proposal, 2023.

[24] Ian Grigg. The Ricardian contract. In *Proceedings of the First IEEE International Workshop on Electronic Contracting*, pages 25–31, 2004.

[25] Haveno contributors. Haveno: A decentralized Monero exchange. `https://github.com/haveno-dex/haveno`.

[26] Ethan Heilman, Alison Kendler, Aviv Zohar, and Sharon Goldberg. Eclipse attacks on Bitcoin's peer-to-peer network. In *Proceedings of the 24th USENIX Security Symposium*, pages 129–144, 2015.

[27] Alexandra Henzinger, Matthew M. Hong, Henry Corrigan-Gibbs, Sarah Meiklejohn, and Vinod Vaikuntanathan. One server for the price of two: Simple and fast single-server private information retrieval. In *Proceedings of the 32nd USENIX Security Symposium*, 2023.

[28] Aaron Johnson, Chris Wacek, Rob Jansen, Micah Sherr, and Paul Syverson. Users get routed: Traffic correlation on Tor by realistic adversaries. In *Proceedings of the 2013 ACM SIGSAC Conference on Computer and Communications Security (CCS)*, pages 337–348, 2013.

[29] George Kappos, Haaroon Yousaf, Ania M. Piotrowska, Sanket Kanjalkar, Sergi Delgado-Segura, Andrew Miller, and Sarah Meiklejohn. An empirical analysis of privacy in the Lightning network. In *Financial Cryptography and Data Security (FC 2021)*, volume 12674 of *LNCS*, pages 167–186. Springer, 2021.

[30] Chelsea Komlo and Ian Goldberg. FROST: Flexible round-optimized Schnorr threshold signatures. In *Selected Areas in Cryptography – SAC 2020*, volume 12804 of *LNCS*, pages 34–65. Springer, 2020.

[31] Hugo Krawczyk and Pasi Eronen. HMAC-based extract-and-expand key derivation function (HKDF). RFC 5869, 2010.

[32] Adam Langley, Mike Hamburg, and Sean Turner. Elliptic curves for security. RFC 7748, 2016.

[33] Lightning Service Provider Specification group. LSPS2 (blip 52): JIT channel negotiation. `https://github.com/lightning/blips/blob/master/blip-0052.md`, 2023.

[34] Gregory Maxwell, Andrew Poelstra, Yannick Seurin, and Pieter Wuille. Simple Schnorr multi-signatures with applications to Bitcoin. *Designs, Codes and Cryptography*, 87(9):2139–2164, 2019.

[35] Sarah Meiklejohn, Marjori Pomarole, Grant Jordan, Kirill Levchenko, Damon McCoy, Geoffrey M. Voelker, and Stefan Savage. A fistful of bitcoins: Characterizing payments among men with no names. In *Proceedings of the 2013 Internet Measurement Conference (IMC)*, pages 127–140, 2013.

[36] Jonas Nick, Tim Ruffing, and Yannick Seurin. MuSig2: Simple two-round Schnorr multi-signatures. In *Advances in Cryptology – CRYPTO 2021*, volume 12825 of *LNCS*, pages 189–221. Springer, 2021.

[37] Jonas Nick, Tim Ruffing, and Elliott Jin. BIP 327: MuSig2 for BIP340-compatible multi-signatures. Bitcoin Improvement Proposal, 2022.

[38] Yoav Nir and Adam Langley. ChaCha20 and Poly1305 for IETF protocols. RFC 8439, 2018.

[39] Nostr contributors. NIP-15: Nostr marketplace. Nostr Implementation Possibilities, `https://github.com/nostr-protocol/nips`.

[40] OpenBazaar contributors. openbazaar-go: OpenBazaar 2.0 server daemon in Go. `https://github.com/OpenBazaar/openbazaar-go`. MIT license; last commit on master 20 November 2020.

[41] Olaoluwa Osuntokun and Alex Akselrod. BIP 158: Compact block filters for light clients. Bitcoin Improvement Proposal, 2017.

[42] Olaoluwa Osuntokun, Alex Akselrod, and Jim Posen. BIP 157: Client side block filtering. Bitcoin Improvement Proposal, 2017.

[43] Marek Palatinus, Pavol Rusnak, Aaron Voisine, and Sean Bowe. BIP 39: Mnemonic code for generating deterministic keys. Bitcoin Improvement Proposal, 2013.

[44] Particl contributors. Particl marketplace. `https://particl.io`, source at `https://github.com/particl`.

[45] Ania M. Piotrowska, Jamie Hayes, Tariq Elahi, Sebastian Meiser, and George Danezis. The Loopix anonymity system. In *Proceedings of the 26th USENIX Security Symposium*, pages 1199–1216, 2017.

[46] Joseph Poon and Thaddeus Dryja. The Bitcoin Lightning network: Scalable off-chain instant payments. `https://lightning.network/lightning-network-paper.pdf`, 2016.

[47] Rusty Russell. BOLT #11: Invoice protocol for lightning payments. Lightning Network specifications, `https://github.com/lightning/bolts`, 2017.

[48] Rusty Russell. BOLT #12: Negotiation protocol for lightning payments. Lightning Network specifications, `https://github.com/lightning/bolts`, 2024.

[49] Nils Schneider and Matt Corallo. BIP 21: URI scheme. Bitcoin Improvement Proposal, 2012.

[50] Omer Shlomovits and Oded Leiba. JugglingSwap: Scriptless atomic cross-chain swaps. arXiv:2007.14423, 2020.

[51] Kyle Soska and Nicolas Christin. Measuring the longitudinal evolution of the online anonymous marketplace ecosystem. In *Proceedings of the 24th USENIX Security Symposium*, pages 33–48, 2015.

[52] Markus Stadler. Publicly verifiable secret sharing. In *Advances in Cryptology – EUROCRYPT '96*, volume 1070 of *LNCS*, pages 190–199. Springer, 1996.

[53] The Tor Project. Tor rendezvous specification – version 3. `https://spec.torproject.org/rend-spec/`. Accessed November 2026.

[54] Martin Thomson and Christopher A. Wood. Oblivious HTTP. RFC 9458, 2024.

[55] Pieter Wuille. BIP 32: Hierarchical deterministic wallets. Bitcoin Improvement Proposal, 2012.

[56] Pieter Wuille, Jonas Nick, and Tim Ruffing. BIP 340: Schnorr signatures for secp256k1. Bitcoin Improvement Proposal, 2020.

[57] Pieter Wuille, Jonas Nick, and Anthony Towns. BIP 341: Taproot: SegWit version 1 spending rules. Bitcoin Improvement Proposal, 2020.

[58] Gloria Zhao. BIP 431: Topology restrictions for pinning. Bitcoin Improvement Proposal, 2024.

A Wire Formats

All integers are little-endian. `str` is a 2-byte length followed by UTF-8 bytes. Every format begins with a 4-byte magic and a 1-byte version, and decoders reject unknown versions and trailing bytes.

Magic	Record	Fields after magic and version
`OBST` v2	Store	name (str), region (str), BOLT 12 offer (str), BIP 352 code (str), store key (32 bytes), store rating (u8: 0 general, 1 sensitive, 2 adult), then a 64-byte BIP 340 signature over the preceding bytes with tag `ob/store/v1`. Version 1 omits the rating. The mailbox key and onion address of §7 are added at the end in a later version.
`OBLS` v5	Listing	store key (32), title (str), category (str), price (u64), ship-from (str), description (str), seller (str), stock (u32), listed-on date (u32), moderated (u8), kind (u8), product (str), shipping (u64), free-over (u64), rating (u8), tags (u16 bit set), then a signature with tag `ob/listing/v1`. Address: SHA-256 of everything before the signature. Version 4 omits the rating and tags.
`OBLS` v7	Listing	Version 6 adds the listing id (16), image hashes (at most 8), and an optional fiat price (currency code, amount, shipping in minor units). Version 7 adds the commerce block of §9 (condition, category, specifics, option axes and variants, sale, tiers, limits, availability, package, services, pickup area, returns) to a fiat-priced listing.
`OBCP` v1	Coupon	Store key (32), code (str), percentage or fixed amount, currency (str), minimum subtotal, listing ids, first and last days, maximum uses; signature by the store key. Kept by the seller's node; not published.
`OBRC` v1	Receipt	Store key (32), listing id (16), review key (32), payment date (u32, `YYYYMMDD`; nodes write the first of the month); signature by the store key.
`OBRV` v1	Review	A signed receipt, stars (u8, 1–5), text (str, at most 1,000 bytes), written-on day (u32, not before the receipt's date); signature by the receipt's review key.
`OBRY` v1	Reply	Store key (32), review hash (32), text (str, 1 to 1,000 bytes), written-on day (u32); signature by the store key.
`OBLB` v1	Label set	labeler key (32), name (str, at most 64 bytes), sequence (u64), issued-on date (u32), entry count (u16, at most 4,096), then entries sorted by target with no repeats: target kind (u8: 0 listing, 1 store), target (32), flags (u8; bit 0 retracts, others zero), rating (u8), tags (u16), reason (str, `[a-z0-9-]`, at most 32 bytes). A retraction has rating 0, tags 0, and no reason. Signature with tag `ob/labels/v1`; address: SHA-256 of the body.
`OBOD` v1	Order plaintext	listing address (32), quantity (u32), option count (u16) and name/value pairs (str, str), ship-to (str), rail (u8), reply key (32). Version 3 appends the terms: up to 20 lines (listing address, variant id, quantity, optional store-signed offer), a service index (`0xff` for pickup or digital delivery), a coupon code, and a review key (32).
`OBSL` v2	Sealed letter	HPKE encapsulated key (32), ciphertext length (u32), ciphertext. The sealed letter is exactly 2 KiB, 8 KiB, or 64 KiB. Inside, `OBLT` version 1 carries the kind, the per-conversation sender key, a message id, the body, a BIP 340 signature with tag `ob/letter/v1`, and zero padding. Orders, later sale messages, and escrow use different HPKE `info` strings.
`OBSR` v2	Sealed reply	As `OBSL`, sealed to the order's reply key, in the 2 KiB or 8 KiB bucket.
`OBML` v1	Onion frame	Letter length (u32), then one `OBSL` letter.
`OBET` v2	Escrow terms	The keys, moderator record (keys, payout, fee, policy), amounts, heights, and payout scripts of §11.1.
`OBEM` v1	Escrow mail	Message kind (u8), escrow id (16), field count (u8), then fields as u32 length and bytes; sealed as an `OBSL` letter between nodes.
`OBDL` v3	Dispute letter	The fields of the dispute letter in §11, then the claimant's signature.
`OBRU` v2	Ruling	Terms digest (32), output key (32), funding outpoint, favored party (u8), adaptor point (33), moderator share (32), signature (64) by the moderator's signing key over all preceding fields.