

---

# Command Reference: ReadResponseFromStateMod()

Read response file data from a StateMod response file

## StateMod Command

Version 3.12.00, 2011-01-17

The `ReadResponseFromStateMod()` command reads a StateMod response file, which contains the list of files in a data set. The primary purpose of this command currently is to facilitate software testing of reading and writing the response file; however, in the future the functionality may be enhanced. The response file can be written using the `WriteResponseToStateMod()` command.

The following dialog is used to edit the command and illustrates the syntax of the command.

**Edit ReadResponseFromStateMod() Command**

This command reads a StateMod response file, which contains a list of files in the data set.  
**The command is used to test reading/writing the response file - do not use in full production.**  
It is recommended that the location of the file be specified using a path relative to the working directory.  
The working directory is: C:\Develop\StateDMI\_SourceBuild\StateDMI\test\regression\commands\ReadResponseFromStateMod

StateMod file:

Read data?: ☐ Optional - read data in files (default=False)

Command:  

```
ReadResponseFromStateMod ( InputFile="Sp2008L.rsp" )
```

ReadResponseFromStateMod

### ReadResponseFromStateMod() Command Editor

The command syntax is as follows:

```
ReadResponseFromStateMod (Parameter=Value, ...)
```

#### Command Parameters

Parameter	Description	Default
InputFile	The name of the StateMod response file to read.	None – must be specified.