

# Command Reference: FillFromTS()

## Fill missing time series data using data from another time series (or ensemble)

Version 11.03.10, 2015-06-29

The `FillFromTS()` command fills missing data in a time series (or ensemble) by transferring non-missing values from another time series (or ensemble). This is useful when two time series typically have very similar values. The filled time series is not automatically extended. A period can be specified to limit the period that is checked for missing data. See also the `SetFromTS()` command, which will transfer all values. If multiple time series or an ensemble is being processed, the number of independent time series must be one or the same number as the time series being filled. Data transfer occurs by date/time, not sequentially. This may be a problem if trying to fill from a time series that has been shifted and leap years have caused an offset – an enhancement may be made in the future to address this issue. The following dialog is used to edit the command and illustrates the command syntax.

**Edit FillFromTS() Command**

Copy data values from the independent time series to replace missing values in the dependent time series. Only data in the fill period will be checked.  
If one independent time series is specified, it will be used for all dependent time series.  
If multiple independent time series are specified (e.g., for ensembles), the same number of dependent time series must be specified.  
Use a `SetOutputPeriod()` command if the dependent time series period will be extended.  
Specify fill start and end dates with precision appropriate for the data.

Dependent TS List:  Optional - indicates the time series to process (default=AllTS).  
TSID (for TSList=\*MatchingTSID):   
EnsembleID (for TSList=EnsembleID):   
Independent TS List:  Optional - indicates the time series to process (default=AllTS).  
Independent TSID (for Independent TSList=\*MatchingTSID):   
Independent EnsembleID (for Independent TSList=EnsembleID):   
Fill start date/time:  Optional - start of period to fill (default=fill all).  
Fill end date/time:  Optional - end of period to fill (default=fill all).  
Fill flag:  Optional - string to indicate filled values (default=no flag).  
Fill flag description:  Optional - description for fill flag.  
Recalculate limits:  Optional - recalculate original data limits after fill (default=False).  
Command: 

```
FillFromTS (TSList=AllMatchingTSID, TSID="08241000.DWR.Streamflow.Month", IndependentTSList=AllMatchingTSID, IndependentTSID="08240500.DWR.Streamflow.Month")
```

FillFromTS

### FillFromTS() Command Editor

The command syntax is as follows:

`FillFromTS (Parameter=Value, ...)`

### Command Parameters

Parameter	Description	Default
TSList	Indicates the list of time series to be processed, one of: <ul style="list-style-type: none"><li>AllMatchingTSID – all time series that match the TSID (single TSID or TSID with wildcards) will be modified.</li></ul>	AllTS

Parameter	Description	Default
	<ul style="list-style-type: none"> <li>AllTS – all time series before the command.</li> <li>EnsembleID – all time series in the ensemble will be modified.</li> <li>FirstMatchingTSID – the first time series that matches the TSID (single TSID or TSID with wildcards) will be modified.</li> <li>LastMatchingTSID – the last time series that matches the TSID (single TSID or TSID with wildcards) will be modified.</li> <li>SelectedTS – the time series are those selected with the SelectTimeSeries() command.</li> </ul>	
TSID	The time series identifier or alias for the time series to be modified, using the * wildcard character to match multiple time series. Can be specified with processor \${Property}.	Required when a TSList=*TSID
EnsembleID	The ensemble to be modified, if processing an ensemble. Can be specified with processor \${Property}.	Required when TSList=EnsembleID.
Independent TSList	Indicates how to determine the list of independent time series (see the explanation of TSList).	AllTS
Independent TSID	The time series identifier or alias for the independent time series (see the explanation of TSID). Can be specified with processor \${Property}.	Required when a IndependentTSList=*TSID
Independent EnsembleID	The ensemble identifier for the independent time series (see the explanation of EnsembleID). Can be specified with processor \${Property}.	Required when IndependentTSList=EnsembleID.
FillStart	The date/time to start filling. Can be specified with processor \${Property}.	Fill the entire period.
FillEnd	The date/time to end filling. Can be specified with processor \${Property}.	Fill the entire period.
FillFlag	If specified, data flags will be enabled for the time series and each filled value will be tagged with the specified string. The flag can then be used later to label graphs, etc. Prefix with + to append the flag. Can be specified with processor \${Property}.	No flag is assigned.
FillFlagDesc	Description for the fill flag, used in reports. Can be specified with processor \${Property}.	Automatically generated.
Recalc Limits	Available only for monthly time series. Indicate whether the original data limits for the time series should be recalculated after the filling the time series. Setting to True is appropriate if the independent time series provides additional data values.	False (only the values in the initial time series will be used for historical data).