

Command Reference: ReadPropertiesFromExcel()

Read cells from a Microsoft Excel workbook file and set processor properties

Version 11.02.00, 2015-05-06

The `ReadPropertiesFromExcel()` command reads cells from a Microsoft Excel worksheet and sets processor properties. This is useful when Excel is used to configure an analysis. The properties can be used directly by TSTool for commands that support `${Property}` notation or can be used to expand a template command file. Property object types are determined from Excel cell type/format unless the type is specified with command parameters. If issues arise, check the Excel cell type and format.

TSTool uses the Apache POI software (<http://poi.apache.org>) to read/write the Excel file and consequently functionality is constrained by the features of that software package. Check the TSTool **Help... About** menu for information on the POI version.

The following dialog is used to edit the command and illustrates the syntax for the command.

Excel | Excel <-> Properties | Properties

This command reads cells from a Microsoft Excel worksheet and sets processor properties.
Currently only a list of specific cells are read. In the future a block of properties may be read.
The cell locations in Excel can be specified using a named range, or A1-style address.
It is recommended that the location of the Excel file be specified using a path relative to the working directory.
The working directory is: C:\owf-gitrepos\cdss-app-tstool-test\test\regression\commands\general\ReadPropertiesFromExcel

Input (Excel workbook) file: Data\CO-SWSI-Control.xlsx Browse

Worksheet: Config Optional - worksheet name (default=first sheet).

Keep file open?: Optional - keep Excel file open? (default=False).

Command: `roperty:*,TextFalseAsBooleanFalseProperty:*,Text1AsBooleanTrueProperty:*,Text0AsBooleanFalseProperty:*,TextAsDateTimeProperty:*,CurrentMonthDateText:*,NRCSForecastPublicationDateText:*,BooleanProperties="NumberAsBooleanTrueProperty,NumberAsBooleanFalseProperty,TextYesAsBooleanTrueProperty,TextNoAsBooleanFalseProperty,TextTrueAsBooleanTrueProperty,TextFalseAsBooleanFalseProperty,Text1AsBooleanTrueProperty,Text0AsBooleanFalseProperty",DateTimeProperties="TextAsDateTimeProperty",IntegerProperties="IntegerProperty")`

Add Working Directory To File Cancel OK

ReadPropertiesFromExcel

ReadPropertiesFromExcel() Command Editor for Excel Parameters

Excel | Excel <-> Properties | Properties

The column cell map is Property:Excel in order to match the similar parameter in the WritePropertiesToExcel() command (future enhancement).


Property to cell address map: `rProperty:*,NumberAsBooleanTrueProperty:*,NumberAsBooleanFalseProperty:*,TextYesAsBooleanTrueProperty:*,TextNoAsBooleanFalseProperty:*,TextTrueAsBooleanTrueProperty:*,TextFalseAsBooleanFalseProperty:*,Text1AsBooleanTrueProperty:*,Text0AsBooleanFalseProperty:*,TextAsDateTimeProperty:*,CurrentMonthDateText:*,NRCSForecastPublicationDateText:*`

Edit

Required - indicate property to cell address mapping (default=none).

ReadPropertiesFromExcel_Map

ReadPropertiesFromExcel() Command Editor for Excel to Properties Map Parameter



ReadPropertiesFromExcel() Command Editor for Properties Parameters

The command syntax is as follows:

ReadPropertiesFromExcel (Parameter=Value,...)

Command Parameters

Parameter	Description	Default
InputFile	The name of the Excel workbook file (*.xls or *.xlsx) to read, as an absolute path or relative to the command file location.	None – must be specified.
Worksheet	The name of the worksheet in the workbook to read.	Read the first worksheet.
KeepOpen	Indicate whether to keep the Excel file open (True) or close after creating (False). Keeping the file open can increase performance because later commands will not need to reread the workbook.	False
PropertyCellMap	Indicate how to map property names to Excel addresses. The format of the parameter is: <code>PropertyName1:ExcelAddress1, PropertyName2:ExcelAddress2, ...</code> where the Excel addresses can be specified using A1 notation, named range, or * to use a named range that matches the property name. The property names cannot be repeated.	None – must be specified.
BooleanProperties	A list of property names to be defined as Boolean objects.	Determine from Excel cell type and format.
DateTimeProperties	A list of property names to be defined as date/time objects.	Determine from Excel cell type and format.
IntegerProperties	A list of property names to be defined as integer objects.	Determine from Excel cell type and format.