
Command Reference: SetProperty()

Set a property for the time series processor

Version 11.02.00, 2015-04-23

The `SetProperty()` command sets the value of a property used by the time series processor. The property will be available to subsequent commands that support using `${Property}` notation in parameters, for example to specify filenames more dynamically or use with `If()` commands. This command should not be confused with the `SetTimeSeriesProperty()` command, which sets a property on specific time series.

The following dialog is used to edit this command and illustrates the syntax of the command.

Edit SetProperty() Command

Set a property for the processor. The property can be referenced in parameters of some commands using `${Property}` notation. Specify date/times using standard notations to appropriate precision (e.g., YYYY-MM-DD hh:mm:ss). Special values also are recognized for date/times (for all precisions):

- CurrentToYear = the current date to year precision
- CurrentToMinute = the current date/time to minute precision
- CurrentToMinute - 7Day = current date/time minus 7 days
- CurrentToMinute + 7Day = current date/time plus 7 days

Property name: Required - do not use spaces \$, { or } in name.

Property type: Required - to ensure proper initialization and checks.

Property value: Required - property value, can use `${Property}`.

Command:

SetProperty

SetProperty() Command Editor

The command syntax is as follows:

```
SetProperty(Parameter=Value,...)
```

Command Parameters

Parameter	Description	Default
PropertyName	The property name.	None – must be specified.
PropertyType	The property type, used for validation, one of: <ul style="list-style-type: none">• Boolean – a boolean• DateTime – a date/time• Double – a floating point number• Integer – an integer• String – a string	None – must be specified.
PropertyValue	The value of the property, adhering to property type constraints. Date/time properties should be specified using standard formats such as “YYYY-MM-DD hh:mm:ss”, to an appropriate precision. Special date/time syntax is recognized, as shown in the above figure. Global properties can be used with the \${Property} syntax.	None – must be specified.

A sample commands file is as follows:

```
SetProperty(PropertyName="Scenario",PropertyType=String,PropertyValue="Likely")
```