
Command Reference: CheckTimeSeriesStatistic()

Check time series statistic against criteria

Version 10.00.01, 2011-04-26

The `CheckTimeSeriesStatistic()` command checks a time series statistic against criteria, for example to perform quality control using full-period statistics. This command is essentially a combination of the `CalculateTimeSeriesStatistic()` command with features similar to the `CheckTimeSeries()` command; however, the latter checks individual data values and this command checks a statistic computed from the entire time series. The `WriteCheckFile()` command can be used to write a summary of the warnings.

The following dialog is used to edit the command and illustrates the command syntax.

Edit CheckTimeSeriesStatistic() Command

Check time series statistic for critical values (see also the CheckTimeSeries() command, which checks data values).
A warning will be generated if the statistic matches the specified condition(s).
Use the WriteCheckFile() command to save the results of all checks.
Specify dates with precision appropriate for the data, use blank for all available data, OutputStart, or OutputEnd.

Time series to process

TS list: Optional - indicates the time series to process (default=AllTS).

TSID (for TSList=AllMatchingTSID):

EnsembleID (for TSList=EnsembleID):

Statistic

Statistic to calculate: Required - may require other parameters.

Statistic value1: Optional - may be needed as input to calculate statistic.

Statistic value2: Optional - may be needed as input to calculate statistic.

Statistic value3: Optional - may be needed as input to calculate statistic.

Analysis start: Optional - analysis start date/time (default=full time series period).

Analysis end: Optional - analysis end date/time (default=full time series period).

Table ID for output: Optional - if statistic should be saved in table.

Table TSID column: Required if using table - column name for TSID.

Format of TSID: Insert: Optional - use %L for location, etc. (default=alias or TSID).

Table statistic column: Required if using table - column name for statistic.

Check and actions

Check criteria: Required - may require other parameters.

Check value1: Optional - minimum (or only) statistic value to check.

Check value2: Optional - maximum value in range, or other statistic value to check.

Problem type: Optional - problem type to use in output (default=Statistic-CheckCriteria).

If criteria met?: Optional - should warning/failure be generated (default=Warn).

Property name: Optional - name of property to set when criteria are met.

Property value: Optional - value of property to set when criteria are met.

Command:

```
CheckTimeSeriesStatistic(TSList=AllMatchingTSID,TSID="516122-precip-year-level3",Statistic="Count",TableID="InclusionChecks",TableTSIDColumn="Alias",TableTSIDFormat="%A",TableStatisticColumn="Count",CheckCriteria="<",CheckValue1=15,IfCriteriaMet=Ignore,PropertyName="PeriodLevel3",PropertyValue="No")
```

CheckTimeSeriesStatistic

CheckTimeSeriesStatistic() Command Editor

The command syntax is as follows:

```
CheckTimeSeriesStatistic(Parameter=Value,...)
```

Command Parameters

Parameter	Description	Default
TSList	Indicates the list of time series to be processed, one of: <ul style="list-style-type: none"> AllMatchingTSID – all time series that match the TSID (single TSID or TSID with wildcards) will be processed. AllTS – all time series before the command will be processed. EnsembleID – all time series in the ensemble will be processed. FirstMatchingTSID – the first time series that matches the TSID (single TSID or TSID with wildcards) will be processed. LastMatchingTSID – the last time series that matches the TSID (single TSID or TSID with wildcards) will be processed. SelectedTS – the time series selected with the SelectTimeSeries() command will be processed. 	AllTS
TSID	The time series identifier or alias for the time series to be processed, using the * wildcard character to match multiple time series.	Required if TSList=*TSID.
EnsembleID	The ensemble to be modified, if processing an ensemble.	Required if TSList=EnsembleID.
Statistic	Statistic to compute. Refer to the CalculateTimeSeriesStatistic() command documentation.	None – must be specified.
StatisticValue1	Input data required by the statistic. Currently the dialog does not check the value for correctness – it is checked when the statistic is computed.	See the CalculateTimeSeriesStatistic() command documentation.
StatisticValue2	Input data required by the statistic. Currently the dialog does not check the value for correctness – it is checked when the statistic is computed.	to the CalculateTimeSeriesStatistic() command documentation.
StatisticValue3	Input data required by the statistic. Currently the dialog does not check the value for correctness – it is checked when the statistic is computed.	to the CalculateTimeSeriesStatistic() command documentation.
AnalysisStart	The date/time to start analyzing data.	Full period is analyzed.
AnalysisEnd	The date/time to end analyzing data.	Full period is analyzed.
TableID	Identifier for table that receives the statistic.	Optional – table output is not

Parameter	Description	Default
		required.
TableTSIDColumn	Table column name that is used to look up the time series. If a matching TSID is not found, a row will be added to the table. If a TSID is found, the statistic cell value for the time series is modified.	Optional – table output is not required.
TableTSIDFormat	The specification to format the time series identifier to insert into the TSID column. Use the format choices and other characters to define a unique identifier.	Time series alias if available, or the time series identifier.
TableStatisticColumn	Table column name to receive the statistic value. If not found in the table, a new column is added automatically.	Optional – table output is not required.
CheckCriteria	The criteria that is checked, one of: <ul style="list-style-type: none"> • InRange – check for value \geq Value1 and \leq Value2. • OutOfRange – check for value $<$ Value1 or $>$ Value2. • $<$ – check for values $<$ CheckValue1. • \leq – check for values \leq CheckValue1. • $>$ – check for values $>$ CheckValue1. • \geq – check for values \geq CheckValue1. • $==$ – check for values equal to CheckValue1. 	None – must be specified.
CheckValue1	A parameter that is used for specific CheckCriteria values.	
CheckValue2	A parameter that is used for specific CheckCriteria values, currently only needed for InRange and OutOfRange criteria.	
ProblemType	The problem type that will be shown in warning messages.	Statistic-CheckCriteria
IfCriteriaMet	Indicate whether to set the command status if the statistic meets the criteria, one of: <ul style="list-style-type: none"> • Ignore – do not set the command status • Warn – set the command status to Warning • Fail – set the command status to Failure 	The command status will not be changed.
PropertyName	If the statistic meets the criteria, set the property identified by PropertyName to PropertyValue.	No property is set.
PropertyValue	If the statistic meets the criteria, set the property identified by PropertyName to PropertyValue.	No property is set.