
Command Reference: SetProperty()

Set a property for the time series processor

Version 08.15.00, 2008-05-11

This is an experimental command that is being evaluated for advanced processing.

The `SetProperty()` command sets the value of a property used by the time series processor. These properties will ultimately be accessible by any command using `${Property}` notation, for example to specify filenames more dynamically. At this time, only a few commands utilize the properties. This command should not be confused with the `SetTimeSeriesProperty()` command, which operates on specific time series.

The following dialog is used to edit this command and illustrates the syntax of the command.

Edit SetProperty() Command

Set a property for the processor. The property can be referenced in parameters using `${Property}` notation.

Property name: Do not use spaces \$, { or } in name.

Property type:

Property value:

Command:

```
SetProperty(PropertyName="Scenario",PropertyType=String,PropertyValue="Likely")
```

SetProperty

SetProperty() Command Editor

The command syntax is as follows:

```
SetProperty (Parameter=Value,...)
```

Command Parameters

Parameter	Description	Default
PropertyName	The property name.	None – must be specified.
PropertyType	The property type, used for validation, one of: <ul style="list-style-type: none">• DateTime – a date/time.• Double – a floating point number• Integer – an integer• String – a string	None – must be specified.
PropertyValue	The value of the property, adhering to property type constraints.	

A sample commands file is as follows:

```
SetProperty(PropertyName="Scenario",PropertyType=String,PropertyValue="Likely")
```