Command Reference: ReadPatternFile()


Read the pattern file to be used with FillPattern() commands

/ersion 08.16.04, 2008-09-19

The ReadPatternFile() command reads pattern time series to be used with FillPattern() commands (see the FillPattern() command for more information). The patterns indicate whether a month is wet, dry, or average, although any number of characterizations can be used. One or more patterns can be included in each pattern file, similar to StateMod time series files (see the **StateMod Input Type** appendix), and multiple pattern files can be used, if appropriate. The following example illustrates the file format. See also the AnalyzePattern() command, which can be used to generate the file.

```
Years Shown = Water Years
Missing monthly data filled by
Time series identifier = 09034500.CRDSS_USGS.QME.MONTH.1
Description = COLORADO RIVER AT HOT SULPHUR SPR
                                                   = 09034500.CRDSS_USGS.QME.MONTH.1
= COLORADO RIVER AT HOT SULPHUR SPRINGS, CO.
                              ---eb-
               -----eb--
                                            ---eb-----eb-----eb----eb---
                            9/1996 ACFT WYR
AVG AVG
WET WET
    10/1908
1909 09034500
1910 09034500
                                                                                             AVG
WET
                                                                                                         AVG
                                                         WET
                                                                     WET
                                                                                                                      AVG
                                                                                                                                  AVG
                                                                                                                                              AVG
                                                                                                                                                                      AVG
                                                                                 WET
                                                                                                                                                          AVG
1911 09034500
                                 AVG
                                             AVG
                                                         WET
                                                                     AVG
                                                                                 AVG
                                                                                             AVG
                                                                                                         AVG
                                                                                                                      WET
                                                                                                                                                          AVG
                                                                                                                                                                      WET
1912 09034500
 ..ommitted...
```

The following dialog is used to edit the command and illustrates the command syntax.



ReadPatternFile() Command Editor

ReadPatternFile

The command syntax is as follows:

ReadPatternFile(Parameter=Value,...)

Command Parameters

Parameter	Description	Default
PatternFile	The path to the pattern file, which can be absolute or relative to the working directory.	None – must be specified.

A sample command file is as follows:

```
ReadPatternFile(PatternFile="fill.pat")
```

ReadPatternFile() Command		TSTool Documentation
	This page is intentionally blank.	