
Command Reference:

NewDayTSFromMonthAndDayTS()

Create a new daily time series from monthly total and daily pattern

Version 10.00.00, 2011-03-27

The `NewDayTSFromMonthAndDayTS()` command creates a new daily time series by distributing a monthly time series “volume” according to the pattern of the independent daily time series. This command currently only handles processing monthly ACFT and daily CFS time series. This command is useful where a monthly flow time series is known at a location, and a daily pattern is known at a related gage. The new time series is assigned the given identifier and alias. The following calculations are performed:

$$DayTS2_i = MonthTS2 \frac{ACFT}{NDAYS} * \left(\frac{1DAY}{86400s} \right) \left(\frac{43560FT^2}{1AC} \right) * \left(\frac{DayTS1_i}{\sum_{i=1}^{i=Nday \sin Month} DayTS1_i} \right)$$

where, for days in a month:

$DayTS2_i$ = the daily value being estimated in daily time series 2

$MonthTS2$ = the monthly value being used for volumes for time series 2, shown in units of ACFT/NDAYS (equivalent to ACFT/Month)

$NDAYS$ = the number of days in the month

$DayTS1_i$ = the daily value for indicator daily time series 1

$\sum DayTS1_i$ = the sum of the daily values for indicator time series for the a month

In summary, the monthly volume in ACFT/NDAYS is first converted to an average monthly CFS rate by multiplying by 43560/86400 (or 1/1.9835), and finally the average CFS value is prorated by the ratio of the indicator daily time series daily value divided by the total daily flows for the month, to give a daily CFS value for each day of the month. In this case, the last term is simply a ratio (converting daily average CFS to daily ACFT and calculating the ratio would result in the same value).

Days with missing data are excluded from the summation and the estimated values. The output period is the global output period from `SetOutputPeriod()`, or if not set the period from the daily time series is used.

For example, consider May a may total for MonthTS2 = 1001.7 ACFT and daily values (CFS) as follows:

Day 1 = 14

14

13

13

14

14

15

15

15

16

17

17

16

18

18

17

18

18

18

18

17

17

17

17

16

16

17

18

18

17

Day 31 = 17

The total is 505 CFS. The estimated value for day 1 of the second daily time series would then be:

$$1001.7 * (1/1.9835) * (14/505) = 14 \text{ CFS}$$

In this case, the indicator time series was the same as the time series being estimated and therefore the estimated value should be the same as the indicator.

The following dialog is used to edit the command and illustrates the syntax for the command.

Edit NewDayTSFromMonthAndDayTS() Command

Create a daily time series by distributing a monthly total using a daily pattern.
Currently this command is only implemented to convert from acre-feet to CFS.
The period is taken from the global output period if set, or the daily time series.

Monthly time series for total: 08236000.DWR.Streamflow.Month

Daily time series for distribution: 08236500.DWR.Streamflow.Day

New time series ID: 08236000.DWR.Streamflow.Day Specify to avoid confusion with TSID from original TS.

Alias to assign: DayTS Insert: -- Select Specifier -- Required - use %L for location, etc.

Command: NewDayTSFromMonthAndDayTS (Alias="DayTS",NewTSID="08236000.DWR.Streamflow.Day",MonthTSID="08236000.DWR.Streamflow.Month",DayTSID="08236500.DWR.Streamflow.Day")

Cancel OK

NewDayTSFromMonthAndDayTS() Command Editor

The command syntax is as follows:

```
NewDayTSFromMonthAndDayTS (Parameter=Value,...)
```

The following older command syntax is updated to the above syntax when a command file is read:

```
TS Alias = NewDayTSFromMonthAndDayTS (Parameter=Value,...)
```


Command Parameters

Parameter	Description	Default
MonthTSID	The time series identifier or alias for a monthly time series supplying monthly ACFT values.	None – must be specified.
DayTSID	The time series identifier or alias for a daily time series supplying daily flow values (only the pattern is used).	None – must be specified.
NewTSID	The time series identifier of the new time series. The interval must be Day.	None – must be specified.
Alias	The alias to assign to the time series, as a literal string or using the special formatting characters listed by the command editor. The alias is a short identifier used by other commands to locate time series for processing, as an alternative to the time series identifier (TSID).	None – must be specified.

A sample command file to process data from the State of Colorado's HydroBase is as follows:

```
SetOutputPeriod(OutputStart="1950-01",OutputEnd="2002-12")
# 08236500 - ALAMOSA RIVER BELOW TERRACE RESERVOIR
08236500.DWR.Streamflow.Day~HydroBase
# 08236000 - ALAMOSA RIVER ABOVE TERRACE RESERVOIR
08236000.DWR.Streamflow.Month~HydroBase
NewDayTSFromMonthAndDayTS(Alias="DayTS",
    NewTSID="08236000.DWR.Streamflow.Day",
    MonthTSID="08236000.DWR.Streamflow.Month",
    DayTSID="08236500.DWR.Streamflow.Day")
```

A graph of data resulting from this command may look similar to the following. Note that the each time series has a similar pattern, but at different levels.



NewDayTSFromMonthAndDayTS_Graph

Result of NewDayTSFromMonthAndDayTS() Command