
Command Reference: WriteReclamationHDB()

Write time series to a Reclamation HDB database

Version 10.24.00, 2013-09-27

The `WriteReclamationHDB()` command writes time series to a Reclamation HDB database:

- a single time series (which can be part of an ensemble), indicated by the individual time series identifier:
 - a “real” time series (observations)
 - a “model” time series (output from a model)
- all time series in an ensemble, indicated by the ensemble identifier:
 - ensemble trace time series are stored as “model” time series, with additional ensemble metadata

See the `ReadReclamationHDB()` command documentation for information about reading the time series that are written by this command. See the **Reclamation HDB Data Store Appendix** for more information about the database features and limitations. Command functionality includes:

- **Time series metadata/new time series:**
 - In general, the command will not define a new time series (site and model data). It is expected that time series previously have been defined in the database. This ensures that TSTool can perform error handling and users do not accidentally load new time series.
 - The exceptions are:
 - New ensembles and corresponding trace time series can be defined by specifying ensemble name, trace number, and model run date using the `NewEnsembleName` and `NewEnsembleModelRunDate` command parameters.
 - New (non-ensemble) time series corresponding to a new run date can be defined by specifying the model run date using the `NewModelRunDate` command parameter.
- **Date/time handling:**
 - TSTool uniformly uses the time at the end of the recorded interval for data values (instantaneous time or end of interval for mean and accumulated values), whereas HDB uses the time at the beginning of the recorded interval for hourly data. See the **ReclamationHDB Datastore** appendix for more information.
 - Writing NNour data uses `WRITE_TO_HDB` procedure where the `SAMPLE_END_DATETIME` is set to the TSTool date/time and `SAMPLE_DATE_TIME` is set the TSTool date/time minus NHour.
 - Writing other than NHour data uses the `WRITE_TO_HDB` procedure with `SAMPLE_DATE_TIME` passed as the same value as the TSTool date/time.
- **Updating time series records:**
 - Time series data records for an existing time series will be updated if previously written.
- **Missing data:**
 - Missing data currently are not written. By convention missing values in HDB are simply not included in the database. Currently the command will not delete previous records if the new value at a date/time is missing. It would be useful to have the ability to clear the time series values in the write period before inserting the new values. This would ensure that the data are current.

- **Data units:**
 - Data units in the time series are not checked against data units in the database because the units in TSTool data may originally have come from various sources that do not use the same units abbreviations as HDB. It is the user's responsibility to ensure that time series that are being written have units that are compatible with HDB.
- **Data flags:**
 - Data flags from the time series are not written to the database. The `ValidationFlag`, `OverwriteFlag`, and `DataFlags` parameters are provided to specify HDB flags. Additional capability may be added in the future.
- **Time zone:**
 - Time zone can be indicated in TSTool time series by including in the start and end date/time information; however, time zones are difficult to standardize when data comes from different sources. The default time zone for HDB is configured for the Reclamation office that uses the database. If the time series time zone is different from the default (displayed in the note for the `TimeZone` command parameter in the command editor), it can be specified as a command parameter. It is the user's responsibility to verify that the correct time zone is being provided to the `WriteReclamationHDB` command.
- **HDB data table:**
 - The time series interval is used to determine the HDB time series table to write, with irregular data being written as instantaneous data with date/time precision to minute.
 - TSTool treats year-interval data generically and does not manage water year (or other types of years) in special fashion, other than when processing data into year interval time series. Water year data can be saved in year interval data but currently there is no way to write to the water-year tables in HDB.
- **HDB database procedure:**
 - The HDB `WRITE_TO_HDB` stored procedure is used to write individual time series data records:
 - The time series is written to a model time series table if model parameters are specified.
 - The model run date, for single time series and ensembles, is truncated to minutes in time series identifiers and for query purposes.
 - When writing ensembles, the HDB procedure `ENSEMBLE.GET_TSTOOL_ENSEMBLE_MRI` is used to determine the model run identifier corresponding to model time series and then the `WRITE_TO_HDB` procedure (above) is used to write data records:
 - The ensemble name is determined from the `EnsembleName` parameter (or `NewEnsembleName` parameter if creating a new ensemble) – existing names can be selected or a new name can be specified
 - The trace number is determined from the `EnsembleTrace` command parameter, and will result in the trace being taken from specific time series properties. Currently this must be an integer but in the future string trace identifiers may be supported (TSTool uses string identifiers internally).
 - The model name is determined from the `EnsembleModelName` parameter. Model names consistent with non-ensemble model time series are used.
 - The model run date is determined from the `EnsembleModelRunDate` parameter (or `NewEnsembleModelRunDate` parameter if writing data for a new run date). If specified then the `P_IS_RUNDATE_KEY` procedure parameter is set to Y, if not specified it is set to N). Consequently, ensemble time series can be written with or without a model run date.

The following dialog is used to edit the command and illustrates the syntax of the command when writing “real” data, in which case model information in the lower panel are not specified. Currently the `site_name` and `site_common_name` are not required to be unique in HDB and therefore specifying the unique `site_datatype_id` (SDI) is the only way to ensure that the proper time series is being selected (unique constraints for the names may be added to the database in the future).

Edit WriteReclamationHDB() Command

Write a single “real” or model time series, or write an ensemble of model time series to a Reclamation HDB database. The HDB time series table is determined from the data interval, with irregular data being written to the instantaneous data table.

Datastore: Required - datastore for HDB database.

TS list: Optional - indicates the time series to process (default=AllTS).

TSID (for TSList=AllMatchingTSID):

EnsembleID (for TSList=EnsembleID):

Specify how to match the HDB site_datatype_id (required for all time series and ensembles) AND provide general command parameters

Select site_datatype_id (SDI) OBSOLETE - select SDI using site common name General parameters

The choices below include: “site_datatype_id - site common name - site name - datatype name”, sorted by site name.

Site data type ID: Required.

Specify how to match the HDB model_run_id (leave blank if not writing single or ensemble model time series data)

Single model time series Ensemble of model time series

Use these parameters to write an ensemble of model time series to an existing or new HDB ensemble. The model name must exist but a new run date can be specified. The trace number for each time series in the ensemble will be determined from ensemble traces at run time.

Ensemble name: Required - used to determine the ensemble model_run_id.

Selected ensemble_id: Information - useful when comparing to database contents.

OR new ensemble name: Optional - specify if new ensemble is being defined (default=specify existing).

Ensemble trace number: -- Select Specifier -- Optional - use %z for sequence (trace) ID or \${TS:property} (default=sequence ID).

Ensemble model name: Required - used to determine the ensemble model_run_id.

Selected ensemble model_id: Information - useful when comparing to database contents.

Ensemble model run date: Optional - used to determine model_run_id (default=run date not used).

OR new ensemble model run date: Optional - specify if new model run date is being defined (default=specify existing).

Selected ensemble model_run_id: Determined from model name and run date when command is run

Ensemble model run ID (model_run_id): Optional - alternative to selecting above choices.

Command: `WriteReclamationHDB (DataStore="ReclamationHDB-Dev", SiteCommonName="AAA_DELETE", DataTypeCommonName="flow", SiteDatatypeID=100376, ValidationFlag="A")`

Cancel OK

WriteReclamationHDB

WriteReclamationHDB() Command Editor for “Real” Time Series

The following figure illustrates general command parameters.

Specify how to match the HDB site_datatype_id (SDI) AND provide general command parameters

Select site_datatype_id (SDI) OBSOLETE - select SDI using site common name General parameters

Agency: Optional - agency supplying data (default=no agency).

Validation flag: Optional - validation flag (default=no flag).

Overwrite flag: Optional - overwrite flag (default=0).

Data flags: Optional - user-defined flag (default=no flag).

Time zone: Optional - time zone for instantaneous and hourly data (default=MST).

Output start: Optional - override the global output start (default=write all data).

Output end: Optional - override the global output end (default=write all data).

WriteReclamationHDB_General

WriteReclamationHDB() Command Editor for General Parameters

The following figure illustrates the syntax of the command when writing “model” data for a single time series, in which case the model parameters are specified via the **Single model time series** tab.

Edit WriteReclamationHDB() Command

Write a single "real" or model time series, or write an ensemble of model time series to a Reclamation HDB database.
The HDB time series table is determined from the data interval, with irregular data being written to the instantaneous data table.

Datastore: Required - datastore for HDB database.
TS list: Optional - indicates the time series to process (default=AllTS).
TSID (for TSList=AllMatchingTSID):
EnsembleID (for TSList=EnsembleID):

Specify how to match the HDB site_datatype_id (required for all time series and ensembles) AND provide general command parameters

Select site_datatype_id (SDI) OBSOLETE - select SDI using site common name General parameters

The choices below include: "site_datatype_id - site common name - site name - datatype name", sorted by site name.
Site data type ID: Required.

Specify how to match the HDB model_run_id (leave blank if not writing single or ensemble model time series data)

Single model time series Ensemble of model time series

Use these parameters to write a single model time series to HDB. The model_run_id choices show model_run_id - model run name - hydrologic indicator - model run date

Model name: Required - used to determine the model_run_id.
Selected model_id: 10 Information - useful when comparing to database contents.
Model run name: Required - used to determine the model_run_id.
Hydrologic indicator: Required - used to determine the model_run_id (can be blank).
Model run date: Required - YYYY-MM-DD hh:mm, used to determine the model_run_id.
Selected model_run_id: 167 Information - useful when comparing to database contents.
OR new model run date: Optional - specify if new model run date is being defined (default=specify existing).
Model run ID (model_run_id): Optional - alternative to selecting above choices.

Command:
`WriteReclamationHDB (DataStore="ReclamationHDB-Dev", SiteCommonName="AAA_DELETE", DataTypeCommonName="flow", SiteDatatypeID=100376, ModelName="CBT AOP RiverWare", ModelRunName="CBT AOP Test", ModelRunDate="2012-07-01 00:00", ValidationFlag="P")`

WriteReclamationHD_Model

WriteReclamationHDB() Command Editor for Single Model Time Series

The following figure illustrates the syntax of the command when writing an ensemble of model time series, in which case ensemble and related model parameters are specified via the **Ensemble of model time series** tab. The TSTool ensemble to write is specified with the `TSList=EnsembleID` and `EnsembleID` parameters. In the following example a new ensemble is being written. The time series trace number and model run date are both taken from the ensemble time series properties, which were read from the original file.

WriteReclamationHDB() Command

Write a single "real" or model time series, or write an ensemble of model time series to a Reclamation HDB database. The HDB time series table is determined from the data interval, with irregular data being written to the instantaneous data table.

Datastore: ReclamationHDB-Dev Required - datastore for HDB database.

TS list: EnsembleID Optional - indicates the time series to process (default=AllTS).

TSID (for TSList=AllMatchingTSID):

EnsembleID (for TSList=EnsembleID): ESSC25

Specify how to match the HDB site_datatype_id (required for all time series and ensembles) AND provide general command parameters

Select site_datatype_id (SDI) OBSOLETE - select SDI using site common name General parameters

The choices below include: "site_datatype_id - site common name - site name - datatype name", sorted by site name.

Site data type ID: 101017 - AAB_DELETE - AAB_DELETE - instantaneous flow Required.

Specify how to match the HDB model_run_id (leave blank if not writing single or ensemble model time series data)

Single model time series Ensemble of model time series

Use these parameters to write an ensemble of model time series to an existing or new HDB ensemble. The model name must exist but a new run date can be specified. The trace number for each time series in the ensemble will be determined from ensemble traces at run time.

Ensemble name: Selected ensemble_id: OR new ensemble name: ESSCN SQIN 6 Ensemble trace number: -- Select Specifier -- => \${ts:sequence_number} Ensemble model name: NWS CBRFC Forecast Selected ensemble model_id: Ensemble model run date: OR new ensemble model run date: \${ts:now} Selected ensemble model_run_id: Determined from model name and run date when command is run Ensemble model run ID (model_run_id):

Required - used to determine the ensemble model_run_id. Information - useful when comparing to database contents. Optional - specify if new ensemble is being defined (default=specify existing). Optional - use %z for sequence (trace) ID or \${TS:property} (default=sequence ID). Required - used to determine the ensemble model_run_id. Information - useful when comparing to database contents. Optional - used to determine model_run_id (default=run date not used). Optional - specify if new model run date is being defined (default=specify existing). Optional - alternative to selecting above choices.

Command: WriteReclamationHDB (DataStore="ReclamationHDB-Dev", TSList=EnsembleID, EnsembleID="ESSC25", SiteCommonName="BTABESCO", DataTypeCommonName="flow", SiteDataTypeID=101017, NewEnsembleName="ESSCN SQIN 6", EnsembleTrace="\${ts:sequence_number}", EnsembleModelName="NWS CBRFC Forecast", NewEnsembleModelRunDate="\${ts:now}", ValidationFlag="P")

Cancel OK

WriteReclamationHDB_Ensemble

WriteReclamationHDB() Command Editor for Ensemble of Model Time Series

The command syntax is as follows:

```
WriteReclamationHDB (Parameter=Value, ...)
```

Command Parameters

Parameter	Description	Default
DataStore	The identifier for the ReclamationHDB data store to use for the database.	None – must be specified.
TsList	Indicates the list of time series to be processed, one of: <ul style="list-style-type: none"> AllMatchingTSID – all time series that match the TSID (single TSID or TSID with wildcards) will be processed. AllTS – all time series before the command. EnsembleID – all time series in the ensemble will be processed. FirstMatchingTSID – the first time series that matches the TSID (single TSID or TSID with wildcards) will be processed. LastMatchingTSID – the last time series that matches the TSID (single TSID or TSID with wildcards) will be processed. SelectedTS – the time series are those selected with the <code>SelectTimeSeries()</code> command. 	AllTS
TSID	The time series identifier or alias for the time series to be processed, using the * wildcard character to match multiple time series.	Required if TsList=*TSID.
EnsembleID	The identifier for the TSTool ensemble to be processed, if processing an ensemble, not to be confused with the Ensemble* parameters below that match HDB data.	Required if TsList=EnsembleID.
SiteDataTypeID	The site_datatype_id value to match the time series. If specified, the value will be used instead of the site_datatype_id determined from SiteCommonName and DataTypeCommonName.	
SiteCommonName	The site common name for the time series location; used with the data type common name to determine the site_datatype_id in the database. Because SiteCommonName is not guaranteed to be unique, the SiteDataTypeID should be specified instead.	None – must be specified unless SiteDataTypeID is specified.
DataTypeCommonName	The data type common name for the time series; used with the site common name to determine the site_datatype_id in the database. Because DataTypeCommonName is not guaranteed to be unique without additional information such as HDB object type, the SiteDataTypeID should be specified instead.	None – must be specified unless SiteDataTypeID is specified.
	Use the following parameters when reading a single model time series.	
ModelName	The model name for the time series; used with the model run name, hydrologic indicator(s), and model run date to determine the model_run_id in the database.	None – must be specified unless ModelRunID is specified.
ModelRunName	The model run name for the time series; used with the	None – must be

Parameter	Description	Default
	model name, hydrologic indicator(s), and model run date to determine the <code>model_run_id</code> in the database.	specified unless <code>ModelRunID</code> is specified.
Hydrologic Indicator	The hydrologic indicator(s) to use for the time series; used with the model name, model run name, and model run date to determine the <code>model_run_id</code> in the database. The hydrologic indicate can be blank.	None – must be specified unless <code>ModelRunID</code> is specified.
ModelRunDate	The model run date (timestamp) to use for the time series; used with the model name, model run name, and hydrologic indicator(s) to determine the <code>model_run_id</code> in the database. The run date should be specified using the format <code>YYYY-MM-DD hh:mm</code> (zero-padded with hour 0-23, minute 0-59). Run dates in HDB include seconds, but this information is ignored when matching time series.	None – must be specified unless <code>ModelRunID</code> is specified.
NewModelRunDate	If specified, the new model run date will be used instead of the <code>ModelRunDate</code> .	Use <code>ModelRunDate</code> .
ModelRunID	The <code>model_run_id</code> value to match the time series. If specified, the value will be used instead of the <code>model_run_id</code> determined from <code>ModelName</code> , <code>ModelRunName</code> , <code>HydrologicIndicator</code> <code>ModelRunDate</code> (or <code>NewModelRunDate</code>).	
	Use the following parameters when writing an ensemble of model time series.	
EnsembleName	The name of the ensemble to write. The <code>TSList=EnsembleID</code> and <code>EnsembleID</code> parameters also should be specified.	Must be specified if writing an ensemble.
NewEnsembleName	If specified, the new ensemble name will be used instead of the <code>EnsembleName</code> .	<code>EnsembleName</code>
EnsembleModelName	The model name corresponding to the ensemble.	Must be specified if writing an ensemble.
EnsembleTrace	Indicate how to identify time series trace identifiers: <ul style="list-style-type: none"> • <code>%z</code> – use standard time series properties to format the ensemble trace ID (see command editor for format characters). <code>%z</code> indicates the sequence identifier from an ensemble trace time series. • <code>\${TS:property}</code> – format the trace identifier from time series properties (e.g., properties read from original ensemble data) • <code>\${property}</code> – format the trace identifier from time series processor (global) properties (e.g., properties set with the <code>SetProperty()</code> command) TSTool and the HDB <code>GET_TSTOOL_ENSEMBLE_MRI</code> procedure currently require the identifier to be an integer – additional options for identifying traces may be added in the future.	The time series sequence number (equivalent to the <code>%z</code> formatting string)
EnsembleModelRunDate	When writing an ensemble, an existing model run date for the ensemble, specified using format:	

Parameter	Description	Default
	<ul style="list-style-type: none"> YYYY-MM-DD hh:mm (zero-padded with hour 0-23) <p>The model time series associated with the existing run will be overwritten.</p>	
NewEnsembleModel RunDate	<p>When writing an ensemble, the new model run date for the ensemble, specified using format:</p> <ul style="list-style-type: none"> YYYY-MM-DD hh:mm (zero-padded with hour 0-23) <code>\${ts:property}</code> – use a run date from a time series property, truncated to minute <code>\${property}</code> – format the new model run date identifier from time series processor (global) properties (e.g., properties set with the <code>SetProperty()</code> command) 	If not specified, the ensemble identifier in HDB will not include the model run date.
	The following parameters are always appropriate.	
Agency	The agency abbreviation (e.g., USBR) for data records written to the database.	No agency is indicated in database.
Validation Flag	HDB validation flag. Only uppercase characters are supported.	No flag is used.
OverwriteFlag	HDB overwrite flag.	Overwrite (enforced by HDB stored procedure)..
DataFlags	User-defined flags, up to 20 characters.	No flags are used.
TimeZone	Three-letter time zone abbreviation for the data records written to the database.	Default HDB time zone is assumed.
OutputStart	The date/time for the start of the output.	Use the global output period.
OutputEnd	The date/time for the end of the output.	Use the global output period.