

Command Reference: SetFromTS()

Set time series data using data from another time series

Version 11.03.05, 2015-06-14

The `SetFromTS()` command sets data in a dependent time series by transferring values from an independent time series. A period and window within the year can be specified to limit the period that is processed. See also the `FillFromTS()` command, which will transfer values only when the dependent time series has missing data. Only data values are transferred – time series properties will not be modified. If multiple time series or an ensemble is being processed, the number of independent time series must be one or the same number as the time series being filled.

It is also possible to use this command to transfer data between time series that have different intervals. If the independent time series has a smaller interval, then `SetWindowStart` and `SetWindowEnd` parameters should be used to specify a window to transfer – the first value in the window will be transferred. For example, when transferring all the January values from a monthly time series to a year-interval dependent time series, specify the window start and end as 01. If the transfer is from longer interval to smaller, then the values from the independent time series will be used multiple times for the dependent time series (e.g., annual value used for each month).

The following dialog is used to edit the command and illustrates the command syntax.

Copy data values from the independent time series to replace values in the dependent time series.
All data values (by default including missing data) in the set period will be copied.
If one independent time series is specified, it will be used for all dependent time series.
If multiple independent time series are specified (e.g., for ensembles), the same number of dependent time series must be specified.

Time series | Period and Window | Set Control

Dependent TS List: AllMatchingTSID Optional - indicates the time series to process (default=AllTS).
TSID (for TSList=AllMatchingTSID): ts1_month
EnsembleID (for TSList=EnsembleID):
Independent TS List: AllMatchingTSID Optional - indicates the time series to process (default=AllTS).
Independent TSID (for Independent TSList=AllMatchingTSID): ts2_month
Independent EnsembleID (for Independent TSList=EnsembleID):

Command:
SetFromTS (TSList=AllMatchingTSID, TSID="ts1_month", IndependentTSList=AllMatchingTSID, IndependentTSID="ts2_month", SetWindowStart="03", SetWindowEnd="06", TransferHow=ByDateTime, HandleMissingHow="IgnoreMissing", RecalcLimits=True)

Cancel OK

SetFromTS() Command Editor for Time Series Parameters

SetFromTS

Time series | Period and Window | Set Control

Specify date/times with precision appropriate for the data.
The set period is for the independent time series.
The set window can be specified using the provided choices or with processor \${Property}.

Set start: Optional - set start, can use \${Property} (default is full period).
Set End: Optional - set end, can use \${Property} (default is full period).

☒ Set window: Start Month: End Month: Optional - window within output year to set data (default=full year).

Set window start \${Property}: Optional (default=full year).
Set window end \${Property}: Optional (default=full year).

SetFromTS_Period

SetFromTS() Command Editor for Period and Window Parameters

Time series | Period and Window | Set Control

The following parameters indicate how to set the data.
If the data should be treated as original data, the time series limits can be recalculated (can be used for filling later).

Transfer data how: Required - how are data values transferred?
Handle missing data how?: Optional - missing in independent handled how? (default=SetMissing).
Set data flags?: Optional - should data flags be copied (default=True).
Set flag: Optional - string to flag set values.
Set flag description: Optional - description for set flag.
Recalculate limits: Optional - recalculate original data limits after set (default=False).

SetFromTS_Control

SetFromTS() Command Editor for Set Control Parameters

The command syntax is as follows:

```
SetFromTS (Parameter=Value, ...)
```

Command Parameters

Parameter	Description	Default
TSList	Indicates the list of time series to be processed, one of: <ul style="list-style-type: none"> AllMatchingTSID – all time series that match the TSID (single TSID or TSID with wildcards) will be modified. AllTS – all time series before the command. EnsembleID – all time series in the ensemble will be modified. FirstMatchingTSID – the first time series that matches the TSID (single TSID or TSID with wildcards) will be modified. 	AllTS

Parameter	Description	Default
	<ul style="list-style-type: none"> LastMatchingTSID – the last time series that matches the TSID (single TSID or TSID with wildcards) will be modified. SelectedTS – the time series are those selected with the <code>SelectTimeSeries()</code> command. 	
TSID	The time series identifier or alias for the time series to be modified, using the * wildcard character to match multiple time series. Can be specified using processor <code>\${Property}</code> .	Required when <code>TSList=*TSID</code>
EnsembleID	The ensemble to be modified, if processing an ensemble. Can be specified using processor <code>\${Property}</code> .	Required when <code>TSList=EnsembleID</code>
Independent TSList	Indicates how to determine the list of independent time series (see the explanation of TSList).	AllTS
Independent TSID	The time series identifier or alias for the independent time series (see the explanation of TSID). Can be specified using processor <code>\${Property}</code> .	Required when a <code>IndependentTSList=*TSID</code>
Independent EnsembleID	The ensemble identifier for the independent time series (see the explanation of EnsembleID). Can be specified using processor <code>\${Property}</code> .	Required when <code>IndependentTSList=EnsembleID</code> .
SetStart	The date/time to start setting data, if other than the full time series period. Can be specified using processor <code>\${Property}</code> .	Full period.
SetEnd	The date/time to end setting data, if other than the full time series period. Can be specified using processor <code>\${Property}</code> .	Full period.
SetWindowStart	<p>The date/time (without year) indicating the start of the window within a year to set values in the output (dependent) time series. For example:</p> <ul style="list-style-type: none"> mm – for monthly time series mm-dd – for daily time series mm-dd-hh – for hourly data <p>If specified using processor <code>\${Property}</code>, the processor property will override date/time selections.</p>	Full year.
SetWindowEnd	The date/time (without year) indicating the end of the window within a year to set values in the output (dependent) time series. If specified using processor <code>\${Property}</code> , the processor property will override date/time selections.	Full year.
TransferHow	Indicates how to transfer data:	None – must be specified.

Parameter	Description	Default
	<ul style="list-style-type: none"> ByDateTime – a date/time in one time series will be lined up with the other time series. Sequentially – data from the independent will be transferred sequentially, even if the date/time does not align (used when transferring continuous data over Feb 28/29, without gaps). 	
HandleMissingHow	<p>Indicates how to handle missing data in the independent time series:</p> <ul style="list-style-type: none"> IgnoreMissing – missing values in the independent time series WILL NOT be transferred to the dependent time series. SetMissing – missing values in the independent time series WILL be transferred to the dependent time series. SetOnlyMissingValues – only the missing values in the independent time series will be transferred, useful when a separate time series has been used to insert additional missing values. 	SetMissing
SetDataFlags	Indicates if data flags should also be transferred from the independent time series to the dependent time series.	True
SetFlag	String that should be used for the data flag for values that are set (overrides SetDataFlags).	No flag is set.
SetFlagDesc	Description that should be used for the SetFlag value.	Auto-generated.
RecalcLimits	Available only for monthly time series. Indicate whether the original data limits for the time series should be recalculated after the setting the time series values. Setting to True is appropriate if the independent time series provides observations consistent with the original data.	False (only the values in the initial time series will be used for historical data).

A sample command file to process data from the State of Colorado's HydroBase is as follows:

```
# 08241000 - TRINCHERA CREEK ABOVE MOUNTAIN HOME RESERVOIR
08241000.DWR.Streamflow.Month~HydroBase
# 08240500 - TRINCHERA CREEK ABOVE TURNER'S RANCH
08240500.DWR.Streamflow.Month~HydroBase
SetFromTS(TSList=AllMatchingTSID, TSID="08241000.DWR.Streamflow.Month",
    IndependentTSList=AllMatchingTSID,
    IndependentTSID="08240500.DWR.Streamflow.Month",
    TransferHow=ByDateTime)
```