

Command Reference: WriteWaterML2()

Write time series to a WaterML 2 XML format file

Version 12.04.00, 2017-07-16

This command is under development. In particular, an evaluation is determining how best to map internal time series properties to the WaterML specification, including selecting reasonable defaults while allowing override of defaults.

The `WriteWaterML2()` command writes time series to a WaterML 2 XML format file. See the **WaterML2 Input Type Appendix** for more information about the file format. This command is under development because there is interpretation of how the specification should be implemented, resulting in various dialects of WaterML 2 files. These dialects require that software such as TSTool understand the dialect and be able to produce it accurately.

The following dialog is used to edit the command and illustrates the syntax of the command.

Edit WriteWaterML2() Command

This command is under development. Functionality currently is limited in that only some JSON elements are written using default data mapping.
Write time series to a WaterML format file, which can be specified using a full or relative path (relative to the working directory).
The working directory is: C:\owf-gitrepos\cdss-app-tstool-test\test\regression\commands\general\WriteWaterML
Enter date/times to a precision appropriate for output time series.

TS list: Optional - indicates the time series to process (default=AllTS).

TSID (for TSList=AllMatchingTSID):

EnsembleID (for TSList=EnsembleID):

WaterML file to write:

WaterML version: Optional - WaterML version (default=most recent supported).

Output precision: Optional - digits after decimal (default=4).

Missing value: Optional - value to write for missing data (default=initial missing value).

Output start: Optional - override the global output start (default=write all data).

Output end: Optional - override the global output end (default=write all data).

Command: `WriteWaterML (OutputFile="Results/Test_WriteWaterML_Day_JSON1.1_out.json", Version="WaterML-1.1-JSON")`

WriteWaterML2

WriteWaterML2() Command Editor

The command syntax is as follows:

`WriteWaterML (Parameter=Value, ...)`

Command Parameters

Parameter	Description	Default
TSList	Indicates the list of time series to process, one of: <ul style="list-style-type: none">AllMatchingTSID – all time series that match the TSID (single TSID or TSID with wildcards) will be processed.AllTS – all time series before the command.	AllTS

	<ul style="list-style-type: none"> EnsembleID – all time series in the ensemble will be processed. FirstMatchingTSID – the first time series that matches the TSID (single TSID or TSID with wildcards) will be processed. LastMatchingTSID – the last time series that matches the TSID (single TSID or TSID with wildcards) will be processed. SelectedTS – the time series are those selected with the <code>SelectTimeSeries()</code> command. 	
TSID	The time series identifier or alias for the time series to be processed, using the * wildcard character to match multiple time series.	Required if <code>TSList=*TSID</code> .
EnsembleID	The ensemble to process, if processing an ensemble.	Required if <code>TSList=EnsembleID</code> .
OutputFile	The WaterML 2 output file. The path to the file can be absolute or relative to the working directory (command file location). Can be specified using <code>\${Property}</code> notation.	None – must be specified.
WriteMethod	<p>The method used to write the file, used by developers and may have an impact on features and performance:</p> <ul style="list-style-type: none"> CreateDOM – write the XML document object model (DOM) directly API – use the WaterML 2.0 auto-generated API to write (less flexibility to control output since code is generated from schema) 	CreateDOM
Version	<p>The WaterML 2 version to write:</p> <ul style="list-style-type: none"> WaterML-2.0 	WaterML-2.0
Dialect	<p>The WaterML 2 dialect, reflecting implementation by different organizations:</p> <ul style="list-style-type: none"> USGS – United States Geological Survey, as used with National Water Information System (NWIS) 	USGS
Precision	The number of digits after the decimal for numerical output.	4 (in the future may default based on data type)
MissingValue	The value to write to the file to indicate a missing value in the time series.	As initialized when reading the time series or creating a new time series, typically -999, NaN, or another value that is not expected in data.
OutputStart	The date/time for the start of the output.	Use the global output period.
OutputEnd	The date/time for the end of the output.	Use the global output period.