
Command Reference: deselectTimeSeries()

Deselect Time Series for Output

Version 06.08.02, 2004-08-03, Color, Acrobat Distiller

The `deselectTimeSeries()` command deselects output time series, as if done interactively. The command minimizes the need for the `free()` command, when used in conjunction with other commands that use a time series list based on selected time series. See also the `selectTimeSeries()` command. The following dialog is used to edit the command and illustrates the command syntax.

Edit deselectTimeSeries() Command

This command deselects time series. This is most often used before a `selectTimeSeries()` command. Time series can be matched by one of the following methods (use only one below):

1. Use a time series identifier (TSID) pattern:
The dot-delimited time series identifier parts are Location.DataSource.DataType.Interval.Scenario
The pattern used to select/deselect time series will be matched against aliases and identifiers.
Use * to match all time series.
Use A* to match all time series with alias or location starting with A.
Use *.XXXXX.* to match all time series with a data type XXXXX.
2. Specify in-memory time series positions:
The first time series created is position 1.
Separate numbers by a comma. Specify a range, for example, as 1-3.

Time series alias/identifier: Specify a TSID pattern.

Time series position(s): For example, 1,2,7-8.

Select all first?: Eliminates need for separate select.

Command:

deselectTimeSeries

deselectTimeSeries() Command Editor

The command syntax is as follows:

```
deselectTimeSeries(param=value,...)
```

Command Parameters

Parameter	Description	Default
TSID	The time series identifier or alias pattern, to indicate time series to deselect. See the above figure for examples.	Can be blank if Pos is specified.
Pos	A list of time series positions in output (1+), separated by commas. This parameter is useful if it is known that the first time series is being modified by subsequent commands.	Use the TSID.
SelectAllFirst	Indicates whether all time series should be selected before deselecting the specified time series: True or False.	False

A sample commands file is as follows:

```
deselectTimeSeries(TSID="40*",SelectAllFirst=True)
```