
Command Reference: StartLog()

(Re)start the log file

Version 09.08.01, 2010-09-14

The `StartLog()` command (re)starts the log file. It is useful to insert this command as the first command in a command file, in order to persistently record the results of processing. A useful standard is to name the log file the same as the command file, with an additional `.log` extension, and this convention is enforced by default. A date or date/time can optionally be added to the log file name.

The following dialog is used to edit the command and illustrates the syntax for the command.

Edit StartLog() command

(Re)start the log file. This is useful when it is desirable to have a log file saved for a commands file.
A blank log file name will restart the current file.
The log file can be specified using a full or relative path (relative to the working directory).
The working directory is: C:\Develop\TSTool_SourceBuild\TSTool\test\regression\UserManualExamples\TestCases\CommandReference\StartLog
The Browse button can be used to select an existing file to overwrite.
Specifying a suffix for the file will insert the suffix before the "log" file extension.

Log file:

Suffix:

Command:

StartLog

StartLog() Command Editor

The command syntax is as follows:

```
StartLog(Parameter=Value,...)
```

Command Parameters

Parameter	Description	Default
LogFile	The name of the log file to write surrounded by double quotes. The extension of <i>.log</i> will automatically be added, if not specified.	If not specified, the existing file will be restarted.
Suffix	<p>Indicates that a suffix will be added before the <i>.log</i> extension, one of:</p> <ul style="list-style-type: none"> ▪ Date – add a date suffix of the form YYYYMMDD. ▪ DateTime – add a date/time suffix of the form YYYYMMDD_HHMMSS. <p>This is useful for automatically archiving logs corresponding to commands files, to allow checking the output at a later time. However, generating date/time stamped log files can increase the amount of disk space that is used.</p>	Do not add the suffix.

A sample command file to process State of Colorado HydroBase data is as follows (the Add () command will generate an error because the units of the time series are incompatible):

```
StartLog(LogFile="Example_StartLog.log")
# 06753400 - LONETREE CREEK AT CARR, CO.
06753400.USGS.Streamflow.Month~HydroBase
# 1179 - BYERS 5 ENE
1179.NOAA.Precip.Month~HydroBase
Add(TSID="06753400.USGS.Streamflow.Month",AddTSLList=AllTS,HandleMissingHow="IgnoreMissing")
```