Start		
Before Start		
	COMPLETE	
Preflight inspection	COMPLETE	
Passenger briefing Brakes		
Dianes	TEST and SET	
Seats, belts, harnesses	SECURE	
Fuel valve	ВОТН	
Radios, electrical equipment	OFF	
Circuit breakers	CHECK IN	
Beacon switch	ON	
Engine Start		
Mixture	RICH	
Carburetor heat	COLD	
Prime	AS REQUIRED	
hrottle OPEN 1/8 INCH		
Master	ON	
Propeller area	CLEAR	
Ignition switch	START	
Release when engine starts		
Oil pressure	CHECK	
If no pressure in 30 seconds, shutdown		
Mixture GROUND LEAN		
Before Taxi		
Headset	ON	
Flaps	RETRACT	
Weather	OBTAIN	
Altimeter	SET	
EFB Setup	AS DESIRED	
Navigation, landing lights	ON	

Run-up	
Instruments	CHECK and SET
VOR Check	IF NEEDED
Brakes	SET
Doors and windows	CLOSED, LOCKED
Flight controls	FREE and CORRECT
Fuel valve	BOTH
Mixture	RICH
	Below 3000 feet
Throttle	1700 RPM
Magnetos	CHECK
Max drop 125 RPM, max diff. 50 RPM	
Engine gauges, ammet	ter CHECK
Vacuum gauge	CHECK
Carburetor heat	TEST
Idle	TEST
Mixture	GROUND LEAN
Throttle friction	ADJUST

Version 1 PR 12