OpenEVSE

OpenEVSE - 50A Charging Station Kit

P50V - Value

P50D - Deluxe



http://www.openevse.com

The OpenEVSE **P50V** and **P50D** kits contain the components required to assemble a **Level 2** Charging Station designed for up to a 50A circuit. It is ideal for use across the globe for single phase charging.

Required to complete: AC input cable matching your outlet and SAE J1772 or IEC Type-2 Cable.

Specifications		Value - P50V	Deluxe - P50D
AC Input			
Operating Voltage		208 - 240 VAC, 1-Ph	
AC Frequency		50 or 60Hz	
AC Output			
Current	50A Circuit	6A - 40A	
	40A Circuit	6A - 32A	
	30A Circuit	6A - 24A	
	20A Circuit	6A - 16A	
Output Power	208 VAC	1248 W - 8320 W	
	240VAC	1440 W - 9600 W	
Features			
Display	Type	LCD 16 Character 2 Lines	
	Backlight	Monochrome	Color
Temperature	Sensor	Yes	
	Type	MCP8908	DS3231
Real Time Clock		No	Yes
Station Based Timers		No	Yes
Current Measurement		Optional	Standard
Display - kWh added		Optional	Standard
Wi-Fi - Energy Monitoring		Optional	Optional
Session Options	Add x kWh	Optional	Standard
	Charge x min	No	Yes
Safety			
Power Interlock		Yes	
Pilot Signal		Yes	
Ground Monitoring		Yes	
Ground Fault Interrupt		15ma - 20ma	
Welded Contact Detection		Yes	
Self test		Power-on and before energizing	
Temperature Throttling	50%	65°C - 150°F	
	25%	68°C - 155°F	
	Shutdown	71°C - 160°F	
	Resume 100%	62°C - 145°F	
Electric Vehicle ID		Yes	
Ventilation Check		Yes	
Warranty			
Standard		1 Year	
Enclosure			
Weight		1.27kg - 2.8 lbs	1.45kg 3.2lbs
Dimensions (H x W x D)	mm	260 x 135 x 70	
	Inches	10.3 x 5.3 x 2.8	

P50V - Value

P50D - Deluxe

Features:

Level 2 Charging

9.6kw Power

Adjustable Current

Serial Remote API

Open Source:

Hardware

Firmware

Optional:

Wi-Fi

Energy Monitoring

Copyright 2016
OpenEVSE LLC

Licensed under a Creative Commons Attribution 4.0 International license.