In the kit (OpenEVSE Kit – Level1 & Level2 50A Deluxe)

10 nylon lock nuts
4 foam washers
4 white nylon spacers
4 metal 1–40 x 11/32 threaded spacers
1 clear acrylic LCD window
1 LCD foam seal
1 nylon LCD window brace
6 spade terminals
1 drilled metal plate
1 polycarbonate enclosure
2 cable glands
4 6AWG wire lugs
3 red 3 black wires with spade connectors
1 push switch
1 4–way ribbon cable with 0.1" pitch connectors
1 green cable with 3 position 0.1" pitch connector
4 long screws
2 hex bolts
4 1/2" wide–head screws
4 short wide–head screws
8 5/8" screws
6 short self–tapping screws
1 DPST Struthers & Dunn contactor 450BXX40–12VDC
1 OpenEVSE PLUS v4 board with 100–240V power module
1 LCD colour panel v2 board with daughter–board
1 green unstranded ground wire
1 current sensor CT with 2–pin connector model CR8450–1000–T7QC
1 GFCI CT with 4–pin connector CR8420–1000
1 ground terminal block

Other required components

J1772 connector and cable assembly

3/10 AWG power cable, circular x–section

Power connector, e.g. NEMA 6–50

CR1220 or CR1225 button cell (optional)