

Framework for High Performance Grid and Web Services


GGF15 October 2 2005

Geoffrey Fox

**Computer Science, Informatics, Physics
Pervasive Technology Laboratories
Indiana University Bloomington IN 47401**


Support for Messages

- Optimize XML representation and transport protocol



Support for Streams

- Optimize Stream representation and transport protocol



Basic Idea

- Bind SOAP to message-oriented middleware that virtualizes representation and protocol
- Build handlers that convert representation and support different protocols
- Specify methodology and specific parameters as meta-data stored in a meta-data (context) service
- Combination of message and context is self-describing
 - Message has a URI referencing context
- Target Axis2 as it supports SOAP Infoset and has a reasonable handler model
 - Some complicated issues here – initially porting technology to Axis2 – might do as Apache project
- Initial targets sensors, mobile devices and audio-video conferencing


Metadata and Service Context

- Consider a collection of services working together
 - Workflow tells you how to specify service interaction but more basically there is shared information or context specifying/controlling collection
- WS-RF and WS-GAF have different approaches to contextualization
 - supplying a common “context” which at its simplest is a token to represent state
- More generally core shared information includes dynamic service metadata and the equivalent of configuration information.
- One can support such a common context either as pool of messages or as message-based access to a “database” (Context Service)
- Two services linked by a stream are perhaps simplest example of a collection of services needing context
- Note that there is a tension between storing metadata in **messages** and **services**.
 - This is shared versus distributed memory debate in parallel computing

Role of WS-Context

- There are many WS-* specifications addressing **meta-data** and both many approaches and many trade-offs
- There are **Distributed Hash Table** based systems (Chord) to achieve scalability in large scale networks
- **Managed dynamic workflows** as in sensor integration and collaboration require
 - **Fault-tolerance** and ability to support **dynamic changes** with **few millisecond** delay
 - But only a **modest number** of involved services (up to 1000's in a **session**)
 - Need **Session** NOT Service/Resource meta-data so don't use WS-RF
- We have built a **WS-Context** compliant metadata catalog supporting distributed or central paradigms
- Use for **OGC Web catalog** service with **UDDI** for slowly varying meta-data
- 3 XML Databases: **UDDI WS-Context WFS** stored as **SQL**


NaradaBrokering



Traditional NaradaBrokering Features


Multiple protocol transport support In publish-subscribe Paradigm with different Protocols on each link	Transport protocols supported include TCP, Parallel TCP streams, UDP, Multicast, SSL, HTTP and HTTPS. Communications through authenticating proxies/firewalls & NATs. Network QoS based Routing Allows Highest performance transport
Subscription Formats	Subscription can be Strings, Integers, XPath queries, Regular Expressions , SQL and tag=value pairs.
Reliable delivery	Robust and exactly-once delivery in presence of failures
Ordered delivery	Producer Order and Total Order over a message type. Time Ordered delivery using Grid-wide NTP based absolute time
Recovery and Replay	Recovery from failures and disconnects. Replay of events/messages at any time. Buffering services.
Security	Message-level WS-Security compatible security
Message Payload options	Compression and Decompression of payloads Fragmentation and Coalescing of payloads
Messaging Related Compliance	Java Message Service (JMS) 1.0.2b compliant Support for routing P2P JXTA interactions.
Grid Feature Support	NaradaBrokering enhanced Grid-FTP . Bridge to Globus GT3 .
Web Services supported	Implementations of WS-ReliableMessaging , WS-Reliability and WS-Eventing .

Mean transit delay for message samples in NaradaBrokering: Different communication hops



**Pentium-3, 1GHz,
256 MB RAM
100 Mbps LAN
JRE 1.3 Linux**

Standard Deviation for message samples in NaradaBrokering Different communication hops - Internal Machines



NB Features Released 2005-2006


- Production implementations of **WS-Eventing**, **WS-RM** and **WS-Reliability**.
 - **WS-Notification** when specification agreed
- **SOAP message support** and NaradaBrokers viewed as SOAP Intermediaries
- **Active replay** support: Pause and Replay live streams.
- **Stream Linkage**: can link permanently multiple streams – using in annotating real-time video streams
- **Replicated storage support** for fault tolerance and resiliency to storage failures.
- **Management**: HPSearch Scripting Interface to administer streams and brokers (uses **WS-Management**)
- **Broker Topics and Message Discovery**: Locate appropriate
- Support of IBM **MQSeries** functionality and Legacy MQSeries Systems as a Grid of Grids gateway

Possible NaradaBrokering Futures

- Clarification and expansion of **NB Broker** to act as a **WS container**
- Integration with **Axis 2.0** as **Message Oriented Middleware infrastructure**
- Support for **High Performance transport and representation for Web Services**
- **Performance based routing**
 - The broker network will dynamically respond to changes in the network based on metrics gathered at individual broker nodes.
- **Replicated publishers** for fault tolerance
- **Pure client P2P** implementation (originally we linked to JXTA)
- **Security Enhancements** for fine-grain topic authorization, multi-cast keys, Broker attacks

SOAP Message Structure I

- SOAP Message consists of **headers and a body**
 - Headers could be for Addressing, WSRM, Security, Eventing etc.
- **Headers** are processed by **handlers or filters** controlled by container as message enters or leaves a service
- **Body** processed by Service itself
- The header processing defines the “**Web Service Distributed Operating System**”
- **Containers** queue messages; control processing of headers and offer convenient (for particular languages) service interfaces
- **Handlers are really the core Operating system services** as they receive and give back messages like services; they just process and perhaps modify different elements of SOAP Message – WS standards specify handler structure



SOAP Message Structure II

- Content of individual headers and the body is defined by XML Schema associated with WS-* headers and the service WSDL
- **SOAP Infoset** captures header and body structure
- **XML Infoset** for individual headers and the body capture the details of each message part
- Web Service Architecture requires that we **capture Infoset structure** but does **not** require that we represent XML in **angle bracket <content>value</content>** notation



High Performance XML I

- There are many approaches to efficient “binary” representations of **XML Infosets**
 - MTOM, XOP, Attachments, Fast Web Services
 - DFDL is one approach to specifying a binary format
- Assume URI-S labels **Scheme** and URI-R labels **realization of Scheme** for a particular message i.e. URI-R defines specific layout of information in each message
 - DFDL from GGF quite interesting for this
- Assume we are interested in conversations where a **stream of messages** is exchanged between two services or between a client and a service i.e. two end-points
- Assume that we need to **communicate fast** between end-points that understand scheme URI-S but must **support conventional representation** if one end-point does not understand URI-S

High Performance XML II

- First Handler **Ft=F1 handles Transport protocol**; it negotiates with other end-point to establish a **transport conversation** which uses either HTTP (default) or a different transport such as UDP with WSRM implementing reliability
 - **URI-T** specifies transport choice
- Second Handler **Fr=F2 handles representation** and it negotiates a **representation conversation** with scheme **URI-S** and realization **URI-R**
 - **Negotiation identifies parts of SOAP header that are present in all messages in a stream and are ONLY transmitted ONCE**
- **Fr** needs to negotiate with Service and other handlers illustrated by **F3** and **F4** below to decide what representation they will process

F1

F2


F3

F4

Container Handlers

High Performance XML III

- Filters controlled by Conversation Context **convert messages between representations** using permanent context (metadata) catalog to hold conversation context
- Different **message views** for each end point or even for individual handlers and service within one end point
 - **Conversation Context** is fast dynamic metadata service to enable conversions
- **NaradaBrokering** will implement **Fr** and **Ft** using its support of multiple transports, fast filters and message queuing;



Location of software for Grid Projects in Community Grids Laboratory

- <http://www.naradabrokering.org> provides Web service (and JMS) compliant **distributed publish-subscribe messaging** (software overlay network)
- <http://www.globlmmcs.org> is a **service oriented (Grid) collaboration environment** (audio-video conferencing)
- <http://www.crisisgrid.org> is an OGC (open geospatial consortium) Geographical Information System (GIS) compliant **GIS and Sensor Grid**
- <http://www.opengrids.org> has WS-Context, Extended UDDI etc.
- The work is still in progress but NaradaBrokering is quite mature
- **All software is open source** and freely available