A Solid-based Architecture for Decentralised Interoperable Location Data


Maxim Van de Wynckel, Beat Signer

Web & Information Systems Engineering Lab Vrije Universiteit Brussel





Current indoor positioning systems (IPS)



Problems with current IPS'


- 1. Users not in **control** of their **data**
- 2. No interoperability between positioning systems
- 3. No interoperability between (navigation) applications

What is Solid?


What is Solid?


RDF: Properties and Observations


PoC Demonstrator



PoC Demonstrator ...







PoC Demonstrator

```
SELECT ?posGeoJSON ?datetime ?accuracy {
    ?profile a sosa:FeatureOfInterest ;
            ssn:hasProperty ?property .
    ?observation sosa:hasResult ?result ;
                sosa:observedProperty ?property ;
                sosa:resultTime ?datetime .
    ?result geosparql:hasSpatialAccuracy ?spatialAccuracy ;
            geosparql:asWKT ?posWKT .
    BIND(geof:asGeoJSON(?posWKT) AS ?posGeoJSON)
    ?spatialAccuracy qudt:numericValue ?value ;
                    qudt:unit ?unit .
    OPTIONAL { ?unit qudt:conversionMultiplier ?multiplier }
    OPTIONAL { ?unit qudt:conversionOffset ?offset }
    BIND(COALESCE(?multiplier, 1) as ?multiplier) # Default 1
    BIND(COALESCE(?offset, 0) as ?offset) # Default 0
    BIND(((?value * ?multiplier) + ?offset) AS ?accuracy)
} ORDER BY DESC(?datetime) LIMIT 20
```