

Getting Started with OpenIndiana

Contents

1	Introduction	4
2	Conventions	4
2.1	Commandlines	4
3	Hipster Software Releases	4
4	System Requirements	5
5	Exploring OpenIndiana Hipster	5
5.1	Live Media	5
5.2	Virtual machines	6
5.3	Vagrant	6
6	Preparing to Install Hipster	7
6.1	Backing up data	7
6.2	Deciding where to install OpenIndiana	7
6.3	Gathering network information	8
6.4	Downloading the software	8
6.5	Checking the MD5/SHA	8
7	Creating a Hipster DVD	8
7.1	BSD/illumos/Solaris	8
7.2	Linux	10
7.3	Mac OS X	11
7.4	Windows	11
8	Creating a Hipster USB Drive	11
8.1	Prerequisites	11
8.2	Identifying the path to your USB device	11
8.3	BSD/Linux/OS X	12
8.4	illumos/Solaris	13
8.5	Windows	13
9	Booting the Hipster Installer	13
9.1	Booting the OpenIndiana installer on virtual hardware	13
9.2	The OpenIndiana installer boot menu	14
9.3	Selecting keyboard layout and display language	15

9.4	The live media desktop	18
9.5	Using the device driver utility	18
9.6	Using the Gparted Partition Editor	20
9.7	Live media authentication	20
10	Installing OpenIndiana	20
10.1	Installing OpenIndiana from live media	20
10.2	Install OpenIndiana (graphical installer)	21
10.3	Install OpenIndiana using the Text Installer	33
10.4	Installing OpenIndiana using the text installer (DVD ISO or USB)	46
10.5	Install OpenIndiana to existing ZFS pool	46
11	Troubleshooting Installations	48
12	Post Installation Steps	48
12.1	Boot Menu - Post Install	48
12.2	Resetting the root password	48
13	Image Package System (IPS)	50
13.1	Introduction	50
13.2	IPS packages	50
13.3	IPS commands	51
13.4	pkg1 uses FMRIs	51
13.5	Finding help with pkg	52
13.6	Searching for packages	52
13.7	Listing the status of packages	53
13.8	Listing information about packages	54
13.9	Listing the contents of packages	54
13.10	Listing the dependencies of packages	54
13.11	Installing packages	55
13.12	Updating packages	56
13.13	Removing packages	56
13.14	Downgrading packages	57
13.15	IPS package repositories	57
13.16	Listing information about repositories	58
13.17	IPS package repository precedence	58
13.18	Listing package history	59
13.19	IPS package archives (.p5p)	60
13.19.1	Creating the p5p package	60
13.19.2	Listing the contents of a p5p package	61
13.19.3	Adding the package as a local repository	61
13.19.4	Installing software from the local repository	61
13.20	Legacy package management tools	61
13.21	3rd party package management tools	62
14	Managing Boot Environments	62
14.1	Why use multiple boot environments?	62
14.2	Features of the beadm utility	64
14.3	beadm command reference	64
14.4	beadm zones support	65

14.5	Zones support limitations	65
14.6	Zones support specifications	66
15	The X-Window System	66
15.1	Video card support (2D)	66
15.2	Video card support (3D)	67
16	Device Drivers	67

❗ **NOTE:**

This is a **DRAFT** document which may contain errors!

Help us improve and expand this site.

Please see the **Contrib** section for more details about joining the OpenIndiana Documentation Team.

1 Introduction

Welcome to the OpenIndiana Handbook!

This collection of documents is aimed at providing a comprehensive source of guidance for both new and seasoned Unix administrators. While our aim is to address as many facets of OpenIndiana use and administration as possible, some topics are simply too complex and beyond the scope of an introductory end user handbook. In such cases external sources of information will be provided in the form of references to other web sites, man pages, or printed books.

2 Conventions

2.1 Commandlines

Commandlines starting with a # character means that they should be run as root. Most of these examples can also be invoked with [pfexec\(1\)](#) or [sudo\(1m\)](#) instead.

You can login as root using [su\(1m\)](#).

An example of a commandline intended to be invoked as root:

```
# dd if=image.usb of=/dev/sdb
```

Commandlines starting with a \$ character means that they should be run as a regular user.

An example of a commandline intended to be invoked as a regular user:

```
$ prstat
```

3 Hipster Software Releases

Approximately every six months, the OpenIndiana project releases a snapshot of the Hipster rolling release branch. Ideally suited for both workstations and servers, simply choose the installer type which best serves your needs.

Workstation	Server	Minimal
Live installer (Mate desktop)	Text Only (No GUI)	Text Only (No GUI)

For a full list of links to the various installer images, visit the [OpenIndiana Downloads](#) page.

① NOTE:

- The legacy oi-dev-151x branch is no longer maintained.
- For details on installing/upgrading legacy OpenIndiana dev, [see this page](#)

△ CAUTION:

Hipster is a rapid development branch where software versions are frequently updated. While every package is tested to ensure stability, caution is nevertheless warranted when deploying Hipster into mission critical production environments.

4 System Requirements

Installation type	CPU	Disk Space	Memory (RAM)
Server	64 Bit	16GB (or more)	2GB (or more)
Desktop	64 Bit	20GB (or more)	4GB (or more)

① NOTE:

- For the best performance (and to reduce the possibility of disk swapping), allocate 4GB RAM or more.
- For desktops, ensure total system memory (RAM + swap) are at least 4GB or greater.
- The default size of the OpenIndiana swap file is 50% of installed memory.
- Minimum and maximum default swap allocations are 512MB and 32GB respectively.

5 Exploring OpenIndiana Hipster

There are several ways in which you can explore OpenIndiana without having to perform a bare metal install.

- Live media (USB/DVD)
- Virtual machines (PC emulation via software)
- Vagrant (virtual machine image automation)

① NOTE:

While the Live Media environment provides an opportunity to use and explore many of the features of OpenIndiana, it is not possible to install additional software into the Live Media environment.

5.1 Live Media

Available in both DVD and USB formats, the OpenIndiana GUI installer also functions as live media. This allows you try OpenIndiana without the need to install it. Exploring OpenIndiana

ana via the live media is an especially good way to test your hardware compatibility prior to installing the operating system.

5.2 Virtual machines

OpenIndiana is known to work with the following virtualization software:

- [VirtualBox](#)
- [VMWare Fusion](#)
- [VMWare Workstation Pro](#)
- [VMWare Workstation Player](#)
- [VMWare VSphere](#)
- [Linux KVM](#)
- illumos KVM - (The illumos port of Linux KVM)
- [bhyve](#)

Virtual machines provide a PC emulation layer in which you install OpenIndiana just as you would on physical 'bare metal' hardware.

5.3 Vagrant

Vagrant provides an excellent way to explore OpenIndiana as it fully automates the process of bringing a virtual machine online. OpenIndiana comes with an official [Vagrant](#) box, which can be used for exploring OpenIndiana before installing it.

① NOTE:

At this time, the OpenIndiana Vagrant box is only available in the form of a text based console. But because Vagrant supports X11 forwarding over ssh, graphical user interface applications can still be ran on this vagrant box over ssh. Additionally, Virtualbox is the only currently supported Vagrant provider. In the future the OpenIndiana project hopes to provide additional Vagrant box options.

① NOTE:

Vagrant is officially available for Mac OS X, Windows and Linux. Vagrant is currently not packaged for OpenIndiana itself, but it can be compiled from source, and it works on OpenIndiana itself as well.

- Download and install the latest version of Vagrant for your platform from the [official download page](#).
- Download and install the latest version of Virtualbox for your platform from the [official download page](#).

△ CAUTION:

Older versions of Vagrant (as packaged by many LTS Linux distributions), may not support downloading the Vagrant box instance. To work around this limitation, be sure to remove any previously installed instances of Vagrant and obtain the latest Vagrant software directly from the Vagrant website.

- Run the following command to download and boot the OpenIndiana vagrant box:

```
$ mkdir ~/openindiana_test
$ cd ~/openindiana_test
$ vagrant init openindiana/hipster
$ vagrant up --provider virtualbox
```

This will create a file titled *Vagrantfile* under the `~/openindiana_test` directory. The Vagrant box will also be booted.

- Once, the Vagrant box virtual machine is online, connect to it using the following command:

```
$ vagrant ssh
```

- To destroy the OpenIndiana Vagrant instance, issue the following command:

```
$ vagrant destroy
```

6 Preparing to Install Hipster

Prior to installing OpenIndiana:

- Ensure your system meets the recommended hardware requirements.
- Ensure to consult the HCL.

△ CAUTION:

Installing OpenIndiana on unsupported hardware may cause excessive CPU usage, instability, or other problems.

Please be sure to consult the hardware compatibility list (HCL):

- [Illumos HLC](#)
- [OpenIndiana HCL - components](#)
- [OpenIndiana HCL - systems](#)

6.1 Backing up data

△ CAUTION:

Before attempting to install OpenIndiana, first ensure you backup any important data. Do not save the data on another partition or on another disk within the same system. Instead save the data to an external device such as a USB hard drive, or external system (network backup service, or a networked system). Always verify your backed up data.

6.2 Deciding where to install OpenIndiana

By default the OpenIndiana installer creates an EFI partition using a GPT partition table. Using this option, OpenIndiana will use the entire disk. No other operating system can share the same disk.

Optionally you may use an existing zpool.

Another option is to use a legacy MBR partition. MBR partitions will allow you to create multiple partitions. MBR will also support dual booting another operating system.

Another option is to install to a virtual machine.

6.3 Gathering network information

If your network uses a DHCP server, OpenIndiana can be configured to automatically obtain it's network information. If a DHCP server is not available, then you will need to manually configure your network settings.

Obtain the following information:

- IP address
- Subnet mask
- Gateway
- Network domain name
- Network DNS servers

6.4 Downloading the software

For a full list of links to the various installer images, visit the following page:

- [OpenIndiana Downloads](#)

For a complete list of alternate mirrors (Asia, Europe, North America, etc.)

- [OpenIndiana Download Mirrors](#)

Download example:

```
$ wget
↳ "http://dlc.openindiana.org/isos/hipster/20170502/OI-hipster-gui-20170502.iso"
$ wget "http://dlc.openindiana.org/isos/hipster/20170502/OI-hipster-gui-20170502.iso"
↳ o.sha256sum"
```

6.5 Checking the MD5/SHA

Checksum verification example:

```
$ sha256sum --check OI-hipster-gui-20170502.iso.sha256sum
OI-hipster-gui-20170502.iso: OK
$
```

7 Creating a Hipster DVD

7.1 BSD/illumos/Solaris

UNIX Console

The command to use for writing a CD or DVD is `cdrecord`. The syntax of the command is:
`cdrecord dev=device imagefile.iso`

Examples:

```
# cdrecord dev=/dev/rdisk/c4t1d0p0 imagefile.iso
```

```
# cdrecord dev=4,1,0 imagefile.iso
```

❗ NOTE:

If you are re-using a DVD-RW, be sure to blank it first.

For example: `cdrecord dev=/dev/rdisk/c4t1d0p0 blank=fast`

Warning: Blanking the disk will destroy all data on the disk.

Locating your DVD or CD writing device:

- For BSD, use `cdrecord -scanbus` to locate your device.

For example:

```
$ cdrecord -scanbus
```

```
Cdrecord-ProDVD-ProBD-Clone 3.00 (i386-pc-solaris2.11) Copyright (C) 1995-2010 Jörg  
↪ Schilling
```

```
Warning: Using USCSI interface.
```

```
Using libscg version 'schily-0.9'.
```

```
scsibus4:
```

```
 4,0,0  400) 'ATA      ' 'HITACHI HTS72321' 'C50B' Disk  
 4,1,0  401) 'HL-DT-ST' 'DVD-RAM GSA-U20N ' 'HX12' Removable CD-ROM  
 4,2,0  402) *  
 4,3,0  403) *  
 4,4,0  404) *  
 4,5,0  405) *  
 4,6,0  406) *  
 4,7,0  407) *
```

```
$
```

❗ NOTE:

When using `cdrecord -scanbus` to determine the device name, specify the device using the SCSI bus ID.

For example: `cdrecord dev=4,1,0 imagefile.iso`

- For illumos/Solaris, you may use either `cdrecord -scanbus` or `rmformat -l` to locate your device.

For example:

```
$ rmformat -l
```

```
Looking for devices...
```

```
1. Logical Node: /dev/rdisk/c4t1d0p0  
   Physical Node: /pci@0,0/pci17aa,20f8@1f,2/cdrom@1,0  
   Connected Device: HL-DT-ST DVD-RAM GSA-U20N HX12  
   Device Type: CD Reader
```

```
Bus: <Unknown>
Size: 810.2 MB
Label: <None>
Access permissions: Medium is not write protected.
```

\$

❗ **NOTE:**

When using `rmformat -l` to determine the device name, specify the device using the *Logical Node*.

For example: `# cdrecord dev=/dev/rdisk/c4t1d0p0 imagefile.iso`

UNIX GUI

Use the application specific to your desktop (Brasero, K3B, etc.)

7.2 Linux

Linux Console

The command to use to write a CD or DVD on Linux is `wodim`.

The syntax of the command is: `wodim -v dev=device -dao imagefile.iso`

For example:

```
# wodim -v dev=/dev/sr0 -dao imagefile.iso
```

Locating your DVD or CD writing device:

- On Linux use the `lsblk` command to locate your device.

For example:

```
$ lsblk
NAME        MAJ:MIN RM  SIZE RO TYPE MOUNTPOINT
sda          8:0    0 232.9G  0 disk
├─sda1       8:1    0 227.8G  0 part /
├─sda2       8:2    0   1K   0 part
└─sda5       8:5    0   4G   0 part
sr0         11:0    1 1024M  0 rom
$
```

Linux GUI

There are several different CD/DVD writer applications available for Linux.

Desktop	Application
GNOME	Brasero
KDE	K3B

Other desktops may offer additional choices. For further information, please consult the help documentation for your Linux distribution.

7.3 Mac OS X

MAC Console

```
# growisofs -Z /dev/dvdrw=image.iso
```

MAC GUI

Applications > Utilities > Disk Utility

7.4 Windows

Windows Console

Isoburn is a Windows GUI utility which can be launched via the command prompt as follows:

```
ISOBurn.EXE [/Q] [<drive letter>:] <disk image file name>
```

Windows GUI

From within Windows Explorer:

- Browse to and select the ISO image file
- Right click the ISO image file
- From the right click menu, select “Burn Disk Image”

8 Creating a Hipster USB Drive

❗ NOTE:

Old versions of OpenIndiana Hipster prior to the 2016.10 release (including legacy oi-dev-151x) require a different procedure for creating bootable USB flash drives, [see this page for details](#)

⚠ CAUTION:

Although that the current OpenIndiana Hipster releases support UEFI without secure boot, old versions of OpenIndiana Hipster did not support UEFI.

- If you intend to install an old version of OpenIndiana Hipster on a system which supports UEFI boot, please boot the system in legacy (CSM) mode.

8.1 Prerequisites

- USB flash drive - (2GB or larger).
- Download the OpenIndiana USB installer image.

8.2 Identifying the path to your USB device

Operating system	Command	Device
BSD	camcontrol devlist	/dev/da*

Operating system	Command	Device
illumos/Solaris	<code>rmformat -l</code>	<code>/dev/rdisk/c*t*d*p0</code>
Linux	<code>lsblk</code>	<code>/dev/sd*</code>
MAC OS X	<code>diskutil list</code>	<code>/dev/disk*</code>

△ CAUTION:

When issuing the USB copy command:

- Make sure you identify the correct storage device as all data on the device will be erased.
- Be sure to specify the entire USB device without appending any partition or slice number.

For example:

Example	Device
Correct	<code>/dev/sda</code>
Incorrect	<code>/dev/sda1</code>
Correct	<code>/dev/rdisk/c0t0d0p0</code>
Incorrect	<code>/dev/rdisk/c0t0d0p1</code>

- In illumos, the whole disk device name is depending on partition type.
 - On x86, the whole disk name ends with p0
 - In the case of a GPT (EFI) partition, the whole disk device name ends with dX.
 - on sparc, the disk has usually VTOC partition and whole disk device name usually ends with s2.
 - Note, if on x86 and an MBR+VTOC is used, then the s2 device is addressing the Solaris2 MBR partition, not the whole disk.
- If any file systems are located on the USB storage device, they must first be unmounted.
 - Desktops may automatically mount removable devices.
 - As necessary, select any desktop icons for the USB device and issue an 'Eject' or 'Unmount' command.
 - For Linux, use `umount <path>`.
 - For illumos/Solaris use `rmumount <path>`.
 - for MAC OS X use `diskutil unmountDisk <path>`.
 - Verify using the `mount` command.

8.3 BSD/Linux/OS X

In the command below, replace x with the appropriate letter for your USB device. At least on Linux and FreeBSD you can add `status=progress` operand to print basic transfer statistics, refer to `dd(1)` man page of your platform for more information.

```
# dd bs=4M if=./image.usb of=/dev/sdX && sync
```

8.4 illumos/Solaris

In the command below, replace each x with appropriate number for your USB device.

```
# /usr/bin/dd if=./image.usb of=/dev/rdisk/cXtXdXpX bs=4194304
```

8.5 Windows

Newer releases can be written using [Win32 Disk Imager](#).

① NOTE:

By default the Win32 Disk Imager utility is looking for .img files and won't see files with a .usb extension. To resolve this issue, be sure to select the *.* (all files) option from the file extension drop down menu.

9 Booting the Hipster Installer

Insert the bootable media (DVD or USB flash drive) and boot (start/restart) your computer. When you see the OpenIndiana boot menu, select a boot entry, and press the enter key to start OpenIndiana on your computer. As it runs, you will be prompted with a few questions.

① NOTE:

For the computer to successfully boot from the media, you may be required to perform one of the following tasks:

- Specify the appropriate boot device by pressing the boot order hotkey.
- Change the boot device order found in your computer's system BIOS configuration.

△ CAUTION:

OpenIndiana supports UEFI (Unified Extensible Firmware Interface) without secure boot:

Secure boot (UEFI boot path validation) must be disabled (if it is enabled by default) because UEFI secure boot is currently not yet supported.

For further information, consult the manufacturers documentation for your computer hardware.

9.1 Booting the OpenIndiana installer on virtual hardware

The most efficient way to boot a virtual machine is to boot directly from the DVD ISO file. Alternately, you may use host to guest DVD/USB passthrough to boot from physical media. See the notes below for optimizing OpenIndiana for several popular hypervisors.

Hypervisor	Configuration Notes
Virtualbox	OS type = Solaris 11 64-bit
Vmware player	OS type = Solaris 11 64-bit

Hypervisor	Configuration Notes
KVM	OS type = Sun OpenSolaris Disk = SATA Remove USB Tablet NIC = e1000 sound = AC97 Processor = Copy host CPU configuration Disable CPU feature 'xsave' Video = VMVGA; may not be shown in virt-manager, edit XML to be as: <model type='vmvga' vram='131072' heads='1' primary='yes'/> Display = VNC (Spice not supported)
Hyper-V	Select single CPU, generation 1 VM, and legacy NIC.

❶ **NOTE:**

The OpenIndiana Project recommends the Oracle Virtualbox hypervisor as it provides the best support for illumos based distributions such as OpenIndiana.

If you experience difficulties booting OpenIndiana on virtual hardware, or find virtual hardware devices which are either not properly recognized, or fail to function as expected, please report the problem to the upstream illumos Project. You may do so by submitting an issue using the [illumos project bug tracker](#).

9.2 The OpenIndiana installer boot menu

Introduced with the Hipster 2016.10 release, the FreeBSD boot loader has been ported to OpenIndiana.

The new boot loader provides many new capabilities:

- Booting to the first disk
- Single user mode
- Debugger options

❶ **NOTE:**

The OpenIndiana installer will automatically boot option # **1. Boot Multi User** within 10 seconds.

- To pause the Autoboot timer, press the space key.

The OpenIndiana installer boot menu offers multiple choices.

Main Menu Option	Description
1. Boot Multi User	Normal boot (desktop or shell)
2. Boot Single user	Boots to rescue mode
3. Escape to loader prompt	Boots to forth shell
4. Reboot	Restarts the computer
5. Configure Boot Options	Enters into boot options menu
6. ChainLoad disk0	Boots the OS found on 1st disk

Main Menu Option	Description
7. Select OI Extras	Enters into extras menu

Select your boot option by pressing the associated number key.

- Options 1, 2, 3, 4, and 6, result in the immediate execution of the selected option.
- Options 5 and 7 provide interactive menus as shown below.

Boot Option Menu	Description
1. Back to Main Menu	Returns to main menu
2. OsConsole	Provides several tty options
3. ACPI	Toggles ACPI to ON, OFF, MADT, or Legacy
4. Single User	Toggles single user mode
5. Verbose	Toggles verbose boot messages
6. Reconfigure	Reconfigures hardware
7. kmdb	Toggles Kernel Mode Debugger
8. Debug	Toggles debug

Toggle (enable/disable) these options by selecting the associated number key.

For example:

- Pressing 5 enables verbose mode.
- Pressing 5 again, disables the verbose option.

OI Extras Menu	Description
1. Back to Main Menu	Returns to main menu
2. Vesa driver	Forces the vesa driver
3. Text console	Enables the text console
4. Enable ssh	Enables ssh server for live desktop

Toggle (enable/disable) these options by selecting the associated number key.

For example:

- Pressing 2 forces the VESA driver.
- Pressing 2 again, disables the VESA driver.

① **NOTE:**

Even when booting the Mate Live Image, selecting option # 3 (text console) option will boot the system to a text based console. The logon credentials required to access the shell are jack/jack.

9.3 Selecting keyboard layout and display language

OpenIndiana offers 47 different keyboard layouts.



Figure 1: forth_menu



Figure 2: forth_boot_menu_options



Figure 3: forth_boot_menu_extras

1. Albanian	25. Latin-American
2. Arabic	26. Lithuanian
3. Belarusian	27. Latvian
4. Belgian	28. Macedonian
5. Brazilian	29. Malta_UK
6. Bulgarian	30. Malta_US
7. Canadian-Bilingual	31. Norwegian
8. Croatian	32. Polish
9. Czech	33. Portuguese
10. Danish	34. Romanian
11. Dutch	35. Russian
12. Dvorak	36. Serbia-And-Montenegro
13. Estonian	37. Slovak
14. Finnish	38. Slovenian
15. French	39. Spanish
16. French-Canadian	40. Swedish
17. Hungarian	41. Swiss-French
18. German	42. Swiss-German
19. Greek	43. Traditional-Chinese
20. Icelandic	44. TurkishF
21. Italian	45. TurkishQ
22. Japanese-type6	46. UK-English
23. Japanese	47. US-English
24. Korean	

To select the keyboard layout, enter a number [default 47]:

Figure 4: Select keyboard layout

- Select your keyboard layout by entering the number corresponding to your desired keyboard layout.
- For example, select 18 for German, or 35 for Russian, etc.
- The default keyboard layout is selection 47 US-English.

Once you have selected a keyboard layout, press the `Enter` key to continue.

```

1. Arabic
2. Catalan
3. Chinese - Simplified
4. Chinese - Traditional
5. Czech
6. Dutch
7. English
8. French
9. German
10. Greek
11. Hebrew
12. Hungarian
13. Indonesian
14. Italian
15. Japanese
16. Korean
17. Polish
18. Portuguese - Brazil
19. Russian
20. Slovak
21. Spanish
22. Swedish
To select the language you wish to use, enter a number [default is 7]:

```

Figure 5: Select display language

OpenIndiana offers 22 different language options.

- Select a language by entering the number corresponding to your desired language.
- For example, select 3 for Chinese - Simplified, or 18 for Portuguese - Brazil, etc.
- The default language selection is 7for English.

Once you have selected a language, press the `Enter` key to continue.

❶ NOTE:

After selecting the keyboard layout and language, OpenIndiana will begin to search for hardware and configure devices. When the configuration process is complete, the system will load to either the Mate desktop, or a logon console.

9.4 The live media desktop

The Live Media DVD and USB installers provide a graphical live environment where you can explore OpenIndiana and test the compatibility of your hardware. When using Live Media, no changes are made to your system unless you explicitly choose to install OpenIndiana or alter the configuration of your disk using the Gparted Partition Editor.

The following options are available to you from the Live Media Desktop:

- Install OpenIndiana using the Text Installer
- Install OpenIndiana (graphical installer)
- Device Driver Utility
- Gparted Partition Editor

9.5 Using the device driver utility

Available from the Live Media desktop, the *Device Driver Utility* may be used to scan your hardware for compatibility. The utility generates a list of hardware devices along with the



Figure 6: live desktop

corresponding driver in use for each device. The utility will also show you devices for which there is no driver loaded. The device driver utility allows you to check whether your hardware requires additional drivers.

9.6 Using the Gparted Partition Editor

The Gparted partition editor allows you to add, remove, or resize partitions in preparation for installing OpenIndiana.

⚠ CAUTION:

Editing partition tables is a potentially destructive process. While you are unlikely to physically damage the disk, there is a risk of losing data. Before using the partition editor, please be sure to back up your data to a remote system or device.

9.7 Live media authentication

- The user login for the live media session is `jack` along with the password `jack`.
- For administrative or elevated access, prepend your commands with `sudo`.
- You may obtain root using the `su` command along with the password `openindiana`.

10 Installing OpenIndiana

📌 NOTE:

For some guidance writing this section:

- Installation walkthrough: [web link](#)
- Installation videos: [web link](#)

⚠ CAUTION:

Please be advised of the following important considerations:

- The installation overwrites the whole disk layout if one of the following is true:
 - The disk table cannot be read.
 - The disk was not previously partitioned.
- If an existing Solaris fdisk partition is on a multiboot system, and the user makes no modifications to the existing partitions, the installation overwrites the Solaris fdisk partition only. Other existing partitions are not changed.

10.1 Installing OpenIndiana from live media

To install OpenIndiana from Live Media, you have two options.

- Install OpenIndiana using the Text Installer
- Install OpenIndiana (graphical installer)

Each of these options is represented by a desktop icon. Select the appropriate installer option by clicking the corresponding desktop installer icon.

① **NOTE:**

From Hipster 2016.10 release onwards

Selecting the ***Install OpenIndiana using the Text Installer*** desktop installer option provides new installation capabilities.

In addition to installing OpenIndiana to single disks, the following are now also supported:

- Mirrors
- RAIDZ

Yes, that's right, you can now install the rpool to logical disk arrays, created during the installation process.

However, please keep in mind the following:

- This capability applies only to the python based installer which runs within a console window.
- The graphical installer does not yet have this capability.

10.2 Install OpenIndiana (graphical installer)

To launch the OpenIndiana graphical installer, locate and double click the desktop icon labeled: ***Install OpenIndiana***.

As shown below, and in the subsequent screens, the installer starts a new process, running within it's own window.

When the installer starts, the first screen you will see is the welcome page. Please take some time to read the additional guidance provided below. When ready to begin, click the ***Next*** button to continue on with the installation process.

① **NOTE:**

Please disregard the reference to the getting started guide. This guide no longer exists on the Live Media installer.

A bug has been opened for this issue and a new getting started guide is being created.

Also, when clicking the link for the release notes, please click it only once and wait until Firefox finishes loading. The Firefox web browser will open to the 'OpenIndiana Releases' page of the OpenIndiana Wiki. This however, is not where you will find the release notes. ***A bug has been opened to correct this issue.***

The release notes can be found [on the main site](#).

The top portion of the disk selection and partitioning screen shows all the disks found on the system, including removable disks. Each disk is represented with a disk icon. Below each disk icon the installer displays the size of each disk in Gigabytes (GB) and the disk type (IDE, ATA, etc.). Within this upper panel, select the disk where you wish to install OpenIndiana. The lower portion of this screen displays partitioning options.

Within the lower panel, select one of the following options:




Figure 7: First install screen



Figure 8: Disk selection and partitioning menu -1

Option	Description
Use the whole disk	When the <i>Use the whole disk</i> option is selected, the entire disk is used for the installation. For the selected disk, all existing partitions and any data which they may contain, will be overwritten with the OpenIndiana operating system.
Partition the disk	When the <i>Partition the disk</i> option is selected, the bottom portion of this panel displays the disk partitioning layout. Prior to selecting this option, please be sure to review all the informational notes and warnings concerning the use of the partitioning option.



If you choose to partition the disk, you have additional options as shown above. Please take some time to read the additional guidance provided below. When you have revised the partitioning as needed, click the **Next** button to continue.

① NOTE:

Regardless of the partitioning option chosen for the installation, manual control of the OpenIndiana file system layout is not supported. During the installation, the Solaris fdisk partition is reformatted with a default ZFS file system layout. All existing file systems on the Solaris partition are destroyed. The installation uses a Solaris fdisk partition to create a ZFS storage pool.

① NOTE:

If you choose to partition the disk, review the following partitioning guidelines, then revise the partitioning panel settings as needed.

- Only one Solaris partition is allowed. If an existing Solaris partition is available, that Solaris partition will be the target for the installation. Or, if you do not have an existing Solaris partition, you can change any existing partition to a Solaris partition.
- You can resize existing partitions, delete partitions, and create new partitions in this panel. For this option, one existing Solaris partition must be available as the target for the installation.
- If you used a third-party partitioning tool such as GParted, then the Disk panel displays a partition named Linux-swap on which you can install OpenIndiana.
 - In this panel, use the drop-down list for the Linux-swap partition name to change the partition name to Solaris.

△ CAUTION:

If the existing partition table cannot be read, a warning is displayed, and the panel displays proposed partitioning. In this case, all data on the selected disk is destroyed. If the table can be read, then the following information applies:

- The partitions are displayed in physically sequential order as they are laid out on the disk.
- Resizing a Solaris partition destroys the data on that partition and all physically subsequent partitions.
 - Existing data is not moved to conform to a new partition layout.
 - However, resizing the last partition or appending a new partition does not affect the data that already exists in other partitions.
- Non-Solaris partitions cannot be resized.
- To make additional space available, you can change an existing partition to Unused.
 - However, if you change an existing partition to Unused, all subsequent non-Solaris partitions are also changed to Unused.
- New partitions can only use the available space that follows the last defined partition.
- The installer cannot utilize unallocated chunks of space between existing defined partitions.
- Use the `fdisk(1M)` command to create new partitions that use the free space between exiting partitions.

This screen enables you to type the correct time zone, date, and time for the system to be installed. The top half of the panel displays a world map with major cities marked. The bottom



Figure 9: Time zone, date and time

half of the panel provides drop-down selections. You can choose the time zone either from the map or from the drop-down list.

- If you select the time zone from the map, click on a city or click anywhere on the map.

If you click on the map, but not on a city, the map automatically magnifies that area. You can click on a location within that magnified area. You can drag the cursor to move the magnified area to a different location on the map. When you select a site on the map, the drop-down selections automatically populate with the time zone, date, and current time for that map selection. You can right-click to undo magnification.

- Instead of using the map, you can make your selections in the drop-down fields.

Select your region, then select Location. Finally, select time zone. The options for each drop-down field are determined by the selection made in the prior drop-down field.

NOTE:

After making your selections, you may also edit the default date and time that is provided.

When the settings are correct, click Next to continue.



Figure 10: Locale

This screen enables you to select a language and locale. These selections determine the language support, the default date and time, and other data formats for the installed system.

- You can accept the default language selection or change the selection.
- A language selection is required. You can select “no default language support.”
- The language chosen automatically determines the available locales in the drop-down list. Only one locale can be selected.

NOTE:

Any time that you log in to the installed system, you can change either the locale for that particular session or the default locale by using the Options button in the Login dialog box.

OpenIndiana Installer (as superuser)

openindiana

Users

Welcome
Disk
Time Zone
Locale
Users
Installation
Finish

Enter a root password for this system.

Root password: [password field]
Confirm password: [password field] Re-enter to check for typing errors.

Create a user account for yourself.

Your real name: jackie
Log-in name: jackie Required when creating a user account.
User password: [password field]
Confirm password: [password field] Re-enter to check for typing errors.

Enter a computer name for this system.

Computer name: openindiana

Quit Help Back Next

Figure 11: Users

Review the following guidelines:

- Root login is not enabled either on the Live CD or on the installed system. You must log in as the user that you create in this panel. After you log in, you can then become root to configure the system.

NOTE:

If you do not create a user account in this panel, root is set up as a normal account on the installed system, instead of as a role. This is the only situation where you can log in to the installed system as root.

- Both the root password and user account are optional. However, for better security, do complete these fields. If the root password is not defined, a reminder is displayed when you click Next. If you do not want to define a root password, you can proceed.
- A user account requires only a Login name for the account to be valid. For better security, however, do complete all fields. If the user account information is not valid, a reminder is displayed when you click Next. If you do not want to define a user account, you can proceed.
- Type a computer name or accept the default. The computer name field cannot be blank.



Figure 12: Installation summary

This screen summarizes the configuration options which will be used to perform the installation. Be sure to take the time to review this summary. If a configuration option needs to be changed, you may do so by clicking the **Back** button. If the installation options are acceptable, click the **Install** button to begin the installation.

△ CAUTION:

Once you have clicked the **Install** button, the option to **Quit** the installation is no longer available. Do not attempt to interrupt an installation already in progress or the system will be left in an inconsistent state.



Figure 13: Installation in progress

During the installation, a progress bar is displayed. The time required to complete the installation is dependent on your hardware.

The final screen displays completion messages. From within this panel you may review the installation log. To view the installation log, click the link titled **OpenIndiana Installation Log**. The installation log will open in a new window.

Using the slider located on the right side of the log viewer window, you may scroll up and down to view the entire log file. After reviewing the log, you may exit the log viewer by clicking the **Close** button.

Congratulations! You have completed the installation of the OpenIndiana Hipster operating system.

From here you now have several options:

- Quit the installer by clicking the **Quit** button and continue to explore the Live Media.



Figure 14: Completion summary



Figure 15: Installation log

- Quit the installer by clicking the **Quit** button and then manually shut down or restart your system.
- Reboot the computer by clicking the **Reboot** button.

NOTE:

To prevent the Live Media from starting again after the reboot, eject the Live Media as the next boot begins. Or alternately, when presented with the Live Media installer options menu, select the **ChainLoad diskN** option.

① NOTE:

After you have installed OpenIndiana, if you have another operating system installed, you might need to update the loader configuration. Usually you can achieve the desired effect by chainloading partitions with other operating systems. To configure the illumos loader to show an additional entry for chainloading another loader, create a file in `/boot/conf.d` directory, containing the string `chain_disk="disk0:"`, where `disk0` is the name of disk or partition to boot from. You can get the list of available disks from loader prompt using `lsdev` command.

If you use GRUB2, you can configure it to show an entry for chainloading the illumos loader. Add the following to a file in the `/etc/grub.d` directory (usually the placeholder '40_custom' file can be used) of the Linux installation:

```
menuentry "Chainload OpenIndiana" {  
    set root=(hd0,2)  
    chainloader +1  
}
```

where `hd0,2` is the location of the partition or disk containing the illumos loader. You can list detected disks/partitions from the GRUB prompt using the `ls` command. From Linux you can run `sudo fdisk -l` to list disks and partitions. The partition 'sda2' would map to 'hd0,2' in GRUB. After making changes you must run `sudo update-grub`, this updates the auto-generated GRUB configuration stored in `/boot/grub/grub.cfg`.

10.3 Install OpenIndiana using the Text Installer

① NOTE:

The text based guided install starts and runs within a command line console. Navigation within the installer is performed by pressing specifically designated navigation keys (F2, Tab, etc.).

The instructions for performing a text based install apply to the following installation scenarios:

- Launching the text based installer icon from the Live Media (GUI) desktop.
- Beginning a text based installation by booting from the OpenIndiana text based installer.

From the 2016.10 release onwards

Mirrors and RAIDZ are now supported install options!

- To install to a mirror, select 2 or more disks.
- To install to RAIDZ, select 3 or more disks.

GUI Desktop may be added post-installation

- To install MATE Desktop Environment (using a metapackage) and enable graphical login

```
pkg install mate_install  
pkg uninstall mate_install  
svcadm enable -r /application/graphical-login/lightdm  
init 6
```



The text based installation process begins with the welcome screen, which provides the following information:

- Location of the installation log file
- Navigational guidance

① NOTE:

At any time during the installation process you may press the F6 key for context specific help.

Text installer allows you to do either usual installation or installation to existing ZFS pool.

If you are doing clean installation, when ready to begin, press the F2 key to continue.

If you intend to install OpenIndiana to existing ZFS pool, see [Install OpenIndiana to existing ZFS pool](#).

On this screen the installer displays the disks which have been discovered and are available for installation.

- Use the up and down arrow keys to navigate between the disks.
- To select a disk, press the space bar while the disk is highlighted.
- A disk is selected for installation when an asterisk appears next to the disk.

Once you have selected the appropriate disk, press the F2 key to continue.

- If your system has only a single disk, it is already selected.
- If your system has multiple disks, select the appropriate disk(s).
- To install to a mirror, select 2 or more disks.
- To install to RAIDZ, select 3 or more disks.



Figure 16: Select_Disks

① **NOTE:**

While the minimum and recommended disk sizes are technically accurate, they do not take into account periodic disk usage growth resulting from:

- ZFS snapshots
- Installation of additional software
- New boot environments automatically created when running the `pkg update` command
- New backup boot environments automatically created when running the `pkg install` command

To account for this, your disk should be at least 20GB or more.

After pressing the F2 key, you may be presented with warning shown above. If reformatting the entire disk is acceptable with you, press the Tab key to select **continue** and then press the Enter key. Otherwise press the Enter key to **cancel**.

If you select cancel, you will have the following options:

- Select another disk
- Abort the installation so you may provide remedial action such as:
- Modifying the partition table using Gparted
- Adding another disk to the system



Figure 17: GPT Warning

△ CAUTION:

If your disk contains a GPT disk label, the entire disk will be used.

- Any existing GPT partitions will be destroyed
- A new single GPT partition will be created.

This warning serves as your advisory.

① NOTE:

This screen will be available only when **2 or more disks** have been selected.

- If 2 disks have been selected, the ZFS mirror option becomes available.
- If 3 or more disks have been selected, the ZFS RAIDZ option become available.

Select between the options using the up and down arrow keys.

When ready, press the F2 key to continue.

① NOTE:

This screen will be available only when a **single disk** has been selected.

In this screen you are presented with the following choices for how to partition the disk:

- Use the whole disk (EFI)
- Use a partition of the disk (MBR)

Select between the options using the up and down arrow keys.

When ready, press the F2 key to continue.



Figure 18: ZFS) rpool options



Figure 19: Fdisk Partitions



Figure 20: Select Partition

NOTE:

This screen will be available only when the **Use a partition of the disk (MBR)** option has been selected.

This screen provides the following options:

- Select the partition where you would like to install OpenIndiana.
- Change the partition type
- Change the partition size
- Free up space by deleting a partition

Navigate the fields using the arrow keys. Change a partition type using the F5 key.

When ready, press the F2 key to continue.

NOTE:

We have illustrated this screen twice as 2 different tasks are required.

In this step you will configure the hostname.

At the top portion of the screen specify the computer name (system hostname) you wish to use. By default the computer name is **openindiana**. Using the backspace key, you may remove the default hostname and provide another hostname.

When ready, proceed to the next screen shot below where you will be provided additional guidance for completing this screen.

Network

Enter a name for this computer that identifies it on the network. It must be at least two characters. It can contain letters, numbers, and minus signs (-).

Computer Name:

Select how the wired ethernet network connection is configured.

Automatically	Automatically configure the connection
Manually	Enter the information on the following screen
None	Do not configure the network at this time

F2 Continue F3 Back F6 Help F9 Quit

Figure 21: Network 1

Network

Enter a name for this computer that identifies it on the network. It must be at least two characters. It can contain letters, numbers, and minus signs (-).

Computer Name: openindiana

Select how the wired ethernet network connection is configured.

<input checked="" type="radio"/> Automatically	Automatically configure the connection
<input type="radio"/> Manually	Enter the information on the following screen
<input type="radio"/> None	Do not configure the network at this time

F2 Continue F3 Back F6 Help F9 Quit

Figure 22: Network 2

① **NOTE:**

We have illustrated this screen twice as 2 different tasks are required.

In this step you will select your network configuration type.

After configuring the system hostname, navigate to the lower portion of the screen to select your networking configuration.

From the lower portion of this screen you have the following choices:

- Automatically configure the (networking) connection (using DHCP)
- Manually configure the network settings by entering the information on the next screen
- Do not configure the network at this time

Select between the options using the up and down arrow keys.

When ready, press the F2 key to continue.

Manually Configure: e1000g0

Enter the configuration for the this network connection. All entries, except Domain, must contain four sets of numbers, 0 to 255, separated by periods.

IP Address:	172.16.0.50	Must be unique for this network
Netmask:	255.255.255.0	Your subnet use may require a different mask
Gateway:	172.16.0.1	The IP address of the gateway on this subnet
DNS:	172.16.0.1	A DNS server was found on the network
Domain:	home.local	The network's domain name

F2 Continue F3 Back F6 Help F9 Quit

Figure 23: Network 3

① **NOTE:**

This screen will be available only when the **Manually** configure network option has been selected.

- The values illustrated above are for example only, do not use them.
- Substitute each field with correct values for your network.

In the fields provided, enter in the following information:

- IP Address
- Netmask
- Gateway

- DNS
- Domain

Navigate between the fields using the up and down arrow keys.

When ready, press the F2 key to continue.



Figure 24: Time Zone - Region

The next few screens illustrate time zone configuration.

Select your time zone **region** by navigating up and down with the arrow keys.

When ready, press the F2 key to continue.

① **NOTE:**

When selecting the **UTC/GMT** time zone region, only this screen will be presented.

Select your time zone **location** by navigating up and down with the arrow keys.

When ready, press the F2 key to continue.

Select your **time zone** by navigating up and down with the arrow keys.

When ready, press the F2 key to continue.

In this screen you may reconfigure the date and time as necessary.

Using the up and down arrow keys, navigate between the fields.

When ready, press the F2 key to continue.

In this screen you are presented with several fields to configure.

- Root password




Figure 25: Time Zone - Location




Figure 26: Time Zone

Date and Time

Edit the date and time as necessary.
The time is in 24 hour format.

Year: 2016 (YYYY)
Month: 11 (1-12)
Day: 23 (1-30)
Hour: 17 (0-23)
Minute: 38 (0-59)

F2 Continue F3 Back F6 Help F9 Quit

Figure 27: Date and Time

Users

Define a root password for the system and user account for yourself.

System Root Password

Root password: *****
Confirm password: *****

Create a user account

Your real name: Jackie
Username: Jackie
User password: *****
Confirm password: *****

F2 Continue F3 Back F6 Help F9 Quit

Figure 28: Users

- Confirm Root password
- Real name
- User name
- User password
- Confirm user password

Using the up and down arrow keys, navigate between the fields and enter the required information.

When ready, press the F2 key to continue.

NOTE:

- The first user created on the system is granted the root role via *Role Based Access Control (RBAC)*.
- In effect this means the following:
 - Without any further configuration, the specified user will be granted the authority to perform administrative task by assuming the root role as needed.

Please take note the following additional information:

- Immediately after installation the root password is automatically expired and needs to be changed prior to being used for any administrative task.



Figure 29: Installation Summary

Now that you have completed the installation configuration, you are presented with an *Installation Summary*.

If these configuration settings are correct, you may begin the installation by pressing the F2 key.

Depending on the speed of your computer, the installation may take several minutes to complete. Installation progress is measured by means of a status bar.



Figure 30: Transferring Contents



Figure 31: Installation Complete

When the installation is complete, a summary screen is presented.

- The installation logs are available by pressing the F4 key.
- If you ran the installation from Live Media, you may exit the installation by pressing the F9 key.
- Otherwise, you will want to reboot the system by pressing the F8 key.



```
Installation Log
^
<ICT Nov 23 23:00:08> current task:enable_nwam
<ICT Nov 23 23:00:09> current task:remove_specific_packages
<ICT Nov 23 23:03:12> current task:set_flush_content_cache_false
<ICT Nov 23 23:03:14> current task:set_root_password
<ICT Nov 23 23:03:14> current task:create_new_user
<ICT Nov 23 23:03:14> current task:set_homedir_map
<ICT Nov 23 23:03:14> current task:setup_rbac
<ICT Nov 23 23:03:14> current task:setup_sudo
<ICT Nov 23 23:03:14> current task:copy_capability_file
<ICT Nov 23 23:03:14> current task:reset_image_uuid
<ICT Nov 23 23:03:19> current task:update_boot_archive
<ICT Nov 23 23:03:33> bootadm update-archive output: ['updating
/a//platform/i86pc/boot_archive', 'updating
/a//platform/i86pc/amd64/boot_archive']
<ICT Nov 23 23:03:33> Post-transfer Python Install Completion Tasks
finished.
<ICT Nov 23 23:03:33> All 29 Python ICTs finished successfully
<ICT Nov 23 23:03:33> current task: ict_snapshot
<ICT Nov 23 23:03:34> ict_snapshot Succeeded
<ICT Nov 23 23:03:34> current task: ict_mark_root_pool_ready
F3 Back
```

Figure 32: Installation Logs

If you chose to view the installation logs, you will be presented with the screen above.

To return to the summary screen, press the F3 key.

10.4 Installing OpenIndiana using the text installer (DVD ISO or USB)

The text installer DVD ISO and USB installer options are not graphical nor do they provide a live environment. When booting from the text based installer, you are presented with the following choices:

- Install OpenIndiana
- Spawn a shell to be used as a rescue disk.

The procedure for installing from the text based installer follows the same process as the previously described [Install OpenIndiana using the Text Installer](#)

10.5 Install OpenIndiana to existing ZFS pool

Starting from OpenIndiana 2017.10, the text installer allows you to perform installation to existing ZFS pool. It will create new boot environment in the pool and install OpenIndiana there.

This option can be useful when you want to do some customizations to root ZFS pool (for example, enable compression) or install OpenIndiana to pool where another operating system is already installed (for example, prior version of OpenIndiana or even FreeBSD). It is recommended to use minimal or server installation images to perform such installations.

❗ **NOTE:**

This feature is intended for advanced users. It's assumed you know what you are doing. Multi-booting of another operating system and OpenIndiana on the same root pool can be possible, but such configuration is out of scope of this tutorial and is not supported.

❗ **NOTE:**

OpenIndiana supports booting from a RAIDZ pool, however you must confirm that all vdevs are accessible from the boot loader. From the boot loader menu, choose Escape to loader prompt and run lsdev to confirm the disks are present.

To start installation to existing ZFS pool, press F5 key when **Welcome Screen** is presented. Installer will present you a 'Pools' screen.



Figure 33: Pools Screen

On this screen installer will allow you to select the root pool for your new installation and boot environment name (which should be unique).

By default installer will install OpenIndiana boot loader and activate created boot environment. If you don't want installer to touch any boot-related options, uncheck `overwrite pool's boot`

configuration checkbox. This can be useful when you install OpenIndiana to ZFS pool where another operating system is already installed and you want to configure boot loader manually.

If you don't see your pool in the list of available pools, check `/tmp/install_log`. The most frequent issue is that there's not enough free space in the pool.

The next steps for **usual installation** and installation to existing ZFS pool are the same.

As there's possibly already another OS instance installed to the selected ZFS pool, no additional users or filesystems (like `rpool/export`) are created during installation. Swap and dump ZFS volumes also are not created and should be added manually after installation. Only root user will be available in created boot environment.

11 Troubleshooting Installations

- If you do not see a menu after booting your computer with the DVD or USB device, and instead see some text and a `boot:` prompt, there may be an error in your copy of the installer, or it was created incorrectly.
- If you see a `login:` prompt after selecting your keyboard and language and no desktop appears after several seconds, there may be a problem with the drivers for your graphics hardware.
- Please let us know via IRC or the mailing list if this happens.
- When you contact us, please include any error messages you see on the console, as well as the output of the `svcs -xv` command.
- If possible, also include the contents of the file `/var/log/Xorg.0.log`.

12 Post Installation Steps

12.1 Boot Menu - Post Install

After successfully installing OpenIndiana Hipster, a new boot menu option becomes available. As shown in the screen below, option # 6 allows you to select the boot environment.

Each time you perform an update of software installed on OpenIndiana Hipster, a new boot environment may be created. Option # 6 allows you to select from among them.

After using OpenIndiana for a period of time, several boot environments will accumulate, with the label for each environment incrementing numerically. The image above illustrates what this looks like on a system with several boot environment choices.

12.2 Resetting the root password

After installation, the root password is immediately expired and you will be required to change it.

Use the following steps to change the root password:

- Open a Terminal
- Execute `su -` and provide the password you chose for your account at installation time
- You will be informed that root's password has expired and prompted to change it



Figure 34: forth_menu



Figure 35: forth_menu

- Once changed you can exit the su session
- You should be able to login/authenticate as root now.

13 Image Package System (IPS)

① NOTE:

The image packaging system is delivered as part of the OpenIndiana userland. As such, the pkg related man pages are not available on the illumos.org website. These pages are only available by running the man page viewer locally on your system.

13.1 Introduction

After an initial installation of the OpenIndiana Hipster operating system, you will find many of the software applications you use on a regular basis are not immediately available to you. These software applications are available as packages in a remote Image Packaging System (IPS) repository for downloading and installing over the Internet.

Written in Python, IPS is a network-centric packaging system which enables users to connect to a remote repository for the purpose of downloading and installing packages. OpenIndiana Hipster uses IPS for its packaging system.

Besides installing packages from a repository, users can also perform the following tasks:

- Create and publish their own IPS packages
- Set up an OpenIndiana Hipster repository
- Mirror an existing repository
- Publish existing packages to a repository

Once you have installed packages, IPS enables you to search, update, and manage those packages on your system.

With IPS, you can upgrade your system to a newer build of OpenIndiana Hipster, install and update your software to the latest available versions, and retrieve packages from mirror repositories.

If the system on which IPS is installed is located on a network, IPS can automatically access the OpenIndiana Hipster package repository. For OpenIndiana Hipster, your IPS client can access the packages from <https://pkg.openindiana.org/hipster>.

13.2 IPS packages

An IPS package is defined as a collection of files, directories, links, drivers and dependencies in a defined format.

Note the following points about IPS packages:

- An IPS package consists of a set of actions. Actions are defined when an IPS package is created. Actions are used for defining the files and directories of the package, setting package attributes, declaring dependencies on other packages, creating users and groups, and installing device drivers. Some actions may optionally have tags that

provide meta information about the action such as locale information and debug configuration.

- IPS packages can only be installed from an IPS repository.
- IPS package repositories can be local to the system or on a remote networked system.

13.3 IPS commands

The Image Packaging System software provides the following commands:

Command	Description
pkg1	Use the <code>pkg1</code> command to create an image, to install packages to your image, and to manage packages on your image.
pkgsend1	Use the <code>pkgsend1</code> command to publish packages from your image to an existing repository.
pkg.depotd1M	Use the <code>pkg.depotd1M</code> command to create and manage your own network repository or set up a mirror repositories.
pkgrecv	Use the <code>pkgrecv</code> command to download the contents of a package from a server. The user can then modify the contents by adding additional package attributes and republish the package with the <code>pkgsend</code> command.

❗ NOTE:

- The `pkg5` man page describes the overall Image Packaging System.
- The `pkg1` man page describes the Image Packaging System retrieval client.

13.4 pkg1 uses FMRI

Each IPS package is represented by a *Fault Management Resource Identifier* (FMRI). The `pkg1` command uses valid FMRI package information to perform its command actions. The FMRI includes descriptive information about the package, such as the package name, version information, and date.

For example:

FMRI: `pkg://openindiana.org/image/editor/gimp@2.8.16-2016.0.0.0:20160702T042138Z`

- Scheme – `pkg`
- Authority – `openindiana.org`
- PackageName – `gimp`
- Version String – Consists of three components :
- Build Version – `2.8.16`
- Branch Version – `2016.0.0.0`
- Timestamp – `20160702T042138Z`

13.5 Finding help with pkg

The primary source of help for any OpenIndiana command is to review the man page for the command. Therefore, be sure to consult the `pkg1` man page for full command information and usage examples.

For example: `man pkg`

To reference command usage directly from the command line, use `pkg help`.

For example:

```
pkg help
```

Usage: `pkg [options] command [cmd_options] [operands]`

The following commands are supported:

Package Information	: list	search	info	contents
Package Transitions	: update	install	uninstall	
	history	exact-install		
Package Maintenance	: verify	fix	revert	
Publishers	: publisher	set-publisher	unset-publisher	
Package Configuration:	mediator	set-mediator	unset-mediator	
	facet	change-facet		
	variant	change-variant		
Image Constraints	: avoid	unavoid	freeze	unfreeze
Image Configuration	: refresh	rebuild-index	purge-history	
	property	set-property	add-property-value	
	unset-property	remove-property-value		
Miscellaneous	: image-create	dehydrate	rehydrate	

For more info, run: `pkg help <command>`

To retrieve information about a specific command use: `pkg help [command]`

For example:

```
pkg help update
```

Usage:

```
pkg update [-fnvq] [-C n] [-g path_or_uri ...] [--accept] [--ignore-missing]
  [--licenses] [--no-be-activate] [--no-index] [--no-refresh]
  [--no-backup-be | --require-backup-be] [--backup-be-name]
  [--deny-new-be | --require-new-be] [--be-name name]
  [-r [-z image_name ...] | -Z image_name ...]]
  [--sync-actuators | --sync-actuators-timeout timeout]
  [--reject pkg_fmri_pattern ...] [pkg_fmri_pattern ...]
```

13.6 Searching for packages

The `pkg search` command is used to search locally or remotely for information about packages. The syntax of the command is `pkg search [options] [package]`. If no search options are specified, the command defaults to performing a search of all the remote repositories defined on the system. Using the `-l` option, you may restrict the search to the local system.

For example:

```
pkg search xchat
```

INDEX	ACTION	VALUE	PACKAGE
pkg.summary	set	XChat IRC Client	
	↪	pkg:/desktop/irc/xchat@2.8.8-2016.0.0.5	
pkg.summary	set	HexChat is an IRC client based on XChat	
	↪	pkg:/desktop/irc/hexchat@2.12.1-2016.0.0.1	
basename	file	usr/bin/xchat	
	↪	pkg:/desktop/irc/xchat@2.8.8-2016.0.0.5	
com.oracle.info.name	set	xchat	
	↪	pkg:/desktop/irc/xchat@2.8.8-2016.0.0.5	
pkg.fmri	set	openindiana.org/desktop/irc/xchat	
	↪	pkg:/desktop/irc/xchat@2.8.8-2016.0.0.5	

As you can see, the search results include package names along with additional information. To search for package names only, include the `-p` option.

For example:

```
pkg search -p xchat
```

PACKAGE	PUBLISHER
pkg:/desktop/irc/hexchat@2.12.1-2016.0.0.1	openindiana.org
pkg:/desktop/irc/xchat@2.8.8-2016.0.0.5	openindiana.org

NOTE:

When using the `pkg search` command, remember it works much like the Unix `find` command. If you have difficulty finding a package you know should exist, try modifying your search by including wildcards.

The `pkg search` command may also be used to find the package containing a particular file.

For example:

```
pkg search -l /usr/bin/gpg2
```

INDEX	ACTION	VALUE	PACKAGE
path	file	usr/bin/gpg2	pkg:/crypto/gnupg@2.0.28-2016.0.0.0

13.7 Listing the status of packages

To list the status of locally installed packages, use the `pkg list [package]` command.

For example:

```
pkg list bash
```

NAME (PUBLISHER)	VERSION	IFO
shell/bash	4.3.46-2016.0.0.0	i--

NOTE:

To list all the packages installed on the local system, use `pkg list` without specifying a package.

13.8 Listing information about packages

To list detailed information about a locally installed package, use the `pkg info [package]` command. If the package is not installed on the local system, use the `-r` option to search the remote repositories defined on the system.

For example:

```
pkg info -r gimp
```

```
Name: image/editor/gimp
Summary: The Gimp image editor
Category: Applications/Graphics and Imaging
State: Not installed
Publisher: openindiana.org
Version: 2.8.16
Branch: 2016.0.0.2
Packaging Date: July 30, 2016 12:04:41 AM
Size: 65.01 MB
FMRI: pkg://openindiana.org/image/editor/gimp@2.8.16-2016.0.0.2:20160730T000441Z
Project URL: http://www.gimp.org/
Source URL: http://download.gimp.org/pub/gimp/v2.8/gimp-2.8.16.tar.bz2
```

13.9 Listing the contents of packages

To list the entire contents of a package, use the `pkg contents [package]` command. If the package is not installed on the local system, use the `-r` option to search the remote repositories defined on the system.

13.10 Listing the dependencies of packages

The `pkg contents` command can also be used to list the dependencies found in a package. If the package is not installed on the local system, be sure to include the `-r` option.

For example:

```
pkg contents -r -t depend -o fmri xchat
```

```
FMRI
pkg://library/desktop/gdk-pixbuf@2.31.6-2016.0.0.0
pkg://library/desktop/gtk2@2.24.30-2016.0.0.0
pkg://library/desktop/libsexy@0.1.11-2016.0.0.0
pkg://library/desktop/pango@1.36.8-2016.0.0.2
pkg://library/glib2@2.43.4-2016.0.0.3
pkg://library/security/openssl@1.0.2.8-2016.0.0.3
pkg://runtime/perl-522@5.22.1-2016.0.0.1
```

```
pkg:/runtime/python-27@2.7.12-2016.0.0.0
pkg:/runtime/tcl-8@8.5.19-2016.0.0.1
pkg:/system/library/libdbus-glib@0.100.2-2016.0.0.0
pkg:/system/library@0.5.11-2016.0.0.15685
pkg:/x11/library/libx11@1.6.3-2016.0.0.0
```

13.11 Installing packages

Use the following command to install a package.

```
pkg install [options] [packages]
```

Some commonly used options are:

Option	Description
-v	Issue verbose progress messages
-n	Perform a dry run (no actual changes are made)
-q	Hides progress messages

For example:

```
pkg install xchat
```

```
    Packages to install:  1
```

```
    Packages to update:  1
```

```
    Services to change:  2
```

```
    Create boot environment:  No
```

```
Create backup boot environment: Yes
```

DOWNLOAD	PKGS	FILES	XFER (MB)	SPEED
Completed	2/2	38/38	2.6/2.6	746k/s

PHASE	ITEMS
Removing old actions	4/4
Installing new actions	69/69
Updating modified actions	2/2
Updating package state database	Done
Updating package cache	1/1
Updating image state	Done
Creating fast lookup database	Done

① NOTE:

- The `pkg install` command is also used to update specific packages on the system.
- The `pkg install` command automatically checks for newer versions of specific packages or package groups and installs them if they are available. Any dependent packages are also automatically updated.
- To install a specific version of a package you may substitute the common name for the FMRI.

13.12 Updating packages

The command to use for updating packages on the system is:

```
pkg update [options] [packages]
```

Some commonly used options are:

Option	Description
-v	Issue verbose progress messages
-n	Perform a dry run (no actual changes are made)
-q	Hides progress messages

To update all the packages installed on a system to their latest available version, use the `pkg update` command without specifying any package names.

For example:

```
pkg update
```

```

    Packages to remove:    4
    Packages to install:   11
    Packages to update: 1018
    Packages to change:    2
    Mediators to change:   1
    Create boot environment: Yes
    Create backup boot environment: No
```

DOWNLOAD	PKGS	FILES	XFER (MB)	SPEED
Completed	1035/1035	7502/7502	303.4/303.4	886k/s

PHASE	ITEMS
Removing old actions	3931/3931
Installing new actions	6889/6889
Updating modified actions	11999/11999
Updating package state database	Done
Updating package cache	1022/1022
Updating image state	Done
Creating fast lookup database	Done

A clone of `openindiana-1` exists and has been updated and activated.
On the next boot the Boot Environment `openindiana-2` will be mounted on `'/'`. Reboot when ready to switch to this updated BE.

13.13 Removing packages

To remove a package from the system, use the command: `pkg uninstall [options] [packages]`

13.14 Downgrading packages

In addition to installing, upgrading, and removing packages, it is also possible to downgrade packages. To downgrade packages, use the `pkg update` command and specify the versions of the packages you wish to install. Where the package has dependencies, you will need to specify the versions of the dependencies as well. The `pkg` utility will remove the newer versions and replace them with the versions you have specified.

For example:

```
pkg update pkg://userland/library/audio/gstreamer@0.10.36 \  
library/audio/gstreamer/plugin/base@0.10.36 \  
library/audio/gstreamer/plugin/good@0.10.31
```

❗ NOTE:

The OpenIndiana project uses package incorporations to ensure packages are maintained to specific versions. Where packages are included in an incorporation, it is not possible to revert to an earlier (or newer) version of the package without first relaxing the restrictions imposed by the incorporation. Where packages are not restricted by an incorporation, you may freely revert to earlier package versions.

To relax the restrictions on a package, the `pkg change-facet` command is used.

The syntax of the command is `pkg change-facet facet.version-lock.[package]=false`

For example:

```
pkg change-facet facet.version-lock.library/security/gstreamer=false
```

13.15 IPS package repositories

As previously mentioned, the IPS repository is the remote network location where IPS packages reside. Below is a list of commands for adding, removing, or replacing repositories.

Task	Command
List configured repositories	<code>pkg publisher</code>
Add a repository	<code>pkg set-publisher -g <repository_URL> <repository_name></code>
Remove a repository	<code>pkg set-publisher -G <repository_URL> <repository_name></code>
Replace a repository	<code>pkg set-publisher -G <old_repository_URL> -g <new_repository_URL> <repository_name></code>

Example (Listing the repositories configured on the system):

```
pkg publisher
```

PUBLISHER	TYPE	STATUS	P	LOCATION
openindiana.org	origin	online	F	https://pkg.openindiana.org/hipster/
hipster-encumbered	origin	online	F	
↪ https://pkg.openindiana.org/hipster-encumbered/				

Example (Replacing a repository):

```
pkg set-publisher \  
-G http://pkg.openindiana.org/hipster-2015 \  
-g https://pkg.openindiana.org/hipster openindiana.org
```

13.16 Listing information about repositories

While the `pkgrepo` command is primarily used for creating and working with IPS repositories. It can also be used for querying the contents of a repository.

For example:

```
pkgrepo info -s https://pkg.openindiana.org/hipster/
```

PUBLISHER	PACKAGES	STATUS	UPDATED
openindiana.org	3692	online	2016-08-21T07:03:11.566484Z

If you want to directly query the remote repository for a full list of all available packages, you can do so using the `pkgrepo list` command.

- `pkgrepo list -s <repo_URL>`

Do keep in mind you may want to filter the output of the command in some way to keep the list more manageable. If not, you're likely to see thousands of lines scroll through your console window.

13.17 IPS package repository precedence

When multiple remote IPS repositories are associated with a system and when using the `pkg` command-line interface with only package names, the following rules apply. These rules can be overridden by using explicit publishers and package version numbers.

Package Installation Type	Rules When Only Package Names Are Provided
New package installations	The latest available version of new packages are always installed from the preferred publisher unless the publisher is provided in the FMRI during installation. Even if later versions of the package are available in other publishers, those later versions are not installed by default.

Package Installation Type	Rules When Only Package Names Are Provided
Package updates: package originally installed from preferred publisher	If the package was originally installed from the preferred publisher, then the latest available update of the package can be installed from the <i>current</i> preferred publisher. The package can be install from the <i>current</i> preferred even if the preferred publisher designation had been moved to another publisher after the package had been originally installed. Even if later versions of the package are available in other publishers, those later versions are not installed by default.
Package updates: package originally installed from non-preferred publisher	If the package was originally installed from a non-preferred publisher, then the latest available update of the package is installed from the publisher from which the package was originally installed. Even if later versions of the package are available in other publishers, those later versions are not installed by default.

13.18 Listing package history

To list the IPS transactional history, use the `pkg history` command.

For example:

```
pkg history
```

START	OPERATION	CLIENT	OUTCOME
2016-04-21T03:30:04	purge-history	pkg	Succeeded
2016-07-02T16:09:56	uninstall	pkg	Succeeded
2016-07-02T16:10:33	uninstall	pkg	Succeeded
2016-07-02T16:11:08	uninstall	pkg	Succeeded
2016-07-02T16:11:42	uninstall	pkg	Succeeded
2016-07-02T16:12:18	set-property	pkg	Succeeded
2016-07-02T16:12:22	set-property	pkg	Succeeded
2016-07-02T16:37:06	refresh-publishers	pkg	Succeeded
2016-07-02T16:37:06	update	pkg	Succeeded
2016-07-02T16:37:32	rebuild-image-catalogs	pkg	Succeeded
2016-07-02T17:33:44	install	pkg	Succeeded
2016-07-02T17:35:11	install	pkg	Succeeded
2016-07-02T18:31:39	install	pkg	Succeeded
2016-07-04T19:49:19	install	pkg	Succeeded
2016-07-04T19:49:23	refresh-publishers	pkg	Succeeded
2016-07-04T19:49:56	rebuild-image-catalogs	pkg	Succeeded
2016-07-09T01:16:43	install	pkg	Succeeded

2016-07-09T01:16:45	refresh-publishers	pkg	Succeeded
2016-07-09T01:17:20	rebuild-image-catalogs	pkg	Succeeded
2016-07-09T11:33:05	install	pkg	Succeeded
2016-07-09T11:33:07	refresh-publishers	pkg	Succeeded
2016-07-09T11:33:37	rebuild-image-catalogs	pkg	Succeeded
2016-07-09T12:27:23	update	pkg	Succeeded

To view more details of a particular IPS transaction, use the command:

```
pkg history [-l] [-t time_stamp]
```

For example:

```
pkg history -l -t 2016-07-09T11:33:05
```

- The `-l` option provides comprehensive details of each transaction
- The `-t` option allows you to specify a particular transaction

13.19 IPS package archives (.p5p)

When the IPS system was originally conceived there was no standard on-disk format for an IPS package. Hence, unlike a `.rpm` file, an SVR4 package, or a `.nbm` file, it was not possible to transfer IPS packages from system to system. The remote IPS repository where the IPS package resided was the only source for the package. This is because in its native state, the IPS package is not something you can normally download as a single archive file.

Recognizing this limitation of IPS, the `.p5p` IPS archive format was developed. For IPS archives, files are stored in the pax archive format, along with additional metadata, such as IPS manifest files, and a specific layout of the contents.

IPS `p5p` archives are not like Linux packages where you can install software directly from the package. Instead `p5p` archives are a portable repository format containing a collection of packages. This allows you to create `p5p` archives for transfer to non-networked systems. IPS package archives are also useful for sharing packages for the purpose of testing.

IPS archives allow you to:

- Download one or more packages (along with all necessary dependencies) into a `p5p` archive file.
- Create a local repository based on the contents of the `p5p` archive file.
- Install packages from the locally created repository.

13.19.1 Creating the `p5p` package

To create an IPS archive, the `pkgrecv` command is used.

For example, to create a `.p5p` IPS package archive containing the package `userland/web/browser/firefox` and all of its dependencies from the repository located at `http://example.com:10000`, use the following command:

```
pkgrecv -s http://example.com:10000 -d ~/firefox_test.p5p -a -r
↪ pkg://userland/web/browser/firefox@45.3.0-2016.0.0.0:20160817T064143Z
```

13.19.2 Listing the contents of a p5p package

There are at least two different ways to view the contents of an IPS archive.

```
pkgrepo -s ~/firefox_test.p5p list
```

```
PUBLISHER NAME                                O VERSION
userland  library/expat
↳ 2.1.0-2015.0.1.1:20150901T125810Z
userland  library/glib2
↳ 2.43.4-2016.0.0.4:20160705T121550Z
userland  library/glib2/charset-alias
↳ 2.43.4-2016.0.0.4:20160705T121609Z
userland  system/library/fontconfig
↳ 2.11.95-2016.0.0.0:20160512T122747Z
userland  web/browser/firefox
↳ 45.3.0-2016.0.0.0:20160817T064143Z
userland  x11/library/toolkit/libxt
↳ 1.1.4-2016.0.0.0:20160706T165209Z
```

This also works:

```
pkg list -f -g ~/firefox_test.p5p
```

NAME (PUBLISHER)	VERSION	IFO
library/expat (userland)	2.1.0-2015.0.1.1	---
library/glib2 (userland)	2.43.4-2016.0.0.4	---
library/glib2/charset-alias (userland)	2.43.4-2016.0.0.4	---
system/library/fontconfig (userland)	2.11.95-2016.0.0.0	---
web/browser/firefox (userland)	45.3.0-2016.0.0.0	---
x11/library/toolkit/libxt (userland)	1.1.4-2016.0.0.0	---

13.19.3 Adding the package as a local repository

```
pkg set-publisher -p firefox_test.p5p
```

13.19.4 Installing software from the local repository

```
pkg install firefox@45.3.0-2016.0.0.0:20160817T064143
```

13.20 Legacy package management tools

OpenIndiana continues to support the use of legacy package tools for managing SVR4 packages. Here are some of the available tools:

- pkginfo
- pkgadd
- pkgrm

13.21 3rd party package management tools

① NOTE:

ITEMS TO WRITE ABOUT:

- Need to answer the question “Where and how can I install more software?”
- Discuss 3rd party package managers ([pkgin](#), etc.)
- Discuss the various 3rd party repos, what’s available in them, and which might break compatibility, etc.:
 - [pkgsrc](#) ([wiki page](#), [NetBSD wiki page](#))
 - Joyent’s [pkgsrc binary packages](#) ([install on illumos](#), [wiki page](#))
 - [opencsw](#)
 - [SFE \(spec-files-extra\)](#) ([wiki page](#), [other wiki page](#)): describe and explain how it differs from OI and other repos.
- How to add additional repos, etc.
- How to compile your own software.
 - Existing wiki pages: [Knowledge base](#), [Compiling software on OpenIndiana](#)
 - Also could look here (might be outdated): [Compiling Software on Solaris](#)
- Given the limited number of IPS packages currently available, these are pretty important subjects to write about.

In addition to IPS and SVR4 package management tools, it is also possible to use `pkgsrc`.

For more information about `pkgsrc`, see the [Joyent package source website](#).

△ CAUTION:

The use of 3rd party repositories and package managers increases the likelihood of conflicts between package versions and their dependencies. Furthermore, the OpenIndiana project cannot guarantee the quality of packages obtained from 3rd party repositories. Therefore, use 3rd party repositories and 3rd party package tools at your own risk.

14 Managing Boot Environments

A boot environment is a bootable instance of an OpenIndiana operating system image plus any other application software packages installed into that image. You can maintain multiple boot environments on your system, and each boot environment could have different software versions installed. Upon the initial installation of OpenIndiana onto your system, a boot environment is created. Use the `beadm1M` utility to administer additional boot environments on your system.

The `beadm` utility is designed to work in concert with the ZFS file system and the IPS package manager.

14.1 Why use multiple boot environments?

With multiple boot environments, the process of updating software becomes a low risk operation because you can create backup boot environments before making any software updates to your system. If needed, you have the option of booting a backup boot environment.

Here are some specific examples where having more than one OpenIndiana boot environment, and managing them with the `beadm` utility, is useful:

- When you use the `pkg update` command to update all the packages in your active OpenIndiana boot environment, this process automatically creates a clone of that boot environment. The packages are updated in the clone rather than in the original boot environment. After successfully completing the updates, the new clone is activated. Then, the clone will become the new default boot environment on the next reboot. You can boot the original boot environment explicitly selecting it from loader menu. `beadm list` command can be used to see a list of all boot environments on the system, including the backup boot environment that still has its original, unchanged software. If you are not satisfied with the updates made to the environment, you can use the `beadm activate` command to specify that the backup will become the default boot environment on the next reboot.
- If you are modifying a boot environment, you can take a snapshot of that environment at any stage during modifications by using the `beadm create` command. A snapshot is a read-only image of a dataset or boot environment at a given point in time. You can create custom names for each snapshot that identify when or why the snapshot was created. For example, if you are doing monthly upgrades to your boot environment, you can capture snapshots for each monthly upgrade. You can use the `beadm list -s` command to view the available snapshots for a boot environment. A snapshot is not bootable. But, you can create a boot environment, based on that snapshot, by using the `-e` option for the `beadm create` command. Then you can use the `beadm activate` command to specify that this boot environment will become the default boot environment on the next reboot.
- You can maintain more than one boot environment on your system, and perform various upgrades on each of them as needed. For example, you can clone a boot environment by using the `beadm create` command. A clone is a bootable copy of a boot environment. Then, you can install, test, and update different software packages on the original boot environment and on its clone. Although only one boot environment can be active at a time, you can mount an inactive boot environment by using the `beadm mount` command. Then you can use the `pkg update` command with the `-R` option to update all the packages in that inactive, mounted environment. Or, use the `pkg install packagename` with the `-R` option to update specific packages on that environment.

① NOTE:

When `pkg` creates new boot environment, it determines its name using `auto-be-name` image property. When prefixed with “time:” string, the remaining part of property is interpreted as `strftime(3C)` argument. If `pkg` can’t produce unique boot environment name based on `auto-be-name` image property, it uses the property as base to generate unique name, appending numerical suffix prefixed by “-” symbol. Note, that due to name generation rules, any numerical suffix, prefixed by “-”, can be incremented to generate unique name, so given “time:openindiana-%Y-%m-%d” `auto-be-name` image property value (which is not recommended), `pkg` will produce boot environment names ending with current date, current date + 1 and so on. By default `auto-be-name` is set to “time:openindiana-%Y-%m-%d”, so that boot environments are named like “openindiana-2019:03:29”. You can get current value using `pkg property` command and set it with `pkg set-property`.

14.2 Features of the beadm utility

The beadm utility has the following features:

- The beadm utility aggregates all datasets in a boot environment and performs actions on the entire boot environment at once. You no longer need to perform ZFS commands to modify each dataset individually.
- The beadm utility manages the dataset structures within boot environments. For example, when the beadm utility clones a boot environment that has shared datasets, the utility automatically recognizes and manages those shared datasets for the new boot environment.
- The beadm utility enables you to perform administrative tasks on your boot environments. These tasks can be performed without upgrading your system.
- The beadm utility manages and updates the `<root pool>/boot/menu.lst` file used by loader to list boot environments. When you use the beadm utility to create a new boot environment, that environment is automatically added to this file.

The beadm utility enables you to perform the following tasks:

- Create a new boot environment based on the active boot environment
- Create a new boot environment based on an inactive boot environment
- Create a snapshot of an existing boot environment
- Create a new boot environment based on an existing snapshot
- Activate an existing, inactive boot environment
- Mount a boot environment
- Unmount a boot environment
- Destroy a boot environment
- Destroy a snapshot of a boot environment
- Rename an existing, inactive boot environment
- Display information about your boot environment snapshots and datasets

14.3 beadm command reference

Command	Description
beadm	Displays command usage
beadm activate <BE>	Makes the specified boot environment the active boot environment upon the next reboot.
beadm create <BE>	Creates a new boot environment with the name specified. Unless the <code>-e</code> option is provided, the new boot environment is created as a clone of the currently running boot environment.
beadm create <BE@snapshot>	Creates a snapshot of the existing boot environment with the specified snapshot name.

Command	Description
<code>beadm destroy <BE></code>	Destroys the boot environment named BE or destroys an existing snapshot, BE@snapshot, of a boot environment. Prompts for confirmation before destroying the boot environment.
<code>beadm list <BE></code>	Lists information about the specified boot environment, or lists information for all boot environments if a boot environment name is not provided. The default is to list boot environments without any additional information.
<code>beadm mount <BE> <mountpoint></code>	Mounts the specified boot environment at the specified mount point. The mount point must be an already existing, empty directory.
<code>beadm rename <old BE> <new BE></code>	Renames the specified boot environment.
<code>beadm unmount [-f] <BE></code>	Unmounts the specified boot environment. -f – Forcefully unmounts the boot environment even if it is currently busy.

For detailed instructions about the `beadm` utility, see the `beadm1M` man page.

14.4 beadm zones support

Zones partitioning technology is used to virtualize operating system services and provide an isolated and secure environment for running applications. Each OpenIndiana system is a global zone. Within a global zone, specific non-global zones can be created.

14.5 Zones support limitations

Note the following limitations of support for non-global zones in the `beadm` utility and in related processes:

- When using the `pkg update` command, the `-r` switch is required to upgrade all zones.
- Non-global zone support is limited to ZFS support. Zones are not supported unless they are on ZFS.
- Zones are not supported in the `rpool/ROOT` namespace. Non-global zones are cloned or copied only when the original zone is within the shared area for the global zone, for example, within `rpool/export` or within `rpool/zones`.
- Although the `beadm` utility affects the non-global zones on your system, the `beadm` utility does not display zones information. Use the `zoneadm` utility to view changes in the zones in your boot environment. For example, use the `zoneadm list` command to view a list of all current zones on the system.

For further information, see the `zoneadm1M` man page.

14.6 Zones support specifications

The beadm command impacts the non-global zones in your boot environments as follows:

Command	Support Details
beadm create	When you clone a boot environment by using the beadm create command, all zones in that boot environment are copied into the new boot environment.
beadm destroy	When you destroy an inactive boot environment, the zones that belong to that boot environment are also destroyed.
beadm mount	When you mount a boot environment, the zones in that environment are mounted relative to the mount points for the environment.
beadm unmount	When you unmount a boot environment, the zones in that environment are also unmounted. All mount points are returned to their states prior to being mounted.
beadm rename	When you rename a boot environment, that change does not impact the names of the zones or the names of the datasets that are used for those zones in that boot environment. The change does not impact the relationships between the zones and their related boot environments.

15 The X-Window System

① NOTE:

Write about:

- How to create and use an xorg.conf file.
- Graphics drivers are found in the `/usr/lib/xorg/modules/drivers/amd64/` graphics driver directory
 - modinfo only shows kernel drivers, not Xorg drivers, since Xorg drivers are just driver.so files dlopen'ed by a userspace process, not loaded into the kernel address space.
 - To see what drivers Xorg loaded, either check `/var/log/Xorg.0.log` or run `p1dd` on the Xorg process.

15.1 Video card support (2D)

- Nearly all cards can use the VESA driver, and are therefore supported for 2D.
- 2D acceleration for NVidia GPU's is provided by the Nvidia binary driver.

- An effort is underway to further improve Radeon (2D) acceleration for both legacy and modern AMD GPU's.

15.2 Video card support (3D)

- Nearly all NVidia GPU's are supported by the Nvidia binary driver.
- Beginning with the July 2016 experimental release, most Intel GPU's are now also supported.
- No 3D support is currently available for AMD GPU's.

① NOTE:

Write about:

- The expected behavior when booting the live CD from a system with an NVIDIA card.
- Discuss procedure for adding an NVIDIA card to a system that was using VESA or some other non-3d video driver.
- Troubleshooting - what logs to look at, manual configuration, etc.
- Walk through NVIDIA utility screens.

16 Device Drivers

Write about:

- Finding hardware id's
- Searching for drivers
- Installing and loading drivers
 - Using the `modinfo` command to list information about loaded kernel driver modules
 - Using `modload` to load kernel driver modules
 - Using `modunload` to unload kernel driver modules
 - Using the `add_drv` command
- Adding device ID's to `/etc/driver_aliases`, and `/etc/driver_classes`, etc.